




Remedial Action and Operations and Maintenance Status Report January through June 2022

Lowry Landfill Superfund Site Arapahoe County, Colorado









REMEDIAL ACTION AND OPERATIONS & MAINTENANCE STATUS REPORT JANUARY THROUGH JUNE 2022 LOWRY LANDFILL SUPERFUND SITE

Prepared for:

CITY AND COUNTY OF DENVER CHEMICAL WASTE MANAGEMENT, INC. WASTE MANAGEMENT OF COLORADO, INC.

SEPTEMBER 30, 2022

PREPARED BY:

PARSONS 1776 LINCOLN ST., SUITE 600 DENVER, COLORADO 80203 (303) 831-8100

REVIEWED AND APPROVED BY:

Lead Author:	Duyley Bill	_ Date:	9/22/22
Program Manager:	PATT	_ Date:	9/22/22
QA Manager:	Krist Dill	_ Date:	9/26/22

TABLE OF CONTENTS

Page

TABLE OF CONTENTS	I
LIST OF TABLES	III
LIST OF FIGURES	IV
LIST OF APPENDICES	V
LIST OF ACRONYMS AND ABBREVIATIONS	VIII
EXECUTIVE SUMMARY	1
1.0 INTRODUCTION	1
1.1 Purpose and Scope11.2 General Site Description11.3 Report Organization2	
2.0 WATER TREATMENT PLANT	3
2.1 Operations and Maintenance 3 2.1.1 NBBW System 3 2.1.2 North End Extraction System 4 2.1.3 Liquid Volumes and Flow Rates 4 2.1.4 pH System 5 2.1.5 Removal of Volatile Organic Compounds 5 2.1.6 Sludge Production 7 2.1.7 Maintenance and Calibration 7 2.2 Monitoring 8 2.2.1 Summary of Activities 8 2.2.2 Sampling 9 2.2.3 Laboratory Analyses 9 2.2.4 Data Validation 9 2.2.5 Monitoring Results 9 2.3 Treatability 11	
3.0 WASTE MANAGEMENT	12
3.1 Drill Cuttings and Well Abandonment Wastes123.2 NTES Recovery Wastes123.3 Treatment Plant Wastes123.4 Decontamination Pad Wastes123.5 Site Monitoring Waste12	
4.0 GROUNDWATER MONITORING	13
4.1 Well Inspections, Maintenance, Installation and Development 13	

4.1.1 Well Inspections and Maintenance	13
4.1.2 Well Installation and Development	13
4.2 Sitewide Groundwater Elevations	13
4.2.1 Alluvium/Weathered Dawson Formation Groundwater	
	1.4
Elevations	1T
	13
4.2.3 Upper Denver Groundwater Elevations	16
4.2.4 Lignite Layer Groundwater Elevations	16
4.2.5 Vertical Hydraulic Gradients	17
4.3 Groundwater Sampling	17
4.3.1 Laboratory Analyses	17
4.3.2 Data Validation	18
4.4 Compliance Evaluation	10 10
4.4.1 Procedures Used to Assess Compliance	18
4.4.2 Results of Compliance Evaluations	
4.5 Effectiveness Evaluation	27
4.5.1 Perimeter Slurry Wall	27
4.5.2 North Toe Extraction System	29
4.5.3 North Boundary Barrier Wall	29
4.5.4 MW38 Channel	34
4.5.5 Vertical Migration Assessment in Deep Groundwater	5 1
(OUG)	25
(OU6)	33
4.6 Voluntary Actions – MW38 and Perimeter Systems	38
4.6.1 MW38 Source Control	
4.6.2 PM-11	
4.6.3 MW51-WD	40
4.6.4 PM-15	41
4.7 NTES Area NAPL Skimming	
4.8 North End Response Actions and Investigations	42
4.8.1 North End Monitoring Results	42
4.0.2 Character Extraction in the Newton End NDDW and	72
4.8.2 Groundwater Extraction in the North End, NBBW and	40
GTEP Area	
4.8.3 Progress from Response Actions and Investigations	43
4.9 GTEP Area Response Actions	48
4.10 Permitted Well Inventory	49
•	
5.0 LANDFILL GAS REMEDY	50
5.1 LFG Extraction, Collection, and Treatment System Operations	50
5.1.1 Extraction Wells and Collection System	
5.1.2 GTEP and Blower/Flare Stations	
5.2 LFG Extraction, Collection, and Treatment System Monitoring	
5.2.1 Flare Sampling	54
5.2.2 GTEP Inlet Sampling	54
5.2.3 GTEP Outlet Sampling	54
5.2.4 POC Probe Sampling	54
5. <u>-</u> 2 5 2 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5	😅 .
6.0 STORMWATER	55
VIV DI ORUM MATERIA	
6.1 Surface Water Demoved Action	55
6.1 Surface Water Removal Action	
6.2 Stormwater Monitoring	55
6.2.1 Sampling	55

7.0 COVER MONITORING
7.1 Landfill Cover 56 7.1.1 Site and Landfill Cover Inspection 56 7.1.2 Landfill Cover Maintenance Activities 56 7.2 Buffer Zones 56 7.2.1 Buffer Zone Inspections 56 7.2.2 Buffer Zone Maintenance Activities 57
7.2.2 Buffer Zone Maintenance Activities
9.0 PROBLEMS ENCOUNTERED, RECOMMENDATIONS, AND MASTER SCHEDULE
9.1 Problems Encountered
10.0 REFERENCES
10.0 REFERENCES

LIST OF FIGURES

No.	Title
4.1	Sitewide Potentiometric Surface – Alluvium/Weathered Dawson January 2022
4.2	Sitewide Potentiometric Surface – Alluvium/Weathered Dawson April 2022
4.3	Sitewide Potentiometric Surface – Unweathered Dawson January 2022
4.4	Sitewide Potentiometric Surface – Unweathered Dawson April 2022
4.5	Sitewide Potentiometric Levels – Upper Denver Formation January 2022
4.6	Sitewide Potentiometric Levels – Upper Denver Formation April 2022
4.7	Sitewide Potentiometric Levels – Lignite Layer January 2022
4.8	Sitewide Potentiometric Levels – Lignite Layer April 2022
4.9	Groundwater Sampling Locations – 1st Half 2022
4.10	Groundwater North End Sampling Locations – 1st Half 2022
4.11	Groundwater Compliance with Performance Standards
4.12	Perimeter Slurry Wall Well Pair Hydrographs
4.13	NTES Trench Water Levels and Pumping Rates
4.14	North Toe Extraction System Area Potentiometric Surface – Alluvium/Weathered Dawson January 2022
4.15	North Toe Extraction System Area Potentiometric Surface – Alluvium/Weathered Dawson April 2022
4.16	NBBW Area Weathered Dawson Potentiometric Surface – January 2022
4.17	NBBW Area Weathered Dawson Potentiometric Surface – April 2022
4.18	B-326-WD and MW113-EW-1 Water Elevation/Dissolved Molybdenum
4.19	MW113 Area - Water Elevation/Bottom of Screen/MW113-EW-1 and NBBW-IW-
1117	3 Extraction Rate
4.20	1,4-Dioxane Concentrations – B-326 / MW113 Area
4.21	1,4-Dioxane Concentrations – B-321 (Extraction Well) / B-313 (Compliance Well)
4.22	NBBW Area Potentiometric Surface – Unweathered Dawson – January 2022
4.23	NBBW Area Potentiometric Surface – Unweathered Dawson – April 2022
4.24	MW38 Area Weathered Dawson Potentiometric Surface – January 2022
4.25	MW38 Area Weathered Dawson Potentiometric Surface – April 2022
4.26	B-326-WD and B-326-UD Water Elevation and NBBW-IW-3, MW113-EW-1 and MW133-UD Extraction Rate
4.27	PM-15 Area Potentiometric Surface – Weathered Dawson – January 2022
4.28	PM-15 Area Potentiometric Surface – Weathered Dawson – April 2022
4.29	Section 31 Weathered Dawson Potentiometric Surface – January 2022
4.30	Section 31 Weathered Dawson Potentiometric Surface – April 2022
4.31	Sections 19 and 30 Weathered Dawson/Weathered Upper Denver
	Potentiometric Surface – January 2022
4.32	Section 31 1,4-Dioxane Results – First Quarter 2022
4.33	Section 31 1,4-Dioxane Results – Second Quarter 2022
4.34	Sections 19 and 30 1,4-Dioxane Most Recent Results
4.35	North End Trend Analysis Plots – Area 1

- 4.36 North End Trend Analysis Plots Area 2
- 4.37 North End Trend Analysis Plots Area 3
- 4.38 North End Trend Analysis Plots Area 4
- 4.39 North End Trend Analysis Plots Sections 30 and 19
- 4.40 North End Trend Analysis Plots Yale Ave
- 4.41 Progress from Response Actions Last Sampling Date
- 4.42 North End Trend Analysis Plots Area 5
- 4.43 Permitted Well Locations in the Vicinity and Downgradient of Lowry Landfill Superfund Site
- 5.1 Gas Monitoring Probe Location Map
- 6.1 Stormwater Sample Location
- 9.1 Master Schedule

LIST OF APPENDICES

No. Title

APPENDIX A WATER TREATMENT PLANT

- A-1 WTP Weekly Summaries and Standard Operations Checklists
- A-2 NBBW Sump Graph
- A-3 Sludge Analysis Data
- A-4 WTP Water Quality Data
 - A-4.1 Summary of Water Treatment Plant Effluent (MP-001) Water Quality
 - A-4.1.1 Compliance Summary of Water Treatment Plant Effluent (MP-001) Water Quality 1,4-Dioxane
 - A-4.1.2 Compliance Summary of Water Treatment Plant Effluent (MP-001) Water Quality Volatile Organic Compounds and Nonylphenol
 - A-4.1.3 Compliance Summary of Water Treatment Plant Effluent (MP-001) Water Quality Metals, pH and Semivolatile Organic Compounds
 - A-4.1.4 Compliance Summary of Water Treatment Plant Effluent (MP-001) Water Quality Radionuclides
 - A-4.2 Summary of Treatment Plant Early Warning Influent Water Quality
 - A-4.2.1 Summary of Treatment Plant Early Warning Influent Water Quality (Volatile Organic Compounds) Individual And Composite Data
 - A-4.2.2 Summary of Treatment Plant Early Warning Influent Water Quality (1,4-Dioxane)
 - A-4.2.2.1 Summary of Treatment Plant Early Warning Influent Water Quality (1,4-Dioxane) Individual And Composite Data
 - A-4.2.2.2 Summary of Treatment Plant Early Warning Influent Water Quality (1,4-Dioxane) Trend Analysis
 - A-4.2.3 Summary of Treatment Plant Early Warning Influent Water Quality (Molybdenum)

LIST OF APPENDICES (continued)

No. Title

- A-4.2.3.1 Summary of Treatment Plant Early Warning Influent Water Quality (Molybdenum) Individual And Composite Data
- A-4.2.3.2 Summary of Treatment Plant Early Warning Influent Water Quality (Molybdenum) Trend Analysis
- A-4.2.4 Summary of Treatment Plant Early Warning Influent Water Quality (Radionuclides)
 - A-4.2.4.1 Summary of Treatment Plant Early Warning Influent Water Quality (Radionuclides)
 - A-4.2.4.2 Summary of Treatment Plant Early Warning Influent Water Quality (Radionuclides) Trend Analysis
- A-4.2.5 Summary of Treatment Plant Early Warning Influent Water Quality (Other Metals and Semivolatile Organic Compounds)

APPENDIX B WASTE DISPOSAL RECORDS

- B-1 Summary of Waste Disposed
- B-2 Waste Manifests

APPENDIX C GROUNDWATER

- C-1 New Monitoring Well Logs
- C-2 Monitoring Well Hydrographs
- C-3 Compliance Evaluation Statistical Testing and Analyte Statistical Trend Analysis Plots
 - C-3.1 Data Summary Table
 - C-3.2 Mann-Kendall Trend Analysis
 - C-3.3 Goodness-of-Fit Testing
 - C-3.4 Outlier Testing
 - C-3.5 Linear Regression Analysis
 - C-3.6 Upper Control Limit Analysis for Data Without Trend
- C-4 Effectiveness Assessment
 - C-4.1 Determination of Hydraulic Gradients
 - C-4.2 Trend Analysis for Wells with Outward Gradients
 - C-4.3 Shewhart-CUSUM Test for Wells with Outward Gradients
- C-5 Vertical Migration Assessment
 - C-5.1 Vertical Migration Well Data
 - C-5.2 Mann-Kendall Trend Analysis
 - C-5.3 Dixon's Test for Outliers
- C-6 North End Monitoring and Response Actions
 - C-6.1 North End All Organics and Nitrate Data

LIST OF APPENDICES (continued)

No. Title

C-6.2 MW77 Area – All Organics and Nitrate Data

C-7 Well Permit Inventory Within Five Miles of the Site

APPENDIX D LANDFILL GAS

- D-1 LFG Quality and Extraction Well Pressures
- D-2 Flare/Gas-to-Energy Plant Station Monitoring
 - D-2.1 Flare Station Monitoring Lowry Inlet
 - D-2.2 Flare Station Monitoring DADS Blower Flare
 - D-2.3 Flare Station Monitoring Flare Station 3
 - D-2.4 Flare Station Monitoring Combined Sources at Gas-to-Energy Plant
 - D-2.5 Flare Station Monitoring Daily Field Notes
- D-3 Engines Inlet Methane and Heat Content Test, February 16, 2022
- D-4 Landfill Gas Monitoring Probes Methane

APPENDIX E COVER MONITORING – FIELD INSPECTION AND MAINTENANCE REPORTS

- E-1 Site and Landfill Cover Inspections
- E-2 Buffer Zone Inspections
 - E-2.1 January 2022 Buffer Zone Inspection
 - E-2.2 April 2022 Buffer Zone Inspection

APPENDIX F ANALYTICAL DATA PACKAGES, DATA VALIDATION REPORTS, AND DATA QUALITY ASSESSMENT

- F-1 Sample Location Cross Reference Table
- F-2 Analytical Data Packages and Data Validation Reports
- F-3 Data Quality Assessment

APPENDIX G ELECTRONIC DATABASE

LIST OF ACRONYMS AND ABBREVIATIONS

% Percent

 $\begin{array}{ll} \Delta h & \quad \text{Change in head} \\ \mu g/L & \quad \text{Micrograms per liter} \end{array}$

14X 1,4-Dioxane

3DVA 3-Dimensional Data Visualization and Analysis

5YRR Five Year Review Report Above mean sea level

ARARs Applicable or Relevant and Appropriate Requirements

bgs Below ground surface

BTS Biological Treatment System

°C Degrees Centigrade CD Consent Decree

CDPHE Colorado Department of Public Health and Environment

CFM Chloroform

Chem Rec Chemical recovery

CSE Containment System Evaluation

CSM Conceptual Site Model

cy Cubic yards d Distance

DADS Denver-Arapahoe Disposal Site

DBF DADS Blower/Flare
DCA Dichloroethane
DCE Dichloroethene

Denver City and County of Denver DNAPL Dense non-aqueous-phase liquid

DQA Data Quality Assessment
DQO Data quality objective
DVR Data Validation Report

EB Equipment blank

EBEW East boundary extraction well

EMSI Engineering Management Support, Inc.

ESW East/South/West EW Extraction well

EWMP Early Warning Monitoring Plan

°F Degrees Fahrenheit

Fm Formation FS3 Flare Station 3

Ft Feet

ft/ft Foot per foot

GAC Granular activated carbon
GC Gas chromatograph
gpd Gallons per day

LIST OF ACRONYMS AND ABBREVIATIONS

gpm Gallons per minute GTEP Gas-to-Energy Plant

GWMP Groundwater Monitoring Plan

H Hour

HMI Human-machine interface in wc Inches of water column IRA Initial Response Action

IX Ion exchange L_c Critical value

LBF Lowry Blower/Flare
LCL Lower confidence limit
LCS Laboratory control sample
LEL Lower explosive limit

LFG Landfill gas

LNAPL Light non-aqueous-phase liquid

M Minute

MARLAP Multi-Agency Radiological Laboratory Analytical Protocols

MB Method blank

MDL Method detection limit

Metro Wastewater Reclamation District (now Metro Water Recovery)

mg/L Milligrams per liter M-K Mann-Kendall

mS/cm micro-Siemens per centimeter
MS/MSD Matrix spike/matrix spike duplicate

mV Millivolt NA Not applicable

NAPL Non-aqueous-phase liquid NBBW North Boundary Barrier Wall ND Non-detect/not detected

NGVD National Geodetic Vertical Datum NTES North Toe Extraction System

NV Not validated

O&M Operations and maintenance

PARCC Precision, accuracy, representativeness, comparability, completeness

PCE Tetrachloroethene

PCR Periodic Compliance Report
PID Photo-ionization detector
PLC Programmable logic controller

POC Point of compliance

POTW Publicly-owned treatment works

ppb Parts per billion

PPE Personal protective equipment

ppm Parts per million
PS Performance standard
psi Pounds per square inch

LIST OF ACRONYMS AND ABBREVIATIONS

PWI Potable water injection

QAPP Quality Assurance Project Plan

RA Remedial action

RAWP Response Action Work Plan
RI Remedial investigation
ROD Record of Decision

RPD Relative percent difference RWST Raw water storage tank

scfm Standard cubic feet per minute

SDG Sample delivery group SIM Selected Ion Monitoring

Site Lowry Landfill Superfund Site

SOW Statement of Work

Surr Surrogate

SVOC Semi-volatile organic compound SWRA Surface Water Removal Action

TB Trip blank
TCA Trichloroethane
TCE Trichloroethene

TCHD Tri County Health Department

TCLP Toxicity characteristic leaching procedure

TDS Total dissolved solids

TENORM Technologically Enhanced Naturally Occurring Radioactive Material

THF Tetrahydrofuran THM Trihalomethane

TM Technical Memorandum

tpy Tons per year

TSDF Treatment, Storage and Disposal Facility

TSS Total suspended solids

U Non-detect

UCL Upper confidence limit

UD Unweathered Dawson formation UPS Uninterruptable power supply

USEPA United States Environmental Protection Agency

USGS United States Geological Survey

UV-Ox Ultraviolet Oxidation
VFD Variable frequency drive
VOC Volatile organic compound
WAP Water Augmentation Plan
WD Weathered Dawson formation

WM Waste Management
WMP Waste Management Plan
WSDs Work Settling Defendants
WTP Water treatment plant



Executive Summary: Status of Operations, Maintenance and Remedial Actions

INTRODUCTION

The EPA has determined in the 2022 Five-Year Review (FYR) that the remedial activities at the Lowry Landfill Superfund site are protective of human health and the environment.

Completed in early 2022, the fifth FYR of the Site included the findings of several site inspections; interviews with the work settling defendants, local and state government officials and community members; and an assessment of all environmental data and found that the remedial components and institutional controls in place at the site are protective of human health and the environment.

September30, 2022

The area around the site consists of ongoing landfilling operations as well as residential areas. While monitoring and other operations and maintenance activities are ongoing, institutional controls, including deed restrictions, water rights, zoning, and ordinances ensure nearby residential areas are not impacted by the site contamination.

As part of the WSDs ongoing commitment to transparency and community engagement, several outreach opportunities were provided. During this reporting period, the WSDs provided community outreach by participating in four meetings with the Lowry Landfill Community Advisory Group with three presentations given regarding the 2022 Five Year Review, Semiannual Status Report and results of the North End risk assessment.

Conclusions from the Fifth Five Year Review for Lowry

✓ Shallow Groundwater and Subsurface Liquids/Deep Groundwater

The groundwater remedy and the implemented contingency measures are functioning as intended by the decision documents. **Conclusion**: Remedy is protective of human health and the environment.

- ✓ A 1,4-dioxane groundwater plume extends north from the Site. The risk assessment determined the concentrations of 1,4-dioxane equate to a risk well within the acceptable risk range. Groundwater contamination from the Site is not affecting the residential areas north and east of the 1,4-dioxane plume.
- √ The NBBW was evaluated in the Containment System Evaluation and the results indicated that the NBBW is achieving hydraulic containment of groundwater.
- ✓ EPA recommended a discussion in the Status Reports regarding deep groundwater and vertical migration providing monitoring results and additional details to support the statement that vertical migration is not occurring and groundwater compliance wells are in compliance: **DONE**

√Landfill Solids

The remedy is functioning as intended by the decision documents. The remedy includes the landfill cover with monitoring, excavation of contaminated soil and drums, and NAPL recovery. **Conclusion**: Remedy is protective of human health and the environment.

√Landfill Gas

The remedy is functioning as intended by the decision documents. The treatment system is operating appropriately, and performance standards are being met. **Conclusion**: Remedy is protective of human health and the environment.

√Soils


The remedy is functioning as intended by the decision documents. The No Further Action remedy consists of continued maintenance on the cover areas. Regular maintenance ensures the covers remain intact. **Conclusion**: Remedy is protective of human health and the environment.

√Surface Water and Sediment


The remedy is functioning as intended by the decision documents. The No Further Action remedy consists of periodic surface water runoff monitoring and continued O&M of the SWRA and the NBBW. **Conclusion**: Remedy is protective of human health and the environment.



LOCATION & CONTAINMENT REMEDY MAPS



Lowry Landfill Superfund Site Containment Remedy Components





Note: Red Labels Denote Remedy Components



GROUNDWATER MONITORING

More than 500 monitoring wells extending into both shallow and deep aquifers have been installed within and outside the site to ensure the community is protected. Well inspections are a routine part of the monitoring program. Data shows that the monitoring system continues to be effective.

Groundwater remedy component effectiveness evaluations conducted in 2021 as part of the fourth five-year review determined that the remedial components are effective and achieve objectives. Specifically, the slurry wall – a vertical barrier wall made of clay that prevents groundwater flow – continues to effectively contain contamination inside the eastern, southern and western limits of the landfill as designed. The North Toe Extraction System, which collects and pumps water to the treatment plant at less than 1 gallon per minute, continues to capture the most contaminated groundwater emanating from the landfill. The 960-foot long North Boundary Barrier Wall (NBBW) located at the north end of the site is the most significant groundwater extraction feature, removing 6 to 10 gallons per minute, which effectively prevents contamination from migrating offsite. Finally, groundwater extraction in the northwest corner of the site, known as the MW38 area, captures contaminated groundwater flowing through this area and prevents offsite migration.

Vertical migration monitoring shows vertical migration wells are in compliance with groundwater performance standards and that contaminated groundwater has not migrated to the deeper aguifers.


There are 60 compliance wells in the network, which are monitored for 29 different chemicals. There are 52 wells in compliance or potentially in compliance, and 8 wells are out of compliance or potentially out of compliance for chemicals such as 1,4-dioxane, PCE, nitrate, and nitrite. The 8 wells that are out, or potentially out of, compliance are being addressed by continuing to pump contaminated water to the treatment plant, as discussed above. This method has proven to be effective at stopping groundwater flow in these areas and reducing the chemical concentrations.


FACTORS AFFECTING CONTAMINANTS IN GROUNDWATER

1.4-dioxane and the North End

In 2005, the Colorado Water Quality Control Commission established a new groundwater standard for 1,4-dioxane. At that time, new technological advancements capable of detecting and measuring 1,4-dioxane at the new standards found 1,4-dioxane north of the site. That standard has been revised over the past 13 years, and the current standard is now 0.35 parts per billion (ppb). Current best available analytical technology is not able to reliably detect 1,4-dioxane at this concentration in site groundwater so a site-specific standard for Lowry Landfill is set at 0.9 ppb.

Numerous response action work plans have been implemented that have effectively reduced the extent of 1,4-dioxane in the North End Area, and









1,4-dioxane

- sometimes added to solvents to prolong their useful life
- Used in some consumer products such as cosmetics, deodorants, soaps, toothpaste, anti-freeze and paint

Site groundwater standard = .9 ppb



there is a comprehensive monitoring program in place. Of the 37 current North End monitoring wells where trend analysis was performed, 86% are decreasing and 14% have no trend. The observed concentration declines in all areas shows the effectiveness of the ongoing response actions and demonstrates that groundwater quality in this area is improving. Data shows that the groundwater extraction response at the site continues to significantly decrease the 1,4-dioxane concentrations, as well as the width and length of the contamination to the north. An animation of the North End plume over time is available at www. lowrylandfillinfo.com. As stated in the 2022 Five Year Review, "Based on the results of the North End investigation, groundwater contamination from the Site is not affecting these residential areas." Furthermore, the report states, "There are no complete exposure pathways from 1,4-dioxane in shallow groundwater. Monitoring results indicate concentrations are decreasing or stable in most off-site wells. Monitoring and extraction will continue to reduce 1,4-dioxane concentrations and prevent migration of the plume to the north."

MW38 Sand Channel


Remedial actions to contain groundwater and reduce contaminant concentrations in the sand channel have also been successful. Water is pumped out of the sand channel to maintain inward groundwater flow directions and prevent offsite migration of contaminants and the extracted water is sent to the treatment plant ensuring the surrounding groundwater is always flowing inward. Levels of 1,4-dioxane have been reduced by 98% since May 2005 in this area. Chloroform and trichloroethene concentrations have also been reduced by 93% and 97%, respectively. See graph at right.

Nitrate in the NBBW Area

One well is exceeding the nitrite and nitrate standards in an area where sewage sludge was historically land farmed to cultivate and enhance microbial degradation of the sludge. This well is located along the northern boundary of the Site. There does not appear to be a potential for significant off-Site migration of nitrate or nitrite at concentrations greater than the performance standard and monitoring is ongoing. Additionally, groundwater extraction from the North End wells further downgradient would capture any potential migration of these compounds if it were to occur.

WATER TREATMENT PLANT

The water treatment plant uses a natural biological process and advanced oxidation treatment to destroy more than 92% of the organic compounds coming into the plant. An ion-exchange system is used to reduce molybdenum by an average of 96%. The pretreated water is then discharged to a publicly owned wastewater treatment plant for further treatment. The on-site treatment plant removes all site chemicals to safe standards and leaves a minimal environmental footprint. It treats approximately 1.5 million gallons of contaminated groundwater every month. The data show the plant continues to operate as designed in compliance with discharge standards.



At Lowry

Extraction and treatment continue to decrease concentrations.

North End Area: 38 Wells



14% remain flat

MW38 Channel:





LANDFILL GAS REMEDY

Landfill gas—made up of methane, carbon dioxide, nitrogen and other gases—is created naturally by the biological decomposition of organic matter in landfills under low-oxygen conditions. The Site's landfill gas extraction, collection and treatment system continues to be effective and in compliance, including the gas-to-energy treatment plant, which removes roughly 5,000 tons of methane annually. This equates to removing more than 22,000 cars from the road each year. The on-site power plant, constructed in 2008, uses landfill gas to fuel four internal combustion engines that generate electricity for a local utility company. The electrical power generated is enough to supply 2,500 to 3,000 households.

LANDFILL COVER

The former landfill is covered by 4 to 12 feet of compacted clay and soil. The "cap" reduces infiltration of rain and snow into the soil, which minimizes further groundwater contamination. The cover continues to effectively drain rain and snow, keeping it from penetrating the soil. The cap is routinely monitored for any depressions that may form due to settlement that would cause rainwater to pond, among other issues. No cap settlement issues were identified in this report.

Gas to Energy Process Gas Extraction & Cleaning Conversion to Electricity via **Generating Engines** Electricity to the Power Grid via Local Electric Co.



Visit the Lowry Landfill website for detailed information and contact information.

www.lowrylandfill.com

1.0 INTRODUCTION

This Remedial Action (RA) and Operations & Maintenance (O&M) Status Report was prepared on behalf of the City and County of Denver (Denver), Chemical Waste Management, Inc., and Waste Management of Colorado, Inc. (WM), collectively Work Settling Defendants (WSDs), pursuant to Subsection 2.1 of the Statement of Work (SOW) attached as Exhibit C to the Consent Decree (CD) entered by the U.S. District Court for the District of Colorado on 28 September 2005 (and reentered on 16 November 2005) in Civil Action No. 02-CV-01341-EWN-MJW regarding the Lowry Landfill Superfund Site (the Site).

No RA activities were performed during the reporting period.

O&M activities consisted of operations, maintenance, and monitoring associated with the Site Water Treatment Plant (WTP), groundwater, surface water, landfill gas (LFG), and landfill covers. These activities were performed in accordance with Addendum 7, Operation and Maintenance Manual, Water Treatment Plant (Parsons/Engineering Management Support, Inc [EMSI], 2021); Revision 3, Operations and Maintenance Manual, Groundwater Extraction (Parsons, 2021a); Revision 2 Groundwater Monitoring Plan (GWMP) (EMSI/Parsons, 2018); the Stormwater Monitoring Plan (EMSI, 2008a); Revision 3, Operations and Maintenance Manual, LFG Remedy (EMSI, 2021); Revision 4, Updated Compliance Monitoring Plan LFG Remedy (EMSI, 2020a); and the Final Operations and Maintenance Manual, Covers and Stormwater (EMSI, 2007a). addition, groundwater extraction from North End and MW77 Area response actions and monitoring of North End groundwater were implemented in accordance with the Revised North End Initial Response Action (IRA) Work Plan Addendum (EMSI, 2008b) as conditionally approved by United States Environmental Protection Agency (USEPA) on March 24, 2008; the North End Groundwater Monitoring Plan (EMSI, 2007b); the North End Groundwater Monitoring Plan Update No.2 (EMSI, 2020b); the North End Groundwater Monitoring Plan Update No. 3 (Parsons, 2021b); the Response Action Work Plan to Extract Additional Groundwater from Upgradient of MW77-WD (EMSI, 2011); the Response Action Workplan for the B-326-UD and B-313 Areas (EMSI, 2013); and the Revised Work Plan to Further Assess the North End 1.4-Dioxane Plume and Update Conceptual Model for North End Area (EMSI, 2018a). The status of North End activities is described in Subsections 4.8 and 4.9.

1.1 Purpose and Scope

This report summarizes results of O&M activities performed from 01 January 2022 through 30 June 2022 (reporting period).

1.2 General Site Description

The Site is located in Section 6, Township 5 South, Range 65 West, and in the southern portion of Section 31, Township 4 South, Range 65 West in west central Arapahoe County, approximately 15 miles east of downtown Denver, Colorado. The Site occupies approximately 508 acres within an unnamed north-south trending valley located west of Murphy Creek and east of East Toll Gate Creek. The North End study area extends for approximately three miles north of the Site and is coincident with the unnamed creek and Murphy Creek drainages.

1.3 Report Organization

This report contains ten sections and seven appendices. The remainder of this report is organized as follows:

- Section 2 and Appendix A contain a summary of WTP operations and monitoring. Appendices F and G contain electronic analytical data packages and data validation reports (DVRs) for the WTP, the Data Quality Assessment (DQA), and the database. The database has been updated for routine database checks and should replace any previous versions still in use.
- Section 3 and Appendix B contain a summary of waste management activities, including: waste storage, treatment, disposal, and maintenance.
- Section 4 and Appendix C contain a summary of groundwater monitoring activities and evaluations of monitoring results, including: well inspections, sitewide groundwater level data, analytical results, and statistical evaluations. Appendices F and G contain electronic analytical data packages, DVRs, the DQA, and the database for groundwater. The database has been updated for routine database checks and should replace any previous versions still in use.
- Section 5 and Appendix D contain a summary of LFG monitoring, extraction, collection, and treatment activities performed during the reporting period, and an evaluation of gas monitoring results and collection system performance. Appendix G contains the database for landfill gas, the Gas-to-Energy Plant (GTEP), and flare gas.
- Section 6 contains a summary of stormwater sampling activities and results. Appendix G contains the database for storm and surface water.
- Section 7 and Appendix E present activities and results related to cover monitoring and maintenance.
- Section 8 presents the status of RA activities.
- Section 9 presents problems encountered and recommendations for each component of this Status Report.
- Section 10 presents the references cited in this report.

2.0 WATER TREATMENT PLANT

This section summarizes WTP O&M activities for the reporting period.

2.1 Operations and Maintenance

Operations of the WTP during the reporting period were limited to treatment of Site waters originating from the North Boundary Barrier Wall (NBBW), North Toe Extraction System (NTES) sump, east boundary extraction wells (EBEWs – PM-11, PM-15 and MW-51 areas), MW38 area extraction wells, on- and off-Site North End Response Action wells, the decontamination pad at the GTEP complex, LFG condensate, and miscellaneous sources such as well sampling purge waters and potable water used for plant wash-down. Following treatment, all of these waters were discharged to the publicly-owned treatment works (POTW) pipeline.

The treatment protocols, process monitoring, and effluent quality monitoring were performed in accordance with Industrial Discharge Permit No. 2360-6, effective January 5, 2020.

Throughout the reporting period, the WTP was discharging to the POTW 99 percent (%) of the calendar time. Downtime was caused by the reasons listed below, in order of decreasing significance. No discharge occurred during these downtimes.

- Granular activated carbon (GAC) changeout: Plant operations were stopped on January 10 while the lead and lag GAC vessels were changed out (scheduled 3 hours and 22 minutes).
- Power interruption: Plant discharge stopped on June 29 for a power grid interruption for 1 hour and 22 minutes.
- Biological system programmable logic controller (PLC), uninterruptable power supply (UPS), and 24-volt power supply changeout: Plant operations were stopped on February 23 while the biological system PLC was powered down for UPS and 24 Volt power supply changeout (scheduled 22 minutes).
- Routine O&M: Effluent pH probe calibration, quarterly POTW discharge line valve exercising and GAC vessel back-flushing (scheduled all less than one day).
- Automatic shutdown tests of auto-alarm sensors and shutdown circuits (scheduled all less than one day).
- Standard time adjustment to daylight savings time: Plant operations were stopped while the PLC and plant computers were adjusted to daylight savings time [March 14, 15 minutes].

All O&M activities were documented on checklists, in the daily operator logs, and/or electronic logs entered automatically into the WTP databases by the operating software. Completed daily operator logs and weekly checklists of pertinent information are provided in Appendix A-1.

2.1.1 NBBW System

As shown in Appendix A-2, groundwater elevations in the NBBW sump fluctuated between 5685.4 feet (ft) above mean sea level (amsl) and 5685.6 ft amsl. The average groundwater elevation was 5685.5 ft amsl, which is the set-point water level in the sump.

Throughout the reporting period, groundwater was extracted from the NBBW sump at an average rate of 6.3 gallons per minute (gpm) while pumping.

The significance of groundwater elevations at the extraction sump and in the overall vicinity of the NBBW system relative to hydraulic containment is evaluated in Subsection 4.5.3 of this report.

2.1.2 North End Extraction System

Extraction wells in the North End include on-Site wells located near the northern boundary of the Site and off-Site wells located north of the Site in Section 31 (Figure 4.34). North End on-Site and off-Site extracted groundwater was conveyed to the main WTP through dedicated North End pipelines. On-Site and off-Site North End groundwaters are introduced to the WTP at the feed surge tank where they are blended with pre-treated on-Site waters, treated by GAC, then discharged to the POTW pipeline. Rates of North End on-Site and off-Site groundwater extraction are presented in more detail in Subsection 4.8.

2.1.3 Liquid Volumes and Flow Rates

The following table summarizes the types, flow rates, and volumes of waters treated during the reporting period.

Water Source	Average Flow Rates (gpm)	Total Volume (gallons)
NBBW Water [total of volume sent directly to WTP plus volume temporarily routed to raw water storage tanks (RWSTs)]	6.3	1,650,039
MW38 area (includes automatic pumping from the sand channel wells and the source-control well)	1.9 (calendar)	486,239
NTES Water	0.5 (calendar)	128,994
LFG Condensate from Tank 530 (treated in WTP from January 1 through June 30, 2022)	0.02 (calendar)	4,533
PM-11 Area	$NA^{a/}$	48,953
MW51 Area	NA	65,641
PM-15 Area	NA	4,657
Decontamination Water and Precipitation	NA	1,034
North End On-Site Water ^{b/}	14.0 (calendar)	3,656,484
North End Off-Site Water ^{b/}	8.6 (calendar)	2,238,252
Potable Water [for plant wash-down, pipeline flushing and Gas Chromatographs (GCs)]	NA	21,360
Total Influent ^{c/}	31.8 (calendar)	8,306,186
Discharge to POTW ^{c/}	32.0 (calendar)	8,328,352

calendar - timeframe used to derive average flow rate. For example, total volume during the reporting period (gallons) divided by number of calendar-minutes during the reporting period equals average flow rate in gpm.

a/ Not applicable – batch transfer to RWSTs, feed surge tank, or clear well, then treatment in WTP.

b/ See Subsection 4.8 for extraction rates from individual North End wells.

c/ The difference between the total influent volume and the volume discharged to the POTW is accounted for in total tank storage capacity associated with the WTP (including temporary storage in external tanks) and in measurement error of the totalizers. Totalizer error is as much as +/-0.5% on each totalizer (10)

totalizers are used to generate the volumes above). For example, the effluent totalizer range of error is +/- 41,642 gallons over the reporting period.

WTP influent volumes dropped substantially from last reporting period (approximately 825,00 gallons overall). Most influent sources displayed a drop in volume especially the North End on-Site wells that displayed a 1.9 gpm drop in their overall extraction rate over last period and the NBBW extraction rate that dropped 0.8 gpm. Precipitation for the reporting period was approximately 4 inches less than the first half of 2021, consequently, there is less recharge of the groundwater than in 2021. This is supported by the dry area in the NBBW containment zone that expanded considerably compared to last period (Figure 4.17).

2.1.4 pH System

During the reporting period, the pH of WTP effluent was measured every minute at the last pH monitoring probe in the plant (probe pH-740 located in the effluent surge tank). Average, minimum, and maximum pH readings during plant operations for the reporting period are summarized below. These represent normal pH readings.

Month	Control pH Set- Point	Average pH Reading	Minimum pH Reading	Maximum pH Reading
January	7.0	6.8	6.5	7.2
February	7.0	6.9	6.7	7.1
March	7.0	6.8	6.6	7.2
April	7.0	6.8	6.7	7.1
May	7.0	6.8	6.7	7.1
June	7.0	6.8	6.7	7.1

2.1.5 Removal of Volatile Organic Compounds

Removal of volatile organic compounds (VOCs) within the WTP is accomplished by biological treatment, UV-Oxidation (UV-Ox), and GAC. Biological treatment occurred in the Biological Treatment System (BTS) when treating a blend of approximately 6% NTES water, 21% MW38 area groundwater, 5% LFG condensate (when processing), and 68% softened water from the chemical precipitation process. The operating temperature of the BTS was maintained at 23.5 degrees Centigrade (°C).

While the BTS remained the primary process for VOC removal this reporting period, a parallel slip-stream of approximately 7.5 to 8.3 gpm of softened, non-NTES water was treated with UV-Ox to increase BTS removal efficiencies and biosolids handling by increasing the retention time within the BTS. The longer retention time in the BTS also allowed for increased flow from the MW38 Source well through the BTS.

The on-line GCs monitor eight target VOCs at least once per day for real-time monitoring at TP-3350 (BTS effluent) and TP-730 (UV-Ox effluent). The following compounds are monitored:

- 1,1-Dichloroethene (DCE)
- trans-1,2-DCE
- 1,1-Dichloroethane (DCA)
- Chloroform (CFM)
- Tetrahydrofuran (THF)
- Benzene
- 1,2-DCA
- 1,4-Dioxane

GC monitoring of GAC efficiencies at TP-710, TP-740, and TP-750 occurs once per week. Due to the large volume of data produced by the three GCs, those data are not included here but are available upon request.

Destruction efficiencies of the VOC compounds that have exceeded their discharge limits in **plant influent** in at least one sampling event since monitoring began are calculated below. Although the permit no longer includes discharge limits for these compounds (except 1,4-dioxane), they are routinely monitored in plant influent per the *Updated Early Warning Monitoring Plan* (EWMP) (EMSI, 2008c) and in plant effluent per the discharge permit (Metro Wastewater Reclamation District [Metro], 2020)]. Approximate destruction efficiencies for these compounds for the <u>WTP as a whole</u> are summarized below. These destruction efficiencies were calculated based on differences between mass loading to the plant from all influent streams and mass remaining in plant effluent.

Organic Destruction Efficiencies across Entire WTP

Compound	Average Efficiency (%) January through June 2022
1,1-DCE	97%
1,2-DCA	71%
1,4-dioxane	97%
Benzene	100%
Vinyl Chloride	NC*

^{*} Influent and effluent concentrations were not detected. Efficiency not calculated

Analytical results from MP-001 (plant effluent, Appendix A-4.1.1 and A-4.1.2) and influent composite sampling (Appendix A-4.2.1 and A-4.2.2) indicate that some breakthrough of target compounds through GAC contactors occurred during the reporting period (as shown in the table above). 1,4-Dioxane, 1,1-DCE and 1,2-DCA showed breakthrough over the reporting period. 1,1-DCE and 1,2-DCA have no permit limit. 1,4-Dioxane breakthrough concentrations were less than 85% of the discharge limit at all times (85% criterion is used as a trigger level to change out carbon, per Section 3.11 of the WTP O&M Manual). Note: GAC is not intended to remove 1,4-dioxane so 100% reduction is not expected.

2.1.6 Sludge Production

During the reporting period, approximately 25 cubic yards (cy) of dry sludge was produced and placed into a lined roll-off box located adjacent to the WTP. Fifteen cy of the sludge were disposed at the Denver Arapaho Disposal Site (DADS) in May in accordance with the *Updated Waste Management Plan* (WMP) (EMSI, 2020c). The remaining sludge will be disposed of in the second half of 2022. The non-hazardous waste manifests for the sludge are presented in Appendix B-2. Analytical results for radiological and toxicity characteristic leaching procedure (TCLP) preparation with analyses of the sludge are presented in Appendix A-3. Analytical and screening results confirmed the sludge remains a non-hazardous, solid waste.

WTP sludge was also sampled for technologically enhanced naturally occurring radioactive material (TENORM) according to 6 CCR 1007-1 Part 20. The goal of the regulation is to determine if naturally occurring radioactive material concentrations are increased by, or as a result of, past or present human practices i.e., the processes within the WTP. The sludge was sampled in triplicate for Radium-226, Radium-228, Polonium-210, and Lead-210 (Appendix A-3). All sample results were below the exemption limit (5 pCi/g for each isotope) therefore Lowry WTP sludge material does not contain concentrations of TENORM above the exemption limit for disposal in landfills.

2.1.7 Maintenance and Calibration

Routine servicing and maintenance of plant equipment included the following:

- Serviced liquid transfer pumps, chemical feed pumps, and mixers;
- Quarterly bag filter inspections;
- Replenished chemical storage totes;
- Added and mixed chemical polymer;
- Serviced the HMR-30 mixing, flocculation, settling, and clear-well chambers;
- Serviced the sludge thickener and holding tanks;
- Serviced the plate and frame filter press;
- Back-flushed the GAC contactors to prevent fines accumulation and hydraulic packing of the carbon;
- Serviced air compressors (Ingersoll Rand);
- Cleaned pump strainers;
- Serviced BTS air blowers; and
- Quarterly UV-Ox unit inspection and test run (when on standby).

Routine maintenance and calibration of plant instrumentation included the following:

- Daily cleaning of pH probe at TP-315;
- Weekly calibration (and cleaning as necessary) of pH probes at TP-315, TP-365, TP-670, and TP-740;
- Weekly cleaning and monthly calibration of pH probes in the BTS;

- Weekly servicing, data backup, and calibration of on-line GCs;
- Weekly data backup and archiving of WTP operating database; and
- Monthly calibration of lower explosive limit (LEL) meter (LEL-740).

On March 7, 2022, the 23-year-old PLC of the Rayox UV-Oxidation unit failed to power up after it was powered down for a scheduled 3,000-hour UV lamp change-out. A change-out of the PLC was begun on March 14, 2022 because of its age and earlier indications that the internal power supply of the PLC was failing. Industrial contractor Browns Hill Engineering & Controls began work on the PLC change-out including a rewrite of the control programming software to enable the new replacement PLC to be used. Plant operations continued at a reduced capacity while UV-Ox unit was inoperable. The balance of untreated water was sent to the BTS and onsite storage until March 23, 2022, when the UV-Ox PLC programing and physical changeout to a new PLC was completed. With the plant treatment capacity returned to normal, the approximate 50,000 gallons of untreated stored raw water was then processed over the next six days.

All maintenance and calibration activities were documented on checklists and in the daily operator logs provided in Appendix A-1.

2.2 Monitoring

2.2.1 Summary of Activities

Compliance monitoring during the reporting period consisted of sampling WTP effluent (MP-001) per the discharge permit (Metro, 2020). Other monitoring included sampling the molybdenum ion exchange (IX) system to measure efficiencies; performance monitoring of the BTS; and Early Warning monitoring per the *Updated Early Warning Monitoring Plan* (EMSI, 2008c) to measure performance of the WTP treatment systems.

2.2.1.1 WTP Effluent Compliance Monitoring

All WTP effluent (MP-001) analytical results for the reporting period were reported in monthly Periodic Compliance Reports (PCRs) that are submitted to Metro, Aurora, USEPA, Colorado Department of Public Health and Environment (CDPHE), and Tri County Health Department (TCHD). Analytical results for MP-001 monitoring are reported in Appendix A-4.1.

2.2.1.2 Ion Exchange Monitoring for Molybdenum

Performance monitoring for the molybdenum IX treatment system included weekly monitoring (while pumping) of MW113-EW-1 influent at plant sampling port TP-170 plus multiple sample ports located within the IX treatment system. The IX treatment system is used to manage the molybdenum in the WTP effluent (MP-001). The rate of extraction at MW113-EW-1 at the beginning of the period was approximately 2 gpm. A steady decline in extraction rate continued throughout the period while the groundwater level remained at the base of the MW113-EW-1 well screen. The extraction rate was approximately 1.7 gpm by the end of the period. A high percentage of molybdenum continues to be efficiently removed by the IX system as the molybdenum concentration entering the IX treatment system remained relatively stable throughout the period.

2.2.1.3 BTS Performance Monitoring

Performance monitoring of the BTS involved collection of samples for 1,4-dioxane, VOCs, total phosphorus, total volatile suspended solids, nitrate, and nitrite. Analytical

results are used to measure organic loading, biomass and efficiency of the biological system. BTS performance monitoring data may be found in the Access[©] database in Appendix G.

2.2.1.4 Early Warning Monitoring

Early Warning monitoring for this reporting period involved monthly and yearly sampling of WTP influent according to the EWMP (EMSI, 2008c) and *Metro Letter of Understanding* (EMSI, 2015). Influent samples from TP-110 (RWSTs), TP-120 (NBBW), TP-150 (North End on-Site and NBBW-IW-3), TP-170 (MW113 Area), TP-160 (North End off-Site and MW77 area) and TP-3310 (BTS influent) were collected for analysis of VOCs, 1,4-dioxane, nonylphenol, and molybdenum (Appendices A-4.2.1 through A-4.2.4). Composite samples were collected for metals and SVOCs (Appendix A-4.2.5).

2.2.2 Sampling

WTP effluent (MP-001) and Early Warning influent samples were collected according to the schedule and analytical protocol presented in Table 2.1. A sampling schedule for the next reporting period for MP-001 and Early Warning is also provided in the table.

Performance monitoring for the BTS and molybdenum in the IX system was performed weekly. Appendix F-1 lists the samples collected for performance and compliance monitoring and Appendix F-2 contains the data packages from the laboratories.

2.2.3 Laboratory Analyses

Eurofins/TestAmerica (Denver) analyzed the samples collected from the WTP for non-radiological parameters. Eberline Services (Oak Ridge, Tennessee) analyzed the radiological samples. Analytical data packages and DVRs for the reporting period are presented in Appendix F-2.

2.2.4 Data Validation

All effluent (MP-001) sample results were validated according to USEPA *National Functional Guidelines for Organic and Inorganic Data Review* (USEPA, 1994a and b as amended) and by SW-846 guidelines specific to the method or as directed by USEPA. All radionuclide results that were less than the critical value (L_C) were qualified as non-detects (U). Radionuclides were validated according to the guidelines and criteria specified in the *Multi-Agency Radiological Laboratory Analytical Protocols* (MARLAP) *Manual* (USEPA, 2004).

Validation is complete for all January through June 2022 compliance sampling events. All compliance data packages were received with no major quality issues except for recurring matrix spike failure of benzidine due to the inadequacy of method 625 to extract this compound without oxidative losses. This problem is discussed in more detail in the DQA report (Appendix F-3). Performance and Early Warning samples are not validated.

2.2.5 Monitoring Results

Compliance, Early Warning, and performance monitoring for the WTP were performed in this period as detailed below.

2.2.5.1 Compliance Monitoring

WTP effluent (sample port MP-001) was sampled according to the schedule in Section E.1 of the discharge permit (Metro, 2020) and results are presented in Appendix A-4.1. All

validated results from WTP effluent sample port MP-001 were below the industrial wastewater discharge permit limits.

2.2.5.2 Early Warning Monitoring

The Updated EWMP (EMSI, 2008c) requires annual sampling for a comprehensive list of parameters from Section E.1 of the discharge permit per the *Metro Letter of Understanding* (EMSI, 2015). Any compound in the **influent** whose concentration exceeds the discharge limit requires periodic follow-up sampling to monitor for statistical trends. An annual influent sampling event for the parameters listed below is required to determine if influent concentrations are less than discharge limits.

- VOCs (E624) (including 1,4-dioxane),
- 1,4-dioxane (8260B Selected Ion Monitoring [SIM])
- Semi-Volatile Organic Compounds (SVOCs) (E625),
- Metals (E200.7 and E200.8),
- Mercury (E245.1),
- Nonylphenol (D7065),
- Gross Alpha/Beta (E900.0),
- Radium-226 and Total Radium (SM 7500-RA-B)
- Radium-228 (EPA-RA-05),
- Plutonium-238, -239, -240 (EPA 600/7-79-081), and
- Americium-241 (ER110 LANL).

The annual influent sampling event was performed on April 4, 2022 and indicated 1,4-dioxane was the only **influent** compound exceeding its **discharge** limit. Consequently, this compound was selected as a compound of concern for monthly influent monitoring. Grab samples were collected and analyzed for 1,4-dioxane to monitor the concentration in each influent source. Influent sampling involved collecting grab samples from each of seven sources (RWSTs, NBBW, MW38, North End on-Site water, North End off-Site water, MW113 water, and BTS influent) and compositing the results based on flow-weighted percentages. VOCs are sampled quarterly and molybdenum is sampled monthly for performance monitoring. Appendix A-4.2 presents the individual results for each influent grab, the percentage of total flow, and the flow-weighted total concentrations for VOCs (A-4.2.1), 1,4-dioxane (A-4.2.2), and molybdenum (A-4.2.3). Appendix A-4.2.4 presents the composite concentrations of radionuclides and Appendix A-4.2.5 presents composite concentrations of metals and SVOCs.

As mentioned above, 1,4-dioxane exceeded the discharge limit in the influent. Statistical trending analyses (Sen's test) for 1,4-dioxane is presented in Appendix A-4.2.2.2. Trend analyses for molybdenum and radionuclides were also performed (Appendices A-4.2.3.2 and A-4.2.4.2, respectively). There were no statistically significant increasing trends for these analytes. The WTP can readily treat 1,4-dioxane to below discharge limits. Molybdenum treatability is discussed in Section 2.3.

2.2.5.3 Performance Monitoring

Performance monitoring results for molybdenum and BTS testing may be found in the database in Appendix G.

2.3 Treatability

As discussed in Section 2.2.1.2, an IX system for molybdenum removal from MW113-EW-1 groundwater was brought online to manage the molybdenum in the WTP effluent (MP-001). At 1.7 gpm to 1.9 gpm extraction rates, influent molybdenum concentrations to the IX system ranged between 4,500 and 7,400 micrograms per liter (μ g/L) and discharge from the IX treatment system ranged from 150 to 320 μ g/L during the reporting period which is below the permit discharge limit of 430 μ g/L. A discussion of MW113-EW-1 extraction rate and mass removal is discussed in Section 4.5.3.

3.0 WASTE MANAGEMENT

Waste management activities during the reporting period were performed in accordance with the *Updated Waste Management Plan* (EMSI, 2020c) and are described below.

3.1 Drill Cuttings and Well Abandonment Wastes

No drill cuttings or well abandonment wastes were generated during the reporting period.

3.2 NTES Recovery Wastes

Non-liquid wastes were generated by activities at the NTES totaling less than one drum of non-liquid waste, personal protective equipment (PPE), absorbent pads, and paper. The partially filled drum of non-liquid waste is temporarily stored in a satellite accumulation area at the NTES.

No liquid skimming wastes were generated from the NTES during the reporting period. Partially filled drums of liquid waste are temporarily stored in satellite accumulation areas at the NTES and will be disposed when the drums are full.

Decontamination liquids and solids that originate from NTES activities are managed as a potentially hazardous substance. No decontamination liquids or solids were generated during the reporting period.

3.3 Treatment Plant Wastes

WTP waste typically consists of spent carbon, chemical precipitation sludge, general trash, and PPE.

Approximately 8,750 pounds of spent liquid-phase GAC from treatment of Site water was manifested and shipped off-Site to Clean Harbors' Kimball, Nebraska incinerator in April 2022. A uniform hazardous waste manifest is provided in Appendix B-2.

Approximately 25 cy of dry chemical precipitation sludge was produced and placed into a lined roll-off box next to the WTP. Approximately 15 cy of the sludge were disposed at DADS in May 2022 (Appendix B-1). The non-hazardous waste manifests for this shipment is presented in Appendix B-2.

Trash and PPE that were visually clean were managed as non-hazardous debris and accumulated in the roll-off adjacent to the WTP. No trash was disposed of during the reporting period.

3.4 Decontamination Pad Wastes

Approximately 1034 gallons of decontamination liquids from the decontamination pad sump were transported to and pumped into the RWSTs for processing through the WTP. This liquid was generated by storm events and decontamination activities. No decontamination solids were generated or disposed during the reporting period.

3.5 Site Monitoring Waste

Purge liquids from groundwater sampling were transported to and pumped into the WTP wet well for processing through the WTP.

4.0 GROUNDWATER MONITORING

This section summarizes groundwater characterization, compliance, and effectiveness activities conducted during the first half of 2022.

4.1 Well Inspections, Maintenance, Installation and Development

Well inspections, maintenance, installation, and development activities performed during the reporting period are discussed below.

4.1.1 Well Inspections and Maintenance

Well inspections are completed as a routine part of the monitoring program. The general condition of each well and any necessary repairs are recorded in a comment field on the water level measurement form and electronically transferred to a separate data table stored in the Site database. The following items were identified:

Location	Comments	State of Repair
MW38-840S-325E	Needs new pad due to landfill cover repairs in that area	Well pad replacement on hold, awaiting cover repair
NTES-EW-2	Well needs repair as the well casing is settling into the ground and the well lid does not close anymore, removal of section of casing will be required, locked at J plug to maintain well security.	To be repaired
MPZ-13	Needs new label	To be repaired
B-504A	Needs new label	To be repaired
MW145-WD	Needs new label	To be repaired
MW38-1363N-180W	Needs new label	To be repaired
NTES-EW3	Needs new label	To be repaired
MW66-WD	No well cap - well cap was removed to be able to close well. Well completion is locked to maintain well security.	To be repaired

Due to schedule and weather limitations some of these repairs were delayed and will be performed in the next reporting period.

4.1.2 Well Installation and Development

No new wells were installed, and no existing wells were abandoned during this reporting period, as indicated on Table 4.1.

4.2 Sitewide Groundwater Elevations

Groundwater elevations were measured in both the first and second quarters of 2022. Due to the number of water elevations recorded, Table 4.2 presents only one record for

each location per quarter, with measurements taken in January and April 2022. Water level measurements were recorded on a PC tablet containing water level data from previous quarters. Data entry screens prompted the field technician to recheck the measurement if the reading was <0.25 or >0.25 ft from the previous quarter's measurement as a QC check. Data from the tablet were then downloaded to a desktop computer and appended to the main database.

Hydrographs for the majority of the wells/piezometers in which water levels were gauged are presented in Appendix C-2. Due to the density of monitoring wells in the MW38 area, hydrographs were developed only for representative wells in that portion of the Site.

Discussion of potentiometric surfaces for the alluvium/weathered Dawson (WD), unweathered Dawson (UD), upper Denver, and lignite layer formations are presented in the following subsections. Lateral and vertical hydraulic gradients are also discussed (Subsection 4.2.5).

4.2.1 Alluvium/Weathered Dawson Formation Groundwater Elevations

The sitewide alluvium/weathered Dawson groundwater potentiometric surfaces for the first and second quarters of 2022 are shown on Figures 4.1 and 4.2, respectively. Groundwater at the Site occurs under water table conditions within the alluvial deposits along the Unnamed Creek drainage and within the weathered portion of the Dawson Formation (Fm.). Groundwater generally occurs at relatively shallow depths beneath drainages and at greater depths beneath topographic highs. The depth to groundwater in the alluvium and weathered Dawson ranges from approximately 3.5 ft below ground surface (bgs) in the detention basin along the T1 transect and MW132-WD in Section 31, to greater than 49 ft bgs along the unnamed creek drainage in the NBBW area (B-326-WD), to approximately 64 ft bgs in the southwestern corner of the Site (RDPZ-102 area). The depth to groundwater has increased in areas of groundwater extraction such as the MW38 area where pumping in the MW38 sand channel has lowered the water table at the southern end of the sand channel (at pumping well MW38-170S-140W) by approximately 10.7 ft below the original static level, and by about 20 ft below the original water table at the northern sand-channel pumping well (MW38-1028N-256E). Continued groundwater extraction and cessation of potable water injection at the NBBW has contributed to declining groundwater elevations in the NBBW area as demonstrated by the absence of saturated weathered Dawson at B-305WD, B-307, B-311, B-312, B-318, B-319, B-319-25S, B-319-26W, B-319-50S, B-319-50W, B-319-75S, B-323-WD, GW-109, NBBW-IW-1, MW-1000, PTP-14, PTP-15, PTP-15S, PTP-16, PTP-17S, PTP-18, PTP-19, PTP-20, PTP-20S, PTP-22S, TR-1, and U-701-WD during this reporting period.

In general, groundwater associated with the alluvium and weathered Dawson moves from south to north beneath the Site (Figures 4.1 and 4.2). However, the direction of groundwater movement may deviate locally near drainages and ridgelines as a consequence of the movement of groundwater away from topographic ridges; convergent flow toward drainages; variations in stratigraphy such as depositional sand channels; and/or groundwater extraction and voluntary actions. Groundwater extraction from wells along the perimeter slurry wall (PM-11, PM-15, and MW51-WD areas), NTES, NBBW, and MW38 channel areas also influences local potentiometric surfaces as discussed in Subsections 4.5.1 through 4.5.4, respectively. Details of pumping from the MW38, PM-11, PM-15, and MW51-WD areas are also discussed in Subsection 4.6. Pumping for

response actions in the North End, NBBW, and GTEP areas are discussed in Subsections 4.8. and 4.9.

In some instances, water level data from some wells were not used for potentiometric surface interpretations. For example, the water level for MW38-320N-305E was not used because the sandy zone in the screened interval is deeper and does not correlate to sandy zones screened in nearby wells. A similar situation occurs at MW38-1373N-180W. Cross Section H-H' in the *Final MW38 Area Pilot Test Report* (Parsons, 2005; Figure 2.10) shows there is no saturated weathered Dawson sand that correlates to the MW38 channel sand.

Overall, the lateral hydraulic gradient within the alluvium/weathered Dawson beneath the Site is approximately 0.021 foot per foot (ft/ft) directed generally to the north-northeast (between PM-8I and A-115 [change in head, $\Delta h = 119.01$ ft; distance, d = 5580 ft] in April 2022). The depth to groundwater, groundwater flow directions, and lateral hydraulic gradients observed during this reporting period are similar to those recorded in previous reporting periods.

4.2.2 Unweathered Dawson Formation Groundwater Elevations

The sitewide unweathered Dawson groundwater potentiometric surfaces for the first and second quarters of 2022 are shown on Figures 4.3 and 4.4, respectively. The depth to the unweathered Dawson potentiometric surface ranges from approximately 19 ft bgs in the NBBW area (B-306) and along the unnamed creek drainage, to approximately 79 ft bgs in the MW38 area (MW38-410N-180W), to approximately 92 ft below the landfill mass (B-708). In general, the groundwater gradient associated with the unweathered Dawson trends from south-southwest to north-northeast beneath the Site. The lateral hydraulic gradient within the unweathered Dawson beneath the Site is approximately 0.017 ft/ft directed generally to the northeast (between PM-6X-UD and MW-EW-2LC [$\Delta h = 97.29$ ft; d = 5,720 ft]) (using April 2022 water levels). The depths to groundwater, groundwater flow direction, and lateral hydraulic gradient observed during the first half of 2022 in the unweathered Dawson are similar to those recorded in previous reporting periods.

Examination of hydrographs (Appendix C-2) for several wells along the western boundary of the Site indicates groundwater levels that are not stable due to slow recovery since installation development or from sample purging. Similarly, the hydrograph for MW37-UD in the NBBW area (Appendix C-2) shows a steadily increasing trend through January 2020 from a sampling event that occurred in January 2005. Groundwater in the well now appears to be in equilibrium with the unweathered Dawson. This slow recovery is not uncommon for a well completed in claystone. In addition, well MW-1 shows a steadily increasing (rising) trend since 1982 probably due to the low hydraulic properties of the screened interval, while other wells (MW-2 and MW-3) show no trend. For these reasons, groundwater levels measured at MW-1 and MW-2 were not used to interpret the potentiometric surfaces shown on Figures 4.3 or 4.4, as noted on the figures. The groundwater elevation for MW-3 was honored for contouring but may not be completely representative due to long screen intervals.

Several well pairs exist with both wells screened in the unweathered Dawson. The water level in MW38-1064N-655E is utilized for the potentiometric surface, but the level in MW38-1064N-660E is not honored because the sand unit in the shallower well (MW38-1064N-655E) is more closely related stratigraphically to adjacent wells than the sand unit in the deeper MW38-1064N-660E well. The weathered and unweathered sand units in the

MW38-1064N area are interpreted to be part of the west to east trending "C"-sand (see *Final Remedial Investigation Report for the Shallow Groundwater and Subsurface Liquids and Deep Groundwater Operable Units [Harding Lawson Associates, 1992]*; Section 4.3.2.2.1, Channel Deposits within the Dawson Formation, p. 4-28). The potentiometric "trough" trending east-northeast from MW38-410N-180W is interpreted to be a result of this stratigraphic condition. Similarly, wells B-712-UD and B-712-LD, situated near the east end of the NTES, are both completed in the unweathered Dawson. However, only B-712-UD was honored for contouring the unweathered potentiometric surface because it is screened in the uppermost sandstone unit of the unweathered Dawson, which is the criterion used for contour-well selection, whereas B-712-LD is screened in a lower portion of the unweathered Dawson.

4.2.3 Upper Denver Groundwater Elevations

Potentiometric data from monitoring wells screened in the upper Denver are shown on Figures 4.5 and 4.6 for the January and April 2022 measurements, respectively. It should be recognized that the design criteria for constructing wells in the upper Denver was to set the screen in the first clean sand (i.e., minimal fines) below the clay separation unit. Because of geologic heterogeneity, the screen intervals are not always completed at the same stratigraphic level. As a result, the potentiometric contours shown on Figures 4.5 and 4.6 should be considered approximate, as variations in the elevations of screen intervals (shown on the figures) can introduce potentiometric variability. Stabilized water levels from the first half of 2022 are consistent with those measured in previous reporting periods.

The potentiometric level in monitoring well MW112-DEN, located in the southwest corner of the Site, has been slowly rising, consistent with the rest of the Denver Basin, since its installation in June 2005. However, interpretation of the potentiometric levels continues to suggest a northeast trending potentiometric trough. This well is screened in a thick, coarse-grained, porous sand unit. The hydraulic gradient along the trough is relatively flat (0.0047 ft/ft between MW112-DEN and MW71-DENR [$\Delta h = 27.95$ ft; d = 5,975 ft]) (using April 2022 water levels).

4.2.4 Lignite Layer Groundwater Elevations

Figures 4.7 and 4.8 show the locations of the 12 wells completed in the Lignite layer and their potentiometric levels for January and April 2022, respectively. The levels indicate that the potentiometric surface is nearly flat with a very low hydraulic gradient of 0.00128 ft/ft between B-506 and MW71-LIG ($\Delta h = 6.61$ ft; d = 5,160 ft) (using April 2022 water levels) to the east-northeast, similar to previous reporting periods. Hydrographs of lignite wells GW-120, GW-121, GW-122, and C-702Q1 (Appendix C-2) installed at least 30 years ago indicate that the potentiometric surface of the lignite layer had gradually and steadily dropped 13 to 22 ft, until mid-2006 when the levels stabilized or even rebounded by approximately one to two feet.

Unlike the Upper Denver, the elevation and stratigraphy of the lignite layer is fairly consistent and predictable across the Site. Except for B-506, all lignite wells are screened across the full saturated thickness of this layer. Monitoring well B-506, located hydraulically upgradient southwest of the Site, has a 40-foot screen that spans the lignite layer and the underlying shale and sandstones of the Lower Denver hydrostratigraphic unit. Consequently, the potentiometric data from this well should be used with caution. Nonetheless, taken as a whole, the potentiometric contours illustrated on Figures 4.7 and 4.8 may be viewed with a relatively high degree of confidence.

4.2.5 Vertical Hydraulic Gradients

Vertical hydraulic gradients between the weathered and unweathered Dawson hydrostratigraphic units were calculated by dividing the head difference between the midpoints of the saturated well screens associated with weathered and unweathered Dawson well pairs. To the extent that they are available, measured water levels and calculated vertical gradients are summarized in Table 4.3.

Upward hydraulic gradients, indicated by positive values (pink highlight) on Table 4.3, occur in 24% of the well pairs (not including well pairs where the WD was dry) during the second quarter 2022.

Areas of upward potential occur around the NBBW groundwater extraction trench and the GTEP extraction well where groundwater is extracted from the weathered Dawson. Other areas with upward gradients are in the vicinity of the PM-15 and MW51 pumping systems where groundwater extraction has lowered the weathered Dawson potentiometric surface. Downward potential occurs along the MW38 sand channel.

The upward and downward vertical gradient directions observed during the first half of 2022 are generally consistent with those previously observed. However, as extraction from the NBBW and GTEP areas continue, additional wells in these areas may become dry.

4.3 Groundwater Sampling

Table 4.4 and Figures 4.9 and 4.10 present the 71 compliance, North End Monitoring, effectiveness, and investigation monitoring wells and 113 samples collected during the reporting period. One sample was from an upper Denver well, 103 samples were from weathered Dawson wells, and 8 samples were from unweathered Dawson wells with one sample from an unweathered Denver well. Table 4.4 presents the wells sampled during the reporting period and their classifications, i.e., compliance (18 wells), compliance/effectiveness (7 wells), effectiveness (5 wells), North End Monitoring (34 wells), and investigation (7 wells). Water bearing units, sampling dates, and frequency of sampling are also included in the table. The table also shows sampling scheduled for the next two quarters in conformance with the updated GWMP and North End GWMP. Table 4.5 presents a summary of detected constituents at each location.

4.3.1 Laboratory Analyses

Analyte lists for groundwater compliance and performance monitoring are presented below.

Classification	Analytical Methods	Analytes
Compliance,	8260B	(25) VOCs
Vertical Migration, and	8260SIM	1,4-Dioxane
NTES, NBBW & MW38	6010B	(2) Dissolved metals
Effectiveness	300.0A	Nitrate and Nitrite
DitE66ti	8260B	(4) VOCs
Perimeter Effectiveness	8260SIM	1,4-Dioxane
North End Monitoring/Investigation	8260SIM	1,4-Dioxane
	8260B	1,1-DCE (VOCs)
MW77 Response Action	8260SIM	1,4-Dioxane
	300.0A	Nitrate

Classification	Analytical Methods	Analytes
B-313/B-326-UD Response	8260SIM	1,4-Dioxane
Action	300.0A	Nitrate
Molybdenum Investigation	6010B	Molybdenum

Indicator chemicals for the compliance wells are listed below:

- 1.1.1-Trichloroethane
- 1,1,2,2-Tetrachloroethane
- 1,1,2-Trichloroethane
- 1.1-Dichloroethane
- 1.1-Dichloroethene
- 1,2-Dichloroethane
- 1,2-Dichloropropane
- 1.4-Dioxane
- Acetone
- Arsenic
- Benzene
- Bromodichloromethane
- Bromoform
- Cadmium
- Carbon Tetrachloride

- Chlorobenzene
- Chloroform
- cis-1,2-Dichloroethene
- Dibromochloromethane
- Ethvlbenzene
- Methylene Chloride
- Naphthalene
- Nitrogen, Nitrate
- Nitrogen, Nitrite
- Tetrachloroethene
- Toluene
- Trans-1,2-Dichloroethene
- Trichloroethene
- Vinyl Chloride

Perimeter effectiveness wells are sampled for 1,1,1-trichloroethane (TCA), 1,1-DCA, trichloroethene (TCE), and tetrachloroethene (PCE) plus low-level 1,4-dioxane. Wells in the NBBW, NTES and MW38 areas are being sampled for all the compliance analytes listed above in the event that indicator chemicals for effectiveness need to be determined.

Sample and data tracking information including the dates of sample collection, sample delivery group (SDG) number, laboratory, and validation reference, are summarized in Appendix F-1. Analytical data packages and DVRs for the reporting period are presented in Appendix F-2. The DQA report is presented in Appendix F-3. The analytical database is presented in Appendix G.

4.3.2 Data Validation

Validation results are presented in the DQA report in Appendix F-3. Data quality was acceptable, and no major issues were encountered.

4.4 Compliance Evaluation

This subsection presents an assessment of compliance with groundwater performance standards along the point of compliance (POC). Sixty monitoring wells are included in the compliance monitoring network (EMSI/Parsons, 2018). Compliance evaluations are performed using the procedures set forth in Appendix C of the updated GWMP (EMSI/Parsons, 2018).

4.4.1 Procedures Used to Assess Compliance

Compliance with groundwater performance standards is assessed at each compliance well for each chemical identified in the updated GWMP as an "indicator of compliance" (listed in Section 4.3.1). Evaluation of compliance at a well is performed by comparing the 90% upper confidence limit (UCL) and, if necessary, the 90% lower confidence limit (LCL) of the chemical concentration in groundwater to its performance standard. A well

is statistically in compliance if the 90% UCL is less than its performance standard and a well is out of compliance if the 90% LCL is greater than its performance standard. If the performance standard lies within the confidence interval (i.e., between the UCL and LCL), it is unknown whether the well is in or out of compliance. In some cases (i.e., where a trend is present in the data), a determination may be made as to potentially in or out of compliance based on empirical evidence such as concentration and trend (see Step 9 of Section 7.3.1 of the revised GWMP (EMSI/Parsons, 2018).

The data evaluation procedures consist of a number of statistical tests (Mann-Kendall [M-K] trend analysis, outlier test, goodness-of-fit test, regression analysis, and calculation of UCLs) which are performed using USEPA's ProUCL software package (version 5.2) or manually in the case of regression analysis. In order to minimize the impact of potential temporal trends, calculation of the 90% LCL and 90% UCL is based on the results of the ten most recent sampling events (with the additional caveat that only samples obtained no more frequently than quarterly intervals will be considered in the identification of the ten most recent sample results). The UCL and LCL are then used to evaluate compliance with the groundwater performance standards. The data evaluation procedures described in the updated GWMP (EMSI/Parsons, 2018) result in calculation of long term (ten most recent events) average concentrations as well as the upper and lower confidence limits. A summary of the data used for the evaluation procedures is presented in Appendix C-3.1.

The sampling results for each compliance monitoring well for each indicator chemical with a reported result greater than the performance standard are analyzed using the M-K test for the presence of temporal trends. If no trend is present, the UCL and mean are determined using the ProUCL software. If an increasing or decreasing trend is determined to be present, compliance is evaluated using linear regression to estimate the mean value and the 90% upper and lower confidence levels for the most recent sample date. This result is a mean value for the most recent sampling date and is not the same as, and should not be confused with, an overall arithmetic or geometric mean of all sampling results.

At least four sample results are necessary to evaluate the long-term average, UCL, and LCL concentrations in a well relative to performance standards. At least four samples have been collected from each well and analyzed for all the 29 indicator chemicals of compliance.

4.4.2 Results of Compliance Evaluations

Tabular and graphical summaries of the results of the compliance monitoring evaluations are presented in Table 4.6 and on Figure 4.11, respectively. Complete copies of the results of the statistical evaluations are contained in Appendix C-3.

Based on the statistical tests, water quality for one or more compliance monitoring parameters at six of the 60 compliance monitoring locations exceeded performance standards (Table 4.6). The locations and the parameters found to exceed performance standards consist of the following:

Well	Compound
B-326-UD	1,4-Dioxane
B-326-WD	1,4-Dioxane
BM-11X-100N	Tetrachloroethene
MW38-830N-230E	1,4-Dioxane
MW62-WDR	1,4-Dioxane

Well	Compound
MW62-WDR	Nitrite
MW62-WDR	Nitrate
MW77-WD	1,4-Dioxane

Statistically-based compliance determinations could not be made for some indicator chemicals in the following monitoring wells although subjective determinations may be possible, and are discussed below:

Well	Compound
B-313	1,4-Dioxane
B-313	Nitrate
B-326-UD	Nitrate
BM-11X-100N	Trichloroethene
BM-15N6	Nitrate
GW-109	1,4-Dioxane
GW-109	Chloroform
GW-109	Bromodichloromethane
MW23-C-SD	1,4-Dioxane
MW38-830N-230E	Chloroform
MW106-UD	1,4-Dioxane

B-313 1,4-Dioxane and Nitrate: The water levels in this well have dropped to the point that there was not enough water available to collect a sample from this well since 11/16/21. Consequently, a formal statistical-based compliance determination could not be made because insufficient volume was available for sampling. Because the measured water level is below the base of the screened interval after well purging, the well is considered to essentially be dry and B-313 is considered to be in compliance for 1,4-dioxane. WSDs consider this to be a temporary condition and will continue monitoring at B-313 and collect samples for laboratory analyses if and when sufficient water is present in this well.

B-326-UD Nitrate: A statistically-based compliance determination could not be made for nitrate in B-326-UD because the data displayed a decreasing trend and the requirements for use of linear regression to estimate the confidence limits were not met. Procedures to be used when this condition occurs are included in Step 9 of Section 7.3.1 of the updated GWMP (EMSI/Parsons, 2018). B-326-UD is considered to be potentially in compliance for nitrate because it had a decreasing trend and the last six results were less than the performance standard (28,000 μ g/L) including the last two samples that did not contain detectable levels of nitrate. WSDs will continue monitoring at B-326-UD and attempt to determine compliance for this constituent.

BM-11X-100N TCE: A statistically-based compliance determination could not be made for TCE in BM-11X-100N because the groundwater performance standard for this chemical (5 μ g/L) falls between the 90% UCL and the 90% LCL values. As per Step 8, Section 7.3.1 of the GWMP, no conclusion can be reached regarding compliance with the groundwater performance standard because the ten most recent results, which range from 3.6 to 5.7 μ g/L, are all very near the groundwater performance standard (5 μ g/L). WSDs will continue monitoring at BM-11X-100N and attempt to determine compliance for this constituent.

BM-15N6 Nitrate: A statistically-based compliance determination could not be made for nitrate in BM-15N6 because the data displayed a decreasing trend and the requirements for use of linear regression to estimate the confidence limits were not met. Procedures to

be used when this condition occurs are included in Step 9 of Section 7.3.1 of the updated GWMP (EMSI/Parsons, 2018). BM-15N6 is considered to be potentially out of compliance for nitrate because all results were greater than the performance standard (28000 μ g/L). The last statistically-based compliance determination (second half 2020) determined that nitrate was out of compliance in this well. WSDs will continue monitoring at BM-15N6 and attempt to determine compliance for this constituent.

GW-109 1,4-Dioxane, Chloroform, and Bromodichloromethane: The water levels in this well have dropped to the point that there was not enough water available to collect a sample from this well since 6/1/20. Consequently, a formal statistical-based compliance determination could not be made for 1,4-dioxane, chloroform and bromodichloromethane; however, because the measured water level is below the base of the screened interval, the well is considered to be dry and GW-109 is considered to be in compliance. WSDs consider this to be a temporary condition and will continue monitoring at GW-109 and collect samples for laboratory analyses if and when sufficient water is present in this well.

MW23-C-SD 1,4-Dioxane: A compliance determination could not be made for 1,4-dioxane in MW23-C-SD because 90% of the results were not detected. The single detected value of 1.4 μ g/L (9/15/20) is an outlier, but data validation could not find a reason to exclude this value from the statistics. If the outlier value is removed and replaced with an earlier value (0.5 U, 9/15/05) to have ten results, all ten results are not detected; therefore, the well would be in compliance with the performance standard for 1,4-dioxane. A confirmation sample was collected in 1st quarter 2021 that did not contain a detectable level of 1,4-dioxane [method detection limit (MDL) = 0.09 μ g/L]. Although formal statistical testing could not be performed, this well is considered to be potentially in compliance with the 1,4-dioxane standard based on the preponderance of non-detect results from this well and because the single detect was not confirmed by a sample collected in first quarter 2021 (0.9 U μ g/L).

MW38-830N-230E Chloroform: A statistically-based compliance determination could not be made for chloroform in MW38-830N-230E because the data displayed a decreasing trend and the requirements for use of linear regression to estimate the confidence limits were not met. Procedures to be used when this condition occurs are included in Step 9 of Section 7.3.1 of the updated GWMP (EMSI/Parsons, 2018). Because the trend is decreasing but 70% of the concentrations were above the performance standard, no potential compliance determination could be made. WSDs will continue monitoring at MW38-830N-230E and attempt to determine its statistical compliance.

MW106-UD 1,4-Dioxane: A statistically-based compliance determination could not be made for 1,4-dioxane in MW106-UD because 90% of the results were not detected. The single detected value of 6.5 μ g/L (2/28/07) is an outlier, but data validation could not find a reason to exclude this value from the statistics. If the outlier value is removed and replaced with an earlier value (0.5 U, 7/21/06) to have ten results, all ten results are not detected; therefore, the well would be in compliance with the performance standard for 1,4-dioxane. Although formal statistical testing could not be performed, this well is considered to be potentially in compliance with the 1,4-dioxane standard based on the preponderance of non-detect results from this well.

The eight wells determined to be statistically out of compliance or potentially out of compliance are summarized below. Recommendations relative to non-compliance with performance standards at these locations follow the summary.

Well	Compound	Compliance Decision	Trend
B-326-UD	1,4-Dioxane	Out of compliance	Decreasing

Well	Compound	Compliance Decision	Trend
B-326-WD	1,4-Dioxane	Out of compliance	No trend
BM-11X-100N	PCE	Out of compliance	No trend
BM-15N6	Nitrate	Potentially Out of compliance	Decreasing
MW62-WDR	1,4-Dioxane	Out of compliance	Decreasing
MW62-WDR	Nitrate	Out of compliance	No trend
MW62-WDR	Nitrite	Out of compliance	No trend
MW77-WD	1,4-Dioxane	Out of compliance	No trend
MW38-830N- 230E	1,4-Dioxane	Out of compliance	No trend

The above compliance determination summary list is the same as that from the second half of 2021, with exception of four wells: well B-313 1,4-dioxane and nitrate were previously out of compliance but are now in compliance because the well is essentially dry; MW38-830N-230E 1,4-dioxane was previously potentially out of compliance and is now out of compliance; MW38-830N-230E chloroform was previously potentially out of compliance and now compliance cannot be determined; well MW62-WDR, which was out of compliance but is now determined to be potentially out of compliance for nitrite. Wells can change their compliance determination from one reporting period to the next because the 10 most-recent sample dataset moves over time and new data are always being incorporated. If the data are trending or fluctuating over time as some of these wells are, the compliance statistics will also change.

Based on the current findings, the necessity and scope of potential corrective actions for the seven monitoring locations identified above are assessed below in accordance with the procedures established in the updated GWMP.

4.4.2.1 1,4-Dioxane in the NBBW Area

Based on the results of the statistical tests, 1,4-dioxane occurs in excess or potentially in excess of its performance standard in four NBBW-area compliance monitoring wells (B-326-UD, B-326-WD, MW62-WDR, and MW77-WD) (Figure 4.11).

In accordance with the Response Action Work Plan (RAWP) in the B-326-UD and B-313 areas (EMSI, 2013), the WSDs initiated groundwater extraction from well B-321 in the area of compliance well B-313 in June 2013 to address occurrences of nitrate and 1,4-dioxane in well B-313. Because of this pumping, B-313 is now essentially dry and is in compliance.

With regard to B-326-UD, groundwater extraction has been ongoing from nearby unweathered Dawson well MW113-UD since July 11, 2013 in accordance with the same RAWP. Groundwater extraction at MW113-UD along with groundwater extraction from adjacent weathered zone wells MW113-WD and MW113-EW-1 which began in 2007, resulted in a long-term downward trend in the water level in B-326-UD over the period from 2007 through 2018. Cessation of potable water injection in October 2018, resulted in a further significant decline in water levels in this well (approximately 22 feet between October 2018 through June 2022) and development of a steep cone of depression in the unweathered zone potentiometric surface around the MW113-UD extraction well and B-326-UD (see Figure 4.23). During this same timeframe (October 2018 through June 2022), concentrations of 1,4-dioxane increased slightly to 7.7 µg/L (2/12/20) then declined to 4.6

μg/L (4/14/22). Relationships between the groundwater level declines and 1,4-dioxane concentration changes were addressed in the Revised Final Cessation Report (EMSI/CDM-Smith, 2020a).

The presence of 1,4-dioxane in B-326-WD at concentrations greater than the groundwater performance standard was the basis for previous determinations that a Case 3 condition (the presence of an out-of-compliance condition with the potential for migration beyond the site boundary) exists in this area. To address this condition, the WSDs have been extracting groundwater from MW113-EW-1 (alluvial/weathered Dawson groundwater) and MW113-UD (unweathered Dawson groundwater) in accordance with USEPA-approved work plans.

The table below shows the changing concentrations of 1,4-dioxane in B-326-WD. These changes of 1,4-dioxane in B-326-WD most likely reflect the effect of extraction at nearby wells.

Well	Date	Conc (µg/L)
B-326-WD	2/12/2020	10
B-326-WD	5/28/2020	11
B-326-WD	8/26/2020	3.5
B-326-WD	11/23/2020	3.9
B-326-WD	2/3/2021	17
B-326-WD	6/1/2021	7.5
B-326-WD	8/30/2021	0.77 J
B-326-WD	10/12/2021	1.0
B-326-WD	2/8/2022	3.6
B-326-WD	4/14/2022	3.2

The changing concentrations of 1,4-dioxane in B-326-WD are believed to be affected by changes in groundwater extraction in nearby MW113-EW-1. With the continued absence of injection water, presumably this extraction well is pulling water from a different area when pumping, likely from the east, which contains lower levels of 1,4-dioxane. When extraction from MW113-EW-1 was temporarily suspended on November 4, 2020 and restarted on January 27, 2021 to allow for treatment of water contained in temporary storage tanks, 1,4-dioxane concentration in B-326-WD increased to 17 $\mu g/L$ as measured on February 3, 2021. This may be the result of less flushing of residual 1,4-dioxane contained in the capillary fringe/vadose zone. After extraction of MW113-EW-1 resumed (March 11, 2021), the 1,4-dioxane concentration in B-326-WD dropped to below the performance standard (0.9 $\mu g/L$) as measured in August 2021 (0.77 $\mu g/L$). The latest sampling results (February and April 2022) have rebounded to 3.6 ug/l and 3.2 $\mu g/L$, respectively. This rebound in concentration is indicative of the changes caused by nearby pumping as discussed above. The extraction rate in MW113-EW-1 decreased from 3 gpm in November 2021 to 1.7 gpm in April 2022.

Like B-326-UD, relationships between the groundwater level declines and changes in 1,4-dioxane concentrations in well B-326-WD were addressed in the Revised Final Cessation Report (EMSI/CDM-Smith, 2020a). The WSDs will continue to monitor both the 1,4-dioxane concentrations and the water level in these wells and continue to evaluate conditions in this area.

With regard to MW62-WDR and MW77-WD, a Case 3 condition exists in the vicinity of these wells. WSDs have implemented four RAWPs (EMSI, 2006a, 2007c, 2008b, and 2010a) to reduce the levels of 1,4-dioxane in these areas and are currently implementing the *Response Action Work Plan to Extract Additional Groundwater from Upgradient of MW77-WD* (EMSI, 2011) to bring these wells into compliance. Visually declining trends in 1,4-dioxane, 1,1-DCE, and nitrate are apparent in compliance well MW77-WD since the start of response action implementation in 2008. 1,4-Dioxane has decreased from 120 μ g/L in May 2008 to 12 μ g/L in April 2022. Similar trends are apparent for nitrate (160,000 μ g/L to 13,000 μ g/L) and 1,1-DCE (22 μ g/L to 0.66 J μ g/L) for the same sampling dates.

In MW62-WDR, 1,4-dioxane is out of compliance and exceeds the performance standard in all of the ten most recent samples (measured concentrations ranging from 2.9 µg/L to 4.2 µg/L) with a decreasing trend. Although the trend is decreasing, the slow decline indicates that 1,4-dioxane will potentially continue to be out of compliance in this well. The well lies within the zone of containment caused by groundwater extraction from the NBBW and Response Actions north and east of the NBBW (see Figures 4.16 and 4.17). Consequently, the exceedances may be a Case 2 condition, which require only long-term monitoring. As required by the Fourth Five-Year Review Report (5YRR) (USEPA, 2017), the WSDs conducted additional evaluations of the effectiveness of the NBBW containment system and the Response Actions in the NBBW area as part of the NBBW Containment System Evaluation (CSE) Plan (EMSI/CDM-Smith/Parsons, 2019). That evaluation (EMSI/CDM-Smith/Parsons, 2021) determined that the NBBW effectively contains flow of contaminated groundwater within the alluvium/weathered bedrock groundwater unit. Any residual 1,4-dioxane remaining north of the containment zone will be captured by ongoing Response Action pumping north of the containment zone.

4.4.2.2 Nitrate and Nitrite in the NBBW Area

Nitrate and nitrite are out of compliance in monitoring well MW62-WDR (Figure 4.11). This well is located along the northern boundary of the Site, in an area where sewage sludge was historically land farmed. Statistical testing of potential temporal trends in the results (Appendix C-3.2) indicates that there is no trend in the nitrate and nitrite concentrations in MW62-WDR. Based on the decision rules established in the GWMP, occurrences of nitrate and nitrite in this well may be classified as a Case 3 condition. As discussed below and in Subsection 4.9, response actions are being implemented in this area. Other wells located in Section 31 north of the NBBW area were previously sampled in 2006 and analyzed for nitrate, nitrite, and VOCs. These compounds were not detected at concentrations greater than performance standards in any of the wells located along unnamed creek, immediately upgradient of the confluence with Murphy Creek (MW115-WD, MW116-WD, MW117-WD, MW118-WD, MW119-WD, and MW120-WD), or in any of the DADS wells located along unnamed creek or Murphy Creek (MW02-AD, MW05-WD, MW07-AD, MW08-WD, MW09-WD, and MW80-WD). Wells located south of the Yale Avenue extension along the northern boundary of Section 31 (MW121-WDR, MW122-WDR, MW123-WD, MW124-WD, MW125-WD, MW126-WD, MW127-WD, MW129-WD, MW130-WD and MW131-WD) were sampled for VOCs and nitrate in 2006 and were resampled in 2016 as part of the Work Plan to Sample North End Wells, Piezometers and Surface Water (EMSI, 2016) or Work Plan for 3DVA Synoptic Sampling Event (EMSI, 2018b, as amended in EMSI, 2018c), and again no nitrate, nitrite, or VOCs were detected above performance standards in any of these wells. Based on these results, the extent of nitrate and nitrite exceedances has been determined to be limited to the area

immediately to the north of the NBBW (i.e., in the immediate vicinity of compliance monitoring well MW62-WDR). The well lies within the NBBW zone of containment on a groundwater divide created by extraction wells MW-113-EW-1 and MW-170-EW-1 depicted on Figures 4.16 and 4.17. The NBBW CSE (EMSI/CDM-Smith/Parsons, 2021) determined that the NBBW effectively contains flow of contaminated groundwater within the alluvium/weathered bedrock groundwater unit. Figure 3-4 of the CSE shows particle tracks emanating from this area are captured by either MW113-EW-1 to the north or by MW-170-EW-1 to the south..

Based on the results of the prior sampling, the analysis of the capture zones around MW62-WDR, and the limited area of nitrate exceedance, there does not appear to be a potential for significant off-Site migration of nitrate or nitrite at concentrations greater than the performance standard.

As discussed above, the WSDs prepared, implemented, and updated various RAWPs to address 1,4-dioxane occurrences east and downgradient of the NBBW. To the extent that the nitrate and nitrite occurrences do not result from a source in the immediate vicinity of these wells (i.e., impacts from prior land farming of sewage sludge in this area), implementation of response actions for 1,4-dioxane should also address nitrate occurrences in these areas. To the extent that the cause of the nitrate and nitrite occurrences in these wells is due to impacts from prior land farming of sewage sludge in this area, the response actions being undertaken in this area may or may not reduce their concentrations in groundwater. Nonetheless, groundwater extraction from North End wells further downgradient should capture any potential migration of nitrate and nitrite from the NBBW area if northern migration were to occur.

4.4.2.3 1,4-Dioxane MW38-830N-230E

1,4-dioxane concentrations in monitoring well MW38-830N-230E exceed the groundwater performance standard. The concentrations of 1,4-dioxane are showing no trend. This well is located along the POC at the north end of the MW38 channel. The hydraulic gradient within the channel at this location is to the north so migration of these chemicals crosses the POC. As part of the groundwater containment remedy for the Site, groundwater extraction is conducted from the MW38 channel at two locations, including a location approximately 200 ft north of well MW38-830N-230E, which is downgradient from and beyond the POC relative to the compliance monitoring well. Therefore, although 1,4-dioxane may migrate across the POC, impacted groundwater is hydraulically contained within, and removed from, the sand channel in the area immediately north of well MW38-830N-230E as depicted on Figures 4-24 and 4-25. Consequently, no action other than continued extraction from the MW38 channel and monitoring of the compliance well is required for these occurrences.

4.4.2.4 Nitrate in BM-15N6

Nitrate occurs in well BM-15N6 at concentrations greater than its performance standard. Statistical testing of potential temporal trends (Appendix C-3.2) indicates that there is a decreasing trend in nitrate concentrations in well BM-15N6. Each of the last 10 results for nitrate in this well are above the performance standard (28,000 μ g/L). Therefore, although the trend is decreasing, the compound is considered potentially out of compliance in this well.

This well is located in an area where sewage sludge had historically been land-farmed. USEPA positioned the compliance boundary within the land farming area such that it straddles the land farming area. That, coupled with an absence of 1,4-dioxane and only low-level detections of VOCs below performance standards since 2003 in this well, would indicate the source of nitrates is not from landfill mass or waste pit contaminant migration; rather, it is likely from the past land farming activities inside and outside the compliance boundary. Groundwater sampling conducted in June 2017 and October 2018 indicated that nitrate has been observed in surrounding wells BM-15N2 (43,000 μ g/L), BM-15NE1 (26,000 μ g/L), BM-15N5 (68,000 μ g/L), BM-15N1 (25,000 μ g/L), BM-15I-15N (54,000 μ g/L), BM-15I-5OS (9,300 μ g/L), and BM-15X-5OS (38,000 μ g/L).

The spatial randomness of nitrate detections in and around well BM-15N6 as compared to other compliance wells in this vicinity is similar to that observed near the NBBW where sewage sludge was land farmed. The randomness is likely attributable to a number of hydrogeochemical variables associated with the leaching, transport, and attenuation of nitrates that can differ significantly from location to location. Nitrate concentrations can also fluctuate with precipitation and rate of groundwater pumping from the PM-15 Area wells.

Because 1) the source of the nitrate in well BM-15N6 is most likely a result of sewage sludge land farming in this area, 2) the presence of active groundwater extraction in this area, and 3) the distance between this well and the Site boundary is approximately 200 feet, (see Figure 4.11), the occurrence of nitrate in well BM-15N6 is considered to be a Case 2 condition as defined in the GWMP (EMSI/Parsons, 2018). Consequently, no action other than continued groundwater monitoring is recommended.

4.4.2.5 BM-11X-100N Tetrachloroethene

PCE in BM-11X-100N is out of compliance with an no statistical trend. The ten most recent PCE concentrations in this well range from 4.6 µg/L to 7.2 µg/L with the most recent sample containing a PCE concentration of 4.9 µg/L (May 18, 2022). PCE levels appeared to slowly increase from October 2017 to November 2020 but have dropped in the last three sampling events. The variation in PCE concentrations appears to be related to changes in the water level in this well. Prior to the summer of 2015, the water level in this well was relatively stable ranging from approximately 5,790 to 5,795 ft amsl. Beginning in the summer of 2015, the water level in this well increased, peaking at a high of just over 5,800 ft amsl in July 2017. Since that time, the water level in this well has declined back below 5,791 ft amsl. Consequently, it is likely that the increase in PCE levels in this well may be the result of flushing of residual PCE contained in the capillary fringe/vadose zone. If this is the case, then the PCE level in this well should decline over time which has been observed in the most recent PCE results (7.2 μg/L in November 2020 to 4.9 μg/L in May 2022). The well is located outside of the perimeter slurry wall in an area where the hydraulic gradient across the slurry wall is inward due to groundwater extraction along the interior of the slurry wall, but with increasing distance away from the slurry wall the hydraulic gradient becomes outward to the northeast toward the Site boundary (Figures 4.1 and 4.2). Well MW50-WD, a weathered Dawson well positioned approximately 150 ft north of well BM-11X-150N and outside the slurry wall, has never contained PCE at concentrations above the method detection limit. Similarly, wells located further to the north and northeast have always been in compliance with the PCE groundwater performance standard (see Figure 4.11). The overall low concentration of PCE in well BM-11X-100N, in addition to an inward gradient across the wall at this location, and no or

very low PCE detections in groundwater to the north and northeast of the well indicate that the PCE occurrences in this area represent a Case 2 condition (little or no downward trend with a low potential for off-Site migration) as defined in the GWMP (EMSI/Parsons, 2018). The WSDs previously completed a Case 2 evaluation for this well (EMSI, 2006b). Results indicated that it is unlikely that the PCE occurrences above the performance standard in this area will migrate to the Site boundary. Rather, PCE occurrences in this area will likely attenuate naturally over time. Consequently, the recommended action is to continue monitoring.

4.5 Effectiveness Evaluation

Four components of the groundwater containment remedy (perimeter slurry wall, NTES, NBBW, and MW38 channel) are intended to provide hydraulic control and contaminant containment in the shallow (alluvium/weathered Dawson) groundwater at the Site. The effectiveness of these features is demonstrated either by hydraulic (water level) monitoring or water quality monitoring, in accordance with Sections 3.2, 4.2, 5.2, and 7.3 of the Revised GWMP (EMSI/Parsons, 2018). The effectiveness of these remedial components was assessed in detail in 2021 and continues to be monitored regularly (EMSI/Parsons, 2021a and b). The four components are discussed below.

4.5.1 Perimeter Slurry Wall

The primary criterion for assessment of the effectiveness of the perimeter slurry wall is the presence of an inward hydraulic gradient across the slurry wall. In the event an outward hydraulic gradient is determined to be present at a particular location along the wall, water quality data obtained from outside the wall are used to assess the effectiveness of the slurry wall at containing Site contaminants.

The presence of an inward hydraulic gradient is determined by reviewing the water level measurements from the weathered Dawson wells located in a paired configuration inside and outside of the perimeter slurry wall. Fifteen well pairs (PM-1 through PM-15) are used for this assessment. Results of the evaluations of the hydraulic gradients across the perimeter slurry wall are summarized in Table 4.7. Hydrographs for the fifteen well pairs are presented on Figure 4.12. A complete set of hydrographs along with results of statistical testing of the water level data are presented in Appendix C-4.1.

Water level data indicate the presence of inward hydraulic gradients across the perimeter slurry wall at eleven of the fifteen well pairs. Outward hydraulic gradients exist across the slurry wall along the southern part of the western portion of the wall in the PM-3 and PM-6 areas and along the northern part of the eastern portion of the slurry wall in the PM-14 area. The gradient calculation for the PM-13 well pair could not be performed because PM-13I was dry, likely due to purging associated with attempts to sample this well. This well was part of the 2018 Synoptic sampling event (EMSI, 2018b and 2018c) and was dewatered during purging before a sample could be collected. The last 15 attempts to measure the water level in PM-13I revealed no recharge at this well since the October 2018 sampling event. PM-13X has been intermittently dry since the 2018 synoptic sampling event.

Where the water level data indicate the presence of an outward gradient, the effectiveness of the perimeter slurry wall is assessed using water quality data for five indicator compounds (1,1,1-TCA, 1,1-DCA, TCE, PCE, and 1,4-dioxane) obtained from wells located outside of the slurry wall in these areas. The presence of no trend or

decreasing trend in water quality data indicates the slurry wall is effective at containing Site contaminants, while the presence of an increasing trend indicates the slurry wall may not be effectively containing Site contaminants.

In accordance with the updated GWMP, a minimum of four sample results is necessary to evaluate water quality trends for the effectiveness evaluation when inward gradients cannot be demonstrated (gradient data for each well is presented in Appendix C-4.1). For wells with 4 to 8 sample results (Appendix C-4.2), Sen's test is used to assess trends (Appendix C-4.3) for the compounds. A minimum of nine sample results is required to perform more rigorous statistical testing including calculation of Shewhart-CUSUM control limits (Appendix C-4.4). Sen's test is performed on the background data sets used to calculate the Shewhart-CUSUM control limits to verify that no temporal trends exist in the background data.

PM-3X has been sampled 37 times for VOCs and 10 times for 1,4-dioxane (Appendix C-4.2). 1,4-Dioxane has never been detected in this well. TCE, 1,1,1-TCA and 1,1-DCA have never been detected above their RLs in this well. PCE has been detected in this well at concentrations substantially below its groundwater performance standard of 5 µg/L. The background data set for 1,1,1-TCA and TCE includes 32 samples. The background data set for 1,1-DCA and PCE includes 12 and 20 samples, respectively. The data sets for 1,1-DCA and PCE were adjusted because they indicated trending data when the number of samples was increased in the baseline data set. No increasing trends were identified in the background data sets and the most recent results for 1,1,1-TCA, 1,1-DCA, 1,4-dioxane, TCE, and PCE are below the Shewhart-CUSUM control limit (Appendix C-4.4). These results indicate the slurry wall is effective at this location.

PM-6X has been sampled 39 times for VOCs and 10 times for 1,4-dioxane (Appendix C-4.2). None of the five indicator compounds have ever been detected in this well. These results indicate the slurry wall is effective in this area.

PM-13X has been sampled 38 times for VOCs and 10 times for 1,4-dioxane (Appendix C-4.2). 1,4-Dioxane has only been detected once in PM-13X (0.35J). It was not detected in the four most recent samples. The other four indicator VOCs have been detected in this well during each of these sampling events, but concentrations have always been less than performance standards. When the background VOC data set is set to more than 16 sampling events, 1,1,1-TCA shows a decreasing trend in the background data set. When the background VOC data set is set to more than 20 sampling events, 1,1-DCA shows a decreasing trend in the background data set. Therefore, it was necessary to revert to the prior background data for these compounds in order to not include trending data in the background data sets. PCE had no trend in the background set of 32 results. TCE had no trend in the background set of 36 results and 1,4-dioxane has no trend in the background set of eight samples. No increasing trends were identified in the background data sets and the 22 most recent results for 1,1,1-TCA, the 18 most recent results for 1,1-DCA, two most recent results for TCE and 1,4-dioxane, and the six most recent samples for PCE are below the Shewhart-CUSUM control limit (Appendix C-4.4). These results indicate the perimeter slurry wall is effective at this location.

PM-14X has been sampled 40 times for 1,1,1-TCA, 1,1-DCA, TCE, and PCE and 37 times for 1,4-dioxane (Appendix C-4.2). PCE has never been detected at this location. 1,4-Dioxane was detected once at a trace detect of 0.1 J μ g/L (12/15/20). 1,1,1-TCA, 1,1-DCA, and TCE have been detected in this well at concentrations substantially below their

respective groundwater performance standards. When the background VOC data set is set to more than 24 sampling events, 1,1-DCA shows a decreasing trend in the background data set. Therefore, the background data set included 24 samples for 1,1-DCA. The most recent 16 samples for 1,1-DCA are below the Shewhart-CUSUM control limit. No increasing or decreasing trends in the background data set of 36 samples were identified for 1,1,1-TCA, TCE and PCE and the four most recent results for each compound are below the Shewhart-CUSUM control limit. 1,4-Dioxane background set is 32 samples with no trends and the five most recent samples are below the Shewhart-CUSUM control limit (Appendix C-4.4). Therefore, the analytical chemistry data indicate the perimeter slurry wall is effective at this location.

Based on evaluation of the water level and water quality data, the perimeter slurry wall is effective at containing contamination inside the eastern, southern, and western limits of the landfill footprint.

Effectiveness of the perimeter barrier wall (EMSI/Parsons, 2021a) surrounding the eastern, southern, and western sides of the Section 6 landfill at the Site was evaluated as it related to findings and recommendations in USEPA's Fourth 5YRR (USEPA, 2017). It was concluded that successful operation of the perimeter barrier wall in conjunction with operations of the other remedial components at the Site address the remedial action objectives for protection of human health and the environment.

4.5.2 North Toe Extraction System

Effectiveness of the NTES is demonstrated based on hydraulic monitoring alone if either of the following conditions occurs:

- 1. Pumping from the NTES results in continuous decline of trench water levels as demonstrated by the well hydrographs for MPZ-10R, NTES-180W, and MPZ-11; or
- 2. Trench water levels (as measured in MPZ-10R, NTES-180W, and MPZ-11) remain below the base of alluvium (elevation of 5,740 ft amsl).

Figure 4.13 shows the water level data from piezometers NTES-180W, MPZ-10R, MPZ-11 and the extraction sump, and indicates that trench water levels remained below the base of alluvium throughout the reporting period. This is displayed by the potentiometric surfaces for the alluvium/weathered Dawson in the NTES area (Figures 4.14 and 4.15 for the first and second quarters of 2022, respectively) showing convergent groundwater flow to the trench. As indicated by Figures 4.13, 4.14, and 4.15, the NTES is effective at capturing contaminated groundwater emanating from the toe of the landfill.

Effectiveness of the MW38 Area, NTES, and North End Response Actions, (EMSI/Parsons, 2021b) at the Site were evaluated as it related to findings and recommendations in USEPA's Fourth 5YRR (USEPA, 2017). The measure of effectiveness for the NTES prescribed in the GWMP is being met by ongoing groundwater extraction from NTES trench wells.

4.5.3 North Boundary Barrier Wall

The presence, location, and extent of the containment area created by the NBBW systems are defined by the weathered Dawson potentiometric surface in the NBBW area.

Figures 4.16 and 4.17 present the potentiometric surfaces for the alluvium/weathered Dawson in the NBBW area for the first and second quarters of 2022, respectively.

The NBBW zone of containment is highlighted in yellow on Figures 4.16 and 4.17. After potable water injection ceased on October 2, 2018, the water table between the NBBW and MW113 area has been flattening and a clear groundwater divide cannot be definitely demonstrated. Instead, a larger containment area north of the NBBW caused by cessation of potable water injection in conjunction with Response Action extraction has developed as shown on Figures 4.16 and 4.17 and has encompassed compliance wells B-313, GW-109, and B-326-WD, plus monitoring wells PTP-14, PTP-15, PTP-16, PTP-17S, PTP-18, PTP-19, PTP-20, and TR-1. Directions of groundwater flow into cones of depression within the enhanced Containment Zone are shown on both figures.

Extraction of groundwater north of the NBBW continued during the reporting period. The extraction rates (gpm) from the four extraction wells are shown below.

Well	1/1 – 1/14//22	1/14 – 2/18/22	2/18 – 3/16/22	3/16 – 4/7/22	4/17 – 5/6/22	5/6- 6/10/22	6/10 – 6/30/22
MW113- EW-1	2.0	1.9	1.8	1.7	1.7	1.7	1.7
B-321	0.0	0.0	0.0	0.0	0.0	0.0	0.0
MW113-UD	0.02	0.01	0.02	0.02	0.02	0.02	0.02
NBBW-IW-3	0.0	0.0	0.0	0.00	0.0	0.0	0.0
Total Extraction	2.02	1.91	1.82	1.72	1.72	1.72	1.72

Fluctuations in groundwater levels and 1,4-dioxane concentrations were observed in most weathered and unweathered Dawson monitoring wells in the NBBW area. As the water levels declined in the area, from both seasonal water decline and cessation of injection, the ability of extraction wells to remove groundwater from the system was affected, as discussed below.

The saturated thickness (defined as the water present in a well between the top of the water column and bottom of the well screen) in MW113-EW-1 has decreased since cessation of potable water injection. Historically, this well was able to sustain extraction in the 3 to 4 gpm range. With decreasing saturated thicknesses, sustained yields from this well appear to stabilize at 1.7 gpm.

On November 18, 2019, total molybdenum was detected in WTP effluent above its permitted limit, which led to a temporary shut-down of the WTP. After sampling all waters entering the WTP, the source was determined to be from extraction well MW113-EW-1.

Flow from that well was decreased to 1 gpm on November 18, 2019 and the WTP was returned to service. Due to continued increases in molybdenum concentrations in that well, and to ensure no additional effluent exceedances occurred in WTP effluent, the extraction rate from MW113-EW-1 was reduced to 0.5 gpm, on June 16, 2020. On July 30, 2020 a recently installed packer in the well was adjusted to a depth of 5664 feet amsl and the extraction pump inlet was raised to 5664.5 feet amsl to increase groundwater extraction from the interval above the packer. The MW113-EW-1 extraction rate remained at 0.5 gpm

through November 3, 2020. Extraction from MW113-EW-1 was terminated on November 4, 2020 to allow the WTP to treat groundwater stored in a Baker tank prior to freezing weather. No additional extraction from MW113-EW-1 occurred between November 9, 2020 and January 26, 2021 to allow for the installation of the IX system. Extraction from MW113-EW-1 resumed on January 27, 2021 (extraction rate between 0.5 and 1 gpm) and was increased on March 11, 2021 to 2 gpm to increase mass removal. Because of decreasing water levels in NBBW area, the packer in MW113-EW-1 was removed on June 7, 2021. The extraction pump inlet was lowered to 6 inches above the bottom of MW113-EW-1's 5-foot sump and extraction resumed on June 8, 2021. An investigation of the extent and possible sources of elevated molybdenum in groundwater was presented in a Technical Memorandum, *Evaluation of Potential Sources of Elevated Molybdenum in Wells MW113-WD and MW113-EW-1* (EMSI/CDM-Smith, 2020b).

The evaluation found the source of molybdenum appears to be naturally-occurring, coincident with fine to coarse-grained sands and clay clasts, deposited at the top of the bedrock interface. Plausible sources are Pike's Peak Granite (primary source of Dawson Formation) and/or rhyolite from the Castle Rock Formation deposited as Eocene age alluvium. Molybdenum is not a compound of concern for the Site but is regulated in the WTP effluent by the Metro permit. On January 27, 2021, an IX treatment system was brought online to treat the molybdenum from well MW113-EW-1. Since January 27 the total molybdenum concentration has dropped from 17000 μ g/L to 6400 μ g/L (4/19/22). The decrease in concentration indicates that the source is limited and appears to be depleting.

Figure 4.18 shows water elevations at monitoring well MW113-WD and dissolved molybdenum concentrations in compliance wells B-326-WD and B-326-UD and monitoring wells MW113-EW-1, MW113-WD, MW113-UD, and MW113-LD. Extraction from MW113-EW-1 was increased to 4 gpm on August 19, 2021. The additional extraction from the weathered Dawson resulted in an increased rate of dewatering of the MW113 area as shown by a steepening of MW113-WD water elevations on Figure 4.18. Dissolved molybdenum concentrations gradually increased in MW113-WD until the well's water elevations flattened in mid-November. Following stabilization of water elevation, the dissolved molybdenum concentration has steadily increased through April 2022. Dissolved molybdenum concentrations appeared to stabilize between 30,000 and 35,000 μg/L for the remainder of the reporting period. Stabilization of both water elevation and groundwater extraction rate suggest the area has reached equilibration under the current precipitation conditions.

To continue, and possibly increase, removal of 1,4-dioxane mass from the MW113 and B-326 areas, former injection well NBBW-IW-3 was converted to an extraction well and groundwater extraction began at 2 gpm on May 25, 2020. Following additional modifications to the well and conveyance system, extraction was increased to 2.5 gpm on June 17, 2020. Groundwater extraction from NBBW-IW-3 ranged between 2.5 and 1.7 gpm until MW113-EW-1 extraction was increased on March 11, 2021. Following the increase in extraction at MW113-EW-1, NBBW-IW-3 became formation limited and the extraction rate decreased to 0.5 gpm. Varying extraction rates during this period are the result of pump cycling, groundwater sampling and mechanical improvements to the well or WTP. After September 2021, no water was available for extraction from NBBW-IW-3.

Figure 4.19 shows water elevations following cessation for extraction well and companion monitoring well pairs MW113-EW-1/MW113-WD and NBBW-IW-3/B-319. Since cessation began, water levels decreased while extracting at 3.7 gpm from well MW113-EW-1. When extraction was reduced to 1 gpm, water levels rebounded (raised) immediately and slowly approached a steady-state (not increasing or decreasing) over time. To increase mass removal, extraction was increased to 2 gpm on May 25, 2020 in NBBW-IW-3 and water levels rapidly declined. Review of the graph shows a steady and continuing water level decline following reduced extraction at 0.5 gpm in MW113-EW-1 and increased extraction to 2.5 gpm in NBBW-IW-3. Extraction from MW113-EW-1 was terminated on November 4, 2020 while extraction at NBBW-IW-3 became formation limited with an average extraction rate at 1.7 gpm. Increased extraction at MW113-EW-1 on March 11, 2021 resulted in decreased extraction at formation limited well NBBW-IW-3 at 0.5 gpm. Following this extraction modification, water level decreases were observed in B-319, MW113-WD and MW113-EW-1. From March 17, 2021 to August 19, 2021, the water level in MW113-WD decreased at an average rate of approximately 0.15 feet per week. MW113-EW-1 extraction was increased to 4 gpm resulting in a water level in MW113-WD decreasing at approximately 0.41 feet per week (August 19, 2021 through November 19, 2021). The extraction rate at MW113-EW-1 steadily decreased and slowly approached a steady-state of 1.7 gpm at the end of the reporting period. From January 4 to April 4, 2022, the water level in MW113-WD declined at a rate of 0.005 feet per week. As previously mentioned, stabilization of water elevation and groundwater extraction rate suggest the area has reached equilibrium (i.e., pumping rate and current precipitation conditions).

Future extraction rates will be dictated by the ability of the wells to maintain yield, balanced against the ability of the WTP to meet its discharge limit for molybdenum (see Section 2.2.1 - Summary of Activities and Section 2.3 - Treatability).

Figure 4.20 shows the effect of the remedial action implemented in this area on 1,4dioxane concentrations. The graph shows overall declining 1,4-dioxane trends for compliance wells B-326-WD and B-326-UD and nearby extraction wells MW113-EW-1 and MW113-UD prior to cessation of potable water injection. Since cessation began, concentrations in the compliance wells have generally remained constant, while concentrations in the nearby extraction wells have generally increased. identification of MW113-EW-1 as the source of the elevated molybdenum concentrations in the WTP effluent, extraction from this well was decreased to 1 gpm on November 18, 2019. Following reduced groundwater extraction from this well, the 1,4-dioxane concentration decreased. Extraction from NBBW-IW-3 beginning on May 28, 2020 and modifications to extraction at MW113-EW-1 did not appear to have any effect on concentrations in compliance wells B-326-WD and B-326-UD. Concentrations of 1,4dioxane in MW113-UD have increased since cessation of potable water and are generally similar to concentrations prior to the start of extraction at MW113-UD on September 27, 2011. It is antipicated that concentrations in both MW113-WD and MW113-UD will gradually decrease as residual 1,4-dioxane present in the weathered Dawson is removed.

Groundwater levels north of the NBBW have declined since cessation began as shown on Figure 4.19. Correlations among groundwater levels, pumping rates, and 1,4-dioxane

concentrations are further addressed in the *Revised Final Report on Pilot Test for Cessation of Potable Water Injection* (EMSI/CDM-Smith, 2020a).

As a result of cessation of injection, availability of water in B-321 is formation limited and the extraction rate is dictated by the groundwater flow rate into the well. Extraction at B-321 remained at 0.001 gpm until November 3, 2020 when extraction was stopped to allow groundwater to enter the well for the fourth quarter sampling event in 2020. Insufficient water entered the well for sampling. Following the attempted sampling, groundwater extraction from the well was no longer possible due to lack of enough water entering the well to allow pump cycling and no additional extraction has occurred since November 3, 2020. Lack of groundwater entering the well reflects continued dry conditions in this area until June 7, 2021 when the B-321 produced enough water to resume extraction and continued through October 14, 2021. Since mid-October 2021, B-321 has not produced enough water to extract. To the extent that seasonal precipitation events raise the groundwater table in this area, pumping will resume when sufficient groundwater is present in the well for extraction. Current conditions have not allowed pumping or sampling of B-321 and at this point it is not known if this is a temporary or long-term condition.

Figure 4.21 shows an overall declining 1,4-dioxane trend for compliance well B-313 prior to and following the start of cessation. It also shows the duration and rates of groundwater extraction from nearby extraction well B-321, and concentrations of 1,4dioxane in the extraction well over time. As shown, between 2010 and the start of cessation in 2018, 1,4-dioxane concentrations in the extraction well varied between 16 and 45 µg/L, with no apparent trend. Since the start of cessation, 1,4-dioxane concentrations became more variable ranging between 8.3 and 97 µg/L again with no apparent trend. The increased variability is believed to be attributed to changes in the direction and rate of groundwater movement caused by cessation of potable water injection, changes in groundwater pumping rates, and changes in groundwater levels. The extraction rate from well B-321 is formation limited and dictated by groundwater availability, so that 1,4dioxane concentration variability is anticipated to continue. Lack of groundwater entering B-321 reflects continued dry conditions at this area until June 7, 2021 when the B-321 produced enough water to resume extraction, albeit at less than 0.10 gpm for only four months. Since 3rd quarter 2020, 1,4-dioxane concentrations in compliance well B-313 stabilized to approximately 17 µg/L in November 2021. The well is now considered dry for sampling because insufficient water was available for sampling. Further discussion is provided in the Revised Final Cessation Report (EMSI/CDM-Smith, 2020a).

Figures 4.22 and 4.23 show the potentiometric surfaces of the unweathered Dawson in the NBBW area. As shown, there appear to be two potentiometric lows, sloped from south to north beneath the eastern, and to a lesser extent, western side of the NBBW. Both lows correspond to the presence of sandstones within the unweathered Dawson in the vicinity of the NBBW. An evaluation of the nature and extent of these sandstones and their influence on groundwater flow conditions are further evaluated as part of the NBBW CSE (EMSI/CDM-Smith/Parsons, 2021).


4.5.4 MW38 Channel

Groundwater extraction continued from wells MW38-170S-140E and MW38-1028N-256E located in the MW38 channel sand (Figures 4.24 and 4.25). Pumping from these two wells is performed to maintain an inward hydraulic gradient toward the sand channel. Pumping occurs on an intermittent basis because the sand channel has been essentially dewatered and it takes several days for sufficient water to accumulate in the areas of these two wells to activate pumping.

Hydraulic (water level) monitoring is used to demonstrate the effectiveness of the MW38 sand channel at containing groundwater in the MW38 area. These data were used to prepare potentiometric maps of the MW38 area (Figures 4.24 and 4.25). Review of these maps indicates the presence of convergent groundwater flow along the entire length of the MW38 channel, as indicated by the flow direction arrows on these two figures. The presence of convergent flow into the MW38 channel indicates that the channel effectively prevents shallow contaminated groundwater within the channel from migrating to the west, east, north, or south from the sand channel.

It should be noted that the northern extraction well (MW38-1028N-256E) is positioned 100 ft north of the Site boundary to take advantage of the thicker and deeper extent of porous channel sand at this location. As a result, groundwater quality from the compliance well (MW38-830N-230E), which is positioned within the sand channel near the Site boundary and south of MW38-1028N-256E, is representative of groundwater that will be extracted by extraction well MW38-1028N-256E and will not migrate beyond the sand channel.

The concentration time-series graph below shows that hydraulic gradient control pumping at channel wells MW38-170S-140W and MW38-1028N-256E and source control pumping at MW38-825N-445E have successfully reduced contaminant concentrations in MW38-830N-230E where the 1,4-dioxane concentration has declined by 97.7% in this compliance well.



It should be noted that on December 11, 2019, a leak from DADS' buried potable water supply pipe was identified near MW38-500N-396E. Potable water is believed to have preferentially flowed along the pipeline bedding and was observed in the pipeline trench 50 feet east of MW38-680N-419E. From this area the pipeline heads eastward, parallel to the DADS main access road. The pipeline is located about 40 feet south of MW76-WD and MW75-WD. Potable water was observed daylighting between MW75-WD and MW74-WD. DADS repaired the leak in January 2020. By April 2020, the higher groundwater elevation at MW38-680N-419E observed in January 2020 had declined to within a few feet of historical water elevations. During the second half of 2021, water levels returned to historical water elevations.

Effectiveness of the MW38 Area, NTES, and North End Response Actions, (EMSI/Parsons, 2021b) at the Site were evaluated as it related to findings and recommendations in USEPA's Fourth 5YRR (USEPA, 2017). The measure of effectiveness for the MW38 area prescribed in GWMP is being met by ongoing groundwater extraction from the MW38 sand channel.

4.5.5 Vertical Migration Assessment in Deep Groundwater (OU6)

The presence of a downward component to the hydraulic gradient at the Site indicates that there is a potential for downward migration of contamination from source area(s) into the underlying unweathered Dawson and potentially the upper Denver and lignite layers (Table 4.3). Although there may be a downward component to the hydraulic gradient, this

downward component is wholly or partially offset by the lower permeability of the deeper bedrock units compared to that of the alluvium and weathered bedrock. This section describes the vertical migration assessment performed using data from four specific non-compliance program wells and a review of deep groundwater compliance wells that are monitored for compounds of concern.

4.5.5.1 Vertical Migration Wells

Monitoring of the 29 water quality parameters that are indicators of compliance with groundwater standards is performed in selected unweathered Dawson and upper Denver wells **inside of the POC**. Contaminant concentrations are monitored for trends and compared to performance standards to assess if contaminants are potentially migrating vertically. The goal for vertical migration monitoring is to show that groundwater contaminant concentrations will be below performance standards, and if present, will exhibit stable or decreasing concentration trends over time. These conditions would indicate no vertical migration of contamination is occurring.

Monitoring for potential vertical migration is separate and distinct from compliance monitoring and monitoring performed to demonstrate the effectiveness of the various remedy components. The purpose of monitoring for potential vertical migration is to allow for ongoing assessment of the well network and sampling frequency used for the deeper compliance monitoring wells at the Site. Water quality data obtained from the interior deeper monitoring wells will be used to identify any modifications to the compliance monitoring network and/or sampling frequencies for the deeper units, if any, that may be necessary to ensure detection of possible occurrences of contamination above performance standards in the deeper units that may be migrating towards either the horizontal or vertical POC.

Although not compliance wells, vertical migration wells (B-504A, B-712-LD, C-702P3, and GW-113) are subject to the same statistical tests used in Section 4.4.1 for comparison of UCLs and LCLs to performance standards. Upper Denver wells B-504A, C-702P3, and GW-113 are sampled every five years and unweathered Dawson well B-712-LD is sampled every two years. These wells were not sampled during the reporting period. The results and statistical analyses for these wells as previously reported in the second half 2021 Status Report are summarized below:

- For wells B-504A, C-702P3 and GW-113, the maximum concentrations for all compounds for each well were less than their respective performance standards; therefore, statistical analyses to determine the UCL and LCL for comparison to performance standards did not need to be performed (Appendix C-5.1).
- For well B-712-LD, the historical maximum concentrations of all compounds were also less than their respective performance standards except for one detect of 1,4-dioxane (0.95 μg/L) in 2007. The eight subsequent samples obtained from this well were all reported as not detected for 1,4-dioxane, down to a method detection limit (MDL) of 0.09 μg/L. A compliance determination could not be made for 1,4-dioxane because 90% of the results were not detected. The single detected value of 0.95 μg/L was determined to be an outlier (Appendix C-5.3). If the outlier is removed and replaced with an earlier value (0.5 U, 6/19/06) in order to have ten results, all ten results are not detected: therefore,

the well would be in compliance with the groundwater performance standard for 1.4-dioxane.

No significant increasing trends were identified for any of the indicator chemicals of compliance in any of these wells (Appendix C-5.2). Based on evaluation of the results obtained from the last sampling event, there is no evidence of vertical migration of contamination beneath and north of the landfill. The WSDs recommend no changes in the frequency of monitoring of the vertical migration wells.

4.5.5.2 Deep Groundwater Water Quality

Thirty-four deep wells (unweathered Dawson, Upper Denver, and Lignite layer) are part of the compliance monitoring network (EMSI/Parsons, 2018) and are sampled routinely for 29 compounds of concern. Although trace or low concentration detects of multiple compounds of concern have been detected over time, only three unweathered Dawson compliance wells have detections of compounds of concern at concentrations greater than performance standards.

- B-326-UD for 1,4-dioxane and nitrate,
- MW23-C-SD for 1,4-dioxane, and
- MW106-UD for 1,4-dioxane

Section 4.4 discusses compliance statistical testing for these wells and compounds and determined 1,4-dioxane in MW23-C-SD and MW106-UD were potentially in compliance due to the preponderance of nondetects and because each well had only one detect of 1,4-dioxane not confirmed by subsequent samples.

B-326-UD nitrate is potentially in compliance because it displays a decreasing trend and the last six results were less than the performance standard. The decrease in nitrate in the deeper monitoring well B-326-UD correlates with the declining water level observed post-cessation and could suggest a change in flow path with non-nitrate impacted water now being monitored by this well.

1,4-Dioxane is out of compliance in B-326-UD with a decreasing trend. This unweathered Dawson well is paired with B-326-WD allowing calculation of vertical gradients. There is an upward gradient at this location meaning that vertical migration in this area is currently upward. B-326-WD is also out of compliance for 1,4-dioxane although no trend is indicated. Water elevations in the B-326-WD/B-326-UD well pair generally mirror each other (Appendix C-2). As water levels in both wells declined following cessation, an upward vertical gradient developed at the end of May 2019 that continued through April 2022. Therefore, if vertical migration is occurring, the direction of migration is upward from the unweathered bedrock in the B-326 area as shown in Figure 4.26.

In contrast, vertical downward gradients were identified at other locations in the NBBW area. Each of the following well pairs displayed vertical gradients with a downward hydraulic gradient indicating a potential for downward migration of groundwater and contaminants; however, water quality monitoring has not detected the presence of site-related contaminants in the deeper well while at least one compound was out of compliance in the paired weathered Dawson well.

• **B-313/B-313-UD**: B-313 was out of compliance for 1,4-dioxane (17 μg/L on the last sampling date of 11/16/21) and nitrate (55000 μg/L, 8/12/21) although the well is now dry. 1,4-dioxane has never been detected in B-313-UD and nitrate has only been detected at 100 J μg/L (7/27/20).

- MW62-WDR/MW62-UD: MW62-WDR is out of compliance for 1,4-dioxane (2.9 μg/L, 4/19/22), nitrite (2,100 μg/L, 4/19/22), and nitrate (120,000 μg/L, 4/19/22). 1,4-dioxane has never been detected in MW62-UD and nitrate has only been detected once at 110 J μg/L. 1,4-Dioxane and nitrite have never been detected in MW62-DENR or MW62-LIG also. Nitrate has been detected in MW62-DENR ranging from 57 J (8/14/18) to 180 J μg/L (9/2/05).
- MW77-WD/MW77-UD: MW77-WD is out of compliance for 1,4-dioxane (112 μ g/L, 4/18/22) and has only been detected once in MW77-UD at 0.38 J μ g/L (8/20/18).

Outside of the NBBW area, there are two weathered Dawson compliance wells paired with unweathered wells that have detected compounds at concentrations above performance standards in the past; however, those compounds are not present or are present at low concentrations in their associated deeper unweathered Dawson well. GW-114A has a downward gradient and the well's last exceedance was methylene chloride at 12 μ g/L (11/5/02). This chemical was not detected (reporting limit of 1 μ g/L) in the associated deep well GW-108A (a compliance well) when this well last sampled on 8/19/20. MW74-WD has a downward gradient and the most recent exceedance is nitrate at 30,000 μ g/L (5/17/17). Nitrate was not detected in the associated unweathered bedrock well (MW74-UD) the last time it was sampled on 8/6/20. Most unweathered Dawson wells that are located in a paired configuration with a weathered Dawson compliance well have never detected chemicals at levels above the performance standards.

The low or not detected concentrations in the deeper (unweathered Dawson) compliance wells in areas of downward vertical gradient where elevated concentrations of site-related chemicals are present in the paired weathered Dawson well indicate there is little or no downward migration of contaminants in this area.

In conclusion, with the exception of B-326-UD, monitoring of deeper groundwater at Lowry demonstrates that deeper groundwater meets the groundwater performance standards in compliance wells and that significant vertical migration of site contaminants is not occurring. 1,4-Dioxane in the B-326-UD area is out of compliance but located in an area where both weathered and unweathered Dawson groundwater are captured by groundwater extraction at MW113-EW-1 and MW113-UD and cessation. Overall, the evidence indicates that vertical migration of contaminants to deeper groundwater is not occurring.

4.6 Voluntary Actions – MW38 and Perimeter Systems

Voluntary measures are being implemented at the Site 1) for source control associated with the MW38 sand channel; 2) to induce inward hydraulic gradients across the perimeter slurry wall; and 3) to remove VOCs from groundwater outside the slurry wall. The systems are located in the following areas, starting on the west side and progressing counterclockwise around the Site:

- MW38-WD groundwater extraction from an upgradient (source-control) well;
- PM-11 groundwater extraction from two internal wells (gradient control);
- MW51-WD groundwater extraction from three internal wells (gradient control) and air sparge at one well (VOC removal outside the wall); and

• PM-15 - groundwater extraction from six internal or northern wells (gradient control) and air sparge at one well (VOC removal outside the wall).


The status of each of these voluntary actions is discussed below.


4.6.1 MW38 Source Control

Voluntary pumping of the source well (MW38-825S-445E) resumed in the first half of 2019 following completion of upgrades to the WTP and installation of the new POTW pipeline. In the first half of 2022, total extracted groundwater from the source well was 61,106 gallons and reflects six months of continuous pumping.

The primary constituents detected in the April 27, 2022 sample were 1,2-DCA at 37,000 μ g/L; 1,1-DCA at 2,500 μ g/L; and 1,4-dioxane at 2,800 μ g/L. Continued extraction resulted in contaminant mass removal of 18.83 pounds of 1,2-DCA; 1.27 pounds of 1,1-DCA; and 1.42 pounds of 1,4-dioxane during the first half of 2022. Cumulative mass removed from this well since pumping began in October 2004 is 3,018.3 pounds of 1,2-DCA; 156.3 pounds of 1,1-DCA; and 154.5 pounds of 1,4-dioxane.

The source well time-series graphs below show volume of groundwater extracted and mass removed semi-annually for 1,1-DCA, 1,2-DCA, and 1,4-dioxane as well as cumulative volume and mass removed semi-annually. The response action at MW38-825S-445E has been successful at reducing contaminant mass in this area.





4.6.2 PM-11

Groundwater extraction from wells PM-11I and BM-11I-100N (see Figure 4.2) was conducted to induce an inward hydraulic gradient by lowering the water table inside the slurry wall relative to outside of the wall. The combined extraction rate from the two PM-11 area wells was 272 gallons per day (gpd). Approximately 48,953 gallons of water were transferred to the WTP during the reporting period. Well BM-11I-100N produces approximately 60% of the combined volume, which has remained fairly consistent over the past several years.

4.6.3 MW51-WD

Voluntary measures in the MW51-WD area (see Figure 4.2) include groundwater extraction from three interior wells and air sparging from one well outside the wall. Groundwater extraction has been on-going since February 2003 and air sparging has been intermittent since 2002. Both measures are discussed below.

4.6.3.1 Groundwater Extraction

Groundwater extraction continued from wells MW51I-WD-15N, MW51I-WD, and MW51I-WD-35S, which are all positioned inside the slurry wall. The cumulative first half of 2022 production from these three wells was 65,641 gallons or 365 gpd. Based on totalizer logs, approximately 72% was from well MW51I-WD-35S and 27% was from well MW51I-WD-15N. Less than one percent was from the middle extraction well MW51I-WD where only saturated clays are present.

4.6.3.2 Air Sparge

Air sparging from MW70-WD, which began in May 2002, was terminated in March 2013 because four quarterly sampling events following cessation of sparging confirmed no VOC detections above performance standards in this well. However, the concentration of PCE in MW70-WD increased to 5.1 μ g/L on November 19, 2014, so air sparging was resumed on December 15, 2014. MW70-WD showed a decreased concentration of PCE (0.5 J μ g/L) and TCE (0.26 J μ g/L) in the May 14, 2020 groundwater sample and neither compound was detected in the groundwater sampled on December 8, 2020, May 27, 2021, November 9, 2021 or May 3, 2022. Compliance well MW60-WD, located downgradient from MW70-WD is also sampled semi-annually. Neither PCE nor TCE have been detected in MW60-WD since April 17, 2000.

4.6.4 PM-15

Voluntary measures in the PM-15 area (see Figures 4.27 and 4.28) included groundwater extraction from six wells and air sparging from one well. Groundwater extraction has been on-going since February 2000, and air sparging has been ongoing since June 2003. Both measures are discussed below.

4.6.4.1 Groundwater Extraction

Six extraction wells were pumped during the reporting period: five interior wells (PM-15I, BM-15I-25S, BM-15I-50S, BM-15I-100S, and BM-15I-150S) and one well positioned 15 ft north of the end of the slurry wall (BM-15I-15N). A total volume of 4,657 gallons or 25.5 gpd was transferred from PM-15 area storage tank to the RWST at the WTP during the first half of 2022. Based on totalizer logs, BM-15I-25S and BM-15I-15N produce the majority of the groundwater.

Groundwater extraction has maintained an inward hydraulic gradient across the northeast end of the slurry wall ranging from 0.27 ft/ft at the extraction pairs to 0.005 ft/ft at the non-extraction well pairs, as can be checked by comparison of paired wells on Figure 4.12, Figure 4.27, and Table 4.2. At non-extraction well pairs, the hydraulic gradient is small, but inward.

4.6.4.2 Air Sparge

Well BM-15N5 has been air sparged since June 2003 and throughout the reporting period to remove low-level residual VOCs from groundwater north of the slurry wall in the PM-15 area. The air sparge well BM-15N5 is positioned downgradient from PM-15X. Ongoing groundwater extraction from wells inside the slurry wall is inducing inward gradients across the wall that will further minimize the potential for migration of residual VOCs outside the wall.

4.7 NTES Area NAPL Skimming

During the reporting period, no light non-aqueous phase liquid (LNAPL) extraction was necessary from the sump riser, MPZ-10R or MPZ-11 based on monitoring of the thickness of the LNAPL layer. A measured product thickness of greater than six inches is used to trigger non-aqueous phase liquid (NAPL) extraction. The last LNAPL extraction from the NTES took place September 13, 2011.

Visual inspection of the groundwater pumped from the NTES to the WTP indicated no LNAPL or dense non-aqueous phase liquid (DNAPL) were present in the extracted groundwater, as there were no visible globules present in the pumped groundwater.

A discussion on the effectiveness and operations at the NTES was provided in Subsection 4.5.2.

4.8 North End Response Actions and Investigations

The following sections describe the monitoring and extraction response actions for the North End (land sections 31, 30, 19, 18, and 24) and progress made to date.

4.8.1 North End Monitoring Results

North End groundwater levels and groundwater quality were monitored during the reporting period in accordance with the *North End Groundwater Monitoring Plan* (EMSI, 2007b and updates EMSI, 2020b and Parsons, 2021b) (collectively, North End GWMP). Depths to groundwater are measured quarterly from all North End investigation wells installed in Section 31. Water levels in North End wells in Sections 30, 19, and 24 are measured semiannually during the first and third quarters of each year. Figures 4.29 and 4.30 show the potentiometric surface in Section 31 for January and April 2022, respectively. Although well control is sparse in Sections 19 and 30, Figure 4.31 shows the interpreted potentiometric surface in the vicinity of Murphy Creek Golf Course during January 2022.

Available nitrate and 1,4-dioxane analytical results from existing North End investigation wells are presented in Table 4.8. Table C-6.1 (Appendix C-6) presents all organic and nitrate data collected from the north end wells in the reporting period. Table C-6.2 (Appendix C-6) presents all organic and nitrate data collected in Area 3 during the reporting period. Section 31 1,4-dioxane concentrations are shown on Figures 4.32 and 4.33 for the first and second quarters of 2022, respectively. Section 31 wells are sampled quarterly. Figure 4.34 shows the spatial distribution of 1,4-dioxane in shallow groundwater in Sections 19 and 30 in the first quarter of 2022; wells are sampled semi-annually in this area. No data are available in Section 19 and 30 for the second quarter 2022.

Two private domestic wells located along East Jewel Avenue, have been sampled annually each spring (second quarter) since 2006 for 1,4-dioxane and were last sampled on June 7, 2022. The wells are perforated from depths of 357 to 600 ft bgs. Sampling of these wells is intended to provide assurances to the well owners that are proximal to the shallow groundwater plume that their drinking water does not contain 1,4-dioxane at concentrations above acceptable levels. Sampling of these wells is not for compliance monitoring purposes. 1,4-Dioxane has never been detected in either of these wells above an MDL of $0.5 \mu g/L$ (from March 28, 2006 through July 16, 2015), above an MDL of $0.15 \mu g/L$ (July 16, 2015 to May 23, 2019), or above an MDL of 0.09 μg/L (June 25, 2020 through the present day). The two domestic wells were sampled on May 19, 2021 for total dissolved solids, alkalinity, metals, VOCs, SVOCs, sulfate, chloride, nitrate, nitrite, and fecal coliform to update the assessment of groundwater quality in the wells and determine if shallow groundwater is potentially being drawn down into the well screens. Fecal coliform was not detected in the wells and groundwater geochemistry was similar to historical deep groundwater conditions. These results indicate that these wells are unlikely to draw shallow groundwater down into the well screens and that the groundwater being extracted by the wells is coming from the screened intervals (e.g., deeper than 350 feet bgs).

4.8.2 Groundwater Extraction in the North End, NBBW and GTEP Area

Groundwater was extracted from the four areas illustrated on Figures 4.32 and 4.33, and described below:

- In Area 1, groundwater extraction is ongoing at three wells (MW153-EW-1, MW154-EW-1, and MW155-EW-1) at a combined rate of between 7.1 and 7.5 gpm during the reporting period. Extraction from MW156-EW-1 was suspended on March 22, 2012 because the 1,4-dioxane concentration dropped to below the performance standard in effect at that time (5 μg/L). 1,4-Dioxane was detected at an estimated concentration of 0.45 J μg/L in MW156-EW-1 groundwater sampled on February 9, 2022 and at an estimated concentration of 0.6 J μg/L in the most recent groundwater sample collected on May 2, 2022.
- In Area 2, pumping from one well (MW160-WD) was conducted. Groundwater extraction from this well is limited by the formation and pumping was limited to 0.5 gpm. The most recent (second quarter 2022) 1,4-dioxane concentrations detected at this well and adjacent well MW132-WD were 2.9 μg/L and 10 μg/L, respectively both above the current performance standard. No extraction occurred from MW118-WD (extraction suspended on 3/19/11). The most recent (May 9, 2022) 1,4-dioxane concentration in this well is 0.22 J μg/L.
- In Area 3 (MW77 area), three wells (MW102-WD, MW77-EW-1 and MW98-WD) were pumped at a combined rate of 0.68 to 1.09 gpm during the reporting period. Extraction was stopped at MW77-EW-2 on June 24, 2011 because the 1,4-dioxane concentration decreased to below the previous 5.0 μg/L performance standard. The most recent sample collected on April 28, 2022, 1,4-dioxane was not detected at an MDL of 0.09 μg/L in this well. Pumping was also suspended at MW114-WD on October 7, 2009 for the same reason. The most recent (May 9, 2022) concentration in this well is 0.89 J μg/L slightly below the current performance standard. Pumping from well MW114-WD was not initiated during this reporting period because of its low concentration and low mass removal potential.
- Groundwater extraction in Area 4 (NBBW area) was discussed in Subsections 4.4.2.1 and 4.4.2.2 relative to compliance with groundwater standards and in effectiveness at reducing 1,4-dioxane and nitrate concentrations. WSDs will continue to optimize pumping from the weathered and unweathered Dawson wells in accordance with the RAWP protocols to meet the removal action objectives (Section 4.5.3).
- Area 5 (GTEP Area) activities are discussed in Subsection 4.9.

4.8.3 Progress from Response Actions and Investigations

Approximately 5.9 million gallons of groundwater were pumped from ten active North End response action wells during the reporting period. Based on the number of gallons pumped and the concentrations at each extraction well, approximately 352 grams (0.76 pounds) of 1,4-dioxane were removed during the reporting period as shown in Table 4.9. The cumulative volume removed since inception of the response actions is about 160.4 million gallons, with a cumulative mass removal of 9,950 grams (21.9 pounds) of 1,4-dioxane. Table 4.9 lists the groundwater volume removed and the 1,4-dioxane mass removed from each north end extraction well.

Trend analyses for the 35 of the 37 wells being monitored in the North End Area are illustrated in Figures 4.35 through 4.40. Additionally, trend analysis was performed on four compliance wells and presented in Appendix C-3.2. Two of these compliance wells are not listed in the North End GWMP Update No. 3 (Parsons, 2021b) but are included here (B-313 and MW77-WD) because they are good indicators of 1,4-dioxane mass removal occurring over time. B-313, B-321, and PTP-14 were dry or lacking enough water to sample during this reporting period so trend could not be determined.

All trend results are summarized in the table below. Of the 37 North End and compliance wells where trend analysis was performed, 32 (86%) are showing declining trends and 5 (14%) are showing no trends. PTP-12 previously had no trend but during the first half of 2022, developed a decreasing trend. PTP-14 presented an increasing trend for 1,4-dioxane through June 2020 but has been dry since that date and no analyses could be performed. B-313 and B-321 were decreasing in the last reporting period but lacked enough water to sample or were dry in first half 2022. The decreasing trends in all four Areas are evidence that the ongoing response actions are effective at removing mass from within Section 31.

Extraction well B-321 was last sampled on August 11, 2021, and showed an increasing trend in nitrate. This increase may be caused by variations in groundwater levels and/or flow directions in the vicinity of this extraction well resulting from cessation of potable water injection. B-321 was dry during the first half of 2022, and no analyses could be performed. Nearby well MW113-EW-1 that had no trend in the last reporting period had a decreasing trend for nitrate in first half 2022.

Results of 1,4-Dioxane and Nitrate Trend Analysis in North End Wells

Well	Trend ^{1/}	Extraction Well?	Well	Trend	Extraction Well?
		1,4-D	ioxane		
B-321	Dry	Yes	MW142-WD	Decreasing	No
B-326-UD*	Decreasing	No	MW144-WD	Decreasing	No
B-326-WD*	No trend	No	MW151-WD	Decreasing	No
MW05-WD	Decreasing	No	MW153-EW-1	Decreasing	Yes
MW102-WD	Decreasing	Yes	MW154-EW-1	Decreasing	Yes
MW103-WD	No Trend	No	MW155-EW-1	Decreasing	Yes
MW113-UD	Decreasing	Yes	MW156-EW-1	Decreasing	Yes
MW113-EW-1	Decreasing	Yes	MW156-WD	Decreasing	No
MW114-WD	Decreasing	Yes	MW157-WD	Decreasing	No
MW117-WD	Decreasing	No	MW160-WD	Decreasing	Yes
MW118-WD	Decreasing	Yes	MW176-DEN	No trend	No
MW121-WDR	Decreasing	No	MW179-UDEN	No trend	No
MW122-WDR	Decreasing	No	MW77-EW-1	Decreasing	Yes
MW123-WD	Decreasing	No	MW77-EW-2	Decreasing	Yes
MW124-WD	Decreasing	No	MW77-WD*	No trend	No
MW125-WD	Decreasing	No	MW98-WD	Decreasing	Yes
MW129-WD	Decreasing	No	PTP-12	Decreasing	No
MW132-WD	Decreasing	No	PTP-13	Decreasing	No
MW135-WD	Decreasing	No	PTP-14	Dry	No

Well	Trend ^{1/}	Extraction Well?	Well	Trend	Extraction Well?
MW141-WD	Decreasing	No	B-313*	Insufficient sample volume	No
Nitrate					
B-321	Dry	Yes	MW113-EW-1	Decreasing	Yes

^{1/} Trend for the compliance wells uses the last ten sampling events. Trend for all other wells uses all sampling events. Compliance wells are indicated by a *. Trend is determined by Mann-Kendall trend test for compliance wells only, remaining well trends determined by Sen's test. MW77-WD and B-313 are not North End Monitoring wells but are listed here for additional information only.

Figure 4.41 depicts the concentration trends spatially with the use of different colored dots to signify increasing, decreasing, and no trend. Inset graphs for wells MW103-WD and B-326-WD which exhibit no trend, are shown on the figure. B-326-WD is a compliance well with no trend over the last 10 samples. An inset on Figure 4.41 displays all data for B-326-WD to demonstrate how 1,4-dioxane has decreased over time. MW77-WD and B-313 had, or currently have, no trend also but display similar results as B-326-WD. MW179-UDEN has no trend but all data was not detected. Figure 4.41 shows the lateral extent of the 1,4-dioxane plume in Sections 31, 30, and 19.

The following table summarizes the status of each task specified in the ongoing RAWPs and Monitoring Plans.

Summary of Progress to Date

Revised North End IRA Work Plan Addendum (EMSI, 2008b)	Status
Continue pumping from extraction wells in Areas 1, 2, 3, and 4.	Ongoing.

Work Plans for Area 4 Response Action (EMSI, 2008b and 2010b)	Status
Extraction coupled with potable water injection upgradient of extraction well MW113-EW-1 is intended to mobilize and recover mass from this otherwise "stagnant zone" of groundwater contamination. Continue pumping from extraction well MW113-EW-1 as deemed appropriate to achieve objectives.	Potable water injection was discontinued on October 2, 2018. Extraction from MW113-EW-1 is ongoing. NBBW-IW-3 was converted to an extraction well and was initially pumping at a rate of about 2 gpm to enhance mass removal from this Area. Water levels continue to decrease in the area and NBBW-IW-3 has become formation limited resulting in an extraction rate of 0.5 gpm through the first half of 2021. Extraction rates continued to decline and the well became dry in September 2021.

Work Plans to Extract Additional Groundwater from Area 3 and 5 of the North End Response Action	Status
(EMSI, 2010a and 2011)	

Assess the presence (or absence) of a preferential pathway beneath the GTEP pad toward MW77-WD, the lateral limits of the pathway (if present), the direction and rate of groundwater movement, and potential yield from an extraction well. Design and install a new extraction well and collection system to best intercept the flow of contaminated groundwater toward MW77-WD.

Initial investigation work complete. Extraction from MW170-EW-1 is ongoing - see Subsection 4.9, below.

North End Groundwater Monitoring Plan and Update No. 3 (EMSI, 2007b and Parsons, 2021b)	Status
Assess results and modify plan as appropriate.	Ongoing. Quarterly and semiannual monitoring of North End wells will continue in accordance with <i>Update No. 3</i> .

Response Action Work Plan for B-326-UD and B-313 Area	Status	
(EMSI, 2013)		
Extract groundwater from MW113-UD to remediate contamination in the vicinity of B-326-UD. Extract groundwater from B-321 to remediate contamination in the vicinity of B-313.	Ongoing. An unweathered Dawson monitoring well MW115-UD was sampled for 1,4-dioxane on August 20, 2013 and March 4, 2014. No 1,4-dioxane was detected in either sample. Groundwater extraction from wells MW113-UD and B-321 commenced in June and July 2013, respectively, in accordance with the RAWP. B-321 became dry and pumping was discontinued in October 2021.	

Work Plan to Assess Northern Extent of 1,4- Dioxane in Shallow Groundwater (North of Well MW144-WD) (EMSI, 2014)	Status
Install four piezometers along western extension of Mississippi Avenue. Sample groundwater and collect confirmation samples. Recommend location for permanent sentry well. Install additional piezometers to delineate lateral extent if 1,4-dioxane concentrations are greater than the performance standard.	Piezometers NEPZ-100 through NEPZ-103 were installed and sampled for 1,4-dioxane. Initial and confirmation sampling results were less than the performance standard of 0.9 μ g/L. A sentry well location was recommended.

Work Plan to Sample North End Wells, Piezometers, and Surface Water	Status
(EMSI, 2016)	

Sample existing monitoring wells, piezometers, and surface water stations for 1,4-dioxane, VOCs, metals, nitrate, and nitrite beginning at the Yale Avenue extension well transect and extending northward up to and including the recently-installed piezometers along Mississippi Avenue.

In addition, one surface water sampling station (SW-3) is located south of the Yale Avenue extension.

Field investigation work complete. Analytical results have been validated and are consistent with previous sampling results.

Revision 1, Addendum to Work Plan to Assess		
Northern Extent of 1,4-Dioxane		
(EMSI, 2017)		

The second phase of the work to delineate lateral extent of 1,4-dioxane concentrations across the NEPZ transect involved extending the Mississippi transect to the east and west and sampling for 1,4-dioxane and VOCs. A location for a permanent sentry well was determined in accordance with the Work Plan.

five-year review (USEPA, 2017).

Status

Additional piezometers to the east and west were installed in 2nd half 2017. Based on assessment of geological and chemical results from the piezometers, a permanent sentry well was installed, developed, and ultimately added to the North End GWMP.

Work Plan to Cease Potable Water Injection at North Boundary Barrier Wall		
	(EMSI, 2018d)	
	Cease potable water injection to evaluate the effectiveness of the NBBW without Potable Water	_
	Injection (PWI), as directed by USEPA in the fourth	

Status

WSDs began baseline sampling in June 2018 and continued sampling and collection of water levels through the first half of 2020. The cessation pilot-test was terminated in July 2019.

Revised Work Plan to Further Assess the North End 1,4-Dioxane Plume	Status
(EMSI, 2018a)	
Assess the northern and vertical extent of the 1,4-dioxane plume and update the Conceptual Site Model (CSM) of the North End area. Work scope includes Installing six wells (shallow and deep), collecting samples, and performing slug tests.	The Work Plan was implemented in 2018 and 2019 and a final report was prepared in 2020. The final report was approved by USEPA in September 2020.

Effectiveness of the MW38 Area, NTES, and North End Response Actions, (EMSI/Parsons, 2021b) at the Site were evaluated as it related to findings and recommendations in USEPA's Fourth 5YRR (USEPA, 2017). Response Action objectives prescribed in work plans and notification documents for the North End are being met by ongoing groundwater extraction from the Response Actions and ongoing monitoring and sampling programs. System optimization is an ongoing component of operations and includes, but is not limited to, maximizing pumping from wells with the highest 1,4-

dioxane concentrations; and cyclical pumping from wells whose concentrations meet the performance standard then rebound to above the performance standard.

4.9 GTEP Area Response Actions

Pumping from the GTEP extraction well (MW170-EW-1, Figure 4.33, Area 5) was initiated on January 9, 2012 and continued throughout the reporting period. During this reporting period, the pumping rate ranged between 12.2 gpm and 13.1 gpm, with approximately 3.2 million gallons pumped during the period. Approximately 67.4 million gallons have been extracted since the start of pumping.

Figures 4.16 and 4.17 show the potentiometric surface configuration of the GTEP area during January and April 2022, respectively. In the center of the GTEP area, groundwater levels at MW170-WD (adjacent to extraction well MW170-EW-1) have been lowered by approximately 16 ft, compared to the January 2012 pre-pumping groundwater elevation of 5703.12 ft amsl. A hydrograph of MW170-WD (below) shows the correlation between pumping rate in MW170-EW-1 and water levels in MW170-WD.



Figures 4.16 and 4.17 indicate that a cone of depression beneath the GTEP area remained throughout the reporting period. The 360-degree capture zone continued to prevent contaminants from migrating toward MW77-WD and MW62-WDR. Pumping rates were sustained during this reporting period.

The inferred flow lines on Figure 4.17 indicate inward flow toward extraction well MW170-EW-1 from all directions. This hydraulic condition is meeting the specific response action objective of the RAWP (EMSI, 2011) "...to cease the potential seepage of contaminated groundwater from the sand channel toward well MW77-WD". The 1,4-dioxane concentration at compliance well MW77-WD has steadily decreased from 41 μ g/L just prior to GTEP pumping to 12 μ g/L on April 18, 2022. Baseline/initial and subsequent analytical results for all GTEP area wells are shown in Table 4.10. These results indicate that groundwater quality within and adjacent to the GTEP sand channel has improved since pumping began.

With regard to MW62-WDR, the well lies within the NBBW zone of containment shown on Figures 4.16 and 4.17. The NBBW CSE (EMSI/CDM-Smith/Parsons, 2021) determined that the NBBW effectively contains flow of contaminated groundwater within the alluvium/weathered bedrock groundwater unit. Any residual 1,4-dioxane remaining north of the containment zone will be captured by ongoing Response Action pumping north of the containment zone.

Statistical trend analyses of VOCs, 1,4-dioxane, and nitrate in well MW170-EW-1 are presented in Figure 4.42 and in the table below. 1,1-DCA, 1,1-DCE, 1,4-dioxane, PCE, and TCE showed statistically significant decreasing trends while cis-1,2-dichloroethene (cis-1,2-DCE) is showing an increasing trend; all other analytes were not trending.

Trends in MW170-EW-1

Compound	Trend
1,4-Dioxane	Decreasing
1,1-DCA	Decreasing
1,1-DCE	Decreasing
cis-1,2-DCE	Increasing
TCE	Decreasing
PCE	Decreasing

4.10 Permitted Well Inventory

In accordance with Section 5.4.3 of the GWMP, an inventory of permitted water wells is to be conducted every five years in accordance with the requirements of the Final Institutional Control Plan (Parsons, 2002). The last inventory performed for the Site was prepared in 2017 and presented in the *Remedial Action and Operations & Maintenance Status Report, January through June 2017, September 30, 2017.*

The scope of the water well inventory includes obtaining current records from the Colorado State Engineers Office of permitted water wells within ½ mile to the east, south and west of the Site, and 5 miles downgradient (north) of the Site (Figure 4.43). Downgradient is defined as within the Murphy Creek drainage basin to the north as shown on Figure 4.43. Table 4.11 presents a summary of relevant information related to the water supply and Aurora's monitoring wells completed in alluvium and/or weathered bedrock, to depths no deeper than 100 feet bgs located within the drainage basin. Appendix C-7 presents all wells within five miles of the Site.

5.0 LANDFILL GAS REMEDY

The current LFG extraction, collection and treatment system consists of the following components: 64 vertical gas extraction wells (EWs), header and lateral piping, three automatic and nine manual condensate traps, two flares, and the GTEP.

The original system began operation in October 1996. All LFG was treated by the Lowry Blower/Flare (LBF) station, which burned LFG in an enclosed flare. Since then, the system has been expanded to include additional extraction wells in both the Lowry and DADS landfills. Additional treatment devices have also been added to treat the combined gas flows from Lowry and DADS landfills.

The GTEP began operation in July 2008 and is a beneficial use treatment system that uses LFG to produce electricity. The DADS Blower/Flare (DBF) station, installed in 2010, burns LFG in an open flare. It began operation in August 2010.

In March 2015, the Lowry/DADS treatment system was updated with the installation of large capacity candlestick flare, referred to as Flare Station 3 (FS3). At that time, FS3 replaced the LBF station, which is currently decommissioned.

On June 4, 2019 the CDPHE approved a Title V Permit modification request to allow operation of the GTEP, DBF, and FS3 at full capacity, full time. The combined capacity of the three treatment units is approximately 3,800 standard cubic feet per minute (scfm). The modification was necessary to accommodate increasing gas volume generated from the DADS Section 32 landfill. This operational change is a departure from the previous routine of operating the DBF on an as needed basis only.

5.1 LFG Extraction, Collection, and Treatment System Operations

The current LFG extraction, collection and treatment system consists of vertical gas extraction wells and condensate traps and the GTEP and blower/flare stations.

5.1.1 Extraction Wells and Collection System

The Lowry LFG extraction and collection system was monitored monthly (Appendix D-1). Of the sixty-four EWs at Lowry, sixty-one were online and three were shut down due to lack of gas production. Adjustments were made to wellhead valves as needed to compensate for changing methane, oxygen, carbon dioxide, and balance gas levels. Gas temperatures at the extraction wells remained stable during the reporting period with no initial gas temperature exceeding 103 degrees Fahrenheit (°F).

5.1.1.1 Wellhead Vacuums

LFG extraction vacuums were monitored at both the wellhead and the collection system piping. Measurements and adjustments made to maintain system balance were recorded on the LFG Extraction Well Monitoring forms (summarized as Appendix D-1).

5.1.1.2 Wellhead Gas Quality

LFG quality measurements (including methane, carbon dioxide, oxygen, and balance gas [mostly nitrogen]) were collected monthly from the 64 EWs. The overall gas quality remained stable within the well field and at the GTEP, DBF, and FS3 stations, as shown in Appendices D-1 and D-2.

5.1.1.3 Collection Piping

The table below shows the LFG oxygen concentrations measured at the Lowry Header Pipe and at each treatment device during the reporting period.

LFG Oxygen Concentrations (% Volume)			
Sample Point	Minimum	Average	Maximum
Lowry Header Pipe	1.3	2.2	3.6
GTEP	0.0	0.6	1.4
DBF	0.0	0.6	1.3
FS3	0.0	0.7	1.3

Generally, oxygen readings up to 3% indicate integrity of the gas collection network. In one instance a hose was found to be split requiring repair. No other problems were encountered. Monitoring data are provided in Appendices D-2.1 through D-2.4.

5.1.1.4 Condensate Traps

Automatic condensate traps were inspected weekly. Pulse counter and totalizing flow meter readings were recorded on the Weekly Service Records on file at the WTP. Monthly automatic condensate volumes measured at the T505 flow meter in the WTP are summarized below:

Period	Condensate Processed (Gallons)
January	1,022
February	1,072
March	325
April	401
May	847
June	866
Total	4,533

The integrity of the automatic traps and conveyance line to the WTP was monitored approximately weekly for volume production and pressure changes. All inspections and testing were documented on WTP checklists and/or in the daily operator logs. Completed checklists are provided in Appendix A-1. No operational problems were observed.

Manual condensate traps were inspected monthly. All manual traps appeared to be collecting condensate. No condensate was removed from the manual traps during the reporting period.

5.1.1.5 Gas Collection System Maintenance

During the reporting period, minor maintenance was performed such as refreshing gas well ID markings.

5.1.2 GTEP and Blower/Flare Stations

During the reporting period, the GTEP, DBF, and FS3 stations provided treatment of extracted LFG. The GTEP, DBF, and FS3 operated for approximately 4,039 hours, 4,297 hours, and 4,097 hours, respectively.

During the reporting period, routine preventive maintenance such as fluid changes and engine overhauls were performed. The flow meter was found to be in good working order with only minor adjustments needed to maintain accurate flow readings.

While the DBF and FS3 stations were operating, flare temperature, flow rate, methane content, and maintenance activities were recorded and are discussed below. Similar data were collected for the GTEP in accordance with the *Modified Construction Permit No. 06AR1264* issued by the CDPHE Air Pollution Control Division. Those data are retained at the GTEP and are available for inspection by USEPA and CDPHE.

5.1.2.1 Flare Temperature

While combustion temperature was recorded, DBF and FS3 are open flares and not subject to combustion temperature requirements - only visual presence of a flame.

5.1.2.2 Gas Flow Rate

For the reporting period, the combined average LFG flow from both Lowry and DADS Landfills was approximately 2,709 scfm. The combined average LFG flow was calculated by first summing the volume of LFG consumed by the GTEP, DBF, and FS3 stations. The sum was then divided by the difference between the total time during the reporting period and the total time that no treatment device was operating. Volume data for each treatment device were collected by fixed instruments on the discharge side of the blower or compressor.

The Lowry well field contributed approximately 7.2% of this flow and 92.7% was contributed by the DADS well field, as described in the Daily Status Reports in Appendix D-2.5. For the reporting period, the average flows for Lowry and DADS were 195 and 2,514 scfm, respectively.

5.1.2.3 Methane Content

Methane content at the Lowry Header Pipe and at each treatment device was measured at least twice weekly when the treatment device was operating during regular business hours. The table below shows the LFG methane concentrations measured at the Lowry Header Pipe and at each treatment device during the reporting period.

Sample Point	Minimum	Average	Maximum
Lowry Header Pipe	23.4	29.4	37.3
GTEP	40.0	51.0	58.8
DBF	31.1	38.6	49.1
FS3	32.9	46.1	52.2

LFG Methane Concentrations (% Volume)

Monitoring data are provided in Appendices D-2.1 through D-2.4.

5.1.2.4 Blower/Flare Station Maintenance

Routine preventive maintenance such as blower rotations and lubrication were performed throughout the reporting period.

5.1.2.5 Additional Reporting Requirements

(1) Value and length of time for exceedance of parameter(s) being monitored. There were no events during the reporting period where vacuum was not observed at an extraction well.

In March 2013, a new operating procedure was approved for EWs-09, -10, and -23 due to oxygen concentrations exceeding 5.0%. The new operating procedure allows the wells to remain fully closed unless gas concentrations of greater than 30% methane and less than 2.0% oxygen are detected. The wells are temporarily opened to collect the gas readings each month. During the reporting period, EWs-09, -10, and -23 remained closed because they did not meet these operating criteria. The wells were turned on only to collect readings.

- (2) Description and duration of all periods when the gas stream is diverted from the treatment device through a bypass line or the indication of bypass flow as specified under §60.756. There were no diversions during the reporting period.
- (3) Description and duration of all periods when the treatment device was not operating for a period exceeding 1 hour and length of time the treatment device was not operating. There were seven occurrences when the treatment device was offline (total system shutdown) for one hour or more during the reporting period.

Date	Total Shutdown Time (hours)	Description
1/25/22	140.5	Compressor Replacement
2/17/22	2.5	Power interruption
2/24/22	4.8	Power interruption
3/4/22	5.8	Power interruption
4/10/22	6.3	General Maintenance
5/19/22	8.3	General Maintenance
6/30/22	8.1	General Maintenance

Treatment Device Shutdown Time

- (4) All periods when the collection system was not operating in excess of 5 days. There were no periods where the collection system was not operational in excess of 5 days during the reporting period.
- (5) The location of each exceedance of the 500 parts per million methane concentration as provided in §60.753(d) and the concentration recorded at each location for which an exceedance was recorded in the previous quarter. This requirement is not applicable to Lowry.

(6) The date of installation and the location of each well or collection system expansion added pursuant to paragraphs (a)(3), (b), and (c)(4) of §60.755. No collection system expansion activities occurred during the reporting period.

5.2 LFG Extraction, Collection, and Treatment System Monitoring

Monitoring activities during the reporting period consisted of collecting gas composition samples at the GTEP, DBF, and FS3 as well as POC probes as discussed in the following subsections.

5.2.1 Flare Sampling

Methane, carbon dioxide, oxygen, and balance gas monitoring at the Lowry header pipe, DBF and FS3 stations was performed at least once weekly during regular business hours while the treatment devices were operating and a technician was available. Results are summarized in Appendices D-2.1 through D-2.4. Monitored parameters were generally within normal historical ranges.

No other gas sampling was performed during the reporting period. No odor evaluation was performed at the flares during the reporting period.

5.2.2 GTEP Inlet Sampling

Methane, carbon dioxide, oxygen, and balance gas monitoring were performed at the GTEP at least twice weekly during regular business hours while the treatment device was operating, and a technician was available. A summary of GTEP monitoring results is provided in Appendix D-2. Monitored parameters were within normal historical ranges.

Inlet gas sampling was performed for heat and methane content during the reporting period (Appendix D-3). This annual sampling occurred on February 16, 2022 as required by the Construction Permit. No odor evaluation was performed at the GTEP during the reporting period.

5.2.3 GTEP Outlet Sampling

No outlet sampling at the GTEP exhaust was performed during the reporting period.

5.2.4 POC Probe Sampling

POC probe locations are shown in Figure 5.1. The last biennial sampling event for VOCs was performed in May 2021. POC probes were not sampled for VOCs this reporting period.

The POC probes were sampled quarterly for methane (Appendix D-4). All concentrations were below the methane performance standard of 5% by volume.

6.0 STORMWATER

The following subsections discuss performance monitoring of the Surface Water Removal Action (SWRA) and stormwater monitoring.

6.1 Surface Water Removal Action

As discussed in Subsection 4.2.1, the depth to groundwater within the alluvium/weathered Dawson beneath the SWRA (which extends between the NTES and WTP access road) is approximately 10 ft bgs. The SWRA blanket drain typically lies between two and four ft bgs. Consequently, the water table is beneath the base of the SWRA blanket drain, so clogging of the drain is not a concern.

6.2 Stormwater Monitoring

Annual stormwater sampling in accordance with the *Stormwater Monitoring Plan* (EMSI, 2008a) was not performed during the reporting period. Stormwater will be sampled in the next reporting period if sufficient flow is available to activate the stormwater sampler. The stormwater sampling location (SWMP-1) is shown on Figure 6.1.

6.2.1 Sampling

Stormwater sampling was not performed during this reporting period.

6.2.2 Stormwater Discharge Rate

A stormwater discharge rate was not estimated because sampling was not performed during this reporting period.

7.0 COVER MONITORING

Inspection and maintenance of the Site is required by the *Final Operations and Maintenance Manual, Covers and Stormwater* (EMSI, 2007a). Inspections are conducted to identify and repair problems arising from nuisance conditions, settlement, cover or ditch erosion, ditch sedimentation, and damage to security fences and gates. The following sections discuss the Site and buffer zone inspections and maintenance performed during this reporting period.

7.1 Landfill Cover

7.1.1 Site and Landfill Cover Inspection

A Site-wide inspection is required annually and after any event that may cause release of waste material. The following remedial components are inspected:

- The landfill prism;
- The traffic cap covering the East/South/West (ESW) slurry wall;
- The SWRA collection system cover (including surface features of the NTES trench);
- The waste pit area; and
- The stormwater conveyance ditches.

A formal inspection was conducted in June 2022 following an above normal rain event (Appendix E-1.1). Some minimal areas of shallow ponding on the cap, in and near roads was noted. The slow rain rate from this event did not create runoff with the potential to erode. Stormwater diversion ditches remain in very good condition.

7.1.2 Landfill Cover Maintenance Activities

Cover maintenance during the first half 2022 was performed to fill shallow areas noted as near flat or possibly low in the cover. Approximately 330 cy of clean topsoil was used to fill shallow areas with the greatest potential for ponding. Weed mitigation in the form of spot spraying was performed as necessary in accordance with the *Integrated Weed Management Plan for Lowry Landfill Superfund Site and Buffer Properties* (Parsons, 2009).

Due to a noticeable decline in the prairie dog population due to control measures performed in November 2020 in surrounding areas and within Section 6, mitigation was not required during the reporting period.

7.2 Buffer Zones

7.2.1 Buffer Zone Inspections

Formal quarterly inspections of the buffer zones surrounding the Site were conducted in January and April 2022 (Appendices E-2.1 and E-2.2, respectively). Inspections focused on the integrity of security fencing, removal of trash and debris, potential soil erosion, wildlife management, and noxious weed management. Items of concern included areas of damaged barbed wire fencing.

Inspection reports provide photographs of items of concern and their locations on a property map (Appendices E-2.1 and E-2.2).

7.2.2 Buffer Zone Maintenance Activities

Fence repairs and prairie dog mitigation in areas of concern were successfully performed during the reporting period.

8.0 REMEDIAL ACTION

Remedial actions have been completed for all remedy components except for groundwater, which has received Interim Completion for the groundwater monitoring program. Groundwater monitoring is continuing in accordance with the USEPA-approved GWMP (EMSI/Parsons, 2018).

9.0 PROBLEMS ENCOUNTERED, RECOMMENDATIONS, AND MASTER SCHEDULE

Problems and recommendations associated with ongoing O&M activities are presented in this section, as well as an updated Master Schedule for Site activities. The master schedule is presented as Figure 9.1.

9.1 Problems Encountered

The status of issues and recommendations identified in USEPA's Fourth Five Year Review is summarized below:

Issue Number	Recommendation	Status
1	Cease potable water injection and evaluate effectiveness of NBBW groundwater extraction system.	WSDs submitted the <i>Revised Final Report</i> on <i>Pilot Test for Cessation of Potable Water Injection</i> (EMSI/CDM-Smith, 2020a). USEPA approved the document on June 26, 2020.
		WSDs submitted the <i>NBBW Containment System Evaluation</i> (EMSI/CDM-Smith/Parsons, 2021). USEPA approved the document on October 11, 2021.
2	Increase capacity of WTP.	Completed on February 1, 2019.
3	Evaluate effectiveness of groundwater remedy components on-site and offsite and optimize, as necessary	Effectiveness Evaluations for the MW38 Area, NTES, North End Response Actions, and Perimeter Barrier Wall were prepared and USEPA approval was achieved in January 2021.
		WSDs submitted the <i>NBBW Containment System Evaluation</i> (EMSI/CDM-Smith/Parsons, 2021). USEPA approved the document on October 11, 2021.
4	Sample and analyze four wells located within and immediately adjacent to the 1,4-dioxane plume and implement appropriate remedial actions. Clarify if closure of abandoned wells was performed in accordance with Rule 16 of the 2CCR 402-2. Provide a Work Plan for detailing how potential at-risk-receptors will be	WSDs submitted the Final Technical Memorandum, Identification and Sampling of Water Supply Wells Within and Immediately Adjacent to Off-Site 1,4-Dioxane Plume (EMSI, 2020d). USEPA approved the document on June 26, 2020.

Issue Number	Recommendation	Status
	effectively identified and addressed.	
5 and 6	Add 1,4-dioxane to the COC list for groundwater remedy effectiveness monitoring and remove iron from the COC list for groundwater compliance monitoring.	WSDs submitted <i>Groundwater Monitoring Plan, Revision 2</i> (EMSI/Parsons, 2018). USEPA approved the document on September 6, 2018.
7 and 9	Develop an updated map and conceptual site model of the off-site 1,4-dioxane plume. Evaluate need for and scope of additional monitoring and additional institutional controls for the plume area.	WSDs submitted <i>Technical Memorandum</i> , <i>Updated 1,4-Dioxane Plume Map and North End Conceptual Model</i> , <i>2017 Five-Year Review Issues #7 and #9</i> (EMSI/CDM-Smith, 2020c). The memorandum included a Risk Summary prepared by USEPA that concluded the plume posed no unacceptable risk to human health. USEPA approved the document. WSDs also submitted <i>North End Groundwater Monitoring Plan – Update No.2</i> (EMSI, 2020b). USEPA approved the document on October 16, 2020. WSDs also submitted <i>North End Groundwater Monitoring Plan – Update No. 3</i> (Parsons, 2021b). USEPA approved the document on September 22, 2021. USEPA, with support and concurrence from CDPHE, TCHD, and WSDs, prepared a Conceptual Site Model Update document to augment the response to Item 7. The CSM Update was finalized October 12, 2021.
8	Reevaluate subsurface gas performance standards utilizing updated toxicity values and Site-specific input data.	WSDs submitted <i>Revision 3, Updated Compliance Monitoring Plan, Landfill Gas Remedy</i> (EMSI, 2018e). USEPA approved the document on August 2, 2018

All issues identified in the Fourth Five-Year Review have been addressed. USEPA's Fifth Five Year Review (USEPA, 2022) was approved on January 10, 2022 and states that all Operable Units are protective of human health and the environment.

With completion of the Fourth and Fifth Five Year Reviews the issues listed above are complete. No other problems were encountered during the reporting period that were not managed within the WTP standard operating procedures or that caused significant plant shutdowns beyond those reported in Section 2.0 of this document.

9.2 Recommendations

9.2.1 Recommendations for Slurry Wall Areas

Continue to monitor groundwater levels in all effectiveness monitoring well pairs. For well pairs that do not demonstrate inward gradients across the wall, collect water quality samples from the external well (PM-X series well) to assess the effectiveness of the perimeter slurry wall in these areas.

9.2.2 Recommendations for NTES, NBBW, and MW38 Areas

Continue to pump and treat groundwater from these areas. For the NTES, continue to operate the product skimming system when product thickness greater than six inches is observed in the trench.

9.2.3 Recommendations for Off-Site North End Response Actions

Continue to optimize ongoing groundwater extraction in off-Site Areas 1, 2, and 3 in accordance with their respective RAWPs. This may include increasing extraction rates, as discussed above.

9.2.4 Recommendations for Sitewide Monitoring Plan – Compliance Monitoring

As discussed in Subsections 4.4.2, seven monitoring locations were found to contain one or more compliance parameters in excess of a performance standard. The seven wells determined to be statistically out of compliance or potentially out of compliance are summarized below.

Well	Compound	Compliance Decision
B-326-UD	1,4-Dioxane	Out of Compliance
B-326-WD	1,4-Dioxane	Out of Compliance
BM-11X-100N	PCE	Out of Compliance
BM-15N6	Nitrate	Potentially Out of compliance
MW38-830N-230E	1,4-Dioxane	Out of Compliance
MW62-WDR	1,4-Dioxane	Out of Compliance
MW62-WDR	Nitrate	Out of Compliance
MW62-WDR	Nitrite	Out of Compliance
MW77-WD	1,4-Dioxane	Out of Compliance

Recommendations relative to non-compliance with performance standards at these locations are discussed in the following sections.

9.2.4.1 1,4-Dioxane in the NBBW Area

Based on the results of the statistical tests, 1,4-dioxane occurs in excess or potentially in excess of its performance standard in four NBBW-area compliance monitoring wells (B-326-UD, B-326-WD, MW62-WDR, and MW77-WD) (Figure 4.11).

The WSDs will continue to monitor both the 1,4-dioxane concentrations and the water level in these wells and continue to evaluate conditions in this area. Continued pumping from extraction wells MW113-EW-1, NBBW-IW-3, MW113-UD, B-321, MW170-EW-1, and MW-77 area wells is recommended if water is available. As of this reporting period NBBW-IW-3 and B-321 are dry.

With regard to the MW62-WDR area, this well lies within the zone of containment caused by groundwater extraction from the NBBW and Response Actions north and east of the NBBW (see Figures 4.16 and 4.17). Consequently, the exceedances may be a Case 2 condition, which requires only long-term monitoring. As required by the Fourth 5YRR (USEPA, 2017), the WSDs conducted additional evaluations of the effectiveness of the NBBW containment system and the Response Actions in the NBBW area as part of the CSE. That evaluation (EMSI/CDM-Smith/Parsons, 2021) determined that the NBBW effectively contains flow of contaminated groundwater within the alluvium/weathered bedrock groundwater unit. In the meantime, 1,4-dioxane that might have migrated north of the containment zone will be captured by ongoing Response Action pumping north of the containment zone.

9.2.4.2 Nitrate and Nitrite in the NBBW Area

Nitrate and nitrite are out of compliance in monitoring well MW62-WDR (Figure 4.11). This well is located along the northern boundary of the Site, in an area where sewage sludge was historically land farmed.

The extent of nitrate and nitrite exceedances has been determined to be limited to the eastern portion of the NBBW area (i.e., in the immediate vicinity of compliance monitoring well MW62-WDR). Therefore, there does not appear to be a potential for significant off-Site migration of nitrate or nitrite at concentrations greater than the performance standard.

To the extent that the nitrate and nitrite occurrences do not result from a source in the immediate vicinity of these wells (i.e., impacts from prior land farming of sewage sludge in this area), implementation of response actions for 1,4-dioxane should also address these compounds in this area. To the extent that the cause of the nitrate and nitrite occurrences in these wells is due to impacts from prior land farming of sewage sludge in this area, the response actions being undertaken in this area may or may not reduce their concentrations in groundwater. Nonetheless, groundwater extraction from North End wells further downgradient should capture any potential migration of nitrate and nitrite from the NBBW area if northern migration were to occur.

9.2.4.3 1,4-Dioxane in MW38-830N-230E

1,4-Dioxane concentrations in monitoring well MW38-830N-230E exceed their respective groundwater performance standards. The concentrations of 1,4-dioxane displayed no trend in this well. This well is located along the POC at the north end of the MW38 channel. The hydraulic gradient within the channel at this location is to the north so migration of 1,4-dioxane crosses the POC. As part of the groundwater containment remedy for the Site, groundwater extraction is conducted from the MW38 channel at two locations, including a location approximately 200 ft north of well MW38-830N-230E,

which is downgradient from and beyond the POC relative to the compliance monitoring well. Therefore, although 1,4-dioxane may migrate across the POC, impacted groundwater is hydraulically contained within the sand channel in the area immediately north of well MW38-830N-230E. No action other than continued extraction and monitoring of the compliance well is required for these occurrences.

9.2.4.4 Nitrate in BM-15N6

Nitrate occurs in well BM-15N6 at concentrations greater than its performance standard. Statistical testing indicates that there is a decreasing trend in nitrate concentrations in this well. As discussed in Subsection 4.4.2.4 of this report, this well is located in an area where sewage sludge had historically been land-farmed. USEPA positioned the compliance boundary within the land farming area such that it straddles the land farming area. That, coupled with an absence of 1,4-dioxane and only low-level detections of VOCs below performance standards since 2003 in this well, would indicate the source of nitrates is not from landfill mass or waste pit contaminant migration; rather, it is likely from the past land farming activities inside and outside the compliance boundary. Nitrate has been observed in surrounding wells BM-15N2 (43,000 μ g/L), BM-15NE1 (26,000 μ g/L), BM-15N5 (68,000 μ g/L) and BM-15N1 (25,000 μ g/L), (1st Half 2017) and BM-15I-15N (54000 μ g/L), BM-15I-5OS (9,300 μ g/L), and BM-15X-5OS (38,000 μ g/L) (October 2018) The spatial randomness of nitrate detections in and around well BM-15N6 as compared to other compliance wells in this vicinity is similar to that observed near the NBBW where sewage sludge was land farmed.

Because 1) the source of the nitrate occurrences in well BM-15N6 is most likely a result of sewage sludge land farming in this area, 2) groundwater is actively being extracted from this area, and 3) the distance between this well and the Site boundary is approximately 200 feet, the occurrence of nitrate in well BM-15N6 is considered to be a Case 2 condition as defined in the GWMP (EMSI/Parsons, 2018). No action other than continued groundwater monitoring is recommended.

9.2.4.5 Tetrachloroethene in BM-11X-100N

PCE in BM-11X-100N is out of compliance with no trend. The ten most recent PCE concentrations in this well range from a low of 4.6 μ g/L in October 2017 to a high of 7.2 μ g/L (October 2020) with the most recent sample containing a PCE concentration of 4.9 μ g/L (May 18, 2022). PCE levels appeared to slowly increase from October 2017 to November 2020 but have dropped in the last three sampling events. The variation in PCE concentrations appears to be related to changes in the water level in this well. Prior to the summer of 2015, the water level in this well was relatively stable ranging from approximately 5,790 to 5,795 ft amsl. Beginning in the summer of 2015, the water level in this well increased, peaking at a high of just over 5,800 ft amsl in July 2017. Since that time, the water level in this well has declined back below 5,791 ft amsl. Consequently, it is likely that the increase in PCE levels in this well may be the result of flushing of residual PCE contained in the capillary fringe/vadose zone. If this is the case, then the PCE level in this well should decline over time as evidenced by the drop in concentration of the most recent PCE result from 7.2 μ g/L in November 2020 to 4.9 μ g/L in May 2022.

The overall low concentration of PCE in well BM-11X-100N, in addition to an inward gradient across the wall at this location, and no or very low PCE detections in groundwater to the north and northeast of the well indicate that the PCE occurrences in this area

represent a Case 2 condition (little or no downward trend with a low potential for off-Site migration) as defined in the GWMP (EMSI/Parsons, 2018). The WSDs previously completed a Case 2 evaluation for this well (EMSI, 2006b). Results indicated that it is unlikely that the PCE occurrences above the performance standard in this area will migrate to the Site boundary. Rather, PCE occurrences in this area will likely attenuate naturally over time. Consequently, the recommended action is to continue monitoring.

9.2.5 Recommendations to Voluntary Actions

As discussed in Subsection 4.6 of this report, the following voluntary measures will continue to be implemented by the WSDs during the next reporting period:

- 1. Continue pumping of the MW38 Area source well (MW38-825S-445E).
- 2. Continue to operate groundwater extraction systems for gradient control in the PM-11, PM-15, and MW51 areas, as appropriate. In addition, continue to operate air sparging operations in the PM-15 and MW51 areas.
- 3. Continue to skim LNAPL from the surface of groundwater in the NTES trench, if present.
- 4. Continue to optimize removal of 1,4-dioxane within the WTP.

9.2.6 Recommendations to WTP Operations

A plan has been developed to upgrade WTP computers, software, alarm notification system and the main PLC to modern standards to enhance WTP processes and cyber security. The scope of the work also includes adding a link to the on-Site CenturyLink fiberoptic line to provide the bandwidth needed to support automatic cloud-based backups of critical plant data and files.

9.3 Schedule of Planned Activities

See Figure 9.1 Master Schedule for an update of planned activities.

10.0 REFERENCES

- EMSI, 2006a. Memorandum North End Work Plan for Initial Response Action (Installation of Two Extraction Wells), Lowry Landfill Superfund Site. October 19.
- EMSI, 2006b. Memo to Evaluate Potential TCE Migration in PM-11 Area, Lowry Landfill Superfund Site. June 6.
- EMSI, 2007a. Final Operations and Maintenance Manual, Covers and Stormwater, Lowry Landfill Superfund Site. January 25.
- EMSI, 2007b. North End Groundwater Monitoring Plan, Lowry Landfill Superfund Site. July 6.
- EMSI, 2007c. Memorandum Work Plan for MW77 Area Response Action, Lowry Landfill Superfund Site. March 5.
- EMSI, 2008a. Stormwater Monitoring Plan, Lowry Landfill Superfund Site, April 30.
- EMSI, 2008b. Revised North End Initial Response Action (IRA) Work Plan Addendum, Lowry Landfill Superfund Site. February 22.EMSI, 2008c. Updated Early Warning Monitoring Plan, Lowry Landfill Superfund Site. December 22.
- EMSI, 2008c. Updated Early Warning Monitoring Plan, Lowry Landfill Superfund Site. December 22.
- EMSI, 2010a. Notification of Work to Extract Additional Groundwater from Area 3 for the North End Response Action. November 19.
- EMSI, 2010b. Proposed Voluntary Action to More Efficiently Manage and Maintain the North Boundary Barrier Wall Containment Zone in Conjunction with Mass Removal of 1,4-Dioxane Immediately North of the Containment Zone. July 27.
- EMSI, 2011. Response Action Work Plan to Extract Additional Groundwater from Upgradient of MW77-WD, Lowry Landfill Superfund Site. November 1.
- EMSI, 2013. Response Action Work Plan, B-326-UD and B-313 Areas, Lowry Landfill Superfund Site. April 4.
- EMSI, 2014. Work Plan to Assess Northern Extent of 1,4-Dioxane in Shallow Groundwater (North of Well MW144-WD), Lowry Landfill Superfund Site. November 10.

- EMSI, 2015. Metro Letter of Understanding, Early Warning Monitoring Plan, Table B.1, Lowry Landfill Superfund Site. January 8.
- EMSI, 2016. Work Plan to Sample North End Wells, Piezometers and Surface Water Lowry Landfill Superfund Site. January 22.
- EMSI, 2017. Revision 1, Addendum to Work Plan to Assess Northern Extent of 1,4-Dioxane. July 27.
- EMSI, 2018a. Revised Work Plan to Further Assess the North End 1,4-Dioxane Plume and Update Conceptual Model for North End Area, Lowry Landfill Superfund Site. November 8.
- EMSI, 2018b. Work Plan for 3DVA Synoptic Sampling Event, Lowry Landfill Superfund Site. July 13.
- EMSI, 2018c. Addendum 1 to Work Plan for 3DVA Synoptic Sampling Event, Lowry Landfill Superfund Site. September 12.
- EMSI, 2018d. Final Pilot Test Work Plan to Temporarily Cease Potable Water Injection North of the North Boundary Barrier Wall, Lowry Landfill Superfund Site, Arapahoe County, Colorado. October 1.
- EMSI, 2018e. Revision 3, Updated Compliance Monitoring Plan, Landfill Gas Remedy, Lowry Landfill Superfund Site. July 27.
- EMSI, 2020a. Revision 4, Updated Compliance Monitoring Plan, Landfill Gas Remedy, Lowry Landfill Superfund Site. February 10.
- EMSI, 2020b. North End Groundwater Monitoring Plan Update No. 2, Lowry Landfill Superfund Site. October 16.
- EMSI, 2020c. Updated Waste Management Plan, Lowry Landfill Superfund Site. October 14.
- EMSI, 2020d. Final Technical Memorandum, Identification and Sampling of Water Supply Wells Within and Immediately Adjacent to Off-Site 1,4-Dioxane Plume, Lowry Landfill Superfund Site. June 3.
- EMSI, 2021. Revision 3, Operations and Maintenance Manual, Landfill Gas Remedy Lowry Landfill Superfund Site (with addendum). February 9.

- EMSI/CDM-Smith, 2020a. Revised Final Report on Pilot Test for Cessation of Potable Water Injection, Lowry Landfill Superfund Site, Arapahoe County, Colorado. May 15.
- EMSI/CDM-Smith, 2020b. Technical Memorandum Molybdenum in NBBW Groundwater, Evaluation of Potential Sources of Elevated Molybdenum in Wells MW113-WD and MW113-EW-1, July 23.
- EMSI/CDM-Smith, 2020c. Technical Memorandum, Updated 1,4-Dioxane Plume Map and North End Conceptual Model, 2017 Five-Year Review Issues #7 and #9, Lowry Landfill Superfund Site. October 16, 2019; Revision September 2, 2020
- EMSI/CDM-Smith/Parsons, 2019. North Boundary Barrier Wall Containment System Evaluation Plan, Lowry Landfill Superfund Site.
- EMSI/CDM-Smith/Parsons, 2021. North Boundary Barrier Wall, Containment System Evaluation, Lowry Landfill Superfund Site. September 21.
- EMSI/Parsons, 2018. Revision 2, Groundwater Monitoring Plan, Lowry Landfill Superfund Site. August 16.
- EMSI/Parsons, 2021a. Technical Memorandum, Effectiveness Evaluation for Perimeter Barrier Wall, 2017 Five-Year Review Issue #3, Lowry Landfill Superfund Site. January 20.
- EMSI/Parsons, 2021b. Technical Memorandum, Effectiveness Evaluations for MW38 Area, North Toe Extraction System, and North End Response Actions, 2017 Five-Year Review Issue #3, Lowry Landfill Superfund Site. January 22.
- Harding Lawson Associates, 1992. Final Remedial Investigation Report for the Shallow Groundwater and Subsurface Liquids and Deep Groundwater Operable Units, Lowry Landfill, Arapahoe County, Colorado. March 25.
- Metro, 2020. Metro Wastewater Reclamation District and Industrial Wastewater Discharge Permit No. 2360-6, issued to City and County of Denver and Chemical Waste Management, Inc/Waste Management of Colorado, Inc., for the Lowry Landfill Superfund Site. Effective January 5, 2020. January 3.
- Parsons, 2002. Final Institutional Controls Plan, Lowry Landfill Superfund Site Remedial Design (as amended February 28, 2005). September 19.
- Parsons, 2005. Final MW38 Area Pilot Test Report Lowry Landfill Superfund Site. April 15.

- Parsons, 2009. Integrated Weed Management Plan for Lowry Landfill Superfund Site and Buffer Properties. November.
- Parsons, 2021a. Revision 3, Operations and Maintenance Manual Groundwater Extraction, Lowry Landfill Superfund Site. August 23.
- Parsons, 2021b. North End Groundwater Monitoring Plan Update No. 3, Lowry Landfill Superfund Site. August 23.
- Parsons, 2021c. Technical Memorandum Anion Exchange Operational Performance at Lowry Landfill Superfund Site. September 24.
- Parsons/EMSI, 2021. Addendum No. 7 to Operations and Maintenance Manual, Water Treatment Plant, Lowry Landfill Superfund Site. March 26.
- USEPA, 1994a. EPA Contract Laboratory Program National Functional Guidelines for Organic Data Review (as amended). December.
- USEPA, 1994b. EPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Review (as amended). February.
- USEPA, 1994c. Record of Decision Lowry Landfill Superfund Site, Arapahoe County, Colorado, March.
- USEPA, 2002. Minor Modification of the March 10, 1994 Record of Decision, Lowry Landfill Superfund Site, Arapahoe County, Colorado. September.
- USEPA, 2004. Multi-Agency Radiological Laboratory Analytical Protocols Manual, Center for Environmental Assessment, Office of Research and Development. July.
- USEPA, 2017. Fourth Five-Year Review Report for Lowry Landfill Superfund Site Arapahoe County, Colorado. September 28.
- USEPA, 2022. Fifth Five-Year Review Report for Lowry Landfill Superfund Site Arapahoe County, Colorado. January 10.

TABLE 2.1 WATER TREATMENT PLANT SAMPLING SCHEDULE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

						Early Warning	Early Warning	Early Warning	
						Influent (grab)	Influent (grab)	Influent (grab)	
						TP-110, TP-120, TP-	TP-110, TP-120, TP-	TP-110, TP-120, TP-	Early Warning
			MP-001			140, TP-150, TP-160,	140, TP-150, TP-160,	140, TP-150, TP-160,	Influent
		(V	VTP Effluent)			TP-170, TP3310	TP-170, TP3310	TP-170, TP3310	(composite)
	Monthly 24-Hour	Monthly	Quarterly 24-	Quarterly	Yearly				
Sampling Date	Grabs ^{a/}	Composite ^{b/}	Hour Grabs ^{a/}	Composite ^{a/}	Composite ^{a/}	Monthly	Quarterly ^{c/}	Yearly	Yearly ^{d/}
January 3&4, 2022	X		X	X		X	X		
			X (VOC	X (SVOC					
February 1&2, 2022	X	X	Resample)	Resample)		X			
				X (SVOC					
March 1&2, 2022	X	X		Resample)		X			
April 4&5, 2022	X		X	X	X	X	X	X	X
May 2&3, 2022	X	X				X			
May 9&10, 2022			X (Nonylphenol Resample)						
June 6, 7 2022	X	X	• '			X			
July 2022	X		X	X		X	X		
August 2022	X	X				X			
September 2022	X	X				X			
October 2022	X		X	X		X	X		
November 2022	X	X				X			
December 2022	X	X				X			
Analytical Methods	1,4-Dioxane (8260 SIM) pH (pH-740 one time at	Molybdenum (200.8)	VOCs (EPA 624.1) Nonylphenols, Total (ASTM D7065-11)	SVOCs (EPA 625.1) Metals ^{e/} (200.8)	Metals ^{e/} (200.7, 200.8)	1,4-Dioxane (8260 SIM)	VOCs (EPA 624.1)	Nonylphenols Total (ASTM D7065_11)	SVOCs (EPA 625.1) Metals ^{f'} (200.7, 200.8)
	start of 24 hours)		(ASIM D/003_II)	Gross alpha/beta Plutonium- 238,239,240	Mercury (245.1)	Molybdenum (200.8)			Mercury (7470) Gross alpha/beta Americium-241
				Americium-241 Radium - 226,228,Total					Plutonium-238,239,240 Radium - 226,228,Total

a/ Individual compounds and frequency are listed in Industrial Discharge Permit No. 2360-6, issued by the Metro Wastewater Reclamation District (Metro), effective January 5, 2020 to January 4, 2025

b/ Monthly sampling of molybdenum performed for performance monitoring, not required by the Discharge Permit

c/ Equivalent to MP-001 VOC quarterly list

d/ Equivalent to MP-001 yearly list

e/ Quarterly Metals - Molybdenum, Zinc and Selenium

f/ Yearly Metals - Arsenic, Cadmium, Chromium, Copper, Lead, Nickel and Silver

TABLE 4.1

SUMMARY OF DRILLING ACTIVITIES COMPLETED JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Well/Boring ID	Date of Installation	Date Abandoned	Type ^{a/} of Well/Boring	Northing ^{b/}	Easting ^{b/}	Ground Surface Elevation	Measuring Point Elevation	Screened Interval	Total Depth
				(feet)	(feet)	(ft NGVD) ^{c/}	(ft NGVD)	(ft bgs) ^{d/}	(ft bgs)
Installed Wells									
None									
Abandoned Well	s	•				•			•
None									

a/ Type: BH = borehole, MW = monitoring well, TMW = temporary monitoring well, PZ = piezometer, EW = extraction well, MPE = multiphase extraction well

b/ Locations referenced to Modified State Plane Coordinate System (in feet).

c/ ft NGVD = elevation (in feet) referenced to the National Geodetic Vertical Datum of 1929.

d/ ft bgs = feet below ground surface.

TABLE 4.2
WATER LEVEL ELEVATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup		Depth	Weathering	
Well ID	Date of	(ft NGVD) ^{a/}	(ft below MP) ^{b/}	(ft bgs) ^{c/}	(& NCVD)	(ft) ^{d/}	(ft has)	(ft has)	(ft has)	Formation ^{e/}
A-102	Measurement 1/4/2022	5,703.25	20.36	17.77	(ft NGVD) 5,723.61	2.59	(ft bgs) 10.4-30.3	(ft bgs)	(ft bgs) 32	ALLUVIUM/WD
A-102	4/4/2022	5,704.11	19.5	16.91	5,723.61	2.59	10.4-30.3	35	32	ALLUVIUM/WD
A-115	1/3/2022	5,696.30	14.45	12.23	5,710.75	2.22	6.9-13.5	21	NE ^{f/} , >21	ALLUVIUM/WD
A-115	4/4/2022	5,696.19	14.56	12.34	5,710.75	2.22	6.9-13.5	21	NE, >21	ALLUVIUM/WD
B-215-WD	1/3/2022	5,702.33	33.59	31.17	5,735.92	2.42	34-36	39	36.5	WD
B-215-WD B-304	4/4/2022 1/4/2022	5,702.53 5,696.41	33.39 30.38	30.97 29.79	5,735.92 5,726.79	2.42 0.59	34-36 24-34	39 39	36.5 37	WD WD
B-304	4/4/2022	5,693.98	32.81	32.22	5,726.79	0.59	24-34	39	37	WD
B-304-UD	1/4/2022	5,686.99	41.65	39.51	5,728.64	2.14	58-78	80	36.5	UNWD
B-304-UD	4/4/2022	5,686.59	42.05	39.91	5,728.64	2.14	58-78	80	36.5	UNWD
B-305R	1/3/2022	5,692.23	32.5	30.07	5,724.73	2.43	28-38	41	27	UNWD
B-305R B-305WD	4/4/2022 1/3/2022	5,691.92 Dry	32.81 Dry	30.38 Dry	5,724.73 5,723.77	2.43 1.87	28-38 13-23	41 28	27 23	UNWD WD
B-305WD	4/4/2022	Dry	Dry	Dry	5,723.77	1.87	13-23	28	23	WD
B-306	1/4/2022	5,689.78	19.79	16.92	5,709.57	2.87	28.5-38.5	43.5	22	UNWD
B-306	4/4/2022	5,689.83	19.74	16.87	5,709.57	2.87	28.5-38.5	43.5	22	UNWD
B-307	1/4/2022	Dry	Dry	Dry	5,708.83	1.34	15-20	22	NE, >22	WD
B-307 B-308	4/4/2022 1/4/2022	Dry 5,691.75	Dry 30.81	Dry 28.75	5,708.83 5,722.56	2.06	15-20 23-33	22 37	NE, >22 33	WD WD
B-308	4/4/2022	5,690.65	31.91	29.85	5,722.56	2.06	23-33	37	33	WD
B-309	1/4/2022	5,686.98	29.43	26.52	5,716.41	2.91	17-27	31	26.5	WD
B-309	4/4/2022	5,686.84	29.57	26.66	5,716.41	2.91	17-27	31	26.5	WD
B-310	1/3/2022	5,687.44	29.71	27.36	5,717.15 5,717.15	2.35	21.5-31.5	34 34	31.3	WD WD
B-310 B-311	4/4/2022 1/4/2022	5,687.21 Dry	29.94 Dry	27.59 Dry	5,718.56	2.35	21.5-31.5 18-23	25.7	31.3 23	WD
B-311	4/4/2022	Dry	Dry	Dry	5,718.56	2.66	18-23	25.7	23	WD
B-312	1/4/2022	Dry	Dry	Dry	5,711.24	2.64	21-31	35	31	WD
B-312	4/4/2022	Dry	Dry	Dry	5,711.24	2.64	21-31	35	31	WD
B-313 B-313	1/4/2022	5,688.50 5,687.00	27.42	24.9	5,715.92	2.52	20-27 20-27	30.1	26.5	WD WD
B-313-UD	4/4/2022 1/4/2022	5,680.70	28.92 34.75	26.4 32.1	5,715.92 5,715.45	2.52	48-63	65	26.5 27	UNWD
B-313-UD	4/4/2022	5,680.55	34.9	32.25	5,715.45	2.65	48-63	65	27	UNWD
B-314	1/4/2022	5,696.23	45.9	43.37	5,742.13	2.53	32.5-47.5	51	47.5	WD
B-314	4/4/2022	5,696.21	45.92	43.39	5,742.13	2.53	32.5-47.5	51	47.5	WD
B-314-UD B-314-UD	1/4/2022 4/4/2022	5,688.42 5,688.27	53.58 53.73	51.18 51.33	5,742.00 5,742.00	2.40	67-87 67-87	89 89	48.5 48.5	UNWD UNWD
B-315	1/4/2022	5,696.76	41.2	38.64	5,737.96	2.56	28-43	46	43	WD
B-315	4/4/2022	5,696.84	41.12	38.56	5,737.96	2.56	28-43	46	43	WD
B-316	1/3/2022	5,695.27	23.39	20.83	5,718.66	2.56	20.5-30.5	34	30.5	WD
B-316	4/4/2022	5,694.73	23.93	21.37	5,718.66	2.56	20.5-30.5	34	30.5	WD
B-316-UD B-316-UD	1/3/2022 4/4/2022	5,691.61 5,691.75	27.23 27.09	24.99 24.85	5,718.84 5,718.84	2.24	41-56 41-56	59 59	33	UNWD UNWD
B-310-0D	1/3/2022	5,690.32	20.5	17.98	5,710.82	2.52	18-24	28.1	24	WD
B-317	4/4/2022	5,689.90	20.92	18.4	5,710.82	2.52	18-24	28.1	24	WD
B-317-UD	1/3/2022	5,690.64	19.29	17.46	5,709.93	1.83	37-52	54.5	23.5	UNWD
B-317-UD	4/4/2022	5,690.58	19.35	17.52	5,709.93	1.83	37-52	54.5	23.5	UNWD
B-318 B-318	1/3/2022 4/4/2022	Dry Dry	Dry Dry	Dry Dry	5,728.49 5,728.49	2.59 2.59	18-25 18-25	28 28	25 25	WD WD
B-319	1/4/2022	Dry	Dry	Dry	5,713.40	2.39	21.5-41.5	44.1	42	WD
B-319	4/4/2022	Dry	Dry	Dry	5,713.40	2.80	21.5-41.5	44.1	42	WD
B-319-25S	1/4/2022	Dry	Dry	Dry	5,712.73	2.23	14-24	24	NE, >24	WD
B-319-25S	4/4/2022	Dry	Dry	Dry	5,712.73	2.23	14-24	24	NE, >24	WD
B-319-26W B-319-26W	1/4/2022 4/4/2022	Dry Dry	Dry Dry	Dry Dry	5,712.60 5,712.60	2.60	12.4-22.4 12.4-22.4	22.4 22.4	NE, >22.4 NE, >22.4	WD WD
B-319-50S	1/4/2022	Dry	Dry	Dry	5,713.85	2.55	14-24	24	NE, >24	WD
B-319-50S	4/4/2022	Dry	Dry	Dry	5,713.85	2.55	14-24	24	NE, >24	WD
B-319-50W	1/4/2022	Dry	Dry	Dry	5,711.78	2.28	14-24	24	NE, >24	WD
B-319-50W	4/4/2022	Dry	Dry	Dry	5,711.78	2.28	14-24	24	NE, >24	WD
B-319-75S	1/4/2022	Dry	Dry	Dry	5,714.00	2.00	14-24	24	NE, >24	WD WD
B-319-75S B-320	4/4/2022 1/4/2022	Dry 5,692,29	Dry 30.73	Dry 28.31	5,714.00 5,723.02	2.00	14-24 19-34	24 38.5	NE, >24 34	WD WD
B-320	4/4/2022	5,690.49	32.53	30.11	5,723.02	2.42	19-34	38.5	34	WD
B-321	1/4/2022	Dry	28.84	27.05	5,712.89	1.79	12-27	30.5	27	WD
B-321	4/4/2022	Dry	29.49	27.7	5,712.89	1.79	12-27	30.5	27	WD
B-322	1/3/2022	5,688.35	31.59	28.81	5,719.94	2.78	15-30	33.5	30	WD
B-322	4/4/2022	5,688.22	31.72	28.94	5,719.94	2.78	15-30	33.5	30	WD

Best			Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
B-323-WD L3/2022 Dy		Date of	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
B-323-WD		Measurement		MP) ^{b/}							
B-324-WD											
B-325-WD											
B-325-WD											
B-325-WD			5,695.92								
B-326-UD											
B-326-WD											
B-32-WD											
B-327-UD											
B-327-UP											
B-317-WD											
B-502 41/2022 5/7490 3072 269 5/7972 382 95-105 120 23 UNWD B-504A 11/9/2022 5/7154 34.84 34.46 5/752.18 0.38 105-125 126.5 36 UPPER DENVI B-504A 41/2022 5/71569 34.49 34.11 5/752.18 0.38 105-125 126.5 36 UPPER DENVI B-506 48/2022 5/869.01 146.49 144.1 5/833.39 2.39 310-350 355 55 LIGNITE B-506 48/2022 5/869.01 146.49 144.1 5/833.39 2.39 310-350 355 55 LIGNITE B-506 48/2022 5/879.11 146.38 144.9 5/833.39 2.39 310-350 355 55 LIGNITE B-518 11/12/2022 5/759.16 38.58 36.24 5/797.74 2.34 75-95 100 50 UNWD B-518 47/2022 5/879.12 38.42 36.08 5/797.74 2.34 75-95 100 50 UNWD B-519 48/2022 5/807.35 19.79 19.65 5/827.14 0.14 66.80 85 50 UNWD B-519 48/2022 5/807.35 19.79 19.65 5/827.14 0.14 66.80 85 50 UNWD B-520 48/2022 5/807.35 19.79 19.65 5/827.14 0.14 66.80 85 50 UNWD B-520 48/2022 5/807.35 19.79 19.65 5/827.14 0.14 66.80 85 50 UNWD B-520 48/2022 5/807.37 61.85 56.16 8/80.20 18.90 125-145 155 50 UPPER DENVI B-706 48/2022 5/807.37 61.85 56.16 8/80.20 18.90 125-145 155 50 UPPER DENVI B-706 48/2022 5/874.26 01.75 8/8.74 5/86.01 3.01 125-132 153 101 UNWD B-708 48/2022 5/742.6 01.75 8/8.74 5/86.01 3.01 125-132 132 101 UNWD B-712-35-UD 41/2022 5/742.6 01.75 8/8.74 5/86.01 3.01 125-132 132 101 UNWD B-712-35-UD 41/2022 5/743.61 52.57 32.28 5/874.8 88.77 5/86.01 3.01 125-132 132 101 UNWD B-712-35-UD 41/2022 5/742.6 01.75 8/8.74 5/86.01 3.01 125-132 132 101 UNWD B-712-35-UD 41/2022 5/743.61 5/874.8 88.77 5/86.01 3.01 125-132 132 101 UNWD B-712-15-UD 11/92022 5/743.61 5/86.24 2.74 105-115 119 36.5 UNWD B-712-15-UD 11/92022 5/743.61 5/86.24 2.74 105-115 119 36.5 UNWD B-712-15-UD 11/92022 5/743.61 5/86.24 2.74 105-115 119 36.5 UNWD B-712-15-UD 11/92022 5/743.61 5/86.24 5/86.51 5/86.24 5/86.51 5/86.8 8 2 35.5 UNWD B-712-15-UD 11/92022 5/743.61 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.24 5/86.51 5/86.2											
B-502				29.67		5,723.39	2.49				
B-504A											
B-504A											
B-506											
B-506											
B-518											
B-519										50	
B-519	B-518				36.08		2.34	75-95	100		
B-520											
B-520											
B-706											
B-706											
B-708											
B-712-25S-UD											
B-712-25S-UD											
B-712-LD											
B-712-LD											
B-712-UD											
B-712-UD											
BKGD-1WD 4/11/2022 5,842.87 32.31 30.08 5,875.18 2.23 44.5-54.5 55 54 WD BKGD-2UD 1/18/2022 5,801.36 50.14 48.19 5,851.50 1.95 58-68 68.5 47.6 UNWD BKGD-2WD 4/11/2022 5,801.38 50.12 48.17 5,851.50 1.95 58-68 68.5 47.6 UNWD BKGD-2WD 1/18/2022 5,840.76 10.66 8.76 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3WD 4/11/2022 5,889.94 11.48 9.58 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.33 56.34 54.28 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,785.3											
BKGD-2UD 1/18/2022 5,801.36 50.14 48.19 5,851.50 1.95 58-68 68.5 47.6 UNWD BKGD-2UD 4/11/2022 5,801.38 50.12 48.17 5,851.50 1.95 58-68 68.5 47.6 UNWD BKGD-2WD 1/18/2022 5,840.76 10.66 8.76 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-2WD 4/11/2022 5,839.94 11.48 9.58 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3UD 4/11/2022 5,785.83 56.34 54.28 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.83 56.34 54.28 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 1/18/2022 5,825.8	BKGD-1WD	1/18/2022	5,842.55		30.4		2.23	44.5-54.5	55	54	
BKGD-2UD 4/11/2022 5,801.38 50.12 48.17 5,851.50 1.95 58-68 68.5 47.6 UNWD BKGD-2WD 1/18/2022 5,840.76 10.66 8.76 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-2WD 4/11/2022 5,839.94 11.48 9.58 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3UD 4/11/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.14 57.44 54.51 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 1/18/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-4UD 1/18/2022 5,822.84<											
BKGD-2WD 1/18/2022 5,840.76 10.66 8.76 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-2WD 4/11/2022 5,839.94 11.48 9.58 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3UD 4/11/2022 5,785.83 56.34 54.28 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.83 56.34 54.28 5,842.18 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-4UD 1/18/2022 5,822.84 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32											
BKGD-2WD 4/11/2022 5,839.94 11.48 9.58 5,851.42 1.90 33.6-48.6 48.6 47.6 WD BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3UD 4/11/2022 5,785.83 56.34 54.28 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.81 57.44 54.51 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,785.30 57.28 54.55 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,825.84 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4UD 1/18/2022 5,832.32 19.57 17.32 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.31											
BKGD-3UD 1/18/2022 5,785.75 56.42 54.36 5,842.17 2.06 94-104 105 70 UNWD BKGD-3UD 4/11/2022 5,785.83 56.34 54.28 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.14 57.44 54.51 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-4UD 1/18/2022 5,822.94 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BK-111-100N 1/18/2022 5,773.76											
BKGD-3UD 4/11/2022 5,785.83 56.34 54.28 5,842.17 2.06 94-104 105 70 UNWD BKGD-3WD 1/18/2022 5,785.14 57.44 54.51 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-3WD 4/11/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-4WD 1/18/2022 5,822.84 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4UD 4/11/2022 5,822.94 28.76 26.7 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BK-GD-4WD 4/11/2022 5,832.31 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-111-100N 1/14/2022 5,773.76 4											
BKGD-3WD 4/11/2022 5,785.30 57.28 54.35 5,842.58 2.93 55.5-70.5 71 70 WD BKGD-4UD 1/18/2022 5,822.84 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4UD 4/11/2022 5,822.94 28.76 26.7 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BKGD-4WD 4/11/2022 5,832.41 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-111-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-111-100N 1/13/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-111-100S 1/13/2022 5,797.15	BKGD-3UD		5,785.83					94-104	105		
BKGD-4UD 1/18/2022 5,822.84 28.86 26.8 5,851.70 2.06 60-75 75 30 UNWD BKGD-4UD 4/11/2022 5,822.94 28.76 26.7 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BKGD-4WD 4/11/2022 5,832.41 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-111-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-111-100N 1/13/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-111-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-111-150N 1/13/2022 5,789.84											
BKGD-4UD 4/11/2022 5,822.94 28.76 26.7 5,851.70 2.06 60-75 75 30 UNWD BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BKGD-4WD 4/11/2022 5,832.41 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-11I-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100N 4/7/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.8											
BKGD-4WD 1/18/2022 5,832.32 19.57 17.32 5,851.89 2.25 21-30 31 30 WD BKGD-4WD 4/11/2022 5,832.41 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-11I-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100N 4/7/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 4/7/2022						_					
BKGD-4WD 4/11/2022 5,832.41 19.48 17.23 5,851.89 2.25 21-30 31 30 WD BM-11I-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100N 4/7/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 4/7/2022											
BM-11I-100N 1/14/2022 5,773.76 43.42 40.42 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100N 4/7/2022 5,773.96 43.22 40.22 5,817.18 3.00 18.5-50.5 56 50.5 WD BM-11I-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022											
BM-1II-100S 1/13/2022 5,797.15 25.08 22.58 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-1II-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-100S 4/7/2022 5,796.81 25.42 22.92 5,822.23 2.50 19.2-51.2 57 51.2 WD BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-150N 1/13/2022 5,789.84 26.07 23.96 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-150N 4/7/2022 5,789.52 26.39 24.28 5,815.91 2.11 17.5-47.5 54 46.5 WD BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-200N 1/13/2022 5,790.54 24.41 21.82 5,814.95 2.59 19-44 49 44 WD BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-200N 4/7/2022 5,790.34 24.61 22.02 5,814.95 2.59 19-44 49 44 WD BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD											
BM-11I-50N 1/13/2022 5,791.99 27 24 5,818.99 3.00 17.5-47.5 53 47.5 WD			- ,								
BM-11I-50N 4/7/2022 5,791.73 27.26 24.26 5,818.99 3.00 17.5-47.5 53 47.5 WD	BM-11I-50N		5,791.99		24		3.00	17.5-47.5			
BM-11I-50S 1/13/2022 5,794.31 27.25 24.25 5,821.56 3.00 18-48 53 47.7 WD											
BM-11I-50S 4/7/2022 5,793.88 27.68 24.68 5,821.56 3.00 18-48 53 47.7 WD BM-11X-100N 1/13/2022 5,791.46 24.05 21.55 5.815.51 2.50 19-46 50 46 WD											
BM-11X-100N 1/13/2022 5,791.46 24.05 21.55 5,815.51 2.50 19-46 50 46 WD BM-11X-100N 4/7/2022 5,791.01 24.5 22 5.815.51 2.50 19-46 50 46 WD											
BM-11X-100N 4//2022 5,791.01 24.3 22 5,813.31 2.30 19-40 30 40 WD BM-11X-100S 1/13/2022 5,803.06 16.69 14.19 5,819.75 2.50 18.5-48.5 53 47.5 WD											
BM-11X-100S 4/7/2022 5,802.62 17.13 14.63 5,819.75 2.50 18.5-48.5 53 47.5 WD											

BM-IIX-I50N	WD W
Well ID Measurement (R NGVD) (R below MP) (R bgy) (R NGVD) (R bgy) (R bgy)	WD W
BM-11X-150N	WD W
BM-IIX-ISON 1/13/2022 5,790.164 23.82 21.14 5,814.46 2.41 19.5-44.5 49.5 44.5 BM-IIX-SON 1/13/2022 5,790.64 23.82 21.15 5.812.99 2.44 19.5-44.5 50.5 44.5 BM-IIX-200N 47/2022 5,790.38 22.11 19.67 5,812.99 2.44 19.5-44.5 50.5 44.5 BM-IIX-50N 1/13/2022 5,793.88 22.82 21.32 5,817.28 2.50 17-47 50 47.5 BM-IIX-50N 1/13/2022 5,793.89 23.82 21.32 5,817.28 2.50 17-47 50 47.5 BM-IIX-50N 47/2022 5,793.89 24.39 21.89 5,817.28 2.50 17-47 50 47.5 BM-IIX-50S 1/13/2022 5,801.83 17.41 14.91 5,819.24 2.50 19-46 50 44.5 BM-IIX-50S 47/2022 5,801.83 17.41 14.91 5,819.24 2.50 19-46 50 44.5 BM-ISEI 1/13/2022 5,731.94 33.21 31.63 5,764.95 1.58 20-40 45 40 45	WD W
BM-11X-150N	WD W
BM-11X-200N	WD W
BM-11X-200N	WD W
BM-11X-50N	WD W
BM-11X-50N	WD W
BM-11X-50S	WD W
BM-11X-50S	WD W
BM-15E1	WD W
BM-15E1	WD W
BM-15E2	WD
BM-15E3	WD
BM-15E3	WD WD WD WD WD WD WD
BM-15E4	WD WD WD WD WD WD WD
BM-15E4 4/7/2022 5,735.21 36.98 34.29 5,772.19 2.69 34-49 54 49 BM-15E5 1/13/2022 5,736.21 34.36 31.59 5,770.57 2.77 31.5-46.5 53 46.5 BM-15E6 1/13/2022 5,738.08 35.04 32.22 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15E6 4/7/2022 5,737.98 35.14 32.32 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15I-100S 1/14/2022 5,726.00 52.55 49.19 5,778.55 3.36 19-51 56.8 50.8 BM-15I-100S 1/14/2022 5,726.00 52.54 49.04 5,778.55 3.36 19-51 56.8 50.8 BM-15I-10SS 1/13/2022 5,739.41 39.24 37.13 5,78.65 2.11 19.5-50.5 53 49.8 BM-15I-15SS 1/13/2022 5,739.41 39.24 37.13 5,778.65 2.11 19.5-50.5 <	WD WD WD WD WD
BM-15E5	WD WD WD WD
BM-15E5 4/7/2022 5,735.58 34.99 32.22 5,770.57 2.77 31.5-46.5 53 46.5 BM-15E6 1/13/2022 5,738.08 35.04 32.22 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15E6 4/7/2022 5,737.98 35.14 32.32 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15I-100S 1/14/2022 5,726.00 52.55 49.19 5,778.55 3.36 19-51 56.8 50.8 BM-15I-100S 4/7/2022 5,726.15 52.4 49.04 5,778.55 3.36 19-51 56.8 50.8 BM-15I-12SS 1/13/2022 5,739.34 39.31 37.2 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-15SS 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 53 49.8 BM-15I-15OS 4/7/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47	WD WD WD
BM-15E6 1/13/2022 5,738.08 35.04 32.22 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15E6 4/7/2022 5,737.98 35.14 32.32 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15I-100S 1/14/2022 5,726.00 52.55 49.19 5,778.55 3.36 19-51 56.8 50.8 BM-15I-100S 4/7/2022 5,726.15 52.4 49.04 5,778.55 3.36 19-51 56.8 50.8 BM-15I-12SS 1/13/2022 5,739.34 39.31 37.2 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-15SS 4/7/2022 5,739.41 39.24 37.13 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-15OS 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-15DN 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47	WD WD
BM-15E6 4/7/2022 5,737.98 35.14 32.32 5,773.12 2.82 29.5-49.5 52.7 49.5 BM-15I-100S 1/14/2022 5,726.00 52.55 49.19 5,778.55 3.36 19-51 56.8 50.8 BM-15I-100S 4/7/2022 5,726.15 52.4 49.04 5,778.55 3.36 19-51 56.8 50.8 BM-15I-125S 1/13/2022 5,739.34 39.31 37.2 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-125S 4/7/2022 5,739.41 39.24 37.13 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-150S 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-150S 1/14/2022 5,725.24 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47	WD
BM-15I-100S	
BM-15I-100S 4/7/2022 5,726.15 52.4 49.04 5,778.55 3.36 19-51 56.8 50.8 BM-15I-125S 1/13/2022 5,739.34 39.31 37.2 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-125S 4/7/2022 5,739.41 39.24 37.13 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-150S 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-150S 4/7/2022 5,725.34 55.01 51.78 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-150S 4/7/2022 5,725.23 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-175S 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51	WD
BM-15I-125S 4/7/2022 5,739.41 39.24 37.13 5,778.65 2.11 19.5-50.5 53 49.8 BM-15I-150S 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-150S 4/7/2022 5,725.34 55.01 51.78 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-15N 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-17S 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-17SS 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 <td< td=""><td>WD</td></td<>	WD
BM-15I-150S 1/14/2022 5,725.07 55.28 52.05 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-150S 4/7/2022 5,725.34 55.01 51.78 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-15N 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-17SS 1/13/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 5	WD
BM-15I-150S 4/7/2022 5,725.34 55.01 51.78 5,780.35 3.23 20.5-50.5 55.5 50.5 BM-15I-15N 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-17SS 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-17SS 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 <td>WD</td>	WD
BM-15I-15N 1/14/2022 5,725.21 50.28 47.49 5,775.49 2.79 17-47 52 47 BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-17SS 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-17SS 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56	WD
BM-15I-15N 4/7/2022 5,725.23 50.26 47.47 5,775.49 2.79 17-47 52 47 BM-15I-175S 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-175S 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-20SS 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59	WD
BM-15I-175S 1/13/2022 5,741.29 39.38 37.52 5,780.67 1.86 19-51 55 50.8 BM-15I-175S 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-20SS 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-30S 1/14/2022 5,723.64 53.95 50.59 5,777.49 3.36 17.7-52.7 59 <td>WD WD</td>	WD WD
BM-15I-175S 4/7/2022 5,741.36 39.31 37.45 5,780.67 1.86 19-51 55 50.8 BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-37.5S 1/14/2022 5,723.03 52.65 50.27 5,775.68 2.38 24-54 59 54 BM-15I-50S 1/14/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59	WD
BM-15I-200S 1/13/2022 5,745.72 35.94 33.67 5,781.66 2.27 20-50 55.5 48.2 BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-37.5S 4/7/2022 5,723.03 52.65 50.27 5,775.68 2.38 24-54 59 54 BM-15I-50S 1/14/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-57SS 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55	WD
BM-15I-200S 4/7/2022 5,745.84 35.82 33.55 5,781.66 2.27 20-50 55.5 48.2 BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-37.5S 4/7/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-25S 1/14/2022 5,720.23 57.33 53.47 5,777.56 3.86 21-51 56 52 BM-15I-25S 4/7/2022 5,720.48 57.08 53.22 5,777.56 3.86 21-51 56 52 BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-37.5S 4/7/2022 5,723.03 52.65 50.27 5,775.68 2.38 24-54 59 54 BM-15I-50S 1/14/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-37.5S 1/13/2022 5,723.05 52.63 50.25 5,775.68 2.38 24-54 59 54 BM-15I-37.5S 4/7/2022 5,723.03 52.65 50.27 5,775.68 2.38 24-54 59 54 BM-15I-50S 1/14/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-37.5S 4/7/2022 5,723.03 52.65 50.27 5,775.68 2.38 24-54 59 54 BM-15I-50S 1/14/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-50S 1/14/2022 5,723.54 53.95 50.59 5,777.49 3.36 17.7-52.7 59 53 BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-50S 4/7/2022 5,723.67 53.82 50.46 5,777.49 3.36 17.7-52.7 59 53 BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
BM-15I-75S 1/13/2022 5,738.13 38.82 37.38 5,776.95 1.44 19-51 55 51	WD
DIVI-131-/35 1/13/2022 3,/36.13 36.62 3/.36 3,//0.93 1.44 19-31 33 31	WD WD
BM-15I-75S 4/7/2022 5,738.15 38.8 37.36 5,776.95 1.44 19-51 55 51	WD
BM-15N1 1/13/2022 5,735.99 35.09 33.21 5,771.08 1.88 22.3-52.3 60 52.3	WD
BM-15N1 4/7/2022 5,735.43 35.65 33.77 5,771.08 1.88 22.3-52.3 60 52.3	WD
BM-15N2 1/13/2022 5,737.69 31.97 29.5 5,769.66 2.47 19-39 45 39.2	WD
BM-15N2 4/7/2022 5,736.96 32.7 30.23 5,769.66 2.47 19-39 45 39.2	WD
BM-15N3 1/13/2022 5,737.68 28.9 26.5 5,766.58 2.40 19.5-39.5 45 39.5	WD
BM-15N3 4/7/2022 5,737.13 29.45 27.05 5,766.58 2.40 19.5-39.5 45 39.5	WD
BM-15N4 1/13/2022 5,735.15 30.41 27.7 5,765.56 2.71 17-37 44 37	WD
BM-15N4	WD WD
BM-15N5 1/13/2022 5,735.38 37.32 35.02 5,7/2.70 2.30 31-56 62 56 BM-15N5 4/7/2022 5,735.06 37.64 35.34 5,772.70 2.30 31-56 62 56	WD
BM-15N6 1/13/2022 5,736.73 35.86 31.27 5,772.59 4.59 16-46 51 47	WD
BM-15N6 4/7/2022 5,736.24 36.35 31.76 5,772.59 4.59 16-46 51 47	WD
BM-15NE1 1/13/2022 5,729.97 34.23 31.73 5,764.20 2.50 17.5-42.5 45 42.5	WD
BM-15NE1 4/7/2022 5,729.78 34.42 31.92 5,764.20 2.50 17.5-42.5 45 42.5	WD
BM-15NE2 1/13/2022 5,729.23 32.38 30.76 5,761.61 1.62 19-39 42.8 39	
BM-15NE2 4/7/2022 5,729.15 32.46 30.84 5,761.61 1.62 19-39 42.8 39	WD
BM-15NW1 1/13/2022 5,753.01 19.55 18.23 5,772.56 1.32 12-22 47 43.8	WD
BM-15NW1 4/7/2022 5,752.74 19.82 18.5 5,772.56 1.32 12-22 47 43.8 PM 15NW2 1/12/2022 5,752.64 20.52 17.22 5,772.17 2.30 22.22 24.5 NE >24.5	WD WD
BM-15NW2 1/13/2022 5,752.64 20.53 17.23 5,773.17 3.30 22-32 34.5 NE, >34.5 BM-15NW2 4/7/2022 5,752.31 20.86 17.56 5,773.17 3.30 22-32 34.5 NE, >34.5 NE, >34.5	WD WD WD
BM-15NW2 4//2022 5,752.51 20.86 17.56 5,775.85 2.50 18.5-52.5 55 52.6	WD WD WD
BM-15X-100S 1/13/2022 5,738.95 36.9 34.4 5,775.85 2.50 18.5-52.5 55 52.6	WD WD WD WD WD
BM-15X-125S 1/13/2022 5,739.67 37.08 34.99 5,776.75 2.09 19-50 55 49.9	WD WD WD WD WD WD WD
BM-15X-125S 4/7/2022 5,739.65 37.1 35.01 5,776.75 2.09 19-50 55 49.9	WD WD WD WD WD WD WD WD WD
BM-15X-150S 1/13/2022 5,740.36 37.28 34.78 5,777.64 2.50 20-50 54 50	WD WD WD WD WD WD WD
BM-15X-150S 4/7/2022 5,740.44 37.2 34.7 5,777.64 2.50 20-50 54 50	WD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Date of Measurement	(ft NGVD) ^{a/}	(ft below MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
BM-15X-175S	1/13/2022	5,742.30	36.65	34.56	5,778.95	2.09	19-50	53	49.9	WD
BM-15X-175S	4/7/2022	5,742.51	36.44	34.35	5,778.95	2.09	19-50	53	49.9	WD
BM-15X-200S	1/13/2022	5,743.62	36.7	34.22	5,780.32	2.48	19.5-51.5	54.5	51.5	WD
BM-15X-200S	4/7/2022	5,743.96	36.36	33.88	5,780.32	2.48	19.5-51.5	54.5	51.5	WD
BM-15X-37.5S	1/13/2022	5,735.96	38.56	35.94	5,774.52	2.62	25-55	60	55	WD
BM-15X-37.5S	4/7/2022	5,735.51	39.01	36.39	5,774.52	2.62	25-55	60	55	WD
BM-15X-50S	1/13/2022	5,737.70	36.91	34.41	5,774.61	2.50	19-51	54	51.4	WD
BM-15X-50S	4/7/2022	5,737.33	37.28	34.78	5,774.61	2.50	19-51	54	51.4	WD WD
BM-15X-75S BM-15X-75S	1/13/2022 4/7/2022	5,738.70 5,738.55	35.64 35.79	33.94 34.09	5,774.34 5,774.34	1.70	19-51 19-51	55 55	51 51	WD
BM-4I-100N	1/6/2022	5,793.17	43.22	40.47	5,836.39	2.75	34-54	60	53.7	WD
BM-4I-100N	4/8/2022	5,793.16	43.23	40.48	5,836.39	2.75	34-54	60	53.7	WD
BM-4I-100S	1/6/2022	5,793.56	43	40.64	5,836.56	2.36	34-49	55	48.6	WD
BM-4I-100S	4/8/2022	5,793.51	43.05	40.69	5,836.56	2.36	34-49	55	48.6	WD
BM-4I-10S	1/6/2022	5,793.48	42.88	40.62	5,836.36	2.26	34-54	59.5	53.5	WD
BM-4I-10S	4/8/2022	5,793.44	42.92	40.66	5,836.36	2.26	34-54	59.5	53.5	WD
BM-4I-50N	1/6/2022	5,793.47	42.5	39.8	5,835.97	2.70	32-47	52.5	46.8	WD
BM-4I-50N	4/8/2022	5,793.47	42.5	39.8	5,835.97	2.70	32-47	52.5	46.8	WD
BM-4I-50S	1/6/2022	5,793.38	43.95	40.92	5,837.33	3.03	30.5-50.5	56	50.2	WD
BM-4I-50S	4/8/2022	5,793.34	43.99	40.96	5,837.33	3.03	30.5-50.5	56	50.2	WD
BM-4X-100N	1/6/2022	5,794.00	42.09	39.37	5,836.09	2.72	31-51	54	50.6	WD
BM-4X-100N BM-4X-100S	4/8/2022 1/6/2022	5,794.11 5,793.44	41.98 43.24	39.26 41.23	5,836.09 5,836.68	2.72 2.01	31-51 34-49	54 53	50.6 48.7	WD WD
BM-4X-100S	4/8/2022	5,793.37	43.24	41.23	5,836.68	2.01	34-49	53	48.7	WD
BM-4X-10S	1/6/2022	5,793.42	43.35	40.88	5,836.77	2.47	33.5-56.5	59	56.3	WD
BM-4X-10S	4/8/2022	5,793.39	43.38	40.91	5,836.77	2.47	33.5-56.5	59	56.3	WD
BM-4X-40S	1/6/2022	5,785.76	50.91	48.54	5,836.67	2.37	68-83	87	52	UNWD
BM-4X-40S	4/8/2022	5,785.46	51.21	48.84	5,836.67	2.37	68-83	87	52	UNWD
BM-4X-50N	1/6/2022	5,793.59	42.86	40.04	5,836.45	2.82	34-49	54	49	WD
BM-4X-50N	4/8/2022	5,793.60	42.85	40.03	5,836.45	2.82	34-49	54	49	WD
BM-4X-50S	1/6/2022	5,793.81	43.31	40.69	5,837.12	2.62	32.5-52.5	55	52.5	WD
BM-4X-50S	4/8/2022	5,793.78	43.34	40.72	5,837.12	2.62	32.5-52.5	55	52.5	WD
BW-PZ-1	1/4/2022	5,692.78	31.69	29.53	5,724.47	2.16	23-33	33	33	WD
BW-PZ-1	4/4/2022	5,692.81	31.66	29.5	5,724.47	2.16	23-33	33	33	WD
BW-PZ-1LC BW-PZ-1LC	1/4/2022 4/4/2022	5,688.11 5,687.96	37.07 37.22	34.64 34.79	5,725.18 5,725.18	2.43	43-53 43-53	53 53	33 33	UNWD UNWD
C-702P1	1/19/2022	5,688.52	41.86	39.48	5,730.38	2.43	196-201	237	31.5	UPPER DENVER
C-702P1	4/12/2022	5,688.85	41.53	39.15	5,730.38	2.38	196-201	237	31.5	UPPER DENVER
C-702P3	1/19/2022	5,711.62	17.75	15.48	5,729.37	2.27	90-100	102	60	UPPER DENVER
C-702P3	4/12/2022	5,711.50	17.87	15.6	5,729.37	2.27	90-100	102	60	UPPER DENVER
C-702P4	1/19/2022	5,713.77	16.1	14.03	5,729.87	2.07	47-52	53	NE, >37	UNWD
C-702P4	4/12/2022	5,713.55	16.32	14.25	5,729.87	2.07	47-52	53	NE, >37	UNWD
C-702Q1	1/19/2022	5,677.92	53.84	51.18	5,731.76	2.66	219-229	230	35	LIGNITE
C-702Q1	4/12/2022	5,678.31	53.45	50.79	5,731.76	2.66	219-229	230	35	LIGNITE
C-702Q3	1/19/2022	5,713.09	18.05	15.81	5,731.14	2.24	30-35	36	32.5	WD
C-702Q3	4/12/2022	5,712.76	18.38	16.14	5,731.14	2.24	30-35	36	32.5	WD NO CEOLOGIC LOC
EAST CLEANOUT EAST CLEANOUT	1/19/2022 4/12/2022	5,734.53 5,734.56	32.58 32.55	NA ^{'g}	5,767.11					NO GEOLOGIC LOG
GW-101	1/13/2022	5,734.56 5,729.08	49.92	NA 48.62	5,767.11 5,779.00	1.30	 78.6-98.6	98.9	42	NO GEOLOGIC LOG UNWD
GW-101	4/7/2022	5,729.10	49.92	48.6	5,779.00	1.30	78.6-98.6	98.9	42	UNWD
GW-101-DEN	1/13/2022	5,720.58	59.96	57.46	5,780.54	2.50	134 - 148.6		50	UPPER DENVER
GW-101-DEN	4/7/2022	5,720.78	59.76	57.26	5,780.54	2.50	134 - 148.6		50	UPPER DENVER
GW-103	1/6/2022	5,739.64	58.64	49.66	5,798.28	8.98	136-155.9	157	40	UPPER DENVER
GW-103	4/8/2022	5,739.66	58.62	49.64	5,798.28	8.98	136-155.9	157	40	UPPER DENVER
GW-104	1/6/2022	5,751.76	48.8	39.14	5,800.56	9.66	44.4-69.3	69.5	36.3	UNWD
GW-104	4/8/2022	5,751.56	49	39.34	5,800.56	9.66	44.4-69.3	69.5	36.3	UNWD
GW-106	1/4/2022	5,716.08	22.76	21.32	5,738.84	1.44	24.5-49.5	50.8	43	WD
GW-106	4/4/2022	5,717.21	21.63	20.19	5,738.84	1.44	24.5-49.5	50.8	43	WD
GW-106-DEN	1/4/2022	5,711.57	27.99	25.43 25.24	5,739.56	2.56	100.6 - 125	135	43	UPPER DENVER
GW-106-DEN GW-106-LIG	4/4/2022 1/4/2022	5,711.76 5,690.90	27.8 49.88	46.9	5,739.56 5,740.78	2.56 2.98	100.6 - 125 235-250	135 258	43.4	UPPER DENVER LIGNITE
GW-106-LIG GW-106-LIG	4/4/2022	5,691.16	49.62	46.64	5,740.78	2.98	235-250	258	43.4	LIGNITE
GW-100-EIG GW-107A	1/3/2022	5,698.16	28.23	26.74	5,726.39	1.49	15-35	59	32	WD
GW-107A	4/4/2022	5,698.16	28.23	26.74	5,726.39	1.49	15-35	59	32	WD
				26.41		1.82	48.5-58.5	58.5	31.6	UNWD
GW-107UD	1/3/2022	5,699.22	28.23	20.41	5,727.45	1.02	40.5-50.5	50.5	51.0	CITTE

Well ID GW-107UDR GW-107UDR GW-108A GW-108A GW-109 GW-109 GW-112 GW-112 GW-113 GW-113 GW-114A GW-120 GW-120 GW-120 GW-121 GW-121 GW-121 GW-121 GW-121 GW-122 GW-121 GW-121 GW-122 GW-121 GW-122 GW-121 GW-121 GW-121 GW-122 GW-121 GW-121 GW-122 GW-121 GW-1	Date of Measurement 1/3/2022 4/4/2022 1/4/2022 1/4/2022 1/4/2022 1/19/2022 4/12/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	Surface Elevation (ft NGVD)a/ 5,680.94 5,683.12 5,687.29 5,687.08 Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.11 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,742.66 5,748.88 5,747.69 5,747.74 Dry	Depth to Water (ft below MP)b' 46.35 44.17 45.2 45.41 Dry Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2 34.01	Columbia	Point Elevation (ft NGVD) 5,727.29 5,727.29 5,732.49 5,707.99 5,707.99 5,769.95 5,773.86 5,732.30 5,732.30 5,732.30 5,732.30 5,732.30 5,732.30 5,732.30 5,732.30 5,784.59 5,784.59 5,784.59 5,777.57	(ft) ^{d'} 2.29 2.29 2.69 1.49 1.49 9.95 9.95 2.46 2.46 2.00 2.00 8.19 8.19 1.99 3.66 3.66 2.39 2.39	(ft bgs) 47-62 47-62 52.6-87.6 52.6-87.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 21.1-41.1	040 (ft bgs) 64.5 64.5 99 99 29 29 34.2 175.5 175.5 40 310 310 298 298 343 343 43.75	Weathering (ft bgs) 34 34 42 42 42 NE, >29 NE, >29 30.5 30.5 38 NE, >40 NE, >40 NE, >40 65 65 32 32 84 84 41.1 41.1 41.1	Formation ^{e/} UNWD UNWD UNWD UNWD ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER UPPER DENVER LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UND LIGNITE LIGNITE LIGNITE UND LIGNITE UND LIGNITE
GW-107UDR GW-107UDR GW-108A GW-108A GW-109 GW-109 GW-112 GW-113 GW-113 GW-113 GW-114A GW-120 GW-120 GW-121 GW-121 GW-121 GW-121 GW-POA-1N GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA-1NE GW-POA-1 G	Measurement 1/3/2022 4/4/2022 1/4/2022 1/4/2022 1/4/2022 1/4/2022 1/19/2022 4/12/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,680.94 5,683.12 5,687.29 5,687.08 Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.59 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	MP)b' 46.35 44.17 45.2 45.41 Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.86 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	44.06 41.88 42.51 42.72 Dry 23.98 23.9 51.88 51.63 34.55 34.55 34.55 101.69 101.29 91.87 91.29 140.62 140.25 31.18 23.85 23.8	5,727.29 5,727.29 5,732.49 5,732.49 5,707.99 5,707.99 5,709.5 5,773.86 5,773.86 5,773.80 5,732.30 5,790.99 5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,778.4.59 5,777.57	2.29 2.29 2.69 1.49 9.95 9.95 2.46 2.00 8.19 8.19 1.99 3.66 2.39 2.39	47-62 47-62 52.6-87.6 52.6-87.6 8.6-28.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 266.7-291.7 21.1-41.1	64.5 64.5 99 99 29 29 34.2 34.2 175.5 175.5 40 40 310 310 298 343 343	34 34 34 42 NE, >29 NE, >29 30.5 30.5 38 NE, >40 NE, >40 65 65 32 32 84 84 84	UNWD UNWD UNWD UNWD UNWD ALLUVIUM ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER WD WD LIGNITE UND
GW-107UDR GW-108A GW-108A GW-108A GW-109 GW-109 GW-112 GW-112 GW-113 GW-113 GW-114A GW-114A GW-120 GW-121 GW-121 GW-121 GW-121 GW-POA-1N GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA-1NE GW-POA-1 GW	1/3/2022 4/4/2022 1/4/2022 4/4/2022 1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,680.94 5,683.12 5,687.29 5,687.08 Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.59 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	44.17 45.2 45.41 Dry Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	44.06 41.88 42.51 42.72 Dry 23.98 23.9 51.88 51.63 34.55 34.55 34.55 101.69 101.29 91.87 91.29 140.62 140.25 31.18 23.85 23.8	5,727.29 5,732.49 5,732.49 5,707.99 5,707.99 5,769.95 5,773.86 5,773.86 5,732.30 5,732.30 5,790.99 5,794.69 5,825.26 5,825.26 5,844.59 5,774.57	2.29 2.29 2.69 1.49 9.95 9.95 2.46 2.00 8.19 8.19 1.99 3.66 2.39 2.39	47-62 47-62 52.6-87.6 52.6-87.6 8.6-28.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 266.7-291.7 21.1-41.1	64.5 64.5 99 99 29 29 34.2 34.2 175.5 175.5 40 40 310 310 298 343 343	34 34 34 42 NE, >29 NE, >29 30.5 30.5 38 NE, >40 NE, >40 65 65 32 32 84 84 84	UNWD UNWD UNWD UNWD ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER WD LIGNITE UND
GW-108A GW-108A GW-108A GW-109 GW-109 GW-112 GW-112 GW-113 GW-113 GW-114A GW-114A GW-120 GW-121 GW-121 GW-122 GW-122 GW-POA-1 GW-POA-1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA-1 GW-POA-	1/4/2022 4/4/2022 1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,687.29 5,687.08 Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.78 5,681.11 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,751.02 5,751.59 5,749.26 5,749.26 5,747.69 5,747.74	45.2 45.41 Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	42.51 42.72 Dry Dry 23.98 51.88 51.63 34.55 34.55 34.52 101.69 91.87 91.29 140.62 140.25 31.18 23.85 23.8	5,732.49 5,732.49 5,707.99 5,707.99 5,769.95 5,769.95 5,773.86 5,732.30 5,732.30 5,732.30 5,790.99 5,794.69 5,825.26 5,825.26 5,784.59 5,784.59 5,774.57	2.69 2.69 1.49 1.49 9.95 9.95 2.46 2.00 2.00 8.19 8.19 1.99 3.66 3.66 2.39	52.6-87.6 52.6-87.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	99 99 29 29 34.2 175.5 175.5 40 310 310 310 298 298 343 343	42 42 NE, >29 NE, >29 30.5 30.5 38 38 NE, >40 65 65 32 32 32 84 84 84	UNWD UNWD ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER UPPER DENVER UPPER DENVER LIGNITE UND
GW-108A GW-109 GW-109 GW-112 GW-112 GW-113 GW-113 GW-113 GW-114A GW-120 GW-120 GW-121 GW-122 GW-122 GW-122 GW-122 GW-POA1 GW-POA-1NE GW-POA-1NE GW-POA-1NE GW-POA-1NE GW-POA-1	4/4/2022 1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,687.08 Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69	45.41 Dry Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	42.72 Dry Dry 23.98 23.9 51.88 51.63 34.55 34.52 101.69 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,732.49 5,707.99 5,707.99 5,769.95 5,769.95 5,773.86 5,732.30 5,732.30 5,732.30 5,732.30 5,732.30 5,74.69 5,774.69 5,825.26 5,825.26 5,784.59 5,784.59 5,777.57	2.69 1.49 1.49 9.95 2.46 2.00 2.00 8.19 1.99 1.99 3.66 3.66 2.39	52.6-87.6 8.6-28.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 267.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	99 29 34.2 34.2 175.5 175.5 40 310 310 298 343 343	42 NE, >29 NE, >29 30.5 30.5 38 38 NE, >40 NE, >40 65 65 65 32 32 84 84 41.1	UNWD ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER WD LIGNITE UGNITE LIGNITE UGNITE UGNITE UGNITE UGNITE UGNITE UGNITE
GW-109 GW-109 GW-109 GW-112 GW-112 GW-113 GW-113 GW-113 GW-114A GW-120 GW-120 GW-121 GW-121 GW-121 GW-122 GW-122 GW-POA-1N GW-POA-1N GW-POA-1N GW-POA-1NE	1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/19/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 1/19/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	Dry Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.78 5,695.78 5,681.11 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	Dry Dry 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	Dry Dry 23.98 23.9 51.88 51.63 34.55 34.52 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,707.99 5,707.99 5,707.99 5,769.95 5,769.95 5,773.86 5,732.30 5,732.30 5,730.99 5,790.99 5,774.69 5,825.26 5,825.26 5,784.59 5,784.59 5,777.57	1.49 1.49 9.95 9.95 2.46 2.00 2.00 8.19 8.19 1.99 3.66 2.39 2.39	8.6-28.6 8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 312.8-332.8 311.8-332.8 21.1-41.1	29 29 34.2 34.2 175.5 175.5 40 40 310 298 298 343 343	NE, >29 NE, >29 NE, >29 30.5 30.5 38 38 NE, >40 NE, >40 65 65 32 32 84 84 41.1	ALLUVIUM ALLUVIUM WD WD UPPER DENVER UPPER DENVER WD LIGNITE UIGNITE LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE
GW-109 GW-112 GW-112 GW-113 GW-113 GW-113 GW-113 GW-114A GW-120 GW-120 GW-121 GW-121 GW-121 GW-122 GW-POA-1N GW-POA-1N GW-POA-1N GW-POA-1NE	4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/4/2022 1/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/18/2022 1/18/2022 4/6/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	Dry 5,736.02 5,736.10 5,719.52 5,719.77 5,695.78 5,695.78 5,681.11 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	Dry 33.93 33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.86 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	Dry 23.98 23.9 23.9 51.88 51.63 34.55 34.52 101.69 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,707.99 5,769.95 5,769.95 5,773.86 5,773.86 5,773.2.30 5,790.99 5,790.99 5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,778.57	1.49 9.95 9.95 2.46 2.00 2.00 8.19 8.19 1.99 3.66 2.39 2.39	8.6-28.6 9.2-29.2 9.2-29.2 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 21.1-41.1	29 34.2 34.2 175.5 175.5 40 40 310 310 298 298 343 343	NE, >29 30.5 30.5 38 38 NE, >40 NE, >40 65 65 32 32 32 84 84 41.1	ALLUVIUM WD WD UPPER DENVER UPPER DENVER WD WD LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE
GW-112 GW-113 GW-113 GW-113 GW-113 GW-114A GW-114A GW-120 GW-120 GW-121 GW-122 GW-122 GW-122 GW-POA1 GW-POA-1N GW-POA-1N GW-POA-INE	1/19/2022 4/12/2022 1/19/2022 1/19/2022 1/4/2022 1/4/2022 1/19/2022 1/19/2022 1/19/2022 1/13/2022 1/13/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,736.02 5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	33.93 33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.86 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	23.98 23.9 51.88 51.63 34.55 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,769.95 5,769.95 5,773.86 5,773.86 5,773.230 5,790.99 5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,774.59	9.95 9.95 2.46 2.46 2.00 2.00 8.19 1.99 3.66 3.66 2.39 2.39	9.2-29.2 9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	34.2 34.2 175.5 175.5 40 40 310 310 298 298 343 343	30.5 30.5 38 38 NE, >40 NE, >40 65 65 32 32 32 84 84	WD WD UPPER DENVER UPPER DENVER WD UD UPER UD WD UD LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE
GW-112 GW-113 GW-113 GW-114A GW-114A GW-120 GW-120 GW-121 GW-121 GW-122 GW-122 GW-122 GW-POA-1 GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA-1NE GW-POA-1 MNA-01 MNA-01 MNA-01 MNA-02 MNA-03	4/12/2022 1/19/2022 4/12/2022 1/4/2022 1/4/2022 1/4/2022 1/19/2022 4/12/2022 1/13/2022 1/13/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,736.10 5,719.52 5,719.77 5,695.75 5,695.78 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,751.02 5,751.54 5,751.59 5,749.26 5,749.26 5,747.69 5,747.74	33.85 54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82	23.9 51.88 51.63 34.55 34.55 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,769.95 5,773.86 5,773.86 5,732.30 5,790.99 5,790.99 5,774.69 5,825.26 5,825.26 5,784.59 5,774.59	9.95 2.46 2.46 2.00 2.00 8.19 8.19 1.99 3.66 3.66 2.39 2.39	9.2-29.2 149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 287.8-297.8 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	34.2 175.5 175.5 40 40 310 310 298 298 343 343	30.5 38 38 NE, >40 NE, >40 65 65 32 32 32 84 84	WD UPPER DENVER UPPER DENVER WD WD LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE
GW-113 GW-114A GW-114A GW-114A GW-120 GW-120 GW-121 GW-122 GW-122 GW-122 GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1	1/19/2022 4/12/2022 1/4/2022 1/4/2022 4/4/2022 1/19/2022 1/19/2022 1/19/2022 1/13/2022 1/13/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,719.52 5,719.77 5,695.75 5,695.78 5,681.11 5,680.83 5,681.41 5,680.98 5,681.35 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	54.34 54.09 36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	51.88 51.63 34.55 34.52 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,773.86 5,773.86 5,732.30 5,732.30 5,790.99 5,790.99 5,774.69 5,825.26 5,825.26 5,784.59 5,784.59 5,777.57	2.46 2.46 2.00 2.00 8.19 8.19 1.99 1.99 3.66 3.66 2.39 2.39	149.8-174.8 149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 287.8-297.8 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	175.5 175.5 40 40 310 310 298 298 343 343	38 38 NE, >40 NE, >40 65 65 32 32 32 84 84 41.1	UPPER DENVER UPPER DENVER WD WD LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE
GW-113 GW-114A GW-114A GW-114A GW-120 GW-120 GW-121 GW-121 GW-122 GW-POA1 GW-POA-1N GW-POA-1NE GW-P	4/12/2022 1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 1/13/2022 1/13/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,719.77 5,695.75 5,695.78 5,681.51 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	54.09 36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	51.63 34.55 34.52 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,773.86 5,732.30 5,732.30 5,732.30 5,790.99 5,790.99 5,774.69 5,825.26 5,825.26 5,825.26 5,824.59 5,784.59 5,774.57	2.46 2.00 2.00 8.19 8.19 1.99 1.99 3.66 3.66 2.39 2.39	149.8-174.8 29.5-39.5 29.5-39.5 287.8-297.8 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	175.5 40 40 310 310 298 298 343 343	38 NE, >40 NE, >40 65 65 32 32 32 84 84	UPPER DENVER WD WD LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE UIGNITE WD
GW-114A GW-120 GW-120 GW-120 GW-121 GW-121 GW-122 GW-122 GW-POA-1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA-3 GW-POA-4 MNA-01 MNA-01 MNA-01 MNA-02 MNA-03	1/4/2022 4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/13/2022 4/7/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,695.75 5,695.78 5,681.11 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	36.55 36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	34.55 34.52 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,732.30 5,732.30 5,790.99 5,790.99 5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,777.57	2.00 2.00 8.19 8.19 1.99 1.99 3.66 3.66 2.39 2.39	29.5-39.5 29.5-39.5 287.8-297.8 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	40 40 310 310 298 298 343 343	NE, >40 NE, >40 65 65 32 32 84 84 41.1	WD WD LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE WD
GW-114A GW-120 GW-120 GW-121 GW-121 GW-122 GW-122 GW-POA1 GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03	4/4/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022 1/13/2022 1/13/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,695.78 5,681.11 5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,747.69 5,747.74	36.52 109.88 109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	34.52 101.69 101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,732.30 5,790.99 5,790.99 5,774.69 5,825.26 5,825.26 5,784.59 5,777.57	2.00 8.19 8.19 1.99 1.99 3.66 3.66 2.39 2.39	29.5-39.5 287.8-297.8 287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	310 310 298 298 343 343	NE, >40 65 65 32 32 84 84 41.1	LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UGNITE
GW-120 GW-121 GW-121 GW-122 GW-122 GW-122 GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03	4/12/2022 1/19/2022 4/12/2022 1/13/2022 4/7/2022 1/18/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022	5,681.51 5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	109.48 93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	101.29 91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,790.99 5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,784.59 5,777.57	8.19 1.99 1.99 3.66 3.66 2.39 2.39	287.8-297.8 266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	310 298 298 343 343	65 32 32 84 84 41.1	LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE UGNITE WD
GW-121 GW-122 GW-122 GW-122 GW-POA1 GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/19/2022 4/12/2022 1/13/2022 4/7/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022 4/12/2022	5,680.83 5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	93.86 93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	91.87 91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,774.69 5,774.69 5,825.26 5,825.26 5,784.59 5,777.57	1.99 1.99 3.66 3.66 2.39 2.39	266.7-291.7 266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	298 298 343 343	32 32 84 84 41.1	LIGNITE LIGNITE LIGNITE LIGNITE LIGNITE WD
GW-121 GW-122 GW-122 GW-POA1 GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA3 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	4/12/2022 1/13/2022 4/7/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/18/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022 1/19/2022	5,681.41 5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	93.28 144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	91.29 140.62 140.25 31.23 31.18 23.85 23.8	5,774.69 5,825.26 5,825.26 5,784.59 5,777.57	1.99 3.66 3.66 2.39 2.39	266.7-291.7 312.8-332.8 312.8-332.8 21.1-41.1	298 343 343	32 84 84 41.1	LIGNITE LIGNITE LIGNITE WD
GW-122 GW-122 GW-POA1 GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/13/2022 4/7/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022 4/12/2022	5,680.98 5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	144.28 143.91 33.62 33.57 26.03 25.98 23.82 24.2	140.62 140.25 31.23 31.18 23.85 23.8	5,825.26 5,825.26 5,784.59 5,784.59 5,777.57	3.66 3.66 2.39 2.39	312.8-332.8 312.8-332.8 21.1-41.1	343 343	84 84 41.1	LIGNITE LIGNITE WD
GW-122 GW-POA1 GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	4/7/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022 4/12/2022	5,681.35 5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	143.91 33.62 33.57 26.03 25.98 23.82 24.2	140.25 31.23 31.18 23.85 23.8	5,825.26 5,784.59 5,784.59 5,777.57	3.66 2.39 2.39	312.8-332.8 21.1-41.1	343	84 41.1	LIGNITE WD
GW-POA1 GW-POA-1N GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022	5,750.97 5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	33.62 33.57 26.03 25.98 23.82 24.2	31.23 31.18 23.85 23.8	5,784.59 5,784.59 5,777.57	2.39 2.39	21.1-41.1		41.1	WD
GW-POA1 GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03	4/6/2022 1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022 4/12/2022	5,751.02 5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	33.57 26.03 25.98 23.82 24.2	31.18 23.85 23.8	5,784.59 5,777.57	2.39		43.75		
GW-POA-1N GW-POA-1N GW-POA-1NE GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/18/2022 4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 4/12/2022 4/12/2022	5,751.54 5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	26.03 25.98 23.82 24.2	23.85 23.8	5,777.57			12.75		
GW-POA-1N GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-02	4/6/2022 1/18/2022 4/6/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022	5,751.59 5,749.26 5,748.88 5,747.69 5,747.74	25.98 23.82 24.2	23.8			21.1-41.1	43.75		WD
GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/18/2022 4/6/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022	5,749.26 5,748.88 5,747.69 5,747.74	23.82 24.2		3,111.31	2.18	19.5-32 19.5-32	35 35	32.5 32.5	WD WD
GW-POA-1NE GW-POA2 GW-POA2 GW-POA3 GW-POA3 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-02 MNA-03	4/6/2022 1/19/2022 4/12/2022 1/19/2022 4/12/2022	5,748.88 5,747.69 5,747.74	24.2	21.10	5,773.08	2.18	17-32	34.5	32.6	WD
GW-POA2 GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-02 MNA-02 MNA-02 MNA-03	1/19/2022 4/12/2022 1/19/2022 4/12/2022	5,747.69 5,747.74		21.56	5,773.08	2.08	17-32	34.5	32.6	WD
GW-POA2 GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	4/12/2022 1/19/2022 4/12/2022	5,747.74		32.01	5,781.70	2.00	17.3-37.3	40.7	37.3	WD
GW-POA3 GW-POA3 GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/19/2022 4/12/2022		33.96	31.96	5,781.70	2.00	17.3-37.3	40.7	37.3	WD
GW-POA4 GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03		DIY	Dry	Dry	5,752.77	2.77	14.7-29.7	33	29.7	WD
GW-POA4 MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	1/19/2022	Dry	Dry	Dry	5,752.77	2.77	14.7-29.7	33	29.7	WD
MNA-01 MNA-01 MNA-02 MNA-02 MNA-03 MNA-03		5,715.91	26.63	23.89	5,742.54	2.74	13.2-38.2	41.2	38.2	WD
MNA-01 MNA-02 MNA-02 MNA-03 MNA-03	4/12/2022	5,715.82	26.72	23.98	5,742.54	2.74	13.2-38.2	41.2	38.2	WD
MNA-02 MNA-02 MNA-03 MNA-03	1/19/2022	5,737.75	23.9	21.15	5,761.65	2.75	15-35	37	33	WD
MNA-02 MNA-03 MNA-03	4/12/2022	5,737.62	24.03	21.28	5,761.65	2.75	15-35	37	33	WD
MNA-03 MNA-03	1/19/2022	5,739.37	19.96	17.43	5,759.33	2.53	12-32	34	32	WD
MNA-03	4/12/2022	5,739.03	20.3	17.77	5,759.33	2.53	12-32	34	32	WD
	1/19/2022 4/12/2022	5,739.39 5,739.19	18.64 18.84	15.91 16.11	5,758.03 5,758.03	2.73	10-35 10-35	37 37	35 35	WD WD
MNA-04	1/19/2022	5,739.19	17.5	14.77	5,756.63	2.73	14-34	39	34	WD
MNA-04	4/12/2022	5,738.93	17.7	14.97	5,756.63	2.73	14-34	39	34	WD
MNA-05	1/19/2022	5,738.25	16.43	14.15	5,754.68	2.28	9-34	37	34	WD
MNA-05	4/12/2022	5,738.08	16.6	14.32	5,754.68	2.28	9-34	37	34	WD
MNA-06	1/19/2022	5,743.00	22.39	19.7	5,765.39	2.69	13-28	30	28	WD
MNA-06	4/12/2022	5,742.39	23	20.31	5,765.39	2.69	13-28	30	28	WD
MNA-07	1/19/2022	5,743.06	22	19.54	5,765.06	2.46	17-37	39	37	WD
MNA-07	4/12/2022	5,742.98	22.08	19.62	5,765.06	2.46	17-37	39	37	WD
MNA-08	1/19/2022	5,722.06	17.59	15.24	5,739.65	2.35	12-32	34	32	WD
MNA-08	4/12/2022	5,721.95	17.7	15.35	5,739.65	2.35	12-32	34	32	WD
MNA-09	1/19/2022	5,716.76	16.68	13.84	5,733.44	2.84	8.5-38.5	41.5	38.5	WD
MNA-09 MNA-10	4/12/2022 1/19/2022	5,716.78 5,713.02	16.66 14.93	13.82 12.18	5,733.44 5,727.95	2.84	8.5-38.5 9-34	41.5 39	38.5 34	WD WD
MNA-10 MNA-10	4/12/2022	5,712.90	15.05	12.18	5,727.95	2.75	9-34	39	34	WD
MNA-10 MNA-11	1/19/2022	5,706.69	18.03	15.01	5,724.72	3.02	9.5-29.5	33	29.5	WD
MNA-11	4/12/2022	5,706.59	18.13	15.11	5,724.72	3.02	9.5-29.5	33	29.5	WD
MNA-12	1/19/2022	5,704.20	15.69	13.1	5,719.89	2.59	8.5-28.5	31	28.5	WD
MNA-12	4/12/2022	5,704.10	15.79	13.2	5,719.89	2.59	8.5-28.5	31	28.5	WD
MNA-13	1/19/2022	5,698.57	18.44	16.33	5,717.01	2.11	10-25	29	25	WD
MNA-13	4/12/2022	5,698.48	18.53	16.42	5,717.01	2.11	10-25	29	25	WD
MPZ-1	1/19/2022	Dry	Dry	Dry	5,722.55	2.08	3.2-13.2	13.5	NE, >13.5	ALLUVIUM
MPZ-1	4/12/2022	Dry	Dry	Dry	5,722.55	2.08	3.2-13.2	13.5	NE, >13.5	ALLUVIUM
MPZ-10R	1/19/2022	5,729.31	33.34	32.29	5,762.65	1.05	16.8-36.8	37	NE,>	FILL
MPZ-10R	4/12/2022	5,728.27	34.38	33.33	5,762.65	1.05	16.8-36.8	37	NE,>	FILL
MPZ-11	1/19/2022	5,734.31 5,734.33	32.12	28.34	5,766.43	3.78	11-36	36	NE NE	FILL FILL
MPZ-11 MPZ-12	4/12/2022 1/19/2022	5,739.04	32.1 24.05	28.32 21.26	5,766.43 5,763.09	3.78 2.79	11-36 7-32	36 35	NE, >35	ALLUVIUM
MPZ-12 MPZ-12		5,738.77	24.03	21.53	5,763.09	2.79	7-32	35	NE, >35	ALLUVIUM
MPZ-13	4/17/70177	5,739.35	24.32	21.75	5,763.35	2.79	7.3-32.3	35	NE, >35	WD
MPZ-13	4/12/2022 1/19/2022	5,738.95	24.4	22.15	5,763.35	2.25	7.3-32.3	35	NE, >35	WD

Well D			Water-	Measured	OWKILA	NDFILL SUP Measuring	EKFUND	SILE			
Well Dots of Macarament M					Denth to			Screened	Total	Rase of	
Well D Wesserment (R NCVD)					-		Stickup				
Well D		D-4f	Lievation		water	Elevation	энскир	intervar	Бери	weathering	
MPIZ-2	W/ II ID		(C. NCVD) a/	`	(6.1.)\$/	(C. NICKID)	(e)d/	(6(1))	(6(1))	(6(1))	F e/
MPP-2						. ,	· /				
MPR2-3											
MPZ-3											
MPF-4											
MPZ-4											
MPZ-5											
MPZ-6					,						
MPZ-6										,	
MPP-6			_								
MPP-7											
MP/E7											
MPZ-8					,						
MPZ-8											
MPZ-9											
MW-10											
MW-I											
MW-100					,						
MW-1000			-			,					
MW-1000											
MW:1000LC											
MWI00-WD						,					
MW100-WD											
MWI01-WD	MW100-WD										WD
MWI01-WD	MW100-WD	4/5/2022	5,700.81	26.76	24.19	5,727.57	2.57	30-35	38.5	35	WD
MWI02-WD	MW101-WD	1/3/2022	5,697.68	24.01	21.62	5,721.69	2.39	22.5-32.5	34	32	WD
MWI02-WD	MW101-WD	4/5/2022	5,697.79	23.9	21.51	5,721.69	2.39	22.5-32.5	34	32	WD
MW103-WD	MW102-WD	1/3/2022	5,695.78	27.37	25.02	5,723.15	2.35	24-36	38.5	36	WD
MW 103-WD	MW102-WD	4/5/2022	5,695.84	27.31	24.96	5,723.15	2.35	24-36	38.5	36	WD
MW104-WD	MW103-WD	1/3/2022	5,693.02	26.46	24.03	5,719.48	2.43	21.7 - 36.7	39	37	WD
MWI04-WD	MW103-WD	4/5/2022	5,693.12		23.93	5,719.48	2.43	21.7 - 36.7	39	37	
MWI05-WD	MW104-WD	1/3/2022	5,686.67	22.43	19.2		3.23	13.7 - 33.7	36	33.7	WD
MW105-WD			-								
MW106-UD 1/13/2022 5,751.00 35.28 32.55 5,786.28 2.73 41-51 54 36 UNWD MW106-UD 47/2022 5,750.86 35.42 32.69 5,786.28 2.73 41-51 54 36 UNWD MW107-UD 1/13/2022 5,751.95 53.8 51.6 5,805.75 2.20 61.9-76.9 79.3 47 UNWD MW107-UD 4/7/2022 5,751.94 53.81 51.61 5,805.75 2.20 61.9-76.9 79.3 47 UNWD MW107-WD 1/13/2022 5,764.13 38.81 51.61 5,805.95 2.41 36-46 48.5 45 WD MW108-WD 4/72022 5,764.93 41.02 38.61 5,805.95 2.41 36-46 48.5 45 WD MW109-WD 1/62022 5,805.92 2.03 17.78 5,826.22 2.52 30-45 50 47.5 WD MW110-WD 1/62022 5,782.51 47.82											
MW106-UD											
MWI07-UD											
MW107-UD			-			,					
MW107-WD											
MWI07-WD			-								
MW108-WD 1/6/2022 5,806.81 19.41 16.89 5,826.22 2.52 30 - 45 50 47.5 WD MW108-WD 4/8/2022 5,805.92 20.3 17.78 5,826.22 2.52 30 - 45 50 47.5 WD MW109-WD 1/6/2022 5,793.92 40.35 38.63 5,834.27 1.72 36 - 51 54 50.8 WD MW109-WD 1/6/2022 5,793.92 40.35 38.63 5,834.27 1.72 36 - 51 54 50.8 WD MW110-WD 1/6/2022 5,782.51 47.82 45.3 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW111-UD 1/6/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,766.79 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,766.79											
MW108-WD 4/8/2022 5,805.92 20.3 17.78 5,826.22 2.52 30 - 45 50 47.5 WD MW109-WD 1/6/2022 5,793.87 40.4 38.68 5,834.27 1.72 36 - 51 54 50.8 WD MW109-WD 4/8/2022 5,793.92 40.35 38.63 5,834.27 1.72 36 - 51 54 50.8 WD MW110-WD 1/6/2022 5,782.31 47.82 45.3 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW110-WD 4/8/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW111-UD 1/6/2022 5,766.69 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5											
MWI09-WD											
MW109-WD 4/8/2022 5,793.92 40.35 38.63 5,834.27 1.72 36 - 51 54 50.8 WD MW110-WD 1/6/2022 5,782.33 48 45.3 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW111-UD 1/6/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW111-UD 4/8/2022 5,766.69 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,766.79 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 -204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5											
MW110-WD 1/6/2022 5,782.51 47.82 45.3 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW110-WD 4/8/2022 5,782.33 48 45.48 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW111-UD 1/6/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,766.79 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 4/8/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/20						,					
MW110-WD 4/8/2022 5,782.33 48 45.48 5,830.33 2.52 41.5 - 56.5 58.8 56.5 WD MW111-UD 1/6/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW111-UD 4/8/2022 5,766.79 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/202											
MW111-UD 1/6/2022 5,766.69 50.12 47.91 5,816.81 2.21 69 - 74 79.5 61 UNWD MW111-UD 4/8/2022 5,766.69 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 </td <td></td>											
MW111-UD 4/8/2022 5,766.79 50.02 47.81 5,816.81 2.21 69 - 74 79.5 61 UNWD MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-UD 4/8/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 1/4/2022 <td></td>											
MW112-DEN 1/6/2022 5,737.86 105.15 102.66 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-UD 4/8/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 1/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022											
MW112-DEN 4/8/2022 5,737.90 105.11 102.62 5,843.01 2.49 174.6 - 204 209 50 UPPER DENVER MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-UD 4/8/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW112-WD 4/8/2022 5,805.79 36.8 34.28 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 1/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-UD 1/4/2022 5,6											
MW112-UD 1/6/2022 5,791.78 50.57 48.02 5,842.35 2.55 60 - 75 79 49 UNWD MW112-UD 4/8/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW112-WD 4/8/2022 5,805.79 36.8 34.28 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 1/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69											
MW112-UD 4/8/2022 5,791.54 50.81 48.26 5,842.35 2.55 60 - 75 79 49 UNWD MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW112-WD 4/8/2022 5,805.79 36.8 34.28 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 4/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,631.69			-			,					
MW112-WD 1/6/2022 5,806.49 36.1 33.58 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW112-WD 4/8/2022 5,805.79 36.8 34.28 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 4/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-LD 1/4/2022 5,674.85 37.29 34.94 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 </td <td></td>											
MW112-WD 4/8/2022 5,805.79 36.8 34.28 5,842.59 2.52 28.5 - 48.5 51 48.5 WD MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 4/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-LD 4/4/2022 5,675.06 37.29 34.94 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43											
MW113-EW-1 1/4/2022 5,659.81 51.46 50.49 5,711.27 0.97 20-50 55.3 46 WD MW113-EW-1 4/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-LD 4/4/2022 5,675.06 37.29 34.94 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 1/4/2022 5,663.36						,					
MW113-EW-1 4/4/2022 5,659.69 51.58 50.61 5,711.27 0.97 20-50 55.3 46 WD MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-LD 4/4/2022 5,675.06 37.29 34.94 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77											
MW113-LD 1/4/2022 5,674.85 37.5 35.15 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-LD 4/4/2022 5,675.06 37.29 34.94 5,712.35 2.35 77.2-97.2 100 35.1 UNWD MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 1/3/2022 5,688.90 <t< td=""><td></td><td>4/4/2022</td><td></td><td></td><td>50.61</td><td></td><td>0.97</td><td>20-50</td><td>55.3</td><td>46</td><td>WD</td></t<>		4/4/2022			50.61		0.97	20-50	55.3	46	WD
MW113-UD 1/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.656.6 24 UNWD	MW113-LD	1/4/2022	5,674.85	37.5	35.15	5,712.35	2.35	77.2-97.2	100	35.1	UNWD
MW113-UD 4/4/2022 5,631.69 80.59 78.31 5,712.28 2.28 59-79 84 51.7 UNWD MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD	MW113-LD	4/4/2022	5,675.06	37.29	34.94	5,712.35	2.35	77.2-97.2	100	35.1	UNWD
MW113-WD 1/4/2022 5,663.43 50.01 46.47 5,713.44 3.54 20-50 55 51.7 WD MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD	MW113-UD	1/4/2022	5,631.69	80.59	78.31		2.28	59-79	84	51.7	UNWD
MW113-WD 4/4/2022 5,663.36 50.08 46.54 5,713.44 3.54 20-50 55 51.7 WD MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD			5,631.69			,	2.28	59-79			
MW114-WD 1/3/2022 5,688.77 24.57 21.73 5,713.34 3.00 22-32 38 32 WD MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD	MW113-WD	1/4/2022	5,663.43	50.01	46.47		3.54	20-50		51.7	
MW114-WD 4/5/2022 5,688.90 24.44 21.6 5,713.34 3.00 22-32 38 32 WD MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD	MW113-WD		5,663.36			5,713.44	3.54				
MW115-UD 1/3/2022 5,687.30 15.05 12.52 5,702.35 2.53 46.6-56.6 24 UNWD			5,688.77	24.57		5,713.34	3.00				
									38		
MW115-UD 4/5/2022 5,687.47 14.88 12.35 5,702.35 2.53 46.6-56.6 24 UNWD											
	MW115-UD	4/5/2022	5,687.47	14.88	12.35	5,702.35	2.53	46.6-56.6		24	UNWD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
	Date of	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW115-WD	1/3/2022	5,687.21	21.16	13.82	5,708.37	2.25	11.3-26.3	30	26.3	WD
MW115-WD MW116-WD	4/5/2022 1/3/2022	5,687.37	21 27.04	13.66 24.39	5,708.37 5,714.47	2.25	11.3-26.3 24.9-39.9	30 45	26.3 39.9	WD WD
MW116-WD MW116-WD	4/5/2022	5,687.43 5,687.62	26.85	24.39	5,714.47	2.65	24.9-39.9	45	39.9	WD
MW117-WD	1/3/2022	5,685.87	14.45	12.03	5,700.32	2.42	10.5-30.5	33	30.5	WD
MW117-WD	4/5/2022	5,686.11	14.21	11.79	5,700.32	2.42	10.5-30.5	33	30.5	WD
MW118-UD	1/3/2022	5,687.38	17.78	15.22	5,705.16	2.56	62-77	80	34.9	UNWD
MW118-UD	4/5/2022	5,687.62	17.54	14.98	5,705.16	2.56	62-77	80	34.9	UNWD
MW118-WD MW118-WD	1/3/2022 4/5/2022	5,685.05 5,685.32	20.29	17.69 17.42	5,705.34 5,705.34	2.60	20.1-35.1	37.5 37.5	35.1 35.1	WD WD
MW119-WD	1/3/2022	5,688.05	16.18	14.35	5,704.23	1.83	18-28	31.5	29	WD
MW119-WD	4/5/2022	5,688.21	16.02	14.19	5,704.23	1.83	18-28	31.5	29	WD
MW120-WD	1/3/2022	5,686.93	15.24	12.97	5,702.17	2.27	18-28	32	30	WD
MW120-WD	4/5/2022	5,687.12	15.05	12.78	5,702.17	2.27	18-28	32	30	WD
MW121-WDR	1/5/2022	5,651.13	24.29	21.77	5,675.42	2.52	23.5-33.5	36	36.5	WD
MW121-WDR	4/11/2022	5,651.99	23.43	20.91	5,675.42	2.52	23.5-33.5	36	36.5	WD
MW122-WDR MW122-WDR	1/5/2022 4/11/2022	5,651.22 5,652.22	21.41 20.41	18.78 17.78	5,672.63 5,672.63	2.63	20.5-30.5 20.5-30.5	36 36	33 33	WD WD
MW123-WDR	1/5/2022	5,651.48	20.41	17.78	5,672.04	2.74	22-32	36	33	WD
MW123-WD	4/11/2022	5,652.70	19.34	16.6	5,672.04	2.74	22-32	36	33	WD
MW124-WD	1/5/2022	5,651.74	20.29	18.06	5,672.03	2.23	23-33	39	34.5	WD
MW124-WD	4/11/2022	5,653.25	18.78	16.55	5,672.03	2.23	23-33	39	34.5	WD
MW125-WD	1/5/2022	5,652.51	20.39	17.19	5,672.90	3.20	22-32	37	36	WD
MW125-WD	4/11/2022	5,654.41	18.49	15.29	5,672.90	3.20	22-32	37	36	WD WD
MW126-WD MW126-WD	1/5/2022 4/11/2022	5,653.20 5,655.13	19.95 18.02	17 15.07	5,673.15 5,673.15	2.95 2.95	20-30 20-30	34 34	33	WD
MW127-WD	1/5/2022	5,653.73	18.63	16.27	5,672.36	2.36	20-30	34	32.5	WD
MW127-WD	4/11/2022	5,655.64	16.72	14.36	5,672.36	2.36	20-30	34	32.5	WD
MW129-WD	1/5/2022	5,649.24	21.87	19.56	5,671.11	2.31	20.8-30.5	34	31	WD
MW129-WD	4/11/2022	5,649.52	21.59	19.28	5,671.11	2.31	20.8-30.5	34	31	WD
MW130-WD	1/5/2022	5,649.23	23.8	21.57	5,673.03	2.23	21.3-31	37.5	32.4	WD WD
MW130-WD MW131-WD	4/11/2022 1/5/2022	5,649.23 5,649.56	23.8 26.69	21.57 24.74	5,673.03 5,676.25	2.23 1.95	21.3-31 23.3-33	37.5 36	32.4 34.3	WD
MW131-WD	4/11/2022	5,649.24	27.01	25.06	5,676.25	1.95	23.3-33	36	34.3	WD
MW132-WD	1/5/2022	5,674.55	4.09	1.75	5,678.64	2.34	4-14	24	21.5	WD
MW132-WD	4/11/2022	5,674.69	3.95	1.61	5,678.64	2.34	4-14	24	21.5	WD
MW133-WD	1/5/2022	5,635.71	12.89	12.79	5,648.60	0.10	14-24	27	24.5	WD
MW133-WD	4/11/2022	5,635.62	12.98	12.88	5,648.60	0.10	14-24	27	24.5	WD
MW134-WD MW135-WD	1/5/2022 1/5/2022	5,637.26 5,638.52	19.31 19.51	16.84 19.93	5,656.57 5,658.03	2.47 -0.42	15-30 18-38	33 41.5	30.5 39	WD WD
MW136-WD	1/5/2022	5,638.13	21.17	21.57	5,659.30	-0.42	21-46	49	46.5	WD
MW137-WD	1/5/2022	5,637.80	17.08	17.46	5,654.88	-0.38	21-41	44	39.5	WD
MW138-WD	1/5/2022	5,637.48	16.32	16.62	5,653.80	-0.30	19-39	43	39.5	WD
MW139-WD	1/5/2022	5,637.66	12.04	12.24	5,649.70	-0.20	17-37	44	39.8	WD
MW140-WD	1/5/2022	5,606.99	18.58	18.91	5,625.57	-0.33	21-36	44	42.5	WD LINIWE A THERED DENIVER
MW141-UDEN MW141-UDEN	1/5/2022 4/11/2022	5,604.45 5,604.90	19.07 18.62	19.53 19.08	5,623.52 5,623.52	-0.46 -0.46	57-77 57-77	79 79	37.5 37.5	UNWEATHERED DENVER UNWEATHERED DENVER
MW141-UDEN MW141-WD	1/5/2022	5,606.78	17.95	18.22	5,624.73	-0.46	21-31	44	42	WD WEATHERED DENVER
MW142-WD	1/5/2022	5,589.66	8.94	9.34	5,598.60	-0.40	10-20	34	33.5	WD
MW144-WD	1/5/2022	5,567.87	14.5	14.67	5,582.37	-0.17	16.5-31.5	36	35.5	WD
MW145-WD	1/5/2022	5,567.90	11.94	12.21	5,579.84	-0.27	13-38	40.9	38	WD
MW151-WD	1/5/2022	5,659.55	19.95	17.45	5,679.50	2.50	17-27	39	36.6	WD
MW151-WD MW153-EW-1	4/11/2022 1/5/2022	5,662.42 5,659.64	17.08 14.75	14.58 12.56	5,679.50 5,674.39	2.50	17-27 13-23	39 29.5	36.6 28.7	WD WD
MW153-EW-1 MW153-EW-1	4/11/2022	5,662.91	11.48	9.29	5,674.39	2.19	13-23	29.5	28.7	WD
MW153-WD	1/5/2022	5,659.75	13.48	11.05	5,673.23	2.43	10-20	32	29.7	WD
MW153-WD	4/11/2022	5,663.01	10.22	7.79	5,673.23	2.43	10-20	32	29.7	WD
MW154-EW-1	1/5/2022	5,659.96	14.51	12.34	5,674.47	2.17	11.5-21.5	28		WD
MW154-EW-1	4/11/2022	5,663.27	11.2	9.03	5,674.47	2.17	11.5-21.5	28		WD
MW154-WD MW154-WD	1/5/2022 4/11/2022	5,659.99 5,663.31	13.72	11.51 8.19	5,673.71 5,673.71	2.21	7-22 7-22	32 32	28.5 28.5	WD WD
MW154-WD MW155-EW-1	1/5/2022	5,660.00	14.32	11.9	5,674.32	2.42	9.5-19.5	25	28.5	WD
MW155-EW-1	4/11/2022	5,663.37	10.95	8.53	5,674.32	2.42	9.5-19.5	25		WD
MW155-WD	1/5/2022	5,659.79	14.65	11.11	5,674.44	3.54	9-19	34	32.3	WD
MW155-WD	4/11/2022	5,663.32	11.12	7.58	5,674.44	3.54	9-19	34	32.3	WD
MW156-EW-1	1/5/2022	5,659.73	13.62	11.17	5,673.35	2.45	11-21	29		WD

		Water-	Measured		Measuring					
		Surface	Depth to	Depth to	Point		Screened	Total	Base of	
	D-46	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Date of Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW156-EW-1	4/11/2022	5,663.32	10.03	7.58	5,673.35	2.45	11-21	29		WD
MW156-WD	1/5/2022	5,659.22	13.58	11.18	5,672.80	2.40	14-24	34	33	WD
MW156-WD	4/11/2022	5,663.00	9.8	7.4	5,672.80	2.40	14-24	34	33	WD
MW157-WD	1/5/2022	5,658.59	13.99	11.71	5,672.58	2.28	14-24	33.3	31.5	WD
MW157-WD	4/11/2022	5,662.31	10.27	7.99	5,672.58	2.28	14-24	33.3	31.5	WD
MW158-WD MW158-WD	1/5/2022	5,657.94	15.32	13.06	5,673.26	2.26	15-25	39	34	WD
MW158-WD MW160-WD	4/11/2022 1/5/2022	5,660.88 5,654.32	12.38 36.15	10.12 31.98	5,673.26 5,690.47	2.26 4.17	15-25 15-30	39 36	34 31	WD WD
MW160-WD	4/11/2022	5,654.33	36.14	31.97	5,690.47	4.17	15-30	36	31	WD
MW170-EW-1	1/3/2022	Dry	Dry	Dry	5,731.80	1.62	25-60	65	60	WD
MW170-EW-1	4/5/2022	5,676.38	55.42	53.8	5,731.80	1.62	25-60	65	60	WD
MW170-WD	1/3/2022	5,687.90	42.01	42.11	5,729.91	-0.10	20-55	58	55.5	WD
MW170-WD	4/5/2022	5,687.27	42.64	42.74	5,729.91	-0.10	20-55	58	55.5	WD
MW171-WD	1/3/2022	5,699.87	30.81	28.41	5,730.68	2.40	17.5-32.5	35	32.5	WD
MW171-WD MW172-WD	4/5/2022 1/3/2022	5,700.20 5,699.78	30.48 30.71	28.08 28.59	5,730.68 5,730.49	2.40	17.5-32.5 18-38	35 43	32.5 38	WD WD
MW172-WD MW172-WD	4/5/2022	5,699.86	30.63	28.51	5,730.49	2.12	18-38	43	38	WD
MW173-WD	1/3/2022	5,701.21	29.58	27.33	5,730.79	2.12	18-33	38	35.5	WD
MW173-WD	4/5/2022	5,701.29	29.5	27.25	5,730.79	2.25	18-33	38	35.5	WD
MW174-WD	1/3/2022	5,701.77	31.78	29.11	5,733.55	2.67	20.7-35.7	38	36	WD
MW174-WD	4/5/2022	5,701.87	31.68	29.01	5,733.55	2.67	20.7-35.7	38	36	WD
MW175-WD	1/3/2022	5,689.76	43.65	41.1	5,733.41	2.55	25.5-45.5	49	46	WD
MW175-WD	4/5/2022	5,689.11	44.3	41.75	5,733.41	2.55	25.5-45.5	49	46	WD
MW176-DEN MW176-DEN	1/5/2022 4/11/2022	5,558.02 5,558.26	16.11 15.87	16.44 16.2	5,574.13 5,574.13	-0.23 -0.23	12-52 12-52	55 55	55 55	Upper Denver Upper Denver
MW176-UDEN	1/5/2022	5,557.22	18	18.53	5,575.22	-0.23	74-94	109	51	UNWEATHERED DENVER
MW176-UDEN	4/11/2022	5,557.17	18.05	18.58	5,575.22	-0.53	74-94	109	51	UNWEATHERED DENVER
MW177-DEN	1/5/2022	5,568.71	13.49	13.93	5,582.20	-0.44	17.5-27.5	33	27.5	UPPER DENVER
MW177-DEN	4/11/2022	5,568.71	13.49	13.93	5,582.20	-0.44	17.5-27.5	33	27.5	UPPER DENVER
MW177-UDEN	1/5/2022	5,565.07	16.85	17.22	5,581.92	-0.37	47-62	69	27.5	UNWEATHERED DENVER
MW177-UDEN	4/11/2022	5,565.37	16.55	16.92	5,581.92	-0.37	47-62	69	27.5	UNWEATHERED DENVER
MW178-DEN MW178-DEN	1/5/2022 4/11/2022	5,559.60 5,560.00	17.89 17.49	18.25 17.85	5,577.49 5,577.49	-0.36 -0.36	16-36 16-36	43	36 36	UPPER DENVER UPPER DENVER
MW178-UDEN	1/5/2022	5,536.69	39.95	40.8	5,576.64	-0.85	67-97	99	36.5	UNWEATHERED DENVER
MW178-UDEN	4/11/2022	5,536.83	39.81	40.66	5,576.64	-0.85	67-97	99	36.5	UNWEATHERED DENVER
MW179-UDEN	1/5/2022	5,648.90	22.96	21.2	5,671.86	1.85	56-81	84	29	UNWEATHERED DENVER
MW179-UDEN	4/11/2022	5,648.72	23.14	21.38	5,671.86	1.85	56-81	84	29	UNWEATHERED DENVER
MW180-WD	1/5/2022	5,678.01	16.83	14.69	5,694.84	2.14	17-27	30	27	WD
MW180-WD	4/11/2022	5,678.20	16.64	14.5	5,694.84	2.14	17-27	30	27	WD
MW-2 MW-2	1/18/2022 4/11/2022	5,758.00 5,758.17	78.57 78.4	76.6 76.43	5,836.57 5,836.57	1.97 1.97	64-119 64-119	142 142	60	UNWD UNWD
MW23-C-SD	1/3/2022	5,698.39	30.28	27.91	5,728.67	2.37	56-71	73	38	UNWD
MW23-C-SD	4/5/2022	5,698.48	30.19	27.82	5,728.67	2.37	56-71	73	38	UNWD
MW23-UPPER-C	1/3/2022	5,701.96	26.97	24.64	5,728.93	2.33	25-35	38	37	WD
MW23-UPPER-C	4/5/2022	5,702.08	26.85	24.52	5,728.93	2.33	25-35	38	37	WD
MW23-WD	1/3/2022	5,701.24	28.74	25.73	5,729.98	3.01	35-55	56.5	NE, >56.5	UNWD
MW23-WD	4/5/2022	5,701.40	28.58	25.57	5,729.98	3.01	35-55	56.5	NE, >56.5	UNWD
MW-3 MW-3	1/18/2022	5,786.65	44.61	42.25 41.9	5,831.26	2.36	47-97 47-97	102 102	55 55	UNWD UNWD
MW-3 MW30-BU	4/11/2022 1/13/2022	5,787.00 5,717.95	44.26 79	76.29	5,831.26 5,796.95	2.36	150-180	183	48	UNWD UPPER DENVER
MW30-BU	4/7/2022	5,718.09	78.86	76.15	5,796.95	2.71	150-180	183	48	UPPER DENVER
MW32-UD	1/6/2022	5,786.59	47.57	45.81	5,834.16	1.76	59.5-69.5	69.8	49	UNWD
MW32-UD	4/8/2022	5,786.26	47.9	46.14	5,834.16	1.76	59.5-69.5	69.8	49	UNWD
MW32-WD	1/6/2022	5,802.61	31.81	29.37	5,834.42	2.44	32.7 - 47.7	50	47.5	WD
MW32-WD	4/8/2022	5,801.40	33.02	30.58	5,834.42	2.44	32.7 - 47.7	50	47.5	WD
MW33-UD	1/6/2022	5,788.87	56.01	54.03	5,844.88	1.98	62.5-72.5	75	51.5	UNWD
MW33-UD MW33-WDR	4/8/2022 1/6/2022	5,788.78 Dry	56.1 Dry	54.12 Dry	5,844.88 5,844.27	1.98 1.97	62.5-72.5 31.5-43.2	75 	51.5 50.6	UNWD WD
MW33-WDR	4/8/2022	Dry	Dry	Dry	5,844.27	1.97	31.5-43.2		50.6	WD
MW34-UD	1/6/2022	5,787.80	48.41	46	5,836.21	2.41	64-74	74	54.5	UNWD
MW34-UD	4/8/2022	5,787.66	48.55	46.14	5,836.21	2.41	64-74	74	54.5	UNWD
MW34-WDR	1/6/2022	5,790.93	45.29	42.57	5,836.22	2.72	43 - 53	56	53.5	WD
MW34-WDR	4/8/2022	5,790.70	45.52	42.8	5,836.22	2.72	43 - 53	56	53.5	WD
MW35-UD	1/6/2022	5,759.63	58.62	56.47	5,818.25	2.15	69.79	79	59	UNWD
MW35-UD	4/8/2022	5,759.53	58.72	56.57	5,818.25	2.15	69.79	79	59	UNWD
MW35-WDR	1/6/2022	5,778.85	39.14	36.45	5,817.99	2.69	36.7 - 56.7	59	58	WD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
	Date of	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Measurement	(ft NGVD)a/	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW35-WDR	4/8/2022	5,778.74	39.25	36.56	5,817.99	2.69	36.7 - 56.7	59	58	WD
MW36-UD	1/6/2022	5,767.28	33.78	31.82	5,801.06	1.96	56.5-66.5	66.5	46.1	UNWD
MW36-UD MW36-WDR	4/8/2022 1/6/2022	5,767.24 5,771.29	33.82 29.92	31.86 27.51	5,801.06 5,801.21	1.96 2.41	56.5-66.5 30.5-42.5	66.5 48.6	46.1 42.5	UNWD WD
MW36-WDR	4/8/2022	5,770.93	30.28	27.87	5,801.21	2.41	30.5-42.5	48.6	42.5	WD
MW37-UD	1/3/2022	5,699.23	28.11	26.17	5,727.34	1.94	38-53	59	32.5	UNWD
MW37-UD	4/4/2022	5,699.27	28.07	26.13	5,727.34	1.94	38-53	59	32.5	UNWD
MW37-WD	1/3/2022	5,695.78	32.63	29.63	5,728.41	3.00	22-32	35	32	WD
MW37-WD	4/4/2022	5,695.72	32.69	29.69	5,728.41	3.00	22-32	35	32	WD
MW38-0N-140W MW38-0N-140W	1/17/2022 4/6/2022	5,745.87 5,745.63	62.01 62.25	59.73 59.97	5,807.88 5,807.88	2.28	48-63 48-63	79 79	63	WD WD
MW38-1005N-150E	1/17/2022	5,731.63	44.65	42.17	5,776.28	2.48	36.5-56.5	61.4	56.5	WD
MW38-1005N-150E	4/6/2022	5,730.51	45.77	43.29	5,776.28	2.48	36.5-56.5	61.4	56.5	WD
MW38-100N-200E	1/17/2022	5,747.39	43.63	41.11	5,791.02	2.52	33-48	50.5	48	WD
MW38-100N-200E	4/6/2022	5,747.30	43.72	41.2	5,791.02	2.52	33-48	50.5	48	WD
MW38-100N-53W	1/17/2022	Dry	Dry	Dry	5,804.53	2.03	48-58	69	58	WD
MW38-100N-53W MW38-100N-60E	4/6/2022 1/17/2022	Dry 5,736.53	Dry 61	Dry 58.47	5,804.53 5,797.53	2.03	48-58 40-60	69 64.5	58 61.5	WD WD
MW38-100N-60E MW38-100N-60E	4/6/2022	5,736.50	61.03	58.47	5,797.53	2.53	40-60	64.5	61.5	WD
MW38-100S-140W	1/18/2022	Dry	Dry	Dry	5,807.35	1.55	48.5-68.5	74	68.5	WD
MW38-100S-140W	4/6/2022	Dry	Dry	Dry	5,807.35	1.55	48.5-68.5	74	68.5	WD
MW38-100S-195W	1/17/2022	Dry	Dry	Dry	5,807.22	-0.35	51-71	73.5	71	WD
MW38-100S-195W	4/6/2022	Dry	Dry	Dry	5,807.22	-0.35	51-71	73.5	71	WD
MW38-100S-200E	1/18/2022	5,748.53	43.53	41.07	5,792.06 5,792.06	2.46	34-49	51.5	49 49	WD WD
MW38-100S-200E MW38-100S-53W	4/6/2022 1/18/2022	5,748.44 Dry	43.62 Dry	41.16 Dry	5,806.51	2.46 3.71	34-49 46-66	51.5 79	66	WD
MW38-100S-53W	4/6/2022	Dry	Dry	Dry	5,806.51	3.71	46-66	79	66	WD
MW38-1028N-256E	1/17/2022	5,719.92	51.88	49.78	5,771.80	2.10	28-53	56	NE, > 56	WD
MW38-1028N-256E	4/6/2022	5,720.25	51.55	49.45	5,771.80	2.10	28-53	56	NE, > 56	WD
MW38-1064N-650E	1/17/2022	5,734.51	26.37	23.89	5,760.88	2.48	20-35	39	35	WD
MW38-1064N-650E MW38-1064N-655E	4/6/2022 1/17/2022	5,733.24 5,726.36	27.64 34.24	25.16 32.04	5,760.88 5,760.60	2.48	20-35 40-55	39 57.5	35 35.5	WD UNWD
MW38-1064N-655E	4/6/2022	5,725.76	34.84	32.64	5,760.60	2.20	40-55	57.5	35.5	UNWD
MW38-1064N-660E	1/17/2022	5,717.12	43.42	41.18	5,760.54	2.24	60-75	77.5	35	UNWD
MW38-1064N-660E	4/6/2022	5,717.43	43.11	40.87	5,760.54	2.24	60-75	77.5	35	UNWD
MW38-1095N-226E	1/17/2022	5,720.70	50.61	48.8	5,771.31	1.81	23-53	69	52.5	WD
MW38-1095N-226E	4/6/2022	5,720.80	50.51	48.7	5,771.31	1.81	23-53	69	52.5	WD
MW38-1100N-0E MW38-1100N-0E	1/17/2022 4/6/2022	5,744.69 5,743.91	35.07 35.85	32.61 33.39	5,779.76 5,779.76	2.46	32-47 32-47	54 54	47 47	WD WD
MW38-1100N-326E	1/17/2022	5,728.24	38.15	38.16	5,766.39	-0.01	34.5-49.5	52.5	49.5	WD
MW38-1100N-326E	4/6/2022	5,727.67	38.72	38.73	5,766.39	-0.01	34.5-49.5	52.5	49.5	WD
MW38-1120N-1000E	1/17/2022	5,716.45	33.76	33.05	5,750.21	0.71	50-70	72.5	44	UNWD
MW38-1120N-1000E	4/6/2022	5,716.84	33.37	32.66	5,750.21	0.71	50-70	72.5	44	UNWD
MW38-1175N-300E	1/17/2022	5,723.38	44.48	44.9	5,767.86	-0.42	25.5-45.5	48.5	45.5	WD
MW38-1175N-300E MW38-1175N-518E	4/6/2022 1/17/2022	5,723.55 5,735.20	44.31 31.21	44.73 31.4	5,767.86 5,766.41	-0.42 -0.19	25.5-45.5 25.5-45.5	48.5 48	45.5 45.5	WD WD
MW38-1175N-518E	4/6/2022	5,734.55	31.86	32.05	5,766.41	-0.19	25.5-45.5	48	45.5	WD
MW38-1200N-226E	1/17/2022	5,710.04	62.05	60.46	5,772.09	1.59	45-70	74	69.5	UNWD
MW38-1200N-226E	4/6/2022	5,709.73	62.36	60.77	5,772.09	1.59	45-70	74	69.5	UNWD
MW38-1363N-180W	1/17/2022	5,724.56	46.28	46.54	5,770.84	-0.26	70-90	94.5	58	UNWD
MW38-1363N-180W MW38-1373N-180W	4/6/2022	5,724.25	46.59	46.85	5,770.84	-0.26	70-90	94.5	58	UNWD
MW38-13/3N-180W MW38-1373N-180W	1/17/2022 4/6/2022	5,723.20 5,723.09	48.89 49	46.1 46.21	5,772.09 5,772.09	2.79	36-51 36-51	54 54	51 51	WD WD
MW38-150S-320W	1/17/2022	5,759.75	53.85	51.35	5,813.60	2.50	47-57	59.5	57	WD
MW38-150S-320W	4/6/2022	5,759.70	53.9	51.4	5,813.60	2.50	47-57	59.5	57	WD
MW38-170S-140W	1/18/2022	5,735.13	71.63	69.37	5,806.76	2.26	58-73	78.5	74	WD
MW38-170S-140W	4/6/2022	5,735.47	71.29	69.03	5,806.76	2.26	58-73	78.5	74	WD
MW38-200N-425E MW38-200N-425E	1/17/2022	5,731.43	49.42 49.97	47.27	5,780.85	2.15	33-58	69 69	40	UNWD
MW38-200N-425E MW38-200N-60E	4/6/2022 1/17/2022	5,730.88 5,736.83	58.59	47.82 56.07	5,780.85 5,795.42	2.15	33-58 38.5-58.5	61.6	58.5	UNWD WD
MW38-200N-60E	4/6/2022	5,736.83	58.65	56.13	5,795.42	2.52	38.5-58.5	61.6	58.5	WD
MW38-200S-140W	1/18/2022	5,735.96	70.6	68.34	5,806.56	2.26	53-73	77	72	WD
MW38-200S-140W	4/6/2022	5,736.19	70.37	68.11	5,806.56	2.26	53-73	77	72	WD
MW38-200S-180W	1/18/2022	5,736.22	71.94	70.08	5,808.16	1.86	55-75	78.8	75	WD
MW38-200S-180W	4/6/2022	5,736.42	71.74	69.88	5,808.16	1.86	55-75	78.8	75	WD
MW38-200S-195W	1/17/2022	5,736.41	70.18	70.66	5,806.59	-0.48	53-73	76.5	73	WD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
	Data of	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Date of Measurement	(ft NGVD)a/	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW38-200S-195W	4/6/2022	5,736.62	69.97	70.45	5,806.59	-0.48	53-73	76.5	73	WD
MW38-250S-160W	1/18/2022	5,743.35	62.96	60.35	5,806.31	2.61	51-63	68	63	WD
MW38-250S-160W	4/6/2022	5,743.35	62.96	60.35	5,806.31	2.61	51-63 45-60	68	63	WD
MW38-250S-320W MW38-250S-320W	1/17/2022 4/6/2022	5,759.62 5,759.60	54.77 54.79	52.28 52.3	5,814.39 5,814.39	2.49	45-60	64 64	60 60	WD WD
MW38-250S-50W	1/18/2022	Dry	Dry	Dry	5,803.99	3.09	34-49	54	49	WD
MW38-250S-50W	4/6/2022	Dry	Dry	Dry	5,803.99	3.09	34-49	54	49	WD
MW38-275S-195W	1/17/2022	5,738.08	67.85	68.02	5,805.93	-0.17	50-70	72.5	69	WD
MW38-275S-195W	4/6/2022	5,738.10	67.83	68	5,805.93	-0.17	50-70	72.5	69	WD
MW38-300S-180W	1/18/2022	5,745.39	62.25	59.41	5,807.64	2.84	56-61	64	61	WD
MW38-300S-180W MW38-300S-315W	4/6/2022 1/17/2022	5,745.35 5,745.06	62.29 68.83	59.45 66.64	5,807.64 5,813.89	2.84	56-61 53.7-68.7	64 87	61 68	WD WD
MW38-300S-315W	4/6/2022	5,745.03	68.86	66.67	5,813.89	2.19	53.7-68.7	87	68	WD
MW38-300S-60E	1/18/2022	5,748.44	47.68	45.96	5,796.12	1.72	40-50	58	50	WD
MW38-300S-60E	4/6/2022	5,748.31	47.81	46.09	5,796.12	1.72	40-50	58	50	WD
MW38-302S-50W	1/18/2022	5,744.00	58.68	56.2	5,802.68	2.48	50-70	79	55	UNWD
MW38-302S-50W	4/6/2022	5,744.10	58.58	56.1	5,802.68	2.48	50-70	79	55	UNWD
MW38-320N-305E	1/17/2022	5,729.03	55.16	52.07	5,784.19	3.09	40-55	64	NE, >64	WD
MW38-320N-305E	4/6/2022 1/17/2022	5,728.94	55.25	52.16 59.04	5,784.19	3.09 -0.16	40-55	64	NE, >64	WD WD
MW38-325S-195W MW38-325S-195W	4/6/2022	5,746.55 5,746.53	58.88 58.9	59.04	5,805.43 5,805.43	-0.16	48.5-63.5 48.5-63.5	66	62.5 62.5	WD WD
MW38-350N-175E	1/17/2022	5,739.08	49.5	46.52	5,788.58	2.98	27-47	49.5	47	WD
MW38-350N-175E	4/6/2022	5,739.08	49.5	46.52	5,788.58	2.98	27-47	49.5	47	WD
MW38-350S-200E	1/18/2022	5,748.68	40.56	38.12	5,789.24	2.44	37.5-44.5	53.8	44.5	WD
MW38-350S-200E	4/6/2022	5,748.64	40.6	38.16	5,789.24	2.44	37.5-44.5	53.8	44.5	WD
MW38-350S-320W	1/17/2022	5,747.64	66.52	64.06	5,814.16	2.46	54-74	77	74	WD
MW38-350S-320W	4/6/2022	5,747.41	66.75	64.29	5,814.16	2.46	54-74	77	74	WD
MW38-350S-50W MW38-350S-50W	1/18/2022 4/6/2022	5,747.80 5,747.77	54.25 54.28	51.7 51.73	5,802.05 5,802.05	2.55 2.55	36-56 36-56	58.5 58.5	57 57	WD WD
MW38-350S-60E	1/18/2022	5,748.35	47.89	45.35	5,796.24	2.54	33.5-53.5	57.2	53.5	WD
MW38-350S-60E	4/6/2022	5,748.29	47.95	45.41	5,796.24	2.54	33.5-53.5	57.2	53.5	WD
MW38-360N-405E	1/17/2022	Dry	Dry	Dry	5,779.52	2.44	40-55	59	49	WD/UNWD
MW38-360N-405E	4/6/2022	Dry	Dry	Dry	5,779.52	2.44	40-55	59	49	WD/UNWD
MW38-390S-60E	1/18/2022	5,748.40	46.53	44	5,794.93	2.53	30.5-50.5	73	50.5	WD
MW38-390S-60E	4/6/2022	5,748.35	46.58	44.05	5,794.93	2.53	30.5-50.5	73	50.5	WD
MW38-400N-100E MW38-400N-100E	1/17/2022 4/6/2022	5,738.64 5,738.42	50.3 50.52	47.96 48.18	5,788.94 5,788.94	2.34	40-55 40-55	62 62	55 55	WD WD
MW38-400N-180W	1/17/2022	5,756.42	42.34	39.18	5,798.76	3.16	41.5-56.5	59	57	WD
MW38-400N-180W	4/6/2022	5,755.86	42.9	39.74	5,798.76	3.16	41.5-56.5	59	57	WD
MW38-400N-240E	1/17/2022	5,738.60	46.11	43.4	5,784.71	2.71	31-46	49.2	46	WD
MW38-400N-240E	4/6/2022	5,738.48	46.23	43.52	5,784.71	2.71	31-46	49.2	46	WD
MW38-400N-300E	1/17/2022	5,718.05	65.06	62.55	5,783.11	2.51	65.6-85.6	89	45	UNWD
MW38-400N-300E	4/6/2022	5,718.28	64.83	62.32	5,783.11	2.51	65.6-85.6	89	45	UNWD
MW38-400S-0W MW38-400S-0W	1/18/2022 4/6/2022	5,747.99 5,747.97	50.81	47.71 47.73	5,798.80 5,798.80	3.10	37.5-51.5 37.5-51.5	54 54	51.7 51.7	WD WD
MW38-400S-140W	1/18/2022	5,747.37	57.04	54.63	5,804.41	2.41	38.5-58.5	61.5	58.5	WD
MW38-400S-140W	4/6/2022	5,747.34	57.07	54.66	5,804.41	2.41	38.5-58.5	61.5	58.5	WD
MW38-400S-195W	1/17/2022	5,746.98	57.4	57.32	5,804.38	0.08	43.5-58.5	64	58.5	WD
MW38-400S-195W	4/6/2022	5,746.96	57.42	57.34	5,804.38	0.08	43.5-58.5	64	58.5	WD
MW38-400S-320W	1/17/2022	5,747.97	65.63	63.33	5,813.60	2.30	59.5-74.5	87	74.2	WD
MW38-400S-320W	4/6/2022	5,747.68	65.92	63.62	5,813.60	2.30	59.5-74.5	87 50.5	74.2	WD
MW38-400S-50W MW38-400S-50W	1/18/2022 4/6/2022	5,747.73 5,747.70	53.49 53.52	51.37 51.4	5,801.22 5,801.22	2.12	42-57 42-57	59.5 59.5	57 57	WD WD
MW38-410N-180W	1/17/2022	5,717.88	79.53	76.82	5,797.41	2.71	71.5-91.5	94	56	UNWD
MW38-410N-180W	4/6/2022	5,718.23	79.18	76.47	5,797.41	2.71	71.5-91.5	94	56	UNWD
MW38-450S-200E	1/18/2022	5,748.66	40.73	37.94	5,789.39	2.79	45.5-48.5	48.8	45.5	WD/UNWD
MW38-450S-200E	4/6/2022	5,748.57	40.82	38.03	5,789.39	2.79	45.5-48.5	48.8	45.5	WD/UNWD
MW38-450S-320W	1/17/2022	5,750.96	61.79	59.14	5,812.75	2.65	50-70	73.2	70	WD
MW38-450S-320W MW38-450S-60E	4/6/2022 1/18/2022	5,750.47 5,748.91	62.28 45.33	59.63 42.89	5,812.75 5,794.24	2.65	50-70	73.2 54	70 52.5	WD WD
MW38-450S-60E MW38-450S-60E	4/6/2022	5,748.82	45.33	42.89	5,794.24	2.44	31.5-51.5 31.5-51.5	54	52.5	WD WD
MW38-500N-396E	1/17/2022	5,740.14	34.95	32.36	5,775.09	2.59	24-39	44	40	WD
MW38-500N-396E	4/6/2022	5,739.80	35.29	32.7	5,775.09	2.59	24-39	44	40	WD
MW38-500S-320W	1/17/2022	5,751.11	60.5	58.39	5,811.61	2.11	55-70	87	69.3	WD
MW38-500S-320W	4/6/2022	5,750.63	60.98	58.87	5,811.61	2.11	55-70	87	69.3	WD
MW38-500S-50W	1/18/2022	5,749.78	51	48.39	5,800.78	2.61	36.5-51.5	54	51.5	WD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
	ı	Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Date of	(ft NGVD) ^{a/}	(ft below MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft has)	(ft bas)	(ft bgs)	Formation ^{e/}
MW38-500S-50W	Measurement 4/6/2022	5,749.69	51.09	48.48	5,800.78	2.61	(ft bgs) 36.5-51.5	(ft bgs)	51.5	WD
MW38-550S-200E	1/18/2022	5,750.77	35.3	32.83	5,786.07	2.47	34-49	54	44.5	WD
MW38-550S-200E	4/6/2022	5,750.71	35.36	32.89	5,786.07	2.47	34-49	54	44.5	WD
MW38-550S-320W	1/17/2022	5,751.83	58.86	56.87	5,810.69	1.99	58-68	72	68	WD
MW38-550S-320W	4/6/2022	5,751.39	59.3	57.31	5,810.69	1.99	58-68	72	68	WD
MW38-600N-250E MW38-600N-250E	1/17/2022 4/6/2022	5,738.42 5,738.15	38.56 38.83	36.08 36.35	5,776.98 5,776.98	2.48	27.5-42.5 27.5-42.5	45.1 45.1	42.5 42.5	WD WD
MW38-600S-320W	1/17/2022	5,752.57	58.29	55.83	5,810.86	2.46	52-62	69	61.5	WD
MW38-600S-320W	4/6/2022	5,752.14	58.72	56.26	5,810.86	2.46	52-62	69	61.5	WD
MW38-650S-200E	1/18/2022	5,751.00	35.54	31.8	5,786.54	3.74	42-47	53	47	WD
MW38-650S-200E	4/6/2022	5,750.95	35.59	31.85	5,786.54	3.74	42-47	53	47	WD
MW38-650S-400E	1/18/2022	5,750.82	26.11	23.78	5,776.93	2.33	16-36	38.5	36	WD
MW38-650S-400E MW38-650S-50W	4/6/2022 1/18/2022	5,750.84 5,752.17	26.09 48.24	23.76 45.73	5,776.93 5,800.41	2.33	16-36 35-55	38.5 58.5	36 55	WD WD
MW38-650S-50W	4/6/2022	5,751.90	48.51	46	5,800.41	2.51	35-55	58.5	55	WD
MW38-680N-419E	1/17/2022	5,744.51	27.75	25.61	5,772.26	2.14	25-40	43	40	WD
MW38-680N-419E	4/6/2022	5,745.31	26.95	24.81	5,772.26	2.14	25-40	43	40	WD
MW38-700S-320W	1/17/2022	5,766.04	44.44	41.56	5,810.48	2.88	54-59	64	58.9	WD
MW38-700S-320W	4/6/2022	5,765.76	44.72	41.84	5,810.48	2.88	54-59	64	58.9	WD
MW38-700S-400E	1/18/2022	5,750.83	26.43	24.07	5,777.26	2.36	20-35	38.3	35	WD
MW38-700S-400E MW38-750S-400E	4/6/2022 1/18/2022	5,750.85 5,750.83	26.41 26.89	24.05 24.87	5,777.26 5,777.72	2.36	20-35 18-33	38.3 37.4	35 33	WD WD
MW38-750S-400E	4/6/2022	5,750.92	26.8	24.78	5,777.72	2.02	18-33	37.4	33	WD
MW38-758N-277E	1/17/2022	5,738.12	33.26	30.78	5,771.38	2.48	24-36	49	36	WD
MW38-758N-277E	4/6/2022	5,737.86	33.52	31.04	5,771.38	2.48	24-36	49	36	WD
MW38-770S-60E	1/18/2022	5,761.40	32.02	29.5	5,793.42	2.52	25-45	48	45	WD
MW38-770S-60E	4/6/2022	5,761.14	32.28	29.76	5,793.42	2.52	25-45	48	45	WD
MW38-794N-383E MW38-794N-383E	1/17/2022 4/6/2022	5,744.33 5,745.60	28.07 26.8	25.63 24.36	5,772.40 5,772.40	2.44	25-40 25-40	42.5 42.5	40 40	WD WD
MW38-815S-445E	1/18/2022	5,750.98	29.33	26.54	5,780.31	2.79	21.7 - 36.7	38	36	WD
MW38-815S-445E	4/6/2022	5,751.04	29.27	26.48	5,780.31	2.79	21.7 - 36.7	38	36	WD
MW38-825S-445E	1/18/2022	5,750.90	30.24	26.7	5,781.14	3.54	26-36	41	36	WD
MW38-825S-445E	4/6/2022	5,750.96	30.18	26.64	5,781.14	3.54	26-36	41	36	WD
MW38-830N-230E	1/17/2022	5,738.05	35.52	33.93	5,773.57	1.59	28 - 38	43.4	40	WD
MW38-830N-230E MW38-830S-380E	4/6/2022 1/18/2022	5,737.78 5,751.03	35.79 29.04	34.2 26.87	5,773.57 5,780.07	1.59 2.17	28 - 38 17.5 - 32.5	43.4 34.8	40 33	WD WD
MW38-830S-380E	4/6/2022	5,751.07	29	26.83	5,780.07	2.17	17.5 - 32.5	34.8	33	WD
MW38-840S-325E	1/18/2022	5,752.77	27.66	25.16	5,780.43	2.50	19 - 34	39	36	WD
MW38-840S-325E	4/6/2022	5,752.73	27.7	25.2	5,780.43	2.50	19 - 34	39	36	WD
MW38-890S-385E	1/18/2022	5,751.67	31.98	29.38	5,783.65	2.60	21.3 - 36.3	39	37	WD
MW38-890S-385E MW38-995N-228E	4/6/2022 1/17/2022	5,751.57 5,720.72	32.08	29.48	5,783.65	2.60	21.3 - 36.3	39 74	37 64	WD WD
MW38-995N-228E MW38-995N-228E	4/6/2022	5,720.72	53.7 53.45	50.98 50.73	5,774.42 5,774.42	2.72	24-64 24-64	74	64	WD
MW38-995N-300E	1/17/2022	5,720.72	50.69	48.18	5,771.41	2.51	27.5-57.5	60	57.5	WD
MW38-995N-300E	4/6/2022	5,721.01	50.4	47.89	5,771.41	2.51	27.5-57.5	60	57.5	WD
MW38-995N-375E	1/17/2022	5,732.96	35.93	32.74	5,768.89	3.19	29-49	51.5	49	WD
MW38-995N-375E	4/6/2022	5,731.90	36.99	33.8	5,768.89	3.19	29-49	51.5	49	WD
MW38-995N-475E MW38-995N-475E	1/17/2022 4/6/2022	5,734.80 5,733.41	25.68 27.07	26.2 27.59	5,760.48 5,760.48	-0.52 -0.52	31-51 31-51	53.9 53.9	51 51	WD WD
MW38-WD MW38-WD	1/18/2022	5,735.96	68.46	65.14	5,804.42	3.32	39.5-69.5	75	69.5	WD
MW38-WD	4/6/2022	5,736.04	68.38	65.06	5,804.42	3.32	39.5-69.5	75	69.5	WD
MW39I-WD	1/6/2022	5,772.75	32.93	30.15	5,805.68	2.78	31.1-41	48.8	41	WD
MW39I-WD	4/8/2022	5,772.61	33.07	30.29	5,805.68	2.78	31.1-41	48.8	41	WD
MW39-UD	1/6/2022	5,751.65	52.9	49.85	5,804.55	3.05	56-76	79	42.8	UNWD
MW39-UD MW39-WD	4/8/2022 1/6/2022	5,751.55 5,773.63	53 31.62	49.95 28.87	5,804.55 5,805.25	3.05 2.75	56-76 24.1-44.1	79 48.7	42.8 44.1	UNWD WD
MW39-WD MW39-WD	4/8/2022	5,773.48	31.77	29.02	5,805.25	2.75	24.1-44.1	48.7	44.1	WD
MW40-WD	1/6/2022	5,777.78	42.88	40.22	5,820.66	2.66	31.7-61.7	65	61.8	WD
MW40-WD	4/8/2022	5,777.61	43.05	40.39	5,820.66	2.66	31.7-61.7	65	61.8	WD
MW41-WD	1/6/2022	5,787.83	45.09	42.67	5,832.92	2.42	25.3-55.3	61	55.3	WD
MW41-WD	4/8/2022	5,787.79	45.13	42.71	5,832.92	2.42	25.3-55.3	61	55.3	WD
MW42-UD MW42-UD	1/6/2022 4/8/2022	5,786.71 5,786.56	49.09 49.24	46.69 46.84	5,835.80	2.40	70-90 70-90	92.5 92.5	60	UNWD UNWD
MW42-UD MW42-WD	1/6/2022	5,789.69	49.24	43.91	5,835.80 5,836.21	2.40	23.3-48.3	92.5 52	48.3	WD
	4/8/2022	5,789.30	46.91	44.3	5,836.21	2.61	23.3-48.3	52	48.3	WD
MW42-WD	4/0/2022	5,765.50								

TABLE 4.2
WATER LEVEL ELEVATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

	1	www.		OWRY LA	NDFILL SUP	ERFUND	SITE			
		Water-	Measured	D	Measuring			m . 1	ъ е	
		Surface	Depth to	Depth to	Point	0.1.1	Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
	Date of	,	(ft below	,						,
Well ID	Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW43-WD	4/8/2022	5,790.79	51.98	49.51	5,842.77	2.47	19.5-54.5	60.5	55.1	WD
MW44-WD	1/6/2022	5,789.02	60.23	57.68	5,849.25	2.55	26.4-66.4	69.7	66.4	WD
MW44-WD	4/8/2022	5,788.87	60.38	57.83	5,849.25	2.55	26.4-66.4	69.7	66.4	WD
MW45-WD	1/6/2022	5,806.49	49.05	46.91	5,855.54	2.14	35-65	70	65	WD
MW45-WD	4/8/2022	5,804.90	50.64	48.5	5,855.54	2.14	35-65	70	65	WD
MW46-WD	1/6/2022	5,824.76	23.69	21.04	5,848.45	2.65	15-65	70	65	WD
MW46-WD	4/8/2022	5,824.00	24.45	21.8	5,848.45	2.65	15-65	70	65	WD
MW47-WD	1/6/2022	5,825.50	16.51	14	5,842.01	2.51	10-45	45.3	NE, >45.3	WD
MW47-WD	4/8/2022	5,824.84	17.17	14.66	5,842.01	2.51	10-45	45.3	NE, >45.3	WD
MW48-WD MW48-WD	1/6/2022	5,823.29	14.57	12.31	5,837.86	2.26	9.7-49.7	55	49.7	WD
	4/8/2022	5,822.71	15.15	12.89	5,837.86	2.26	9.7-49.7	55	49.7	WD WD
MW49-WD MW49-WD	1/6/2022 4/8/2022	5,806.81 5,805.92	18.13 19.02	15.89 16.78	5,824.94 5,824.94	2.24	19-54 19-54	58.5 58.5	54 54	WD
MW50-WD	1/13/2022	5,790.04	20.91	18.36	5,810.95	2.24	15.2-45.2	50	45.2	WD
MW50-WD	4/7/2022	5,789.45	21.5	18.95	5,810.95	2.55	15.2-45.2	50	45.2	WD
MW51-10S	1/13/2022	5,752.89	43.43	41.01	5,796.32	2.42	51-61	64	43.2	UNWD
MW51-10S	4/7/2022	5,752.87	43.45	41.03	5,796.32	2.42	51-61	64	44	UNWD
MW51I-WD	1/14/2022	5,751.63	46.4	43.37	5,798.03	3.03	34-44	49	44	WD
MW51I-WD	4/7/2022	5,751.63	46.4	43.37	5,798.03	3.03	34-44	49	44	WD
MW51I-WD-10S	1/13/2022	5,756.43	41.48	38.77	5,797.91	2.71	40.5-41.5	44	NE, >44	WD
MW51I-WD-10S	4/7/2022	5,756.42	41.49	38.78	5,797.91	2.71	40.5-41.5	44	NE, >44	WD
MW51I-WD-103	1/14/2022	5,747.22	49.39	47.35	5,796.61	2.04	29-44	49	44	WD
MW511-WD-15N	4/7/2022	5,747.14	49.47	47.43	5,796.61	2.04	29-44	49	44	WD
MW51I-WD-35S	1/14/2022	5,746.12	51.82	49.46	5,797.94	2.36	26-46	51	46	WD
MW51I-WD-35S	4/7/2022	5,745.90	52.04	49.68	5,797.94	2.36	26-46	51	46	WD
MW51I-WD-65N	1/13/2022	5,752.03	43.19	41.47	5,795.22	1.72	28.5-43.5	50.5	44	WD
MW51I-WD-65N	4/7/2022	5,752.00	43.22	41.5	5,795.22	1.72	28.5-43.5	50.5	44	WD
MW51I-WD-80S	1/13/2022	5,756.68	41.76	39.82	5,798.44	1.94	39-54	59	52	WD
MW51I-WD-80S	4/7/2022	5,756.59	41.85	39.91	5,798.44	1.94	39-54	59	52	WD
MW51-WD	1/13/2022	5,753.66	42.74	40.44	5,796.40	2.30	16.2-41.2	45.1	41.2	WD
MW51-WD	4/7/2022	5,753.67	42.73	40.43	5,796.40	2.30	16.2-41.2	45.1	41.2	WD
MW51X-WD-100S	1/13/2022	5,751.73	46.9	44.17	5,798.63	2.73	46.5-48.5	51	52	WD
MW51X-WD-100S	4/7/2022	5,751.71	46.92	44.19	5,798.63	2.73	46.5-48.5	51	52	WD
MW51X-WD-35S	1/13/2022	5,751.95	44.1	42.09	5,796.05	2.01	28-43	45.5	43.5	WD
MW51X-WD-35S	4/7/2022	5,751.94	44.11	42.1	5,796.05	2.01	28-43	45.5	43.5	WD
MW51X-WD-65N	1/13/2022	5,751.99	43.26	39.92	5,795.25	3.34	21-41	44.5	41	WD
MW51X-WD-65N	4/7/2022	5,751.94	43.31	39.97	5,795.25	3.34	21-41	44.5	41	WD
MW51X-WD-90S	1/13/2022	5,751.80	46.03	44.1	5,797.83	1.93	38-53	56.5	52	WD
MW51X-WD-90S	4/7/2022	5,751.78	46.05	44.12	5,797.83	1.93	38-53	56.5	52	WD
MW52-DEN	1/13/2022	5,728.65	54.88	52.77	5,783.53	2.11	155-175	180	45	UPPER DENVER
MW52-DEN	4/7/2022	5,728.88	54.65	52.54	5,783.53	2.11	155-175	180	45	UPPER DENVER
MW52-LIG	1/13/2022	5,680.75	102.79	99.95	5,783.54	2.84	285-300	307	45	LIGNITE
MW52-LIG	4/7/2022	5,680.89	102.65	99.81	5,783.54	2.84	285-300	307	45	LIGNITE
MW52-UD	1/13/2022	5,748.06	36.08	33.24	5,784.14	2.84	65-85	88	45	UNWD
MW52-UD	4/7/2022	5,748.23	35.91	33.07	5,784.14	2.84	65-85	88	45	UNWD
MW52-WD	1/13/2022	5,751.50	33.37	30.5	5,784.87	2.87	25-45	50	45	WD
MW52-WD	4/7/2022	5,751.24	33.63	30.76	5,784.87	2.87	25-45	50	45	WD
MW53-WD	1/13/2022	5,748.19	36.52	35.01	5,784.71	1.51	17.5-52.5	55.5	52.5	WD
MW53-WD	4/7/2022	5,748.26	36.45	34.94	5,784.71	1.51	17.5-52.5	55.5	52.5	WD
MW54-UDR	1/13/2022	5,719.58	26.29	23.82	5,745.87	2.47	54-64	67	37 37	UNWD
MW54-UDR MW54-WD	4/7/2022 1/13/2022	5,719.62 5,719.52	26.25 25.75	23.78	5,745.87 5,745.27	2.47	54-64 16.8-36.8	67 40	36.8	UNWD WD
MW54-WD MW54-WD	4/7/2022	5,719.32	25.49	23.13	5,745.27	2.62	16.8-36.8	40	36.8	WD
MW55-WD	1/17/2022	5,753.77	37.5	34.63	5,791.27	2.62	28.4-48.4	54	48.4	WD
MW55-WD MW55-WD	4/6/2022	5,753.36	37.91	35.04	5,791.27	2.87	28.4-48.4	54	48.4	WD
MW56-WD	1/18/2022	5,750.25	47.99	44.95	5,798.24	3.04	25-50	54	50	WD
MW56-WD	4/6/2022	5,750.23	48.03	44.99	5,798.24	3.04	25-50	54	50	WD
MW57-WD	1/18/2022	5,740.66	36.49	34.34	5,777.15	2.15	24-39	44	39	WD
MW57-WD	4/6/2022	5,740.72	36.43	34.28	5,777.15	2.15	24-39	44	39	WD
MW58-WD	1/17/2022	5,756.79	53.22	50.11	5,810.01	3.11	26-56	59	56	WD
MW58-WD	4/6/2022	5,756.70	53.31	50.2	5,810.01	3.11	26-56	59	56	WD
MW59-WD	1/17/2022	5,756.03	47.07	45.48	5,803.10	1.59	39.5-57	60	57	WD
MW59-WD	4/6/2022	5,755.76	47.34	45.75	5,803.10	1.59	39.5-57	60	57	WD
MW60-WD	1/13/2022	5,751.68	35.21	32.56	5,786.89	2.65	19-44	49	44	WD
MW60-WD	4/7/2022	5,751.60	35.29	32.64	5,786.89	2.65	19-44	49	44	WD
MW61-WD	1/13/2022	5,751.69	34.35	32.21	5,786.04	2.14	27-39	44	39	WD

		Water- Surface	Measured Depth to	Depth to	Measuring Point		Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
	Date of		(ft below			•		-		
Well ID	Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW61-WD MW62-DENR	4/7/2022 1/3/2022	5,751.63 5,698.32	34.41 30.03	32.27 28.03	5,786.04 5,728.35	2.14	27-39 124-144	44 149	39 35	WD UPPER DENVER
MW62-DENR	4/4/2022	5,698.33	30.03	28.02	5,728.35	2.00	124-144	149	35	UPPER DENVER
MW62-LIG	1/3/2022	5,674.36	52.94	51.24	5,727.30	1.70	208-223	227	30.5	LIGNITE
MW62-LIG	4/4/2022	5,674.61	52.69	50.99	5,727.30	1.70	208-223	227	30.5	LIGNITE
MW62-UD	1/3/2022	5,690.47	37.19	35.13	5,727.66	2.06	53.5-68.5	71	32	UNWD
MW62-UD MW62-WDR	4/4/2022 1/3/2022	5,690.47 5,697.10	37.19 31.15	35.13 28.83	5,727.66 5,728.25	2.06	53.5-68.5 20.4-30.4	71 33.5	32 30	UNWD WD
MW62-WDR	4/4/2022	5,696.89	31.36	29.04	5,728.25	2.32	20.4-30.4	33.5	30	WD
MW63-WD	1/6/2022	5,773.63	34.86	32.97	5,808.49	1.89	33-53	57.9	53	WD
MW63-WD	4/8/2022	5,773.38	35.11	33.22	5,808.49	1.89	33-53	57.9	53	WD
MW64-WD	1/6/2022	5,775.43	30.6	27.87	5,806.03	2.73	31-46	49	45.4	WD
MW64-WD MW65-WD	4/8/2022 1/6/2022	5,775.18 5,771.96	30.85 27.63	28.12 25.24	5,806.03 5,799.59	2.73	31-46	49 42	45.4 37.7	WD WD
MW65-WD	4/8/2022	5,771.65	27.94	25.55	5,799.59	2.39	26-38 26-38	42	37.7	WD
MW66-WD	1/13/2022	5,751.69	39.75	37.11	5,791.44	2.64	31.8-41.8	49	41	WD
MW66-WD	4/7/2022	5,751.65	39.79	37.15	5,791.44	2.64	31.8-41.8	49	41	WD
MW67-WD	1/6/2022	5,772.91	28.7	26.19	5,801.61	2.51	31-43	49	43	WD
MW67-WD	4/8/2022	5,772.72	28.89	26.38	5,801.61	2.51	31-43	49	43	WD
MW68-WD MW68-WD	1/6/2022 4/8/2022	5,774.07 5,773.94	32.34 32.47	29.73 29.86	5,806.41 5,806.41	2.61	29-44 29-44	52.8 52.8	44 44	WD WD
MW70-WD	1/13/2022	5,751.75	39.4	37.25	5,791.15	2.01	34.5-49.5	52.8	49	WD
MW70-WD	4/7/2022	5,751.67	39.48	37.33	5,791.15	2.15	34.5-49.5	52.3	49	WD
MW71-DENR	1/13/2022	5,709.86	23.05	20.59	5,732.91	2.46	102.1 -	130	41.5	UPPER DENVER
MW71-DENR	4/7/2022	5,709.95	22.96	20.5	5,732.91	2.46	102.1 -	130	41.5	UPPER DENVER
MW71-LIG	1/13/2022	5,680.11	52.58	49.89	5,732.69	2.69	208-223	228	33	LIGNITE
MW71-LIG MW71-UD	4/7/2022 1/13/2022	5,680.40 5,709.85	52.29 23.29	49.6 20.85	5,732.69 5,733.14	2.69 2.44	208-223 67.5-82.5	228 84	33	LIGNITE UNWD
MW71-UD	4/7/2022	5,710.01	23.13	20.69	5,733.14	2.44	67.5-82.5	84	37	UNWD
MW71-WD	1/13/2022	5,709.21	23.85	21.09	5,733.06	2.76	20.5-35.5	39.2	35.5	WD
MW71-WD	4/7/2022	5,709.36	23.7	20.94	5,733.06	2.76	20.5-35.5	39.2	35.5	WD
MW72-DEN	1/13/2022	5,716.15	40.58	38	5,756.73	2.58	109.4 - 124	128	42	UPPER DENVER
MW72-DEN MW72-LIGR	4/7/2022 1/13/2022	5,716.23 5,681.00	40.5 78.07	37.92 75.67	5,756.73 5,759.07	2.58	109.4 - 124 253-263	128 268	42 42	UPPER DENVER LIGNITE
MW72-LIGR MW72-LIGR	4/7/2022	5,681.35	77.72	75.32	5,759.07	2.40	253-263	268	42	LIGNITE
MW72-UD	1/13/2022	5,721.17	35.49	33.03	5,756.66	2.46	66-81	84	43	UNWD
MW72-UD	4/7/2022	5,721.22	35.44	32.98	5,756.66	2.46	66-81	84	43	UNWD
MW72-WD	1/13/2022	5,724.31	32.97	29.99	5,757.28	2.98	32.5-42.5	45	42.5	WD
MW72-WD MW73-UD	4/7/2022 1/4/2022	5,724.22 5,710.97	33.06 25.23	30.08 22.73	5,757.28 5,736.20	2.98 2.50	32.5-42.5 57.7-77.7	45 80	42.5 35	WD UNWD
MW73-UD	4/4/2022	5,711.22	24.98	22.73	5,736.20	2.50	57.7-77.7	80	35	UNWD
MW73-WD	1/4/2022	5,715.03	21.79	19.23	5,736.82	2.56	15.7-35.7	38	34.5	WD
MW73-WD	4/4/2022	5,716.12	20.7	18.14	5,736.82	2.56	15.7-35.7	38	34.5	WD
MW74-UD	1/17/2022	5,713.21	36.15	33.79	5,749.36	2.36	72.7-92.7	95	54	UNWD
MW74-UD MW74-WD	4/6/2022 1/17/2022	5,713.30 5,716.96	36.06 32.42	33.7 30.04	5,749.36 5,749.38	2.36	72.7-92.7	95 62	54 54	UNWD WD
MW74-WD MW74-WD	4/6/2022	5,717.18	32.42	29.82	5,749.38	2.38	38-58 38-58	62	54	WD WD
MW75-UD	1/17/2022	5,716.71	40.12	37.5	5,756.83	2.62	71.5-91.5	94	51	UNWD
MW75-UD	4/6/2022	5,717.43	39.4	36.78	5,756.83	2.62	71.5-91.5	94	51	UNWD
MW75-WD	1/17/2022	5,731.62	25.55	22.68	5,757.17	2.87	25-50	52.5	50	WD
MW75-WD MW76-UD	4/6/2022 1/17/2022	5,730.41	26.76	23.89	5,757.17 5,760.04	2.87 -0.16	25-50 60-80	52.5	50	WD UNWD
MW76-UD MW76-UD	4/6/2022	5,717.30 5,717.62	42.74 42.42	42.9 42.58	5,760.04	-0.16	60-80	83 83	34.5 34.5	UNWD
MW76-WD	1/17/2022	5,738.33	21.31	21.37	5,759.64	-0.16	20-35	38	34.5	WD
MW76-WD	4/6/2022	5,739.78	19.86	19.92	5,759.64	-0.06	20-35	38	34.5	WD
MW77-EW-1	1/3/2022	5,688.45	36.78	34.15	5,725.23	2.63	25-35	39	37.6	WD
MW77-EW-1	4/5/2022	5,687.99	37.24	34.61 22.55	5,725.23	2.63	25-35 22-32	39 39	37.6 34.9	WD WD
MW77-EW-2 MW77-EW-2	1/3/2022 4/5/2022	5,695.95 5,696.03	25.03 24.95	22.33	5,720.98 5,720.98	2.48	22-32	39	34.9	WD
MW77-UD	1/3/2022	5,695.15	32.41	30.18	5,727.56	2.22	57-72	75	35	UNWD
MW77-UD	4/5/2022	5,695.19	32.37	30.14	5,727.56	2.22	57-72	75	35	UNWD
MW77-WD	1/3/2022	5,699.80	28.45	25.6	5,728.25	2.85	19.7-34.7	37	34.5	WD
MW77-WD	4/5/2022	5,700.18	28.07	25.22	5,728.25	2.85	19.7-34.7	37	34.5	WD
MW78-UD MW78-UD	1/13/2022 4/7/2022	5,705.06 5,704.98	26.48 26.56	24.14 24.22	5,731.54 5,731.54	2.34	57-77 57-77	79.5 79.5	42.5 42.5	UNWD UNWD
MW78-WD	1/13/2022	5,704.98	26.91	24.22	5,731.58	2.48	24-44	47.5	42.5	WD
		-,			-,					

		Water-	Measured		Measuring		Screened	Total	Dogo of	
		Surface Elevation	Depth to Water	Depth to Water	Point Elevation	Stickup	Interval	Total Depth	Base of Weathering	
	Date of		(ft below							
Well ID	Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
MW78-WD MW79-UD	4/7/2022 1/13/2022	5,704.72 5,712.35	26.86 14.95	24.38 12.65	5,731.58 5,727.30	2.48	24-44 52-72	47.5 75	42.5 35	WD UNWD
MW79-UD	4/7/2022	5,712.46	14.84	12.54	5,727.30	2.30	52-72	75	35	UNWD
MW79-WD	1/13/2022	5,712.82	15.21	12.38	5,728.03	2.83	20-35	38	35	WD
MW79-WD	4/7/2022	5,712.86	15.17	12.34	5,728.03	2.83	20-35	38	35	WD
MW90-UD MW90-UD	1/13/2022 4/7/2022	5,730.89 5,731.34	29.06 28.61	25.81 25.36	5,759.95 5,759.95	3.25 3.25	44-64 44-64	66.5 66.5	41	UNWD UNWD
MW90-UD MW90-WD	1/13/2022	5,730.89	29.16	26.21	5,760.05	2.95	26-41	43.5	41	WD
MW90-WD	4/7/2022	5,731.33	28.72	25.77	5,760.05	2.95	26-41	43.5	41	WD
MW91-UD	1/13/2022	5,715.94	19.9	17.66	5,735.84	2.24	60-80	82.5	31.5	UNWD
MW91-UD	4/7/2022	5,715.96	19.88	17.64	5,735.84	2.24	60-80	82.5	31.5	UNWD
MW91-WD MW91-WD	1/13/2022 4/7/2022	5,717.11	18.48 18.29	16.49 16.3	5,735.59 5,735.59	1.99 1.99	21.5-31.5	34 34	31.5 31.5	WD WD
MW91-WD MW92-WD	1/13/2022	5,717.30 5,723.52	24.49	21.88	5,748.01	2.61	21.5-31.5 19.5-39.5	42	39.5	WD
MW92-WD	4/7/2022	5,723.85	24.16	21.55	5,748.01	2.61	19.5-39.5	42	39.5	WD
MW93-UD	1/13/2022	5,730.98	26.39	23.82	5,757.37	2.57	42-62	75	35	UNWD
MW93-UD	4/7/2022	5,731.40	25.97	23.4	5,757.37	2.57	42-62	75	35	UNWD
MW93-WD	1/13/2022	5,729.02	28.46	25.98	5,757.48	2.48	15-35	37.5	35	WD
MW93-WD MW97-WD	4/7/2022 1/3/2022	5,729.12 5,698.07	28.36 29.59	25.88 26.73	5,757.48 5,727.66	2.48	15-35 29-31	37.5 34	35 30.5	WD WD
MW97-WD MW97-WD	4/5/2022	5,698.45	29.39	26.73	5,727.66	2.86	29-31	34	30.5	WD
MW98-WD	1/3/2022	5,691.05	34.68	32.35	5,725.73	2.33	25.5-33	36	33	WD
MW98-WD	4/5/2022	5,690.96	34.77	32.44	5,725.73	2.33	25.5-33	36	33	WD
MW99-WD	1/3/2022	5,699.60	25.9	23.4	5,725.50	2.50	25.5-33	35.5	31.5	WD
MW99-WD	4/5/2022	5,699.73	25.77	23.27	5,725.50	2.50	25.5-33	35.5	31.5	WD
MW-EW-1 MW-EW-1	1/3/2022 4/4/2022	5,696.83 5,696.75	16.69 16.77	13.77 13.85	5,713.52 5,713.52	2.92 2.92	7.8-17.8 7.8-17.8	17.8 17.8	NE, >17.8 NE, >17.8	ALLUVIUM ALLUVIUM
MW-EW-1LC	1/3/2022	5,694.37	18.6	16.66	5,712.97	1.94	28-38	38.1	23	UNWD
MW-EW-1LC	4/4/2022	5,694.33	18.64	16.7	5,712.97	1.94	28-38	38.1	23	UNWD
MW-EW-1LCRA	1/3/2022	5,692.20	20.66	18.3	5,712.86	2.36	46.5-61.5	64	23	UNWD
MW-EW-1LCRA	4/4/2022	5,692.08	20.78	18.42	5,712.86	2.36	46.5-61.5	64	23	UNWD
MW-EW-2	1/3/2022	5,696.62	17.02	14	5,713.64	3.02	8-18	18	NE, >18	ALLUVIUM
MW-EW-2 MW-EW-2LC	4/4/2022 1/3/2022	5,696.37 5,694.72	17.27 19.69	14.25 16.63	5,713.64 5,714.41	3.02	8-18 28-38	18 38	NE, >18 25	ALLUVIUM UNWD
MW-EW-2LC	4/4/2022	5,694.59	19.82	16.76	5,714.41	3.06	28-38	38	25	UNWD
MW-EW-2LCR	1/3/2022	5,694.60	21.34	18.4	5,715.94	2.94	46.5-56.5	59	24.5	UNWD
MW-EW-2LCR	4/4/2022	5,694.34	21.6	18.66	5,715.94	2.94	46.5-56.5	59	24.5	UNWD
NBBW-IW-1	1/4/2022	Dry	Dry	Dry	5,709.43	2.61	10-20	27.5	22	WD
NBBW-IW-1 NBBW-IW-2	4/4/2022 1/4/2022	Dry 5,685.87	Dry 23.23	Dry 20.07	5,709.43 5,709.10	2.61 3.16	10-20 12-22	27.5 28	22 23	WD WD
NBBW-IW-2 NBBW-IW-2	4/4/2022	5,685.78	23.32	20.07	5,709.10	3.16	12-22	28	23	WD
NBBW-IW-3	1/4/2022	Dry	44.8	42.53	5,711.74	2.27	11-41	47	42	WD
NBBW-IW-3	4/4/2022	Dry	44.65	42.38	5,711.74	2.27	11-41	47	42	WD
NEPZ-097	1/5/2022	5,553.31	25.18	25.38	5,578.49	-0.20	23-43	47.3	43.5	UPPER DENVER
NEPZ-097 NEPZ-098	4/11/2022 1/5/2022	5,553.40 5,554.38	25.09 22.25	25.29 22.24	5,578.49 5,576.63	-0.20 0.01	23-43 16-46	47.3 49.5	43.5 45.5	UPPER DENVER UPPER DENVER
NEPZ-098	4/11/2022	5,554.49	22.14	22.13	5,576.63	0.01	16-46	49.5	45.5	UPPER DENVER
NEPZ-099	1/5/2022	5,556.16	19.3	19.26	5,575.46	0.04	12.5-42.5	48.5	43.5	UPPER DENVER
NEPZ-099	4/11/2022	5,556.36	19.1	19.06	5,575.46	0.04	12.5-42.5	48.5	43.5	UPPER DENVER
NEPZ-101	1/5/2022	5,560.04	12.36	13.04	5,572.40	-0.68	19-44	49	43	UPPER DENVER
NEPZ-101	4/11/2022	5,560.27	12.13	12.81	5,572.40	-0.68	19-44	49	43	UPPER DENVER
NEPZ-102 NEPZ-102	1/5/2022 4/11/2022	5,562.54 5,562.74	11.06 10.86	11.5 11.3	5,573.60 5,573.60	-0.44 -0.44	27-42 27-42	49 49	43	UPPER DENVER UPPER DENVER
NEPZ-102 NEPZ-103	1/5/2022	5,563.87	10.41	10.95	5,574.28	-0.54	24-44	46	43	UPPER DENVER
NEPZ-103	4/11/2022	5,564.10	10.18	10.72	5,574.28	-0.54	24-44	46	43	UPPER DENVER
NEPZ-104	1/5/2022	5,564.23	10.4	10.62	5,574.63	-0.22	14.8-29.8	33	29.5	UPPER DENVER
NEPZ-104	4/11/2022	5,564.42	10.21	10.43	5,574.63	-0.22	14.8-29.8	33	29.5	UPPER DENVER
NEPZ-105 NEPZ-105	1/5/2022 4/11/2022	5,565.71 5,565.80	10.47	10.7 10.61	5,576.18 5,576.18	-0.23 -0.23	11.8-26.8 11.8-26.8	29.8 29.8	27.2 27.2	UPPER DENVER UPPER DENVER
NTES SUMP	1/19/2022	5,729.25	28.68	32.55	5,757.93	-0.23		29.8		OH EK DENVEK
NTES SUMP	4/12/2022	5,729.30	28.63	32.5	5,757.93	-3.87				
NTES-180W	1/19/2022	5,729.82	35.81	33.69	5,765.63	2.12	15-35	40.5	36	Fill (tire shreds)
NTES-180W	4/12/2022	5,729.76	35.87	33.75	5,765.63	2.12	15-35	40.5	36	Fill (tire shreds)
NTES-EW1	1/19/2022	5,749.35	28.93	27.35	5,778.28	1.58	41-51	53.5	50.5	WD
NTES-EW1 NTES-EW2	4/12/2022 1/19/2022	5,749.40 5,745.51	28.88 32.55	27.3 29.97	5,778.28 5,778.06	1.58 2.18	41-51 30-50	53.5 55	50.5 52	WD WD
1V1E3-E W Z	1/19/2022	ا د.د۳۱,د	رد.2د	27.71	3,770.00	2.10	30-30	55	34	WD

TABLE 4.2
WATER LEVEL ELEVATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

	1	***		OWKY LA	NDFILL SUP	ERFUND	SILE		ı	
		Water-	Measured	D 41.4	Measuring			T ()	D e	
		Surface	Depth to	Depth to	Point	Gr. 1	Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
	Date of	-/	(ft below	-/						-1
Well ID	Measurement	(ft NGVD) ^{a/}	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
NTES-EW2	4/12/2022	5,745.53	32.13	29.95	5,777.66	2.18	30-50	55	52	WD
NTES-EW3	1/19/2022	5,748.09	31.91	28.61	5,780.00	3.30	27.5-37.5	40	37.5	WD
NTES-EW3	4/12/2022	5,748.38	31.62	28.32	5,780.00	3.30	27.5-37.5	40	37.5	WD
PM-10I	1/6/2022	5,813.88	20.6	18.02	5,834.48	2.58	11.7-49.2	55.25	49.2	WD
PM-10I	4/8/2022	5,813.27	21.21	18.63	5,834.48	2.58	11.7-49.2	55.25	49.2	WD
PM-10X	1/6/2022	5,817.52	16.87	14.08	5,834.39	2.79	11.7-41.7	45.6	41.7	WD
PM-10X	4/8/2022	5,816.34	18.05	15.26	5,834.39	2.79	11.7-41.7	45.6	41.7	WD
PM-11I	1/14/2022	5,773.53	46.49	44.07	5,820.02	2.42	12.5-52.5	58.5	52.5	WD
PM-11I	4/7/2022	5,773.74	46.28	43.86	5,820.02	2.42	12.5-52.5	58.5	52.5	WD
PM-11X	1/13/2022	5,793.55	23.92	22.15	5,817.47	2.44	16-51	55	50.8	WD
PM-11X	4/7/2022	5,792.79	24.68	22.91	5,817.47	2.44	16-51	55	50.8	WD
PM-12I	1/13/2022	5,762.65	41.98	39.25	5,804.63	2.73	23.2-43.2	49.2	43.2	WD
PM-12I	4/7/2022	5,762.63	42	39.27	5,804.63	2.73	23.2-43.2	49.2	43.2	WD
PM-12X	1/13/2022	5,767.38	36.13	33.62	5,803.51	2.51	17-47	50	44	WD
PM-12X	4/7/2022	5,767.27	36.24	33.73	5,803.51	2.51	17-47	50	44	WD
PM-13I	1/13/2022	Dry	Dry	Dry	5,791.09	2.89	14.5-34.5	41	34.5	WD
PM-13I	4/7/2022	Dry	Dry	Dry	5,791.09	2.89	14.5-34.5	41	34.5	WD
PM-13X	1/13/2022	5,752.11	37.65	34.79	5,789.76	2.86	15-35	35	35	WD
PM-13X	4/7/2022	5,752.29	37.47	34.61	5,789.76	2.86	15-35	35	35	WD
PM-14I	1/13/2022	5,749.19	33.25	30.72	5,782.44	2.53	11.6-56.6	62	56.6	WD
PM-14I	4/7/2022	5,748.99	33.45	30.92	5,782.44	2.53	11.6-56.6	62	56.6	WD
PM-14ID	1/13/2022	5,750.77	32.97	30.88	5,783.74	2.09	44.5-54.5	64	54.5	WD
PM-14ID	4/7/2022	5,750.58	33.16	31.07	5,783.74	2.09	44.5-54.5	64	54.5	WD
PM-14X	1/13/2022	5,748.23	32.95	30.29	5,781.18	2.66	26.3-51.3	55	51.3	WD
PM-14X	4/7/2022	5,747.98	33.2	30.54	5,781.18	2.66	26.3-51.3	55	51.3	WD
PM-15I	1/14/2022	5,723.21	53.71	50.19	5,776.92	3.52	18.6-48.6	54	48.6	WD
PM-15I	4/7/2022	5,723.47	53.45	49.93	5,776.92	3.52	18.6-48.6	54	48.6	WD
PM-15I-UD	1/13/2022	5,735.46	39.93	37.24	5,775.39	2.69	57.5-77.5	80	53.10	UNWD
PM-15I-UD	4/7/2022	5,735.45	39.94	37.25	5,775.39	2.69	57.5-77.5	80	53.10	UNWD
PM-15W	1/13/2022	5,746.19	34.16	31.24	5,780.35	2.92	22-32	54	53	WD
PM-15W	4/7/2022	5,746.15	34.2	31.28	5,780.35	2.92	22-32	54	53	WD
PM-15WR	1/13/2022	5,739.57	40.28	38.04	5,779.85	2.24	25-55	58	55.7	WD
PM-15WR	4/7/2022	5,739.47	40.38	38.14	5,779.85	2.24	25-55	58	55.7	WD
PM-15X	1/13/2022	5,736.48	38.16	35.32	5,774.64	2.84	29.3-49.3	52.5	49.4	WD
PM-15X	4/7/2022	5,735.96	38.68	35.84	5,774.64	2.84	29.3-49.3	52.5	49.4	WD
PM-1I	1/18/2022	5,771.43	22.63	19.67	5,794.06	2.96	15.5-35.5	41	35.5	WD
PM-1I	4/6/2022	5,770.70	23.36	20.4	5,794.06	2.96	15.5-35.5	41	35.5	WD
PM-1X	1/18/2022	5,772.15	19.78	17.15	5,791.93	2.63	14.5-34.5	38	34.5	WD
PM-1X	4/6/2022	5,771.33	20.6	17.97	5,791.93	2.63	14.5-34.5	38	34.5	WD
PM-2I	1/6/2022	5,770.00	46.9	44.1	5,816.90	2.80	30.2-65.2	71	65.2	WD
PM-2I	4/8/2022	5,769.82	47.08	44.28	5,816.90	2.80	30.2-65.2	71	65.2	WD
PM-2X	1/6/2022	5,777.02	38.2	36.08	5,815.22	2.12	28-63	68	63	WD
PM-2X	4/8/2022	5,776.84	38.38	36.26	5,815.22	2.12	28-63	68	63	WD
PM-3I	1/6/2022	5,778.74	48.8	46.16	5,827.54	2.64	29-64	70	64	WD
PM-3I	4/8/2022	5,778.46	49.08	46.44	5,827.54	2.64	29-64	70	64	WD
PM-3X	1/6/2022	5,778.39	48.63	46.11	5,827.02	2.52	28-68	71	68	WD
PM-3X	4/8/2022	5,778.29	48.73	46.11	5,827.02	2.52	28-68	71	68	WD
PM-4EW1	1/6/2022	5,794.55	43.39	40.75	5,837.94	2.64	32-45	48	45	WD
PM-4EW1	4/8/2022	5,794.51	43.43	40.79	5,837.94	2.64	32-45	48	45	WD
PM-4EW1 PM-4EW2	1/6/2022	5,794.50	43.42	40.79	5,837.94	2.62	45-52	54.5	52	WD
PM-4EW2	4/8/2022	5,794.48	43.44	40.82	5,837.92	2.62	45-52	54.5	52	WD
PM-4I	1/6/2022	5,793.37	43.44	40.82	5,836.72	2.62	22-57	62.9	57	WD
PM-4I PM-4I	4/8/2022	5,793.31	43.41	40.79	5,836.72	2.62	22-57	62.9	57	WD
PM-41 PM-4X	1/6/2022	5,793.80	43.41	40.79	5,830.72	2.62	28.8-48.8	51.9	48.8	WD
PM-4X PM-4X	4/8/2022	5,793.85	43.34	40.8	5,837.19	2.59	28.8-48.8	51.9	48.8	WD
PM-5I	1/6/2022	5,798.61	38.8	36.69	5,837.41	2.39	22.4-52.4	59	51.4	WD
PM-5I PM-5I	4/8/2022	5,798.17	39.24	37.13	5,837.41	2.11	22.4-52.4	59	51.4	WD
PM-5X	1/6/2022	5,798.17	38.21	35.66	5,837.41	2.11	22.4-32.4	51.9	31.4 47.9	WD
									47.9	WD
PM-5X	4/8/2022	5,799.29	38.76	36.21	5,838.05	2.55	22.9-47.9	51.9		
PM-6I	1/6/2022	5,797.99	54.19	51.61	5,852.18	2.58	43.9-63.9	69.9	63.9	WD
PM-6I	4/8/2022	5,797.80	54.38	51.8	5,852.18	2.58	43.9-63.9	69.9	63.9	WD
PM-6X	1/6/2022	5,793.98	57.69	55.12	5,851.67	2.57	36.5-61.5	65	61.5	WD
PM-6X	4/8/2022	5,793.65	58.02	55.45	5,851.67	2.57	36.5-61.5	65	61.5	WD
PM-6X-UD	1/6/2022	5,792.16	59.87	57.36	5,852.03	2.51	85 - 109.5	112.5	75	UNWD
PM-6X-UD	4/8/2022	5,791.88	60.15	57.64	5,852.03	2.51	85 - 109.5	112.5	75	UNWD
PM-7I	1/6/2022	5,811.03	41.92	39.87	5,852.95	2.05	27.5-62.5	68.75	62.5	WD

TABLE 4.2
WATER LEVEL ELEVATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

		Water-	Measured	OWKILA	NDFILL SUP Measuring	ERFORD	SITE			
		Surface	Depth to	Depth to	Point	6.1.1	Screened	Total	Base of	
	Date of	Elevation	Water (ft below	Water	Elevation	Stickup	Interval	Depth	Weathering	
Well ID	Measurement	(ft NGVD)a/	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
PM-7I	4/8/2022	5,810.48	42.47	40.42	5,852.95	2.05	27.5-62.5	68.75	62.5	WD
PM-7X	1/6/2022	5,818.07	35.54	32.73	5,853.61	2.81	16.5-66.5	70	66.5	WD
PM-7X	4/8/2022	5,817.10	36.51	33.7	5,853.61	2.81	16.5-66.5	70	66.5	WD
PM-8I PM-8I	1/6/2022 4/8/2022	5,816.07 5,815.20	27.35 28.22	25.13 26	5,843.42 5,843.42	2.22	12.3-64.8 12.3-64.8	71.3 71.3	64.8 64.8	WD WD
PM-8X	1/6/2022	5,825.26	18.56	15.74	5,843.82	2.82	10.2-65.2	70	65.2	WD
PM-8X	4/8/2022	5,824.58	19.24	16.42	5,843.82	2.82	10.2-65.2	70	65.2	WD
PM-9I	1/6/2022	5,815.73	25.7	23.27	5,841.43	2.43	12-44.5	50.25	44.5	WD
PM-9I PM-9X	4/8/2022 1/6/2022	5,815.33 5,824.09	26.1 16.8	23.67	5,841.43	2.43 3.19	12-44.5	50.25	44.5 46.8	WD WD
PM-9X PM-9X	4/8/2022	5,823.48	17.41	13.61 14.22	5,840.89 5,840.89	3.19	11.75-46.75 11.75-46.75	50	46.8	WD
PTP-1	1/4/2022	5,695.54	37.13	33.36	5,732.67	3.77	25-40	40	NE, >40	WD
PTP-1	4/4/2022	5,695.54	37.13	33.36	5,732.67	3.77	25-40	40	NE, >40	WD
PTP-10C	1/3/2022	5,693.88	32.62	28.32	5,726.50	4.30	19-34	34	32	WD
PTP-10C PTP-11	4/4/2022 1/3/2022	5,693.81 5,687.10	32.69 23.08	28.39 19.5	5,726.50 5,710.18	4.30 3.58	19-34 12-22	34 23.9	32 22	WD WD
PTP-11	4/5/2022	5,687.13	23.05	19.3	5,710.18	3.58	12-22	23.9	22	WD
PTP-12	1/3/2022	5,688.43	24.7	21.87	5,713.13	2.83	12-27	27	26	WD
PTP-12	4/5/2022	5,688.53	24.6	21.77	5,713.13	2.83	12-27	27	26	WD
PTP-13	1/4/2022	5,687.30	26.26	24.1	5,713.56	2.16	12.5-27.5	27.5	27	WD
PTP-13 PTP-14	4/4/2022 1/4/2022	5,687.35 Dry	26.21 Dry	24.05 Dry	5,713.56 5,709.05	2.16	12.5-27.5 12-27	27.5 27	27 26.5	WD WD
PTP-14 PTP-14	4/4/2022	Dry	Dry	Dry	5,709.05	2.25	12-27	27	26.5	WD
PTP-15	1/4/2022	Dry	Dry	Dry	5,704.94	2.84	7.5-22.5	23.7	22.5	WD
PTP-15	4/4/2022	Dry	Dry	Dry	5,704.94	2.84	7.5-22.5	23.7	22.5	WD
PTP-15S	1/4/2022	Dry	Dry	Dry	5,704.55	2.35	7-12	12	NE, >12	WD
PTP-15S	4/4/2022	Dry	Dry	Dry	5,704.55	2.35	7-12	12 17	NE, >12	WD WD
PTP-16 PTP-16	1/4/2022 4/4/2022	Dry Dry	Dry Dry	Dry Dry	5,703.46 5,703.46	0.36	4.5-14.5 4.5-14.5	17	NE, >17 NE, >17	WD
PTP-17S	1/4/2022	Dry	Dry	Dry	5,711.50	4.50	10-15	15	NE, >15	WD
PTP-17S	4/4/2022	Dry	Dry	Dry	5,711.50	4.50	10-15	15	NE, >15	WD
PTP-18	1/4/2022	Dry	Dry	Dry	5,712.55	3.85	15.5-30.5	30.5	30.5	WD
PTP-18	4/4/2022 1/4/2022	Dry	Dry	Dry	5,712.55	3.85	15.5-30.5	30.5	30.5	WD WD
PTP-19 PTP-19	4/4/2022	Dry Dry	Dry Dry	Dry Dry	5,715.56 5,715.56	3.86 3.86	9.5-24.5 9.5-24.5	39	38.8 38.8	WD
PTP-20	1/4/2022	Dry	Dry	Dry	5,707.16	3.66	6-21	23.5	21	WD
PTP-20	4/4/2022	Dry	Dry	Dry	5,707.16	3.66	6-21	23.5	21	WD
PTP-20S	1/4/2022	Dry	Dry	Dry	5,706.15	2.65	NA		NA	WD
PTP-20S PTP-21	4/4/2022 1/4/2022	Dry 5,688.14	Dry 22.47	Dry 20.06	5,706.15 5,710.61	2.65 2.41	NA 7.5-22.5	22.5	NA 21	WD WD
PTP-21	4/4/2022	5,687.43	23.18	20.00	5,710.61	2.41	7.5-22.5	22.5	21	WD
PTP-22	1/4/2022	5,688.64	23.53	20.66	5,712.17	2.87	6-21	21	21	WD
PTP-22	4/4/2022	Dry	Dry	Dry	5,712.17	2.87	6-21	21	21	WD
PTP-22S	1/4/2022	Dry	Dry	Dry	5,711.50	2.20	7-12	12	NE, >12	WD
PTP-22S PTP-23	4/4/2022 1/3/2022	Dry 5,693.27	Dry 32.06	Dry 28.25	5,711.50 5,725.33	2.20 3.81	7-12 23-33	12 33	NE, >12 32	WD WD
PTP-23	4/4/2022	5,693.23	32.1	28.29	5,725.33	3.81	23-33	33	32	WD
PTP-24	1/3/2022	5,692.44	28.79	25.59	5,721.23	3.20	22-32	32	29.5	WD
PTP-24	4/4/2022	5,692.26	28.97	25.77	5,721.23	3.20	22-32	32	29.5	WD
PTP-25	1/4/2022	5,687.86	25.53	23.56	5,713.39	1.97	18.3-28.3	28.29	27	WD
PTP-25 PTP-26	4/4/2022 1/4/2022	5,687.78 5,689.21	25.61 35.38	23.64 32.48	5,713.39 5,724.59	1.97 2.90	18.3-28.3 24-34	28.29	27 34	WD WD
PTP-26	4/4/2022	5,689.09	35.5	32.46	5,724.59	2.90	24-34	34	34	WD
PTP-27	1/4/2022	5,693.99	33.55	30.85	5,727.54	2.70	24-34	34	34	WD
PTP-27	4/4/2022	5,693.88	33.66	30.96	5,727.54	2.70	24-34	34	34	WD
PTP-2F	1/4/2022	5,692.84	36.28	32.26	5,729.12	4.02	22.5-37.5	37.5	36	WD
PTP-2F PTP-3F	4/4/2022 1/4/2022	5,692.79 5,690.95	36.33 34.09	32.31 30.45	5,729.12 5,725.04	4.02 3.64	22.5-37.5 16.5-31.5	37.5 31.5	36 NE, >31.5	WD WD
PTP-3F	4/4/2022	5,690.89	34.09	30.43	5,725.04	3.64	16.5-31.5	31.5	NE, >31.5 NE, >31.5	WD
PTP-4C	1/4/2022	5,690.89	29.58	25.71	5,720.47	3.87	17-27	27.2	NE, >27.2	WD
PTP-4C	4/4/2022	5,690.84	29.63	25.76	5,720.47	3.87	17-27	27.2	NE, >27.2	WD
PTP-5A	1/4/2022	Dry	Dry	Dry	5,717.37	3.37	15-25	25	NE, >25	WD
PTP-5A PTP-6B	4/4/2022 1/3/2022	Dry 5,688.55	Dry 24.51	Dry 20.55	5,717.37 5,713.06	3.37	15-25 9-24	25 24	NE, >25 NE, >24	WD WD
PTP-6B	4/4/2022	5,688.54	24.51	20.56	5,713.06	3.96	9-24	24	NE, >24 NE, >24	WD
PTP-7H	1/3/2022	5,688.90	23.63	20.2	5,712.53	3.43	12.5-22.5	22.5	NE, >22.5	WD
•		l								

TABLE 4.2 WATER LEVEL ELEVATIONS

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

		Water-	Measured		Measuring					
		Surface	Depth to	Depth to	Point		Screened	Total	Base of	
		Elevation	Water	Water	Elevation	Stickup	Interval	Depth	Weathering	
	Date of		(ft below			•		ì	ņ	
Well ID	Measurement	(ft NGVD)a/	MP) ^{b/}	(ft bgs) ^{c/}	(ft NGVD)	(ft) ^{d/}	(ft bgs)	(ft bgs)	(ft bgs)	Formation ^{e/}
PTP-7H	4/4/2022	5,688.87	23.66	20.23	5,712.53	3.43	12.5-22.5	22.5	NE, >22.5	WD
PTP-8A	1/3/2022	5,689.72	28.14	25.18	5,717.86	2.96	16-26	26	NE, >26	WD
PTP-8A	4/4/2022	5,689.72	28.14	25.18	5,717.86	2.96	16-26	26	NE, >26	WD
PTP-9	1/3/2022	Dry	Dry	Dry	5,722.06	3.46	17-27	27	NE, >27	WD
PTP-9	4/4/2022	Dry	Dry	Dry	5,722.06	3.46	17-27	27	NE, >27	WD
PZ-101A	1/6/2022	5,679.88	146.32	144.02	5,826.20	2.30	314.6-325.1	328	48	LIGNITE
PZ-101A	4/8/2022	5,681.20	145	142.7	5,826.20	2.30	314.6-325.1	328	48	LIGNITE
PZ-103	1/6/2022	5,679.83	115.95	109.47	5,795.78	6.48	291.5-302	302.3	30	LIGNITE
PZ-103	4/8/2022	5,679.93	115.85	109.37	5,795.78	6.48	291.5-302	302.3	30	LIGNITE
RDPZ-102	1/6/2022	5,783.87	64.21	61.76	5,848.08	2.45	47.5-67	69.5	69.5	WD
RDPZ-102	4/8/2022	5,783.82	64.26	61.81	5,848.08	2.45	47.5-67	69.5	69.5	WD
SUMP	1/4/2022	5,685.74	27	27.9	5,712.74	-0.90	10-32.9	32.9		NO GEOLOGIC LOG
SUMP	4/4/2022	5,685.68	27.06	27.96	5,712.74	-0.90	10-32.9	32.9		NO GEOLOGIC LOG
T1-1	1/5/2022	5,674.68	3.59	1.52	5,678.27	2.07	7.5-17.5	17.5		ALLUVIUM
T1-1	4/11/2022	5,674.78	3.49	1.42	5,678.27	2.07	7.5-17.5	17.5		ALLUVIUM
T1-2	1/5/2022	5,675.33	9.69	6.37	5,685.02	3.32	10-20	20		WD
T1-2	4/11/2022	5,675.48	9.54	6.22	5,685.02	3.32	10-20	20		WD
T1-3	1/5/2022	5,675.59	3.87	0.41	5,679.46	3.46	6.4-16.4	16.4		WD
T1-3	4/11/2022	5,674.73	4.73	1.27	5,679.46	3.46	6.4-16.4	16.4		WD
T1-4	1/5/2022	5,676.16	3.93	0.54	5,680.09	3.39	4-14	14		WD
T1-4	4/11/2022	5,676.20	3.89	0.5	5,680.09	3.39	4-14	14		WD
T1-5	1/5/2022	5,677.38	15.32	11.92	5,692.70	3.40	14-24	24		WD
T1-5	4/11/2022	5,677.62	15.08	11.68	5,692.70	3.40	14-24	24	1	WD
TR-1	1/4/2022	Dry	Dry	Dry	5,706.65	1.72	8-18	18	NE, >18	WD
TR-1	4/4/2022	Dry	Dry	Dry	5,706.65	1.72	8-18	18	NE, >18	WD
U-518R-WD	1/13/2022	5,751.86	46.85	44.64	5,798.71	2.21	39.5 - 49.5	52.7	50.5	WD
U-518R-WD	4/7/2022	5,751.83	46.88	44.67	5,798.71	2.21	39.5 - 49.5	52.7	50.5	WD
U-701	1/3/2022	5,688.21	28.13	25.51	5,716.34	2.62	34-44	44	33.6	UNWD
U-701	4/4/2022	5,688.01	28.33	25.71	5,716.34	2.62	34-44	44	33.6	UNWD
U-701-WD	1/3/2022	Dry	Dry	Dry	5,716.24	2.23	12.7-22.7	22.7	34.9	WD
U-701-WD	4/4/2022	Dry	Dry	Dry	5,716.24	2.23	12.7-22.7	22.7	34.9	WD
WEST CLEANOUT	1/19/2022	Dry	Dry	Dry	5,772.41					NO GEOLOGIC LOG
WEST CLEANOUT	4/12/2022	Dry	Dry	Dry	5,772.41					NO GEOLOGIC LOG

a/ ft NGVD = elevation in feet referenced to the National Geodetic Vertical Datum of 1929.

ALLUVIUM = Alluvium of un-named creek.

FILL = imported soils - not native

LIGNITE = "Lignite zone" in Denver Formation

UNWD = Unweathered Dawson Formation

UPPER DENVER = Upper part of Denver Formation

WD = Weathered Dawson Formation

f/ NE = Base of weathering not encountered during drilling of boring

g/ -- or NA = Information not available at this time

b/ ft below MP = feet below measuring point

c/ ft bgs = feet below ground surface

d/ ft = feet

e/ Formation = formation or zone in which well screen is located. Formation/zone designations are as follow:

TABLE 4.3
SUMMARY OF VERTICAL HYDRAULIC GRADIENT CALCULATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

			1st Qua	rter 2021			2nd Qua	rter 2021	
Shallow Well	Deep Well	Measure Date	Head Difference a/ (ft)b/	Diff. in Saturated Screen Elev. c/ (ft)	Vertical Gradient ^{d/} (ft/ft)	Measure Date	Head Difference	Diff. in Saturated Screen Elev. (ft)	Vertical Gradient (ft/ft)
B-304	B-304-UD	1/4/2022	-9.42	35.81	-0.263	4/4/2022	-7.39	34.59	-0.214
B-305WD	B-305-R	1/3/2022	71.12	B-305WD D		4/4/2022	,,	B-305WD Dry	0.21
B-307	B-306	1/4/2022		B-307 Dry		4/4/2022		B-307 Dry	
B-313	B-313-UD	1/4/2022	-5.80	28.15	-0.206	4/4/2022	-4.45	27.40	-0.162
B-314	B-314-UD	1/4/2022	-7.81	31.57	-0.247	4/4/2022	-7.94	31.56	-0.252
B-316	B-316-UD	1/3/2022	-3.66	22.63	-0.162	4/4/2022	-2.98	22.36	-0.133
B-317	B-317-UD	1/3/2022	0.32	23.70	0.014	4/4/2022	0.68	23.50	0.029
B-326-WD	B-326-UD	1/4/2022	3.91	21.30	0.184	4/4/2022	3.95	21.20	0.186
B-327-WD	B-327-UD	1/3/2022	-2.76	29.70	-0.093	4/4/2022	-1.97	29.31	-0.067
B-712-UD	B-712-LD	1/19/2022	-6.52	43.40	-0.150	4/12/2022	-6.54	43.40	-0.151
BKGD-2WD	BKGD-2UD	1/18/2022	-39.40	21.87	-1.802	4/11/2022	-38.56	21.87	-1.763
BM-4X-50S	BM-4X-40S	1/6/2022	-8.05	29.10	-0.277	4/8/2022	-8.32	29.09	-0.286
BW-PZ-1	BW-PZ-1LC	1/4/2022	-4.67	16.30	-0.287	4/4/2022	-4.85	16.31	-0.297
C-702Q3	C-702P4	1/19/2022	0.68	18.10	0.038	4/12/2022	0.79	18.10	0.044
GW-107A	GW-107UD	1/3/2022	1.06	21.90	0.048	4/4/2022	0.91	21.90	0.042
GW-114A	GW-108A	1/4/2022	-8.46	33.57	-0.252	4/4/2022	-8.70	33.59	-0.259
MW-1000	MW-1000LC	1/4/2022		MW-1000 D	y	4/4/2022		MW-1000 Dry	
MW33-WDR	MW33-UD	1/6/2022	N	AW33-WDR	Ory	4/8/2022	N	MW33-WDR Dry	
MW36-WDR	MW36-UD	1/6/2022	-4.01	24.70	-0.162	4/8/2022	-3.69	24.70	-0.149
MW37-WD	MW37-UD	1/3/2022	3.46	14.68	0.236	4/4/2022	3.56	14.66	0.243
MW38-1064N-650E	MW38-1064N-655E	1/17/2022	-8.15	18.06	-0.451	4/6/2022	-7.48	17.42	-0.429
MW38-1373N-180W	MW38-1363N-180W	1/17/2022	1.36	29.65	0.046	4/6/2022	1.16	29.59	0.039
MW38-350S-50W	MW38-302S-50W	1/18/2022	-3.80	8.55	-0.444	4/6/2022	-3.67	8.49	-0.433
MW38-400N-180W	MW38-410N-180W	1/17/2022	-38.54	36.06	-1.069	4/6/2022	-37.63	35.89	-1.049
MW38-400N-240E	MW38-400N-300E	1/17/2022	-20.55	32.30	-0.636	4/6/2022	-20.20	32.24	-0.627
MW39-WD	MW39-UD	1/6/2022	-21.98	30.51	-0.720	4/8/2022	-21.93	30.44	-0.720
MW42-WD	MW42-UD	1/6/2022	-2.98	34.10	-0.087	4/8/2022	-2.74	33.90	-0.081
MW49-WD	B-519	1/6/2022	0.54	29.20	0.018	4/8/2022	0.52	29.20	0.018
MW51-WD	MW51-10S	1/13/2022	-0.77	15.38	-0.050	4/7/2022	-0.80	15.39	-0.052
MW51X-WD-100S	B-518	1/13/2022	7.43	38.00	0.196	4/7/2022	7.61	38.00	0.200
MW52-WD	MW52-UD	1/13/2022	-3.44	37.95	-0.091	4/7/2022	-3.01	37.82	-0.080
MW54-WD	MW54-UDR	1/13/2022	0.06	28.28	0.002	4/7/2022	-0.16	28.42	-0.006
MW62-WDR	MW62-UD	1/3/2022	-6.63	31.72	-0.209	4/4/2022	-6.42	31.61	-0.203
MW71-WD	MW71-UD	1/13/2022	0.64	46.31	0.014	4/7/2022	0.65	46.38	0.014
MW72-WD	MW72-UD	1/13/2022	-3.14	36.10	-0.087	4/7/2022	-3.00	36.10	-0.083
MW73-WD	MW73-UD	1/4/2022	-4.06	40.80	-0.100	4/4/2022	-4.90	41.34	-0.119

TABLE 4.3 SUMMARY OF VERTICAL HYDRAULIC GRADIENT CALCULATIONS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE

		1st Quarter 2021 2nd Quarter 2021							
Shallow Well	Deep Well	Measure Date	Head Difference a/ (ft)b/	Diff. in Saturated Screen Elev. c/ (ft)	Vertical Gradient ^{d/} (ft/ft)	Measure Date	Head Difference (ft)	Diff. in Saturated Screen Elev. (ft)	Vertical Gradient (ft/ft)
MW74-WD	MW74-UD	1/17/2022	-3.75	34.70	-0.108	4/6/2022	-3.88	34.70	-0.112
MW75-WD	MW75-UD	1/17/2022	-14.91	44.09	-0.338	4/6/2022	-12.98	44.09	-0.294
MW76-WD	MW76-UD	1/17/2022	-21.13	42.00	-0.503	4/6/2022	-22.26	42.00	-0.530
MW77-WD	MW77-UD	1/3/2022	-4.65	34.42	-0.135	4/5/2022	-4.99	34.61	-0.144
MW78-WD	MW78-UD	1/13/2022	0.39	32.69	0.012	4/7/2022	0.26	32.71	0.008
MW79-WD	MW79-UD	1/13/2022	-0.47	34.70	-0.014	4/7/2022	-0.40	34.70	-0.012
MW91-WD	MW91-UD	1/13/2022	-1.17	43.50	-0.027	4/7/2022	-1.34	43.50	-0.031
MW93-WD	MW93-UD	1/13/2022	1.96	21.71	0.090	4/7/2022	2.28	21.76	0.105
MW-EW-1	MW-EW-1LC	1/3/2022	-2.46	17.22	-0.143	4/4/2022	-2.42	17.17	-0.141
MW-EW-1	MW-EW-1LCRA	1/3/2022	-6.99	38.32	-0.182	4/4/2022	-7.03	38.27	-0.184
MW-EW-2	MW-EW-2LC	1/3/2022	-1.90	16.26	-0.117	4/4/2022	-1.78	16.14	-0.110
NTES-EW1	B-712-UD	1/19/2022	-1.65	24.40	-0.068	4/12/2022	-1.49	24.40	-0.061
BM-15I-15N	PM-15I-UD	1/14/2022	10.25	20.26	0.506	4/7/2022	10.22	20.27	0.504
U-701-WD	U-701	1/3/2022		U-701-WD D	ry	4/4/2022		U-701-WD Dry	

a/ The midpoint of the saturated portion of the screen interval is used to calculate the vertical distance between well pairs.

Highlighted cells indicate upward gradients

b/ ft = feet

c/ Groundwater elevations are presented in Table 4.2.

d/ A negative value indicates a downward gradient and a positive value indicates an upward gradients.

TABLE 4.4
GROUNDWATER SAMPLING ACTIVITIES
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Sample ID	Sample Type	Location a/	Water-Bearing Unit ^{b/}	Sampling Frequency ^{c/}	Date of Last Sample Collection ^{d/}	1st Quarter 2022	2nd Quarter 2022	3rd Quarter 2022 ^{e/}	4th Quarter 2022 ^{e/}
B-313	Compliance/Effectiveness/B-326-UD & B-313 RAWP ^{f/}	NB	WD	Semi-annual (Compliance)/Quarterly (RAWP & North End Monitoring)	11/16/2021	DRY	DRY	X	X
B-313-UD	Compliance	NB	UNWD	Biennial	12/7/2020			X	
B-314	Compliance/Effectiveness	NB	WD	Semi-annual	4/13/2022		4/13/2022		X
B-314-UD	Compliance	NB	UNWD	Biennial	8/5/2020			X	
B-321	B-326-UD & B-313 RAWP	NB	WD	Quarterly	8/30/2021	DRY	DRY	X	X
B-326-UD	Compliance/B-326-UD & B-313 RAWP/North End Monitoring/Molybdenum Investigation	NB	UNWD	Biennial (Compliance)/Quarterly (RAWP, North End Monitoring & Molybdenum Investigation)	4/14/2022	2/8/2022	4/14/2022	X	X
B-326-WD	Compliance/Effectiveness/North End Monitoring/Molybdenum Investigation	NB	WD	(Compliance)/Quarterly (North End Monitoring & Molybdenum	4/14/2022	2/8/2022	4/14/2022	X	X
B-327-UD	Compliance	NB	UNWD	Biennial	8/26/2020			X	
B-712-LD	Compliance	INT	UNWD	Biennial	9/2/2020			X	
BM-11X-100N	Compliance/Effectiveness	EB	WD	Semi-annual	5/18/2022		5/18/2022		X
BM-11X-100S	Compliance/Effectiveness	EB	WD	Semi-annual	5/18/2022		5/18/2022		X
BM-15E2	Compliance	EB	WD	Semi-annual	4/26/2022		4/26/2022		X
BM-15N6	Compliance/Effectiveness	EB	WD	Semi-annual	4/25/2022		4/25/2022		X
GW-106	Compliance	NB	WD	Semi-annual	4/18/2022		4/18/2022		X
GW-108A	Compliance	NB	UNWD	Biennial	8/19/2020			X	
GW-109	Compliance	NB	WD	Semi-annual	6/1/2020		DRY		X
MNA-01	Effectiveness	INT	WD	Semi-annual	5/19/2022		5/19/2022		X
MNA-03	Effectiveness	INT	WD	Semi-annual	5/19/2022		5/19/2022		X
MW05-WD	North End Monitoring	NE	WD	Semi-annual	3/1/2022	3/1/2022		X	
MW102-WD	North End Monitoring	NB	WD	Quarterly	4/28/2022	1/24/2022	4/28/2022	X	X
MW103-WD	North End Monitoring	NE	WD	Quarterly	5/9/2022	2/7/2022	5/9/2022	X	X
MW105-WD	Compliance	EB	WD	Semi-annual	4/20/2022		4/20/2022		X
MW106-UD	Compliance	EB	UNWD	Biennial	8/26/2020			X	
MW107-UD	Compliance	EB	UNWD	Biennial	8/20/2020			X	
MW108-WD	Compliance	EB	WD	Semi-annual	4/21/2022		4/21/2022		X
MW113-EW-1	North End Monitoring/Molybdenum Investigation	NE	WD	Quarterly	4/19/2022	1/25/2022	4/19/2022	X	X
MW113-UD	North End Monitoring/Molybdenum Investigation	NE	UNWD	Quarterly (RAWP & North End Monitoring)/Monthly (Molybdenum Investigation)	6/15/2022	1/25/2022 2/8/2022 3/8/2022	4/5/2022 5/17/2022 6/15/2022	X	X

TABLE 4.4
GROUNDWATER SAMPLING ACTIVITIES
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Sample ID	Sample Type	Location a/	Water-Bearing Unit ^{b/}	Sampling Frequency ^{c/}	Date of Last Sample Collection ^{d/}	1st Quarter 2022	2nd Quarter 2022	3rd Quarter 2022 ^{e/}	4th Quarter 2022 ^{e/}
MW113-WD	Molybdenum Investigation	NE	WD	Bi-weekly	6/29/2022	1/11/2022 1/25/2022 2/8/2022 2/22/2022 3/8/2022 3/22/2022	4/5/2022 4/19/2022 5/3/2022 5/17/2022 6/7/2022 6/15/2022 6/29/2022	X	X
MW114-WD	North End Monitoring	NE	WD	Quarterly	5/9/2022	1/20/2022	5/9/2022	X	X
MW117-WD	North End Monitoring	NE	WD	Quarterly	5/9/2022	1/20/2022	5/9/2022	X	X
MW118-WD	North End Monitoring	NE	WD	Quarterly	5/9/2022	1/20/2022	5/9/2022	X	X
MW121-WDR	North End Monitoring	NE	WD	Semi-annual	1/26/2022	1/26/2022		X	
MW122-WDR	North End Monitoring	NE	WD	Semi-annual	1/26/2022	1/26/2022		X	
MW123-WD	North End Monitoring	NE	WD	Semi-annual	1/26/2022	1/26/2022		X	
MW124-WD	North End Monitoring	NE	WD	Semi-annual	1/27/2022	1/27/2022		X	<u> </u>
MW125-WD	North End Monitoring	NE	WD	Semi-annual	1/27/2022	1/27/2022		X	<u> </u>
MW129-WD	North End Monitoring	NE	WD	Semi-annual	2/28/2022	2/28/2022		X	
MW132-WD	North End Monitoring	NE	WD	Quarterly	5/10/2022	1/31/2022	5/10/2022	X	X
MW135-WD	North End Monitoring	NE	WD	Semi-annual	2/23/2022	2/23/2022		X	
MW141-WD	North End Monitoring	NE	WD	Semi-annual	2/15/2022	2/15/2022		X	
MW142-WD	North End Monitoring	NE	WD	Semi-annual	2/23/2022	2/23/2022		X	
MW144-WD	North End Monitoring	NE	WD	Semi-annual	2/15/2022	2/15/2022		X	
MW151-WD	North End Monitoring	NE	WD	Quarterly	5/16/2022	1/31/2022	5/16/2022	X	X
MW153-EW-1	North End Monitoring	NE	WD	Quarterly	4/27/2022	1/27/2022	4/27/2022	X	X
MW154-EW-1	North End Monitoring	NE	WD	Quarterly	4/28/2022	1/27/2022	4/28/2022	X	X
MW155-EW-1	North End Monitoring	NE	WD	Quarterly	5/2/2022	1/31/2022	5/2/2022	X	X
MW156-EW-1	North End Monitoring	NE	WD	Quarterly	5/2/2022	2/9/2022	5/2/2022	X	X
MW156-WD	North End Monitoring	NE	WD	Quarterly	5/16/2022	2/10/2022	5/16/2022	X	X
MW157-WD	North End Monitoring	NE	WD	Quarterly	5/16/2022	2/10/2022	5/16/2022	X	X
MW160-WD	North End Monitoring	NE	WD	Quarterly	4/26/2022	1/31/2022	4/26/2022	X	X
MW170-EW-1	RAWP/MW77 Response Action/Molybdenum Investigation	EB	WD	Quarterly	5/10/2022	1/25/2022	5/10/2022	X	X
MW176-DEN	North End Monitoring	NE	Upper Denver	Semi-annual	2/15/2022	2/15/2022		X	
MW179-UDEN	North End Monitoring	NE	UNWEATHERED DENVER	Semi-annual	3/1/2022	3/1/2022		X	
MW23-C-SD	Compliance	EB	UNWD	Biennial	2/18/2021			X	
MW23-UPPER-C	Compliance	EB	WD	Semi-annual	4/20/2022		4/20/2022		X

TABLE 4.4
GROUNDWATER SAMPLING ACTIVITIES
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Sample ID	Sample Type	Location a/	Water-Bearing Unit ^{b/}	Sampling Frequency ^{c/}	Date of Last Sample Collection ^{d/}	1st Quarter 2022	2nd Quarter 2022	3rd Quarter 2022 ^{e/}	4th Quarter 2022 ^{e/}
MW36-WDR	Compliance	WB	WD	Semi-annual	5/10/2022		5/10/2022		X
MW38-1028N-256E	MW38 Source Control	WB	WD	Semi-annual	4/27/2022		4/27/2022		X
MW38-170S-140W	MW38 Source Control	WB	WD	Semi-annual	4/27/2022		4/27/2022		X
MW38-825S-445E	MW38 Source Control	WB	WD	Semi-annual	4/27/2022		4/27/2022		X
MW38-830N-230E	Compliance	WB	WD	Semi-annual	4/13/2022		4/13/2022		X
MW42-UD	Compliance	WB	UNWD	Biennial	8/31/2020			X	
MW43-WD	Compliance	WB	WD	Semi-annual	4/26/2022		4/26/2022		X
MW54-WD	Compliance	EB	WD	Semi-annual	4/18/2022		4/18/2022		X
MW60-WD	Compliance	EB	WD	Semi-annual	4/26/2022		4/26/2022		X
MW62-WDR	Compliance/Effectiveness	NB	WD	Semi-annual	4/19/2022		4/19/2022		X
MW70-WD	VES Performance	EB	WD	Semi-annual	5/3/2022		5/3/2022		X
MW71-WD	Compliance	EB	WD	Semi-annual	4/19/2022		4/19/2022		X
MW72-UD	Compliance	EB	UNWD	Biennial	8/20/2020			X	
MW74-WD	Compliance	NB	WD	Semi-annual	4/13/2022		4/13/2022		X
MW74-UD	Compliance	NB	UNWD	Biennial	8/6/2020			X	
MW76-UD	Compliance	NB	UNWD	Biennial	8/13/2020			X	
MW77-EW-1	North End Monitoring	EB	WD	Quarterly	4/28/2022	1/24/2022	4/28/2022	X	X
MW77-EW-2	North End Monitoring	EB	WD	Quarterly	4/28/2022	1/24/2022	4/28/2022	X	X
MW77-WD	Compliance	EB	WD	Semi-annual	4/18/2022		4/18/2022		X
MW78-WD	Compliance	EB	WD	Semi-annual	4/18/2022		4/18/2022		X
MW78-UD	Compliance	EB	UNWD	Biennial	2/23/2021			X	
MW90-WD	Compliance	EB	WD	Semi-annual	5/17/2022		5/17/2022		X
MW90-UD	Compliance	EB	UNWD	Biennial	5/18/2020			X	
MW91-WD	Compliance	EB	WD	Semi-annual	5/3/2022		5/3/2022		X
MW91-UD	Compliance	EB	UNWD	Biennial	8/13/2020			X	
MW98-WD	North End Monitoring	NB	WD	Quarterly	4/28/2022	1/24/2022	4/28/2022	X	X
NBBW-IW-3 ^{g/}	Molybdenum Investigation	NB	WD	Quarterly	8/5/2021	DRY	DRY	X	X
PM-13X	Effectiveness	EB	WD	Semi-annual	5/5/2022		5/5/2022		X
PM-14X	Compliance/Effectiveness	EB	WD	Semi-annual	4/21/2022		4/21/2022		X
PM-3X	Effectiveness	WB	WD	Semi-annual	5/5/2022		5/5/2022		X
PM-6X	Effectiveness	SB	WD	Semi-annual	5/5/2022		5/5/2022		X
PM-6X-UD	Compliance	SB	UNWD	Biennial	9/9/2020			X	
Private Well 1	Homeownwer Well	NE	Upper Denver	Annual	6/7/2022		6/7/2022		
Private Well 2	Homeownwer Well	NE	Denver	Annual	6/7/2022		6/7/2022		
PTP-11	Molybdenum Investigation	NB	WD	Quarterly	5/11/2022	2/7/2022	5/11/2022	X	X

TABLE 4.4

GROUNDWATER SAMPLING ACTIVITIES

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Sample ID	Sample Type	Location a/	Water-Bearing Unit ^{b/}	Sampling Frequency ^{c/}	Date of Last Sample Collection ^{d/}	1st Quarter 2022	2nd Quarter 2022	3rd Quarter 2022 ^{e/}	4th Quarter 2022 ^{e/}
PTP-12	North End Monitoring/Molybdenum Investigation	NB	WD	Quarterly	5/11/2022	2/7/2022 2/14/2022	5/11/2022	X	X
PTP-13	North End Monitoring/Molybdenum Investigation	NB	WD	Quarterly	5/12/2022	3/1/2022	5/12/2022	X	X
PTP-14	North End Monitoring/Molybdenum Investigation	NB	WD	Quarterly	6/2/2020	DRY	DRY	X	X
U-518R-WD	Compliance	EB	WD	Semi-annual	4/21/2022		4/21/2022		X

a/ Location = geographic location at the site

EB = East Boundary

WB = West Boundary

SB = South Boundary

INT = Interior

NB = North Boundary

NE = North End

NT = North Toe

EXT-S = Exterior South

b/ Water-bearing unit = formation or zone in which well screen is located

Formation/zone designations are as follow:

Alluvium = Alluvium

WD = Weathered Dawson Formation

UNWD = Unweathered Dawson Formation

DEN = Upper part of Denver Formation

UDEN = Unweathered Denver Formation Lignite = "Lignite zone" in Denver Formation c/ Represents frequency for long term monitoring.

d/ Last sampling date - may be for 1,4-dioxane only or for full contaminant of concern list

e/ An "x" indicates that the well is scheduled to be sampled during the 3rd and/or 4th quarter of 2022

f/ RAWP = Response Action Work Plan

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

W-II ID	Constituent/Powers	Data Servel	Da14	Qualifier ^{a/}	Units ^{b/}	Donoutin - I in '
Well ID B-314	Constituent/Parameter 1,1-Dichloroethane	4/13/2022	Result	Quanner	μg/L	Reporting Limit
B-314 B-314	Nitrogen, Nitrate	4/13/2022	890		μg/L μg/L	500
B-326-UD	1,4-Dioxane	2/8/2022	4.5	_	μg/L μg/L	0.9
B-326-UD	1,4-Dioxane	4/14/2022	4.6	_	μg/L μg/L	0.9
B-326-UD	Molybdenum, Dissolved	2/8/2022	4.7	J	μg/L μg/L	20
B-326-UD	Molybdenum, Dissolved	4/14/2022	6	J	μg/L μg/L	20
B-326-WD	1,4-Dioxane	2/8/2022	3.6	J	μg/L μg/L	0.9
B-326-WD	1,4-Dioxane	4/14/2022	3.2	_	μg/L μg/L	0.9
B-326-WD	Cadmium	4/14/2022	0.54	J	μg/L μg/L	5
B-326-WD	Molybdenum, Dissolved	2/8/2022	120	, ,		20
B-326-WD	Molybdenum, Dissolved	4/14/2022	100		μg/L	20
B-326-WD	Nitrogen, Nitrate	4/14/2022	360	J	μg/L	500
BM-11X-100N	1,1-Dichloroethane	5/18/2022	29	J	μg/L	1
BM-11X-100N	1,4-Dioxane	5/18/2022	0.1	J	μg/L	0.9
	Cadmium	5/18/2022		J	μg/L	5
BM-11X-100N BM-11X-100N		5/18/2022	0.43	J	μg/L	
	Chloroform	5/18/2022	1.1 12000		μg/L	1
BM-11X-100N	Nitrogen, Nitrate			¥	μg/L	2500
BM-11X-100N	Nitrogen, Nitrite	5/18/2022	400	J	μg/L	500
BM-11X-100N	Tetrachloroethene Trichloroethene	5/18/2022 5/18/2022	4.9	_	μg/L	1
BM-11X-100N	1,1-Dichloroethane				μg/L	1
BM-11X-100S	· ·	5/18/2022	4.8	¥	μg/L	1
BM-11X-100S	1,1-Dichloroethene	5/18/2022	0.63	J	μg/L	1
BM-11X-100S	Arsenic	5/18/2022	4.8	J	μg/L	15
BM-11X-100S	Cadmium	5/18/2022	0.58	J	μg/L	5
BM-11X-100S	Chloroform	5/18/2022	1.2		μg/L	1
BM-11X-100S	Nitrogen, Nitrate	5/18/2022	11000	_	μg/L	2500
BM-11X-100S	Nitrogen, Nitrite	5/18/2022	400	J	μg/L	500
BM-11X-100S	Tetrachloroethene	5/18/2022	1.2		μg/L	1
BM-11X-100S	Trichloroethene	5/18/2022	1.3		μg/L	1
BM-15E2	1,1-Dichloroethane	4/26/2022	1.5		μg/L	1
BM-15E2	Nitrogen, Nitrate	4/26/2022	18000		μg/L	5000
BM-15N6	1,1-Dichloroethane	4/25/2022	1.6		μg/L	1
BM-15N6	Nitrogen, Nitrate	4/25/2022	34000		μg/L	5000
BM-15N6	Tetrachloroethene	4/25/2022	2		μg/L	1
GW-106	Nitrogen, Nitrate	4/18/2022	5600		μg/L	500
M105-WD	Nitrogen, Nitrate	4/20/2022	220	J	μg/L	500
MNA-01	1,1-Dichloroethane	5/19/2022	59		μg/L	10
MNA-01	1,2-Dichloroethane	5/19/2022	27		μg/L	10
MNA-01	1,4-Dioxane	5/19/2022	8600		μg/L	2000
MNA-01	Benzene	5/19/2022	8.6	J	μg/L	10
MNA-01	Cadmium	5/19/2022	0.65	J	μg/L	5
MNA-03	1,1-Dichloroethane	5/19/2022	120		μg/L	4
MNA-03	1,2-Dichloroethane	5/19/2022	3.1	J	μg/L	4
MNA-03	1,4-Dioxane	5/19/2022	3600		μg/L	800
MNA-03	Arsenic	5/19/2022	6.8	J	μg/L	15
MNA-03	Benzene	5/19/2022	23		μg/L	4

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Wall ID	Constituent/D	Data Carrell	D14	Qualifier ^{a/}	Units ^{b/}	Domestin T.
Well ID MNA-03	Constituent/Parameter Cadmium	Date Sampled 5/19/2022	Result 0.58	J		Reporting Limit 5
MNA-03	Ethylbenzene	5/19/2022	0.38	J	μg/L μg/L	4
MNA-03	Toluene	5/19/2022	1	J		4
MNA-03	Trans-1,2-Dichloroethene	5/19/2022	0.66	J	μg/L	2
MW05-WD	1,4-Dioxane	3/1/2022	3.6	J	μg/L	0.9
MW102-WD	1,4-Dioxane	1/24/2022	0.92		μg/L	0.9
	<u> </u>	4/28/2022	1.2		μg/L	0.9
MW102-WD	1,4-Dioxane		0.35	J	μg/L	0.9
MW103-WD	1,4-Dioxane	2/7/2022			μg/L	
MW103-WD	1,4-Dioxane	5/9/2022	0.27	J	μg/L	0.9
MW108-WD	Cadmium	4/21/2022	0.55	J	μg/L	5
MW108-WD	Chloroform	4/21/2022	0.46	J	μg/L	1
MW108-WD	Nitrogen, Nitrate	4/21/2022	10000		μg/L	2500
MW113-EW-1	1,4-Dioxane	1/25/2022	99		μg/L	0.9
MW113-EW-1	1,4-Dioxane	4/19/2022	89		μg/L	0.9
MW113-EW-1	Molybdenum, Dissolved	4/19/2022	6500		μg/L	20
MW113-EW-1	Molybdenum, Total	4/19/2022	6400		μg/L	20
MW113-EW-1	Nitrogen, Nitrate	1/25/2022	210	J	μg/L	500
MW113-EW-1	Nitrogen, Nitrate	4/19/2022	150	J	μg/L	500
MW113-UD	1,4-Dioxane	1/25/2022	59		μg/L	0.9
MW113-UD	1,4-Dioxane	5/17/2022	57		μg/L	0.9
MW113-UD	Molybdenum, Dissolved	1/25/2022	830		μg/L	20
MW113-UD	Molybdenum, Dissolved	2/8/2022	770		μg/L	20
MW113-UD	Molybdenum, Dissolved	3/8/2022	740		μg/L	20
MW113-UD	Molybdenum, Dissolved	4/5/2022	780		μg/L	20
MW113-UD	Molybdenum, Dissolved	5/17/2022	680		μg/L	20
MW113-UD	Molybdenum, Dissolved	6/15/2022	640		μg/L	20
MW113-UD	Molybdenum, Total	1/25/2022	700		$\mu g/L$	20
MW113-UD	Molybdenum, Total	2/8/2022	740		μg/L	20
MW113-UD	Molybdenum, Total	3/8/2022	770		μg/L	20
MW113-UD	Molybdenum, Total	4/5/2022	800		μg/L	20
MW113-UD	Molybdenum, Total	5/17/2022	750		μg/L	20
MW113-UD	Molybdenum, Total	6/15/2022	650		μg/L	20
MW113-WD	1,4-Dioxane	5/3/2022	36		μg/L	0.9
MW113-WD	Molybdenum, Dissolved	1/11/2022	23000		μg/L	200
MW113-WD	Molybdenum, Dissolved	1/25/2022	21000		μg/L	200
MW113-WD	Molybdenum, Dissolved	2/8/2022	27000		μg/L	200
MW113-WD	Molybdenum, Dissolved	2/22/2022	25000		μg/L	200
MW113-WD	Molybdenum, Dissolved	3/8/2022	24000		μg/L	200
MW113-WD	Molybdenum, Dissolved	3/22/2022	30000		μg/L	200
MW113-WD	Molybdenum, Dissolved	4/5/2022	32000		μg/L	200
MW113-WD	Molybdenum, Dissolved	4/19/2022	31000		μg/L	200
MW113-WD	Molybdenum, Dissolved	5/3/2022	29000		μg/L	200
MW113-WD	Molybdenum, Dissolved	5/17/2022	29000		μg/L	200
MW113-WD	Molybdenum, Dissolved	6/7/2022	35000		μg/L	200
MW113-WD	Molybdenum, Dissolved	6/15/2022	31000		μg/L	200
MW113-WD	Molybdenum, Dissolved	6/29/2022	34000		μg/L	200

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
MW113-WD	Molybdenum, Total	1/11/2022	23000	Quanner	μg/L	200
MW113-WD	Molybdenum, Total	1/25/2022	22000		μg/L	200
MW113-WD	Molybdenum, Total	2/8/2022	26000		μg/L μg/L	200
MW113-WD	Molybdenum, Total	2/22/2022	24000		μg/L μg/L	200
MW113-WD	Molybdenum, Total	3/8/2022	27000		μg/L μg/L	200
MW113-WD	Molybdenum, Total	3/22/2022	29000			200
	Molybdenum, Total	4/5/2022	32000		μg/L	200
MW113-WD	Molybdenum, Total	4/3/2022	33000		μg/L	200
MW113-WD	•				μg/L	
MW113-WD	Molybdenum, Total	5/3/2022	32000		μg/L	200
MW113-WD	Molybdenum, Total	5/17/2022	31000		μg/L	200
MW113-WD	Molybdenum, Total	6/7/2022	33000		μg/L	200
MW113-WD	Molybdenum, Total	6/15/2022	32000		μg/L	200
MW113-WD	Molybdenum, Total	6/29/2022	34000		μg/L	200
MW114-WD	1,4-Dioxane	1/20/2022	0.96	_	μg/L	0.9
MW114-WD	1,4-Dioxane	5/9/2022	0.89	J	μg/L	0.9
MW117-WD	1,4-Dioxane	1/20/2022	1.3		μg/L	0.9
MW117-WD	1,4-Dioxane	5/9/2022	1.2		μg/L	0.9
MW118-WD	1,4-Dioxane	1/20/2022	0.28	J	μg/L	0.9
MW118-WD	1,4-Dioxane	5/9/2022	0.22	J	μg/L	0.9
MW121-WDR	1,4-Dioxane	1/26/2022	0.77	J	μg/L	0.9
MW122-WDR	1,4-Dioxane	1/26/2022	1.9		μg/L	0.9
MW123-WD	1,4-Dioxane	1/26/2022	1.7		μg/L	0.9
MW124-WD	1,4-Dioxane	1/27/2022	0.48	J	$\mu g/L$	0.9
MW125-WD	1,4-Dioxane	1/27/2022	0.34	J	μg/L	0.9
MW129-WD	1,4-Dioxane	2/28/2022	4.7		μg/L	0.9
MW132-WD	1,4-Dioxane	1/31/2022	15		μg/L	0.9
MW132-WD	1,4-Dioxane	5/10/2022	10		μg/L	0.9
MW135-WD	1,4-Dioxane	2/23/2022	5.1		μg/L	0.9
MW141-WD	1,4-Dioxane	2/15/2022	2.2		μg/L	0.9
MW142-WD	1,4-Dioxane	2/23/2022	1.4		μg/L	0.9
MW151-WD	1,4-Dioxane	1/31/2022	4.8		μg/L	0.9
MW151-WD	1,4-Dioxane	5/16/2022	1.8		μg/L	0.9
MW153-EW-1	1,4-Dioxane	1/27/2022	3.3		μg/L	0.9
MW153-EW-1	1,4-Dioxane	4/27/2022	2.3		μg/L	0.9
MW154-EW-1	1,4-Dioxane	1/27/2022	1.7		μg/L	0.9
MW154-EW-1	1,4-Dioxane	4/28/2022	2.6		μg/L	0.9
MW155-EW-1	1,4-Dioxane	1/31/2022	0.49	J	μg/L	0.9
MW155-EW-1	1,4-Dioxane	5/2/2022	1.5	-	μg/L	0.9
MW156-EW-1	1,4-Dioxane	2/9/2022	0.45	J	μg/L	0.9
MW156-EW-1	1,4-Dioxane	5/2/2022	0.43	J	μg/L μg/L	0.9
MW156-WD	1,4-Dioxane	2/10/2022	0.19	J	μg/L μg/L	0.9
MW156-WD	1,4-Dioxane	5/16/2022	0.19	J	μg/L μg/L	0.9
MW160-WD	1,4-Dioxane	1/31/2022	3.7	J		0.9
	1,4-Dioxane		2.9		μg/L	
MW160-WD	1,1,1-Trichloroethane	4/26/2022			μg/L	0.9
MW170-EW-1	1 1	1/25/2022	1.8		μg/L	1
MW170-EW-1	1,1,1-Trichloroethane	5/10/2022	1.3		μg/L	1

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

				2/	b /	
Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
MW170-EW-1	1,1-Dichloroethane	1/25/2022	3.7		μg/L	1
MW170-EW-1	1,1-Dichloroethane	5/10/2022	3.3		μg/L	1
MW170-EW-1	1,1-Dichloroethene	1/25/2022	3		μg/L	1
MW170-EW-1	1,1-Dichloroethene	5/10/2022	2.4		μg/L	1
MW170-EW-1	1,4-Dioxane	1/25/2022	14		μg/L	0.9
MW170-EW-1	1,4-Dioxane	5/10/2022	11		μg/L	0.9
MW170-EW-1	Acetone	5/10/2022	4.4	J	μg/L	10
MW170-EW-1	Cadmium	5/10/2022	0.31	J	μg/L	5
MW170-EW-1	cis-1,2-Dichloroethene	1/25/2022	9		μg/L	1
MW170-EW-1	cis-1,2-Dichloroethene	5/10/2022	8.2		μg/L	1
MW170-EW-1	Molybdenum, Dissolved	1/25/2022	1.3	J	μg/L	20
MW170-EW-1	Molybdenum, Total	1/25/2022	1.4	J	μg/L	20
MW170-EW-1	Nitrogen, Nitrate	1/25/2022	11000		μg/L	2500
MW170-EW-1	Nitrogen, Nitrate	5/10/2022	9700		μg/L	5000
MW170-EW-1	Tetrachloroethene	1/25/2022	1.2		μg/L	1
MW170-EW-1	Tetrachloroethene	5/10/2022	0.7	J	μg/L	1
MW170-EW-1	Trichloroethene	1/25/2022	0.49	J	μg/L	1
MW170-EW-1	Trichloroethene	5/10/2022	0.51	J	μg/L	1
MW176-DEN	1,4-Dioxane	2/15/2022	0.52	J	μg/L	0.9
MW179-UDEN	Molybdenum, Dissolved	3/1/2022	10	J	μg/L	20
MW23-UPPER-C	Nitrogen, Nitrate	4/20/2022	120	J	μg/L	500
MW23-UPPER-C	Nitrogen, Nitrite	4/20/2022	340	J	μg/L	500
MW36-WDR	Cadmium	5/10/2022	0.5	J	μg/L	5
MW36-WDR	Nitrogen, Nitrate	5/10/2022	18000		μg/L	5000
MW38-1028N-256E	1,1-Dichloroethane	4/27/2022	1.9		μg/L	1
MW38-1028N-256E	1,2-Dichloroethene	4/27/2022	0.55	J	μg/L	1
MW38-1028N-256E	1,4-Dioxane	4/27/2022	2		μg/L	0.9
MW38-1028N-256E	Bromodichloromethane	4/27/2022	0.29	J	μg/L	1
MW38-1028N-256E	Chloroform	4/27/2022	1.9		μg/L	1
MW38-1028N-256E	cis-1,2-Dichloroethene	4/27/2022	0.55	J	μg/L	1
MW38-1028N-256E	Tetrachloroethene	4/27/2022	0.46	J	μg/L	1
MW38-1028N-256E	Trichloroethene	4/27/2022	1		μg/L	1
MW38-170S-140W	1,1-Dichloroethane	4/27/2022	17		μg/L	1
MW38-170S-140W	1,2-Dichloroethene	4/27/2022	5.7		μg/L	1
MW38-170S-140W	1,4-Dioxane	4/27/2022	29		μg/L	0.9
MW38-170S-140W	1,4-Dioxane	4/27/2022	30		μg/L	20
MW38-170S-140W	Chloroform	4/27/2022	5.4		μg/L	1
MW38-170S-140W	cis-1,2-Dichloroethene	4/27/2022	5.7		μg/L	1
MW38-170S-140W	Dichlorodifluoromethane	4/27/2022	0.56	J	μg/L μg/L	2
MW38-170S-140W	Tetrachloroethene	4/27/2022	1.3	,	μg/L μg/L	1
MW38-170S-140W	Tetrahydrofuran	4/27/2022	2.6	J	μg/L μg/L	7
MW38-170S-140W	Trichloroethene	4/27/2022	3.9	J	μg/L μg/L	1
MW38-825S-445E	1,1-Dichloroethane	4/27/2022	2500		μg/L μg/L	400
MW38-825S-445E	1,1-Dichloroethene	4/27/2022	420		μg/L μg/L	400
	1,1-Dichioloculcuc	7/2//2022	720		μg/L	+00
MW38-825S-445E	1,2-Dichloroethane	4/27/2022	37000		μg/L	400

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
MW38-825S-445E	1,3-Dichlorobenzene	4/27/2022	76	J	μg/L	400
MW38-825S-445E	1,4-Dichlorobenzene	4/27/2022	390	J	μg/L	400
MW38-825S-445E	1,4-Dioxane	4/27/2022	2800		μg/L	90
MW38-825S-445E	Benzene	4/27/2022	160	J	μg/L	400
MW38-825S-445E	Chloroform	4/27/2022	140	J	μg/L	400
MW38-825S-445E	cis-1,2-Dichloroethene	4/27/2022	540		μg/L	400
MW38-825S-445E	m-Xylene & p-Xylene	4/27/2022	97	J	μg/L	800
MW38-825S-445E	Tetrahydrofuran	4/27/2022	2100	J	μg/L	2800
MW38-825S-445E	Trichloroethene	4/27/2022	210	J	μg/L	400
MW38-825S-445E	Vinyl Chloride	4/27/2022	1200		μg/L	400
MW38-825S-445E	Xylenes, Total	4/27/2022	97	J	μg/L	800
MW38-830N-230E	1,1-Dichloroethane	4/13/2022	3.3		μg/L	1
MW38-830N-230E	1,4-Dioxane	4/13/2022	4.2		μg/L	0.9
MW38-830N-230E	Bromodichloromethane	4/13/2022	0.99	J	μg/L	1
MW38-830N-230E	Chloroform	4/13/2022	3.8		μg/L	1
MW38-830N-230E	cis-1,2-Dichloroethene	4/13/2022	1.1		μg/L	1
MW38-830N-230E	Nitrogen, Nitrate	4/13/2022	8900		μg/L	500
MW38-830N-230E	Trichloroethene	4/13/2022	1.3		μg/L	1
MW43-WD	Nitrogen, Nitrate	4/26/2022	8500		μg/L	500
MW54-WD	Nitrogen, Nitrate	4/18/2022	4100		μg/L	500
MW62-WDR	1,4-Dioxane	4/19/2022	2.9		μg/L	0.9
MW62-WDR	Nitrogen, Nitrate	4/19/2022	120000		μg/L	25000
MW62-WDR	Nitrogen, Nitrite	4/19/2022	2100	J	μg/L	2500
MW71-WD	Nitrogen, Nitrate	4/19/2022	4700		μg/L	500
MW74-WD	Nitrogen, Nitrate	4/13/2022	3300		μg/L	500
MW77-EW-1	1,4-Dioxane	1/24/2022	2.5		μg/L	0.9
MW77-EW-1	1,4-Dioxane	4/28/2022	2.7		μg/L	0.9
MW77-EW-2	1,4-Dioxane	1/24/2022	0.09	J	μg/L	0.9
MW77-WD	1,1-Dichloroethene	4/18/2022	0.66	J	μg/L	1
MW77-WD	1,4-Dioxane	4/18/2022	12		μg/L	0.9
MW77-WD	Nitrogen, Nitrate	4/18/2022	13000	J	μg/L	500
MW77-WD	Tetrachloroethene	4/18/2022	0.74	J	μg/L	1
MW78-WD	Nitrogen, Nitrate	4/18/2022	190	J	μg/L	500
MW90-WD	Cadmium	5/17/2022	0.42	J	μg/L	5
MW90-WD	Nitrogen, Nitrate	5/17/2022	100	J	μg/L	500
MW91-WD	Cadmium	5/3/2022	0.21	J	μg/L	5
MW98-WD	1,4-Dioxane	1/24/2022	5.9		μg/L	0.9
MW98-WD	1,4-Dioxane	4/28/2022	7.8		μg/L	0.9
PM-13X	1,1,1-Trichloroethane	5/5/2022	0.2	J	μg/L	1
PM-13X	1,1-Dichloroethane	5/5/2022	18		μg/L	1
PM-13X	Chloroform	5/5/2022	0.53	J	μg/L	1
PM-13X	Tetrachloroethene	5/5/2022	0.69	J	μg/L	1
PM-13X	Trichloroethene	5/5/2022	0.92	J	μg/L	1
PM-14X	1,1-Dichloroethane	4/21/2022	3		μg/L	1
PM-14X	Cadmium	4/21/2022	0.43	J	μg/L	5
PM-14X	Chloroform	4/21/2022	0.26	J	μg/L	1

TABLE 4.5
SUMMARY OF DETECTED CONSTITUENTS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

	T					
Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
PM-14X	Nitrogen, Nitrate	4/21/2022	9600		μg/L	2500
PM-3X	1,1-Dichloroethane	5/5/2022	0.54	J	μg/L	1
PM-3X	Tetrachloroethene	5/5/2022	0.32	J	μg/L	1
PM-3X	Trichloroethene	5/5/2022	0.19	J	μg/L	1
PTP-11	Molybdenum, Dissolved	2/7/2022	6.4	J	μg/L	20
PTP-11	Molybdenum, Dissolved	5/11/2022	10	J	μg/L	20
PTP-11	Molybdenum, Total	2/7/2022	5.8	J	μg/L	20
PTP-11	Molybdenum, Total	5/11/2022	9.6	J	μg/L	20
PTP12	Molybdenum, Dissolved	2/7/2022	14	J	μg/L	20
PTP12	Molybdenum, Total	2/7/2022	15	J	μg/L	20
PTP-12	1,4-Dioxane	2/14/2022	7.1		μg/L	0.9
PTP-12	1,4-Dioxane	5/11/2022	4.8		μg/L	0.9
PTP-12	Molybdenum, Dissolved	5/11/2022	25		μg/L	20
PTP-12	Molybdenum, Total	5/11/2022	24		μg/L	20
PTP-13	1,4-Dioxane	3/1/2022	8.2		μg/L	0.9
PTP-13	1,4-Dioxane	5/12/2022	6.3		μg/L	0.9
PTP-13	Molybdenum, Dissolved	3/1/2022	620		μg/L	20
PTP-13	Molybdenum, Dissolved	5/12/2022	660		μg/L	20
PTP-13	Molybdenum, Total	3/1/2022	660		μg/L	20
PTP-13	Molybdenum, Total	5/12/2022	650		μg/L	20
U-518R-WD	1,1-Dichloroethane	4/21/2022	3.6		μg/L	1
U-518R-WD	1,2-Dichloroethane	4/21/2022	0.15	J	μg/L	1
U-518R-WD	Cadmium	4/21/2022	0.22	J	μg/L	5
U-518R-WD	Nitrogen, Nitrate	4/21/2022	140	J	μg/L	500
U-518R-WD	Trichloroethene	4/21/2022	0.78	J	μg/L	1

Shaded wells are compliance wells.

a/ Qualifiers: J=The analyte was analyzed for, and was positively identified, but the associated numerical value

may not be consistent with the amount actually present in the environmental sample.

J-= Same as J qualification but with an indication of negative bias in the sample concentration.

J+= Same as J qualification but with an indication of positive bias in the sample concentration.

b/ Units

 $\mu g/L = micrograms per liter$ pCi/L = picocuries per liter

TABLE 4.6 SUMMARY OF COMPLIANCE MONITORING EVALUATIONS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Well	Compound	Date F	Range	Trend ^{a/}	Distribution	90%	Mean	90%	Performance	Compliance Decision
						UCL ^{b/}		LCL ^{c/}	Standard	
B-313	1,4-Dioxane	NA	NA	NC	NC	NC	NC	NC	0.9	Well was dry -no samples collected this period, statistical evaluation could not be performed,
										considered in compliance
B-313	Nitrate	NA	NA	NC	NC	NC	NC	NC	0.9	Well was dry -no samples collected this period, statistical evaluation could not be performed,
										considered in compliance
B-326-UD	1,4-Dioxane	2/12/2020	4/14/2022	Decreasing	NC	5	4.628	4.256	0.9	Out of Compliance
B-326-UD	Nitrate	4/28/2015	2/4/2021	Decreasing	NC	NC	NC	NC	28,000	Not determined - Did not meet linear regression requirements, Potentially in compliance
B-326-WD	1,4-Dioxane	2/12/2020	4/14/2022	No trend	Normal	8.409	6.147	3.885	0.9	Out of Compliance
BM-11X-100N	Tetrachloroethene	10/20/2017	5/18/2022	No trend	Normal	6.429	6.05	5.671	5	Out of Compliance
BM-11X-100N	Trichloroethene	10/20/2017	5/18/2022	No trend	Normal	5.003	4.74	4.477	5	Indeterminant ^{g/}
BM-15N6	Nitrate	10/24/2017	4/25/2022	Decreasing	NC	NC	NC	NC	28,000	Not determined - Did not meet linear regression requirements, Potentially out of compliance
GW-109	1,4-Dioxane	NA	NA	NC	NC	NC	NC	NC	0.9	Well was dry -no samples collected this period, statistical evaluation could not be performed, considered in compliance
GW-109	Chloroform	NA	NA	NC	NC	NC	NC	NC	3.5	Well was dry -no samples collected this period, statistical evaluation could not be performed,
3.1.10)	c.merererm	1111	1111	1,0	110	1,0	1.0	1,0	3.5	considered in compliance
GW-109	Bromodichloromethane	NA	NA	NC	NC	NC	NC	NC	1	Well was dry -no samples collected this period, statistical evaluation could not be performed,
										considered in compliance
MW23-C-SD	1,4-Dioxane	3/15/2006	2/18/2021	No trend	NC	NC	NC	NC	0.9	Potentially in compliance f, 90% Nondetects - data not processed - 4th quarter 2020 results >
		3/13/2000	2/16/2021							GWPS but not verified by confirmation sample that was non detect.
MW38-830N-230E	1,4-Dioxane	11/1/2017	4/13/2022	No trend	Normal	7.897	6.12	4.343	0.9	Out of Compliance
MW38-830N-230E	Chloroform	11/1/2017	4/12/2022	Decreasing	NC	NC	NC	NC	3.5	Not determined - Did not meet linear regression requirements - a compliance determination
		11/1/2017	4/13/2022							could not be made
MW62-WDR	1,4-Dioxane	3/7/2018	4/19/2022	Decreasing	NC	3.117	2.962	2.807	0.9	Out of Compliance
MW62-WDR	Nitrate	3/7/2018	4/19/2022	No trend	Nonparametric	122,916	120,000	117,084	28,000	Out of Compliance
MW62-WDR	Nitrite	3/7/2018	4/19/2022	No trend	Normal	2,923	2,308	1,693	1,000	Out of Compliance
MW77-WD	1,4-Dioxane	10/26/2017	4/18/2022	No trend	Normal	10.03	8.02	6.01	0.9	Out of Compliance
MW106-UD	1,4-Dioxane	11/01/06 **	0/0//0/55	Decreasing	NC	NC	NC	NC	0.9	Not determined - Did not meet linear regression requirements, Potentially in compliance fi
		11/21/2006	8/26/2020	Č						90% Nondetects (decreasing trend due to decreasing MDL over time).

- a/ Trend determined by Mann-Kendall trend test analysis. When there is an increasing or decreasing trend, least squares regression analysis is used to determine the UCL and LCL
- b/ Upper Confidence Limit
- c/ Lower Confidence Limit
- d/ NA Not applicable
- e/ NC Not calculated
- f/ Potentially in compliance a statistical determination could not be made but the preponderance of evidence (i.e., decreasing trend and recent results < performance standard) suggests the parameter is in compliance at this well.
- g/ UCL above performance standard and LCL below performance standard cannot determine potential for compliance
- h/ Potentially out of compliance a statistical determination could not be made but the preponderance of evidence (i.e., increasing trend and recent results > performance standard or all results > performance standard) suggests the parameter is out of compliance at this well.

Note: * Statistics performed per the 2018 GWMP

* For all other parameters for the above listed 11 wells and all 29 parameters in the other compliance monitoring wells, the maximum detection for any compound did not exceed the performance standard. Compliance statistics were not performed.

TABLE 4.7
SUMMARY OF SLURRY WALL GRADIENT CALCULATIONS
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT
LOWRY LANDFILL SUPERFUND SITE

Well Pair	· · · · · · · · · · · · · · · · · · ·		Mean of Differences	80% Lower Confidence Limit	95% Upper Confidence Limit	Gradient	Conclusion
	Minimum	Maximum	(ft)	(ft)	(ft)		
PM-1	-2.78	-0.31	-1.00	-1.33	-0.31	Inward Gradient exists	Wall is effective
PM-2	-7.09 -6.98		-7.01	-7.09	-6.85	Inward Gradient exists	Wall is effective
PM-3	0.17	0.73	0.55	0.45	0.76	Outward Gradient exists	Review water quality data
PM-4	-0.54	-0.27	-0.37	-0.44	-0.23	Inward Gradient exists	Wall is effective
PM-5	-1.23	-0.03	-0.87	-1.08	-0.42	Inward Gradient exists	Wall is effective
PM-6	3.83	4.15	4.02	3.96	4.14	Outward Gradient exists	Review water quality data
PM-7	-7.44	-6.54	-7.06	-7.23	-6.70	Inward Gradient exists	Wall is effective
PM-8	-10.17	-8.72	-9.35	-9.68	-8.64	Inward Gradient exists	Wall is effective
PM-9	-10.90	-7.77	-8.98	-9.44	-8.01	Inward Gradient exists	Wall is effective
PM-10	-5.67	-3.07	-4.35	-4.84	-3.30	Inward Gradient exists	Wall is effective
PM-11	-22.03	-19.05	-20.85	-21.15	20.20	Inward Gradient exists	Wall is effective
PM-12	-5.11	-4.29	-4.72	-4.85	-4.42	Inward Gradient exists	Wall is effective
PM-13	Not calculated	Not calculated	Not calculated	Not calculated	Not calculated	PM-13I was dry	Continue to review water quality data
PM-14	0.96	1.16	1.04	0.94	1.18	Outward Gradient exists	Review water quality data
PM-15	-13.84 -11.87		-12.67	-12.86	-12.27	Inward Gradient exists	Wall is effective

ft = feet

TABLE 4.8

NORTH END MONITORING - NITRATE AND 1,4-DIOXANE (NEW DATA ONLY)

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	Sample Date	1,4-Dioxane (μg/L) ^{a/}	Nitrogen, Nitrate (µg/L)	VOCs ^{b/}	Anions	Metals
31	B-314	4/13/2022	0.9 U	890	X ^{c/}	X	X
31	B-326-UD	2/8/2022	4.5				X
31	B-326-UD	4/14/2022	4.6				X
31	B-326-WD	2/8/2022	3.6				X
31	B-326-WD	4/14/2022	3.2	360 J	X	X	X
31	MW05-WD	3/1/2022	3.6				
31	MW113-EW-1	1/25/2022	99	210 J			
31	MW113-EW-1	4/19/2022	89	150 J			X
31	MW113-UD	1/25/2022	59				X
31	MW113-UD	5/17/2022	57				X
31	MW113-WD	5/3/2022	36				X
31	MW114-WD	1/20/2022	0.96				
31	MW114-WD	5/9/2022	0.89 J				
31	MW117-WD	1/20/2022	1.3				
31	MW117-WD	5/9/2022	1.2				
31	MW118-WD	1/20/2022	0.28 J				
31	MW118-WD	5/9/2022	0.22 J				
31	MW121-WDR	1/26/2022	0.77 J				
31	MW122-WDR	1/26/2022	1.9				
31	MW123-WD	1/26/2022	1.7				
31	MW124-WD	1/27/2022	0.48 J				
31	MW125-WD	1/27/2022	0.34 J				
31	MW129-WD	2/28/2022	4.7				
31	MW132-WD	1/31/2022	15				
31	MW132-WD	5/10/2022	10				
30	MW135-WD	2/23/2022	5.1				
30	MW141-WD	2/15/2022	2.2				
19	MW142-WD	2/23/2022	1.4				
24	MW144-WD	2/15/2022	0.9 U				
31	MW151-WD	1/31/2022	4.8				
31	MW151-WD	5/16/2022	1.8				
31	MW153-EW-1	1/27/2022	3.3				
31	MW153-EW-1	4/27/2022	2.3				
31	MW154-EW-1	1/27/2022	1.7				
31	MW154-EW-1	4/28/2022	2.6				
31	MW155-EW-1	1/31/2022	0.49 J				
31	MW155-EW-1	5/2/2022	1.5	† †			
31	MW156-EW-1	2/9/2022	0.45 J	† †			
31	MW156-EW-1	5/2/2022	0.6 J	† †			
31	MW156-WD	2/10/2022	0.19 J	† †			
31	MW156-WD	5/16/2022	0.51 J				
31	MW157-WD	2/10/2022	0.9 U	† †			
31	MW157-WD	5/16/2022	0.9 U	† †			
31	MW160-WD	1/31/2022	3.7	† †			
31	MW160-WD	4/26/2022	2.9	† †			
13	MW176-DEN	2/15/2022	0.52 J	† †			1
31	MW179-UDEN	3/1/2022	0.9 U	† †			X
19	Private Well 1	6/7/2022	0.9 U	 			1

TABLE 4.8

NORTH END MONITORING - NITRATE AND 1,4-DIOXANE (NEW DATA ONLY) JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

			1,4-Dioxane	Nitrogen,			
Section	Well ID	Sample Date	$(\mu g/L)^{a/}$	Nitrate (μg/L)	$VOCs^{b/}$	Anions	Metals
30	Private Well 2	6/7/2022	0.9 U				
31	PTP-12	2/14/2022	7.1				
31	PTP-12	5/11/2022	4.8				X
31	PTP-13	3/1/2022	8.2				X
31	PTP-13	5/12/2022	6.3				X

Final Q definitions:

a/ μ g/L = micrograms per liter

b/ VOCs = volatile organic compounds

c/ X = indicates the sample was analyzed for at least one compound within the group.

- J+=a "J" qualifier indicating positive bias in the associated result
- J=The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- U= The analyte was analyzed for and is not present above the level of the associated value. The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.
- UJ=The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.

TABLE 4.9

NBBW & NORTH END EXTRACTION SYSTEMS - VOLUME AND MASS REMOVED

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE

	,	ane from North End Ground through June 2022 (1H22)	lwater Extraction
	Volume Removed	through ounc 2022 (11122)	
Extraction Well	(gallons)	Mass (grams)	Mass (pounds)
MW153-EW-1	1,090,368	11.34	0.025
MW154-EW-1	353,808	2.43	0.005
MW155-EW-1	454,752	1.35	0.003
MW156-EW-1	0	0.00	0.000
MW160-WD	120,240	1.52	0.003
MW118-WD	0	0.00	0.000
MW114-WD	0	0.00	0.000
MW77-EW-2	0	0.00	0.000
MW102-WD	234,432	0.92	0.002
MW77-EW-1	11,880	0.12	0.000
MW98-WD	9,230	0.26	0.001
MW170-EW-1	3,220,848	156.92	0.346
MW113-EW-1	472,752	175.70	0.387
MW113-UD	4,709	1.12	0.002
B-321	0	0.00	0.000
NBBW-IW-3	0	0.00	0.000
TOTAL	5,973,019	351.66	0.775

Т	otal Mass Removal of 1,4-D Cun	ioxane from North End nulative through 6/30/22	
Extraction Well	Volume Removed (gallons)	Mass (grams)	Mass (pounds)
MW153-EW-1	22,626,840	427.0	0.941
MW154-EW-1	15,203,237	346.8	0.764
MW155-EW-1	14,206,096	213.8	0.471
MW156-EW-1	6,103,619	174.0	0.384
MW160-WD	6,202,594	259.0	0.571
MW118-WD	1,490,372	123.7	0.273
MW114-WD	805,136	58.4	0.129
MW77-EW-2	149,192	8.6	0.019
MW102-WD	7,503,212	257.4	0.568
MW77-EW-1	292,584	14.7	0.032
MW98-WD	763,487	119.4	0.263
MW170-EW-1	67,419,504	5538.1	12.210
MW113-EW-1	14,704,351	1719.8	3.791
MW113-UD	166,366	41.9	0.092
B-321	1,777,661	160.1	0.353
NBBW-IW-3	988,762	488.4	1.077
TOTAL	160,403,015	9,950.9	21.9

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	$Q^{b/}$	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	andard→	5		5		70		7		200		5		990		0.9		28	
MW62-WDR	7/25/2016	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	5.6		130	
MW62-WDR	11/9/2016	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	4.4		150	
MW62-WDR	2/7/2017	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	5.2		140	
MW62-WDR	5/17/2017	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	5.3		110	
MW62-WDR	8/1/2017	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	5.8		110	
MW62-WDR	10/13/2017	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	4.6		120	
MW62-WDR	3/7/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.9		110	
MW62-WDR	5/10/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	4.2		120	
MW62-WDR	7/31/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.8		120	
MW62-WDR	5/14/2019	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.9		120	
MW62-WDR	12/17/2019	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.5		120	
MW62-WDR	5/14/2020	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.4		130	
MW62-WDR	11/11/2020	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.4		130	J
MW62-WDR	4/27/2021	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.3		120	
MW62-WDR	10/27/2021	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3.2		110	
MW62-WDR	4/19/2022	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	2.9		120	
B-323-WD	3/4/2011	1.5		0.85	J	0.98	J	2.5		2.2		0.13	U	3.7		53			
MW170-WD	3/7/2011	5.4		2.1		3.8		11		6.9		0.13	U	8.3		72			
MW170-EW-1	1/5/2012	11		3.6		8		26		11		0.55	J	15		150		110	
MW170-EW-1	8/22/2012	5		2		3.4		11		2.7		0.33	J	10		77		33	
MW170-EW-1	9/19/2012	4.5		2.2		3		11		3.1		0.35	J	9.3		72		27	
MW170-EW-1	10/22/2012	4.3		1.5		2.2		9.2		2		0.19	J	6.2		56		24	
MW170-EW-1	11/13/2012	3.8		1.5		2.2		8.7		1.9		0.13	U	5.9		46		19	
MW170-EW-1	12/10/2012	4.2		1.6		2		8		2.1		0.13	U	6.2		40		17	
MW170-EW-1	1/30/2013	5.2		1.8		1.9		11		2.7		0.17	J	6.9		45		13	
MW170-EW-1	2/20/2013	5.4		2.4		3.2		14		3.1		0.13	U	10		71		12	
MW170-EW-1	3/14/2013	8.3		3.5		4.6		21		4		0.34	J	15		79		8.8	
MW170-EW-1	4/22/2013	5.8		2.2		2.5		11		1.6		0.13	J	7.9		64		5.5	
MW170-EW-1	5/15/2013	5.2		2.1		2.7		9		1.6		0.13	U	8.1		50		5.5	
MW170-EW-1	6/17/2013	4.9		1.9		2.7		8		1.6		0.13	U	6.5		39		5.3	
MW170-EW-1	7/29/2013	4		1.4		2.1		6.2		1.2		0.13	U	5.1		32		5.3	
MW170-EW-1	8/21/2013	4.8		1.5		2		6.8		1.7		0.13	U	5.4		29		5	
MW170-EW-1	9/18/2013	3.3		1.1		1.6		4.4		0.93		0.13	U	3.7		32		5.3	
MW170-EW-1	11/11/2013	2.7		1.1		1.4	-	4.6		1		0.13	U	3.7		27		5.8	
MW170-EW-1	2/20/2014	1.7		0.64	J	0.8	J	2.5		0.72	J	0.13	U	2.6		15		5.1	
MW170-EW-1	5/28/2014	2.1		0.87	J	1		3.2		0.88	J	0.13	U	3.1		18		6.2	
MW170-EW-1	9/4/2014	2.3		0.86	J	1.9		4.3		1.1		0.13	U	3.1		22		14	
MW170-EW-1	12/3/2014	1.5		0.56	J	2		3.1		1.1		0.13	U	2.6		17		13	
MW170-EW-1	3/5/2015	1.7		0.59	J	2.3		2.9		1.3		0.13	U	2.2		12		14	

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	Q ^{b/}	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	andard→	5		5		70		7		200		5		990		0.9		28	
MW170-EW-1	6/18/2015	1.2		0.4	J	1.9		2.3		1.2		0.13	U	1.9		9.9		19	
MW170-EW-1	9/16/2015	1.1		0.43	J	1.4		1.8		0.98	J	0.13	U	1.6		8.8		22	
MW170-EW-1	12/10/2015	0.87	J	0.3	J	0.82	J	1.1		0.49	J	0.13	U	0.99	J	6.7		22	
MW170-EW-1	2/24/2016	0.76	J	0.23	J	0.8	J	0.94	J	0.48	J	0.13	U	0.82	J	5.3		18	
MW170-EW-1	6/23/2016	0.7	J	0.26	J	1.4		1.3		0.73	J	0.13	U	1.2		6		24	
MW170-EW-1	12/19/2016	0.56	J	0.19	J	0.69	J	0.79	J	0.42	J	0.13	U	0.69	J	3.9		21	
MW170-EW-1	3/13/2017	0.74	J	0.29	J	1.3		1.3		0.77	J	0.13	U	1.2		3.7		18	
MW170-EW-1	6/26/2017	0.61	J	0.21	J	0.98	J	1.2		0.55	J	0.13	U	0.92	J	4.6		15	
MW170-EW-1	9/11/2017	0.76	J	0.21	J	1.2		1.3		0.73	J	0.13	U	1.1		4.7		13	
MW170-EW-1	12/4/2017	0.67	J	0.26	J	2.7		1.6		0.98	J	0.13	U	1.4		5.5		11	
MW170-EW-1	3/7/2018	0.78	J	0.3	J	5.6		2.1		1.9		0.13	U	2.8		8.6		19	
MW170-EW-1	6/11/2018	1.3		0.53	J	17		5.4		5.1		0.16	J	6.8		15		12	
MW170-EW-1	9/5/2018	1.4		0.5	J	14		4.3		4.3		0.13	U	5.6		17		8.7	
MW170-EW-1	11/19/2018	1.7		0.65	J	17		5.5		5.5		0.2	J	7.1		20		7.7	
MW170-EW-1	2/8/2019	1.1		0.44	J	13		3.4		3.4		0.13	U	5.3		16		8.8	
MW170-EW-1	3/18/2019	1.6		0.63	J	13		4.4		3.1		0.13	U	5.6		18		8	
MW170-EW-1	4/18/2019	1.2		0.52	J	10		2.7		2.9		0.13	U	4.4		15		7.8	
MW170-EW-1	5/17/2019	1.2		0.49	J	10		2.8		2.8		0.13	U	4.6		15		8.4	
MW170-EW-1	6/14/2019	1		0.42	J	11		3.5		2.2		0.13	U	4		15		8.9	
MW170-EW-1	7/17/2019	1.4		0.62	J	14		4.7		3.8		0.13	U	6		30	J	7.8	
MW170-EW-1	8/19/2019	1.6		0.73	J	15		4.7		3.7		0.13	U	6.3		29	J	7.5	
MW170-EW-1	9/17/2019	1.1		0.43	J	12		3.5		2.5		0.13	U	4.8		17		7.4	
MW170-EW-1	10/15/2019	1.3		0.51	J	13		2.8		3.2		0.13	U	5.6		18		7.7	
MW170-EW-1	11/12/2019	1.2		0.48	J	12		3.4		2.6		0.13	U	4.8		19		7.8	
MW170-EW-1	12/10/2019	1.6		0.62	J	15		5		3.6		0.13	U	6.5		21		8.3	
MW170-EW-1	2/11/2020	1.3		0.5	J	13		4.3		2.8		0.14	J	5.1		18		8.1	
MW170-EW-1	5/12/2020	1.4		0.48	J	13		4.1		3.2		0.13	U	5.6		16		8.7	
MW170-EW-1	8/10/2020	1.1		0.42	J	11		3.7		2.4		0.28	J	4.9		19	U	9.2	
MW170-EW-1	8/20/2020															16			
MW170-EW-1	11/10/2020	1.6		0.64	J	12		3.6		2.6		0.13	U	4.7		16		8.8	
MW170-EW-1	2/4/2021	1.1		0.35	J	12		3.7		2.6		0.13	U	5.1		16		9.2	
MW170-EW-1	5/12/2021	0.95	J	0.38	J	9.8		2.8		1.8		0.13	U	4.1		15		11	J
MW170-EW-1	8/9/2021	1		0.45	J	9.5		2.8		1.8		0.13	U	4		14		9.8	
MW170-EW-1	10/27/2021	0.93	J	0.33	J	11		3.4		2		0.13	U	4.6		12		9.9	
MW170-EW-1	1/25/2022	1.2		0.49	J	9		3		1.8		0.13	U	3.7		14		11	
MW170-EW-1	5/10/2022	0.7	J	0.51	J	8.2		2.4		1.3		0.13	U	3.3		11		9.7	
MW171-WD	3/3/2011	1		0.65	J	0.36	J	2.1		1.1		0.13	U	2.8		21			
MW171-WD	1/4/2012	0.2	U	0.16	U	0.15	U	0.64	J	0.16	U	0.13	U	0.77	J	6.6		18	

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	Q ^{b/}	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	andard→	5		5		70		7		200		5		990		0.9		28	
MW171-WD	8/28/2012	0.3	J	0.21	J	0.15	U	0.71	J	0.24	J	0.13	U	0.93	J	8.4		15	
MW171-WD	1/31/2013	0.25	J	0.18	J	0.15	U	0.63	J	0.25	J	0.13	U	0.82	J	9.5		16	
MW171-WD	8/21/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	3		10	
MW172-WD	3/1/2011	1.7		0.83	J	0.86	J	6		1.3		0.13	U	6		51			
MW172-WD	1/4/2012	2.3		1.2		0.95	J	4.9		0.94	J	0.13	U	5.8		68		28	
MW172-WD	8/28/2012	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.82	J	1.3	
MW172-WD	1/30/2013	0.62	J	0.26	J	0.15	U	1.1		0.26	J	0.13	U	1		16		8.1	
MW172-WD	9/19/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.6	J	2.1	
MW173-WD	3/1/2011	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U		
MW173-WD	8/24/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.15	U		
MW174-WD	1/5/2012	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U	10	
MW174-WD	9/6/2012	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U	6.7	
MW174-WD	2/5/2013	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U	5.3	
MW174-WD	9/25/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.15	U	2.9	
MW175-WD	1/5/2012	3.5		2.1		3.5		13		0.42	J	0.27	J	12		76		62	
MW175-WD	9/6/2012	0.2	J	0.16	U	0.15	U	0.46	J	0.33	J	0.13	U	0.22	U	2.4	J	35	
MW175-WD	2/5/2013	0.2		0.47	J	0.61	J	2.3		0.24	J	0.13	U	2		15		19	
MW175-WD	9/19/2018	0.2		0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.53	J	28	
MW77-WD	12/19/2003	6.2		2.6		1.5		11		11		0.32	J	11		85	J	68	
MW77-WD	1/21/2004	6.7		2.9		1.6		12		11		0.13	U	11		76	J		
MW77-WD	5/26/2010	3.3		1.2		0.82	J	7		2.8		0.13	U	4.7		45		160	
MW77-WD	11/18/2010	2.3		0.9	J	0.66	J	4.2		1.7		0.13	U	3.5		37		120	
MW77-WD	3/2/2011	3		1.1		0.82	J	5.8		2		0.13	U	4.7		41			
MW77-WD	5/25/2011	4.6		2		1.3		10		3.5		0.13	U	7.2		61		170	
MW77-WD	11/15/2011	2.8		1.1		0.89	J	5.1		1.6		0.13	U	4.3		41		130	
MW77-WD	5/24/2012	1.6		0.46	J	0.15	U	2.1		0.76	J	0.13	U	1.6		23		42	
MW77-WD	11/8/2012	2.2		0.68	J	0.37	J	1.9		0.92	J	0.13	U	1.9		29		46	
MW77-WD	5/8/2013	2.1		0.55	J	0.22	J	1.9		0.67	J	0.13	U	1.3		27		65	
MW77-WD	11/12/2013	0.8		0.21	J	0.15	U	0.56	J	0.32	J	0.13	U	0.67	J	11		74	
MW77-WD	4/29/2014	1.6		1.49	J	0.17	J	1.4		0.58	J	0.13	U	1.1		23		63	
MW77-WD	11/18/2014	0.74	J	0.24	J	0.15	U	0.93	J	0.3	J	0.13	U	0.54	J	7.7		59	
MW77-WD	4/23/2015	0.57	J	0.16	U	0.15	U	0.37	J	0.17	J	0.13	U	0.28	J	5.8		53	
MW77-WD	11/12/2015	1.4		0.42	J	0.16	J	1.7		0.5	J	0.13	U	1.2		15		23	
MW77-WD	5/16/2016	0.36	J	0.16	U	0.15	U	0.24	J	0.16	U	0.13	U	0.22	U	3.5		35	
MW77-WD	10/31/2016	1.4		0.38	J	0.16	J	1.5		0.32	J	0.13	U	1		14		16	
MW77-WD	4/24/2017	1.3		0.51	J	0.19	J	1.9		0.44	J	0.13	U	1.7		20		24	
MW77-WD	10/26/2017	0.61	J	0.17	J	0.15	U	0.52	J	0.16	U	0.13	U	0.36	J	5.3		27	
MW77-WD	5/3/2018	0.98	J	0.22	J	0.15	U	0.75	J	0.16	U	0.13	U	0.51	J	9		26	
MW77-WD	8/2/2018	0.27	J	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	2.6		9.7	

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	n/								
Well	Sample Date	PCE	O_{p}	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance S	tandard→	5		5		70		7		200		5		990		0.9		28	
MW77-WD	5/2/2019	0.48	J	0.16	U	0.15	U	0.26	J	0.16	U	0.13	U	0.22	U	3		17	
MW77-WD	10/22/2019	1.3		0.18	J	0.15	U	1.7		0.16	U	0.28	J	0.91	J	12		17	
MW77-WD	5/4/2020	0.61	J	0.18	J	0.15	U	0.43	J	0.16	U	0.13	U	0.22	U	5		18	
MW77-WD	10/28/2020	1.7		0.47	J	0.15	U	2.1		0.31	J	0.13	U	1.1		16		12	
MW77-WD	4/21/2021	0.56	J	0.16	U	0.15	U	0.52	J	0.16	U	0.13	U	0.22	U	4.3		15	
MW77-WD	10/27/2021	1.1		0.16	U	0.15	U	1.7		0.16	U	0.13	U	0.99	J	11		12	
MW77-WD	4/18/2022	0.74	J	0.16	U	0.15	U	0.66	J	0.16	U	0.13	U	0.22	U	12		13	J
MW98-WD	3/8/2010															44			
MW98-WD	6/10/2010															42			
MW98-WD	9/7/2010															38			
MW98-WD	12/1/2010															34			
MW98-WD	3/9/2011															36			
MW98-WD	6/14/2011															35			
MW98-WD	8/30/2011															40			
MW98-WD	12/13/2011															29			
MW98-WD	3/20/2012															26			
MW98-WD	6/13/2012															24			
MW98-WD	9/5/2012															23			
MW98-WD	12/6/2012															22			
MW98-WD	3/6/2013															19			
MW98-WD	6/4/2013															20			
MW98-WD	9/10/2013															21			
MW98-WD	11/4/2013															17	J		
MW98-WD	2/13/2014															17			
MW98-WD	5/14/2014															18			
MW98-WD	8/13/2014															22			
MW98-WD	12/2/2014															19			
MW98-WD	2/9/2015															16			
MW98-WD	6/11/2015															21			
MW98-WD	9/3/2015															16			
MW98-WD	12/28/2015															16			
MW98-WD	3/1/2016															15			
MW98-WD	6/20/2016															16			
MW98-WD	12/28/2016															14			
MW98-WD	3/2/2017															13			
MW98-WD	6/27/2017															14			
MW98-WD	7/27/2017															14			
MW98-WD	11/30/2017															12			
MW98-WD	3/21/2018															12			

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	ı/								
Well	Sample Date	PCE	$\mathbf{O}_{\mathbf{p}}$	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	andard→	5		5		70		7		200		5		990		0.9		28	
MW98-WD	5/24/2018															11			
MW98-WD	9/4/2018	0.82	J	0.24	J	0.15	U	0.69	J	0.29	J	0.13	U	0.83	J	11		4.40	
MW98-WD	11/20/2018															12			
MW98-WD	2/22/2019															11			
MW98-WD	5/16/2019															10			
MW98-WD	7/24/2019															11			
MW98-WD	10/23/2019															12			
MW98-WD	2/13/2020															11			
MW98-WD	5/21/2020															8.6			
MW98-WD	8/24/2020															9.8			
MW98-WD	11/18/2020															11			
MW98-WD	2/11/2021															6.3			
MW98-WD	6/7/2021															9.8			
MW98-WD	8/31/2021															11			
MW98-WD	11/18/2021															11			
MW98-WD	1/24/2022															5.9			
MW98-WD	4/28/2022															7.8			
MW102-WD	3/8/2010															29			
MW102-WD	6/10/2010															29			
MW102-WD	9/7/2010															25			
MW102-WD	12/1/2010															19			
MW102-WD	3/9/2011															20			
MW102-WD	6/14/2011															21			
MW102-WD	8/30/2011															21			
MW102-WD	12/13/2011															12			
MW102-WD	3/20/2012															9.7			
MW102-WD	6/13/2012															6.4			
MW102-WD	9/5/2012															5.8			
MW102-WD	12/6/2012															4	J		
MW102-WD	3/6/2013															3.3	J		
MW102-WD	6/4/2013					·										3.2	J		
MW102-WD	9/10/2013															2.8	J		
MW102-WD	11/4/2013															2.8	J		
MW102-WD	2/13/2014															2.4	J		
MW102-WD	5/14/2014															2.7	J		
MW102-WD	8/13/2014															5.2			
MW102-WD	12/2/2014															3.6	J		
MW102-WD	2/9/2015															2.8	J		
MW102-WD	6/11/2015															4.4	J		

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	$\mathbf{O}_{\mathbf{p}}$	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q			1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance S	tandard→	5	Ì	5		70		7		200		5		990		0.9		28	
MW102-WD	9/3/2015															3.3			
MW102-WD	12/28/2015															2.9			
MW102-WD	3/1/2016															2.2			
MW102-WD	6/20/2016															3.3			
MW102-WD	12/28/2016															2.5			
MW102-WD	3/2/2017															2.9			
MW102-WD	6/27/2017															2.5			
MW102-WD	7/27/2017															2.5			
MW102-WD	11/30/2017															1.3			
MW102-WD	3/21/2018															1.4			
MW102-WD	5/24/2018															0.81	J		
MW102-WD	9/4/2018	0.24	J	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	1.8		2.9	
MW102-WD	11/20/2018															1.8			
MW102-WD	2/22/2019															1.5			
MW102-WD	5/16/2019															1.5			
MW102-WD	7/24/2019															1.7			
MW102-WD	10/23/2019															1.5			
MW102-WD	2/13/2020															1.1			
MW102-WD	5/21/2020															1.3			
MW102-WD	8/24/2020															1.1			
MW102-WD	11/18/2020															0.99			
MW102-WD	2/11/2021															0.9			
MW102-WD	6/7/2021															1.8			
MW102-WD	8/31/2021															1.7			
MW102-WD	11/18/2021															1.1			
MW102-WD	1/24/2022															0.92			
MW102-WD	4/28/2022															1.2			
MW77-EW-1	3/8/2010															32			
MW77-EW-1	6/10/2010															33			
MW77-EW-1	9/7/2010															27			
MW77-EW-1	12/1/2010															24			
MW77-EW-1	3/9/2011															22			
MW77-EW-1	6/14/2011															23			
MW77-EW-1	8/30/2011															30			
MW77-EW-1	12/13/2011															18			
MW77-EW-1	3/20/2012															16			
MW77-EW-1	6/13/2012															12			
MW77-EW-1	9/5/2012			-												12			
MW77-EW-1	12/6/2012			•												10			

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	ı/							\neg
Well	Sample Date	PCE	O_{p}	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance S	tandard→	5		5		70		7		200		5	990		0.9		28	
MW77-EW-1	3/6/2013														9.7			
MW77-EW-1	6/4/2013														8.6			
MW77-EW-1	9/10/2013														9.1			
MW77-EW-1	12/17/2013														7.6			
MW77-EW-1	2/13/2014														7.6			
MW77-EW-1	5/14/2014														7.1			
MW77-EW-1	8/13/2014														10			
MW77-EW-1	12/2/2014														7.5			
MW77-EW-1	2/9/2015														6.6			
MW77-EW-1	6/11/2015														9.5			
MW77-EW-1	9/3/2015														6.5			
MW77-EW-1	12/28/2015														8.4			
MW77-EW-1	3/1/2016														4.8			
MW77-EW-1	6/20/2016														5.8			
MW77-EW-1	12/28/2016														4.5			
MW77-EW-1	3/2/2017														11			
MW77-EW-1	6/27/2017														11			
MW77-EW-1	7/27/2017														5.4			
MW77-EW-1	11/30/2017														3.7			
MW77-EW-1	3/21/2018														3.5			
MW77-EW-1	5/24/2018														2.5			
MW77-EW-1	9/4/2018	0.43	J	0.16	U	0.15	U	0.23	J	0.16	J	0.13 U	0.55	J	10		3	
MW77-EW-1	11/20/2018														3.3			
MW77-EW-1	2/22/2019														2.9			
MW77-EW-1	5/16/2019														2.9			
MW77-EW-1	7/24/2019														3.3			
MW77-EW-1	10/23/2019														4.5			
MW77-EW-1	2/13/2020														3			
MW77-EW-1	5/21/2020														2.8			
MW77-EW-1	8/24/2020														3			
MW77-EW-1	11/18/2020														3.4			
MW77-EW-1	2/11/2021														2.7			
MW77-EW-1	6/7/2021														3.2			
MW77-EW-1	8/31/2021														3.7			
MW77-EW-1	11/18/2021														3			
MW77-EW-1	1/24/2022														2.5			
MW77-EW-1	4/28/2022														2.7			
MW77-EW-2	3/8/2010														9.4			\neg
MW77-EW-2	6/10/2010														8.9			

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	O_{p}	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA (2	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	tandard→	5	_	5		70		7		200		5		990		0.9		28	
MW77-EW-2	9/7/2010															8.6			
MW77-EW-2	12/1/2010															11			
MW77-EW-2	3/9/2011															6.3			
MW77-EW-2	6/14/2011															1.7	J		
MW77-EW-2	8/30/2011															1.5	J		
MW77-EW-2	12/13/2011															0.82	J		
MW77-EW-2	3/20/2012															0.7	J		
MW77-EW-2	6/13/2012															0.58	J		
MW77-EW-2	9/5/2012															0.85	J		
MW77-EW-2	12/6/2012															0.52	J		
MW77-EW-2	3/6/2013															0.5	U		
MW77-EW-2	6/4/2013															0.5	U		
MW77-EW-2	9/10/2013															0.5	U		
MW77-EW-2	12/17/2013															0.5	U		
MW77-EW-2	2/13/2014															0.5	U		
MW77-EW-2	5/14/2014															0.5	U		
MW77-EW-2	8/13/2014															0.5	U		
MW77-EW-2	12/2/2014															0.5	U		
MW77-EW-2	2/9/2015															0.68	J		
MW77-EW-2	6/11/2015															0.94	J		
MW77-EW-2	9/3/2015															0.65	J		
MW77-EW-2	12/28/2015															0.53	J		
MW77-EW-2	3/1/2016															0.5	J		
MW77-EW-2	6/20/2016															0.3	J		
MW77-EW-2	12/28/2016															0.6	J		
MW77-EW-2	3/2/2017															0.81	J		
MW77-EW-2	6/27/2017															0.44	J		
MW77-EW-2	7/27/2017															0.18	J		
MW77-EW-2	11/30/2017															0.15	U		
MW77-EW-2	3/21/2018															0.37	J		
MW77-EW-2	5/24/2018					·										0.15	U		
MW77-EW-2	9/4/2018	0.20	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13 U	J	0.22	U	0.15	U	0.55	
MW77-EW-2	11/20/2018															0.15	U		
MW77-EW-2	2/22/2019															0.17	J		
MW77-EW-2	5/16/2019															0.15	J		
MW77-EW-2	7/24/2019															0.4	U		
MW77-EW-2	10/23/2019												T			0.4	U		
MW77-EW-2	2/13/2020												\dashv			0.12	J		

TABLE 4.10 SUMMARY OF GTEP AREA ANALYTICAL RESULTS SINCE 2010 VOCs AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

										Compounds	a/								
Well	Sample Date	PCE	$\mathbf{Q}_{\mathbf{p}}$	TCE	Q	cis-1,2-DCE	Q	1,1-DCE	Q	1,1,1-TCA	Q	1,2-DCA	Q	1,1-DCA	Q	1,4-Dioxane	Q	NO3	Q
Performance St	andard→	5		5		70		7		200		5		990		0.9		28	
MW77-EW-2	5/21/2020															0.17	J		
MW77-EW-2	8/24/2020															0.19	J		
MW77-EW-2	11/18/2020															0.19	J		
MW77-EW-2	2/11/2021															0.18	J		
MW77-EW-2	6/7/2021															2			
MW77-EW-2	9/14/2021															0.13	J		
MW77-EW-2	11/18/2021															0.12	J		
MW77-EW-2	1/24/2022															0.09	J		
MW77-EW-2	4/28/2022															0.09	U		
MW77-UD	1/4/2012	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U	0.5	U
MW77-UD	2/7/2012	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	U	0.5	U	0.5	U
MW77-UD	9/6/2012	0.2	U	0.16	U	0.15	Ü	0.23	U	0.16	Ū	0.13	U	0.22	Ü	0.5	U	0.31	J
MW77-UD	8/20/2018	0.2	U	0.16	U	0.15	U	0.23	U	0.16	U	0.13	U	0.22	Ü	0.38	J	0.047	J

^{**}All concentrations listed in micrograms per liter [µg/L], except nitrate (NO 3), which is listed in milligrams per liter [mg/L]

 a/
 PCE = tetrachloroethene
 1,1,1-TCA = 1,1,1-trichloroethane

 TCE = trichloroethene
 1,2-DCA = 1,2-dichloroethane

 cis-1,2-DCE = cis-1,2-dichloroethene
 1,1-DCA = 1,1-dichloroethane

1,1-DCE = 1,1-dichloroethene NO3 = Nitrate

b/ Q = Final qualifier

Qualifiers J = The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.

U = The analyte was analyzed for and is not present above the level of the associated value.

^{**}Yellow shaded cells indicate the concentration exceeds the performance standard

TABLE 4.11

SUMMARY OF PERMITTED WATER WELLS LOCATED WITHIN 1/2 MILE OF EAST/SOUTH/WEST SITE BOUNDARIES AND 5 MILES NORTH OF NORTH BOUNDARY JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE


Well ID ^{1/}	Recorded Owner	Recorded Use	Completion Interval or Formation	Distance Downgradient from Superfund Site	Comments	Within 1,4-Dioxane Plume Boundary
3384	City of Aurora	Other (monitoring well)	Total depth of approx. 45 feet bgs ^{2/}	Approximately 2.6 miles	Monitoring well in Murphy Creek subdivision	No
3385	City of Aurora	Other (monitoring well)	Total depth of approx. 35 feet bgs	Approximately 2.4 miles	Monitoring well in Murphy Creek subdivision	No
3388	City of Aurora	Other (monitoring well)	Total depth of approx. 18 feet bgs	Approximately 3.3 miles	Monitoring well in Murphy Creek subdivision	No
3553	C. Chappell	Domestic	Total depth of approx. 40 feet bgs	Approximately 4.2 miles		No
1879	F.E. Heintz	Domestic	Unknown	Approximately 4.2 miles	Probably a deep water supply well, but needs to be verified	No
3313	J. Compton	Domestic	23 to 60 feet below ground surface (ft bgs)	Approximately 4.6 miles	Subject of past research by TCHD - abandoned and unusable	No
3312	J. Compton	Domestic	Unknown	Approximately 4.6 miles	Probably a deep water supply well, but needs to be verified	No
3556	West Arapahoe Soil Conservation	Stock ^{3/}	Quaternary	Approximately 1 mile	Livestock watering	No
2027	City of Aurora	Other (monitoring well)	18 ft to 23 ft bgs	Approximately 2.7 miles	2-inch diameter monitoring well in Murphy Creek subdivision	Yes
3561	Buckley Investment Company	Stock	Total depth of approx. 70 feet bgs	Approximately 1.5 miles	Livestock watering	No


^{1/} Wells within the drainage basin with total depth less than 100 feet. Waste Management and Lowry monitoring wells not included.


These wells are also limited to 15 gpm. The wells are not used for human consumption.


^{2/} bgs = below ground surface


^{3/} STOCK use is for watering for livestock on farms and ranches that are generally 35 acres or more in size.



































Figure 4.18
B-326 and MW113 - Water Elevation/Dissolved Molybdenum




Figure 4.19
MW113 Area - Water Elevation/Bottom of Screen/MW113-EW-1 and NBBW-IW-3 Extraction Rate




Figure 4.20 1,4-Dioxane Concentrations B-326 / MW113 Area









Figure 4.21 1,4-Dioxane Concentrations B-321 (Extraction Well) / B-313 (Compliance Well)















B-326-WD and B-326-UD Water Elevation and NBBW-IW-3, MW113-EW-1 and MW133-UD Extraction Rate NBBW-IW-3 extraction 5693 MW113-EW-1 Extraction 5.0 commenced to increase - NBBW-IW-3 Extraction mass removal 5692 Total Molybdenum detected in MW113-EW-1. 4.5 Packer installed (5664 feet amsl) and MW113-EW-1 inlet MW113-EW-1 extraction rate reduced adusted on 7/30/20 (5664.5 feet amsl) 4.0 5691 Extraction Rate (gallons per Packer removed and MW113-EW-1 inlet 5690 3.5 adusted on 6/7/21 (5659.8 feet amsl) 3.0 5689 2.5 5688 2.0 5687 1.5 5686 1.0 5685 MW113-UD Extraction Rate 0.5 5684 0.0 5683 5682 5681 of Potable Water 5680 Water Elevation (feet amsl) 5679 B-326-UD Water Elevation 5678 5677 5676 Cessation 5675 5674 5673 **B-326-WD Water Elevation** 5672 5671 5670 5669 5668 5667 5666 5665 5664 5663 5662 B-326-WD Bottom of Well Screen 5661 5660 1/31/19 3/2/19 4/1/19 5/2/19 8/1/19 10/31/19 3/1/20 3/31/20 12/30/20 7/2/19 9/1/19 10/1/19 12/31/19 1/31/20 5/1/20 5/31/20 7/1/20 7/31/20 8/31/20 9/30/20 10/30/20 11/30/20 5/1/21 7/31/21 9/30/21 10/30/21 11/30/21 1/30/22 5/1/22 5/31/22 3/31/21 5/31/21 7/1/21 8/31/21 12/30/21 B-326-WD ----- MW113-EW-1 Extraction Rate B-326-UD ----- NBBW-IW-3 Extration Rate — MW113-UD Extraction Rate


Figure 4.26




















Figure 4.35
North End Trend Analysis Plots - Area 1
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund





Figure 4.35 North End Trend Analysis Plots - Area 1 January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund






Figure 4.36
North End Trend Analysis Plots - Area 2
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.37
North End Trend Analysis Plots - Area 3
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.37 North End Trend Analysis Plots - Area 3

January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.38

North End Trend Analysis Plots - Area 4

January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site






Figure 4.38
North End Trend Analysis Plots - Area 4
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site





Graph 5

Figure 4.38

North End Trend Analysis Plots - Area 4

January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.39
North End Trend Analysis Plots - Sections 30 and 19
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site






Figure 4.39
North End Trend Analysis Plots - Sections 30 and 19
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site





Graph 5

Graph 6

Figure 4.40
North End Trend Analysis Plots - Yale Area
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site







Figure 4.40
North End Trend Analysis Plots - Yale Area
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site










Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site




Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site







Figure 4.42
North End Trend Analysis Plots - Area 5
January through June 2022 Operations and Maintenance Status Report Lowry Landfill Superfund Site





Graph 25

Graph 26








Figure 9.1 Master Schedule





APPENDIX A

WATER TREATMENT PLANT

APPENDIX A-1

WTP WEEKLY SUMMARIES AND STANDARD OPERATIONS CHECKLISTS

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level:	Counter: Cycles:
LFG Cond Automatic Trap CT-2	Sump Level:	Counter: Cycles:
LFG Cond Automatic Trap CT-3	Sump Level:	Counter: Cycles:
CT-4 Containment/Vessel (LFG Cond)	Level: %	Tank Level: Counter: Cycles: Sump:
PM-15 Containment / Vessel	Level: %	200 E-200 E-
MW-51 Containment / Vessel	Level: %	
PM-11 Containment / Vessel	Level: %	
MW-38 Systems	/	
North Toe System	/	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)	/	Last Done: 12-22-21
North End Pipeline(s)Flushing (As Needed)		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	_	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	~	Monthly Sump Level: 12-16-21 Date: 12-16-21
North Boundary System P-001:	CV 73.4 % @ 6.4 gpm	40.52 Hz/2.07 Amps. / vault psi @ 18/Auleurs
T-101 & T-102 Containment / Tank		Levels: 32 % & 30 %
Raw Water Storage Tanks Piping		7
RWST Building Temp. (TT-101)	53.4 °F	Outside Temp.: ~ 3 °F EXTRA HEATERON
(P-121) or P-122		0.6 gpm/CV 54 %
RWST 2ndry Cont. High Level Switch	V	(LSH-101) Last Test(monthly): /2 - /6-21
RWST Back-Up Generator		Last Test Run(monthly): /2-16-2/

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	/	~ 600 Gallons Reserve = 3707es
Caustic Bay Heater	~	
Peroxide Tote Level		~ 270 Gallons Reserve = ~55 J
HCL Tote Levels	~	~ SS Gallons Reserve = ~30
Chemical Totes and Piping Inspected	V	Leaks observed: Y / 🕦
Emergency Shower Inspected		Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	V	
Ion Exchange Acid Feed Pump (P-632)	~	PI-0632 PSI: 84-90 CV: 4 %
Primary Acid Retention Tank (T-510)	~	
All Acid Feed Lines	-	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 qpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022		
Inspection Performed by:	Mike Gelwick		

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)		Last Cleaning (Qtrly): /フ・フゥーン/
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	V	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.72	
pH 315	Value: 10.69	
Flocculation Chamber Paddle Wheel	1	
Precipitate Floc Quality	/	Good
Clarifier Water Quality	/	Oil or sheen observed: Y / (1)
Clarifier Effluent Piping / Water Level	1	
Clear-well Chamber and Water Level	V	
HMR PLC Panel	_	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	_	
Polymer Pump (P-310)	/	
Polymer Tank Mixer		
Polymer Tank Level	Gallons: ~ 550	JUST REWILL
Clear-well Transfer Pumps (P-371)/ 372)	~	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 60thot
Manual Sludge Lateral pumping	~	Last done (As Needed): 4/42-3-20-21/3-7-20-21
Manual Sludge Lateral Ball Valves	1	Exercise Weekly: Mloc
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	1-6-22-Today	1335
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX	/	1403
pH-740 Discharge Surge Tank	•	Discharge suspended: /₹25 ← ►/333
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: // m

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)	_	Level:~ 45 %
Sludge Holding Tank (T-352)		Level: 76 %
Decant Transfer Pump (P-352)	-	CV 62 % @o.8 gpm
Filter Press Pumps (P-381 / P-382)	-	
Filter Press	~	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022		
Inspection Performed by:	Mike Gelwick		

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 34,2 psi	CV@ 73 % @ /.9 gpm
Retention Tank (T-114)	✓ Operating Press: 34 psi	pH-113 @ 3.81
Bag Filter (BF-113)	Operating Press: 36 psi	
Ion Exchange (Cage (2) or 2) + Guard	✓ Operating Press: 34 psi	TP-173 A-2-> TP-175A /4 configure + Coperd
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521)or P-522)	Operating Press: 27 psi	CV@ 79 % @ 32.4 gpm
T-520 to GAC Total (FT-675)	254821980 gal	Time: 0947
North End On-Site Pumping	Operating Press: 2-3 psi	11,9 gpm @ 0941
North End Off-Site Pumping	Operating Press: 2-6 psi	8.5 gpm @ 0941
Peroxide Feed Pump (P-680)		SPD 2.4 % / RATE 0.7
Peroxide Conc. At (TP-710)	(,O PPM	
Peroxide Conc. At (TP-740)	o.o PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	~	Check sheet completed: NA/Empty
Satellite Haz. Waste Areas (BLDG #1)		Condition: IX LUSIN + MATE GOOD
Satellite Haz. Waste Area (BLDG #2)		Condition: Grand

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	~ 4D	
Annual Test Run (Calgon)	Date: 9-16-1221	Next: 9-2022
Quarterly Test Run	Date: NA/Rummy	Next: Nukummy
Peroxide Feed Pump (P-650)	V	Flow Rate: ~ 7.1 cc/min.
UV-Ox Power		25.7 kVA 2561 Volts 121 Amps
Lamp Hours	1677 Hrs	
Crystal Condition & Wiper Status	~	Oiler status: ou
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned:7-13-21	/2.5 psi In /2.5 psi Out
UV-OX Feed Pump (P-600 or (P-601)		CV@ 77 % @ 7.5 gpm
UV-OX Temperature	In(TT-670): /3,3 °C	Out(TT-710): 25.9 °C
PDU GAC (PDT-710)	/	Δ Pressure: 4 psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	Za PPM	
Peroxide Conc. Post PDU (TP-730)	PPM درو	
Secondary Acid Feed Pump (P-630)		CV@ 3 %
Secondary Acid Retention Tank (T-645)	/	
Pre – UV Oxidizer Total (FT-670)	20869176 gal	Time: 6947
Post UV-Ox / Pre PDU		Pressure: 14.5 psi
Post PDU		Pressure: 8.0 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, January 06, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	~	Δ Pressure: /3 psi
PDT-730		Δ Pressure: 9 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751) or P752)		CV@ 54.5 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		32.4 gpm @ 0945
POTW Line Pressure (PT-770)		32.1 psi
Effluent Totalizer Reading (FT-770)	248 967866 gal	Time: 0948
POTW MH17S-078 Discharge Check (Monthly)	/	Last Done: /2-13-2/
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done: ✓
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done: //-8-2/
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	/	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 12-23-21	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or N
Verify Bridge Current between.300v360v	Reading: 0.30 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0949-0955

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19760493	(FT-505) LFG Cond. to T-530	219567
(FT-025) NBBW Influent	94696971	(FT-056) Off - Site N. End Influent	44027060
(FT-012) MW-38 Inf. to HMR-30	8456081	(FT-113) Ion Exchange Influent	(03.3023
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30073924
(FT-043) MW-38 to RWST	3085327	(FT-026) NBBW Bypass to RWST	4427726
(FT-042 RWST) MW-38 Source to RWST	72736	(FT-014) Misc. Water to RWST	8215198
(FT-012T) MW-38 to T-540/541	8646830	(FT-035) NTES Inf. to BIO	6711642
(FT-040T) MW-38N to T-540/541	1978778	(FT-035T) NTES to T-530	466341
(FT-041T) MW-38S to T-540/541	2697029	(FT-017) BIO Inf. from T-530	659780
(FT-042T) MW-38 Source to T-540/541	4043007	(FT-018) T-540/541 Influent	8691532
(FT-055) On - Site N. End Influent	99437693	(FT-352) T-352 to HMR-30	1322529

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

P. AIR COMPRESSORS	Status	Comments
Compressor Intake Temp.	40 °F (Analog Gauge)	Outside Temp.: ~ 4 °F
Compressor Building Vent	76 1 (Allalog Gauge)	Closed - operand
Primary Air Compressor	2,000 Hour service date: 7-8-21	Coolant present in sight glass: Ø / N
(IRN30H)	Serviced @ 6-952 Hours	Next service @ 62152 Hours Current Hours @ 62153
IRN30H Motor Speed	0 %	
IRN30H Pressure	(Zo psi	
IRN30H Moisture purge valve chk(Weekly):	~	
IRN30H Intake Filter		Date Last Changed: 9-30-2/
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / (N)
Backup Air Compressors (T-30 East and West)		Both cool to touch: 🟠 / N
Air Dryer	V Eco on	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: /2-23-2/	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		(10 psi
Bag Filter Sump Wet Well Sump		
R. GAS CHROMATOGRA	\PH	
Item	Status	Comments
GC Operational	/	GC # checking UV-Ox Effluent: # /
Alarms Enabled		EC-Californion + matrix 1-5-22
GC Influent Filters		
S. SAFETY		A 1977 - 1977 - 1977 - 1978 - 1977 -
- C-15-monner - C	Status	Comments
	/	Date inspected: /Z-2Z-2/
Building #1 Fire Extinguishers		Checked and Flushed- All OK: 🔗 / I
Building #1 Fire Extinguishers		
Building #1 Fire Extinguishers Building #1 Eye Wash/Shower Other Comments:	No an least ! Las Illas	1220 657 taken eff standby

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022		
Inspection Performed by:	Mike Gelwick		

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					and the state of t
P-3301	/	1.85	33.6 %	6.5	
P-3301A	SB	_	- %		
NTES Pump P-002(Sump) / (P-002W(10R))	v	0.53	48 %	P035 P038	Globules Observed at TP-130: Y / P
T-530 P-005	~	0.21	41 %	7.0	
T-540/541 P-006	/	0.30	73 %	7.5	
LFG COND Auto-Traps	~	0.0	NA	5,0	Between Cycles: Ø / N
Reactor Feed Pumps				A Service Commission	
P-3321	/	2.43	55.9 %	7,5	
P-3322	V	3.44	46.9 %	5.0	
P-3323	V	2.44	79.0 %	6.0	
P-3324	28	-	- %	_	
Reactor Effluent Pumps	- 5	Walanama and American			
P-3341	1	2.80	57.9 %	15.0	
P-3341A	58	-	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-20-2/
B-3331		4.25	110	3-2022	Greased, Belt and Filter Checked: (Y) / N
B-3332	5B	-	-	1	Belt and Filter Checked: Y / (N)
B-3333	/	4.30	110		Greased, Belt and Filter Checked: / N
B-3334	/	4.27	109	V	Greased, Belt and Filter Checked: ① / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	/	On-line: 2/10/18
Reactor Vent Blower	~	
Reactor Vent Booster	/	
VTP-3350	1	PID Reading: (7.6 PPM
VTP-3360	/	PID Reading: pois PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments	
T-510 Post HMR-30 Mixing Tank	Level: 66 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21	
T-530 LFG Condensate / NTES Tank	✓ Level: 30 %		
T-530 Mixer	~		
LFG Condensate Conveyance Line	V	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)	
T-540/541 MW38 Tanks	Lvls: 47 % & 48 %		
T-540/541 Mixers			
Chiller	/	Chiller Coolant Lvl: ~ _ " Below full mark	
Chiller Cooling Fins (as needed)	/	Last Cleaning: 4/20/18 (unit on Standby)	
Secondary Containments	/	Heat Trace: On OK)/ Off Warm out	
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 12-22-21	
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021	
T-3320 Blend Tank	✓ Level: 70 %	Last Cleaning (Semi Annual): 9-10-21	
T-3331 Reactor No. 1	/	Digital Displays: GOOD \ Needs Attn	
T-3332 Reactor No. 2	· ·	Digital Displays: GOOD Needs Attn	
T-3333 Reactor No. 3	~	Digital Displays: GOOD// Needs Attn	
T-3334 Settling Tank		Last Cleaning (Semi Annual): 9-10-21	
P-3334 Biosolids Pump	/		
T-3340 Overflow Tank	✓ Level: 30 %		
Recycle Valve to Blend Tank	/	4.00 gpm @ 1006	
Building Containment Sump		Last Alarm Test Date (Monthly): /2-/6-2/	

E. CHEMICAL FEED SYSTEM

Item	Status	Comments	
Phosphorous Supply	~	Bags: /4 Gallons: ~ /00	
Phosphorous Pump (P-2221)	/		
Caustic Supply	V	~ 210 Gallons	
Caustic Pump (P-2211)	SB Currently in acid addition mode		
Acid Supply	V	~ 4o Gallons	
Acid Pump (P-2211)	V		
Caustic Pump (P-2231)	✓ Leaks: Y /	(D) Last tubing tip cleaning (monthly): 12-16-21	
Caustic Pump (P-2232)	Leaks: Y / 🛈 Last tubing tip cleaning (monthly):		
Caustic Pump (P-2233)	✓ Leaks: Y /	iks: Y / D Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

H Probe Location Calibration Date (Monthly)		Comments	
pH-3320 Blend Tank	12-23-21	SAray OF FClean tulay	
pH-3331 Reactor 1		1	
pH-3332 Reactor 2			
pH-3333 Reactor 3	V	√	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	·	
Automatic Backwash	Cycle Count: 11	Reset
BF-3340 a/b Differential Pressure	PSI: (14/13 2 2.400m
75-micron Bags Last Cleaning	Date: / !-!4-19	
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date: V	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 6	13/7 = 2.45M
Last Backwash Performed	Date: 9-77-21	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments	
"BIO" Backup Generator			Block Heater On Oly / Off Warm Out	
Electrical Surge Suppressor	V			
Motor Control Center	~			
PLC	V		UPS @ 97 min / 95 Events	
HMI's	~	20		
BTS Process KWH Meter	1833969	KWH	Time: 1109	
Building#2 KWH Meter	5301385	KWH	Time: [109	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V	GC # checking BIO: ₩2
Alarms Enabled	V	ce-caribourson a marrier 15-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 06, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments	
FT-3321 Feed to Reactor 1	6229099		
FT-3324 Feed Spare	122780		
FT-3322 Feed to Reactor 2	11067394		
FT-3323 Feed to Reactor 3	913489		
FT-3301 T-510 to BIO	51722809		
FT-3341 BIO Effluent	66616262		
FT-3342 BIO Recycle	55958162		

K. SAFETY

em Status		Comments
Building #2 Fire Extinguishers	~	Inspection date: /2-72-2/
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N

L.	OTHER COMMENTS:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, January 13, 2022

Inspection Performed by: Chris Carlson

A. PERIMETER COLLECTION SYSTEMS

Item	Status		Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12	.73 00	Counter: 193 458	Cycles: /092
LFG Cond Automatic Trap CT-2	Sump Level: 8	16204	Counter: 274946	Cycles: 227
LFG Cond Automatic Trap CT-3	Sump Level: 7	.23 on	Counter: 319 405	Cycles: 788
CT-4 Containment/Vessel (LFG Cond)		32 %	Tank Level: / 94 Counter: /9/261	Cycles: O Sump: 8.27
PM-15 Containment / Vessel	ب Level: ٩	17%		2.0
MW-51 Containment / Vessel		5 %	W 8	
PM-11 Containment / Vessel	Level: •	10 %	Gory found 1-14-22	
MW-38 Systems				0,00000000000000
North Toe System	/			
North End Systems (Weekly)	V			
Full N. End Systems Check (Monthly)	/		Last Done: 12-22-21	
North End Pipeline(s)Flushing (As Needed)	V		Perform if suspended solids present La	ast Done: 11/15/15
NTES line flush to T-530 (As needed)	✓		Perform if suspended solids present La	
NTES Piping Containment			Monthly Sump Level: Dry &	
North Boundary System P-001:	CV 73.1% @ 6.1	U gpm	40,43 Hz / 2,05 Amps. / va	ault psi @ 18 (no lak)
T-101 & T-102 Containment / Tank			Levels: 16 % & 10	% e 0837 level low.
Raw Water Storage Tanks Piping	/			
RWST Building Temp. (TT-101)	53.9	°F	Outside Temp.: ~ 56	r °F
P-121 or P-122	UN SB While RI	estlow	- 0 = 0 gpm / CV -	%
RWST 2ndry Cont. High Level Switch	V		(LSH-101) Last Test(month	ly): 12/16/21
RWST Back-Up Generator			Last Test Run(monthly):	2/16/21

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~ 500 Gallons Reserve = 3 to tes
Caustic Bay Heater		
Peroxide Tote Level		~ 240 Gallons Reserve = ~ 55 94 / ~ 30 Gallons Reserve = / 16443044
HCL Tote Levels		~ 30 Gallons Reserve = 1 to fc+304 =
Chemical Totes and Piping Inspected		Leaks observed: Y / (A)
Emergency Shower Inspected	/	Checked and Flushed - All OK: (Y) / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	V	
Ion Exchange Acid Feed Pump (P-632)	V	PI-0632 PSI: 90-90 CV 3%
Primary Acid Retention Tank (T-510)	V	
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 13, 2022		
Inspection Performed by:	Chris Carlson		

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	· .	Last Cleaning (Qtrly): (0 2 0 21
T-300A/B Water Level	V	
T-300B (Caustic Mix Chamber)	V /	Last Cleaning (Qtrly): [6 20 21
T-300A/B Overflow	V	
pH Set-point for (pH 315)	Value: Lo. 8	
pH 310	Value: 6, 88	
pH 315	Value: [0,79	
Flocculation Chamber Paddle Wheel	V	
Precipitate Floc Quality	V	6000
Clarifier Water Quality	/	Gwu Oil or sheen observed: Y (N)
Clarifier Effluent Piping / Water Level	V .	
Clear-well Chamber and Water Level	V	
HMR PLC Panel	V	50 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -
Caustic Pump (P-270)	ŚB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)	V	
Polymer Tank Mixer	V	
Polymer Tank Level	Gallons: ~ 475	
Clear-well Transfer Pumps(P-371)/ 372)	V.	
Sludge Transfer Pump (P-330)	V	Exercise Valves Weekly: Both okar
Manual Sludge Lateral pumping	V .	Last done (As Needed) 1 2 3/20/21 3 7/20/2
Manual Sludge Lateral Ball Valves		Exercise Weekly: All 6K
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date		Comments: (Time de	one)	
pH-310 HMR-30 (T-300A)	1	13	122	1309	*
pH-315 HMR-30 (T-300B)		7			
pH-365 Primary Acid Ret. Tank					
pH-113 Pre-Ion Exchange					5.5
pH-670 Pre-UV-OX		/	/-		► 1341
pH-740 Discharge Surge Tank		$\neg \lor$		Discharge suspended	B00++ 1308
Out of Hold Double Check				None in hold:	A (W)
Valves Back to Normal Position				All OK: VVI	(w)

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	~	Gauge Reading: ()%
Sludge Thick. Transfer Pump (P-350)	V.	
Sludge Holding Tank (T-351)		Level:~ 25 %
Sludge Holding Tank (T-352)	V	Level: 4/6 %
Decant Transfer Pump (P-352)		CV 71% @ 0.6gpm
Filter Press Pumps (P-381 / P-382)	7	P-381 being rebuilt. P-382 ga
Filter Press	V	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, January 13, 2022

Inspection Performed by: Chris Carlson

Chris Carlson

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 3 ° %	
Feed Pump (P-114)	Operating Press: 37.(psi	CV@ 44% @ 1,9gpm
Retention Tank (T-114)	Operating Press: 36 psi	pH-113 @ 3.78
Bag Filter (BF-113)	Operating Press: 4/0psi	Cokina
Ion Exchange (Cage 1 or 2) + Guard	Operating Press: 36 psi	Deliver 2 alstine 1/12/22 6:70 15 Tradby
Post Ion Exchange	Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	✓ Level: 39 %	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 10 psi	CV@ 54 % @ 34.3 gpm
T-520 to GAC Total (FT-675)	255137724 gal	Time: 0653
North End On-Site Pumping	Operating Press: 2-3 psi	13.3 gpm @ 0652
North End Off-Site Pumping	Operating Press: 2-5 psi	8.4gpm @ 0652
Peroxide Feed Pump (P-680)	V	SPD 2.6% / RATE 0.7
Peroxide Conc. At (TP-710)	₹ PPM	-
Peroxide Conc. At (TP-740)	O PPM	1000

J. HAZARDOUS WASTE STORAGE

	Item		Status	Comments
60	180 Day storage area check (Epusodic		Check sheet completed: V () 1 0 22
	Satellite Haz. Waste Areas (Bl	DG #1)	~	Condition: Ix Resin & Main bowl.
	Satellite Haz. Waste Area (BL	DG #2)	✓	Condition: Gove

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	V	
Annual Test Run (Calgon)	Date: 9/16/21	Next: 9 /2022
Quarterly Test Run	Date: NA RUNNING	Next: NA / RUNNING
Peroxide Feed Pump (P-650)		Next: NA / Running Flow Rate: ~ 7.2 cc/min.
UV-Ox Power	V	25.8 kVA 2530 Volts (0.1 Amps
Lamp Hours	1839 Hrs	
Crystal Condition & Wiper Status	./	Oiler status: Guel Refilled today.
UV-OX Bagfilters Status	Last change: 3 13 2 Cleaned: 7 [3]2	/4 psi In /4 psi Out
UV-OX Feed Pump (P-600 or (P-601)		CV@ 82% @ 7.4 gpm
UV-OX Temperature	In(TT-670): 12.8 °C	Out(TT-710): 25.1 °C
PDU GAC (PDT-710)	~	Δ Pressure: 6 psi
Peroxide Concentration Pre UV	Ø PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	<i>O</i> PPM	
Secondary Acid Feed Pump (P-630)	~	CV @ 3%
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	20939072 gal	Time: 0640
Post UV-Ox / Pre PDU	V.	Pressure: 13 3.75 %si
Post PDU		Pressure: 7.75 psi

Table 3.19.1 Rev 7.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, January 13, 2022

Inspection Performed by: Chris Carlson

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item			Status	Comments
PDT-720	NEW GAC	1/10/22 6	3	Δ Pressure: $\boldsymbol{\mathcal{X}}$ psi
PDT-730	NEW GAL	1110/22 (4		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or P752)		CV@ 55.4%
Effluent Surge Tank (T-740)		Level: 40%
Effluent Discharge Rate (FT-770)	~	34.4 gpm @ 0656
POTW Line Pressure (PT-770)	V	32.4 psi
Effluent Totalizer Reading (FT-770)	249264110 gal	Time: 0656
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: [2]/3 21
4X8-Inch POTW Leak Detection Checks (Monthly)	V	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	/	Last Done: \$\\\[\frac{11\\xi}{2}\ \]
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 5/49/20 2 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	-	Last Done: 5/19/20 //
2-Inch POTW Isolation Valve Exercise (Annual)	r	Last Done: 5/19/20
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	<i>N</i>	Reading: 6%
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 1/2/21	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.00 / volts(monthly)	Adjustment Needed: Y or 🐼
Verify Bridge Current between.300v360v	Reading: 0.33 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 109 - 1115

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19771104	(FT-505) LFG Cond. to T-530	219892
(FT-025) NBBW Influent	94759075	(FT-113) Ion Exchange Influent	1052108
(FT-012) MW-38 Inf. to HMR-30	8469407	(FT-056) Off - Site N. End Influent	44111516
(FT-042 HMR30) MW-38 Source to HMR-30	354184	(FT-810) Plant Potable Water In	30074898
(FT-043) MW-38 to RWST	3086016	(FT-026) NBBW Bypass to RWST	4430359
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8215199
(FT-012T) MW-38 to T-540/541	8654647	(FT-035) NTES Inf. to BIO	6716541
(FT-040T) MW-38N to T-540/541	1978784	(FT-035T) NTES to T-530	466632
(FT-041T) MW-38S to T-540/541	2697035	(FT-017) BIO Inf. from T-530	660269
(FT-042T) MW-38 Source to T-540/541	4050820	(FT-018) T-540/541 Influent	8694405
(FT-055) On - Site N. End Influent	99562239	(FT-352) T-352 to HMR-30	1326755

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, January 13, 2022

Inspection Date:

P. AIR COMPRESSORS	The state of the s	T-2
Item	Status	Comments
Compressor Intake Temp.	71 °F (Analog Gauge)	Outside Temp.: ~ 50 °F
Compressor Building Vent	V grate	0
Primary Air Compressor	2,000 Hour service date: 7/8/1	Coolant present in sight glass: \(\mathbb{V} \) N
(IRN30H)	Serviced @ 60952 Hours	Next service @ 62952 Hours Current Hours @ 62646
IRN30H Motor Speed	31 %	•
IRN30H Pressure	[[9 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter	V	Date Last Changed: 9 30 21
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / 4P
Backup Air Compressors		
(T-30 East and West)		Both cool to touch: (Y) / N
Air Dryer	V ECO IN	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: /2/23/21	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	19	//o psi
Q. SUMPS Item Bag Filter Sump	Status	Comments
	V .	
Wet Well Sump	V	
R. GAS CHROMATOGRA	PH	
Item	Status	Comments
GC Operational	~	GC # checking UV-Ox Effluent: /
Alarms Enabled	~	
GC Influent Filters		
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers		Date inspected: [2/22/2/
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: (Y) / N
Other Comments: New virgin Ditunion (Column #2 of IX sys Standby 1/12/22 @		1/10/22@ lunns#65#7 +AKEN . Ff

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 13, 2022	
Inspection Performed by:	Chris Carlson	

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	1	1.90	35.0%	7	
P-3301A	513		- %		
P-002(Sump) P-002W(10R)	V	0.51	નુષ્ઠ %	P035 P038	Globules Observed at TP-130: Y /N Time: 0345 (Tom)
T-530 P-005	V	0.20	41 %	7	
T-540/541 P-006	~	0.21	63 %	7.5	
LFG COND Auto-Traps	V	0.0	NA	4	Between Cycles: (Y)/ N
Reactor Feed Pumps					
P-3321	V	1.12	42.7%	8.0	
P-3322	V	1.39	JE, 1%	6.0	
P-3323	53	_	%	-	
P-3324	V	1.29	62.0%	6.5	
Reactor Effluent Pumps				DEC.	
P-3341	V	1.90	48.0%	17	The second secon
P-3341A	5 B	_	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: (2/20/2/
B-3331		4.21	139	3/2022	Greased, Belt and Filter Checked: (Y) / N
B-3332	18		_	1	Belt and Filter Checked: Y / (N)
B-3333	V	4,36	137		Greased, Belt and Filter Checked: // N
B-3334	V	4.20	128	V	Greased, Belt and Filter Checked: (7) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	V	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	V	
VTP-3350	V	PID Reading: 9.6 PPM
VTP-3360	V	PID Reading: 4.7 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 13, 2022
Inspection Performed by:	Chris Carlson

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	Level: 31 %	Last Cleaning (As needed, if 2" of solids accumulate): 12/15/19
T-530 LFG Condensate / NTES Tank	✓ Level: 3/ %	
T-530 Mixer		
LFG Condensate Conveyance Line	-	Last Pressure Test: 7/19/21 Next: 7/2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 8/ % & 82%	
T-540/541 Mixers	V	
Chiller	- offline -	Chiller Coolant Lvl: ~ — " Below full mark
Chiller Cooling Fins (as needed)	- OFFILME -	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	1/	Heat Trace: On OK Off Warm out
Feed Piping to Sedimentation Tank	~ ·	Last Back Flushing (Quarterly): 12/22/21
T-3310 Sedimentation Tank	Visual Level: 🛝	Last Cleaning (As Needed, use TSS info to determine): 12/2017 9/2021
T-3320 Blend Tank	✓ Level: 72 %	Last Cleaning (Semi Annual): 9/(0/2)
T-3331 Reactor No. 1	V	Digital Displays: GOOD/ Needs Attn
T-3332 Reactor No. 2		Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3		Digital Displays: GOOP / Needs Attn
T-3334 Settling Tank	V	Last Cleaning (Semi Annual): 9/10/2/
P-3334 Biosolids Pump	V	
T-3340 Overflow Tank	✓ Level: 3/ %	
Recycle Valve to Blend Tank	V	4.00 gpm @ 1050
Building Containment Sump	V	Last Alarm Test Date (Monthly): (2/16/2)

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	V	Bags: /3, 75 Gallons: ~ /60
Phosphorous Pump (P-2221)	V	
Caustic Supply	V	~ 200 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	√	
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): 12/16/21
Caustic Pump (P-2232)	Leaks: Y /	(N) Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	(N) Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 13, 2022	
Inspection Performed by:	Chris Carlson	

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	12/23/21	RIADEC Clean Today
pH-3331 Reactor 1		
pH-3332 Reactor 2		1/
pH-3333 Reactor 3		V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 9	
BF-3340 a/b Differential Pressure	PSI: (12/12/12
75-micron Bags Last Cleaning	Date: 11 // 1/19	1 / 19/1-
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date: V	
GACF-3340 Status	V	- 1 Marie - 1 Ma
GACF-3340 Differential Pressure	PSI: 4	12/7 07.7610
Last Backwash Performed	Date: 9/21/2/	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator		Block Heater: On OK Off Warm Out
Electrical Surge Suppressor	V	
Motor Control Center	/	
PLC	V	UPS @ 97 min / 95 Events
HMI's	/ .	
BTS Process KWH Meter	1836571 KWH	Time: (054
Building#2 KWH Meter	5366 186 KWH	Time: Losy

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V	GC # checking BIO: 2
Alarms Enabled	V	
GC Influent Filters	V	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 13, 2022
Inspection Performed by:	Chris Carlson

J. TOTALIZERS

Item	Readings (gallons)	Comments	
FT-3321 Feed to Reactor 1	6250458		
FT-3324 Feed Spare	122984		
FT-3322 Feed to Reactor 2	11097077		
FT-3323 Feed to Reactor 3	934327		
FT-3301 T-510 to BIO	51740233		
FT-3341 BIO Effluent	666 41670		
FT-3342 BIO Recycle	56000312		

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	V	Inspection date: 2/22/21
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (Y) / N

L. OT	HER COMMENTS:		
	S NA		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12.6304	
LFG Cond Automatic Trap CT-2	Sump Level: 8.71	Counter: 274946 275313 Cycles: 227367
LFG Cond Automatic Trap CT-3	Sump Level:).50 .*	Counter: 319405319628 Cycles: 788-223
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 84 %	Tank Level: 1.40 Counter: 19/262 Cycles: 1 Sump: 8.78 06
PM-15 Containment / Vessel	Level: 55 %	
MW-51 Containment / Vessel	∠ Level: 28 %	800000000000000000000000000000000000000
PM-11 Containment / Vessel	✓ Level: 55 %	
MW-38 Systems		
North Toe System	~	
North End Systems (Weekly)	~	
Full N. End Systems Check (Monthly)		Last Done: /2-22- 2 \
North End Pipeline(s)Flushing (As Needed)	·	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	_	Monthly Sump Level: 47 2/607 Date: 1-20-22-19
North Boundary System P-001:	CV73.3%@6.3gpm	40.43 Hz/2.0) Amps. / vault psi @ 18 (No leases
T-101 & T-102 Containment / Tank		Levels: /6 % & /4 %
Raw Water Storage Tanks Piping	_	
RWST Building Temp. (TT-101)	54.8 °F	Outside Temp.: ~ Z 8 °F
(P-121) or P-122	~	0.60 gpm/CV 66 %
RWST 2ndry Cont. High Level Switch	_	(LSH-101) Last Test(monthly): /-20-22 - Polary
RWST Back-Up Generator		Last Test Run(monthly): 1-20-22-12ky

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~ 370 Gallons Reserve = 3757 es
Caustic Bay Heater		
Peroxide Tote Level	~	~ 225 Gallons Reserve = 55 year
HCL Tote Levels	-	مرود = - عدد - Reserve = - عدد
Chemical Totes and Piping Inspected	-	Leaks observed: Y / DP
Emergency Shower Inspected		Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	~	PI-0632 PSI: 92-94 CV: 3 %
Primary Acid Retention Tank (T-510)	~	
All Acid Feed Lines	~	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

Table 3.19.1 Rev 7 WTP.docx

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	/	Last Cleaning (Qtrly): (0-20-21
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	_	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10,90	
pH 310	Value: 6.82	
pH 315	Value: 10.37	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	Good
Clarifier Water Quality	/	Good Oil or sheen observed: Y / (N
Clarifier Effluent Piping / Water Level	V	
Clear-well Chamber and Water Level	~	
HMR PLC Panel	V	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	-	
Polymer Pump (P-310)		
Polymer Tank Mixer	·	
Polymer Tank Level	Gallons: ~ 350	
Clear-well Transfer Pumps (P-371)/ 372)		
Sludge Transfer Pump (P-330)		Exercise Valves Weekly: Loth ok
Manual Sludge Lateral pumping		Last done (As Needed): 4/+2-3-20-21 /43-7-20
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: Allok
Automatic Blow-down Operations	/	

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	1-20-22-10/41	1341
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1405
pH-740 Discharge Surge Tank	V	Discharge suspended: £332 ← ►1340
Out of Hold Double Check		None in hold: W/4 m
Valves Back to Normal Position		All OK: Vid um

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	/	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)	/	Level:~ 40 %
Sludge Holding Tank (T-352)	/	Level: 41 %
Decant Transfer Pump (P-352)	/	CV69 % @0.5 gpm
Filter Press Pumps (P-381 / P-382)		P-381 berny Rebull+, A-382 04
Filter Press	/	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 38.cpsi	CV@ 73 % @ 1.9 gpm
Retention Tank (T-114)	Operating Press: 39 psi	pH-113 @ 3.72
Bag Filter (BF-113)	✓ Operating Press: 41 psi	
Ion Exchange (Cage 1) or 2) + Guard	Operating Press: 37 psi	TP-174A = TP-176Af Scanssters + Concer
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 39 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522))	Operating Press: 10 psi	CV@ 55 % @ 34.0 gpm
T-520 to GAC Total (FT-675)	255472737 gal	Time: 1028
North End On-Site Pumping	Operating Press: 2-3 psi	12.6 gpm @ 1021
North End Off-Site Pumping	Operating Press: 2-6 psi	9.3 gpm @ 1021
Peroxide Feed Pump (P-680)	~	SPD 2,6 % / RATE 0,7
Peroxide Conc. At (TP-710)	(O PPM	
Peroxide Conc. At (TP-740)	ao PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
62186 Day storage area check (Engoline)		Check sheet completed: yes me 1-20
Satellite Haz. Waste Areas (BLDG #1)	/	Condition: Extern + main Good
Satellite Haz. Waste Area (BLDG #2)		Condition: Gusad

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Rumma	Next: NA/Lunurus
Peroxide Feed Pump (P-650)		Flow Rate: ~ 2.2 cc/min.
UV-Ox Power		25.7 kVA 2539 Volts 10.3 Amps
Lamp Hours	2 <i>009</i> Hrs	
Crystal Condition & Wiper Status		Oiler status: OK
UV-OX Bagfilters Status	Last change: 7-(3-2) Cleaned: 7-(3-2)	9.5 psiln 9.5 psiOut
UV-OX Feed Pump (P-600 or (P-601))	V	CV@ 66 % @ 7.4 gpm
UV-OX Temperature	In(TT-670): /3.3 °C	Out(TT-710): 25.9 °C
PDU GAC (PDT-710)	· BALKENSSED TODAY	Δ Pressure: psi
Peroxide Concentration Pre UV	(∞ PPM	
Peroxide Concentration Post UV(TP-720)	Z5 PPM	
Peroxide Conc. Post PDU (TP-730)	O.o PPM	
Secondary Acid Feed Pump (P-630)		CV@ 3 %
Secondary Acid Retention Tank (T-645)	~	
Pre – UV Oxidizer Total (FT-670)	Z1011672 gal	Time: 1029
Post UV-Ox / Pre PDU		Pressure: // psi
Post PDU		Pressure: 7.5 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022	
Inspection Performed by:	Mike Gelwick	

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments	
PDT-720		Δ Pressure: 3 p	si
PDT-730	~	Δ Pressure: 3 p	si

M. EFFLUENT DISCHARGE

Item	Status	Comments	
Effluent Surge Pump (P751) or P752)	~	CV@ 55,4 %	
Effluent Surge Tank (T-740)	~	Level: 40 %	
Effluent Discharge Rate (FT-770)		340 gpm @ 1025	
POTW Line Pressure (PT-770)		32,4 psi	
Effluent Totalizer Reading (FT-770)	249619996 gal	Time: 1029	
POTW MH17S-078 Discharge Check (Monthly)		Last Done: (~17-22	
4X8-Inch POTW Leak Detection Checks (Monthly)	V _	Last Done:	
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:	
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done: 11-8-21	
2-Inch POTW Backup Pressure Testing (Annual)	~	Last Done: 7/8/21	
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21	
2-Inch POTW Isolation Valve Exercise (Annual)	~	Last Done: 7/8/21	
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2	

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	V	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 12-23-2 l	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or (1)
Verify Bridge Current between.300v360v	Reading: o.330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: (030-1035

Source Reading(Gallons)		Source	Reading(Gallons	
(FT-015) RWST Influent	015) RWST Influent (9780332			
(FT-025) NBBW Influent	94821643	(FT-056) Off - Site N. End Influent	44196116	
(FT-012) MW-38 Inf. to HMR-30 848379		(FT-113) Ion Exchange Influent	1070945	
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30075425	
(FT-043) MW-38 to RWST	3090578	(FT-026) NBBW Bypass to RWST	4431446	
(FT-042 RWST) MW-38 Source to RWST 72734 (FT-012T) MW-38 to T-540/541 8655376		(FT-014) Misc. Water to RWST	8219124	
		(FT-035) NTES Inf. to BIO		
(FT-040T) MW-38N to T-540/541	1979086	(FT-035T) NTES to T-530	466877	
(FT-041T) MW-38S to T-540/541	2697441	(FT-017) BIO Inf. from T-530		
(FT-042T) MW-38 Source to T-540/541	4050820	(FT-018) T-540/541 Influent	8697029	
(FT-055) On - Site N. End Influent 99690964		(FT-352) T-352 to HMR-30	1329611	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, January 20, 2022

Primary Air Compressor (IRN30H)	Status 64 °F (Analog Gauge)	
Compressor Building Vent Primary Air Compressor (IRN30H)		Outside Temp.: ~ 30 °F
Primary Air Compressor (IRN30H)		open - operational
(IRN30H)	2,000 Hour service date: 7-8-21	Coolant present in sight glass: Ø / N
IDMONU Motor Cross	Serviced @ 60952 Hours	Next service @ 62952 Hours Current Hours @ 62751
IRN30H Motor Speed	31 %	
IRN30H Pressure	//S psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter	~	Date Last Changed: 9-30-21
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / 💭
Backup Air Compressors		
(T-30 East and West)		Both cool to touch: 🍄 / N
Air Dryer	~ Ecopy	Moisture at Receiver Tank: Y / 🐠
Oil Moisture Prevention (Monthly)	Last Done: /2-23-21	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		llo psi
O SUMPS		
Q. SUMPS	Status	Comments
Item	Status	Comments
CONTRACTOR	Status	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA	PH	
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item	Ž	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational	PH	Comments GC # checking UV-Ox Effluent: 4/
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	PH	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	PH Status	Comments GC # checking UV-Ox Effluent: # CC- Calvanton + mant -19-22
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item	PH	Comments GC # checking UV-Ox Effluent: # cc-cause + ment -19-22
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	PH Status	Comments GC # checking UV-Ox Effluent: # CC- Calvanton + mant -19-22

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022		
Inspection Performed by:	Mike Gelwick		

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)		Comments
T-510 Pumps						
P-3301	/	1.84	34.1 %	7.	0	
P-3301A	38	_	- %	_		
NTES Pump P-002(Sump) / (P-002W(10R))	~	0.51	48 %	P035	P038	Globules Observed at TP-130: Y / (N) Time: 0900
T-530 P-005	V	0.19	41 %	107-1	.0	
T-540/541 P-006	~	0.30	65 %	7.	6	
LFG COND Auto-Traps	/	0.0	NA	5.0	>	Between Cycles: 💮 / N
Reactor Feed Pumps					ALW - P-P-	
P-3321	~	2.49	67.5 %	3.5	(č	
P-3322	~	3.49	50.3 %	6.0		
P-3323	58	_	- %	-		
P-3324	V	2.49	44.7 %	6.5		
Reactor Effluent Pumps						
P-3341	~	2,83	63.1 %	18		
P-3341A	58	_	- %	-		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-20-2/
B-3331	~	4.23	124	3-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	35	_	_		Belt and Filter Checked: Y / 🐠
B-3333	~	4.40	122		Greased, Belt and Filter Checked: Ø / N
B-3334		4,26	114	V	Greased, Belt and Filter Checked: 🚫 / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	~	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster		
VTP-3350		PID Reading: 22.6 PPM
VTP-3360	/	PID Reading: 15.8 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	Level: 53 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 34 %	
T-530 Mixer	~	
LFG Condensate Conveyance Line	~	Last Pressure Test: 7-4-21 Next: 7-20-27 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 67 % &68 %	
T-540/541 Mixers	-	
Chiller	offlowe	Chiller Coolant Lvl: ~ _ " Below full mark
Chiller Cooling Fins (as needed)	offlow	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On Old / Off Warm out
Feed Piping to Sedimentation Tank	~	Last Back Flushing (Quarterly): /2-22-2(
T-3310 Sedimentation Tank	Visual Level: 04	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	~	Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	~	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	~	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	~	4.00 gpm @ 1057
Building Containment Sump	/	Last Alarm Test Date (Monthly): ١-20-22-

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	~	Bags: /3.5 Gallons: ~ 72
Phosphorous Pump (P-2221)	~	
Caustic Supply	V	~ 170 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	~	~ 40 Gallons
Acid Pump (P-2211)	V	1-20-227
Caustic Pump (P-2231)	Leaks: Y / (V	Last tubing tip cleaning (monthly):
Caustic Pump (P-2232)	Leaks: Y / (N)	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	✓ Leaks: Y / (N)	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	12-23-21	Acod/Buse clean potacy
pH-3331 Reactor 1	1	/
pH-3332 Reactor 2		1,
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 7	LegaT
BF-3340 a/b Differential Pressure	PSI: (8/9 21.3 000
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 2.5	9/6.5 21.3,An
Last Backwash Performed	Date: 9-27-21	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator		Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor		
Motor Control Center		
PLC		UPS @ 97 min / 95 Events
HMI's		
BTS Process KWH Meter	1839044 KWH	Time: 1202
Building#2 KWH Meter	5315014 KWH	Time: /202

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: ₩2
Alarms Enabled	V	cc-culidonorum + marris 1-29-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 20, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6271783	
FT-3324 Feed Spare	143653	
FT-3322 Feed to Reactor 2	11126020	
FT-3323 Feed to Reactor 3	934327	
FT-3301 T-510 to BIO	51756103	
FT-3341 BIO Effluent	66665203	
FT-3342 BIO Recycle	56042107	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	-	Inspection date: 12-22-21
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: 🕜 / N

-

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

A. PERIMETER COLLECTION	STOTEMO	
Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: /2.66 ot	
LFG Cond Automatic Trap CT-2		Counter: 275366 Cycles: 53
LFG Cond Automatic Trap CT-3		Counter: 319656 Cycles: 28
CT-4 Containment/Vessel (LFG Cond)	Level: 85 %	Tank Level: 19 Counter: 19126 Cycles: Sump: 8.78
PM-15 Containment / Vessel	Level: 60 %	1,30 191262 0 3,850
MW-51 Containment / Vessel	Level: 55 %	
PM-11 Containment / Vessel	Level: 45 %	
MW-38 Systems	/	
North Toe System	~	
North End Systems (Weekly)	<i>∨</i>	
Full N. End Systems Check (Monthly)	_	Last Done: /-Z/-ZZ
North End Pipeline(s)Flushing (As Needed)	V	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: 17 216.07' Date: 1-20-22
North Boundary System P-001:	CV 73.2 % @ 6.2 gpm	40.41 Hz / 2.06 Amps. / vault psi @ 18/00 leves
T-101 & T-102 Containment / Tank		Levels: 35 % & 34 %
Raw Water Storage Tanks Piping	-	
RWST Building Temp. (TT-101)	54,1°F	Outside Temp.: ~ 2 6 °F
P-120 or P-122	v	1.0 gpm/CV 53 %
RWST 2ndry Cont. High Level Switch	V	(LSH-101) Last Test(monthly): ノーマン・ここ
RWST Back-Up Generator		Last Test Run(monthly): 1-20-22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 780 Gallons Reserve = 3 Totes
Caustic Bay Heater	~	
Peroxide Tote Level	~	~ 200 Gallons Reserve = ~ 555=
HCL Tote Levels		~ 290 Gallons Reserve = ~30jal
Chemical Totes and Piping Inspected	_	Leaks observed: Y / 🕦
Emergency Shower Inspected	-	Checked and Flushed - All OK: / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI: 38-90 CV: 3 %
Primary Acid Retention Tank (T-510)	~	
All Acid Feed Lines	~	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	1	Last Cleaning (Qtrly): /0-20-2/
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10,8	
pH 310	Value: 6.32	
pH 315	Value: 60.87	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	V	Good
Clarifier Water Quality	/	Good Oil or sheen observed: Y / 🕦
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	~	
HMR PLC Panel	~	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	-	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 500	
Clear-well Transfer Pumps (P-371) 372)	/	*
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 60+hok
Manual Sludge Lateral pumping	-	Last done (As Needed): 4/2-3-20-21/#3-7-20-21
Manual Sludge Lateral Ball Valves		Exercise Weekly: Allow
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	1-77-22 - today	1236
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1305
pH-740 Discharge Surge Tank	<u> </u>	Discharge suspended: /3∘7 ← ►/324
Out of Hold Double Check		None in hold: w war
Valves Back to Normal Position		All OK: V'd am

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 2 %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)		Level:~ 40 %
Sludge Holding Tank (T-352)	~	Level: 55 %
Decant Transfer Pump (P-352)	_	CV 60 % @ 0.5 gpm
Filter Press Pumps (P-381 / P-382)	~	P381 Rebuilt . Needs +cst. P-38204
Filter Press		Stage: leady to All / Empty

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 387psi	CV@ 72 % @ [.#3 gpm
Retention Tank (T-114)	✓ Operating Press: 38 psi	pH-113 @ 3.67
Bag Filter (BF-113)	Operating Press: 41 psi	
Ion Exchange (Cage 1) or 2) + Guard	✓ Operating Press: 326psi	TP-174A -> TP-176-A/S CANTHUN + GAND
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: /t psi	CV@ 55 % @ 32.5 gpm
T-520 to GAC Total (FT-675)	255790625 gal	Time: 0956
North End On-Site Pumping	Operating Press: 2-3 psi	12.3 gpm @ 0943
North End Off-Site Pumping	Operating Press: 2-9 psi	8.9 gpm @ 6943
Peroxide Feed Pump (P-680)	~	SPD 2.5 % / RATE 0.7
Peroxide Conc. At (TP-710)	I.O PPM	
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE

	Item	Status	Comments
O	180 Day storage area check	_	Check sheet completed: yes/www-1-27-22
	Satellite Haz. Waste Areas (BLDG #1)	~	Condition: IX REST + MAIN GOOD
9	Satellite Haz. Waste Area (BLDG #2)	V	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-(6-21	Next: 9-2022
Quarterly Test Run	Date: NA/Aunnyma	Next: N4/Running
Peroxide Feed Pump (P-650)	V	Flow Rate: ~), ¿ cc/min.
UV-Ox Power		25.7 KVA 2556 Volts 10.2 Amps
Lamp Hours	2/57 Hrs	
Crystal Condition & Wiper Status	-	Oiler status: Ok
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	100 psi In 100 psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 70 % @ 7.4 gpm
UV-OX Temperature	In(TT-670): /2.9 °C	Out(TT-710): 2574 °C
PDU GAC (PDT-710)	~	Δ Pressure: / psi
Peroxide Concentration Pre UV	<i>¿∞</i> PPM	
Peroxide Concentration Post UV(TP-720)	zs PPM	
Peroxide Conc. Post PDU (TP-730)	DO PPM	
Secondary Acid Feed Pump (P-630)	~	CV@ 3 %
Secondary Acid Retention Tank (T-645)		
Pre - UV Oxidizer Total (FT-670)	21075420 gal	Time: 9957
Post UV-Ox / Pre PDU	~	Pressure: /2 psi
Post PDU		Pressure: 7.75 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, January 27, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments		
PDT-720		Δ Pressure: 4 psi		
PDT-730	V	Δ Pressure: 3 psi		

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751) or P752)	~	CV@ 54.6 %
Effluent Surge Tank (T-740)	~	Level: 40 %
Effluent Discharge Rate (FT-770)		32.7gpm @ 0953
POTW Line Pressure (PT-770)		32,2 psi
Effluent Totalizer Reading (FT-770)	249938 798 gal	Time: 0957
POTW MH17S-078 Discharge Check (Monthly)	~	Last Done: (-17-22
4X8-Inch POTW Leak Detection Checks (Monthly)	~	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	~	Last Done: 11-8-21 WexT- 2-2027
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	~	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 1-27-22-7-	Plant Effluent Suspended: /307 ← 1324
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or 🐿
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0958-1004

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19791723	(FT-505) LFG Cond. to T-530	220523
(FT-025) NBBW Influent	94876184	(FT-056) Off - Site N. End Influent	44281456
(FT-012) MW-38 Inf. to HMR-30	~ 3548850010Z	(FT-113) Ion Exchange Influent	1089476
(FT-042 HMR30) MW-38 Source to HMR-30	n 2092061 35484	(FT-810) Plant Potable Water In	30076804
(FT-043) MW-38 to RWST	- 72236309 2061	(FT-026) NBBW Bypass to RWST	4440239
(FT-042 RWST) MW-38 Source to RWST	~ 865 5376	(FT-014) Misc. Water to RWST	3226120
(FT-012T) MW-38 to T-540/541	-+ + + + + + + + + + + + + + + + + + +	(FT-035) NTES Inf. to BIO	6726451
(FT-040T) MW-38N to T-540/541	269744t	(FT-035T) NTES to T-530	467072
(FT-041T) MW-38S to T-540/541	~4050820	(FT-017) BIO Inf. from T-530	661280
(FT-042T) MW-38 Source to T-540/541	4050820	(FT-018) T-540/541 Influent	8699932
(FT-055) On - Site N. End Influent	99815820	(FT-352) T-352 to HMR-30	133 2497

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, January 27, 2022

tem	Status	Comments
Compressor Intake Temp.	57 °F (Analog Gauge)	Outside Temp.: ~ 23 °F
Compressor Building Vent	V	closed - operational
Primary Air Compressor	2,000 Hour service date: 7-8-21	Coolant present in sight glass: N
(IRN30H)	Serviced @ 60952 Hours	Next service @ 62952 Hours Current Hours @ 62836
RN30H Motor Speed	0 %	Current rious & P = 515
RN30H Pressure	//7 psi	
RN30H Moisture purge valve chk(Weekly):		
RN30H Intake Filter		Date Last Changed: /-27-22- youlay
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / (1)
Backup Air Compressors	mandany / totalata(woods)	87-ac
(T-30 East and West)		Both cool to touch: Ø / N
Air Dryer	V Eloan	Moisture at Receiver Tank: Y / 🐿
Oil Moisture Prevention (Monthly)	Last Done: 127:22 - 10-day	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		10 psi
	Status	Comments
Item Bag Filter Sump	Status	Comments
Item Bag Filter Sump Wet Well Sump	V	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGR	APH	
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item	V	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational	APH	Comments GC # checking UV-Ox Effluent: (
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	APH	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	APH	Comments GC # checking UV-Ox Effluent: (
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	APH	Comments GC # checking UV-Ox Effluent: (
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	APH Status	Comments GC # checking UV-Ox Effluent: (

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

y 27, 2022
rick
W

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	/	1.85	29 %	6.5	
P-3301A	SB	-	- %	_	
NTES Pump P-002(Sump) / (P-002W(10R))		0.50	48 %	P035 P038	Globules Observed at TP-130: Y / N Time: 09 25
T-530 P-005	~	0.21	41 %	7.0	
T-540/541 P-006	~	6,30	74 %	7.5	
LFG COND Auto-Traps	/	0.0	NA	5.0	Between Cycles: Ø / N
Reactor Feed Pumps					
P-3321	~	z. 5 0	55.2%	6.5	
P-3322	~	3.14	55.4 %	6.5	
P-3323	5 &	_	- %	_	
P-3324	~	247	46.1 %	7.0	
Reactor Effluent Pumps			A STATE OF THE STA		
P-3341	/	4,13	48.0%	10.0	
P-3341A	28	_	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 12-70-71
B-3331	/	4,22	120	3-2022	Greased, Belt and Filter Checked: 🎔 / N
B-3332	SB	_	-	1	Belt and Filter Checked: Y / (V)
B-3333	/	4.45	118		Greased, Belt and Filter Checked: Ø / N
B-3334	V	4.27	110	V	Greased, Belt and Filter Checked: 🏈 / N

C. REACTOR VENTILATION

Item	Status	Comments		
Vapor Carbon Contactor	/	On-line: 2/10/18		
Reactor Vent Blower	~			
Reactor Vent Booster	/			
VTP-3350	-	PID Reading: しゅる PPM		
VTP-3360	~	PID Reading: 7, G PPM		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_ Level: 69 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 33 %	
T-530 Mixer	-	
LFG Condensate Conveyance Line	~	Last Pressure Test: 2-/9-2/ Next: >-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvis: 46 % & 47%	
T-540/541 Mixers	V	
Chiller	ofthe	Chiller Coolant Lvl: ~ — " Below full mark
Chiller Cooling Fins (as needed)	occur	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	V	Last Back Flushing (Quarterly): /2-22-2/
T-3310 Sedimentation Tank	Visual Level: ak	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD V Needs Attn
T-3332 Reactor No. 2	V	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	V	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	V	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	V	
T-3340 Overflow Tank	√ Level: 3 %	
Recycle Valve to Blend Tank	V	3.97 gpm@ (03C
Building Containment Sump	~	Last Alarm Test Date (Monthly): /-20-22

E. CHEMICAL FEED SYSTEM

Item	Status Comments		
Phosphorous Supply	V	Bags: /3.25 Gallons: ~ 75	
Phosphorous Pump (P-2221)			
Caustic Supply	/	~ 165 Gallons	
Caustic Pump (P-2211)	SB Currently in acid addition mode		
Acid Supply	~	~ 40 Gallons	
Acid Pump (P-2211)			
Caustic Pump (P-2231)	Leaks: Y / Ø	Last tubing tip cleaning (monthly): 1-20-22	
Caustic Pump (P-2232)	Leaks: Y / 🛱	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / (N	Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	1-27-22- takey	New 4+10 PHSTOT USEN
pH-3331 Reactor 1		
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	_	
Automatic Backwash	Cycle Count: 17	Reset
BF-3340 a/b Differential Pressure	PSI: 3	9/7 = 3,19Am
75-micron Bags Last Cleaning	Date: /1-14-19	
75-micron Bags Last Inspection	Date: f	
75-micron Bags Last Changed	Date: 🗸	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: O	7/7 a 3.13Pm
Last Backwash Performed	Date: 1-26-22	UV-OXOFFLANE BUTTY SACRAMES &

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Block Heater: On OK / Off Warm Ou	
"BIO" Backup Generator			
Electrical Surge Suppressor	/		
Motor Control Center			
PLC		UPS @ 97 min / 95 Events	
HMI's			
BTS Process KWH Meter	1841753 KWH	Time: //26	
Building#2 KWH Meter	5322620 KWH	Time: //26	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: €2
Alarms Enabled	1	CE-colt Brutish + maint 1-26-22
GC Influent Filters	~	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, January 27, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6292963	
FT-3324 Feed Spare	150561	
FT-3322 Feed to Reactor 2	11156145	
FT-3323 Feed to Reactor 3	948842	
FT-3301 T-510 to BIO	51775209	
FT-3341 BIO Effluent	66692408	
FT-3342 BIO Recycle	56083371	V 12-10-10-10-1

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	-	Inspection date: /-2/-22
Building #2 Eye Wash/Shower	~	Checked and Flushed- All OK: 🕚 / N

OTHER COMMENTS:	
- 18	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, February 03, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12.55 06	_	les: 238
LFG Cond Automatic Trap CT-2	Sump Level: 9.720k		les: / 2
LFG Cond Automatic Trap CT-3	Sump Level: 7,24 a		les: 948
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 8≤ %		cles: 7 Sump: 8,92
PM-15 Containment / Vessel	/ Level: 65 %		7 0,100
MW-51 Containment / Vessel	✓ Level: 40 %		
PM-11 Containment / Vessel	✓ Level: 60 %		
MW-38 Systems			
North Toe System	-		
North End Systems (Weekly)			
Full N. End Systems Check (Monthly)	Last Done: 1-2 1-22		
North End Pipeline(s)Flushing (As Needed)	Perform if suspended solids present Last Done: 11/15/15		one: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last D	
NTES Piping Containment	-	Monthly Sump Level: Ary 26.0	
North Boundary System P-001:	CV73.(% @ 6.2 gpm	40.30 Hz / 206 Amps. / vault p	Si @ 19/100 hours
T-101 & T-102 Containment / Tank		Levels: 34 % & 33 %	o. @ IDI IOD! -LC
Raw Water Storage Tanks Piping		20,000, 20, 70	
RWST Building Temp. (TT-101)	49.9 °F	Outside Temp.: ~ 3 °F	
(P-12) or P-122	0.6 gpm/CV 57 %		*
RWST 2ndry Cont. High Level Switch	(LSH-101) Last Test(monthly): /-20-72		-20-77
RWST Back-Up Generator	V	Last Test Run(monthly): 1-20-	.77

B. CHEMICAL STORAGE BAYS

Item	Status		Comments	
Caustic Tote Levels			~ 470 Gallons Reserve = 2 totes	
Caustic Bay Heater	1/	7	170 Callotte - 2 Joje 5	
Peroxide Tote Level	7		~ 175 Gallons Reserve = ~55 adlionS	
HCL Tote Levels	V	,	~ 175 Gallons Reserve = ~ 55 gallons Reserve = ~ 30 gallons	
Chemical Totes and Piping Inspected	1	/	Leaks observed: Y / (N)	
Emergency Shower Inspected	/		Checked and Flushed - All OK: (Y) / N	

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	V.	
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 58-60 CV: 5 %
Primary Acid Retention Tank (T-510)	1/	70
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, February 03, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NĄ	
T-300B (Caustic Mixer)	√ .	Last Cleaning (Qtrly): 10-20-21
T-300A/B Water Level		
T-300B (Caustic Mix Chamber)		Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 7,19	
pH 315	Value: 11.04	
Flocculation Chamber Paddle Wheel		
Precipitate Floc Quality	V.	Good
Clarifier Water Quality		Good Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	√	
Clear-well Chamber and Water Level	J,	
HMR PLC Panel	7	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	/ .	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	V	
Polymer Tank Level	Gallons: ~ 405	
Clear-well Transfer Pumps (P-37) / 372)	√ , —	
Sludge Transfer Pump (P-330)	V.	Exercise Valves Weekly: bolk ok
Manual Sludge Lateral pumping	V.	Last done (As Needed):#1 -2 3-2021 #3 7-20-
Manual Sludge Lateral Ball Valves	V/	Exercise Weekly: All ok
Automatic Blow-down Operations		711

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	2/4/22 Friday	160905
pH-315 HMR-30 (T-300B)		0920
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		→ i020
pH-740 Discharge Surge Tank	V	Discharge suspended: 0905 ←→ 0918
Out of Hold Double Check		None in hold: / / 2422 TG
Valves Back to Normal Position		All OK: JJ 214122- 1/4

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	/	Comments	
Verify Sludge Thickener Running			Gauge Reading:	0 %
Sludge Thick. Transfer Pump (P-350)	/			
Sludge Holding Tank (T-351)	/	/	Level:~ 38 %	
Sludge Holding Tank (T-352)	1		Level: 32 %	
Decant Transfer Pump (P-352)	/		CV 71 % @0.3	mag
Filter Press Pumps (P-381) / P-382)	Rebuilt - Stone 4	Ruming Well		0
Filter Press	/			operational

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, February 03, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press:38.5 psi	CV@ 7 % @ 1.8 gpm
Retention Tank (T-114)	√ Operating Press: 38 psi	
Bag Filter (BF-113)	Operating Press: 41 psi	
lon Exchange (Cage 1) or 2) + Guard	√ Operating Press: 37 psi	TP-174A -> TP176A / 5 conistors + Guard
Post Ion Exchange	V Operating Press:3,5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: psi	CV@ 55 % @ 32.\ gpm
T-520 to GAC Total (FT-675)	256119034 gal	Time: \\5\
North End On-Site Pumping	Operating Press: 2-3 psi	12.3 gpm @ 0938
North End Off-Site Pumping	Operating Press: 2-8 psi	8.3 gpm @ 0938
Peroxide Feed Pump (P-680)	/	SPD 2.4 % / RATE O.6 gom
Peroxide Conc. At (TP-710)	Ay 1.0 ≥.0 PPM	- Jt
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments MTG 2-3-22
60180 Day storage area check	7	Check sheet completed:
Satellite Haz. Waste Areas (BLDG #1)	V.	Condition: IX Resin + Main Good
Satellite Haz. Waste Area (BLDG #2)		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status ,	Comments
UV-Oxidation System		Operational
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NK - Running	Next: NA - Running
Peroxide Feed Pump (P-650)	7, 3	Flow Rate: ~ 7.3 cc/min.
UV-Ox Power	_	25.8 kVA 2430 Volts 10.6 Amps
Lamp Hours	2325 Hrs	
Crystal Condition & Wiper Status	~	Oiler status: OK
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	12 psi In (1.5 psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 3772% @ 7.4 gpm
UV-OX Temperature	In(TT-670): 14.7 °C	Out(TT-710): 25.6 °C
PDU GAC (PDT-710)		Δ Pressure: 3 psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	O,O PPM	
Secondary Acid Feed Pump (P-630)	V ,	CV @ 1 %
Secondary Acid Retention Tank (T-645)	/	
Pre – UV Oxidizer Total (FT-670)	21148006 gal	Time: 0951
Post UV-Ox / Pre PDU	1	Pressure: 14 psi
Post PDU		Pressure: 9 psi

Table 3.19.1 Rev 7 WTP.docx

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, February 03, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	1	Δ Pressure: 3 psi
PDT-730		Δ Pressure: 2 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P75) or P752)	1	CV@ 52.4 %
Effluent Surge Tank (T-740)	/	Level: 38 %
Effluent Discharge Rate (FT-770)	27.1	₹ 31.4 gpm @ 0959
POTW Line Pressure (PT-770)		31,5 psi
Effluent Totalizer Reading (FT-770)	250264788 gal	Time: 1000
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 1-17-22
4X8-Inch POTW Leak Detection Checks (Monthly)	7	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	√,	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	J.	Last Done: 11-8-21 Next 2-22
2-Inch POTW Backup Pressure Testing (Annual)	1,	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	1/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	√	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed:	Plant Effluent Suspended: 1307 → 1324
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.00 volts(monthly)	Adjustment Needed: Y or (N)
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1002 - 1012

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19800075	(FT-505) LFG Cond. to T-530	220577
(FT-025) NBBW Influent	94938033	(FT-056) Off - Site N. End Influent	44365960
(FT-012) MW-38 Inf. to HMR-30	8519486	(FT-113) Ion Exchange Influent	1107933
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30077
(FT-043) MW-38 to RWST	3092450	(FT-026) NBBW Bypass to RWST	4441603
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8232139
(FT-012T) MW-38 to T-540/541	8655376	(FT-035) NTES Inf. to BIO	6731395
(FT-040T) MW-38N to T-540/541	1979086	(FT-035T) NTES to T-530	467258
(FT-041T) MW-38S to T-540/541	2697441	(FT-017) BIO Inf. from T-530	661803
(FT-042T) MW-38 Source to T-540/541	4050820	(FT-018) T-540/541 Influent	8702410
(FT-055) On - Site N. End Influent	9939899	(FT-352) T-352 to HMR-30	1335900

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, February 03, 2022

Inspection Date:

tem	Status	Comments
Compressor Intake Temp.	54 °F (Analog Gauge)	Outside Temp.: ~ O °F
Compressor Building Vent	7 7	closed-operational
Primary Air Compressor (IRN30H)	2,000 Hour service date: 7-8-21 Serviced @ 60952 Hours	Coolant present in sight glass: (V) / I Next service @ 62952 Hours Current Hours @ 62923
RN30H Motor Speed	31 %	
RN30H Pressure	J22 pşi	
IRN30H Moisture purge valve chk(Weekly):		
RN30H Intake Filter		Date Last Changed: 1-27-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / (N)
Backup Air Compressors	Walitally Notivate(weekly)	Excessive Moisture: 1 7 (1)
(T-30 East and West)	✓	Both cool to touch: Ø / N
Air Dryer	√ Eco on	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 1-27-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		110 psi
Bag Filter Sump Wet Well Sump	7	
R. GAS CHROMATOGRA	\PH	
ltem	Status	Comments
GC Operational	Heater on	GC # checking UV-Ox Effluent: /
Alarms Enabled	1	GC calibration + Maint 1-25-2
GC Influent Filters		2-2-22
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers	1	Date inspected: 1-21-22
Building #1 Eye Wash/Shower	— —	Checked and Flushed- All OK: Ø /
ther Comments:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, February 03, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	√	2.11	33.8 %	7.5	
P-3301A	SB		%		
NTES Pump P-002(Sump) / P-002W(10R)	1	0.52	48 %	P035 P038 33-36 7	Globules Observed at TP-130: Y / (N) Time: 1055
T-530 P-005	1	0.20	4\ %	7	
T-540/541 P-006	5 g	0.00	40-%	\$,5	New Inseller proposited tendancy
LFG COND Auto-Traps	1	0.0	NA	6.5500	Between Cycles: (Y) / N
Reactor Feed Pumps					
P-3321	1	1.84	43 %	6.5	
P-3322	\checkmark	2.65	41 %	5	
P-3323	1	1.88	60.9 %	4.5	
P-3324	SB		%		
Reactor Effluent Pumps					
P-3341	1	3.88	54.8 %	q	
P-3341A	SB		%		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-30-21
B-3331		4.18	110	3-2022	Greased, Belt and Filter Checked: / N
B-3332	SB			1	Belt and Filter Checked: Y / N
B-3333		4,27	109		Greased, Belt and Filter Checked: (Y) / N
B-3334		4.18	100	V	Greased, Belt and Filter Checked: (Y) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	√,	On-line: 2/10/18
Reactor Vent Blower	//	
Reactor Vent Booster		10.000
VTP-3350	√ /	PID Reading: 122.7 PPM Ampon Am
VTP-3360		PID Reading: 5.7 PPM ne Piece.

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection	Date:
------------	-------

Thursday, February 03, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	√ Level: 55 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 27 %	
T-530 Mixer		
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 26 % & 27 %	
T-540/541 Mixers	1	Operational
Chiller	offline	Chiller Coolant Lvl: ~ " Below full mark
Chiller Cooling Fins (as needed)	offline	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	7,	Heat Trace: On OR / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): +2.33
T-3310 Sedimentation Tank	Visual Level:	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	√ Level: 74 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: 600D/ Needs Attn
T-3332 Reactor No. 2	1/	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	1	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	1	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	1	
T-3340 Overflow Tank	√ Level: 32 %	
Recycle Valve to Blend Tank	1	6.45 gpm@ \037
Building Containment Sump		Last Alarm Test Date (Monthly): 1-20-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply		Bags: \3.25 Gallons: ~ 70
Phosphorous Pump (P-2221)	/	
Caustic Supply	/	~ \65 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	/	~ 40 Gallons
Acid Pump (P-2211)	1,	1_
Caustic Pump (P-2231)	Leaks: Y	/ W Last tubing tip cleaning (monthly): 1-20-22
Caustic Pump (P-2232)	Leaks: Y	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	✓ Leaks: Y	/N Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, February 03, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	1-27-22	New SADS 1-27-22 Strang of
pH-3331 Reactor 1		315
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	1/

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 14	Reset
BF-3340 a/b Differential Pressure	PSI: 3	10/7 @ 1.8 gpm
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date: 1	
75-micron Bags Last Changed	Date:	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI:	7/7 @ 1-8 apm
Last Backwash Performed	Date: 2-4-12-1-20-22	7. 0 130 17.

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments
"BIO" Backup Generator			Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	1/	71078	
Motor Control Center	√ ,		
PLC	1		UPS @ 97 min / 95 Events
HMI's			
BTS Process KWH Meter	1844364	KWH	Time: 1300
Building#2 KWH Meter	5330560	KWH	Time: \300

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational		GC # checking BIO: 7
Alarms Enabled	1/	Gc calibration + Mount 1-26-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 03, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6314254	
FT-3324 Feed Spare	163172	
FT-3322 Feed to Reactor 2	11185714	
FT-3323 Feed to Reactor 3	957315	
FT-3301 T-510 to BIO	51793231	
FT-3341 BIO Effluent	66717997	
FT-3342 BIO Recycle	46 5612588 56125850	

K. SAFETY

Item	Status	Comments 1-21-77
Building #2 Fire Extinguishers	7,	Inspection date: 2-4-22-1
Building #2 Eye Wash/Shower	/	Checked and Flushed- All OK: (Y) / N

L. OTHER COMI	IENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 1255 ~	Counter: 196050 Cycles: 362
LFG Cond Automatic Trap CT-2	Sump Level: 8.63	Counter: 275 430 Cycles: 52
LFG Cond Automatic Trap CT-3		Counter: 322258 Cycles: 1654
CT-4 Containment/Vessel (LFG Cond)	/ Level: 95 %	Tank Level: / 41 Counter: 191270 Cycles: Sump: 7.11
PM-15 Containment / Vessel	✓ Level: 68 %	
MW-51 Containment / Vessel	✓ Level: 45 %	
PM-11 Containment / Vessel	/ Level: 70 %	
MW-38 Systems	~	
North Toe System	_	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)	_	Last Done: 1-21-22
North End Pipeline(s)Flushing (As Needed)	_	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	_	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: Ary =16.07' Date: 1-20-22
North Boundary System P-001:	CV73.3 % @ 6, 2 gpm	40.49 Hz /2.06 Amps. / vault psi @ 18/00 Longs
T-101 & T-102 Containment / Tank	_	Levels: 47 % & 47 %
Raw Water Storage Tanks Piping	-	
RWST Building Temp. (TT-101)	56.3 °F	Outside Temp.: ~ 40 °F
(P-121)or P-122		Z Ø gpm/CV 49 %
RWST 2ndry Cont. High Level Switch	V	(LSH-101) Last Test(monthly): 1-70-22
RWST Back-Up Generator	/	Last Test Run(monthly): /-20-22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	V	~ 300 Gallons Reserve = 2 4045
Caustic Bay Heater	/	
Peroxide Tote Level		~ 155 Gallons Reserve = ~55 grad
HCL Tote Levels	V	~ 270 Gallons Reserve = ~ 30 yel
Chemical Totes and Piping Inspected	~	Leaks observed: Y / W
Emergency Shower Inspected		Checked and Flushed - All OK:

C. PRIMARY AND SECONDARY ACID FEED SYSTEM & FURE VENT MOTOR 648, WESTING ON ARCES FOR FORTH FORTH

Item	Status	Comments
Primary Acid Feed Pump (P-631)	~	
Ion Exchange Acid Feed Pump (P-632)	·/	PI-0632 PSI: 56-58 CV: 5 %
Primary Acid Retention Tank (T-510)	V	
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	-	Last Cleaning (Qtrly): [0-20-2]
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	V	Last Cleaning (Qtrly): 10-20-2(
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.83	
pH 315	Value: เอเอา	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	Good
Clarifier Water Quality	V	Cross Oil or sheen observed: Y /
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	1	
HMR PLC Panel		
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	V	
Polymer Pump (P-310)	1	
Polymer Tank Mixer	~	
Polymer Tank Level	Gallons: ~ 52₽	
Clear-well Transfer Pumps (P-371) 372)	~	
Sludge Transfer Pump (P-330)	/	Exercise Valves Weekly: Somok
Manual Sludge Lateral pumping	/	Last done (As Needed): 4/42 -3-20-21/3-7-2-
Manual Sludge Lateral Ball Valves		Exercise Weekly: Allok
Automatic Blow-down Operations		

F pH PROBES

r. pri rivodeo		
pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	2-10-22 - Today	1249
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		→ i330
pH-740 Discharge Surge Tank	V	Discharge suspended: 1240 ← 1249
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: Va

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	/	Gauge Reading: O %
Sludge Thick. Transfer Pump (P-350)	~	
Sludge Holding Tank (T-351)	/	Level:~ 50 %
Sludge Holding Tank (T-352)	/	Level: 65 %
Decant Transfer Pump (P-352)	/	CV 53 % @ 0.5 gpm
Filter Press Pumps (P-381 / P-382)	7	
Filter Press		Stage: ~11

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 37,2 psi	CV@ 69 % @ 1,80 gpm
Retention Tank (T-114)	✓ Operating Press: 37 psi	pH-113 @ 3,87
Bag Filter (BF-113)	✓ Operating Press: 40 psi	
Ion Exchange (Cage(1) or 2) + Guard	✓ Operating Press: 36 psi	TP-174A->TP-17CA/5 cantitions + GAUND
Post Ion Exchange	Operating Press: 3,5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 43 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522)	Operating Press: 16 psi	CV@ 61 % @ 31.0 gpm
T-520 to GAC Total (FT-675)	756419435 gal	Time: 1002
North End On-Site Pumping	Operating Press: 2-3 psi	12.3 gpm @ 0950
North End Off-Site Pumping	Operating Press: 2-6 psi	8.7 gpm @ 0150
Peroxide Feed Pump (P-680)	~	SPD 2.7 % / RATE 0.7
Peroxide Conc. At (TP-710)	1.0 PPM	
Peroxide Conc. At (TP-740)	OO PPM	

J. HAZARDOUS WASTE STORAGE

ı	Item	Status	Comments
6	1-186 Day storage area check	V	Check sheet completed: yes men 2-10-22 min
ı	Satellite Haz. Waste Areas (BLDG #1)		Condition: Ix Augin + murn Gost
ı	Satellite Haz. Waste Area (BLDG #2)	/	Condition: Guest

K. UV-OXIDATION SYSTEM * New Selonish valueon FV-708 - Z-9-Z2 *

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-7022
Quarterly Test Run	Date: NA/Running	Next: will kinder
Peroxide Feed Pump (P-650)	/	Flow Rate: ~ 7, 2 cc/min.
UV-Ox Power		25.7 kVA 2549 Volts 10.1 Amps
Lamp Hours	2418 Hrs	
Crystal Condition & Wiper Status		Oiler status: O /C
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	// psi In / Z.O psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 74 % @ 7,5 gpm
UV-OX Temperature	In(TT-670): /Z.7 °C	Out(TT-710): 2.573 °C
PDU GAC (PDT-710)		Δ Pressure: 3 psi
Peroxide Concentration Pre UV	(O○ PPM	
Peroxide Concentration Post UV(TP-720)	z5 PPM	
Peroxide Conc. Post PDU (TP-730)	o.o PPM	
Secondary Acid Feed Pump (P-630)		CV@ 3 %
Secondary Acid Retention Tank (T-645)	~	
Pre – UV Oxidizer Total (FT-670)	2/187928 gal	Time: 1002
Post UV-Ox / Pre PDU	/	Pressure: 14 psi
Post PDU	~	Pressure: 7.75 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, February 10, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720		Δ Pressure: > psi
PDT-730		Δ Pressure: '3' psi

M. EFFLUENT DISCHARGE * New Check SAHS DISTRIBLY 2-9-22 ON STELLING AMOS &

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 55.2 %
Effluent Surge Tank (T-740)	/	Level: 40 %
Effluent Discharge Rate (FT-770)		36.0gpm @ 1000
POTW Line Pressure (PT-770)		32.7 psi
Effluent Totalizer Reading (FT-770)	250569416 gal	Time: 1003
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: 1-17-22
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done: 11-8-21 MAY 2 - 2082
2-Inch POTW Backup Pressure Testing (Annual)	/	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	~	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	-	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed:	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	1-27-22	1307 + 1324
LEL Sensor Bridge Adjustment to 2.0 volts	(wonthly) احص: Reading: 2	Adjustment Needed: Y or (1)
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1004 →1008

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19879038	(FT-505) LFG Cond. to T-530	220738
(FT-025) NBBW Influent	94971887	(FT-056) Off - Site N. End Influent	44449268
(FT-012) MW-38 Inf. to HMR-30	8529781	(FT-113) Ion Exchange Influent	1126194
(FT-042 HMR30) MW-38 Source to HMR-30	35 484	(FT-810) Plant Potable Water In	30078564
(FT-043) MW-38 to RWST	3096783	(FT-026) NBBW Bypass to RWST	4470758
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8232630
(FT-012T) MW-38 to T-540/541	8664186	(FT-035) NTES Inf. to BIO	6736378
(FT-040T) MW-38N to T-540/541	1979523	(FT-035T) NTES to T-530	467495
(FT-041T) MW-38S to T-540/541	2697994	(FT-017) BIO Inf. from T-530	662327
(FT-042T) MW-38 Source to T-540/541	4058622	(FT-018) T-540/541 Influent	8703275
(FT-055) On - Site N. End Influent	100063229	(FT-352) T-352 to HMR-30	1338405

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, February 10, 2022

Inspection Date:

ction Performed by:	ike Gelwick
SORS	
Status	Comments
6 └ (°F (Analog Gauge)	Outside Temp.: ~ 42 °F
	Open - operationed
2,000 Hour service date: 2-7-22 Serviced @ 62950 Hours	Coolant present in sight glass: ダ / N Next service @ 64950 Hours Current Hours @ 63006
0 %	
1/7 psi	
Weekly):	
	Date Last Changed: 2-7-22
Valves Manually Activate(weekly) -	Excessive Moisture: Y / D
	Both cool to touch: Ø / N
~ Ecost	Moisture at Receiver Tank: Y / 🐿
thly) Last Done: 1-27-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
	110 psi
Status	Comments
	Comments
_	
	Comments
	GC # checking UV-Ox Effluent: #/
	CC-cultifulton town ut 2-9-22
04-1	
	Comments
ers	Date inspected: /-Z/-ZZ
wer	Checked and Flushed- All OK: (Y) /
- GAd. STARTED LEPEN, wasting on AAA	
	SORS Status 6 4 °F (Analog Gauge) 2,000 Hour service date: 2 °7-22 Serviced @ 62950 Hours 0 % (17 psi Neekly): Valves Manually Activate(weekly) Last Done: 1-27-22 Status OGRAPH Status Status Status Status Status ers wer

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301		2.05	25,0%	5,5	
P-3301A	SB	_	- %	-	
NTES Pump 5 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		0.50	48 %	P035 P038	Globules Observed at TP-130: Y / © Time: 0920
T-530 P-005	./	0.19	41 %	7.0	
T-540/541 P-006		0.21	41 %	7.0	New Inpellor 2-3-22
LFG COND Auto-Traps	COLON	0.0	NA	500	Between Cycles: ② / N
Reactor Feed Pumps					
P-3321	~	2,51	59.3%	8.5	
P-3322		3,52	53.6 %	6.5	
P-3323	56	-	- %	-	
P-3324	~	2,49	39,4 %	6.0	
Reactor Effluent Pumps					
P-3341	~	2.20	46.2%	8.5	
P-3341A	3B	-	- %	_	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: / Z-30-Z1
B-3331		4.17	124	3-2022	Greased, Belt and Filter Checked: () / N
B-3332	SB	-	3 3		Belt and Filter Checked: Y / 🕪
B-3333	V	4,29	126		Greased, Belt and Filter Checked: 🕚 / N
B-3334	-	4,11	119	V	Greased, Belt and Filter Checked: (Y) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	~	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	· /	
VTP-3350	V	PID Reading: 12.8 PPM Land on Asi
VTP-3360	/	PID Reading: 4.6 PPM AFFE HATELE

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_ Level: 71 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	► Level: 24 %	
T-530 Mixer	V	
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-12-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	LvIs: 85% & 86%	
T-540/541 Mixers	/	
Chiller	OPFLMC	Chiller Coolant Lvl: ~ ~ " Below full mark
Chiller Cooling Fins (as needed)	othere	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments		Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	r	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: 0k	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	~	Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	V	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	1	Digital Displays: GOOD// Needs Attn
T-3334 Settling Tank		Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	V	
T-3340 Overflow Tank	✓ Level: 2.9 %	
Recycle Valve to Blend Tank	~	4.02 gpm@ 1040
Building Containment Sump	~	Last Alarm Test Date (Monthly): /-20-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	V	Bags: 12,80 Gallons: ~ 75
Phosphorous Pump (P-2221)	/	
Caustic Supply	/	~ (55 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	1	~ 40 Gallons
Acid Pump (P-2211)		
Caustic Pump (P-2231)	Leaks: Y /(N	Last tubing tip cleaning (monthly): 1-20-27
Caustic Pump (P-2232)	✓ Leaks: Y /Û	D Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	1-27-22	Strang over Clean today
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	1	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	~	
Automatic Backwash	Cycle Count: 93	Reset (Kunning of Higher Flow's Dest Free 245)
BF-3340 a/b Differential Pressure	PSI: 4	21/17 24,740
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date: V	
GACF-3340 Status	·	
GACF-3340 Differential Pressure	PSI: 9,5	17/7,5 24,7400
Last Backwash Performed	Date: j-26-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator		Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	~	
Motor Control Center	-	
PLC	/	UPS@ 97 min / 95 Events
HMI's		
BTS Process KWH Meter	1947538 KWH	Time: //26
Building#2 KWH Meter	5338/22 KWH	Time: //26

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #Z
Alarms Enabled	V	CC-culibration + main + 2-9-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 10, 2022	
Inspection Performed by:	Mike Gelwick	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6340094	
FT-3324 Feed Spare	181812	
FT-3322 Feed to Reactor 2	11221631	
FT-3323 Feed to Reactor 3	964303	
FT-3301 T-510 to BIO	51827561	
FT-3341 BIO Effluent	667 58658	
FT-3342 BIO Recycle	56165405	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	~	Inspection date: /-2/-22
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N

L. OTHER COMMENTS:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

12-000000		S
Inc	pection	Date.
1115	Dection	ı Date

Thursday, February 17, 2022

Inspection Performed by: Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: /3,27 @	Counter: /96400 Cycles: 350
LFG Cond Automatic Trap CT-2	Sump Level: 8.68 00	Counter: 275558 Cycles: (28
LFG Cond Automatic Trap CT-3	Sump Level: 7,56 04	Counter: 324489 Cycles: 2230
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 35 %	Tank Level: 3.36 Counter: 196900 Cycles: O Sump: 9.06
PM-15 Containment / Vessel	✓ Level: 72 %	191271
MW-51 Containment / Vessel	✓ Level: 30 %	
PM-11 Containment / Vessel	✓ Level: 30 %	
MW-38 Systems	_	
North Toe System	~	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)	~	Last Done: /-21-22
North End Pipeline(s)Flushing (As Needed)		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	/	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	9/	Monthly Sump Level: Ary @ 16.07 Date: 2-17-22-
North Boundary System P-001:	CV 73.0% @6.1 gpm	40.27 Hz / 2.06 Amps. / vault psi @ 18/20 Lesks
T-101 & T-102 Containment / Tank	<u>_</u>	Levels: 34 % & 34 %
Raw Water Storage Tanks Piping	6	
RWST Building Temp. (TT-101)	54.8 °F	Outside Temp.: ~ / 4 °F
P-1210or P-122	V	1,0 gpm/CV 53 %
RWST 2ndry Cont. High Level Switch	~	(LSH-101) Last Test(monthly): 2-17-2マーアンプロー
RWST Back-Up Generator 6100K Ikum	r Good for.	Last Test Run(monthly): 2-17-22- 70-2017

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 560 Gallons Reserve = 1 tok
Caustic Bay Heater	V	
Peroxide Tote Level	~	~ /30 Gallons Reserve = ~55 gul
HCL Tote Levels	v	~ 2570 Gallons Reserve = ~ 3050
Chemical Totes and Piping Inspected	v	Leaks observed: Y / 🕪
Emergency Shower Inspected	/	Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM \$2-10-72- New Self + Motor on Acid Forme very &

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	1	PI-0632 PSI: 58 CV: 3 %
Primary Acid Retention Tank (T-510)	-	
All Acid Feed Lines	~	Leaks observed: Y / 🚯

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)		Last Cleaning (Qtrly): 10-20-21
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	~	Last Cleaning (Qtrly): (0-20-21
T-300A/B Overflow	~	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6,57	
pH 315	Value: 10.63	
Flocculation Chamber Paddle Wheel	v	
Precipitate Floc Quality		Crosse
Clarifier Water Quality		Good Oil or sheen observed: Y / (1)
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	~	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)	~	
Polymer Tank Mixer	-	
Polymer Tank Level	Gallons: ~ 475	
Clear-well Transfer Pumps(P-371)/ 372)	~	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: Both ox
Manual Sludge Lateral pumping		Last done (As Needed): #/+2-3-20-24/43-7-20-2
Manual Sludge Lateral Ball Valves	_	Exercise Weekly: Allow
Automatic Blow-down Operations	/	

F. pH PROBES

i. piirkobes		
pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	7-17-22-roly	1237
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		≯ i33°
pH-740 Discharge Surge Tank	V	Discharge suspended:/249 ↔/256
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: VVid m

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	_	The second secon
Sludge Holding Tank (T-351)	-	Level:~ 40 %
Sludge Holding Tank (T-352)	~	Level: 47 %
Decant Transfer Pump (P-352)	<u></u>	CV 63 % @ o.5 gpm
Filter Press Pumps (P-381 / P-382)	/	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Filter Press	/	Stage: 4 - curantly known on J-35

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	► Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 39.2 psi	CV@ 71 % @ 1.79 gpm
Retention Tank (T-114)	Operating Press: 38 psi	pH-113 @ 3, 85
Bag Filter (BF-113)	Operating Press: 41 psi	
Ion Exchange (Cage(1)or 2) + Guard	✓ Operating Press: 37 psi	TP-1744-778-1764/5canisters + Colord
Post Ion Exchange	✓ Operating Press: 3.√ psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	✓ Level: 38 %	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522))	Operating Press: / 4 psi	CV@ 58 % @ 31.5 gpm
T-520 to GAC Total (FT-675)	256746046 gal	Time: 0826
North End On-Site Pumping	Operating Press: 2-3 psi	12.2 gpm @ 0817
North End Off-Site Pumping	Operating Press: 2-6 psi	8.4 gpm @ 0817
Peroxide Feed Pump (P-680)	V	SPD 2.4 % / RATE 0.6
Peroxide Conc. At (TP-710)	1.0 PPM	
Peroxide Conc. At (TP-740)	0.0 PPM	

J. HAZARDOUS WASTE STORAGE

	Itema	Status	Comments
£	.180 Day storage area check		Check sheet completed: yes/muc/2-12-22-72-44
	Satellite Haz. Waste Areas (BLDG #1)		Condition: Ix Lesin + num Good
	Satellite Haz. Waste Area (BLDG #2)		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	~	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Lummy	Next: Not (Running
Peroxide Feed Pump (P-650)		Flow Rate: ~ 7.7 cc/min.
UV-Ox Power		25.7 KVA 2671 Volts 10.1 Amps
Lamp Hours	2584 Hrs	
Crystal Condition & Wiper Status	-	Oiler status: 04
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	12.0 psi In (2.0 psi Out
UV-OX Feed Pump (P-600 or (P-601))	V	CV@ 76 % @ 7.4 gpm
UV-OX Temperature	In(TT-670): /3, Z °C	Out(TT-710): Z 6.1 °C
PDU GAC (PDT-710)	~	Δ Pressure: ᠘ psi
Peroxide Concentration Pre UV	100 PPM	•
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	0.0 PPM	
Secondary Acid Feed Pump (P-630)	~	CV @ 2 %
Secondary Acid Retention Tank (T-645)	·	
Pre - UV Oxidizer Total (FT-670)	21260618 gal	Time: 0826
Post UV-Ox / Pre PDU	~	Pressure: 15 psi
Post PDU	/	Pressure: 7.75 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, February 17, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	~	Δ Pressure: 7 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	~	CV@ 53.7 %
Effluent Surge Tank (T-740)	/	Level: 40 %
Effluent Discharge Rate (FT-770)	~	32.2gpm @ 0825
POTW Line Pressure (PT-770)	V	32.3 psi
Effluent Totalizer Reading (FT-770)	250897036 gal	Time: 0827
POTW MH17S-078 Discharge Check (Monthly)	/	Last Done: 246-72
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done:
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: Ø %
LEL Sensor Calibration / Automatic High	Last Completed:	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	1-27-22	1307 + 1324
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.20 volts(monthly)	Adjustment Needed: Y or (V)
Verify Bridge Current between 300v-360v	Reading: 0.331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0827 - 0831

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19843964	(FT-505) LFG Cond. to T-530	221426
(FT-025) NBBW Influent	95032940	(FT-056) Off - Site N. End Influent	44532920
(FT-012) MW-38 Inf. to HMR-30	8547664	(FT-113) Ion Exchange Influent	1144090
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30079222
(FT-043) MW-38 to RWST	3097108	(FT-026) NBBW Bypass to RWST	4471949
(FT-042 RWST) MW-38 Source to RWST	72Z3G	(FT-014) Misc. Water to RWST	8240429
(FT-012T) MW-38 to T-540/541	8664186	(FT-035) NTES Inf. to BIO	6741318
(FT-040T) MW-38N to T-540/541	1979523	(FT-035T) NTES to T-530	467623
(FT-041T) MW-38S to T-540/541	2697994	(FT-017) BIO Inf. from T-530	662830
(FT-042T) MW-38 Source to T-540/541	4058622	(FT-018) T-540/541 Influent	8706165
(FT-055) On - Site N. End Influent	100185502	(FT-352) T-352 to HMR-30	1341841

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, February 17, 2022

Inspection Date:

Compressor Building Vent Primary Air Compressor (IRN30H)	Status 56 °F (Analog Gauge)	Comments
Compressor Intake Temp. Compressor Building Vent Primary Air Compressor (IRN30H)		
Compressor Building Vent Primary Air Compressor (IRN30H)	J & I (Allalog Cauge)	Outside Temp.: ~ /8 °F
Primary Air Compressor (IRN30H)		Closed - Opening
(IRN30H)	2,000 Hour service date: 2-7-22	Coolant present in sight glass: \$\P\$ / N
IDM20U Mater Creed	Serviced @ 62950 Hours	Next service @ 64950 Hours Current Hours @ 63091
IRN30H Motor Speed	6 %	
IRN30H Pressure	<i>((6</i> psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter		Date Last Changed: 2-7-27
Air Tanks Moisture Purge Valves	Manually Activate(weekly) :	Excessive Moisture: Y / 🕸
Backup Air Compressors		
(T-30 East and West)	V	Both cool to touch: V / N
Air Dryer	V Eco on	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 1-27-2 2	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	V	106 psi
Item Bag Filter Sump	Status	Comments
	31 0 mm 61 10 10 mm 6 mm 6 mm 7 mm 6 mm 7 mm 7 mm 7 mm	- Commonto
Wet Well Sump		
R. GAS CHROMATOGRAF	PH Status	Comments
	~	GC # checking UV-Ox Effluent: # (
GC Operational	00.400	
GC Operational Alarms Enabled	V	C1 - Caller than & market >-11-22
Alarms Enabled	~ ~	CC-Carron + mint 2-16-22
Alarms Enabled GC Influent Filters S. SAFETY		
Alarms Enabled GC Influent Filters S. SAFETY Item	Status	Comments
Alarms Enabled GC Influent Filters S. SAFETY	Status	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)		narge sure si)	Comments					
T-510 Pumps											
P-3301	~	1.82	34,4 %	7.0							
P-3301A	53		- %	_							
NTES Pump P-002(Sump) / (P-002W(10R))		0.51	47 %	P035	P038	Globules Observed at TP-130: Y / W Time: 6720					
T-530 P-005	~	0.21	41 %	7.5	5						
T-540/541 P-006	1	0.30	44 %	8.0							
LFG COND Auto-Traps	/	0-0	NA	5.	0	Between Cycles: Ø / N					
Reactor Feed Pumps											
P-3321	-	2.51	57.9 %	9.0							
P-3322	·-	3,40	541 %	6.0							
P-3323	SB	-	- %	-							
P-3324	<i>i</i> -	2.51	38.8 %	50							
Reactor Effluent Pumps											
P-3341	~	2,59	57.3 %	17.0		11.7					
P-3341A	58	-	- %	-							

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-3c-2/
B-3331	~	4.16	112	3-7022	Greased, Belt and Filter Checked: 🍪 / N
B-3332	<i>3</i> 8	-	_	1	Belt and Filter Checked: Y / 🕥
B-3333	/	4.35	114		Greased, Belt and Filter Checked: 🔮 / N
B-3334	/	4.14	100	1	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments On-line: 2/10/18		
Vapor Carbon Contactor	V			
Reactor Vent Blower	/			
Reactor Vent Booster	V			
VTP-3350	/	PID Reading: /7,3 PPM		
VTP-3360	/	PID Reading: io. PPM		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_Level: 67 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 29 %	
T-530 Mixer	V	
LFG Condensate Conveyance Line	~	Last Pressure Test: 7-/9-21 Next: 7-20-72 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 64 % & 65%	i i
T-540/541 Mixers		
Chiller	OFFLINE	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	OFF Line	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	_	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	~	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: ۵&	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	1	Digital Displays: GOOD// Needs Attn
T-3334 Settling Tank		Last Cleaning (Semi Annual): 9~10~21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	~	4.00 gpm @ 0845
Building Containment Sump		Last Alarm Test Date (Monthly): 2-12-22-1

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	V	Bags: /2,75 Gallons: ~ 25
Phosphorous Pump (P-2221)	V	
Caustic Supply	V	~ /35 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	1	
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): Zーi?~227
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	1-27-22	Aced KARE clean sedan
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	- V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	~	
Automatic Backwash	Cycle Count: 2/	LERET
BF-3340 a/b Differential Pressure	PSI: 4	18/14 22.7 gam
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date: 🗸	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: 7.5	14/6.5 22.7gm
Last Backwash Performed	Date: 1-26-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator		Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	~	
Motor Control Center	~	
PLC	/	UPS @ 97 min / 95 Events
HMI's	/	
BTS Process KWH Meter	1850335 KWH	Time: 1001
Building#2 KWH Meter	5345231 KWH	Time: (00)

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	~	GC # checking BIO: #Z
Alarms Enabled	/	a-ceirbrasion + majort 2-16-22
GC Influent Filters	/	-

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 17, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6362903	
FT-3324 Feed Spare	204469	
FT-3322 Feed to Reactor 2	11253334	
FT-3323 Feed to Reactor 3	964305	
FT-3301 T-510 to BIO	51849940	
FT-3341 BIO Effluent	66789336	
FT-3342 BIO Recycle	56206217	

K. SAFETY

ltem	Status	Comments
Building #2 Fire Extinguishers	V	Inspection date: 1-21-72
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (V) / N

OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022		
Inspection Performed by:	Mike Gelwick		

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12.82 04	Counter: 197013 Cycles: 613	
LFG Cond Automatic Trap CT-2	Sump Level: 8.63 ou	Counter: 275703 Cycles: 145	
LFG Cond Automatic Trap CT-3	Sump Level: 7.44 04	Counter: 324806 Cycles: 318	
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3,36 Counter: 191278 Cycles: 7 Sump: 8,890	
PM-15 Containment / Vessel	✓ Level: 78 %		
MW-51 Containment / Vessel	Level: 60 %		
PM-11 Containment / Vessel	Level: 50 %		
MW-38 Systems	~		
North Toe System	~		
North End Systems (Weekly)	~	4	
Full N. End Systems Check (Monthly)		Last Done: 121-22 2-18-22	
North End Pipeline(s)Flushing (As Needed)	~	Perform if suspended solids present Last Done: 11/15/15	
NTES line flush to T-530 (As needed)	V	Perform if suspended solids present Last Done: 10/29/21	
NTES Piping Containment	~	Monthly Sump Level: 1/4 all 27' Date: 2-17-22	
North Boundary System P-001:	CV 73.0% @6.2 gpm	40.74Hz / 2.55 Amps. / vault psi @ 18/10/60445	
T-101 & T-102 Containment / Tank		Levels: 73 % & 72 %	
Raw Water Storage Tanks Piping	~		
RWST Building Temp. (TT-101)	49.9 °F	Outside Temp.: ~ 4 °F	
P -12 J or P-122	/	0,6 gpm/CV 60 %	
RWST 2ndry Cont. High Level Switch	/	(LSH-101) Last Test(monthly): Z-17-22	
RWST Back-Up Generator block Heater and	* /	Last Test Run(monthly): Z-17-22	

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 440 Gallons Reserve = 1 tote
Caustic Bay Heater	/	
Peroxide Tote Level	/	~ 115 Gallons Reserve = ~55 ml
HCL Tote Levels	1	~ 2 20 Gallons Reserve = ~3074
Chemical Totes and Piping Inspected	/	Leaks observed: Y / 🕦
Emergency Shower Inspected		Checked and Flushed - All OK: (Y) / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments		
Primary Acid Feed Pump (P-631)	· ·			
Ion Exchange Acid Feed Pump (P-632)	~	PI-0632 PSI: 56-59	CV: 4	%
Primary Acid Retention Tank (T-510)	V			
All Acid Feed Lines	~	Leaks observed: Y /	(N)	

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022		
Inspection Performed by:	Mike Gelwick		

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	V	Last Cleaning (Qtrly): 10-20-2/
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	1	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: (0.8	
pH 310	Value: 6.87	
pH 315	Value: 10.89	
Flocculation Chamber Paddle Wheel	V	
Precipitate Floc Quality	/	Good
Clarifier Water Quality		Good Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level		
Clear-well Chamber and Water Level	1	
HMR PLC Panel		
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)	-	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 365	
Clear-well Transfer Pumps(P-371)/ 372)	V	
Sludge Transfer Pump (P-330)	V	Exercise Valves Weekly: Bothsk
Manual Sludge Lateral pumping	V	Last done (As Needed): 4/42-3-20-21/3-7-20-2
Manual Sludge Lateral Ball Valves	V	Exercise Weekly: Alloc
Automatic Blow-down Operations	~	

F. pH PROBES

pH Probe Location	Calibration Da		Comments: (Ti	me done)
pH-310 HMR-30 (T-300A)	2-24-	22-Today	1330	
pH-315 HMR-30 (T-300B)				\
pH-365 Primary Acid Ret. Tank				1
pH-113 Pre-Ion Exchange				
pH-670 Pre-UV-OX				1400
pH-740 Discharge Surge Tank	1)	Discharge suspe	ended: 1403 ←→ 1427
Out of Hold Double Check			None in hold: _	Vid un
Valves Back to Normal Position			All OK: VVid	m

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	/	Gauge Reading: Ø %
Sludge Thick. Transfer Pump (P-350)	~	
Sludge Holding Tank (T-351)	V	Level:~ 45 %
Sludge Holding Tank (T-352)	/	Level: 41 %
Decant Transfer Pump (P-352)		CV 67 % @ 05 gpm
Filter Press Pumps (P-381 / P-382)	V	
Filter Press		Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022		
Inspection Performed by:	Mike Gelwick		

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 27,2 psi	CV@ 69 % @ 1,80 gpm
Retention Tank (T-114)	✓ Operating Press: 3€ psi	pH-113 @ 3,68
Bag Filter (BF-113)	✓ Operating Press: 39 psi	
Ion Exchange (Cage(1) or 2) + Guard	✓ Operating Press: 3 c psi	TP-174A->TP-176A/5 Cays ters + GALING
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522)	Operating Press: 14 psi	CV@ 58 % @ 37.1 gpm
T-520 to GAC Total (FT-675)	257071178 gal	Time: 0956
North End On-Site Pumping	Operating Press: 2-3 psi	12,3 gpm @ 0945
North End Off-Site Pumping	Operating Press: 2-8 psi	8.8 gpm @ 0945
Peroxide Feed Pump (P-680)		SPD 24 % / RATE O.G
Peroxide Conc. At (TP-710)	(,⊅ PPM	
Peroxide Conc. At (TP-740)	O.⊅ PPM	

J. HAZARDOUS WASTE STORAGE

	Item_	Status	Comments
60	186 Day storage area check	~	Check sheet completed: ye5-MKL-2-24-22-70-lay
	Satellite Haz. Waste Areas (BLDG #1)		Condition: TX Lesin + man Good
	Satellite Haz. Waste Area (BLDG #2)	/	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		3000
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Emm	Next: NA (Lungrag
Peroxide Feed Pump (P-650)	/ ,	Flow Rate: ~7, o cc/min.
UV-Ox Power	-	25.7 kVA 2472 Volts 103 Amps
Lamp Hours	2754 Hrs	
Crystal Condition & Wiper Status		Oiler status: 🗠
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	12.0 psi ln 12.5 psi Out
UV-OX Feed Pump (P-600 or (P-601))	<u></u>	CV@ 76 % @ 7.4 gpm
UV-OX Temperature	In(TT-670): /ʒ, ७ °C	Out(TT-710): 25,4 °C
PDU GAC (PDT-710)		Δ Pressure: 3 psi
Peroxide Concentration Pre UV	(00 PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)	·	CV@ 3 %
Secondary Acid Retention Tank (T-645)	· ·	
Pre – UV Oxidizer Total (FT-670)	2/333244 gal	Time: 095-9
Post UV-Ox / Pre PDU		Pressure: /5 psi
Post PDU	~	Pressure: 8 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022		
Inspection Performed by:	Mike Gelwick		

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments		
PDT-720	~	Δ Pressure: 7 psi		
PDT-730		Δ Pressure: > psi		

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	~	CV@ 53.4 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		32.1 gpm @ 0955
POTW Line Pressure (PT-770)	V	32.1 psi
Effluent Totalizer Reading (FT-770)	251273312 gal	Time: (000)
POTW MH17S-078 Discharge Check (Monthly)	14	Last Done: 2-16-22
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done:
2-Inch POTW Backup Pressure Testing (Annual)	V	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	V	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 2-24-22-100au	Plant Effluent Suspended: /403 ← /427
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2001 volts(monthly)	Adjustment Needed: Y or (N)
Verify Bridge Current between.300v360v	Reading: 0.33(volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: (000 - 600)

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19852431	(FT-505) LFG Cond. to T-530	221505
(FT-025) NBBW Influent	95094752	(FT-056) Off - Site N. End Influent	44618692
(FT-012) MW-38 Inf. to HMR-30	8565347	(FT-113) Ion Exchange Influent	1162203
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30079882
(FT-043) MW-38 to RWST	3097557	(FT-026) NBBW Bypass to RWST	4473525
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8242116
(FT-012T) MW-38 to T-540/541	8664186	(FT-035) NTES Inf. to BIO	6746306
(FT-040T) MW-38N to T-540/541	1979523	(FT-035T) NTES to T-530	467849
(FT-041T) MW-38S to T-540/541	2697984	(FT-017) BIO Inf. from T-530	663354
(FT-042T) MW-38 Source to T-540/541	4058622	(FT-018) T-540/541 Influent	8709073
(FT-055) On - Site N. End Influent	100310277	(FT-352) T-352 to HMR-30	1344410

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, February 24, 2022

Inspection P	erformed by: Mi	ke Gelwick
D 41D 00MDD5000D0		
P. AIR COMPRESSORS	Status	Comments
Compressor Intake Temp.	50 °F (Analog Gauge)	Outside Temp.: ~ /O °F
Compressor Building Vent		Closed- operations
Primary Air Compressor	2,000 Hour service date: 2-7-22	Coolant present in sight glass: \(\Omega \) N
(IRN30H)	Serviced @ 62971 Hours	Next service @ 64 97/ Hours
(,		Current Hours @ 63180
IRN30H Motor Speed	31 %	
IRN30H Pressure	118 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter	_	Date Last Changed: Z-7-27
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / N
Backup Air Compressors	***	
(T-30 East and West)	<i>V</i>	Both cool to touch: 🍄 / N
Air Dryer	V ECO DE	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 2-24-2 2- Teslus	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	r	[10 psi
Q. SUMPS	Towns and the second se	
Item	Status	Comments
Bag Filter Sump	~	
Wet Well Sump	/	
D 040 0UD0M4T00D4	DU.	
R. GAS CHROMATOGRA	T-12-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	10
Item	Status	Comments
GC Operational Alarms Enabled	-	GC # checking UV-Ox Effluent:
GC Influent Filters	,	cc-cedigration + major 2-23-22
GC Illidelit Filters	V	
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers	V	Date inspected: Z-27-22-Annual
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: (N
Other Comments: New UPS IN HMR30 + Kee	15 T N/C 5 12 2 1 1 1 1	
TO THE SE F ACT	Ji- Fic Johny,	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	~	1.84	35.9 %	7,5	
P-3301A	5B	-	- %	-	
NTES Pump P-002(Sump) / (P-002W(10R))	V	0,49	48 %	P035 P038 3536 7.0	Globules Observed at TP-130: Y / No Time: 0910
T-530 P-005	-	0.21	41 %	2,5	
T-540/541 P-006	_	0.32	57 %	8.0	
LFG COND Auto-Traps	~	0.0	NA	500	Between Cycles: N
Reactor Feed Pumps				en e	
P-3321	12:52	3752 589m	58.9 %	8.0	
P-3322	31	3,46	53.9 %	515	
P-3323	56	—	- %	_	
P-3324		2.48	39.5 %	5.5	
Reactor Effluent Pumps					
P-3341		3.08	60.1 %	18	
P-3341A	5B	_	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-30-2/
B-3331	~	4.31	116	3-2022	Greased, Belt and Filter Checked: (Ý) / N
B-3332	58	-	~	1	Belt and Filter Checked: Y / (N)
B-3333	~	4.38	112		Greased, Belt and Filter Checked: 4 / N
B-3334	~	4.24	106	V	Greased, Belt and Filter Checked: (Ý) / N

C. REACTOR VENTILATION

Item	Status	Comments		
Vapor Carbon Contactor		On-line: 2/10/18		
Reactor Vent Blower	V			
Reactor Vent Booster	V			
VTP-3350	/	PID Reading: 32,1 PPM		
VTP-3360		PID Reading: 26.1 PPM		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022	
Inspection Performed by:	Mike Gelwick	

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	∠ Level: 60 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: כך %	
T-530 Mixer	_	
LFG Condensate Conveyance Line	~	Last Pressure Test: 7-19-21 Next: 7-2-22 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 39 % & 49 %	T-540 Fed line my be frozen.
T-540/541 Mixers	V	
Chiller	offline	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	ORCCIAL	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	/	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	·	Last Back Flushing (Quarterly): 2-3-72
T-3310 Sedimentation Tank	Visual Level:	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: 70 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	_	Digital Displays: GOOD Needs Attn
T-3332 Reactor No. 2	/	Digital Displays GOOD / Needs Attn
T-3333 Reactor No. 3	/	Digital Displays. GOOD / Needs Attn
T-3334 Settling Tank		Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	1	•
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	V	3.98 gpm @ 1025
Building Containment Sump	-	Last Alarm Test Date (Monthly): 2-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments	
Phosphorous Supply	/	Bags: /2.5 Gallons: ~ 70	
Phosphorous Pump (P-2221)	V		
Caustic Supply		~ /IO Gallons	
Caustic Pump (P-2211)	SB	Currently in acid addition mode	
Acid Supply	V	~ 40 Gallons	
Acid Pump (P-2211)	/		
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): 2-(7-22	
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y /	Y / (N) Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022	
Inspection Performed by:	Mike Gelwick	

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	2-24-22- roley	New 4+ 10 14 5105 USED
pH-3331 Reactor 1		1
pH-3332 Reactor 2		
pH-3333 Reactor 3		V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	~	
Automatic Backwash	Cycle Count: 16	Reset
BF-3340 a/b Differential Pressure	PSI: 3	16/13 72.7
75-micron Bags Last Cleaning	Date: //-/4	
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date: U	
GACF-3340 Status	-	
GACF-3340 Differential Pressure	PSI: 6	13/7 22.76Am
Last Backwash Performed	Date: 1-26-72	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status Comments	
"BIO" Backup Generator	/	Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	-	
Motor Control Center	✓	
PLC	V KA	UPS@/3/ min/ O Events#
HMI's	~ 2.	10-22
BTS Process KWH Meter	1853106 KW	H Time: //24
Building#2 KWH Meter	5352874 KW	H Time: //24

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #Z
Alarms Enabled	~	acceptantum + main+ . 2-23-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, February 24, 2022	
Inspection Performed by:	Mike Gelwick	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6384052	
FT-3324 Feed Spare	225461	
FT-3322 Feed to Reactor 2	11282695	
FT-3323 Feed to Reactor 3	964310	
FT-3301 T-510 to BIO	51865837	
FT-3341 BIO Effluent	66813013	
FT-3342 BIO Recycle	562480d	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	~	Inspection date: 2-21-22-Autwel
Building #2 Eye Wash/Shower	V	Checked and Flushed- All OK: Ø / N

L. OTHER COMMENTS:

2-10-22- New UAS &n Mora- Commol Center.	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022	
Inspection Performed by:	Mike Gelwick	

A. PERIMETER COLLECTION SYSTEMS

Item	Status		Comments
LFG Cond Automatic Trap CT-1	Sump Level: /2	15504	
LFG Cond Automatic Trap CT-2		6704	Counter: 276675 Cycles: 379
LFG Cond Automatic Trap CT-3	Sump Level: 7	2204	Counter: 3285-22 Cycles: 1236
CT-4 Containment/Vessel (LFG Cond)	Level: 3	۷ %	Tank Level: 3.36 Counter: 19/296 Cycles: 2 Sump: 9,01 a
PM-15 Containment / Vessel	Level: 20	%	
MW-51 Containment / Vessel		- %	
PM-11 Containment / Vessel	✓ Level: 70	%	
MW-38 Systems	/		
North Toe System	V		
North End Systems (Weekly)	/		
Full N. End Systems Check (Monthly)	~		Last Done: 3-25-22
North End Pipeline(s)Flushing (As Needed)	/		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~		Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	~		Monthly Sump Level: 00 7/6.07 Date: 3-17-22
North Boundary System P-001:	CV72,9 % @ 6.Z	gpm	40.18 Hz / 2.05 Amps. / vault psi @ 18/Nolentes
T-101 & T-102 Containment / Tank	~		Levels: 27 % & 27 %
Raw Water Storage Tanks Piping	~		
RWST Building Temp. (TT-101)		°F	Outside Temp.: ~ 40 °F
(P-121) or P-122	-		0.6 gpm/CV 49 %
RWST 2ndry Cont. High Level Switch	V		(LSH-101) Last Test(monthly): 3-17-27
RWST Back-Up Generator	V :		Last Test Run(monthly): 3-17-27

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	V	~ 460 Gallons Reserve = 250gg
Caustic Bay Heater		- Ger
Peroxide Tote Level	V	~260 Gallons Reserve = ~/3054
HCL Tote Levels	_	~ //O Gallons Reserve = ~30
Chemical Totes and Piping Inspected	~	Leaks observed: Y / D
Emergency Shower Inspected		Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	/	
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI: 52-54 CV: 3 %
Primary Acid Retention Tank (T-510)	V	70
All Acid Feed Lines	/	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 qpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	~	Last Cleaning (Qtrly): 4-7-22 - Today
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	V	Last Cleaning (Qtrly): 4-7-22- Taking
T-300A/B Overflow	6	
pH Set-point for (pH 315)	Value: (0,8	
pH 310	Value: 6.64	
pH 315	Value: 10.74	
Flocculation Chamber Paddle Wheel	~	
Precipitate Floc Quality	V	Good
Clarifier Water Quality	~	Good Oil or sheen observed: Y / (1)
Clarifier Effluent Piping / Water Level	~	
Clear-well Chamber and Water Level	~	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	/	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	~	
Polymer Tank Level	Gallons: ~ 510	
Clear-well Transfer Pumps (P-371)/ 372)		
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 60+4 54
Manual Sludge Lateral pumping	V	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	/	Exercise Weekly: #11 64
Automatic Blow-down Operations	/	- FILL OIL

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	4-7-22-roday	1426
pH-315 HMR-30 (T-300B)	1	1120
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1457
pH-740 Discharge Surge Tank	V	Discharge suspended:/⟨1/7 ←>/⟨1/2 ⟨4
Out of Hold Double Check		None in hold: //d m
Valves Back to Normal Position		All OK:

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Status	Comments
	Gauge Reading: $ > $ %
~	oudge Hodding. 2 70
V	Level:~ 65 %
~	Level: 30 %
22	CV — % @ — gpm
	70 @ gpill
	Stage: Empty-ledy +2 Fill
	Status V S&

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 400psi	CV@ 70 % @ (.74gpm
Retention Tank (T-114)	✓ Operating Press: 40 psi	
Bag Filter (BF-113)	✓ Operating Press: ५3 psi	3, 12
Ion Exchange (Cage (1) or 2) + Guard		TP-174A->TP-176A/5cantstas + Colore
Post Ion Exchange	✓ Operating Press: 3 ∕ psi	The state of the s

I. FEED SURGE TANK

Item	Status Comments	
Feed Surge Tank (T-520)	Last Cleaning (As Needed, if 4" or	f
	Level: 38 % solids accumulate): 12/15/19	
Feed Surge Pump (P-521 or (P-522))	Operating Press: (9 psi CV@ 63 %@ 52.3 gpr	n
T-520 to GAC Total (FT-675)	258982585 gal Time: (210	
North End On-Site Pumping	Operating Press: 23 psi (2.3 gpm @ //56	
North End Off-Site Pumping	Operating Press: 2-6 psi 8-4 gpm @ (15-6	
Peroxide Feed Pump (P-680)	SPD 2.4 % / RATE 0.7	
Peroxide Conc. At (TP-710)	1.0 PPM	
Peroxide Conc. At (TP-740)	OLO PPM	

J. HAZARDOUS WASTE STORAGE 4-6-22-GAC AKKED OF BY Clem HAR BONS X

	Item	Status	Comments	
20	180 Day storage area check	-		
	, ,		Check sheet completed: yes-smal-4-2	22
	Satellite Haz. Waste Areas (BLDG #1)		Condition: Ix hism + man Good	
- [Satellite Haz. Waste Area (BLDG #2)		Condition: Good	

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	~	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Rummian	Next: NA/LUNNIM
Peroxide Feed Pump (P-650)		Flow Rate: ~ 7,0 cc/min.
UV-Ox Power		27.17 kVA 2682 Volts 10.2 Amps
Lamp Hours	382 Hrs	
Crystal Condition & Wiper Status		Oiler status: Ou
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	9 psi In 9 psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 65 % @ 7.1 gpm
UV-OX Temperature	In(TT-670): /2.9 °C	Out(TT-710): 25.7 °C
PDU GAC (PDT-710)	BALLWASAND HORAY	Δ Pressure: psi
Peroxide Concentration Pre UV	(00 PPM	, , , , , , , , , , , , , , , , , , , ,
Peroxide Concentration Post UV(TP-720)	20 PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)		CV @ 1 %
Secondary Acid Retention Tank (T-645)	/	
Pre – UV Oxidizer Total (FT-670)	21612280 gal	Time: (210
Post UV-Ox / Pre PDU	~	Pressure: // psi
Post PDU	/	Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, April 07, 2022

Inspection Performed by:

Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720		Δ Pressure: // psi
PDT-730		Δ Pressure: 7 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752)	/	CV@ 53.6 %
Effluent Surge Tank (T-740)	/	Level: 3 9 %
Effluent Discharge Rate (FT-770)		31.9 gpm @ 1201
POTW Line Pressure (PT-770)		32,4 psi
Effluent Totalizer Reading (FT-770)	253142392 gal	Time: /2 //
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: 3-23-22
4X8-Inch POTW Leak Detection Checks (Monthly)	_	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done: 2-16-21
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	/	Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed:	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	3-24-62	1307 +> 1326
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or W
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	The state of the s

O. WTP INFLUENT TOTALIZERS Time: 12127 1216

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20001489	(FT-505) LFG Cond. to T-530	221994
(FT-025) NBBW Influent	95389425	(FT-056) Off - Site N. End Influent	45141404
(FT-012) MW-38 Inf. to HMR-30	8633257	(FT-113) Ion Exchange Influent	1267963
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30085662
(FT-043) MW-38 to RWST	3122273	(FT-026) NBBW Bypass to RWST	455 6290
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8276332
(FT-012T) MW-38 to T-540/541	8672314	(FT-035) NTES Inf. to BIO	6775548
(FT-040T) MW-38N to T-540/541	1979829	(FT-035T) NTES to T-530	468980
(FT-041T) MW-38S to T-540/541	2698389	(FT-017) BIO Inf. from T-530	664465
(FT-042T) MW-38 Source to T-540/541	4066047	(FT-018) T-540/541 Influent	8716648
(FT-055) On - Site N. End Influent	101050914	(FT-352) T-352 to HMR-30	1364947

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, April 07, 2022	
Mike Gelwick	

P. AIR COMPRESSORS

Item	Status	Comments
Compressor Intake Temp.	60 °F (Analog Gauge)	Outside Temp.: ~ 45 °F
Compressor Building Vent		O Pen - operations
Primary Air Compressor	2,000 Hour service date: 2-7-22	Coolant present in sight glass: Ø / N
(IRN30H)	Serviced @ 62971 Hours	Next service @ 64971 Hours
		Current Hours @ 63716
IRN30H Motor Speed	31 %	
IRN30H Pressure	115 psi	
IRN30H Moisture purge valve chk(Weekly):	~	
IRN30H Intake Filter	V	Date Last Changed: と~7~2マ
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / 🖎
Backup Air Compressors		
(T-30 East and West)		Both cool to touch: Ø / N
Air Dryer	- Econ	Moisture at Receiver Tank: Y /
Oil Moisture Prevention (Monthly)	Last Done: 3-24-27	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		(10 psi

Q. SUMPS

Item	Status	Comments	
Bag Filter Sump			
Wet Well Sump	V		

R. GAS CHROMATOGRAPH

Item	Status	Comments
GC Operational	V	GC # checking UV-Ox Effluent: #1
Alarms Enabled	~	CC-Caltigration + matrix 4-6-22
GC Influent Filters		CC CON OF THE WATER & C. CE

S. SAFETY

Item	Status	Comments
Building #1 Fire Extinguishers	V	Date inspected: 3-24-27
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: V / N

Other Comments:

\$4-6-22-5 Pent 6	nAC Presed up by	Clean HARbours	. HAZARdows Storage area Europy

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	r	1.76	43.6 %	8-5	
P-3301A	35	_	- %	-	
NTES Pump 4-4-22 Suffer P-002(Sump) / P-002W(10R)		0.50	49 %	P035 P038 36-37 65	Globules Observed at TP-130: Y / Time:// LO
T-530 P-005	~	0.20	41 %	7.0	
T-540/541 P-006		0.30	50 %	7.0	
LFG COND Auto-Traps		0.0	NA	5,0	Between Cycles: Ø / N
Reactor Feed Pumps					
P-3321	V	2.30	75.8 %	7.5	
P-3322	/	3.32	51.2%	6.0	
P-3323	56	_	- %	-	
P-3324	/	2.32	40,7 %	6.0	
Reactor Effluent Pumps					
P-3341	/	3,57	64.2 %	16.0	
P-3341A	56	_	-%	_	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-/6-22
B-3331		4.26	132	6-2022	Greased, Belt and Filter Checked: O / N
B-3332	SB		-	1	Belt and Filter Checked: Y / P
B-3333	/	4.31	130		Greased, Belt and Filter Checked: Ø / N
B-3334	/	4.20	124		Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor		On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	V	
VTP-3350		PID Reading: 52.5 PPM will Check who went
VTP-3360		PID Reading: 51.3 PPM WELL

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_ Level:55 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 34 %	
T-530 Mixer	~	
LFG Condensate Conveyance Line	V	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvis: 44 % & 46 %	
T-540/541 Mixers	/	
Chiller	offline	Chiller Coolant Lvl: ~ _ " Below full mark
Chiller Cooling Fins (as needed)	offline	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	/	Heat Trace: On OR / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): Z-3-22
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: 76 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	~	Digital Displays: GOOD V Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	~	Digital Displays: GOOD// Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	, , , ,
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	_	3.97 gpm @ /233
Building Containment Sump	V	Last Alarm Test Date (Monthly): 3-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	~	Bags: [[Gallons: ~ 25
Phosphorous Pump (P-2221)	~	37
Caustic Supply	V	~ 320 Gallons New PTC 4-6-22
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	/	
Caustic Pump (P-2231)	Leaks: Y /	D Last tubing tip cleaning (monthly): 3イ7-2て
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	N Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	3-24-22	Stray of Clean today
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	d	1

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	-	
Automatic Backwash	Cycle Count: 5	LoseT
BF-3340 a/b Differential Pressure	PSI: O	11/11 = (. Bypn
75-micron Bags Last Cleaning	Date: //-14-19	11/11/11/11/11/11
75-micron Bags Last Inspection	Date: I	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 4	11/7 A 1.8 gpm
Last Backwash Performed	Date: 3~18-22	111 1 Ogsic

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	V	Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor		- Vannout
Motor Control Center	V	
PLC	V	UPS @ /3/ min / Events
HMI's		or o @ / 5/ min/ / Events
BTS Process KWH Meter	1873600 KWH	Time: /339
Building#2 KWH Meter	5395236 KWH	1 - 2

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V	GC # checking BIO: #2
Alarms Enabled	<i>(</i> /	CL-Californian+ maps 4-6-22
GC Influent Filters	/	CC- CAT IS POTON & MATIN + 4-6-22

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 07, 2022	
Inspection Performed by:	Mike Gelwick	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6556139	
FT-3324 Feed Spare	396619	
FT-3322 Feed to Reactor 2	11521860	
FT-3323 Feed to Reactor 3	964313	
FT-3301 T-510 to BIO	52116070	
FT-3341 BIO Effluent	67101660	
FT-3342 BIO Recycle	56498179	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	V	Inspection date: 3-24-22
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N

OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12,55 04	Counter: (98362 Cycles: 202
LFG Cond Automatic Trap CT-2	Sump Level: 8.58 ac	Counter: 277170 Cycles: 495
LFG Cond Automatic Trap CT-3	Sump Level: 7.23 .*	Counter: 330450 Cycles: 1928
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 32 %	Tank Level: 3.36 Counter: 19/296 Cycles: O Sump: 8,91-4
PM-15 Containment / Vessel	Level: 30 %	
MW-51 Containment / Vessel	Level: 55 %	
PM-11 Containment / Vessel	∠ Level: 40 %	
MW-38 Systems		
North Toe System	~	
North End Systems (Weekly)	_	
Full N. End Systems Check (Monthly)	~	Last Done: 3-25-22
North End Pipeline(s)Flushing (As Needed)	V	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	V	Monthly Sump Level: Ary コル・37' Date: 3~17-22
North Boundary System P-001:	CV 73.2 % @ 6.2 gpm	40.48 Hz / 2.06 Amps. / vault psi @ 18/No lenes
T-101 & T-102 Containment / Tank	_	Levels: 28 % & 27 %
Raw Water Storage Tanks Piping		
RWST Building Temp. (TT-101)	54.6 °F	Outside Temp.: ~ 42 °F
€-12 or P-122	~	2.0 gpm/CV 64 %
RWST 2ndry Cont. High Level Switch	V	(LSH-101) Last Test(monthly): 3-17-22
RWST Back-Up Generator		Last Test Run(monthly): 3~17~22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 330 Gallons Reserve = ~250gal
Caustic Bay Heater		
Peroxide Tote Level	_	~ 280 Gallons Reserve = ~ 3074
HCL Tote Levels	/	~ 95 Gallons Reserve = ~305%
Chemical Totes and Piping Inspected	~	Leaks observed: Y / 🔊
Emergency Shower Inspected	/	Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	_	
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 50-54 CV: 3 %
Primary Acid Retention Tank (T-510)	V	
All Acid Feed Lines	/	Leaks observed: Y / ND

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	/	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 4-7-2こ
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10,8	
pH 310	Value: 6.71	
pH 315	Value: 10.87	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	Good
Clarifier Water Quality	/	Goal very clear Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	/	
HMR PLC Panel		
Caustic Pump (P-270)	SB	A
Caustic Pump (P-280)		
Polymer Pump (P-310)	_	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 425	
Clear-well Transfer Pumps(P-371) 372)	~	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: So Hu 34
Manual Sludge Lateral pumping	~	Last done (As Needed): 3-/5-22
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: Allow
Automatic Blow-down Operations		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	4-14-22-75kay	1250
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX	- i	1329
pH-740 Discharge Surge Tank	V	Discharge suspended: (240 ←>/248
Out of Hold Double Check		None in hold: A d
Valves Back to Normal Position		All OK:

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	~	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	_	
Sludge Holding Tank (T-351)		Level:~ 45 %
Sludge Holding Tank (T-352)	~	Level: 40 %
Decant Transfer Pump (P-352)		CV 71 % @ 0.5 gpm
Filter Press Pumps (P-381 / P-382)	_	
Filter Press		Stage: Empty Realy to All

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 46.6 psi	CV@ 77 % @ 1.7/ gpm
Retention Tank (T-114)	✓ Operating Press: 45 psi	
Bag Filter (BF-113)	✓ Operating Press: 49 psi	
Ion Exchange (Cage Or 2) + Guard	✓ Operating Press: 44 psi	TP-174A-2+P-176A/5 county pers + control
Post Ion Exchange	✓ Operating Press: 3. ≤ psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 2 (psi	CV@ 64 % @ 31,9 gpm
T-520 to GAC Total (FT-675)	259298972 gal	Time: 0947
North End On-Site Pumping	Operating Press: 2-3 psi	/2.3 gpm @ ♥939
North End Off-Site Pumping	Operating Press: 2 - 8 psi	8.6 gpm @ 0939
Peroxide Feed Pump (P-680)	~	SPD 2.4 % / RATE 0.6
Peroxide Conc. At (TP-710)	(10 PPM	
Peroxide Conc. At (TP-740)	PPM صه	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	VEMITY	Check sheet completed: NH/Eurty
Satellite Haz. Waste Areas (BLDG #1)		Condition: Ix desir + much Good
Satellite Haz. Waste Area (BLDG #2)	~	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: N4/Running	Next: NA/RUNNIN
Peroxide Feed Pump (P-650)	~	Flow Rate: ~ 7.0 cc/min.
UV-Ox Power	_	26.46 kVA 2712 Volts 9.8 Amps
Lamp Hours	546 Hrs	1.7
Crystal Condition & Wiper Status	Wifer was been streeting . oficed come # Incress PSI	Oiler status: 🍫
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	9.5 psi In 9.5 psi Out
UV-OX Feed Pump (P-600 or (P-601))	~	CV@ 6 Z % @ 6.4 gpm
UV-OX Temperature	In(TT-670): /3,3°C	Out(TT-710): 2 7. 3 °C
PDU GAC (PDT-710)	-	Δ Pressure: Z psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	ZO PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)	V	CV@ 3 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	21675172 gal	Time: 0947
Post UV-Ox / Pre PDU	_	Pressure: // psi
Post PDU	/	Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, April 14, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments	
PDT-720	V	Δ Pressure: /3 psi	
PDT-730		Δ Pressure: 3 psi	

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	_	CV@ 53.5 %
Effluent Surge Tank (T-740)	_	Level: 40 %
Effluent Discharge Rate (FT-770)		32,0 gpm @ 0945
POTW Line Pressure (PT-770)		32.2 psi
Effluent Totalizer Reading (FT-770)	253460166 gal	Time: 0947
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: 4-14-22 - Today
4X8-Inch POTW Leak Detection Checks (Monthly)	~	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	V	Last Done: 2-16-27
2-Inch POTW Backup Pressure Testing (Annual)	/	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: o %
LEL Sensor Calibration / Automatic High	Last Completed:	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	3-24-22	1307 +> 1326
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: اسرع volts(monthly)	Adjustment Needed: Y or 🖎
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	-

O. WTP INFLUENT TOTALIZERS Time : 0948→ 8952

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20009961	(FT-505) LFG Cond. to T-530	222110
(FT-025) NBBW Influent	95450261	(FT-056) Off - Site N. End Influent	45227968
(FT-012) MW-38 Inf. to HMR-30	8646320	(FT-113) Ion Exchange Influent	1284955
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30086120
(FT-043) MW-38 to RWST	3122615	(FT-026) NBBW Bypass to RWST	4557825
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8281347
(FT-012T) MW-38 to T-540/541	8677.988	(FT-035) NTES Inf. to BIO	6780298
(FT-040T) MW-38N to T-540/541	1979891	(FT-035T) NTES to T-530	469149
(FT-041T) MW-38S to T-540/541	2698448	(FT-017) BIO Inf. from T-530	664962
(FT-042T) MW-38 Source to T-540/541	4071626	(FT-018) T-540/541 Influent	8719393
(FT-055) On - Site N. End Influent	101172801	(FT-352) T-352 to HMR-30	1367944

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Inspection D	ate: Thursda	y, April 14, 2022
Inspection Performed by:		ke Gelwick
P. AIR COMPRESSORS		
Item	Status	Comments
Compressor Intake Temp.	65 °F (Analog Gauge)	Outside Temp.: ~ 45 °F
Compressor Building Vent	~	closed - securard
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-21 Serviced @ 62971 Hours	Coolant present in sight glass: Ø / N Next service @ 6497/ Hours Current Hours @ 6380/
IRN30H Motor Speed	31 %	
IRN30H Pressure	/(7 psi	
IRN30H Moisture purge valve chk(Weekly):	~	
IRN30H Intake Filter	~	Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly) /	Excessive Moisture: Y / AP
Backup Air Compressors (T-30 East and West)	~	Both cool to touch: Ø / N
Air Dryer	v Elo en	Moisture at Receiver Tank: Y / 🖎
Oil Moisture Prevention (Monthly)	Last Done: 3.24-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		No psi
Q. SUMPS		
Item	Status	Comments
Bag Filter Sump		
Wet Well Sump	/	
R. GAS CHROMATOGRA	PH	
Item	Status	Comments
GC Operational	V	GC # checking UV-Ox Effluent: #/
Alarms Enabled	~	Californian + 10000 4-13-22
GC Influent Filters		ment
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers	V .	Date inspected: 31 24-27
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N
Other Comments:		
* UV-OX Crystal wrter Hasten	nameng pensodacally peoplese to	to down Lower and Decres se As i straythy.
	•	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	100000000000000000000000000000000000000	narge sure si)	Comments
T-510 Pumps						
P-3301	_	1,87	44.6%	8.5	5	
P-3301A	SB	-	- %	_		
NTES Pump P-002(Sump) / (-002W(10R)		0.50	48%	P035	P038	Globules Observed at TP-130: Y / (1) Time: 0911
T-530 P-005	~	0.19	41 %	7.0	9	
T-540/541 P-006		0.20	41 %	7-	CO.	
LFG COND Auto-Traps	/	0,0	NA	5		Between Cycles: (N
Reactor Feed Pumps		A PART OF THE REAL PROPERTY.				
P-3321	~	2.37	534 %	4.0	>	
P-3322	~	3.22	50.2%	510		
P-3323	SB	_	- %			
P-3324	V	2.33	35.6%	4.5		
Reactor Effluent Pumps						
P-3341	1	2,90	63.1 %	19.	0	
P-3341A	58	_	- %			

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331	-	4.25	132	6-2022	Greased, Belt and Filter Checked: 🍄 / N
B-3332	SS	_		1	Belt and Filter Checked: Y / 🕡
B-3333	~	4.76	130		Greased, Belt and Filter Checked: Ø / N
B-3334	V	4.17	126	4	Greased, Belt and Filter Checked:

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	_	On-line: 2/10/18
Reactor Vent Blower	~	
Reactor Vent Booster	~	
VTP-3350	~	PID Reading: (O. 8 PPM
VTP-3360		PID Reading: 3.5 PPM

Using pinoc Rental SN 592-908710 UNHI our site one Gues serviced

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	Level: 61 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 29 %	·
T-530 Mixer	~	
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-/9-21 Next?-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvis: 64 % & 65%	
T-540/541 Mixers	~	
Chiller	offline	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	OFLIM	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	/	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: 66	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 7/ %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	~	Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	V	Digital Displays: GOOD/ Needs Attn
T-3334 Settling Tank	V	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	r	4.24 gpm @ 1030
Building Containment Sump		Last Alarm Test Date (Monthly): 3-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply		Bags: // Gallons: ~ 75
Phosphorous Pump (P-2221)	V	
Caustic Supply	V	~ 280 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	~	
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): 3-17-27
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	N Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	3-24-22	3 May of F Clean fooday
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	√	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	-	
Automatic Backwash	Cycle Count: 13	Reset
BF-3340 a/b Differential Pressure	PSI: /	15/16 22.44Am
75-micron Bags Last Cleaning	Date: 11-14-19	770
75-micron Bags Last Inspection	Date: 1	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	/	
GACF-3340 Differential Pressure	PSI: 8	15/7 BZ,49pm
Last Backwash Performed	Date: 3~18-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	~	Block Heater: On OK / Off Warm Out)
Electrical Surge Suppressor		
Motor Control Center		
PLC		UPS @ /3/ min / / Events
HMI's	~	
BTS Process KWH Meter	1876346 KWH	Time: 1100
Building#2 KWH Meter	5401059 KWH	Time: (100

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	~	GC # checking BIO: # 2
Alarms Enabled		Caybrattan + matrix 4-13-22
GC Influent Filters	/	2,74

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 14, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6578603	
FT-3324 Feed Spare	418928	
FT-3322 Feed to Reactor 2	11553066	
FT-3323 Feed to Reactor 3	964317	
FT-3301 T-510 to BIO	52(37915	
FT-3341 BIO Effluent	67131556	
FT-3342 BIO Recycle	56539259	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	~	Inspection date: 3-24-2-2
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: 65 / N

L. OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12,55 04	Counter: 198525 Cycles: 163
LFG Cond Automatic Trap CT-2	Sump Level: 8.62 of	Counter: 277821 Cycles: 651
LFG Cond Automatic Trap CT-3	Sump Level: 7.23 of	Counter: 33/878 Cycles: /428
CT-4 Containment/Vessel (LFG Cond)	∠ Level: 3=36%	Tank Level: 3.38 Counter: / 9/296 Cycles: O Sump: 8,91
PM-15 Containment / Vessel	✓ Level: 3032%	7/1010 0 017(
MW-51 Containment / Vessel	✓ Level: 5525%	
PM-11 Containment / Vessel	Level: 4015%	
MW-38 Systems	~	
North Toe System	~	
North End Systems (Weekly)		
Full N. End Systems Check (Monthly)	~	Last Done: 3-25-22
North End Pipeline(s)Flushing (As Needed)	~	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	~	Monthly Sump Level: Any 2/6.07' Date: 4-21-22-7
North Boundary System P-001:	CV 73,0 % @ 6.3 gpm	40.80 Hz/207 Amps. / vault psi @ 18/Noleaus
T-101 & T-102 Containment / Tank	~	Levels: 37 % & 35 %
Raw Water Storage Tanks Piping	_	37
RWST Building Temp. (TT-101)	59.1 °F	Outside Temp .: ~ 58 °F UNP POTALOR HEN
(P-121) or P-122	~	0.6 gpm/CV 50 %
RWST 2ndry Cont. High Level Switch	/	(LSH-101) Last Test(monthly): 4-21-22 - rodus
RWST Back-Up Generator	/	Last Test Run(monthly): 4-21-22- roduy

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	V	~ 445 Gallons Reserve =
Caustic Bay Heater	/	WARM TERM
Peroxide Tote Level	/	~ 225 Gallons Reserve = ~/30441
HCL Tote Levels		~ 60 Gallons Reserve = ~ 30gal
Chemical Totes and Piping Inspected	/	Leaks observed: Y /
Emergency Shower Inspected		Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	~	
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI: 52-54 CV: 3 %
Primary Acid Retention Tank (T-510)	/	70
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	~	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.64	
pH 315	Value: 10.91	
Flocculation Chamber Paddle Wheel	~	
Precipitate Floc Quality	V	Good
Clarifier Water Quality	~	Good Oil or sheen observed: Y /
Clarifier Effluent Piping / Water Level	~	
Clear-well Chamber and Water Level	/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	V	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 550	JUST RECILLED
Clear-well Transfer Pumps (P-371) / 372)	~	g-strip-
Sludge Transfer Pump (P-330)	/	Exercise Valves Weekly: 60+40-4
Manual Sludge Lateral pumping	V	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	/	Exercise Weekly: Alloc
Automatic Blow-down Operations		7

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	4-21-22- Today	/327 🛧
pH-315 HMR-30 (T-300B)	1	1201
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1405
pH-740 Discharge Surge Tank		Discharge suspended: /320 ← ►/326
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK:

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	_	Caage reading. 2 76
Sludge Holding Tank (T-351)	~	Level:~ 45 %
Sludge Holding Tank (T-352)		Level: 41 %
Decant Transfer Pump (P-352)	1	CV67 % @ o. 5 gpm
Filter Press Pumps (P-381 / P-382)	10	0 1 8 1 70 @ 8,4 9pm
Filter Press	~	Stage: Empty Realy to All

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022		
Inspection Performed by:	Mike Gelwick		

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 43.7psi	CV@ 74 % @ 1.70 gpm
Retention Tank (T-114)	✓ Operating Press: 43 psi	
Bag Filter (BF-113)	Operating Press: 46 psi	0 2, 10
Ion Exchange (Cage Ø or 2) + Guard		98-174A-57P176A/5canisters+GAUND
Post Ion Exchange	Operating Press: 3.5 psi	The second secon

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 22 psi	CV@ 66 % @ 32.2 gpm
T-520 to GAC Total (FT-675)	25962(244 gal	Time: loll
North End On-Site Pumping	Operating Press: 2-3 psi	/2.3 gpm @ (007
North End Off-Site Pumping	Operating Press: 2-6 psi	8.7 gpm @ 6007
Peroxide Feed Pump (P-680)		SPD 2.4 % / RATE 0.7
Peroxide Conc. At (TP-710)	(+O PPM	5.2 2. 7 10112 017
Peroxide Conc. At (TP-740)	O-O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status		Comments
180 Day storage area check		V Emity	Check sheet completed: NA/Eury
Satellite Haz. Waste Areas (BLDG #1)		V	Condition: Ix losin + main Good
Satellite Haz. Waste Area (BLDG #2)		/	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	~	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/LUNATING	Next: NH/ Lummy
Peroxide Feed Pump (P-650)	/	Flow Rate: ~ 7,0 cc/min.
UV-Ox Power	~	26.33 kVA 2 707 Volts 9.7 Amps
Lamp Hours	714 Hrs	The state of the s
Crystal Condition & Wiper Status	with Holden ok Thee who putin	Oiler status: 04
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: \$24-22	9.5 psi In (0.0 psi Out
UV-OX Feed Pump (P-600 or (P-601))	_	CV@ 63 % @ 6.5 gpm
UV-OX Temperature	In(TT-670): /3.6 °C	Out(TT-710): 2 7.3 °C
PDU GAC (PDT-710)	~	Δ Pressure: 2 psi
Peroxide Concentration Pre UV	<i>L∞</i> PPM	
Peroxide Concentration Post UV(TP-720)	20 PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)		CV @ Z %
Secondary Acid Retention Tank (T-645)	~	
Pre – UV Oxidizer Total (FT-670)	21738294 gal	Time: 1012
Post UV-Ox / Pre PDU	~	Pressure: (Z psi
Post PDU	/	Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, April 21, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments		
PDT-720	•	Δ Pressure: / Y psi		
PDT-730		Δ Pressure: 3 psi		

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752)	V	CV@ 53.5 %
Effluent Surge Tank (T-740)	/	Level: 40 %
Effluent Discharge Rate (FT-770)	~	32.3 gpm @ (010
POTW Line Pressure (PT-770)	/	32.1 psi
Effluent Totalizer Reading (FT-770)	253784034 gal	Time: 10/2
POTW MH17S-078 Discharge Check (Monthly)	~	Last Done: 4-14-72
4X8-Inch POTW Leak Detection Checks (Monthly)	V	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done: 2-16-27
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	_	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	~	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	~	Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed: 3-24-27	Plant Effluent Suspended:
		1307 +> 1326
LEL Sensor Bridge Adjustment to 2.0 volts		Adjustment Needed: Y or (A)
Verify Bridge Current between.300v360v	Reading: a 331 volts(monthly)	,

O. WTP INFLUENT TOTALIZERS Time: 1013-1017

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20016291	(FT-505) LFG Cond. to T-530	222201
(FT-025) NBBW Influent	95512298	(FT-056) Off - Site N. End Influent	45315560
(FT-012) MW-38 Inf. to HMR-30	8663827	(FT-113) Ion Exchange Influent	1302145
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30086576
(FT-043) MW-38 to RWST	3123002	(FT-026) NBBW Bypass to RWST	455 9103
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8289213
(FT-012T) MW-38 to T-540/541	8678491	(FT-035) NTES Inf. to BIO	6785741
(FT-040T) MW-38N to T-540/541	1980144	(FT-035T) NTES to T-530	469298
(FT-041T) MW-38S to T-540/541	7698686	(FT-017) BIO Inf. from T-530	665495
(FT-042T) MW-38 Source to T-540/541	4071626	(FT-018) T-540/541 Influent	8722207
(FT-055) On - Site N. End Influent	101296560	(FT-352) T-352 to HMR-30	1370021

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, April 21, 2022

Inspection Date:

Inspection Performed by:		ike Gelwick	
P. AIR COMPRESSORS			
Item	Status	Comments	
Compressor Intake Temp.	70 °F (Analog Gauge)	Outside Temp.: ~ 58 °F	
Compressor Building Vent		open - speraward	
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-22 Serviced @ 62971 Hours	Coolant present in sight glass: Ø / N Next service @ 6497/ Hours Current Hours @ 6388	
IRN30H Motor Speed	31 %	Carrent Flours (@ \$3888	
IRN30H Pressure	(/a psi		
IRN30H Moisture purge valve chk(Weekly):			
IRN30H Intake Filter	/	Date Last Changed: Z~7~ZZ	
Air Tanks Moisture Purge Valves	Manually Activate(weekly) -	Excessive Moisture: Y / 🖎	
Backup Air Compressors (T-30 East and West)	/		
Air Dryer	~ Ecoon	Both cool to touch: 🐠 / N	
Oil Moisture Prevention (Monthly)	Last Done: 4-21-22-70day	Moisture at Réceiver Tank: Y / (AD) Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs	
Air Receiver Tank	~	10 psi	
Q. SUMPS	Status	Comments	
Bag Filter Sump			
Wet Well Sump		-	
R. GAS CHROMATOGRA	PH		
Item	Status	Comments	
GC Operational	/	GC # checking UV-Ox Effluent:	
Alarms Enabled	/	cultivation + main+ 4-20-22	
GC Influent Filters		The state of the s	
S. SAFETY			
Item	Status	Comments	
Building #1 Fire Extinguishers		Date inspected: 4-21-22-75day	
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N	
Other Comments:			

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	~	3,50	65.5%	15.0	
P-3301A	58	_	- %	_	
NTES Pump P-002(Sump) / P-002W(10R)	/	0.50	48 %	P035 P038	Globules Observed at TP-130: Y / (1) Time: 0940
T-530 P-005	/	0.20	41 %	6.5	
T-540/541 P-006		0.30	43 %	7.0	
LFG COND Auto-Traps	-	0.0	NA	50	Between Cycles: Ø / N
Reactor Feed Pumps			- 1		
P-3321	/	2.66	68.6 %	5.0	
P-3322	~	3.65	53.1 %	5.0	
P-3323	58	_	- %	-	
P-3324	~	2.65	38.7 %	5.0	
Reactor Effluent Pumps					
P-3341	/	4.06	73.2%	25.0	
P-3341A	SB	_	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-27
B-3331		4.23	140	6-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	58	_	~	1	Belt and Filter Checked: Y / 🛇
B-3333	-	4.35	142		Greased, Belt and Filter Checked: Ø / N
B-3334	V	4.28	140	↓	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments On-line: 2/10/18	
Vapor Carbon Contactor	V		
Reactor Vent Blower	/		
Reactor Vent Booster			
VTP-3350	V.	PID Reading: \$7,7 PPM	
VTP-3360		PID Reading: 2,7 PPM	

Site unit serviced and worktay ok bow # Used today

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_ Level: 69 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 25 %	
T-530 Mixer	V	
LFG Condensate Conveyance Line	~	Last Pressure Test: \(\)\(\)(1-2) Next: \(7-20^2\) (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 45% & 46%	
T-540/541 Mixers	~	
Chiller	offlme	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	offine	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 73 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	-	Digital Displays: GOOD\/ Needs Attn
T-3332 Reactor No. 2	/	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	~	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	/	3.99 gpm @ 1027
Building Containment Sump	/	Last Alarm Test Date (Monthly): 4-21-27-70-

E. CHEMICAL FEED SYSTEM

Item	Status Comments	
Phosphorous Supply	_	Bags: 10.9 Gallons: ~ 20
Phosphorous Pump (P-2221)	~	gar, a camerio. 70
Caustic Supply	_	~ 275 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	/	~ 40 Gallons
Acid Pump (P-2211)	V	, o omeno
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): 4-21-22-704
Caustic Pump (P-2232)	Leaks: Y /	
Caustic Pump (P-2233)	Leaks: Y /	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022	
Inspection Performed by:	Mike Gelwick	

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	3-24-22	Acril 1645c Clean today
pH-3331 Reactor 1		1
pH-3332 Reactor 2		
pH-3333 Reactor 3	<u> </u>	<u> </u>

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: / 9	ReseT
BF-3340 a/b Differential Pressure	PSI: 5	30/25 24,5 nom
75-micron Bags Last Cleaning	Date: 11-14-19	75723 113 3
75-micron Bags Last Inspection	Date: 1	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: /7.5	7,5/25 24,5 pm
Last Backwash Performed	Date: 3-18-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments
"BIO" Backup Generator			Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	1/		and the state of t
Motor Control Center			
PLC	V		UPS @ / 3/ min / Z Events
HMI's	V		Evento
BTS Process KWH Meter	1879116	KWH	Time: (103
Building#2 KWH Meter	5406293	KWH	Time: //03

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V	GC # checking BIO: # 2
Alarms Enabled	V	Calleration + main + 4-20-22
GC Influent Filters	/	caller work & mark + 1-20 CZ

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 21, 2022		
Inspection Performed by:	Mike Gelwick		

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6602017	
FT-3324 Feed Spare	442177	
FT-3322 Feed to Reactor 2	11585586	
FT-3323 Feed to Reactor 3	192 964317	
FT-3301 T-510 to BIO	52161110	
FT-3341 BIO Effluent	67163102	
FT-3342 BIO Recycle	56580598	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	~	Inspection date: 4-71-22 - 10day
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N

L. OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, April 28, 2022

Inspection Performed by: Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

A. I EKIMETEK GOLLEGITON GTOTEMO			
Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: /2,55 %	Counter: 198680 Cycles: 155	
LFG Cond Automatic Trap CT-2	Sump Level: 8.68 0	Counter: 278760 Cycles: 939	
LFG Cond Automatic Trap CT-3	Sump Level: 7.25 **	Counter: 332 929 Cycles: (05)	
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3.38 Counter: 191297 Cycles: 1 Sump: 8,84	
PM-15 Containment / Vessel	✓ Level: 35 %		
MW-51 Containment / Vessel	✓ Level: 50 %		
PM-11 Containment / Vessel	✓ Level: 45 %	3	
MW-38 Systems	~		
North Toe System	~		
North End Systems (Weekly)	~		
Full N. End Systems Check (Monthly)	_	Last Done: 4-22-22	
North End Pipeline(s)Flushing (As Needed)	Perform if suspended solids present Last Done: 11/15/15		
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21	
NTES Piping Containment	Monthly Sump Level: 000 2/6.07 Date: 4-2/		
North Boundary System P-001:	CV 73.2 % @ 6.2 gpm	40,49 Hz/2.07 Amps. / vault psi @ 18/Nokolas	
T-101 & T-102 Containment / Tank	Levels: 22 % & 20 %		
Raw Water Storage Tanks Piping	_		
RWST Building Temp. (TT-101)	58.2 °F	Outside Temp.: ~ 60 °F	
(P-121) or P-122		2.0 gpm/CV 69 % 50000 will 44444	
RWST 2ndry Cont. High Level Switch	(LSH-101) Last Test(monthly): 4-21-22		
RWST Back-Up Generator		Last Test Run(monthly): 4-21-22	
·			

B. CHEMICAL STORAGE BAYS

Item	Status	Comments	
Caustic Tote Levels		~ 335 Gallons Reserve = 3 75/es	
Caustic Bay Heater			
Peroxide Tote Level	~	~ 275 Gallons Reserve = "5"53~1	
HCL Tote Levels		~ 345 Gallons Reserve = ~394	
Chemical Totes and Piping Inspected	~	Leaks observed: Y / 🖎	
Emergency Shower Inspected	/	Checked and Flushed - All OK: Ø / N	

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	~	
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI: 52-54 CV: 3 %
Primary Acid Retention Tank (T-510)	~	
All Acid Feed Lines	~	Leaks observed: Y / 🕥

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 28, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	~	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow	-	
pH Set-point for (pH 315)	Value: 10, €	
pH 310	Value: 6.92	
pH 315	Value: 10.91	
Flocculation Chamber Paddle Wheel	~	
Precipitate Floc Quality	~	(400)
Clarifier Water Quality	/	Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	/	
Polymer Pump (P-310)		
Polymer Tank Mixer	~	
Polymer Tank Level	Gallons: ~ 460	
Clear-well Transfer Pumps (P-371) / 372)	~	
Sludge Transfer Pump (P-330)	/	Exercise Valves Weekly: 50+4 64
Manual Sludge Lateral pumping	/	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: Allok
Automatic Blow-down Operations	V	•

F. pH PROBES * New 4+10 AH STO Today *

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	4-28-22- Today	1228
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX	•	1258
pH-740 Discharge Surge Tank	√	Discharge suspended: /300 ← 1317
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: V' m

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	~	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	_	
Sludge Holding Tank (T-351)		Level:~ 45 %
Sludge Holding Tank (T-352)	~	Level: 41 %
Decant Transfer Pump (P-352)	_	CV69 % @05 gpm
Filter Press Pumps (P-381 / P-382)	V	
Filter Press	~	Stage: Empty Ready to fill

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 28, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	∠ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press:40.5 psi	CV@ 74 % @ 1.70 gpm
Retention Tank (T-114)	✓ Operating Press: 37,≤psi	pH-113 @ 3.72
Bag Filter (BF-113)	✓ Operating Press: 43 psi	
Ion Exchange (Cage(1) or 2) + Guard	✓ Operating Press: 39 psi	TP-174A-27P-176A/5capisters + GAURD
Post Ion Exchange	✓ Operating Press: 3. 5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 23 psi	CV@ 66 % @ 31.3 gpm
T-520 to GAC Total (FT-675)	259943892 gal	Time: 0952
North End On-Site Pumping	Operating Press: 2-3 psi	12.2 gpm @ 0945
North End Off-Site Pumping	Operating Press: 2-8 psi	8.7 gpm @ 0945
Peroxide Feed Pump (P-680)	~	SPD 2, 4 % / RATE 0.6
Peroxide Conc. At (TP-710)	1.0 PPM	
Peroxide Conc. At (TP-740)	o.o PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	V Empty	Check sheet completed: NA/Emit
Satellite Haz. Waste Areas (BLDG #1)	/	Condition: Dx lesm + main Good
Satellite Haz. Waste Area (BLDG #2)	/	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-/6-21	Next: 9-2022
Quarterly Test Run	Date: NA/Aummy	Next: NH/RUMAMY
Peroxide Feed Pump (P-650)	V	Flow Rate: ~ > cc/min.
UV-Ox Power		26.38 kVA 2711 Volts 9.7 Amps
Lamp Hours	<i>981</i> Hrs	
Crystal Condition & Wiper Status		Oiler status: 🗸
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	psi In (O psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 65 % @ 6.4 gpm
UV-OX Temperature	In(TT-670): 14.3 °C	Out(TT-710): 27.9 °C
PDU GAC (PDT-710)	/	Δ Pressure: 2 psi
Peroxide Concentration Pre UV	(OO PPM	
Peroxide Concentration Post UV(TP-720)	/S PPM	
Peroxide Conc. Post PDU (TP-730)	0.0 PPM	
Secondary Acid Feed Pump (P-630)	_	CV @ 3 %
Secondary Acid Retention Tank (T-645)	V	
Pre – UV Oxidizer Total (FT-670)	2/80/356 gal	Time: 0953
Post UV-Ox / Pre PDU	_	Pressure: /Z psi
Post PDU	~	Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, April 28, 2022

Inspection Performed by:

Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	~	Δ Pressure: /6 psi
PDT-730		Δ Pressure: 2 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	/	CV@ 53.1 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		31.3 gpm @ 0951
POTW Line Pressure (PT-770)		32.1 psi
Effluent Totalizer Reading (FT-770)	254108352 gal	Time: 0953
POTW MH17S-078 Discharge Check (Monthly)	/	Last Done: 4-14-27
4X8-Inch POTW Leak Detection Checks (Monthly)	/	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	/	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	V	Last Done: 2-/6-27
2-Inch POTW Backup Pressure Testing (Annual)	/	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed: 4-28-22	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	7-28-22	1300 ++ (317
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2,001 volts(monthly)	Adjustment Needed: Y or 10
Verify Bridge Current between.300v360v	Reading: volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0956-1093

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20023936	(FT-505) LFG Cond. to T-530	222302
(FT-025) NBBW Influent	95574320	(FT-056) Off - Site N. End Influent	45402932
(FT-012) MW-38 Inf. to HMR-30	868 1191	(FT-113) Ion Exchange Influent	1319230
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30087000
(FT-043) MW-38 to RWST	3123285	(FT-026) NBBW Bypass to RWST	4560184
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8289213
(FT-012T) MW-38 to T-540/541	8683285	(FT-035) NTES Inf. to BIO	6789963
(FT-040T) MW-38N to T-540/541	1980324	(FT-035T) NTES to T-530	469444
(FT-041T) MW-38S to T-540/541	2698701	(FT-017) BIO Inf. from T-530	665982
(FT-042T) MW-38 Source to T-540/541	4076218	(FT-018) T-540/541 Influent	8725011
(FT-055) On - Site N. End Influent	101419578	(FT-352) T-352 to HMR-30	1372186

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, April 28, 2022

Inspection Date:

Inspection P	erformed by: Mi	ke Gelwick
P. AIR COMPRESSORS		
Item	Status	Comments
Compressor Intake Temp.	64 °F (Analog Gauge)	Outside Temp.: ~ 6 2 °F
Compressor Building Vent		open - operational
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-72 Serviced @ 62971 Hours	Coolant present in sight glass: V / N Next service G G4971 Hours
(ITANSOTT)	Services & Living Hours	Current Hours @ 63974
IRN30H Motor Speed	31 %	
IRN30H Pressure	117 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter	/	Date Last Changed: 2-7-27
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / (N)
Backup Air Compressors		
(T-30 East and West)	_	Both cool to touch: (Y) / N
Air Dryer	/ Eco on	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 4-21-27	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		/ 06 psi
Q. SUMPS	Status	Comments
Bag Filter Sump		
Wet Well Sump		
R. GAS CHROMATOGRA	PH	
Item	Status	Comments
GC Operational		GC # checking UV-Ox Effluent: /
Alarms Enabled	/	California amount 4-27-22
GC Influent Filters		
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers		Date inspected: 4-21-27
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N
Other Comments:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 28, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	/	1.29	33.4 %	6.0	
P-3301A	SB	_	- %	-	
NTES Pump P-002(Sump) / P-002W(10R)		0.51	48 %	P035 P038	Globules Observed at TP-130: Y / 1 Time: 0925
T-530 P-005	5B	~	- %	-	
T-540/541 P-006	~	0.20	42 %	6.5	
LFG COND Auto-Traps	-	0.0	NA	5.0	Between Cycles: Ø / N
Reactor Feed Pumps					
P-3321	2.26	2.26	73.3 %	6.5	
P-3322	~	3,15	58.5 %	7.0	
P-3323	5B	_	- %	_	
P-3324	V	2.30	49.2 %	7.0	
Reactor Effluent Pumps					
P-3341		3,22	69.8 %	20.0	
P-3341A	SB	_	- %	_	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331		4.14	138	6-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	SB	_	-		Belt and Filter Checked: Y / N
B-3333		4.28	148		Greased, Belt and Filter Checked: Ø / N
B-3334		4.31	142	V	Greased, Belt and Filter Checked: (Y) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	~	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	~	
VTP-3350	V	PID Reading: 20.5 PPM
VTP-3360	V	PID Reading: 9.1 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 28, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	∠ Level: 72 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	∠ Level: 21 %	
T-530 Mixer	~	
LFG Condensate Conveyance Line		Last Pressure Test: 7-19-21 Next: 7-2927 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 59 % & 59 %	
T-540/541 Mixers	V	
Chiller	offine	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	offlone	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: هد	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 72 %	Last Cleaning (Semi Annual): 7-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD \ Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	V	Digital Displays: GOOD/ Needs Attn
T-3334 Settling Tank	V	Last Cleaning (Semi Annual): 9-10-2
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	~	4.17 gpm @ 1015
Building Containment Sump	/	Last Alarm Test Date (Monthly): 4-21-72

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	~	Bags: 10.8 Gallons: ~ 70
Phosphorous Pump (P-2221)	/	
Caustic Supply	/	~ 270 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	~	
Caustic Pump (P-2231)	Leaks: Y / 0	Last tubing tip cleaning (monthly): 4-21-72
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y / (Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, April 28, 2022
Inspection Performed by: Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	4-28-22- Today	New 4+10 pHSTOS today
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	V	
Automatic Backwash	Cycle Count: 25	KeseT
BF-3340 a/b Differential Pressure	PSI: /	15-/14 22,49Am
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date: 🗸	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: 7	14/7 2 24 span
Last Backwash Performed	Date: 3-18-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments
"BIO" Backup Generator			Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	~		
Motor Control Center	V		
PLC	~		UPS @ /3/ min / 2 Events
HMI's	/		
BTS Process KWH Meter	1031864	KWH	Time: 1100
Building#2 KWH Meter	5411003	KWH	Time: /100

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	~	GC # checking BIO: Z
Alarms Enabled	/	Calledration + maint 4-27-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, April 28, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6625896	
FT-3324 Feed Spare	465887	
FT-3322 Feed to Reactor 2	11613741	
FT-3323 Feed to Reactor 3	964317	
FT-3301 T-510 to BIO	52185822	
FT-3341 BIO Effluent	67196318	
FT-3342 BIO Recycle	56621999	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers		Inspection date: 4-21-22
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: 60 / N

L. OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12,55 00	Counter: 1972/4 Cycles: 20/
LFG Cond Automatic Trap CT-2	Sump Level: 8,63 ac	
LFG Cond Automatic Trap CT-3	Sump Level: 7.40 au	Counter: 324806 Cycles: 0
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3.36 Counter: 14/281 Cycles: 3 Sump: 9,042
PM-15 Containment / Vessel	✓ Level: 82 %	
MW-51 Containment / Vessel	Level: 85 %	
PM-11 Containment / Vessel	✓ Level: 35 %	
MW-38 Systems	~	
North Toe System	/	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)		Last Done: 2-18-27
North End Pipeline(s)Flushing (As Needed)	~	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: 417-216.07 Date: 2-17-22
North Boundary System P-001:	CV73.3 % @6.2 gpm	40. 49 Hz/202 Amps. / vault psi @ 13/100cm
T-101 & T-102 Containment / Tank	~	Levels: 17 % & 16 %
Raw Water Storage Tanks Piping	V	
RWST Building Temp. (TT-101)	54,4 °F	Outside Temp.: ~ 5> °F
(P-121) or P-122	V	Z.3 gpm/CV 74 % sourcemell to Archicument
RWST 2ndry Cont. High Level Switch	~	(LSH-101) Last Test(monthly): Z-27-22
RWST Back-Up Generator	~	Last Test Run(monthly): 2-17-22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 335 Gallons Reserve = / **
Caustic Bay Heater		
Peroxide Tote Level	-	~ 82 Gallons Reserve = ~55
HCL Tote Levels	~	~ 210 Gallons Reserve = ~30
Chemical Totes and Piping Inspected	~	Leaks observed: Y / (1)
Emergency Shower Inspected	~	Checked and Flushed - All OK: V / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 52 CV: 3 %
Primary Acid Retention Tank (T-510)		
All Acid Feed Lines		Leaks observed: Y / 4

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	1	Last Cleaning (Qtrly): (0-20-21
T-300A/B Water Level	~	Last Glodining (Wally). 10-28-21
T-300B (Caustic Mix Chamber)	~	Last Cleaning (Qtrly): (2-20-21
T-300A/B Overflow	~	Last Glodining (Qury). 10 Co. D.
pH Set-point for (pH 315)	Value: (0.8	
pH 310	Value: 6.88	
pH 315	Value: 10.38	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	
Clarifier Water Quality		Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	~	On or sheer observed. 1 / (V)
Clear-well Chamber and Water Level	~	
HMR PLC Panel	~	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)		
Polymer Pump (P-310)		
Polymer Tank Mixer	-	
Polymer Tank Level	Gallons: ~ 500	
Clear-well Transfer Pumps (P-371)/ 372)		
Sludge Transfer Pump (P-330)		Exercise Valves Weekly: & fn ok
Manual Sludge Lateral pumping	v	Last done (As Needed): #/17-3-3-22/#3-7-20-21
Manual Sludge Lateral Ball Valves	V	Exercise Weekly: Allok
Automatic Blow-down Operations	~	Exclose veckly. All 6k

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	3-3-22-Today	1218
pH-315 HMR-30 (T-300B)	1	1610
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1255
pH-740 Discharge Surge Tank	1	Discharge suspended: /2/2 ← → /2/2
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK:

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 6 %
Sludge Thick. Transfer Pump (P-350)		Caage reading. 6 78
Sludge Holding Tank (T-351)	1	Level:~ 45 %
Sludge Holding Tank (T-352)		Level: _30 %
Decant Transfer Pump (P-352)	SA	CV ~ % @ ~ gpm
Filter Press Pumps (P-381 / P-382)	30	gpin
Filter Press	-	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	The state of the s
Feed Pump (P-114)	/ Operating Press: 39.opsi	
Retention Tank (T-114)		
Bag Filter (BF-113)	- Operating Press: 42 psi	
Ion Exchange (Cage (1) or 2) + Guard		TP-1744-5TA-1764/5 contitues + GALAN
Post Ion Exchange	Operating Press: 3.4 psi	The state of the s

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	✓ Level: 39 %	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 15 psi	CV@ 57 % @ 31.7 gpm
T-520 to GAC Total (FT-675)	257392855 gal	Time: 09/2
North End On-Site Pumping	Operating Press: 2-3 psi	/ Z.3 gpm @ 0857
North End Off-Site Pumping	Operating Press: 2-8 psi	9.1 gpm @ 0851
Peroxide Feed Pump (P-680)	V	SPD 2.4 % / RATE O.C.
Peroxide Conc. At (TP-710)	1.0 PPM	O. D. C. T. NOTICALE DIC
Peroxide Conc. At (TP-740)	OIO PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check		Check sheet completed: ye1 - MK4 - 3-3-22 - policy
Satellite Haz. Waste Areas (BLDG #1)		Condition: I x lest n + mum Good
Satellite Haz. Waste Area (BLDG #2)		Condition: Green

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	1	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Aunumy	Next: NH Lummy
Peroxide Feed Pump (P-650)	V	Flow Rate: ~ 2.3 cc/min.
UV-Ox Power	/	25.7 kVA 2562 Volts 103 Amps
Lamp Hours	2921 Hrs	will best this + change out on menday 3.
Crystal Condition & Wiper Status		Oiler status: Ok
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned: 7-13-21	/2.0 psi In /2.0 psi Out
UV-OX Feed Pump (P-600 or (P-601))	-	CV@ 76 % @ 7.0 gpm
UV-OX Temperature	In(TT-670): (2.2 °C	Out(TT-710): 25.6 °C
PDU GAC (PDT-710)		Δ Pressure: မ psi
Peroxide Concentration Pre UV	/co PPM	= 1 recente. 4 psi
Peroxide Concentration Post UV(TP-720)	ZS PPM	
Peroxide Conc. Post PDU (TP-730)	0.0 PPM	
Secondary Acid Feed Pump (P-630)	~	CV @ 3 %
Secondary Acid Retention Tank (T-645)		7.6 7 %
Pre – UV Oxidizer Total (FT-670)	21401344 gal	Time: 0913
Post UV-Ox / Pre PDU		Pressure: 14 psi
Post PDU	/	Pressure: 7.25 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, March 03, 2022
Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments	
PDT-720		Δ Pressure: 8 psi	
PDT-730		Δ Pressure: Z psi	

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 53.4 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		31.7 gpm @ 0911
POTW Line Pressure (PT-770)		32.Z psi
Effluent Totalizer Reading (FT-770)	251546046gal	Time: 09/3
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 2-16-22
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done:
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	7	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	~	Reading: O %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 2-24-22	Plant Effluent Suspended: 1403 ← 1427
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.20 volts(monthly)	Adjustment Needed: Y or (1)
Verify Bridge Current between.300v360v	Reading: >331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 0914-0918

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19860801	(FT-505) LFG Cond. to T-530	221615
(FT-025) NBBW Influent	95755750	(FT-056) Off - Site N. End Influent	44705452
(FT-012) MW-38 Inf. to HMR-30	8579869	(FT-113) Ion Exchange Influent	1180098
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30081234
(FT-043) MW-38 to RWST	3097876	(FT-026) NBBW Bypass to RWST	4474776
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8245931
(FT-012T) MW-38 to T-540/541	8671325	(FT-035) NTES Inf. to BIO	6751171
(FT-040T) MW-38N to T-540/541	1979523	(FT-035T) NTES to T-530	467957
(FT-041T) MW-38S to T-540/541	2697994	(FT-017) BIO Inf. from T-530	663846
(FT-042T) MW-38 Source to T-540/541	4065762	(FT-018) T-540/541 Influent	8711385
(FT-055) On - Site N. End Influent	100433732	(FT-352) T-352 to HMR-30	1346974

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, March 03, 2022

Inspection Date:

Inspection Performed by:		fike Gelwick	
B. AID COMPRESSORS			
P. AIR COMPRESSORS	Status	Comments	
npressor Intake Temp.	7o °F (Analog Gauge)	Outside Temp.: ~ 55 °F	
npressor Building Vent	/ (Finding Cauge)	Open - oferentand	
	2,000 Hour service date: Z-7-27	Coolant present in sight glass: / N	
1997 F. C. B.	Serviced @ 62971 Hours	Next service @ 64971 Hours Current Hours @ 63271	
30H Motor Speed	0 %	6 63217	
30H Pressure	//7 psi		
30H Moisture purge valve chk(Weekly):			
30H Intake Filter		Date Last Changed: 2-7-27	
	Manually Activate(weekly)	Excessive Moisture: Y / 🕦	
kup Air Compressors	manadily montate(moonly)	EXCESSIVE INCIDIAL . 1 7	
0 East and West)		Both cool to touch: 🏠 / N	
Dryer	V Eco on	Moisture at Receiver Tank: Y / 🖎	
	Last Done: 2-24-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs	
Receiver Tank		(10 psi	
	Status	Comments	
Filter Sump			
Well Sump	~		
R. GAS CHROMATOGRAP	PH		
1	Status	Comments	
Operational	~	GC # checking UV-Ox Effluent:	
ms Enabled		(c-calibration + many - 3-2-22	
Influent Filters	V.		
S. SAFETY			
	Status	Comments	
ding #1 Fire Extinguishers		Date inspected: 2-21-22-August	
		Checked and Flushed- All OK: 4	
S. SAFETY ding #1 Fire Extinguishers ding #1 Eye Wash/Shower r Comments:	Status Status Le keress #1+#2 today -3-3	Date inspected: 2-21-22-4 Checked and Flushed- All OK:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps	e inner rent un nenen			V	The state of the s
P-3301	/	1.31	ZB.5 %	6.5	10 10 44 P (48 1)
P-3301A	5 B		- %		
NTES Pump P-002(Sump) / P-002W(10R)	~	0.52	49 %	P035 P038	Globules Observed at TP-130: Y / (1) Time: 0830
T -530 P-005	136	_	- %	-	THUL 222%
T-540/541 P-006	-	0.20	41 %	7.5-80	14100-20
LFG COND Auto-Traps		0,0	NA	5.0	Between Cycles: (Y) / N
Reactor Feed Pumps					
P-3321		2.16	60,0%	8.5	The control towards and the property and account of the control towards and th
P-3322	/	3.10	4019%	510	
P-3323	56		- %	-	
P-3324	/	2,10	44.8 %	6.0	
Reactor Effluent Pumps					
P-3341		2.87	51.7 %	16.5	The state of the s
P-3341A	58	-	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 12-30-21
B-3331	/	4.20	138	3-2022-5000	Greased, Belt and Filter Checked: Ø / N
B-3332	5B	-			Belt and Filter Checked: Y / (N)
B-3333		4.23	132		Greased, Belt and Filter Checked: Ø / N
B-3334	/	4,20	130	V	Greased, Belt and Filter Checked: / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	~	On-line: 2/10/18
Reactor Vent Blower	~	
Reactor Vent Booster		
VTP-3350	V	PID Reading: 31.6 PPM
VTP-3360	/	PID Reading: 22.6 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	/ Level: 70 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: Z2 %	Currently on SB
T-530 Mixer	V	
LFG Condensate Conveyance Line	V	Last Pressure Test: 7-(9-2) Next: 7-2027 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 74% & 74%	currently knowing secure well worth
T-540/541 Mixers	V	Constitution of Branch Constitution
Chiller	offlme	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	Offlore	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: Ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	/	Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	_/	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	/	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 940 -21
P-3334 Biosolids Pump		
T-3340 Overflow Tank	✓ Level: 31 %	
Recycle Valve to Blend Tank	1	4.00 gpm @ 1005
Building Containment Sump	/	Last Alarm Test Date (Monthly): 2-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply		Bags: 12.25 Gallons: ~ 20
Phosphorous Pump (P-2221)		70
Caustic Supply	V	~ /OO Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	/	~ 40 Gallons
Acid Pump (P-2211)	/	
Caustic Pump (P-2231)	Leaks: Y	Last tubing tip cleaning (monthly): 2-17-22
Caustic Pump (P-2232)	Leaks: Y	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	2-24-22	Spray of Cleur today
pH-3331 Reactor 1		1
pH-3332 Reactor 2		
pH-3333 Reactor 3	4	1/

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	~	Comments
Automatic Backwash	Cycle Count: 22	Reset
BF-3340 a/b Differential Pressure	PSI: /	12/11 21.9,00
75-micron Bags Last Cleaning	Date: //-/4-19	12/(1 11/13/2000
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date:	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: C	11/6 = 1.9gm
Last Backwash Performed	Date: /-26-22	11/ 6 11/1gpm

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments	
"BIO" Backup Generator	/	Block Heater: On OK / Off Warm Out)	
Electrical Surge Suppressor	V	C. Flam Gg.	
Motor Control Center	~		
PLC	V	UPS@/3/ min/ O Events	
HMI's	V	Events	
BTS Process KWH Meter	1855883 KWH	Time: (057	
Building#2 KWH Meter	5359541 KWH	Time: (057)	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational		GC # checking BIO: 42
Alarms Enabled	/	CC-cultbratton + metry, -3-2-22
GC Influent Filters	~	CC CARTE THAT TO SE

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 03, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6406062	
FT-3324 Feed Spare	247319	
FT-3322 Feed to Reactor 2	11313276	
FT-3323 Feed to Reactor 3	964310	
FT-3301 T-510 to BIO	51883469	
FT-3341 BIO Effluent	66838780	
FT-3342 BIO Recycle	56289225	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers		Inspection date: 2-21-22- Annual
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N

OTHER COMMENTS:		
	10	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

SISIENIS	
Status	Comments
Sump Level: 12.92 04	Counter: 197570 Cycles: 306
Sump Level: 8.66 04	Counter: 2759/6 Cycles: O
Sump Level: 7.31 64	Counter: 325044 Cycles: 238
✓ Level: 30 %	Tank Level: 3,3c Counter: 191282 Cycles: 1 Sump: 9,116
∠ Level: 85 %	Currently classed or Frozen. Gruy to Amor THIS weekend
✓ Level: 40 %	
✓ Level: 60 %	
_	
	Last Done: 2-18-22
	Perform if suspended solids present Last Done: 11/15/15
	Perform if suspended solids present Last Done: 10/29/21
	Monthly Sump Level: 07-216-07' Date: 2-17-22
CV 730% @ 6.2 gpm	40.27 Hz / 2.06 Amps. / vault psi @18/wolcows
	Levels: 34 % & 33 %
52.9 °F	Outside Temp.: ~ / ムー °F
<u></u>	0.60 gpm/CV 5~2 %
~	(LSH-101) Last Test(monthly): 2-/7-22
/	Last Test Run(monthly): 2-17-27
	Status Sump Level: 12.92 04 Sump Level: 8.66 04 Sump Level: 7.31 04 - Level: 30 % - Level: 85 % - Level: 40 % - Level: 60 % CV 730% @ 6.2 gpm

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~ 525 Gallons Reserve = 3 70 ccs
Caustic Bay Heater	/	
Peroxide Tote Level	/	~ 75 Gallons Reserve = ~ 55, 1 +1
HCL Tote Levels	/	~ 170 Gallons Reserve = ~30
Chemical Totes and Piping Inspected		Leaks observed: Y / (N)
Emergency Shower Inspected	/	Checked and Flushed - All OK: / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI: 52-56 CV: 3 %
Primary Acid Retention Tank (T-510)	/	
All Acid Feed Lines	/	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)		Last Cleaning (Qtrly): /0-20-2/
T-300A/B Water Level	V	7/1
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): LO-20-21
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.82	
pH 315	Value: 10.87	
Flocculation Chamber Paddle Wheel		
Precipitate Floc Quality		
Clarifier Water Quality	/	Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	/	
HMR PLC Panel		
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)	~	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 425	
Clear-well Transfer Pumps (P-371)/ 372)		
Sludge Transfer Pump (P-330)		Exercise Valves Weekly: Soth 54
Manual Sludge Lateral pumping	~	* Last done (As Needed): DAMy currently / Clogging I 550
Manual Sludge Lateral Ball Valves	V	Exercise Weekly: Allor
Automatic Blow-down Operations		

pH Probe Location	Calibration Date	Comments: (Time done)	
pH-310 HMR-30 (T-300A)	3-10-22-10day	1314	
pH-315 HMR-30 (T-300B)	K		
pH-365 Primary Acid Ret. Tank			
pH-113 Pre-Ion Exchange		1340	
pH-670 Pre-UV-OX	UV-0x off LINC/ NO cultirum	1	
pH-740 Discharge Surge Tank	3-10-22-10Any	Discharge suspended: /305 ← >/3/3	
Out of Hold Double Check		None in hold:	
Valves Back to Normal Position		All OK: VI'd am	

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

ltem	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: Ø %
Sludge Thick. Transfer Pump (P-350)	~	
Sludge Holding Tank (T-351)		Level:~ 65 %
Sludge Holding Tank (T-352)	_	Level: 58 %
Decant Transfer Pump (P-352)		CV 64 % @ 0.5 gpm
Filter Press Pumps (P-381 / P-382)		
Filter Press	/	Stage: 4 currently Running on T-351

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 39.7 psi	CV@ 71 % @ 1.76 gpm
Retention Tank (T-114)	✓ Operating Press: 38,5 psi	pH-113 @ 3,57
Bag Filter (BF-113)	✓ Operating Press: 41.5 psi	
Ion Exchange (Cage 1) or 2) + Guard	✓ Operating Press: 38 psi	7P+74A->7P-176A/5 cunsters + GALLED
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 37 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: /9 ps	si CV@ 62 % @ 31,3 gpm
T-520 to GAC Total (FT-675)	257707280 g	al Time: (03/
North End On-Site Pumping	Operating Press: 2-3 ps	si /2.2 gpm @ 1029
North End Off-Site Pumping	Operating Press: 2-8 ps	8.9 gpm @ 1029
Peroxide Feed Pump (P-680)		SPD 2.4 % / RATE 0.6
Peroxide Conc. At (TP-710)	10 PPM	
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE*Lective Affrord For steam GACTO 90 days From MANTA Foster/CDPHE * 3-10-22

90 Item

Status

Comments

Check sheet completed: yes -3-10-22-man-invent

Satellite Haz. Waste Areas (BLDG #1)

Satellite Haz. Waste Area (BLDG #2)

Condition: Grand

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	offlive/ALCIOSURS -3	-7-22
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: —	Next: —
Peroxide Feed Pump (P-650)	_	Flow Rate: ~ - cc/min.
UV-Ox Power	_	— kVA ─ Volts ─ Amps
Lamp Hours	O Hrs	New Lamp mostaled 3-7-22 - UV-ox off
Crystal Condition & Wiper Status	_	Oiler status: 🏕
UV-OX Bagfilters Status	Last change: 7-13-71 Cleaned: 7-13-71	psi In _ psi Out
UV-OX Feed Pump (P-600 or P-601)		CV@ - % @ - gpm
UV-OX Temperature	In(TT-670): - °C	Out(TT-710): - °C
PDU GAC (PDT-710)	4	Δ Pressure: — psi
Peroxide Concentration Pre UV	- PPM	
Peroxide Concentration Post UV(TP-720)	- PPM	
Peroxide Conc. Post PDU (TP-730)	PPM	
Secondary Acid Feed Pump (P-630)		CV@ - %
Secondary Acid Retention Tank (T-645)		
Pre - UV Oxidizer Total (FT-670)	21439568 gal	Time: (031
Post UV-Ox / Pre PDU	_	Pressure: - psi
Post PDU	-	Pressure: _ psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022	
Inspection Performed by:	Mike Gelwick	

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720		Δ Pressure: // psi
PDT-730		Δ Pressure: & psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 52.9 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		31.0 gpm @ 1030
POTW Line Pressure (PT-770)		31.9 psi
Effluent Totalizer Reading (FT-770)	251861650 gal	Time: 632
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 2-/6-27
4X8-Inch POTW Leak Detection Checks (Monthly)	~	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	/	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)		Last Done:
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	_	Reading: O %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 2 -24 - 22	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2,501 volts(monthly)	Adjustment Needed: Y or 1
Verify Bridge Current between.300v360v	Reading: a 331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 1032-1036

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19874790	(FT-505) LFG Cond. to T-530	221746
(FT-025) NBBW Influent	95206718	(FT-056) Off - Site N. End Influent	44793836
(FT-012) MW-38 Inf. to HMR-30	8594810	(FT-113) Ion Exchange Influent	1197941
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30082204
(FT-043) MW-38 to RWST	3099727	(FT-026) NBBW Bypass to RWST	4487191
(FT-042 RWST) MW-38 Source to RWST	72736	(FT-014) Misc. Water to RWST	8252108
(FT-012T) MW-38 to T-540/541	8672314	(FT-035) NTES Inf. to BIO	6756094
(FT-040T) MW-38N to T-540/541	(979829	(FT-035T) NTES to T-530	468207
(FT-041T) MW-38S to T-540/541	2698388	(FT-017) BIO Inf. from T-530	663846
(FT-042T) MW-38 Source to T-540/541	4066047	(FT-018) T-540/541 Influent	8713411
(FT-055) On - Site N. End Influent	100558309	(FT-352) T-352 to HMR-30	1349908

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Performed by: Mike Gelwick

Thursday, March 10, 2022

Inspection Date:

Table 3.19.1 Rev 7 WTP.docx

tem	Status	Comments
Compressor Intake Temp.	45 °F (Analog Gauge)	Outside Temp.: ~ (5 °F
Compressor Building Vent		Closed - a Assayand
Primary Air Compressor	2,000 Hour service date: 2-7-22	Coolant present in sight glass: / N
(IRN30H)	Serviced @ 62971 Hours	Next service @ 64971 Hours
		Current Hours @ 63359
IRN30H Motor Speed	31 %	
IRN30H Pressure	1(5 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter		Date Last Changed: 2~7~22
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / 🖅
Backup Air Compressors		
(T-30 East and West)	~	Both cool to touch: Ø / N
Air Dryer	V	Moisture at Receiver Tank: Y / 🐿
Oil Moisture Prevention (Monthly)	Last Done: 2-24-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	~	110 psi
Q. SUMPS Item	Status	Comments
Bag Filter Sump	✓	
Wet Well Sump		
R. GAS CHROMATOGRA		
Item	Status ON SB UV-OX OFFI	
GC Operational		GC # checking UV-Ox Effluent:
Alarms Enabled	_	
GC Influent Filters		
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers	_	Date inspected: Z-ZI-ZZ-Annual
	New 3-7-22* V	Checked and Flushed- All OK: ()
Other Comments:		
2-7-17-11	82	1.
3-1-26- New UV-OK Lamp	DISTAILED. UV-OX PLC ISSUES. A	wothernarms New Studge Lateral propry
		be thansfel fump/New SAFetys Hower 2
	laterals DATLY corrently Due to	
HALLSO JOOGE		
		Dalays Acr BAUT FOSTEr From COPHE

Tables - 115

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps		o the desirence of			
P-3301	/	9.85	53.3 %	10.0	
P-3301A	54		- %	-	
NTES Pump P-002(Sump) / P-002W(10R)	~	0.54	49 %	P035 P038	Globules Observed at TP-130: Y / N Time: 0935
T-530 P-005	56	_	- %	-	1,113
T-540/541 P-006	SB	-	- %	_	
LFG COND Auto-Traps	v	0.0	NA	5.0	Between Cycles: Ø / N
Reactor Feed Pumps					
P-3321	-	4.71	57,6 %	4.5	* New Malog Prosurgange 3-4-22 *
P-3322	~	6.55	48.6 %	510	The state of the s
P-3323	56	-	- %	-	
P-3324	~	4.70	39.3 %	5.0	# House Bauley Possion Garage \$ 304-23
Reactor Effluent Pumps	Andrew Comment				
P-3341	~	69.79	72.2 %	14.0	
P-3341A	SB	_	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: /2-30-2/
B-3331	~	4.33	116	3-2027-500N	Greased, Belt and Filter Checked: () / N
B-3332	5B	_	-	1	Belt and Filter Checked: Y / (N)
B-3333	v	4.38	114		Greased, Belt and Filter Checked: () / N
B-3334	V	4,27	108	1	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor		On-line: 2/10/18
Reactor Vent Blower		
Reactor Vent Booster	_	
VTP-3350	-	PID Reading: 44,1 PPM wen AEDLAMP
VTP-3360	-	PID Reading: 31.2 PPM THIS ONE GETTING
SANCE SANCE	31	an a sensor

murgenstone to

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_ Level: 69 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 27 %	'ccoverthy on SB
T-530 Mixer	v	
LFG Condensate Conveyance Line		Last Pressure Test: 7-19-21 Next: 7-6227 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 68 % & 69 %	
T-540/541 Mixers	~	
Chiller	offline	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	outstime	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	<u>_</u>	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	-	Last Back Flushing (Quarterly): マーヌーママ
T-3310 Sedimentation Tank	Visual Level:	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 72 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD\/ Needs Attn
T-3332 Reactor No. 2	-	Digital Displays: GOOD V Needs Attn
T-3333 Reactor No. 3	1	Digital Displays: GOOD// Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 7-10-21
P-3334 Biosolids Pump	~	
T-3340 Overflow Tank	✓ Level: 28 %	3 .1-
Recycle Valve to Blend Tank		3.83 gpm @ 1054
Building Containment Sump	-	Last Alarm Test Date (Monthly): さいつって

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	~	Bags: 12 Gallons: ~75
Phosphorous Pump (P-2221)	V	
Caustic Supply	/	~ 75 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V	~ 40 Gallons
Acid Pump (P-2211)	/	
Caustic Pump (P-2231)	Leaks: Y /	D Last tubing tip cleaning (monthly): とー/フーとて
Caustic Pump (P-2232)	Leaks: Y /	♠ Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	✓ Leaks: Y /	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	2-24-22	5 Pray off Clean today
pH-3331 Reactor 1	1	
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 139	RESET. BACKARATING MORE ONC to Hoyen Flows
BF-3340 a/b Differential Pressure	PSI: 8	17/9 2 9.90 M
75-micron Bags Last Cleaning	Date: /1-14-19	
75-micron Bags Last Inspection	Date:	,
75-micron Bags Last Changed	Date:	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 3	20/17 39,950
Last Backwash Performed	Date: 3~8-22	* humany Hogher Flows + And 573. will read Move Evenum Buckwarthing &
	UN-OX OFF LINE 3-7-22	More Frequent weekwasting &

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator		Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	/	
Motor Control Center	~	
PLC	~	UPS@/3/ min/ O Events
HMI's	V	
BTS Process KWH Meter	1859445 KWH	Time: //47
Building#2 KWH Meter	5367952 KWH	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	~	GC # checking BIO: #Z
Alarms Enabled	V	CC-covarumen + Metry - 3-9-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 10, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6434550	
FT-3324 Feed Spare	275666	
FT-3322 Feed to Reactor 2	11352832	
FT-3323 Feed to Reactor 3	964313	
FT-3301 T-510 to BIO	51925770	
FT-3341 BIO Effluent	66887176	
FT-3342 BIO Recycle	56331195	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	V	Inspection date: Z-21-22-Annual
Building #2 Eye Wash/Shower	<u></u>	Checked and Flushed- All OK: (Y) / N

L. OTHER COMMENTS:

-7-22-UV-OK OFFLINE ALC ISSUES. START RUNNING HOSPET Flows + ATU 675.	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022	
Inspection Performed by:	Mike Gelwick	

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: (2.77 #	Counter: 197714 Cycles: (94
LFG Cond Automatic Trap CT-2	Sump Level: 8.64	Counter: 275990 Cycles: 79
LFG Cond Automatic Trap CT-3	Sump Level: 7,40 🕰	Counter: 325 429 Cycles: 385
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3.38 Counter: 191291 Cycles: 9 Sump: 9.05
PM-15 Containment / Vessel	✓ Level: 20 %	
MW-51 Containment / Vessel	✓ Level: 35 %	
PM-11 Containment / Vessel	✓ Level: 40 %	
MW-38 Systems		
North Toe System	/	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)	_	Last Done: 2-/8-27
North End Pipeline(s)Flushing (As Needed)		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	(FORWATS).	Monthly Sump Level: 012 /607 Date: 3-17-22-7
North Boundary System P-001:	CV70.8 % @ 6.2 gpm	38.52 Hz / 2.02 Amps. / vault psi @ 18/20leans
T-101 & T-102 Containment / Tank	_	Levels: 63 % & 61 %
Raw Water Storage Tanks Piping		
RWST Building Temp. (TT-101)	56.7 °F	Outside Temp.: ~ 3/ °F
(P-121) or P-122	-	6.0 gpm/CV 71 %
RWST 2ndry Cont. High Level Switch		(LSH-101) Last Test(monthly): 3-17-22 - reday
RWST Back-Up Generator	/	Last Test Run(monthly): 3~17-22 - Today

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 540 Gallons Reserve = 480 + 1 +04
Caustic Bay Heater	/	
Peroxide Tote Level	/	~ 305 Gallons Reserve =130541
HCL Tote Levels	/	~ 165 Gallons Reserve = ~30301
Chemical Totes and Piping Inspected	V	Leaks observed: Y / 🗭
Emergency Shower Inspected	V	Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	~	
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 52-56 CV: _> %
Primary Acid Retention Tank (T-510)	/	
All Acid Feed Lines	-	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments	
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18	
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.	
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, March 17, 2022	
Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	/	Last Cleaning (Qtrly): /0-20-2/
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)		Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	~	
pH Set-point for (pH 315)	Value: (0.8	
pH 310	Value: 6.89	
pH 315	Value: (0.96	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	1	6004
Clarifier Water Quality	15/44/5	Oil or sheen observed: Y / 🕦
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level		
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)		
Polymer Tank Mixer		
Polymer Tank Level	Gallons: ~ 540	
Clear-well Transfer Pumps (P-37) / 372)	/	
Sludge Transfer Pump (P-330)	V	Exercise Valves Weekly: Act ac
Manual Sludge Lateral pumping	~	Last done (As Needed): 3-15-22 All Laterity
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: Allox
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	3-17-22-TDA	my 1424 +
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange	1	1455
pH-670 Pre-UV-OX	NO cateranin - UV-04	
pH-740 Discharge Surge Tank	3-17-22-100	Discharge suspended: /4/7 ← ► /42
Out of Hold Double Check		None in hold: ,,,,,,,
Valves Back to Normal Position		None in hold: // All OK: // /

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	~	
Sludge Holding Tank (T-351)	~	Level:~ 45 %
Sludge Holding Tank (T-352)		Level: 54 %
Decant Transfer Pump (P-352)	~	CV 73 % @ 0.8 gpm
Filter Press Pumps (P-381 / P-382)	~	
Filter Press		Stage: Emply/webswastat

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: ५०.opsi	CV@ 70 % @ 1.74 gpm
Retention Tank (T-114)	Operating Press: 37 psi	pH-113 @ 3.89
Bag Filter (BF-113)	✓ Operating Press: 43 psi	<u> </u>
Ion Exchange (Cage (f) or 2) + Guard	✓ Operating Press: 39 psi	TP-1744->TP-176 N 5 cunisters + Gard
Post Ion Exchange	✓ Operating Press: 7.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 3	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522))	Operating Press: 17 psi	CV@ 60 % @ 29.0 gpm
T-520 to GAC Total (FT-675)	258003772 gal	Time: (030
North End On-Site Pumping	Operating Press: 7-3 psi	/2.2 gpm @ (019
North End Off-Site Pumping	Operating Press: 7-6 psi	9.2 gpm @ 1d8
Peroxide Feed Pump (P-680)	~	SPD 2.2 % / RATE 0:6
Peroxide Conc. At (TP-710)	PPM د.ا	
Peroxide Conc. At (TP-740)	O-O PPM	

J. HAZARDOUS WASTE STORAGE & Received Extension to godays For Spent GAC per DAVIS FOSTER/COPHE -3-10-22 *

	Item	Status	Comments
7	180 Day storage area check	_	Check sheet completed: Ves-me4-Total
	Satellite Haz. Waste Areas (BLDG #1)	_	Condition: Ix lesin + man Good
	Satellite Haz. Waste Area (BLDG #2)		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	offline - ALC tosues /3-7-22	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: -	Next: —
Peroxide Feed Pump (P-650)	_	Flow Rate: ~ - cc/min.
UV-Ox Power	_	- kVA - Volts - Amps
Lamp Hours	O Hrs	NEW LAWS ON 3-7-27
Crystal Condition & Wiper Status	-	Oiler status: ok
UV-OX Bagfilters Status	Last change: 7-13-21 Cleaned:7-13-21	- psi In - psi Out
UV-OX Feed Pump (P-600 or P-601)		CV@ — % @ gpm
UV-OX Temperature	In(TT-670): — °C	Out(TT-710): - °C
PDU GAC (PDT-710)	_	Δ Pressure: — psi
Peroxide Concentration Pre UV	— PPM	1 (22 (2012) 2011)
Peroxide Concentration Post UV(TP-720)	- PPM	
Peroxide Conc. Post PDU (TP-730)	— PPM	
Secondary Acid Feed Pump (P-630)	-	CV @ - %
Secondary Acid Retention Tank (T-645)	_	
Pre – UV Oxidizer Total (FT-670)	21439568 gal	Time: (030
Post UV-Ox / Pre PDU	_	Pressure: - psi
Post PDU	-	Pressure: – psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022
Inspection Performed by:	Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	V	Δ Pressure: // psi
PDT-730		Δ Pressure: Z psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	_	CV@ 52.7 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)	_	29.7 gpm @ 1028
POTW Line Pressure (PT-770)	~	31.7 psi
Effluent Totalizer Reading (FT-770)	252159450 gal	Time: 1031
POTW MH17S-078 Discharge Check (Monthly)	/	Last Done: 2-16-22
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	_	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status		Comments
LEL-740 Sensor	~		Reading: O %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed	1: Z-24-22	Plant Effluent Suspended: (403 ←→ 1427
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001	volts(monthly)	Adjustment Needed: Y or 🗗
Verify Bridge Current between 300v360v	Reading: 0.331	volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1032-1036

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19893305	(FT-505) LFG Cond. to T-530	221833
(FT-025) NBBW Influent	95247702	(FT-056) Off - Site N. End Influent	44880684
(FT-012) MW-38 Inf. to HMR-30	8596665	(FT-113) Ion Exchange Influent	1215488
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30083204
(FT-043) MW-38 to RWST	3113184	(FT-026) NBBW Bypass to RWST	4508625
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8262141
(FT-012T) MW-38 to T-540/541	8672314	(FT-035) NTES Inf. to BIO	6761069
(FT-040T) MW-38N to T-540/541	1979829	(FT-035T) NTES to T-530	468389
(FT-041T) MW-38S to T-540/541	269 8389	(FT-017) BIO Inf. from T-530	663846
(FT-042T) MW-38 Source to T-540/541	4066047	(FT-018) T-540/541 Influent	8713411
(FT-055) On - Site N. End Influent	100680435	(FT-352) T-352 to HMR-30	1355826

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, March 17, 2022

Inspection Date:

Inspection F	ike Gelwick		
P. AIR COMPRESSORS			
Item	Status	Comments	
Compressor Intake Temp.	50 °F (Analog Gauge)	Outside Temp.: ~ 3 2 °F	
Compressor Building Vent	y indica suage)	Closed - Operational	
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-27 Serviced @ 6297! Hours	Coolant present in sight glass: Ø / N Next service @ 6497/ Hours Current Hours @ 63450	
IRN30H Motor Speed	31 %		
IRN30H Pressure	/2/ psi		
IRN30H Moisture purge valve chk(Weekly):	701 poi		
IRN30H Intake Filter		Date Last Changed: 2~7~27	
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / D	
Backup Air Compressors	Walidally Activate(weekly)		
(T-30 East and West)		Both cool to touch: 4 / N	
Air Dryer		Moisture at Receiver Tank: Y / 🕪	
Oil Moisture Prevention (Monthly)	Last Done: 2-24-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs	
Air Receiver Tank	V	/IO psi	
Q. SUMPS	8		
Item	Status	Comments	
Bag Filter Sump	~		
Wet Well Sump	V		
R. GAS CHROMATOGRA	PH		
Item	Status ONSB-UV-OK OFFCIME	Comments	
GC Operational	-	GC # checking UV-Qx Effluent:	
Alarms Enabled		cc calibration and maint 3-23-2	
GC Influent Filters	-	CC Company of Maril 3 23	
S. SAFETY			
Item	Status	Comments	
Building #1 Fire Extinguishers	~	Date inspected: 2-21-72- Annual	
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: (Y) / N	
Other Comments:	LC FJques		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022		
Inspection Performed by:	Mike Gelwick		

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Dischar Pressu (psi)	ıre	Comments
T-510 Pumps						
P-3301	~	7.50	52.3%	10.0		
P-3301A	25		- %	-		
NTES Pump P-002(Sump) / P-002W(10R)	~	0.51	49 %		038 4.5	Globules Observed at TP-130: Y / N Time: 0930
T-530 P-005	56	_	- %	-		
T-540/541 P-006	55	-	- %	-		
LFG COND Auto-Traps	/	0.0	NA	5.0		Between Cycles: Ø / N
Reactor Feed Pumps						
P-3321	/	3,99	64.1 %	515	-	
P-3322	~	5.51	51.4%	6.0		
P-3323	SB		- %	-		
P-3324	V	3.91	44.1 %	7.0		
Reactor Effluent Pumps						
P-3341	•	8.64	82.1 %	20.0	28.0	
P-3341A	38		- %	~		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331	/	4.29	122	6-2022	Greased, Belt and Filter Checked: 6 / N
B-3332	56	-		1	Belt and Filter Checked: Ø / N
B-3333	~	4.41	124		Greased, Belt and Filter Checked: Ø / N
B-3334		4.23	116	1	Greased, Belt and Filter Checked:

C. REACTOR VENTILATION

Item	Status	Comments		
Vapor Carbon Contactor	/	On-line: 2/10/18		
Reactor Vent Blower	1			
Reactor Vent Booster	/	-		
VTP-3350	/	PID Reading: 34.6 PPM		
VTP-3360		PID Reading: 25.6 PPM		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022	
Inspection Performed by:	Mike Gelwick	

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	∠ Level: 71 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	∠Level: 33 %	3.00
T-530 Mixer		
LFG Condensate Conveyance Line	~	Last Pressure Test: 7-19-21 Next: 7-2-22 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls:69 % & 70%	
T-540/541 Mixers	1	
Chiller	offline	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	offine	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	_	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 2-3~27
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 70 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	V	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 32 %	
Recycle Valve to Blend Tank	~	4.09 gpm @ /(0/
Building Containment Sump	~	Last Alarm Test Date (Monthly): 3-17-22-70-44

E. CHEMICAL FEED SYSTEM

Item	Status	Comments	
Phosphorous Supply	/	Bags: [1, 9 Gallons: ~ 70	
Phosphorous Pump (P-2221)	~	•	
Caustic Supply	~ 60 Gallons		
Caustic Pump (P-2211)	SB	Currently in acid addition mode	
Acid Supply	_	~ 40 Gallons	
Acid Pump (P-2211)	/		
Caustic Pump (P-2231)	Leaks: Y / 0	Last tubing tip cleaning (monthly): 3-17-22-754	
Caustic Pump (P-2232)	Leaks: Y / (Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / (Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly) Comments		
pH-3320 Blend Tank	2-24-22	Acrd/BASE Cleaning today	
pH-3331 Reactor 1	1		
pH-3332 Reactor 2			
pH-3333 Reactor 3	→	V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 187	LegeT
BF-3340 a/b Differential Pressure	PSI: /9	78/9 28.91m
75-micron Bags Last Cleaning	Date: 11-14-19	9
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date: 🗸	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 6 "	34/28 08.9 pm
Last Backwash Performed	Date: 3822 3-18-22	-

H. ELECTRICAL AND INSTRUMENTATION

Item	Status Comments		
"BIO" Backup Generator	✓	Block Heater On OK) / Off Warm Ou	
Electrical Surge Suppressor	V		
Motor Control Center			
PLC	V	UPS @ /3/ min/ / Events	
HMI's	~		
BTS Process KWH Meter	1863665 KWH	Time: /224	
Building#2 KWH Meter	5375989 KWH	Time: /224	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #2
Alarms Enabled	V	CC-California + majort 3-16-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 17, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6471278	
FT-3324 Feed Spare	3 2239	
FT-3322 Feed to Reactor 2	11403918	
FT-3323 Feed to Reactor 3	964313	
FT-3301 T-510 to BIO	51995483	
FT-3341 BIO Effluent	66962278	
FT-3342 BIO Recycle	56372611	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers		Inspection date: 2-21-22-Annual
Building #2 Eye Wash/Shower	~	Checked and Flushed- All OK: (2) / N

L.	OTHER COMMENTS:		
		 200 USB	
	*		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, March 24, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1		Counter: 197899 Cycles: 185
LFG Cond Automatic Trap CT-2		Counter: 2 76/14 Cycles: 124
LFG Cond Automatic Trap CT-3	Sump Level: 7.25 04	Counter: 326135 Cycles: 706
CT-4 Containment/Vessel (LFG Cond)	∠ Level: 30 %	Tank Level: 3.38 Counter: 191292 Cycles: 1 Sump: 8,94
PM-15 Containment / Vessel	✓ Level: 23 %	
MW-51 Containment / Vessel	✓ Level: 25 %	
PM-11 Containment / Vessel	/ Level: 15 %	
MW-38 Systems	/	
North Toe System	/	
North End Systems (Weekly)	~	
Full N. End Systems Check (Monthly)	-	Last Done: 2-19-22
North End Pipeline(s)Flushing (As Needed)	1	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	V.	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	✓	Monthly Sump Level: D(y @ 16,07 Date: 3-17-22
North Boundary System P-001:	CV 3.6 % @ 6.2 gpm	41.13 Hz /2.07 Amps. / vault psi @ 18/ No lacks
T-101 & T-102 Containment / Tank	1	Levels: 35 % & 34 %
Raw Water Storage Tanks Piping	7	
RWST Building Temp. (TT-101)	54,8 °F	Outside Temp.: ~ 50 °F
(P-12) or P-122		6.0 gpm/CV 97_ %
RWST 2ndry Cont. High Level Switch	1,	(LSH-101) Last Test(monthly): 3-17-22
RWST Back-Up Generator		Last Test Run(monthly): 3-17-22

B. CHEMICAL STORAGE BAYS

Item	Status ,	Comments
Caustic Tote Levels	√ ,	~ 440 Gallons Reserve = 480 -1 total
Caustic Bay Heater	√,	operational
Peroxide Tote Level	-	~302 Gallons Reserve = 130 gallons
HCL Tote Levels	1,	~ 155 Gallons Reserve = 30 gallons
Chemical Totes and Piping Inspected		Leaks observed: Y / (N)
Emergency Shower Inspected		Checked and Flushed - All OK: (Y) / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	V	
Ion Exchange Acid Feed Pump (P-632)	V,	PI-0632 PSI: 55-60 CV: 3 %
Primary Acid Retention Tank (T-510)	1	
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, March 24, 2022
Inspection Performed by: Mike Gelwick / Tom Gilbert

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	1,	Last Cleaning (Qtrly): 10-20-21
T-300A/B Water Level		
T-300B (Caustic Mix Chamber)	1	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.65	
pH 315	Value: , 10,92	
Flocculation Chamber Paddle Wheel	~,	
Precipitate Floc Quality	, <i>J</i>	Good
Clarifier Water Quality	V Slightly cloudy	Oil or sheen observed: Y / N
Clarifier Effluent Piping / Water Level	1, ,	
Clear-well Chamber and Water Level	√ ,	
HMR PLC Panel	✓	
Caustic Pump (P-270)	SB,	
Caustic Pump (P-280)	√ ,	
Polymer Pump (P-310)	✓	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ \$50	
Clear-well Transfer Pumps(P-371 / 372)	1,	
Sludge Transfer Pump (P-330)	\ ,	Exercise Valves Weekly: Bak OK
Manual Sludge Lateral pumping	-	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	1	Exercise Weekly: A\\ OK \
Automatic Blow-down Operations	✓	- ·

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)	
pH-310 HMR-30 (T-300A)	3-24-22-10day	123/1300	
pH-315 HMR-30 (T-300B)			
pH-365 Primary Acid Ret. Tank			
pH-113 Pre-Ion Exchange			
pH-670 Pre-UV-OX		→1306	
pH-740 Discharge Surge Tank	V	Discharge suspended: /3○7 ←►1374	
Out of Hold Double Check		None in hold:	
Valves Back to Normal Position	[All OK: V'd	

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS & Great THICKENER, SUDGE HOLDING TANKS, FILTER PRESS

Item	Status	/	Comments
Verify Sludge Thickener Running	√	/	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	/		
Sludge Holding Tank (T-351)		//	Level:~ 식O %
Sludge Holding Tank (T-352)		//	Level: 53 %
Decant Transfer Pump (P-352)		,	CV67 % @ 0,5 gpm
Filter Press Pumps (P-381 / P-382)	/		
Filter Press	√		Stage: Clean - Ready for USE

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, March 24, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	√/ Operating Press:3%,2 psi	CV@ 69 % @ 1.73 gpm
Retention Tank (T-114)	√ Operating Press: 38 psi	рН-113 @ 3.6 Ч
Bag Filter (BF-113)	√ Operating Press: ↓ psi	
Ion Exchange (Cage 1)or 2) + Guard	√ Operating Press: 38 psi	TPITYA-TPITEA 5 constas + guard
Post Ion Exchange	√ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status		Comments
Feed Surge Tank (T-520)	/ Level: 38	%	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: Z (psi	CV@ 66 % @ 36.8 gpm
T-520 to GAC Total (FT-675)	258307972	gal	Time: 1004
North End On-Site Pumping	Operating Press: 2-3	psi	12-2 gpm @ 1005
North End Off-Site Pumping	Operating Press: 2-8	psi	8.7 gpm @ 1005
Peroxide Feed Pump (P-680)	✓		SPD 2.3 % / RATE 0.7 40M
Peroxide Conc. At (TP-710)	1-0 PF	PM	J.
Peroxide Conc. At (TP-740)	0.0 PF	PM	

J. HAZARDOUS WASTE STORAGE * lecented as Extention to 90 days per pluid footer/copte on 3-10-22 for shour 6 40

Item_	Status	Comments
180 Day storage area check	√ .	Check sheet completed: VS -TR' + toba
Satellite Haz. Waste Areas (BLDG #1)	V/	Condition: Ix Rosin + Main Good
Satellite Haz. Waste Area (BLDG #2)	V	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	Nesmath 3-22/23-22	NewPLC + HMI Screen
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date:	Next:
Peroxide Feed Pump (P-650)	V ,	Flow Rate: ~ \$7.0 cc/min.
UV-Ox Power		28,41 kVA 2837 Volts 10.0 Amps
Lamp Hours	48 Hrs	
Crystal Condition & Wiper Status	√ operational	Oiler status: 🗸
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	10 psi In 10 psi Out
UV-OX Feed Pump (P-600 or (P-601))	√	CV@ 69 % @ 9.\ gpm
UV-OX Temperature	In(TT-670): 12.3 °C	Out(TT-710): 22,5 °C
PDU GAC (PDT-710)	1	Δ Pressure: 2. psi
Peroxide Concentration Pre UV	√, 90 PPM	
Peroxide Concentration Post UV(TP-720)	J/ Ø PPM	
Peroxide Conc. Post PDU (TP-730)	√ , 00 PPM	
Secondary Acid Feed Pump (P-630)	7.	CV @ 3 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	21462022 gal	Time: @ 10;22
Post UV-Ox / Pre PDU		Pressure: 12 psi
Post PDU	✓ ·	Pressure: 6 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, March 24, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	1	Δ Pressure: 12 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 55.6 %
Effluent Surge Tank (T-740)	√.	Level: 40 %
Effluent Discharge Rate (FT-770)	√ 36.5	32.7 gpm @ 1040
POTW Line Pressure (PT-770)	-	32.7 psi
Effluent Totalizer Reading (FT-770)	252466344 gal	Time:
POTW MH17S-078 Discharge Check (Monthly)	~	Last Done: 3-23-27
4X8-Inch POTW Leak Detection Checks (Monthly)		Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	-	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	_	Last Done: Z-16-2 2
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	~	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 3-24-22	Plant Effluent Suspended: 1307 ←►13 26
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.00 volts(monthly)	Adjustment Needed: Y or (1)
Verify Bridge Current between.300v360v	Reading: 0.331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1041

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19951587	(FT-505) LFG Cond. to T-530	221888
(FT-025) NBBW Influent	95266121	(FT-056) Off - Site N. End Influent	44967664
(FT-012) MW-38 Inf. to HMR-30	8601220	(FT-113) Ion Exchange Influent	1233040
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30083964
(FT-043) MW-38 to RWST	3121457	(FT-026) NBBW Bypass to RWST	4553208
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8262141
(FT-012T) MW-38 to T-540/541	8672314	(FT-035) NTES Inf. to BIO	6765984
(FT-040T) MW-38N to T-540/541	1979829	(FT-035T) NTES to T-530	468541
(FT-041T) MW-38S to T-540/541	2698389	(FT-017) BIO Inf. from T-530	663846
(FT-042T) MW-38 Source to T-540/541	4066047	(FT-018) T-540/541 Influent	8713411
(FT-055) On - Site N. End Influent	100803383	(FT-352) T-352 to HMR-30	1359957

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, March 24, 2022

Inspection Date:

tatus	Comments
61 °F (Analog Gauge)	Outside Temp.: ~ 45 °F
	open-operational
000 Hour service date: 2-7-22	Coolant present in sight glass: Y / N
erviced @ 6297i Hours	Next service @ 6497 i Hours Current Hours @ 63537
31 %	
/	Date Last Changed: 2-7-22
lanually Activate(weekly)	Excessive Moisture: Y / (N)
,	
✓	Both cool to touch: / N
√	Moisture at Receiver Tank: Y / (N)
ast Done: 3-24-22-744	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
✓	110 psi
tatus	Comments
1	
itatus	GC # checking UV-Ox Effluent: #1
	CO # Cricolling CV OX Emiconic
	CC- Cultures + major 3-23-22
Status	Comments 3-24-22-Takey
V/	Date inspected: 2-21-22 Annual
—	Checked and Flushed- All OK: (4) / N
	ast Done: 3-24-22-7044 tatus

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, March 24, 2022

Inspection Performed by:

Mike Gelwick / Tom Gilbert

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	/	6.0	42 %	8	
P-3301A	SB		- %		
NTES Pump P-002(Sump) / (P-002W(10R))	J	0.48	48 %	P035 P038 34-35 4.5	Globules Observed at TP-130: Y / (1) Time: 0930
T-530 P-005	5B		- %		
T-540/541 P-006	513		%		- 3
LFG COND Auto-Traps	1	0.0	NA	5	Between Cycles: (Y) / N
Reactor Feed Pumps		3.15			A CONTRACTOR OF THE PROPERTY O
P-3321		2.791	58.4 %	4,5	
P-3322	\	4.27	50.9 %	6.0	
P-3323	SB		- %	-	
P-3324	1	3.29	42,6%	6.5	
Reactor Effluent Pumps					
P-3341	\ \	4.1	14 %	14	
P-3341A	SB	-	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331		4,24	130	6-2022	Greased, Belt and Filter Checked: () / N
B-3332	SB				Belt and Filter Checked: Y / N
B-3333	J	4,33	135	5/	Greased, Belt and Filter Checked: (V) / N
B-3334	J	4.15	125	V	Greased, Belt and Filter Checked: (Y) / N

C. REACTOR VENTILATION

Item	Staţús	Comments
Vapor Carbon Contactor	1/	On-line: 2/10/18
Reactor Vent Blower	V/	
Reactor Vent Booster	√	
VTP-3350	√,	PID Reading: 35.29 PPM was came
VTP-3360		PID Reading: 29.8 PPM order

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 24, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	√ Level: 67 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	√ Level: 35 %	
T-530 Mixer	/	
LFG Condensate Conveyance Line		Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls:69 % &70%	
T-540/541 Mixers	✓	
Chiller	offline	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	offine	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	1	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: 0K	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: %	Last Cleaning (Semi Annual): 9 -10 -21
T-3331 Reactor No. 1	1	Digital Displays: QOOD/ Needs Attn
T-3332 Reactor No. 2	1	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	√	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	1	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump		
T-3340 Overflow Tank	Level: 30 %	
Recycle Valve to Blend Tank	√ ,	4.23 gpm @ 1240
Building Containment Sump		Last Alarm Test Date (Monthly): 3-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply		Bags: \\.5 Gallons: ~ 75
Phosphorous Pump (P-2221)	V/	
Caustic Supply	/	~ 55 Gallons
Caustic Pump (P-2211)	\$B __	Currently in acid addition mode
Acid Supply	1,	~ 40 Gallons
Acid Pump (P-2211)	, 1	
Caustic Pump (P-2231)	√ Leaks: Y	Last tubing tip cleaning (monthly): 3-17-22
Caustic Pump (P-2232)	Leaks: Y	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y	/ (N) Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, March 24, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments		
pH-3320 Blend Tank	3-24-22-10day	New 4 and 10 PH STDS today		
pH-3331 Reactor 1				
pH-3332 Reactor 2				
pH-3333 Reactor 3	•	V		

G. FILTER SYSTEM

Item	Status /	Comments
BF-3340 a/b Status	✓	
Automatic Backwash	Cycle Count: 128	Reset to 8
BF-3340 a/b Differential Pressure	PSI: 6	9/15 @ 5.4 GPM
75-micron Bags Last Cleaning	Date: 11-14-19	•
75-micron Bags Last Inspection	Date: 1/	
75-micron Bags Last Changed	Date: V	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: 2	97 C 5.4 GPM
Last Backwash Performed	Date: 3-18-22	1269et 10 0 ~

H. ELECTRICAL AND INSTRUMENTATION

Item	Status				Comm		
"BIO" Backup Generator	1		Block H	eater:	On OK	COff	Warm Out
Electrical Surge Suppressor	1						
Motor Control Center	\						
PLC	\' ,		UPS @	131	min /	\	Events
HMI's	/		_				
BTS Process KWH Meter	●18678	25 KWH	Time:	1233	5		
Building#2 KWH Meter	1 5384045		Time:	123	3		

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational		GC # checking BIO: ₩2
Alarms Enabled	~	CC-CALBRAGON & MAINT 3-23-22
GC Influent Filters	-	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 24, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6506204	
FT-3324 Feed Spare	347010	
FT-3322 Feed to Reactor 2	11452460	
FT-3323 Feed to Reactor 3	964313	
FT-3301 T-510 to BIO	52059637	
FT-3341 BIO Effluent	67031547	
FT-3342 BIO Recycle	56414607	

K. SAFETY

Item	Status	Comments	3-24-22-12	mery.
Building #2 Fire Extinguishers	1	Inspection date:	2-21-22 200	mat-
Building #2 Eye Wash/Shower	/	Checked and Flu	shed- All OK: (Y) / N

L. OTHER COMMENTS:		_	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

A. PENIMETER COLLECTION	SISILINIS	
Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12,55 ac	Counter: (98013 Cycles: 144
LFG Cond Automatic Trap CT-2		Counter: 276296 Cycles: 182
LFG Cond Automatic Trap CT-3	Sump Level: 7,26 de	Counter: 327286 Cycles: 1151
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 32 %	Tank Level: 3.36 Counter: 191294 Cycles: 2 Sump: 8.929
PM-15 Containment / Vessel	∠ Level: 24 %	
MW-51 Containment / Vessel	✓ Level: 45 %	
PM-11 Containment / Vessel	✓ Level: 38 %	
MW-38 Systems	/	
North Toe System	~	
North End Systems (Weekly)	-	
Full N. End Systems Check (Monthly)	-	Last Done: 3-25-22
North End Pipeline(s)Flushing (As Needed)	_	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: Dry 216.07 Date: 3-17-22
North Boundary System P-001:	CV 73.1 % @6.2 gpm	41,32 Hz/2,07 Amps. / vault psi @ 18/00 leaks
T-101 & T-102 Containment / Tank	~	Levels: 32 % & 30 %
Raw Water Storage Tanks Piping	_	
RWST Building Temp. (TT-101)	53.9 °F	Outside Temp.: ~ 30 °F
(P-121) or P-122	<u> </u>	0.6 gpm/CV 54 %
RWST 2ndry Cont. High Level Switch	_	(LSH-101) Last Test(monthly): 3-17-22
RWST Back-Up Generator	V	Last Test Run(monthly): 3-17-22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 325 Gallons Reserve = 180 21 tote
Caustic Bay Heater		
Peroxide Tote Level		~ 287 Gallons Reserve = 130 gal
HCL Tote Levels	-	~145 Gallons Reserve = ~30
Chemical Totes and Piping Inspected	· ·	Leaks observed: Y / 1
Emergency Shower Inspected	V	Checked and Flushed - All OK: 6 / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	/	PI-0632 PSI34-5C CV: 3 %
Primary Acid Retention Tank (T-510)	/	
All Acid Feed Lines	/	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	/	Last Cleaning (Qtrly): 10-20-21
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 10-20-21
T-300A/B Overflow	V	
pH Set-point for (pH 315)	Value: /0.8	
pH 310	Value: 637	No. 2000
pH 315	Value: 10.89	1 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	Good
Clarifier Water Quality		Stigeth clause Oil or sheen observed: Y / 🗗
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	~	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~ 480	
Clear-well Transfer Pumps (P-371)/ 372)	/	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 40+404
Manual Sludge Lateral pumping	/	Last done (As Needed): 3-/5-22
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: Allow
Automatic Blow-down Operations	V	

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	3-31-22-10day	1210
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1245
pH-740 Discharge Surge Tank		Discharge suspended: (136 ←> /145
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: V'

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running		Gauge Reading: O %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)	-	Level:~ 45 %
Sludge Holding Tank (T-352)	_	Level: 40 %
Decant Transfer Pump (P-352)	54	CV - % @ - gpm
Filter Press Pumps (P-381 / P-382)		
Filter Press		Stage: EMP +y/Kerdy & All

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 40.7 psi	CV@ 70 % @ 1.72 gpm
Retention Tank (T-114)	Operating Press: 40 psi	pH-113 @ 3.87
Bag Filter (BF-113)	✓ Operating Press: 43 psi	
Ion Exchange (Cage(Dor 2) + Guard	✓ Operating Press: • 9 psi	TP-174A->TP-176A/5cuntsters + GANNA
Post Ion Exchange	✓ Operating Press: 3.≼ psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	✓ Level: 38 %	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522)	Operating Press: /8 psi	CV@ 61 % @ 31,5 gpm
T-520 to GAC Total (FT-675)	2586572∞ gal	Time: 0732
North End On-Site Pumping	Operating Press: 2-3 psi	12.2 gpm @ 0837
North End Off-Site Pumping	Operating Press: 2-8 psi	8.3 gpm @ 0837
Peroxide Feed Pump (P-680)		SPD 2.4 % / RATE 0.6
Peroxide Conc. At (TP-710)	1.0 PPM	
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE X RECEIVED an EXTENSION to godays Per DAVID FOSTER/COPHE FOR SEWA WAR. 3-10/20

	Item_	Status	Comments
90	180 Day storage area check	/	Check sheet completed: yes - mk 4-70-4-
	Satellite Haz. Waste Areas (BLDG #1)	~	Condition: Excessor + man Good
	Satellite Haz. Waste Area (BLDG #2)	~	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	~	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Running	Next: NA/RUMNING
Peroxide Feed Pump (P-650)	-	Flow Rate: ~ 2,0 cc/min.
UV-Ox Power	~	26,46 kVA 2708 Volts 9.8 Amps
Lamp Hours	2/2 Hrs	
Crystal Condition & Wiper Status		Oiler status: ok
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	/2 psi In /2 psi Out
UV-OX Feed Pump (P-600 or (2-601))		CV@ 75 % @ 7.1 gpm
UV-OX Temperature	In(TT-670): /3.8 °C	Out(TT-710): 26.8 °C
PDU GAC (PDT-710)		Δ Pressure:
Peroxide Concentration Pre UV	/ 95 PPM	
Peroxide Concentration Post UV(TP-720)	∠ 20 PPM	
Peroxide Conc. Post PDU (TP-730)	✓ 0.0 PPM	
Secondary Acid Feed Pump (P-630)	~	CV @ 2 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	21543500 gal	Time: 0733
Post UV-Ox / Pre PDU		Pressure: 14 psi
Post PDU	_	Pressure: 7,5 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022	
Inspection Performed by:	Mike Gelwick	

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

ltem	Status	Comments	
PDT-720		Δ Pressure: /C) psi
PDT-730		Δ Pressure: 3	psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 55,6 %
Effluent Surge Tank (T-740)	_	Level: 48 %
Effluent Discharge Rate (FT-770)		35.9 gpm @ 0724
POTW Line Pressure (PT-770)		33.z psi
Effluent Totalizer Reading (FT-770)	2528/5690 gal	Time: 0733
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 3-23-22
4X8-Inch POTW Leak Detection Checks (Monthly)	V	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	-	Last Done: 2-16-22
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	_	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	-	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	V	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 3-24-22	Plant Effluent Suspended: /307 ←→ /326
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or 🕪
Verify Bridge Current between.300v360v	Reading: o. 331 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0734 -0738

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	19995192	(FT-505) LFG Cond. to T-530	159155
(FT-025) NBBW Influent	95326391	(FT-056) Off - Site N. End Influent	45052136
(FT-012) MW-38 Inf. to HMR-30	8617687	(FT-113) Ion Exchange Influent	1250161
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30084460
(FT-043) MW-38 to RWST	3121820	(FT-026) NBBW Bypass to RWST	4554666
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8272755
(FT-012T) MW-38 to T-540/541	8672314	(FT-035) NTES Inf. to BIO	6770729
(FT-040T) MW-38N to T-540/541	1979829	(FT-035T) NTES to T-530	468684
(FT-041T) MW-38S to T-540/541	2698389	(FT-017) BIO Inf. from T-530	663927
(FT-042T) MW-38 Source to T-540/541	4066047	(FT-018) T-540/541 Influent	8713715
(FT-055) On - Site N. End Influent	100924173	(FT-352) T-352 to HMR-30	1363278

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, March 31, 2022

Inspection Date:

Primary Air Compressor	Status	Comments
Compressor Building Vent Primary Air Compressor	58 °F (Analog Gauge)	Outside Temp.: ~ 35 °F
Primary Air Compressor	~	open/openarious
	2,000 Hour service date: Z-7-77	Coolant present in sight glass: \(\varphi\) / N
(IRN30H)	Serviced @ 6297/ Hours	Next service @ 64971 Hours Current Hours @ 63628
IRN30H Motor Speed	31%	
IRN30H Pressure	(16 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter		Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly) -	Excessive Moisture: Y / N
Backup Air Compressors		
(T-30 East and West)		Both cool to touch: Ø / N
Air Dryer		Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 3-24-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	3 0 . 0 0	108 psi
Q. SUMPS	Status	Comments
Q. SUMPS		
Item	Status	Comments
Item Bag Filter Sump	Status	Comments
Item Bag Filter Sump		Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA	PH	
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item		Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational	PH	
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	PH	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA	PH	Comments GC # checking UV-Ox Effluent: #/
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	PH	Comments GC # checking UV-Ox Effluent: #/
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	PH	Comments GC # checking UV-Ox Effluent: #/
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	PH Status	Comments GC # checking UV-Ox Effluent: #/ cc-californian + matrix 3-50-22

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps			acada in cum de la base. An Medical Carlo de persona	i Literatura	
P-3301		1.77	46.4%	9.0	
P-3301A	5.B	-	- %	=	
NTES Pump P-002(Sump) / (P-002W(10R))	/	0.51	49 %	P035 P038	Globules Observed at TP-130: Y / 100 Time: 08/5
T-530 P-005	/	0:19	41 %	7.0	
T-540/541 P-006		0.31	42%	7.0	
LFG COND Auto-Traps	~	0.0	NA	5	Between Cycles: Ø / N
Reactor Feed Pumps					The product of the second of t
P-3321	~	2,30	58,3 %	4.0	
P-3322	/	3,12	56.2 %	6.0	
P-3323	5B	-	- %		
P-3324	1	15.5	390 %	5.5	
Reactor Effluent Pumps	in Cover of Section	Company of the Compan			
P-3341	~	2.60	5z.7 %	12.0	
P-3341A	58	~	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331		4.27	130	6-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	SB	_	: 		Belt and Filter Checked: Y / 🔊
B-3333	~	4.38	130		Greased, Belt and Filter Checked: 60 / N
B-3334	/	4.19	122	1	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	/	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	~	LAMA
VTP-3350	V	PID Reading: 38.6 PPM PTD 01d and
VTP-3360		PID Reading: 38.6 PPM over suspersion

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	Level: 63 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 37 %	4.0000
T-530 Mixer	V	
LFG Condensate Conveyance Line	v	Last Pressure Test: 7-/9-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 67% &67 %	
T-540/541 Mixers	~	
Chiller	Off Line	Chiller Coolant Lvl: ~ - " Below full mark
Chiller Cooling Fins (as needed)	offline	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments		Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 2-3-22
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 73 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1		Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD V Needs Attn
T-3333 Reactor No. 3		Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	-	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	~	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank		3.98 gpm @ 0850
Building Containment Sump		Last Alarm Test Date (Monthly): 3-17-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	~	Bags: /1.25 Gallons: ~ 85
Phosphorous Pump (P-2221)		
Caustic Supply	~	~ 45 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	_	~ 40 Gallons
Acid Pump (P-2211)	-	
Caustic Pump (P-2231)	Leaks: Y / 🛈	Last tubing tip cleaning (monthly): 3-/7-22
Caustic Pump (P-2232)	Leaks: Y / 🛈	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y / W	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments Spray off Clean forders	
pH-3320 Blend Tank	3-24-22		
pH-3331 Reactor 1			
pH-3332 Reactor 2			
pH-3333 Reactor 3	V	V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	-	
Automatic Backwash	Cycle Count: 65	LeseT
BF-3340 a/b Differential Pressure	PSI: 6	8/8 21.5gpm
75-micron Bags Last Cleaning	Date: //-/4-/9	
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date: V	-
GACF-3340 Status		8/7215500
GACF-3340 Differential Pressure	PSI: (8/7.21.5,000
Last Backwash Performed	Date: 3-18-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	V	Block Heater: On OK / Off Warm Out)
Electrical Surge Suppressor		
Motor Control Center		
PLC	/	UPS @ /3 / min / [Events
HMI's	/	
BTS Process KWH Meter	1871066 KWH	Time: 0943
Building#2 KWH Meter	5389839 KWH	Time: 0943

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #2
Alarms Enabled	~	CC- Cultbraken + major - 3-30-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, March 31, 2022	
Inspection Performed by:	Mike Gelwick	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6534152	
FT-3324 Feed Spare	374795	
FT-3322 Feed to Reactor 2	11491304	
FT-3323 Feed to Reactor 3	964313	
FT-3301 T-510 to BIO	52100497	
FT-3341 BIO Effluent	67077888	
FT-3342 BIO Recycle	56454759	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	~	Inspection date: 3-24-22
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (/ N

L. OTHER COMMENTS:	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: /2,5500	Counter: 199644 Cycles: 964
LFG Cond Automatic Trap CT-2	Sump Level: 8.660	Counter: 279480 Cycles: 720
LFG Cond Automatic Trap CT-3	Sump Level: 7,2200	Counter: 3337/5 Cycles: 786
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 3 ° %	Tank Level: 3.38 Counter: /91297 Cycles: O Sump: 8.83
PM-15 Containment / Vessel	✓ Level: 38 %	
MW-51 Containment / Vessel	✓ Level: Հ⊃ %	
PM-11 Containment / Vessel	∠ Level: 18 %	
MW-38 Systems	_	
North Toe System	~	
North End Systems (Weekly)		
Full N. End Systems Check (Monthly)		Last Done: 4-22-27
North End Pipeline(s)Flushing (As Needed)	V	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: ハマントロー Date: 4-71-22
North Boundary System P-001:	CV72.9 % @ 6.3 gpm	40.21 Hz/2.06 Amps. / vault psi @ 18/20 links
T-101 & T-102 Containment / Tank	_	Levels: 15 % & M %
Raw Water Storage Tanks Piping	V	
RWST Building Temp. (TT-101)	57.1 °F	Outside Temp.: ~ 55 °F
(P-121) or P-122	~5B	- gpm/CV - % TANKS Low/Gurpo Park
RWST 2ndry Cont. High Level Switch	_	(LSH-101) Last Test(monthly): Y-z/-zz
RWST Back-Up Generator	-	Last Test Run(monthly): 4-21-72

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ I/O Gallons Reserve = 2+ojes
Caustic Bay Heater	/	
Peroxide Tote Level		~ 267 Gallons Reserve = ~55 quel
HCL Tote Levels	~	~310 Gallons Reserve = ~30ged
Chemical Totes and Piping Inspected	V	Leaks observed: Y / 🐿
Emergency Shower Inspected		Checked and Flushed - All OK: V / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments	
Primary Acid Feed Pump (P-631)			
Ion Exchange Acid Feed Pump (P-632)	~	PI-0632 PSI: 52-54 CV: 3	%
Primary Acid Retention Tank (T-510)	/		
All Acid Feed Lines	-	Leaks observed: Y / (N)	

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	V	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	V	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6 79	
pH 315	Value: 10.96	
Flocculation Chamber Paddle Wheel		
Precipitate Floc Quality	/	
Clarifier Water Quality	/	Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level	/	
Clear-well Chamber and Water Level	/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	/	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	V	
Polymer Tank Level	Gallons: ~ 380	
Clear-well Transfer Pumps (P-371) 372)	~	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 60th 66
Manual Sludge Lateral pumping	V	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	V	Exercise Weekly: Allou
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)	
pH-310 HMR-30 (T-300A)	5-5-27- reiley	1352	
pH-315 HMR-30 (T-300B)	1		
pH-365 Primary Acid Ret. Tank			
pH-113 Pre-Ion Exchange			
pH-670 Pre-UV-OX		→ 1425	
pH-740 Discharge Surge Tank	Discharge suspended:/ 34		
Out of Hold Double Check		None in hold:	
Valves Back to Normal Position		All OK: VV	

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	~	Gauge Reading: 6 %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)	~	Level:~ 45 %
Sludge Holding Tank (T-352)	/	Level: 40 %
Decant Transfer Pump (P-352)	~	CV 69 % @ 0.5 gpm
Filter Press Pumps (P-381 / P-382)	~	
Filter Press	/	Stage: Emsty/Kenty to All.

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: ५२,६ psi	CV@ 79 % @ (.68 gpm
Retention Tank (T-114)	✓ Operating Press: 47 psi	pH-113 @ 3.69
Bag Filter (BF-113)	✓ Operating Press: 50 psi	
Ion Exchange (Cage 4 or 2) + Guard	✓ Operating Press: 46.5 psi	TP-174A ->TP-176A/5 charsters + GALING
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status		Comments
Feed Surge Tank (T-520)			Last Cleaning (As Needed, if 4" of
	✓ Level: 38	%	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522))	Operating Press: 2 (psi	CV@ 64 % @ 31.1 gpm
T-520 to GAC Total (FT-675)	260266719	gal	Time: 1038
North End On-Site Pumping	Operating Press: 2-3	psi	/2.Z gpm @ /033
North End Off-Site Pumping	Operating Press: 2-6	psi	8.7 gpm @ 1033
Peroxide Feed Pump (P-680)	~		SPD 2.3 % / RATE 0.6
Peroxide Conc. At (TP-710)	1.0 PF	M	
Peroxide Conc. At (TP-740)	ON PF	M	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	1 Empha	Check sheet completed: NA Empty
Satellite Haz. Waste Areas (BLDG #1)	/	Condition: Txtes, n + mun Good
Satellite Haz. Waste Area (BLDG #2)		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NUKummy	Next: NH/Running
Peroxide Feed Pump (P-650)	~	Flow Rate: ~ 7.0 cc/min.
UV-Ox Power	_	26.57 kVA 2714 Volts 9.8 Amps
Lamp Hours	1050 Hrs	
Crystal Condition & Wiper Status	_	Oiler status: OK/Ketilled
UV-OX Bagfilters Status	Last change: 3-24-72 ^{Cleaned} : 3-24-27	10.0psi In 10.0 psi Out
UV-OX Feed Pump (P-600 or (P-601))	~	CV@ 65 % @ 6.4 gpm
UV-OX Temperature	In(TT-670): /4,(°C	Out(TT-710): 2フ.7 °C
PDU GAC (PDT-710)	~	Δ Pressure: 2 psi
Peroxide Concentration Pre UV	joo PPM	
Peroxide Concentration Post UV(TP-720)	zO PPM	
Peroxide Conc. Post PDU (TP-730)	O.J PPM	
Secondary Acid Feed Pump (P-630)	~	CV @ 3 %
Secondary Acid Retention Tank (T-645)	V	
Pre – UV Oxidizer Total (FT-670)	2/864772 gal	Time: 1039
Post UV-Ox / Pre PDU	·	Pressure: /Z psi
Post PDU		Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, May 05, 2022
Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720		Δ Pressure: /3 psi
PDT-730	V	Δ Pressure: 2 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments	
Effluent Surge Pump (P751 or (P752))	V	CV@ 53.1 %	
Effluent Surge Tank (T-740)	~	Level: 40 %	
Effluent Discharge Rate (FT-770)	-	31.3 gpm @ /037	
POTW Line Pressure (PT-770)	~	31,9 psi	
Effluent Totalizer Reading (FT-770)	2 54432940 gal	Time: 1039	
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: 4-14-22	
4X8-Inch POTW Leak Detection Checks (Monthly)	~	Last Done:	
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:	
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	V	Last Done: 2-/6-27	
2-Inch POTW Backup Pressure Testing (Annual)	/	Last Done: 7/8/21	
2-In POTW Backup Air Reliefs Checks (Annual)	/	Last Done: 7/8/21	
2-Inch POTW Isolation Valve Exercise (Annual)	~	Last Done: 7/8/21	
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2	

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	~	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed:	Plant Effluent Suspended: (3∞ ←→ /3/7
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: z.∞i volts(monthly)	Adjustment Needed: Y or (N)
Verify Bridge Current between.300v360v	Reading: 0.330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 1040-1044

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	70028118	(FT-505) LFG Cond. to T-530	222654
(FT-025) NBBW Influent	95636298	(FT-056) Off - Site N. End Influent	45491332
(FT-012) MW-38 Inf. to HMR-30	8700330	(FT-113) Ion Exchange Influent	1336424
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30087808
(FT-043) MW-38 to RWST	3123759	(FT-026) NBBW Bypass to RWST	4561713
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8289213
(FT-012T) MW-38 to T-540/541	8683745	(FT-035) NTES Inf. to BIO	6794672
(FT-040T) MW-38N to T-540/541	1980552	(FT-035T) NTES to T-530	469685
(FT-041T) MW-38S to T-540/541	2698950	(FT-017) BIO Inf. from T-530	666039
(FT-042T) MW-38 Source to T-540/541	4076218	(FT-018) T-540/541 Influent	8727820
(FT-055) On - Site N. End Influent	101542815	(FT-352) T-352 to HMR-30	1374652

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, May 05, 2022

Inspection Date:

Inspection P	erformed by: Mi	Mike Gelwick		
P. AIR COMPRESSORS	Status	Comments		
Compressor Intake Temp.		Comments Outside Temp.: ~ 60 °F		
Compressor Building Vent	50 °F (Analog Gauge)	Outside Temp.: ~ 60 °F		
Primary Air Compressor	2,000 Hour service date: 2-7-72	Coolant present in sight glass: Ø / N		
(IRN30H)	Serviced @ 62971 Hours	Next service @ 64971 Hours Current Hours @ 64055		
IRN30H Motor Speed	38 %	Carron 10010 (6) 6 (102 2		
IRN30H Pressure	//5 psi			
IRN30H Moisture purge valve chk(Weekly):	112 501			
IRN30H Intake Filter		Date Last Changed: 2-7-27		
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / 🐿		
Backup Air Compressors (T-30 East and West)	manually rollvate(veekly)	Both cool to touch: Ø / N		
Air Dryer	1 Eco on	Moisture at Receiver Tank: Y / 🚱		
Oil Moisture Prevention (Monthly)	Last Done: 4-21-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs		
Air Receiver Tank	_	(10 psi		
Q. SUMPS Item	Status	Comments		
Bag Filter Sump	_	- Commonto		
Wet Well Sump				
R. GAS CHROMATOGRA	PH			
Item	Status	Comments		
GC Operational	V	GC # checking UV-Ox Effluent: 4		
Alarms Enabled	/	Calibration + major 5-4-22		
GC Influent Filters				
S. SAFETY				
Item	Status	Comments		
Building #1 Fire Extinguishers	~	Date inspected: 4-21-77		
Building #1 Eye Wash/Shower	/	Checked and Flushed- All OK: (V) / N		
Other Comments:				

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Pres	narge sure si)	Comments
T-510 Pumps				Line I in		
P-3301	1	1,20	31.3%	6.	5	
P-3301A	56	-	- %	_		20
NTES Pump P-002(Sump) / (P-002W(10R))	-	0.49	48 %	P035	P038	Globules Observed at TP-130: Y / 1 Time: 1005
T-530 P-005	ŚB		- %	_		
T-540/541 P-006	/	0.30	65 %	10.	5	
LFG COND Auto-Traps	~	0.0	NA	5.0	0	Between Cycles: Ø / N
Reactor Feed Pumps						
P-3321	-	2,66	50.1 %	5.5	5	
P-3322	1	3.68	49.4 %	5.0)	
P-3323	56	_	- %	_		
P-3324	~	2,65	35.5 %	50	Ð.	
Reactor Effluent Pumps						
P-3341	/	3.23	52.5 %	14.0		
P-3341A	SB	-	- %	-		

B. BLOWERS

ltem	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3~/6~z \tag{2}
B-3331	*	4.2(132	6-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	58	_	_		Belt and Filter Checked: Y / (N)
B-3333	~	4.30	140		Greased, Belt and Filter Checked: Ø / N
B-3334	1	4.33	136	V	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	V	On-line: 2/10/18
Reactor Vent Blower	~	
Reactor Vent Booster	1	
VTP-3350	~	PID Reading: //, 6 PPM
VTP-3360	1	PID Reading: 4, 8 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	_Level: 66 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 30 %	
T-530 Mixer	~	
LFG Condensate Conveyance Line	V	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 41 % & 47%	
T-540/541 Mixers	~	
Chiller	offline	Chiller Coolant Lvl: ~ " Below full mark
Chiller Cooling Fins (as needed)	offine	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	~	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	~	Last Back Flushing (Quarterly): 2-3-zz
T-3310 Sedimentation Tank	Visual Level: OK	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	✓ Level: 7/ %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	V	Digital Displays: GOOD V Needs Attn
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	1	Digital Displays: GOOD// Needs Attn
T-3334 Settling Tank	/	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 32 %	
Recycle Valve to Blend Tank		3.98 gpm @ 1106
Building Containment Sump	v	Last Alarm Test Date (Monthly): 4-2/-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments	
Phosphorous Supply		Bags: 10.5 Gallons: ~260 70	
Phosphorous Pump (P-2221)	~		
Caustic Supply	~	~ 260 Gallons	
Caustic Pump (P-2211)	SB	Currently in acid addition mode	
Acid Supply	~	~ 40 Gallons	
Acid Pump (P-2211)	1		
Caustic Pump (P-2231)	Leaks: Y / 🚯	Last tubing tip cleaning (monthly): 4-21-27	
Caustic Pump (P-2232)	Leaks: Y / 🐿	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / (N)	Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	4-28-22	Stray out Clean today
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	·	
Automatic Backwash	Cycle Count: 22	Reset
BF-3340 a/b Differential Pressure	PSI: 4	15/11 Q40ABM
75-micron Bags Last Cleaning	Date: //-14-19	/
75-micron Bags Last Inspection	Date: /	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	~	
GACF-3340 Differential Pressure	PSI: 4	11/7 24.0 mm
Last Backwash Performed	Date: 4-29-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	~	Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	·	
Motor Control Center	~	
PLC	/	UPS @ / 3/ min / 2 Events
HMI's	/	
BTS Process KWH Meter	1884433 KWH	Time: /(57
Building#2 KWH Meter	5416122 KWH	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #2
Alarms Enabled	/	Culibration + maint 5-4-22
GC Influent Filters	/	Cay page page 0-100

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 05, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6648912	
FT-3324 Feed Spare	488739	
FT-3322 Feed to Reactor 2	(1650707	
FT-3323 Feed to Reactor 3	964324	
FT-3301 T-510 to BIO	577.09449	
FT-3341 BIO Effluent	67227469	
FT-3342 BIO Recycle	56663501	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	V	Inspection date: 4-71-72
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (Y) / N

L.	OTHER COMMENTS:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12.55 at	Counter: 199944 Cycles: ₃∞
LFG Cond Automatic Trap CT-2	Sump Level: 8.67 04	Counter: 280344 Cycles: 864
LFG Cond Automatic Trap CT-3	Sump Level: 7.25 04	Counter: 334335 Cycles: 620
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3.38 Counter: 191298 Cycles: [Sump: 8.82,
PM-15 Containment / Vessel	∠ Level: 45 %	
MW-51 Containment / Vessel	✓ Level: 40 %	1828/1920
PM-11 Containment / Vessel	✓ Level: 45 %	
MW-38 Systems		
North Toe System	~	
North End Systems (Weekly)	~	
Full N. End Systems Check (Monthly)	-	Last Done: 4-27-22
North End Pipeline(s)Flushing (As Needed)	~	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	_	Monthly Sump Level: Any al (6.07' Date: 4-21-22
North Boundary System P-001:	CV 73.3 % @ 6.3 gpm	40,49 Hz / 2.07 Amps. / vault psi @18/1006eus.
T-101 & T-102 Containment / Tank	~	Levels: 25 % & 24 %
Raw Water Storage Tanks Piping	V	
RWST Building Temp. (TT-101)	63.5 °F	Outside Temp.: ~ 60 °F
(P-121)or P-122		2.0 gpm/CV 67 %
RWST 2ndry Cont. High Level Switch		(LSH-101) Last Test(monthly): ムーンノーこと
RWST Back-Up Generator		Last Test Run(monthly): ムーマーママ

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~ 345 Gallons Reserve = 2 totas
Caustic Bay Heater	~	
Peroxide Tote Level		~ 237 Gallons Reserve = ~5514
HCL Tote Levels		~ 280 Gallons Reserve = 4-3074
Chemical Totes and Piping Inspected	/	Leaks observed: Y / 🖎
Emergency Shower Inspected	/	Checked and Flushed - All OK: V / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	V	
Ion Exchange Acid Feed Pump (P-632)	~	PI-0632 PSI: 52-54 CV: 3 %
Primary Acid Retention Tank (T-510)	V	
All Acid Feed Lines	/	Leaks observed: Y / 🕦

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022
Inspection Performed by:	Mike Gelwick

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	v	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)	/	Last Cleaning (Qtrly): 4-7-27
T-300A/B Overflow	-	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.82	
pH 315	Value: 10,87	
Flocculation Chamber Paddle Wheel	/	
Precipitate Floc Quality	/	
Clarifier Water Quality	-	Oil or sheen observed: Y / (i)
Clarifier Effluent Piping / Water Level	V	
Clear-well Chamber and Water Level	/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	1	
Polymer Pump (P-310)	/	
Polymer Tank Mixer	/	
Polymer Tank Level	Gallons: ~5∞	
Clear-well Transfer Pumps(R-37) / 372)	~	
Sludge Transfer Pump (P-330)	V	Exercise Valves Weekly: 5>thok
Manual Sludge Lateral pumping	~	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	V	Exercise Weekly: All ox
Automatic Blow-down Operations	/	

F. pH PROBES

r. pn rkobes		
pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	5-12-22- Today	h51+
pH-315 HMR-30 (T-300B)	1	
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		→ ,323
pH-740 Discharge Surge Tank	•	Discharge suspended: 243 ← >/250
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: // w

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	~	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	~	
Sludge Holding Tank (T-351)	1	Level:~ 45 %
Sludge Holding Tank (T-352)	_	Level: 43 %
Decant Transfer Pump (P-352)	~	CV 68 % @ 0.6 gpm
Filter Press Pumps (P-381 / P-382)	~	
Filter Press		Stage: Fill / Ready por Clement

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022	
Inspection Performed by:	Mike Gelwick	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	/ Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 44.3 psi	CV@ 76 % @ 1.68 gpm
Retention Tank (T-114)	✓ Operating Press: 43.0 psi	pH-113 @ 3,51
Bag Filter (BF-113)	✓ Operating Press: 47.0 psi	
lon Exchange (Cage(1)or 2) + Guard	✓ Operating Press: 42.5 psi	T7-174A-TP-1764/Schargers + Gasterd
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 39 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: /6 psi	CV@ 61 % @ 33.5 gpm
T-520 to GAC Total (FT-675)	260571035 gal	Time: 1002
North End On-Site Pumping	Operating Press: 2-3 psi	13.9 gpm @ 0152
North End Off-Site Pumping	Operating Press: 2-6 psi	8.7 gpm @ 0152
Peroxide Feed Pump (P-680)	V	SPD 2.5 % / RATE 0.7
Peroxide Conc. At (TP-710)	I-O PPM	
Peroxide Conc. At (TP-740)	OW PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	V Empty	Check sheet completed: NA/EmPty
Satellite Haz. Waste Areas (BLDG #1)	V	Condition: Ix resin + man Good
Satellite Haz. Waste Area (BLDG #2)		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2027
Quarterly Test Run	Date: NA/Rinning	Next: NA/RUMM
Peroxide Feed Pump (P-650)		Flow Rate: ~ 7.00 cc/min.
UV-Ox Power		7675 kVA 2730 Volts 9,8 Amps
Lamp Hours	リヌ/フ Hrs	
Crystal Condition & Wiper Status		Oiler status: ok
UV-OX Bagfilters Status	Last change: 3-24-72 Cleaned: 3-24-22	9.5 psi In 10 psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 66 % @ 6.5 gpm
UV-OX Temperature	In(TT-670): 15,3 °C	Out(TT-710): 29,1 °C
PDU GAC (PDT-710)	_	Δ Pressure: Z psi
Peroxide Concentration Pre UV	/◯O PPM	
Peroxide Concentration Post UV(TP-720)	ZO PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)		CV @ Z %
Secondary Acid Retention Tank (T-645)	~	
Pre – UV Oxidizer Total (FT-670)	21927488 gal	Time: 1003
Post UV-Ox / Pre PDU	~	Pressure: iZ psi
Post PDU	V	Pressure: 7 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, May 12, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments may there that his + mapped
PDT-720	~	Δ Pressure: 8 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752)	V	CV@ 54.2 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)	·~	33.5 gpm @ 0959
POTW Line Pressure (PT-770)		32,5 psi
Effluent Totalizer Reading (FT-770)	254738960gal	Time: 1003
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 4-4-22
4X8-Inch POTW Leak Detection Checks (Monthly)	V	Last Done: /
4X8-Inch POTW Air Reliefs Checks (Monthly)	~	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	~	Last Done: 2-16-72
2-Inch POTW Backup Pressure Testing (Annual)	V	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	~	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	~	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 4-78-22	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2,001 volts(monthly)	Adjustment Needed: Y or 🕪
Verify Bridge Current between.300v360v	Reading: 0-330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1004-1007

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20035855	(FT-505) LFG Cond. to T-530	222771
(FT-025) NBBW Influent	95698117	(FT-056) Off - Site N. End Influent	45578360
(FT-012) MW-38 Inf. to HMR-30	8716422	(FT-113) Ion Exchange Influent	1353340
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30088300
(FT-043) MW-38 to RWST	3124084	(FT-026) NBBW Bypass to RWST	4563005
(FT-042 RWST) MW-38 Source to RWST	77236	(FT-014) Misc. Water to RWST	8298355
(FT-012T) MW-38 to T-540/541	8689223	(FT-035) NTES Inf. to BIO	6799432
(FT-040T) MW-38N to T-540/541	1980775	(FT-035T) NTES to T-530	469839
(FT-041T) MW-38S to T-540/541	2699208	(FT-017) BIO Inf. from T-530	666274
(FT-042T) MW-38 Source to T-540/541	4081246	(FT-018) T-540/541 Influent	8730740
(FT-055) On - Site N. End Influent	101650386	(FT-352) T-352 to HMR-30	1376595

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:		rsday, May 12, 2022
Inspection Performed by:		Mike Gelwick
P. AIR COMPRESSORS		
Item	Status	Comments
Compressor Intake Temp.	62 °F (Analog Gauge)	Outside Temp.: ~ 6 5 °F
Compressor Building Vent	~	Open-aperational
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-23 Serviced @ 62971 Hou	
IRN30H Motor Speed	31 %	46, 20 - 10 - 100) . C 4 - 10 - 100
IRN30H Pressure	パコ psi	
IRN30H Moisture purge valve chk(Weekly):	~	
IRN30H Intake Filter	V	Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly) 🛩	Excessive Moisture: Y / D
Backup Air Compressors (T-30 East and West)	~	Both cool to touch: Ø / N
Air Dryer	1 ELDON	Moisture at Receiver Tank: Y / ₺
Oil Moisture Prevention (Monthly)	Last Done: 4-21-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	~	//o psi
Q. SUMPS		
Item	Status	Comments
Bag Filter Sump	~	2 Carrier
Wet Well Sump		
R. GAS CHROMATOGRA	PH	
Item	Status	Comments
GC Operational		GC # checking UV-Ox Effluent: [#] ℓ
Alarms Enabled	~	a-automora + mash 5-11-22
GC Influent Filters	~	
S. SAFETY		
Item	Status	Comments
Building #1 Fire Extinguishers	V,	Date inspected: 4-21-22
Building #1 Eye Wash/Shower		Checked and Flushed- All OK: / N
Other Comments:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022		
Inspection Performed by:	Mike Gelwick		

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	V	1.73	32.6 %	6.5	
P-3301A	36	_	- %	_	
NTES Pump P-002(Sump) / (P-002W(10R))		0.48	48 %	P035 P038	Globules Observed at TP-130: Y / D
T-530 P-005		0.20	73 %	8.0	
T-540/541 P-006		0.30	73 %	\$15.0	
LFG COND Auto-Traps	~	0.0	NA	5.0	Between Cycles: Ø / N
Reactor Feed Pumps					
P-3321	~	2.32	49.5 %	6.0	
P-3322	1	3,06	49.1 %	500	
P-3323	SB	-	- %	-	
P-3324	V	2,26	34.3 %	50	
Reactor Effluent Pumps					
P-3341	~	3.29	58.2 %	15.5	
P-3341A	58	-	- %	_	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-77
B-3331	V	4.15	140	6-2022	Greased, Belt and Filter Checked: Ø / N
B-3332	58	_	-	1	Belt and Filter Checked: Y /
B-3333	~	4,26	146		Greased, Belt and Filter Checked: (6 / N
B-3334	~	4.29	144	1	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments		
Vapor Carbon Contactor	/	On-line: 2/10/18		
Reactor Vent Blower	V			
Reactor Vent Booster	~			
VTP-3350	V	PID Reading: 29,C PPM Kesh Sava and App		
VTP-3360	~	PID Reading: 6.7 PPM		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21		
T-510 Post HMR-30 Mixing Tank	✓ Level: 71 %			
T-530 LFG Condensate / NTES Tank	✓ Level: 30 %			
T-530 Mixer	~			
LFG Condensate Conveyance Line	~	Last Pressure Test: フ-/9-マ(Next: みなさて (Annual at a minimum or if flow drops off)		
T-540/541 MW38 Tanks	Lvls: 59 % & 60 %			
T-540/541 Mixers	~			
Chiller	offlone	Chiller Coolant Lvl: ~ - " Below full mark		
Chiller Cooling Fins (as needed)	0 FFLAN	Last Cleaning: 4/20/18 (unit on Standby)		
Secondary Containments	~	Heat Trace: On OK / Off Warm out		
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly):		
T-3310 Sedimentation Tank	Visual Level: OK	Last Cleaning (As Needed, use TSS info to determine): 9/2021		
T-3320 Blend Tank	✓ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21		
T-3331 Reactor No. 1	~	Digital Displays: GOOD Y Needs Attn		
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn		
T-3333 Reactor No. 3	1	Digital Displays: GOOD / Needs Attn		
T-3334 Settling Tank	~	Last Cleaning (Semi Annual): 9-10-21		
P-3334 Biosolids Pump	/			
T-3340 Overflow Tank	✓ Level: 31 %			
Recycle Valve to Blend Tank		3.99 gpm @ 028		
Building Containment Sump	_	Last Alarm Test Date (Monthly): 4-21-22		

E. CHEMICAL FEED SYSTEM

Item	Status	Comments		
Phosphorous Supply	V	Bags: 10,25 Gallons: ~ 75		
Phosphorous Pump (P-2221)	/			
Caustic Supply		~ 235 Gallons		
Caustic Pump (P-2211)	SB	Currently in acid addition mode		
Acid Supply	/	~ 40 Gallons		
Acid Pump (P-2211)	V			
Caustic Pump (P-2231)	Leaks: Y / DP	Last tubing tip cleaning (monthly): 4-2(-22		
Caustic Pump (P-2232)	Leaks: Y / OV	Last tubing tip cleaning (monthly):		
Caustic Pump (P-2233)	Leaks: Y /ON	Last tubing tip cleaning (monthly):		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022		
Inspection Performed by:	Mike Gelwick		

F. pH Probes

pH Probe Location	Calibration Date (Monthly) Comments		
pH-3320 Blend Tank	4-28-22	Straybutt Clean tolay	
pH-3331 Reactor 1			
pH-3332 Reactor 2			
pH-3333 Reactor 3	4	V	

G. FILTER SYSTEM

Item	Status	Comments		
BF-3340 a/b Status	~			
Automatic Backwash	Cycle Count: 27	Kerset		
BF-3340 a/b Differential Pressure	PSI: /	11/10 22.4gpm		
75-micron Bags Last Cleaning	Date: /1-14-19			
75-micron Bags Last Inspection	Date: /			
75-micron Bags Last Changed	Date:			
GACF-3340 Status	_			
GACF-3340 Differential Pressure	PSI: 4	1016 22.4 gon		
Last Backwash Performed	Date: 4-29-22			

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments		
"BIO" Backup Generator		Block Heater: On OK / Off Warm Out		
Electrical Surge Suppressor	V			
Motor Control Center	V			
PLC	V	UPS @ /31 min / Z Events		
HMI's	~			
BTS Process KWH Meter	1886858 KV	/H Time: //07		
Building#2 KWH Meter	5419941 KV	/H Time: パロコ		

I. GAS CHROMATOGRAPHY

ltem	Status	Comments
GC Operational	V	GC # checking BIO: #2
Alarms Enabled	1	a-current mint 3-11-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 12, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6671843	
FT-3324 Feed Spare	511493	
FT-3322 Feed to Reactor 2	11682553	
FT-3323 Feed to Reactor 3	964324	
FT-3301 T-510 to BIO	52232259	
FT-3341 BIO Effluent	67258291	
FT-3342 BIO Recycle	56704824	

K. SAFETY

Item	Status	Comments	
Building #2 Fire Extinguishers		Inspection date: 4-z/-27	
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (*) / N	

L.	OTHER COMMENTS:			

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022
Inspection Performed by:	Mike Gelwick

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12.55	Counter: 200,337 Cycles: 393
LFG Cond Automatic Trap CT-2	Sump Level: 3.66	Counter: 281,093 Cycles: 749
LFG Cond Automatic Trap CT-3	Sump Level: 7,25	Counter: 335 122 Cycles: 787
CT-4 Containment/Vessel (LFG Cond)	Level: 30 %	Tank Level: 3,38 Counter: 191,299 Cycles: O Sump: 8,80
PM-15 Containment / Vessel	Level: 낙웅 %	
MW-51 Containment / Vessel	Level: 25 %	
PM-11 Containment / Vessel	Level: 15 %	
MW-38 Systems	1	
North Toe System	~	
North End Systems (Weekly)	/	
Full N. End Systems Check (Monthly)	~	Last Done: 4-22-22
North End Pipeline(s)Flushing (As Needed)	~	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	/	Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	_	Monthly Sump Level: 127 216.07' Date: 5-19-22-7
North Boundary System P-001:	CV 73.1 % @ 6.3 gpm	40,38 Hz / 2.0 Amps. / vault psi @ 18/100less
T-101 & T-102 Containment / Tank		Levels: 3L % & 35 %
Raw Water Storage Tanks Piping	V	
RWST Building Temp. (TT-101)	66.7 58°F	Outside Temp.: ~ 68 °F
(P-121)or P-122	~	0.5 gpm/CV 50 %
RWST 2ndry Cont. High Level Switch	~	(LSH-101) Last Test(monthly): 4-19-22 -124
RWST Back-Up Generator		Last Test Run(monthly): 5-19-22 - many

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	~	~ 235 Gallons Reserve = 2 totes
Caustic Bay Heater	V	
Peroxide Tote Level	~	~ 210 Gallons Reserve = ~555
HCL Tote Levels	-	~ 2.75 Gallons Reserve = ~ 300 pcl
Chemical Totes and Piping Inspected	V	Leaks observed: Y / 👀
Emergency Shower Inspected	~	Checked and Flushed - All OK: Ø / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	r	
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 52-54 CV: 3 %
Primary Acid Retention Tank (T-510)	~	
All Acid Feed Lines	-	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA NA	
T-300B (Caustic Mixer)	/	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	~	
T-300B (Caustic Mix Chamber)	V	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow	V	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.73	
pH 315	Value: 10.75	
Flocculation Chamber Paddle Wheel	V	
Precipitate Floc Quality	V	
Clarifier Water Quality	/	Oil or sheen observed: Y / (N)
Clarifier Effluent Piping / Water Level		
Clear-well Chamber and Water Level		
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	/	
Polymer Pump (P-310)	-	
Polymer Tank Mixer	1	5
Polymer Tank Level	Gallons: ~ 425	
Clear-well Transfer Pumps(2-371) / 372)	V	
Sludge Transfer Pump (P-330)	~	Exercise Valves Weekly: 60+404
Manual Sludge Lateral pumping	V	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	~	Exercise Weekly: 41104
Automatic Blow-down Operations	V	

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	5-19-22-Today	1241
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1310
pH-740 Discharge Surge Tank	V	Discharge suspended:/234 ↔/>Co
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK:

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	-	Gauge Reading: > %
Sludge Thick. Transfer Pump (P-350)	V	
Sludge Holding Tank (T-351)		Level:~ 45 %
Sludge Holding Tank (T-352)		Level: 45 %
Decant Transfer Pump (P-352)	~	CV65 % @ o.c gpm
Filter Press Pumps (P-381 / P-382)	-	T. G. 10 G. D. 12 Spill
Filter Press	-	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022		
Inspection Performed by:	Mike Gelwick		

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: ΨΨ, ⊆ psi	CV@ 75 % @ (.C? gpm
Retention Tank (T-114)	✓ Operating Press: 44 psi	
Bag Filter (BF-113)	✓ Operating Press: 48 psi	7
Ion Exchange (Cage(Dor 2) + Guard	✓ Operating Press: 42 psi	TP-1744-77P-1764/5 considers + Golard
Post Ion Exchange	✓ Operating Press: 3.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 23 psi	CV@ 66 % @ 31.6 gpm
T-520 to GAC Total (FT-675)	260899155 gal	Time: 0920
North End On-Site Pumping	Operating Press: 2-3 psi	(2.7 gpm @ 39/5
North End Off-Site Pumping	Operating Press: 2-8 psi	8.1 gpm @ 0915
Peroxide Feed Pump (P-680)	V	SPD Z.4 % / RATE O.6
Peroxide Conc. At (TP-710)	I.O PPM	
Peroxide Conc. At (TP-740)	OVO PPM	ONING TO A BLOCK

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	V Empty	Check sheet completed: WHENPY
Satellite Haz. Waste Areas (BLDG #1)	~	Condition: IX lesin + main Good
Satellite Haz. Waste Area (BLDG #2)	/	Condition: Gazail

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-zozz
Quarterly Test Run	Date: NA (LUNNING	Next: NH/Lunnim
Peroxide Feed Pump (P-650)		Flow Rate: ~ 7,0 cc/min.
UV-Ox Power		27.13 kVA 2101 Volts 10.0 Amps
Lamp Hours	/3.83 Hrs	
Crystal Condition & Wiper Status		Oiler status: o
UV-OX Bagfilters Status	Last change: 3-24-22 Cleaned: 3-24-22	9.0 psi In (0.0 psi Out
UV-OX Feed Pump ((P-600) or P-601)	v	CV@ 63 % @ 6-4 gpm
UV-OX Temperature	In(TT-670): /5เฯ °C	Out(TT-710): 29,6 °C
PDU GAC (PDT-710)	V BACKWASINI today	Δ Pressure: <i>[</i> psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	o.o PPM	
Secondary Acid Feed Pump (P-630)		CV @ 1 %
Secondary Acid Retention Tank (T-645)	~	
Pre – UV Oxidizer Total (FT-670)	2/9 <i>89920</i> gal	Time: 0920
Post UV-Ox / Pre PDU		Pressure: /2 psi
Post PDU	/	Pressure: 7 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022
Inspection Performed by:	Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments		
PDT-720		Δ Pressure: /5	psi	
PDT-730	~	Δ Pressure: 3	psi	

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	_	CV@ \$3.5 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)	~	346 gpm @ 0919
POTW Line Pressure (PT-770)		32.3 psi
Effluent Totalizer Reading (FT-770)	255068808 gal	Time: 092/
POTW MH17S-078 Discharge Check (Monthly)	V	Last Done: 5-18-22
4X8-Inch POTW Leak Detection Checks (Monthly)	/	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	/	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	/	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 4-28-22	Plant Effluent Suspended: /3∞ ← /3/7
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or 👀
Verify Bridge Current between.300v360v	Reading: 0.330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0922-0926

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20041510	(FT-505) LFG Cond. to T-530	222902
(FT-025) NBBW Influent	95759213	(FT-056) Off - Site N. End Influent	45665268
(FT-012) MW-38 Inf. to HMR-30	8733070	(FT-113) Ion Exchange Influent	1370218
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30087124
(FT-043) MW-38 to RWST	3124631	(FT-026) NBBW Bypass to RWST	4564917
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8305638
(FT-012T) MW-38 to T-540/541	8689484	(FT-035) NTES Inf. to BIO	6804081
(FT-040T) MW-38N to T-540/541	1980893	(FT-035T) NTES to T-530	470040
(FT-041T) MW-38S to T-540/541	2699345	(FT-017) BIO Inf. from T-530	666780
(FT-042T) MW-38 Source to T-540/541	4081746	(FT-018) T-540/541 Influent	8733628
(FT-055) On - Site N. End Influent	101782247	(FT-352) T-352 to HMR-30	1378886

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, May 19, 2022

Inspection Date:

P. AIR COMPRESSORS Item Compressor Intake Temp. Compressor Building Vent		
Compressor Intake Temp.		
	Status	Comments
Compressor Building Vent	63 °F (Analog Gauge)	Outside Temp.: ~ フェ °F
		Open - openisons
Primary Air Compressor (IRN30H)	2,000 Hour service date: 2-7-22 Serviced @ 6297(Hours	Coolant present in sight glass: 华/ N Next service @ ピイタブ Hours Current Hours @ ピイマタタ
IRN30H Motor Speed	31 %	
IRN30H Pressure	/70 psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter	~	Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y /
Backup Air Compressors	manually ristrate(wooding)	EXOCOUNT MOISIGNO. 1 7 BD
(T-30 East and West)		Both cool to touch: Ø / N
Air Dryer	1 Ecc on	Moisture at Receiver Tank: Y / D
Oil Moisture Prevention (Monthly)	Last Done: 4-21-27	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank		//o psi
O. SUMPS		
Q. SUMPS Item	Status	Comments
	Status	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA	PH	
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item	~	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational	PH	Comments GC # checking UV-Ox Effluent:
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	PH Status	Comments
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	PH Status	Comments GC # checking UV-Ox Effluent:
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	PH Status	Comments GC # checking UV-Ox Effluent: 41 cc-culturaf on the street 5-18-22
Item Bag Filter Sump Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	PH Status	Comments GC # checking UV-Ox Effluent:

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	/	1.85	40.6 %	6.5	
P-3301A	SB	_	- %	-	
NTES Pump P-002(Sump) / (-002W(10R))	~	0.49	47 %	P035 P038	Globules Observed at TP-130: Y / D
T-530 P-005	V	0.18	40 %	7.0	
T-540/541 P-006	~	0.30	45 %	7.0	
LFG COND Auto-Traps	1	0.0	NA	5.0	Between Cycles: (Y) / N
Reactor Feed Pumps				The state of the s	
P-3321	~	7.35	599 %	5.0	
P-3322	/	3,09	5311 %	5.0	
P-3323	1	2,44	560%	5.0	
P-3324 * New POMPHONE	SB		~ %	_	New AMA FRESTO 5-16-22
Reactor Effluent Pumps					
P-3341	~	3.60	66.9 %	21.0	The second secon
P-3341A	58	-	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331	~	4.22	146	6-7022	Greased, Belt and Filter Checked: 4 / N
B-3332	5 <u>B</u>			1	Belt and Filter Checked: Y / (V)
B-3333		4.27	152		Greased, Belt and Filter Checked: Ø / N
B-3334		4.28	150	1	Greased, Belt and Filter Checked: V / N

C. REACTOR VENTILATION

Item	Status	Comments	
Vapor Carbon Contactor	/	On-line: 2/10/18	
Reactor Vent Blower	<i>▶</i>		
Reactor Vent Booster	_		
VTP-3350	<u>-</u>	PID Reading: (©-9 PPM	
VTP-3360	-	PID Reading: 5.6 PPM	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022	
Inspection Performed by:	Mike Gelwick	

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments	
T-510 Post HMR-30 Mixing Tank	_ Level: 70 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21	
T-530 LFG Condensate / NTES Tank	✓ Level: 26 %		
T-530 Mixer			
LFG Condensate Conveyance Line	v	Last Pressure Test: 7-19-24 Next: 7- 2-22 (Annual at a minimum or if flow drops off)	
T-540/541 MW38 Tanks	Lvls: 37 % & 39 %		
T-540/541 Mixers	~		
Chiller	offlore	Chiller Coolant Lvl: ~ - " Below full mark	
Chiller Cooling Fins (as needed)	osseme	Last Cleaning: 4/20/18 (unit on Standby)	
Secondary Containments	~	Heat Trace: On OK / Off Warm out	
Feed Piping to Sedimentation Tank	~	Last Back Flushing (Quarterly): 5~17-27	
T-3310 Sedimentation Tank	Visual Level: 04	Last Cleaning (As Needed, use TSS info to determine): 9/2021	
T-3320 Blend Tank	✓ Level: 70 %	Last Cleaning (Semi Annual): 9-10-71	
T-3331 Reactor No. 1	r	Digital Displays: GOOD \ Needs Attn	
T-3332 Reactor No. 2	~	Digital Displays: GOOD / Needs Attn	
T-3333 Reactor No. 3	V	Digital Displays: GOOD/ Needs Attn	
T-3334 Settling Tank		Last Cleaning (Semi Annual): 9-10-21	
P-3334 Biosolids Pump			
T-3340 Overflow Tank	Level: 31 %		
Recycle Valve to Blend Tank	V	4,41 gpm @ 0953	
Building Containment Sump	~	Last Alarm Test Date (Monthly): 5-19-22-10-44	

E. CHEMICAL FEED SYSTEM

Item	Status	Comments Bags: 10 Gallons: ~ 85	
Phosphorous Supply	V		
Phosphorous Pump (P-2221)	~		
Caustic Supply	✓ ~ ≥z⊘ Gallons		
Caustic Pump (P-2211)	SB Currently in acid addition mode		
Acid Supply	~ 40 Gallons		
Acid Pump (P-2211)	/		
Caustic Pump (P-2231)	Leaks: Y /	Last tubing tip cleaning (monthly): 5-19-22-7204	
Caustic Pump (P-2232)	Leaks: Y /	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / N Last tubing tip cleaning (monthly):		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	4-28-22	Acit/Bitse Clean today
pH-3331 Reactor 1	1	
pH-3332 Reactor 2		
pH-3333 Reactor 3	1	V

G. FILTER SYSTEM

Item	Status	Comments		
BF-3340 a/b Status				
Automatic Backwash	Cycle Count: 3 2_	Leset		
BF-3340 a/b Differential Pressure	PSI: Z	20/18 7 3.5 pm		
75-micron Bags Last Cleaning	Date: 11-14-19			
75-micron Bags Last Inspection	Date: /			
75-micron Bags Last Changed	Date:	18		
GACF-3340 Status	an V			
GACF-3340 Differential Pressure	PSI: # /1	18/7 23.5000		
Last Backwash Performed	Date: 4-29-22			

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments Block Heater: On OK / Off Warm Out	
"BIO" Backup Generator	V		
Electrical Surge Suppressor	./		
Motor Control Center			
PLC	/	UPS @ /3/ min / 2 Events	
HMI's	/		
BTS Process KWH Meter	(B89275 KWH	Time: 1040	
Building#2 KWH Meter	5423423 KWH	Time: 1040	

I. GAS CHROMATOGRAPHY

Item	Status	Comments	
GC Operational	V	GC # checking BIO: #Z	
Alarms Enabled	1	CC - Califfration + major 5-18-22	
GC Influent Filters	/		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 19, 2022
Inspection Performed by:	Mike Gelwick

J. TOTALIZERS

Item	Readings (gallons)	Comments		
FT-3321 Feed to Reactor 1	6694522			
FT-3324 Feed Spare	528717	N = 1 prims + united 5-16:22		
FT-3322 Feed to Reactor 2	11714052			
FT-3323 Feed to Reactor 3	969550			
FT-3301 T-510 to BIO	52254354			
FT-3341 BIO Effluent	67288605			
FT-3342 BIO Recycle	56746318			

K. SAFETY

Item	Status	Comments	
Building #2 Fire Extinguishers		Inspection date: 4-21-22	
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: Ø / N	

L. OTHER COMMENTS:

5-16-2L- New fum	"+ motor Drytallad on i	1-3324	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, May 26, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12,55	Counter: 200,634 Cycles: 297	
LFG Cond Automatic Trap CT-2	Sump Level: 8.65'	Counter: 281,801 Cycles: 708	
LFG Cond Automatic Trap CT-3	Sump Level: 7,24	Counter: 335,991 Cycles: 769	
CT-4 Containment/Vessel (LFG Cond)	Level: 30 %	Tank Level: 3,33 Counter: 141,248 Cycles: O Sump: 8,41	
PM-15 Containment / Vessel	Level: 50 %		
MW-51 Containment / Vessel	Level: 40 %	8	
PM-11 Containment / Vessel	Level: 45 %		
MW-38 Systems	✓.		
North Toe System	√ 2		
North End Systems (Weekly)		40 MAC	
Full N. End Systems Check (Monthly)	/	Last Done: 4-22-22 5-25-22	
North End Pipeline(s)Flushing (As Needed)	1,	Perform if suspended solids present Last Done: 11/15/15	
NTES line flush to T-530 (As needed)	/	Perform if suspended solids present Last Done: 10/29/21	
NTES Piping Containment	/	Monthly Sump Level: Dry @ 16.07 Date: 5-19-22	
North Boundary System P-001:	CV67.5 % @ 0.0 gpm	36.15 Hz/2.02 Amps. / vault psi @ 18/1000004	
T-101 & T-102 Containment / Tank	1,	Levels: 16 % & 13 %	
Raw Water Storage Tanks Piping	✓		
RWST Building Temp. (TT-101)	59 °F	Outside Temp.: ~ 61 °F	
(P-121) or P-122	√ ,	2,5 gpm/CV 71 %	
RWST 2ndry Cont. High Level Switch	1/	(LSH-101) Last Test(monthly): 5'-19-22	
RWST Back-Up Generator		Last Test Run(monthly): 5-19-22	

B. CHEMICAL STORAGE BAYS

Item	Status		Comments	
Caustic Tote Levels	7		~ 450 Gallons Reserve = 1 tote	
Caustic Bay Heater	V.			
Peroxide Tote Level	√	/	~ 190 Gallons Reserve = 55 qu)	
HCL Tote Levels	/	/	~ 160 Gallons Reserve = 30 gal	
Chemical Totes and Piping Inspected	V	1	Leaks observed: Y / (N)	
Emergency Shower Inspected			Checked and Flushed - All OK: (Y) / N	

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	1	
Ion Exchange Acid Feed Pump (P-632)	1	PI-0632 PSI: 46-48 CV: 3 %
Primary Acid Retention Tank (T-510)	1,	
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 26, 2022	
Inspection Performed by:	Mike Gelwick / Tom Gilbert	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NĄ.	
T-300B (Caustic Mixer)	1	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	1	
T-300B (Caustic Mix Chamber)	V,	Last Cleaning (Qtrly): 1/-7-22
T-300A/B Overflow	1	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 7.38	
pH 315	Value: 11.25	
Flocculation Chamber Paddle Wheel	1	
Precipitate Floc Quality	1	
Clarifier Water Quality	V.	Oil or sheen observed: Y / N
Clarifier Effluent Piping / Water Level	1	
Clear-well Chamber and Water Level	1,	
HMR PLC Panel		
Caustic Pump (P-270)	SB,	
Caustic Pump (P-280)	1,	
Polymer Pump (P-310)	1	
Polymer Tank Mixer		
Polymer Tank Level	Gallons: ~ 550	
Clear-well Transfer Pumps(P-371 / 372)		
Sludge Transfer Pump (P-330)	/	Exercise Valves Weekly: both ok
Manual Sludge Lateral pumping		Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves		Exercise Weekly: OK
Automatic Blow-down Operations		

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)	
pH-310 HMR-30 (T-300A)	5-26-22	/330 🛧	
pH-315 HMR-30 (T-300B)	1		
pH-365 Primary Acid Ret. Tank			
pH-113 Pre-Ion Exchange			
pH-670 Pre-UV-OX		+1420	
pH-740 Discharge Surge Tank	V	Discharge suspended: 1424 ←► 1454	
Out of Hold Double Check		None in hold: VV 17-	
Valves Back to Normal Position		All OK: VV T/3	

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	1,	Gauge Reading: () %
Sludge Thick. Transfer Pump (P-350)		
Sludge Holding Tank (T-351)	1	Level:~ 닉O %
Sludge Holding Tank (T-352)		Level: 30 %
Decant Transfer Pump (P-352)		CV 7名% @ O,O gpm
Filter Press Pumps (P-381 / P-382)	<i>J.</i>	
Filter Press		Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, May 26, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)		
Retention Tank (T-114)	Operating Press: 40 psi	pH-113 @ 3.8
Bag Filter (BF-113)	Operating Press: 44 psi	
Ion Exchange (Cag€ 1 or 2) + Guard	Operating Press: 38 psi	TP-174A ->TP-176A Scanishes + Quan
Post Ion Exchange	Operating Press: 3,5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	/	Last Cleaning (As Needed, if 4" of
	✓ Level: 34 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 2) psi	CV@ 53 % @ 24.4 gpm
T-520 to GAC Total (FT-675)	26) 223 302 gal	Time: 0840
North End On-Site Pumping	Operating Press: 1-2 psi	12.4 gpm @ 0842
North End Off-Site Pumping	Operating Press: 4-8 psi	8.9 gpm @ 0846
Peroxide Feed Pump (P-680)	/	SPD 1.8 % / RATE 0.5 40M
Peroxide Conc. At (TP-710)	0.5 PPM	,
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	√ Empty	Check sheet completed: NIY empty
Satellite Haz. Waste Areas (BLDG #1)	11	Condition: Ix Resin + Main good
Satellite Haz. Waste Area (BLDG #2)	/	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System	offine/SB	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 4-2022
Quarterly Test Run	Date: NA Raving	Next: NA Rimany
Peroxide Feed Pump (P-650)	OFF	Flow Rate: ~ N/A cc/min. N/A
UV-Ox Power	offline	 kVA – Volts – Amps
Lamp Hours	Hrs	
Crystal Condition & Wiper Status	NA	Oiler status: NA
UV-OX Bagfilters Status	Last change: 3-4-22 Cleaned: 3 4-22	니 psiIn 니 psiOut
UV-OX Feed Pump (P-600 or (P-601)	,	CV@ % @ gpm
UV-OX Temperature	In(TT-670): N ♣ °C	Out(TT-710): N/A °C
PDU GAC (PDT-710)	UV-OX OFF	Δ Pressure: O psi
Peroxide Concentration Pre UV	NOO PPM	
Peroxide Concentration Post UV(TP-720)	15 PPM	
Peroxide Conc. Post PDU (TP-730)	O, O PPM	
Secondary Acid Feed Pump (P-630)	$\sqrt{}$	CV @ \ %
Secondary Acid Retention Tank (T-645)	\checkmark	
Pre – UV Oxidizer Total (FT-670)	22055368 gal	Time: 0850
Post UV-Ox / Pre PDU		Pressure: 9 psi
Post PDU		Pressure: 2 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, May 26, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments		
PDT-720		Δ Pressure: 10 psi		psi
PDT-730	V	Δ Pressure:	2	psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))	7.	CV@ 50.5 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)	✓ ✓	Z4.5 gpm @ 0858
POTW Line Pressure (PT-770)		31.2 psi
Effluent Totalizer Reading (FT-770)	255395674 gal	Time: 0900
POTW MH17S-078 Discharge Check (Monthly)	1	Last Done: 5-18-22
4X8-Inch POTW Leak Detection Checks (Monthly)	1	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	V.	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	V,	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)	1/	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	1	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	√	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 5-26-22 hidry	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2-00 volts(monthly)	Adjustment Needed: Y or N
Verify Bridge Current between.300v360v	Reading: 530 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0901 - 0910

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20052542	(FT-505) LFG Cond. to T-530	223089
(FT-025) NBBW Influent	95820547	(FT-056) Off - Site N. End Influent	45753016
(FT-012) MW-38 Inf. to HMR-30	8747101	(FT-113) Ion Exchange Influent	1387056
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30089840
(FT-043) MW-38 to RWST	3124977	(FT-026) NBBW Bypass to RWST	4567094
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8305642
(FT-012T) MW-38 to T-540/541	8694808	(FT-035) NTES Inf. to BIO	6808858
(FT-040T) MW-38N to T-540/541	1981036	(FT-035T) NTES to T-530	470190
(FT-041T) MW-38S to T-540/541	2699602	(FT-017) BIO Inf. from T-530	667303
(FT-042T) MW-38 Source to T-540/541	4086188	(FT-018) T-540/541 Influent	8736292
(FT-055) On - Site N. End Influent	101907835	(FT-352) T-352 to HMR-30	1380968

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, May 26, 2022

Inspection Date:

P. AIR COMPRESSORS	Status	Comments
Compressor Intake Temp.	T	Outside Temp.: ~ 72 °F
	5 °F (Analog Gauge)	Outside Femp ~ / < F
Compressor Building Vent	2,000 Hour service date: 2-7-22	Content present in sight place: 30 / N
Primary Air Compressor (IRN30H)	Serviced @ 62921 Hours	Coolant present in sight glass: V / N Next service @ 64971 Hours
		Current Hours @ 64333
IRN30H Motor Speed	31 %	
IRN30H Pressure	115 psi	
IRN30H Moisture purge valve chk(Weekly):	V/	
IRN30H Intake Filter	✓	Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / (N)
Backup Air Compressors		
(T-30 East and West)	•	Both cool to touch: (Y) / N
Air Dryer	1 Econ	Moisture at Receiver Tank: Y / N
Oil Moisture Prevention (Monthly)	Last Done: 5-26-22 today	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	✓	110 psi
Q. SUMPS	Status	Comments
Bag Filter Sump	✓.	
Bag Filter Sump Wet Well Sump	7	
Wet Well Sump		Comments
Wet Well Sump R. GAS CHROMATOGRA	PH	
Wet Well Sump R. GAS CHROMATOGRA Item	PH Status	GC # checking UV-Ox Effluent:
R. GAS CHROMATOGRA Item GC Operational	PH Status	The state of the s
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled	PH Status	GC # checking UV-Ox Effluent:
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintance 5-25-2
Wet Well Sump R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item	PH Status	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintance 5-25-2
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintenance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers Building #1 Eye Wash/Shower	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintenance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers Building #1 Eye Wash/Shower	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintrance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers Building #1 Eye Wash/Shower	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintenance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers Building #1 Eye Wash/Shower	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brations + Maintenance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers Building #1 Eye Wash/Shower	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - call brakions + Maintenance 5-25-2 Comments Date inspected: 4-21-22
R. GAS CHROMATOGRA Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item Building #1 Fire Extinguishers	Status ONS OVOROFF	GC # checking UV-Ox Effluent: 22 CC - cal; brations + Maintance 5-25-25-25-25-25-25-25-25-25-25-25-25-25

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 26, 2022		
Inspection Performed by:	Mike Gelwick / Tom Gilbert		

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301		2.3	44 %	フ	
P-3301A	513	_	_ %		
NTES Pump P-002(Sump) / P-002W(10R)	1	0.48	47 %	P035 P038 35-38 6	Globules Observed at TP-130: Y / (N) Time: 1050
T-530 P-005		0.00	41 %	フ	
T-540/541 P-006	✓	0.00	43 %	7.5	
LFG COND Auto-Traps		0.00	NA	4.5	Between Cycles: // N
Reactor Feed Pumps					
P-3321	1	2.57	71.5%	7.5	
P-3322		3.58	59.4 %	7	
P-3323	/	2,69	52.4%	8	
P-3324	53		%	_	New pump + Motor 5-16-22
Reactor Effluent Pumps	/				
P-3341	/	4.99	76.2%	27	
P-3341A	SB	_	- %		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-:22
B-3331	$\sqrt{}$	4.3	148	6-2022	Greased, Belt and Filter Checked: (Y)/ N
B-3332	SB,		-	1	Belt and Filter Checked: Y / (N)
B-3333	1	4.31	150	1,	Greased, Belt and Filter Checked: (Y) / N
B-3334		4.29	146	V	Greased, Belt and Filter Checked: (Y)/ N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	/	On-line: 2/10/18
Reactor Vent Blower	√	
Reactor Vent Booster	✓	
VTP-3350	√,	PID Reading: 200 + PPM Fresh mus g Sur well 641
VTP-3360		PID Reading: 9.8 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 26, 2022		
Inspection Performed by:	Mike Gelwick / Tom Gilbert		

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	√ Level: 76 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	√ Level: 23 %	
T-530 Mixer		
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 56 % & 57%	
T-540/541 Mixers	/	
Chiller	offline	Chiller Coolant Lvl: ~ — " Below full mark
Chiller Cooling Fins (as needed)	offine	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments		Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 5-12-22
T-3310 Sedimentation Tank	Visual Level: OK	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	√ Level: 73 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	✓	Digital Displays: 600D Needs Attn
T-3332 Reactor No. 2	1/	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	1/	Digital Displays: GOOD Needs Attn
T-3334 Settling Tank	1	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	, /	
T-3340 Overflow Tank	/ Level: 67 %	
Recycle Valve to Blend Tank	1	3.98 gpm @ 0434
Building Containment Sump		Last Alarm Test Date (Monthly): 5-14-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	1,	Bags: 9,5 Gallons: ~ 70
Phosphorous Pump (P-2221)		
Caustic Supply	/	~ 210 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	V.	~ 40 Gallons
Acid Pump (P-2211)	/	
Caustic Pump (P-2231)	Leaks: Y /(i	Last tubing tip cleaning (monthly): 5-14-22
Caustic Pump (P-2232)	Leaks: Y / (1	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	√ Leaks: Y /(I	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, May 26, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	5-26-22-70lay	New 4+ 10 PH STAS today
pH-3331 Reactor 1		1
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	1

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 27	Reset
BF-3340 a/b Differential Pressure	PSI: .5	28/23 & 5,3 gpm
75-micron Bags Last Cleaning	Date: 1]-14-19	- 1
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date:	
GACF-3340 Status	1	28 7 6 5
GACF-3340 Differential Pressure	PSI: 19	28/7 @ 5.3 com
Last Backwash Performed	Date: 5-26-22 today	1 2009

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments	
"BIO" Backup Generator	√		Block Heater: On OK / Off Warm Out	
Electrical Surge Suppressor				
Motor Control Center	1	-		
PLC	1		UPS@131 min/ 2 Events	
HMI's	J			
BTS Process KWH Meter	01891731	KWH	Time: j015	
Building#2 KWH Meter	5428678	KWH	Time: 1015	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	1	GC # checking BIO: # 2
Alarms Enabled		CC - Calibrations + Maint 5-25-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, May 26, 2022		
Inspection Performed by:	Mike Gelwick / Tom Gilbert		

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6717158	
FT-3324 Feed Spare	528717	
FT-3322 Feed to Reactor 2	11745495	
FT-3323 Feed to Reactor 3	991866	
FT-3301 T-510 to BIO	52276255	
FT-3341 BIO Effluent	67318707	
FT-3342 BIO Recycle	56788545	

K. SAFETY

	Comments	Status ,	Item
: 4-21-22	Inspection date:	1/	Building #2 Fire Extinguishers
lushed- All OK: (Y) / N	Checked and Flu	<i>-</i>	Building #2 Eye Wash/Shower
lus	Checked and Flu	,	Building #2 Eye Wash/Shower

L. OTHER COMMENTS:		
	85-04-0-08	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 02, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12,55	Counter: 201,015 Cycles: 381	
LFG Cond Automatic Trap CT-2	Sump Level: ももち	Counter: 282,647 Cycles: 846	
LFG Cond Automatic Trap CT-3	Sump Level: 7, 28	Counter: 336,634 Cycles: 743	
CT-4 Containment/Vessel (LFG Cond)	Level: 30 %	Tank Level: 3.33 Counter: 191,298 Cycles: 0 Sump: 8,85	
PM-15 Containment / Vessel	Level: 52 %		
MW-51 Containment / Vessel	Level: 70 %		
PM-11 Containment / Vessel	Level: 68 %		
MW-38 Systems	<i>J</i> ,		
North Toe System	<i>\'</i>		
North End Systems (Weekly)	1,		
Full N. End Systems Check (Monthly)		Last Done: 5-25-22	
North End Pipeline(s)Flushing (As Needed)	1	Perform if suspended solids present Last Done: 11/15/15	
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21	
NTES Piping Containment	1	Monthly Sump Level: Dry @ 16.07 Date: 5-19-22	
North Boundary System P-001:	CV 73.1 % @ 6,4 gpm	40.46 Hz / 2.07 Amps. / vault psi @ 18/ No baks	
T-101 & T-102 Containment / Tank	/	Levels: 28 % & 27 %	
Raw Water Storage Tanks Piping	/		
RWST Building Temp. (TT-101)	,58 °F	Outside Temp.: ~ 56 °F	
(P-121) or P-122		0.6 gpm/CV 57 %	
RWST 2ndry Cont. High Level Switch	1,	(LSH-101) Last Test(monthly): 5-19-22	
RWST Back-Up Generator	1	Last Test Run(monthly): 5-19-22	

B. CHEMICAL STORAGE BAYS

	Comments
7	~ 325 Gallons Reserve = 1 tota
/	~ 175 Gallons Reserve = 55 gallons
<i>J.</i>	~ 135 Gallons Reserve = 30 gallons
1/	Leaks observed: Y / (N)
/	Checked and Flushed - All OK: (Y) / N
-	<i>y y y y</i>

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	,	Comments	
Primary Acid Feed Pump (P-631)	/			
Ion Exchange Acid Feed Pump (P-632)	√	,	PI-0632 PSI: 52-56	CV: 5 %
Primary Acid Retention Tank (T-510)	V	1		
All Acid Feed Lines	1		Leaks observed: Y	(N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 02, 2022		
Inspection Performed by:	Mike Gelwick / Tom Gilbert		

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	1	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	✓	
T-300B (Caustic Mix Chamber)	V,	Last Cleaning (Qtrly): リーフ・ユス
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.5	
pH 315	Value: 10.87	
Flocculation Chamber Paddle Wheel	1	
Precipitate Floc Quality	1,	
Clarifier Water Quality	√ ,	Oil or sheen observed: Y / 🐧
Clarifier Effluent Piping / Water Level	V/	
Clear-well Chamber and Water Level	V/	
HMR PLC Panel	/	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	1	
Polymer Pump (P-310)	4	
Polymer Tank Mixer		
Polymer Tank Level	Gallons: ~, 450	
Clear-well Transfer Pumps(P-371 / 372)	√ .	,
Sludge Transfer Pump (P-330)	√,	Exercise Valves Weekly: both ok
Manual Sludge Lateral pumping	√ ,	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	1//	Exercise Weekly: ⊘K ✓
Automatic Blow-down Operations	7	

F. pH PROBES

r. priritobes		
pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)		1413
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1454
pH-740 Discharge Surge Tank		Discharge suspended: 1403 ←>1412
Out of Hold Double Check		None in hold: // TG
Valves Back to Normal Position		All OK: VJ TG

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	,	Comments
Verify Sludge Thickener Running	· ·	,	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	/	1	
Sludge Holding Tank (T-351)	-	/	Level:~ 40 %
Sludge Holding Tank (T-352)	- /	/	Level: 30 %
Decant Transfer Pump (P-352)	/		CV 78 % @ 0.0 gpm
Filter Press Pumps (P-381 / P-382)	,	1	
Filter Press		/	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, June 02, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	Operating Press: 31,7 psi	CV@ 66 % @ 1,7 gpm
Retention Tank (T-114)	Operating Press: 31 psi	pH-113 @ 3.6
Bag Filter (BF-113)	Operating Press: 34 psi	A
Ion Exchange (Cage 1)or 2) + Guard	Operating Press: 26 psi	TP-174A -> TP-176A 4 Conses + Gue
Post Ion Exchange	Operating Press:3,5 psi	TP-174A#1 OFFLINE 6-1-22
		Cour 43

I. FEED SURGE TANK

Item	Status Comments	
Feed Surge Tank (T-520)	Level: 38 % Last Cleaning (As solids accumulate	
Feed Surge Pump (P-521 or P-522)	70 000000000000000000000000000000000000	@ 31.2 gpm
T-520 to GAC Total (FT-675)	261543653 gal Time: 1006	
North End On-Site Pumping		0817
North End Off-Site Pumping		0817
Peroxide Feed Pump (P-680)		RATE D.6 gpm
Peroxide Conc. At (TP-710)	O.5 PPM	,
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	V EMON	Check sheet completed: NA Empty
Satellite Haz. Waste Areas (BLDG #1)	1/1	Condition: I'x Resin + Main goed
Satellite Haz. Waste Area (BLDG #2)	V	Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Rimmy	Next: NA/Running
Peroxide Feed Pump (P-650)	V,	Flow Rate: ~ cc/min.
UV-Ox Power	√	2646 kVA 2714 Volts 9,8 Amps
Lamp Hours	169O Hrs	
Crystal Condition & Wiper Status		Oiler status:
UV-OX Bagfilters Status	Last change: 3.4.22 Cleaned: 3.4.12	II psi In II.5 psi Out
UV-OX Feed Pump (P-600 or (P-601)		CV@ 70 % @ 6,9 gpm
UV-OX Temperature	In(TT-670): 14.5 °C	Out(TT-710): 27.1 °C
PDU GAC (PDT-710)		Δ Pressure: 2 psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	20 19 PPM	
Peroxide Conc. Post PDU (TP-730)	, 0,0 PPM	
Secondary Acid Feed Pump (P-630)	1	CV @ 3 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	2211136 gal	Time: 1020
Post UV-Ox / Pre PDU		Pressure: \4 psi
Post PDU	7	Pressure: 9 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, June 02, 2022

Inspection Performed by: Mike Gelwick / Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	1,	Δ Pressure: 13 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 53.8 %
Effluent Surge Tank (T-740)	1	Level: 40 %
Effluent Discharge Rate (FT-770)		32.5 gpm @ 0826
POTW Line Pressure (PT-770)	/	32,4 psi
Effluent Totalizer Reading (FT-770)	2557i2890 gal	Time: 0918
POTW MH17S-078 Discharge Check (Monthly)	V.	Last Done: 5-\8-22
4X8-Inch POTW Leak Detection Checks (Monthly)	V.	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	√ ,	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	1,	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)	1	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	1/	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)	√	Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed:	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	5-26-22	1424 +> 1454
LEL Sensor Bridge Adjustment to 2.0 volts	Reading:2001 volts(monthly)	Adjustment Needed: Y or (N)
Verify Bridge Current between.300v360v	Reading: 330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 0830 -0845

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20061552	(FT-505) LFG Cond. to T-530	223253
(FT-025) NBBW Influent	95873766	(FT-056) Off - Site N. End Influent	45840072
(FT-012) MW-38 Inf. to HMR-30	8764874	(FT-113) Ion Exchange Influent	1403887
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30090136
(FT-043) MW-38 to RWST	3127762	(FT-026) NBBW Bypass to RWST	4578025
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8305643
(FT-012T) MW-38 to T-540/541	8695623	(FT-035) NTES Inf. to BIO	6813512
(FT-040T) MW-38N to T-540/541	1981295	(FT-035T) NTES to T-530	470431
(FT-041T) MW-38S to T-540/541	2700099	(FT-017) BIO Inf. from T-530	667836
(FT-042T) MW-38 Source to T-540/541	4086188	(FT-018) T-540/541 Influent	8739054
(FT-055) On - Site N. End Influent	102032430	(FT-352) T-352 to HMR-30	1382988

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, June 02, 2022

Inspection Date:

Inspection P	erformed by: Mike Gelv	wick / Tom Gilbert
B. AID COMPRESSORS		
P. AIR COMPRESSORS	Status	Comments
Compressor Intake Temp.	58 °F (Analog Gauge)	Outside Temp.: ~ 65 °F
Compressor Building Vent	50 . (/inaleg 522g5)	Outoido Formp OD T
Primary Air Compressor	2,000 Hour service date: 2-7-22	Coolant present in sight glass: (Y) / N
(IRN30H)	Serviced @ 62921 Hours	Next service @ ६५१७७। Hours Current Hours @ ६५५१७
IRN30H Motor Speed	31 %	Current Hours @ 8741 /
IRN30H Pressure	119 ,psi	
IRN30H Moisture purge valve chk(Weekly):		
IRN30H Intake Filter		Date Last Changed: 2-7-22
Air Tanks Moisture Purge Valves	Manually Activate(weekly)	Excessive Moisture: Y / N
Backup Air Compressors	/	Exacello Molotaro. 1 / 13
(T-30 East and West)	,	Both cool to touch: Q / N
Air Dryer	V ECO ON	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (Monthly)	Last Done: 5-26-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank	/	\08 psi
Q. SUMPS	Status	Comments
Bag Filter Sump	J.	Comments
Wet Well Sump	/	
R. GAS CHROMATOGRA		12
GC Operational	Status	Comments
Alarms Enabled	1-1	GC # checking UV-Ox Effluent: #1
GC Influent Filters	- - /	calibrations + Manthone 6-1-22
		6-1-77
S. SAFETY	Ctatura	
	Status	Comments
Building #1 Fire Extinguishers		Date inspected: 4-21-22
Building #1 Eye Wash/Shower	,	Checked and Flushed- All OK: (Y) / N
Other Comments:		
ST 76 1620 760000	ma #3 taken offline t Emajor	of protes satalise arm.

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 02, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					The American Control of the Control
P-3301	✓	1.8	37 %	7.5	
P-3301A	SB		%		
NTES Pump 50 100 6-1-22 P-002(Sump) / (P-002W(10R))	1	0.50	47 %	P035 P038 33-34 6	Globules Observed at TP-130: Y / Time: 0945
T-530 P-005	V.	0.20	41 %	7	
T-540/541 P-006	1	0,30	49 %	7.5	
LFG COND Auto-Traps	Ĵ	0,00	NA	4.5	Between Cycles: (Y)/ N
Reactor Feed Pumps					
P-3321	√,	1,97	66 %	7.5	
P-3322	√,	2.89	51.3 %	6,5	
P-3323	/	3,20	50.7 %	7.5	
P-3324	SB		- %		New pump + Motor 5-16-22
Reactor Effluent Pumps	/				
P-3341	 	2.88	58,3%	30	
P-3341A	SB		%		

B. BLOWERS

ltem	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331		4.32	149	6-2022	Greased, Belt and Filter Checked: / N
B-3332	SB,			1	Belt and Filter Checked: Y / 🔞
B-3333		4,33	#148		Greased, Belt and Filter Checked: Ø / N
B-3334		4.08	130	1	Greased, Belt and Filter Checked: () / N

C. REACTOR VENTILATION

Item	Status	Comments	
Vapor Carbon Contactor	- /,	On-line: 2/10/18	
Reactor Vent Blower	√ ,		
Reactor Vent Booster	1		
VTP-3350	1	PID Reading: 230 r PPM	
VTP-3360	1	PID Reading: 30, 10 PPM	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 02, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	√ Level: 64 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 21 %	
T-530 Mixer		
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-19-2i Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 40 % & 41 %	
T-540/541 Mixers	1	
Chiller	offine 1	Chiller Coolant Lvl: ~ Below full mark
Chiller Cooling Fins (as needed)	offine/	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	1/	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 5-12-22
T-3310 Sedimentation Tank	Visual Level: OK	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: 70 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	√	Digital Displays: GOOD Needs Attn
T-3332 Reactor No. 2	1	Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	V ,	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank	7 ,	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	Level: 30 %	
Recycle Valve to Blend Tank	1	4.00 gpm @ 0909
Building Containment Sump		Last Alarm Test Date (Monthly): 5-19-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	1/	Bags: 9,25 Gallons: ~ 75
Phosphorous Pump (P-2221)	/ .	
Caustic Supply		~ 200 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply		~ 4() Gallons
Acid Pump (P-2211)	V	
Caustic Pump (P-2231)	Leaks: Y	(N) Last tubing tip cleaning (monthly): 5-19-22
Caustic Pump (P-2232)	Leaks: Y /	
Caustic Pump (P-2233)	Leaks: Y /	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 02, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	5-26-22	Sonay of probes with walk
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	

G. FILTER SYSTEM

Item	Status /	Comments
BF-3340 a/b Status	/	,
Automatic Backwash	Cycle Count: 28	21/24 C 3.7 Jpm
BF-3340 a/b Differential Pressure	PSI: 3	
75-micron Bags Last Cleaning	Date: 11-14 -19	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date: √,	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: / 1	21/7 6 3,6 gpm
Last Backwash Performed	Date: 5-26-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments		
"BIO" Backup Generator	V/		Block Heater: On OK / Off Warm Out		
Electrical Surge Suppressor	1,				
Motor Control Center	√,				
PLC	1,		UPS@122 min / 2 Events		
HMI's					
BTS Process KWH Meter	1894184	KWH	Time: 1150		
Building#2 KWH Meter	5432627	KWH	Time: \150		

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	\	GC # checking BIO: #2
Alarms Enabled	1	calibrations + Moint all comme
GC Influent Filters	√	6-1-22

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 02, 2022
Inspection Performed by:	Mike Gelwick / Tom Gilbert

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6740160	
FT-3324 Feed Spare	531540	
FT-3322 Feed to Reactor 2	11777444	
FT-3323 Feed to Reactor 3	1011725	
FT-3301 T-510 to BIO	52298601	
FT-3341 BIO Effluent	67349039	
FT-3342 BIO Recycle	56829330	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	1,	Inspection date: 4-21-22
Building #2 Eye Wash/Shower	V	Checked and Flushed- All OK: Y / / N

L. OTH	ER COMMENTS:		
		-4	
	-		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, June 09, 2022

Inspection Performed by:

Mike Gelwick Tom Glbat

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 12.55	Counter: 201,513 Cycles: 448
LFG Cond Automatic Trap CT-2	Sump Level: 8.66	Counter: 283, L54 Cycles: 1007
LFG Cond Automatic Trap CT-3	Sump Level: 7.25	Counter: 337,628 Cycles: 994
CT-4 Containment/Vessel (LFG Cond)	Level: 30 %	Tank Level: 3.38 Counter: 141,248 Cycles: O Sump: 8.93
PM-15 Containment / Vessel	Level: LO %	
MW-51 Containment / Vessel	Level: 38 %	
PM-11 Containment / Vessel	Level: 30 %	
MW-38 Systems		
North Toe System	1.	
North End Systems (Weekly)		
Full N. End Systems Check (Monthly)		Last Done: 5-20-22
North End Pipeline(s)Flushing (As Needed)	1	Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment		Monthly Sump Level: Dry & 16.07 Date:5-19-22
North Boundary System P-001:	CV73.6% @ 6.5 gpm	40.82 Hz /207 Amps. / vault psi @ 18/ No leaks
T-101 & T-102 Containment / Tank		Levels: 35 % & 33 %
Raw Water Storage Tanks Piping		
RWST Building Temp. (TT-101)	64.7 °F	Outside Temp.: ~ 52 °F
(P-121) or P-122		0.6 gpm / CV 52 %
RWST 2ndry Cont. High Level Switch	✓,	(LSH-101) Last Test(monthly): 5-19-22
RWST Back-Up Generator		Last Test Run(monthly): 5-19-22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels	1,	~ 500 Gallons Reserve = None
Caustic Bay Heater		
Peroxide Tote Level	1	~ 160 Gallons Reserve = 55 gallons
HCL Tote Levels	1	~ 115 Gallons Reserve = 30 gallons
Chemical Totes and Piping Inspected		Leaks observed: W / (N)
Emergency Shower Inspected		Checked and Flushed - All OK: (Y) / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)	/ .	
Ion Exchange Acid Feed Pump (P-632)	1,	PI-0632 PSI: 54-60 CV: 4 %
Primary Acid Retention Tank (T-510)		
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

Table 3.19.1 Rev 7 WTP.docx

Tables - 111

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

inspection Dai	.e:	Thursday, June 09, 2022
Inspection Per	formed by:	Mike October Tom Gilbert / Chris Carl
E. CHEMICAL PRECIPITAT	TION SYSTEM (US F	FILTER HMR-30)
Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)		Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level		
T-300B (Caustic Mix Chamber)	V.	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow		
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.7	
pH 315	Value: 10.86	
Flocculation Chamber Paddle Whee	el 🗸	
Precipitate Floc Quality		
Clarifier Water Quality	1	Oil or sheen observed: Y /
Clarifier Effluent Piping / Water Lev		
Clear-well Chamber and Water Lev	el 🗸	
HMR PLC Panel		
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	√.	
Polymer Pump (P-310)		
Polymer Tank Mixer	✓	
Polymer Tank Level	Gallons: ~/3	75
Clear-well Transfer Pumps(P-371 /	372)	
Sludge Transfer Pump (P-330)	V	Exercise Valves Weekly: OK V
Manual Sludge Lateral pumping	✓	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves		Exercise Weekly: OK 🗸
Automatic Blow-down Operations		
F. pH PROBES		
	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)		2 // // *
pH-315 HMR-30 (T-300B)	111	119

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	7.	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	1	
Sludge Holding Tank (T-351)	1,	Level:~ 40 %
Sludge Holding Tank (T-352)		Level: 30 %
Decant Transfer Pump (P-352)	1	CV 74 % @ 0.0 gpm
Filter Press Pumps (P-381 / P-382)		
Filter Press		Stage: Empty needs to be Washed

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 09, 2022	
Inspection Performed by:	Mike Gelwick Tom Gilbert	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	Operating Press:33.1 psi	CV@ 66 % @ 1.7 gpm
Retention Tank (T-114)	Operating Press: 32 psi	pH-113 @ 4.4
Bag Filter (BF-113)	Operating Press: 35 psi	
Ion Exchange (Cage 1 or 2) + Guard	Operating Press: 26 psi	TP-1741+ -> TP-1761+ 4 consters + quard
Post Ion Exchange	Operating Press: 2.5 psi	TP-174k #10ffline 6-1-22

I. FEED SURGE TANK

Item	Status		Comments
Feed Surge Tank (T-520)	1	2002	Last Cleaning (As Needed, if 4" of
	✓ Level:	38 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press:	19 psi	CV@ 62 % @ 32 gpm
T-520 to GAC Total (FT-675)	2619682	o¥ gal	Time: 0905
North End On-Site Pumping		6.5 psi	12.5 gpm @ 0406
North End Off-Site Pumping	Operating Press:	7 psi	8.6 gpm @ 0906
Peroxide Feed Pump (P-680)			SPD 2.4 % / RATE 0.6 4PM
Peroxide Conc. At (TP-710)	0.5	PPM	3.
Peroxide Conc. At (TP-740)	0.0	PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status		Comments
180 Day storage area check	1	Empty	Check sheet completed: NA County
Satellite Haz. Waste Areas (BLDG #1)	7		Condition: Ix Resin + Main good
Satellite Haz. Waste Area (BLDG #2)	-		Condition: Good

K. UV-OXIDATION SYSTEM

Item	Status /	Comments
UV-Oxidation System	1	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA Running	Next: NK Ruming
Peroxide Feed Pump (P-650)	1.	Flow Rate: ~ 7.2 cc/min.
UV-Ox Power		2658 kVA 2726 Volts 9.8 Amps
Lamp Hours	1957 Hrs	
Crystal Condition & Wiper Status		Oiler status: OK
UV-OX Bagfilters Status	Last change: 3-4-22 Cleaned: 3-4-22	11.5 psi In 12 psi Out
UV-OX Feed Pump (P-600 or (P-601))		CV@ 72 % @ 6.9 gpm
UV-OX Temperature	In(TT-670): 15.3 °C	Out(TT-710): 27,9 °C
PDU GAC (PDT-710)		Δ Pressure: 3 psi
Peroxide Concentration Pre UV	IOO PPM	
Peroxide Concentration Post UV(TP-720)	20 PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)		CV @ 3 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	22181744 gal	Time: 0914
Post UV-Ox / Pre PDU	1/	Pressure: 14 psi
Post PDU		Pressure: 8 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 09, 2022

Inspection Performed by: Mike Gelwick Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	V.	Δ Pressure: 11 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752))		CV@ 53.7 %
Effluent Surge Tank (T-740)	V	Level: 40 %
Effluent Discharge Rate (FT-770)		32.4 gpm @ 0917
POTW Line Pressure (PT-770)		32.3 psi
Effluent Totalizer Reading (FT-770)	256043690gal	Time: 0920
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 5-18-22
4X8-Inch POTW Leak Detection Checks (Monthly)	V.	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	1	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	1,	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)	7.	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	J .	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor	/	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 5-26-22	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.00\ volts(monthly)	Adjustment Needed: Y or N
Verify Bridge Current between.300v360v	Reading: .330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 0924 - 0932

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20072105	(FT-505) LFG Cond. to T-530	223366
(FT-025) NBBW Influent	95938583	(FT-056) Off - Site N. End Influent	45927976
(FT-012) MW-38 Inf. to HMR-30	8778687	(FT-113) Ion Exchange Influent	1420778
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30000896
(FT-043) MW-38 to RWST	3128929	(FT-026) NBBW Bypass to RWST	4579330
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	831567
(FT-012T) MW-38 to T-540/541	8704445	(FT-035) NTES Inf. to BIO	6818260
(FT-040T) MW-38N to T-540/541	1981567	(FT-035T) NTES to T-530	470587
(FT-041T) MW-38S to T-540/541	2700478	(FT-017) BIO Inf. from T-530	667979
(FT-042T) MW-38 Source to T-540/541	4094323	(FT-018) T-540/541 Influent	8741965
(FT-055) On - Site N. End Influent	102158516	(FT-352) T-352 to HMR-30	1385160

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, June 09, 2022

Inspection Date:

or service date: ed @ 62921 Hours 120 psi	Comments Outside Temp.: ~ 58 °F OREMIONA Coolant present in sight glass: ⑦ / N Next service @ 64971 Hours Current Hours @ 64505
"F (Analog Gauge) Hour service date: ed @ 62921 Hours 31 % 120 psi	Outside Temp.: ~ 58 °F O Remitoria\ Coolant present in sight glass: ⑦ / N Next service ② 64971 Hours Current Hours ② 64505
Hour service date: ed @ 62921 Hours 31 % 120 psi	Coolant present in sight glass: N Next service @ 64471 Hours Current Hours @ 64505
Hour service date: ed @ 62921 Hours 31 % 120 psi	Coolant present in sight glass: N Next service @ 64471 Hours Current Hours @ 64505
Bed @ 6292 Hours 31 % 120 psi	Next service @ 64971 Hours Current Hours @ 64505
120 psi	
	
✓	
	Date Last Changed: 2-7-22
ally Activatę(weekly)	Excessive Moisture: Y / N
/	Both cool to touch: Ø / N
V ECO ON	Moisture at Receiver Tank: Y / (N)
one: 5-26-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
1	l10 psi
;	Comments
5	Comments
	GC # checking UV-Ox Effluent: #1
1	Calibrations + Maint 6-9-22
3	Comments
V	Date inspected: 4-21-22

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 09, 2022
Inspection Performed by:	Mike Gelwick Tom Gilbert (Chots Cadson

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301		1.2	30 %	7.5	
P-3301A	SB	-	- %		
NTES Pump 6-1-22 Swap P-002(Sump) / (P-002W(10R)	1	0.48	48 %	P035 P038 34-35 5.5	Globules Observed at TP-130: Y / N Time: 0955
T-530 P-005	/	0.0	40 %	7	
T-540/541 P-006	1	0.21	41 %	7.5	
LFG COND Auto-Traps	1	0.00	NA	4	Between Cycles: Ø / N
Reactor Feed Pumps				Service (A.S. III - M	
P-3321	1.	1.70	42.7 %	2.5	
P-3322	1	2.19	38.6 %	5	
P-3323	V	1.32	54.7 %	5	
P-3324	SB		%		NEW pump + motor 5-16-22
Reactor Effluent Pumps					
P-3341		1.58	%	12	
P-3341A	SB	-	%		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 35-2022
B-3331	V	4, 29	150	6-2022	Greased, Belt and Filter Checked: 🕥 / N
B-3332	SB				Belt and Filter Checked: Y /
B-3333	-	4.31	149	6-2022	Greased, Belt and Filter Checked: 6 / N
B-3334		4.06	132	6-2022	Greased, Belt and Filter Checked: (7) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	/	On-line: 2/10/18
Reactor Vent Blower		
Reactor Vent Booster	✓.	
VTP-3350		PID Reading: 67.0 PPM
VTP-3360		PID Reading: 62,5 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 09, 2022
Inspection Performed by:	Mike Gelwick Tom Gibert

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	✓ Level: 70 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 24 %	
T-530 Mixer		
LFG Condensate Conveyance Line	/	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls:82 % & 82 %	
T-540/541 Mixers		
Chiller	OFF V	Chiller Coolant Lvl: ~ N
Chiller Cooling Fins (as needed)	OFF	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	√ ,	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 5-12-22
T-3310 Sedimentation Tank	Visual Level: 0K	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: 70 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	1	Digital Displays: 600D Needs Attn
T-3332 Reactor No. 2	√	Digital Displays: 600D Needs Attn
T-3333 Reactor No. 3	√ ,	Digital Displays: GOOD Needs Attn
T-3334 Settling Tank	1	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	~	
T-3340 Overflow Tank	Level: 30 %	
Recycle Valve to Blend Tank	1	3.98 gpm @ 0948
Building Containment Sump		Last Alarm Test Date (Monthly): 5-19-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	7,	Bags: 9.25 Gallons: ~ 85
Phosphorous Pump (P-2221)	1/	
Caustic Supply	1	~ 175 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply	1,	~ 40 Gallons
Acid Pump (P-2211)	√ /	
Caustic Pump (P-2231)	Leaks: Y / N	Last tubing tip cleaning (monthly): 5-19-22
Caustic Pump (P-2232)	Leaks: Y / 🐧	Last tubing tip cleaning (monthly):
Caustic Pump (P-2233)	Leaks: Y /	Last tubing tip cleaning (monthly):



WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 09, 2022		
Inspection Performed by:	Mike Gelwick Tam G:160+		

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	5-26-22	Spray off probes with
pH-3331 Reactor 1	1	water today 6-9-22
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 27	
BF-3340 a/b Differential Pressure	PSI: 1	13/14 C 1.8
75-micron Bags Last Cleaning	Date: 11-14 - 19	1
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date:	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: 7	13/6 C 21
Last Backwash Performed	Date: 5-26-33 6-9-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status		Comments
"BIO" Backup Generator			Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	/		
Motor Control Center			
PLC	1		UPS @ 13 min / 2 Events
HMI's			
BTS Process KWH Meter	01896388	KWH	Time: III3
Building#2 KWH Meter	05435857	KWH	Time: \\\\\

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	/	GC # checking BIO: #2
Alarms Enabled	1	calibration + Moint 6-9-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 09, 2022	
Inspection Performed by:	Mike-Gelwick Tom Gilbert	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6762164	
FT-3324 Feed Spare	531544	
FT-3322 Feed to Reactor 2	11808010	
FT-3323 Feed to Reactor 3	1033398	
FT-3301 T-510 to BIO	52320273	
FT-3341 BIO Effluent	67378734	
FT-3342 BIO Recycle	56871151	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	4	Inspection date: Y-21-22
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (Y) / N

L. OTHER COMMENTS:	



WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022
Inspection Performed by:	Tom Gilbert

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: (2.55	Counter: 201773 Cycles: 760
LFG Cond Automatic Trap CT-2	Sump Level: 8.65	Counter: 284/02 Cycles: 448
LFG Cond Automatic Trap CT-3	Sump Level: 7.73	Counter: 338897 Cycles: 1769
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 30 %	Tank Level: 3.38 Counter: 191 298 Cycles: O Sump: 8.84
PM-15 Containment / Vessel	/ Level: 65 %	2.30 111010 1 10 2.81
MW-51 Containment / Vessel	∠ Level: 20 %	
PM-11 Containment / Vessel	✓ Level: (5 %	
MW-38 Systems	_	
North Toe System	/	
North End Systems (Weekly)		
Full N. End Systems Check (Monthly)		Last Done: 5-20-22
North End Pipeline(s)Flushing (As Needed)		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)		Perform if suspended solids present Last Done: 10/29/21
NTES Piping Containment	1	Monthly Sump Level: Dry 6 16.07 Date:5-19-22
North Boundary System P-001:	CV 73.7% @ 6.6 gpm	40.75 Hz / 2.07 Amps. / vault psi @18 No lanks
T-101 & T-102 Containment / Tank	J. 5. 5	Levels: 24 % & 23 %
Raw Water Storage Tanks Piping		20 70 a 2 70
RWST Building Temp. (TT-101)	71 °F	Outside Temp.: ~ 72 °F
P-12 or P-122		0.6 gpm / CV 60 %
RWST 2ndry Cont. High Level Switch	/	(LSH-101) Last Test(monthly): 5-19-22
RWST Back-Up Generator		Last Test Run(monthly): 5-19-22

B. CHEMICAL STORAGE BAYS

Item	Status	,	Comments
Caustic Tote Levels			~ 368 Gallons Reserve = None
Caustic Bay Heater	V		TOOLIVE TOOLIVE
Peroxide Tote Level			~ 300 Gallons Reserve = 205
HCL Tote Levels	-	-	~ 100 Gallons Reserve = 1 tote
Chemical Totes and Piping Inspected		/	Leaks observed: Y / 🚳
Emergency Shower Inspected		/	Checked and Flushed - All OK: (7) / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments
Primary Acid Feed Pump (P-631)		
Ion Exchange Acid Feed Pump (P-632)	1	PI-0632 PSI: 54-60 CV: 3 %
Primary Acid Retention Tank (T-510)	V	76 J. 100
All Acid Feed Lines		Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 qpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022
Inspection Performed by:	Tom Gilbert / Chots On Kon

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NĄ	
T-300B (Caustic Mixer)		Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	1,	(201)
T-300B (Caustic Mix Chamber)	1	Last Cleaning (Qtrly): 4-7-22
T-300A/B Overflow		(, , , , , , , , , , , , , , , , , , ,
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 7.00	
pH 315	Value: 10.86	
Flocculation Chamber Paddle Wheel	1	
Precipitate Floc Quality	V	
Clarifier Water Quality	V.	Oil or sheen observed: Y / 🕥
Clarifier Effluent Piping / Water Level	V	on or oricon observed. 1 7 db
Clear-well Chamber and Water Level	1,	
HMR PLC Panel		
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	1	
Polymer Pump (P-310)	√,	
Polymer Tank Mixer		
Polymer Tank Level	Gallons: ~ 475	
Clear-well Transfer Pumps(P-371 / 372)	1,	
Sludge Transfer Pump (P-330)	1	Exercise Valves Weekly: 6K-V
Manual Sludge Lateral pumping	1	Last done (As Needed): 3-15-22
Manual Sludge Lateral Ball Valves	1,	Exercise Weekly: All ok
Automatic Blow-down Operations	/	

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	6 16 22	14424
pH-315 HMR-30 (T-300B)		1.12
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX	1	÷ 1510
pH-740 Discharge Surge Tank	V	Discharge suspended: (432 ←)44/
Out of Hold Double Check		None in hold: VV (C)
Valves Back to Normal Position		All OK: VV d (w)

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

ltem	Status .	Comments
Verify Sludge Thickener Running		Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	/	oddgo riodding. 0 70
Sludge Holding Tank (T-351)		Level:~ 40 %
Sludge Holding Tank (T-352)		Level: 36 %
Decant Transfer Pump (P-352)	V	CV 67 % @ 0.5gpm
Filter Press Pumps (P-381 / P-382)	/	5. G, 7. g 0.3gpm
Filter Press	1	Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022	
Inspection Performed by:	Tom Gilbert	

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30 %	
Feed Pump (P-114)	Operating Press: 33 psi	CV@ 66 % @ 1.7 gpm
Retention Tank (T-114)	Operating Press: 34 psi	pH-113 @ 3.6
Bag Filter (BF-113)	Operating Press: 36 psi	
Ion Exchange (Cage 1 or 2) + Guard	Operating Press: 26 psi	TP-174 A -> TP176A/4 con; sters + quard
Post Ion Exchange	Operating Press: 2.5 psi	TP-174A #1 offline 6-1-22

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 39 %	solids accumulate): 12/15/19
Feed Surge Pump (P-521 or P-522)	Operating Press: 19 psi	CV@ 62 % @ 33.1 gpm
T-520 to GAC Total (FT-675)	262193587 gal	Time: 0920
North End On-Site Pumping	Operating Press: 1-3 psi	12.6 gpm @ 0921
North End Off-Site Pumping	Operating Press: 2-7 psi	8.6 gpm @ 0921
Peroxide Feed Pump (P-680)		SPD 2.5 % / RATE 0.7 4000
Peroxide Conc. At (TP-710)	O.S PPM	
Peroxide Conc. At (TP-740)	O.O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status		Comments
180 Day storage area check	✓	-HOL HEL	Check sheet completed: NA (Entry)
Satellite Haz. Waste Areas (BLDG #1)	V	1	Condition: Ix Resin + Main good
Satellite Haz. Waste Area (BLDG #2)	-		Condition: Cood

K. UV-OXIDATION SYSTEM

Item	Status ,	Comments
UV-Oxidation System	/	
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9 - 2022
Quarterly Test Run	Date: Nh Running	Next: Nr Russing
Peroxide Feed Pump (P-650)	7.	Flow Rate: ~ 7.2 cc/min.
UV-Ox Power	1	26.19 kVA 2717 Volts 9.7 Amps
Lamp Hours	2025 Hrs	
Crystal Condition & Wiper Status		Oiler status: OK
UV-OX Bagfilters Status	Last change: 3-4-22 Cleaned: 3-4-22	11.5 psi In 12.5 psi Out
UV-OX Feed Pump (P-600 or (P-601)		CV@ 74 % @ 7.0 gpm
UV-OX Temperature	In(TT-670): , 16.3 °C	Out(TT-710): 28.9 °C
PDU GAC (PDT-710)		Δ Pressure: 3 psi
Peroxide Concentration Pre UV	ICO PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	O.O PPM	
Secondary Acid Feed Pump (P-630)	1/	CV @ 2 %
Secondary Acid Retention Tank (T-645)		
Pre – UV Oxidizer Total (FT-670)	22249832 gal	Time: 0928
Post UV-Ox / Pre PDU	/	Pressure: 14 psi
Post PDU	/	Pressure: 9 psi

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 16, 2022

Inspection Performed by: Tom Gilbert

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments
PDT-720	1 ,	Δ Pressure: 9 psi
PDT-730		Δ Pressure: 3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (P752)	V	CV@ 53.9 %
Effluent Surge Tank (T-740)	V.	Level: 40 %
Effluent Discharge Rate (FT-770)	1,	32.7 gpm @ 0930
POTW Line Pressure (PT-770)		32. 4 psi
Effluent Totalizer Reading (FT-770)	256370762 gal	Time: 0932
POTW MH17S-078 Discharge Check (Monthly)	<i>J.</i>	Last Done: 5-18-22
4X8-Inch POTW Leak Detection Checks (Monthly)	✓	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)	✓.	Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	√.	Last Done:
2-Inch POTW Backup Pressure Testing (Annual)	V.	Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)	1	Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status /	Comments
LEL-740 Sensor	1	Reading: 0 %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 5-24-22	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.001 volts(monthly)	Adjustment Needed: Y or (N)
Verify Bridge Current between.300v360v	Reading: .330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 0933 - 0940

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20078042	(FT-505) LFG Cond. to T-530	223498
(FT-025) NBBW Influent	96004348	(FT-056) Off - Site N. End Influent	46016264
(FT-012) MW-38 Inf. to HMR-30	8793761	(FT-113) Ion Exchange Influent	1437480
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30091704
(FT-043) MW-38 to RWST	3129258	(FT-026) NBBW Bypass to RWST	4580578
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8315667
(FT-012T) MW-38 to T-540/541	8704445	(FT-035) NTES Inf. to BIO	6822999
(FT-040T) MW-38N to T-540/541	1981567	(FT-035T) NTES to T-530	470730
(FT-041T) MW-38S to T-540/541	2700478	(FT-017) BIO Inf. from T-530	667979
(FT-042T) MW-38 Source to T-540/541	4094323	(FT-018) T-540/541 Influent	8744635
(FT-055) On - Site N. End Influent	102285134	(FT-352) T-352 to HMR-30	1386666

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, June 16, 2022

Inspection Date:

Primary Air Compresso			Comments
Compressor Building V Primary Air Compresso (IRN30H)		°F (Analog Gauge)	Outside Temp.: ~ 74 °F
Primary Air Compresso	ent		operational
	r 2,000 H	Hour service date: 2 7 22 ed @ 62921 Hours	Coolant present in sight glass: (Y) / N Next service @ 64971 Hours Current Hours @ 64595
IRN30H Motor Speed		31 %	Carrent route & City
IRN30H Pressure		II6 psi	
IRN30H Moisture purge valve of	chk(Weekly):	110 001	
IRN30H Intake Filter	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1	Date Last Changed: 2-7-22
Air Tanks Moisture Pur	ne Valves Manus	illy Activate(weekly)	Excessive Moisture: Y / (N)
Backup Air Compressor (T-30 East and West)		✓	Both cool to touch: Ø / N
Air Dryer		V ECO ON	Moisture at Receiver Tank: Y / (N)
Oil Moisture Prevention (N	Monthly) Last D	one: 5-26-22	Run at max speed by bleeding air from filter canister above/after air dryer for 2 hrs
Air Receiver Tank			110 psi
Wet Well Sump		✓	
5 040 0000			
R. GAS CHROM			Community
Item	ATOGRAPH Status		Comments
Item GC Operational		· /,	GC # checking UV-Ox Effluent:
Item GC Operational Alarms Enabled			GC # checking UV-Ox Effluent: # 1 Calibrations + Maint 6-16-22
Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	Status		GC # checking UV-Ox Effluent: # Calibrations + Maint 6-16-22 False Calculation Error
Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY Item	Status		GC # checking UV-Ox Effluent: # Calibrations + Maint 6-16-22 False Calculation Error Comments
Item GC Operational Alarms Enabled GC Influent Filters S. SAFETY	Status Status		GC # checking UV-Ox Effluent: # Calibrations + Maint 6-16-22 False Calculation Error

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022
Inspection Performed by:	Tom Gilbert

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps	,				
P-3301	✓	3.5	62 %	13-14	
P-3301A	SB		- %		
NTES Pump 6-1-22 Swap P-002(Sump) / P-002W(10R)	1	0.48	48 %	P035 P038 33-34 8	Globules Observed at TP-130: Y / N Time: 1000
T-530 P-005	√.	0.00	40 %	7	
T-540/541 P-006		0.30	41 %	7.5	
LFG COND Auto-Traps	J	0.00	NA	4	Between Cycles: (Y) / N
Reactor Feed Pumps					
P-3321		2.66	54.9%	2.5	
P-3322	V	3.67	49.9%	5	
P-3323	V	2.67	71.8 %	5	
P-3324	58		%		New pump + motor 5-16-22
Reactor Effluent Pumps			1.		
P-3341		3.85	%	20	
P-3341A	SB		%		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 5-2022 3(16/22
B-3331		4.26	158	6-2022	Greased, Belt and Filter Checked: (Y) / N
B-3332	SB				Belt and Filter Checked: Y / (N)
B-3333	1	4.29	155	6-2022	Greased, Belt and Filter Checked: (Y) / N
B-3334		4.04	140	6-2022	Greased, Belt and Filter Checked: Ø / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	✓	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	V	
VTP-3350	V.	PID Reading: 2.9 PPM
VTP-3360	V	PID Reading: /. o PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022		
Inspection Performed by:	Tom Gilbert		

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	✓ Level: 66 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 27 %	
T-530 Mixer		
LFG Condensate Conveyance Line	1	Last Pressure Test: 7-19-21 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvis: 61 % &62 %	
T-540/541 Mixers	1	
Chiller	OFF V	Chiller Coolant Lvl: ~ N A " Below full mark
Chiller Cooling Fins (as needed)	OFF V	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	1	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 5-12-22
T-3310 Sedimentation Tank	Visual Level: OK	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	Level: 69 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	✓	Digital Displays: GOOD Needs Attn
T-3332 Reactor No. 2	V,	Digital Displays: GOOD P Needs Attn
T-3333 Reactor No. 3	/	Digital Displays: GOOD Needs Attn
T-3334 Settling Tank	V	Last Cleaning (Semi Annual): 9-10-21
P-3334 Biosolids Pump	, /	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	1	4.00 gpm @ \000
Building Containment Sump	/	Last Alarm Test Date (Monthly): 5-19-22

E. CHEMICAL FEED SYSTEM

Item	Status.	Comments	
Phosphorous Supply	1/	Bags: 9 Gallons: ~ 85	
Phosphorous Pump (P-2221)	1/		
Caustic Supply	/	~ I60 Gallons	
Caustic Pump (P-2211)	SB,	Currently in acid addition mode	
Acid Supply	1,	~ 40 Gallons	
Acid Pump (P-2211)	4	6/16/22	
Caustic Pump (P-2231)	Leaks: Y	Last tubing tip cleaning (monthly): 5-19-22	
Caustic Pump (P-2232)	Leaks: Y	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / N Last tubing tip cleaning (monthly):		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022		
Inspection Performed by:	Tom Gilbert / Chris Carlson		

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	5/26/22	Cleaned with Acid BASE SAKE
pH-3331 Reactor 1	1	1
pH-3332 Reactor 2		.//
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status		
Automatic Backwash	Cycle Count: 20	
BF-3340 a/b Differential Pressure	PSI: 3	15 18 C 2.8 gpm
75-micron Bags Last Cleaning	Date: 11-14-19	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date:	
GACF-3340 Status		2
GACF-3340 Differential Pressure	PSI: 9	15/6 @ 2.9 gpm
Last Backwash Performed	Date: (c) 6-16-22 4/	29/11

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	V .	Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	1	
Motor Control Center	1	
PLC	V_	UPS @ 131 min / 2 Events
HMI's	1/	
BTS Process KWH Meter	1898327KWH	1 Time: 1115
Building#2 KWH Meter	√5438731 KWH	

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	1	GC # checking BIO: 42
Alarms Enabled	V.	Calibrations + Maint 6-16-22
GC Influent Filters		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 16, 2022	
Inspection Performed by:	Tom Gilbert	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6783391	
FT-3324 Feed Spare	531544	
FT-3322 Feed to Reactor 2	11937503	
FT-3323 Feed to Reactor 3	1054276	
FT-3301 T-510 to BIO	52338765	
FT-3341 BIO Effluent	67404792	
FT-3342 BIO Recycle	56912549	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers	<i>//</i>	Inspection date 24-21-22 5/23/23
Building #2 Eye Wash/Shower	V	Checked and Flushed- All OK: (Y) / N

OTHER COMMENTS:		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Ins	pection	Date:
------------------	-----	---------	-------

Thursday, June 23, 2022

Inspection Performed by:

Chris Carlson

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments
LFG Cond Automatic Trap CT-1	Sump Level: 14.90	Counter: 20241 Cycles: 468
LFG Cond Automatic Trap CT-2	Sump Level: 8.62	Counter: 284534 Cycles: 432
LFG Cond Automatic Trap CT-3	Sump Level: 7,20'	Counter: 3 3.9258 Cycles: 361
CT-4 Containment/Vessel (LFG Cond)	✓ Level: ~3/1/ %	Tank Level: 3,34 Counter: 19 13 16 Cycles: 18 Sump: 845
PM-15 Containment / Vessel	Level: ~65%	
MW-51 Containment / Vessel	✓ Level: ~ 50 %	
PM-11 Containment / Vessel	✓ Level: ~ 50 %	
MW-38 Systems		
North Toe System	_	
North End Systems (Weekly)		
Full N. End Systems Check (Monthly)		Last Done: 5-20-22
North End Pipeline(s)Flushing (As Needed)		Perform if suspended solids present Last Done: 11/15/15
NTES line flush to T-530 (As needed)	/	Perform if suspended solids present Last Done: \$\frac{13/2}{2}0 \tag{2}
NTES Piping Containment		Monthly Sump Level: Drye 16.07 Date: 6/20/22
North Boundary System P-001:	CV73.6% @ 6.7 gpm	40.91 Hz / 2.08 Amps. / vault psi @ 18 (No leaks)
T-101 & T-102 Containment / Tank	V.	Levels: 32 % & 30 %
Raw Water Storage Tanks Piping		
RWST Building Temp. (TT-101)	06 70,4 °F	Outside Temp.: ~ &o °F
P-121 or P-122	· /	0.6 gpm/CV 54 %
RWST 2ndry Cont. High Level Switch		(LSH-101) Last Test(monthly): 6 20 22
RWST Back-Up Generator		Last Test Run(monthly): 6/20/22

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~ 250 Gallons Reserve = 3 to tes
Caustic Bay Heater		
Peroxide Tote Level		~ 275 Gallons Reserve = ~ 255,40
HCL Tote Levels	~ Top-100 bottom ~75	~ 175 Gallons Reserve = ~ 255 44
Chemical Totes and Piping Inspected	V	Leaks observed: Y / (N)
Emergency Shower Inspected		Checked and Flushed - All OK: Y / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status /	Comments
Primary Acid Feed Pump (P-631)	1	
Ion Exchange Acid Feed Pump (P-632)	V/	PI-0632 PSI: 47-48 CV: 31
Primary Acid Retention Tank (T-510)	V	3
All Acid Feed Lines	V	Leaks observed: Y / (N)

D. NBBW INJECTION TRENCH

Item	Status	Comments	
Injection Carbon (GAC-810)	AC-810) OFFLINE Date online: 7/20/		
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.	
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545	

Table 3.19.1 Rev 7.docx

Tables - 111

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 23, 2022
Inspection Performed by: Chris Carlson

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status		Comment
T-300A Mixer		NA	
T-300B (Caustic Mixer)	/	V	Last Cleaning (Qtrly): 4 2 2
T-300A/B Water Level		<u></u>	
T-300B (Caustic Mix Chamber)		r	Last Cleaning (Qtrly): 4/7/22
T-300A/B Overflow		/	
pH Set-point for (pH 315)	Value:	10,9	
pH 310	Value:	6.99	
pH 315	Value:	(0,78	
Flocculation Chamber Paddle Wheel		/	- STATE OF THE STA
Precipitate Floc Quality	V		Very Good
Clarifier Water Quality	,	/	Viry Gaul Oil or sheen observed: Y N
Clarifier Effluent Piping / Water Level	1		
Clear-well Chamber and Water Level	\	/	
HMR PLC Panel	V		
Caustic Pump (P-270)		SB	3333333
Caustic Pump (P-280)		/	
Polymer Pump (P-310)			
Polymer Tank Mixer			
Polymer Tank Level	Gallons:	- 410	
Clear-well Transfer Pumps(P-371 372)	V		
Sludge Transfer Pump (P-330)	,		Exercise Valves Weekly: Top a little 5tiff.
Manual Sludge Lateral pumping		~	Last done (As Needed): 3115/22
Manual Sludge Lateral Ball Valves			Exercise Weekly: All okay
Automatic Blow-down Operations		/	

F. pH PROBES

pH Probe Location	Calibration Date			Comments: (Tir	ne done)
pH-310 HMR-30 (T-300A)	6/23	1/22 8	ruh 5705	1115	
pH-315 HMR-30 (T-300B)		1	ı		\
pH-365 Primary Acid Ret. Tank			\neg		
pH-113 Pre-Ion Exchange					
pH-670 Pre-UV-OX	1	/			+ 1145
pH-740 Discharge Surge Tank	V	,	1/	Discharge suspe	ended:1045 -> 1110
Out of Hold Double Check			V	None in hold: 🗸	
Valves Back to Normal Position				All OK: Vr	

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS

Item	Status	Comments
Verify Sludge Thickener Running	V	Gauge Reading: 0 %
Sludge Thick. Transfer Pump (P-350)	7	
Sludge Holding Tank (T-351)	V	Level:~ 35 %
Sludge Holding Tank (T-352)	<u></u>	Level: 34 %
Decant Transfer Pump (P-352)	54	CV —% @ — gpm
Filter Press Pumps (P-381 / P-382)	V.	P-382 neceles leaving (Sticks)
Filter Press		Stage: Full

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, June 23, 2022

Inspection Performed by: Chris Carlson

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	✓ Level: 30%	
Feed Pump (P-114)	Operating Press: 34,2psi	CV@ 66% @ 1.7gpm
Retention Tank (T-114)	Operating Press: 33 psi	pH-113 @ 3.9
Bag Filter (BF-113)	Operating Press: 35 psi	
Ion Exchange (Cage 1)or 2) + Guard	Operating Press: 25 psi	Columns4, 5, 6: 7 online
Post Ion Exchange	Operating Press: 2.5 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)	✓ Level: 38 %	Last Cleaning (As Needed, if 4" of solids accumulate): 12/15/19
Feed Surge Pump (P-521 of P-522)	Operating Press: 17 psi	CV@ 61%@ 31.9 gpm
T-520 to GAC Total (FT-675)	2625/634 gal	Time: 0657
North End On-Site Pumping	Operating Press: 1 psi	12.5gpm @ 0756
North End Off-Site Pumping	Operating Press: 2-6 psi	8.5 gpm @ 0756
Peroxide Feed Pump (P-680)	V	SPD 2.4% / RATE 0.6
Peroxide Conc. At (TP-710)	/ PPM	
Peroxide Conc. At (TP-740)	O PPM	

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check		Check sheet completed: NA (Firsty)
Satellite Haz. Waste Areas (BLDG #1)	V	Condition Tx Speet Resin & Min good
Satellite Haz. Waste Area (BLDG #2)		Condition: 6 and.

K. UV-OXIDATION SYSTEM

Item	Status	Comments
UV-Oxidation System		
Annual Test Run (Calgon)	Date: 5/16/7.1 .	Next: 9/2022 .
Quarterly Test Run	Date: NA KUNNWS	Next: NA / RUNING
Peroxide Feed Pump (P-650)		Flow Rate: ~ 7 cc/min.
UV-Ox Power		26,52 kVA 2717 Volts 9.8 Amps
Lamp Hours	2190 Hrs	
Crystal Condition & Wiper Status		Oiler status: Needed oil (very low)
UV-OX Bagfilters Status	Last change: 3/4/22 leaned: 3/4/22	R psi In 9 psi Out
UV-OX Feed Pump (P-600 of P-601)	111/	CV@ 63 % @ 7.0 gpm
UV-OX Temperature	In(TT-670): /5.4 °C	Out(TT-710): 29.2 °C
PDU GAC (PDT-710)		Δ Pressure: 2 psi
Peroxide Concentration Pre UV	100 PPM	
Peroxide Concentration Post UV(TP-720)	25 PPM	
Peroxide Conc. Post PDU (TP-730)	O PPM	
Secondary Acid Feed Pump (P-630)		CV @ /%
Secondary Acid Retention Tank (T-645)	V	
Pre – UV Oxidizer Total (FT-670)	22317628 gal	Time: 0653
Post UV-Ox / Pre PDU	V.	Pressure: /2 psi
Post PDU		Pressure: 3 psi

Table 3.19.1 Rev 7.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:

Thursday, June 23, 2022

Inspection Performed by:

Chris Carlson

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments	
PDT-720	V	Δ Pressure:	9 psi
PDT-730		Δ Pressure:	3 psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751 or (752))	V	CV@ 53.3%
Effluent Surge Tank (T-740)	~	Level: 40%
Effluent Discharge Rate (FT-770)		32.2 gpm @ 0659
POTW Line Pressure (PT-770)		32. (psi
Effluent Totalizer Reading (FT-770)	256,695,010 gal	Time: 0659
POTW MH17S-078 Discharge Check (Monthly)		Last Done: 6/20/22
4X8-Inch POTW Leak Detection Checks (Monthly)	V	Last Done: 6/70/22
4X8-Inch POTW Air Reliefs Checks (Monthly)	V	Last Done: 6 / 20/22
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	V.	Last Done: 5 / 18/22
2-Inch POTW Backup Pressure Testing (Annual)	V.	Last Done: 5/19/20 (6) 7/8/2/
2-In POTW Backup Air Reliefs Checks (Annual)	1	Last Done: 5 /19/20 (a)
2-Inch POTW Isolation Valve Exercise (Annual)	V	Last Done: 5/19/20
Rotate Chiller Compressors	NA on Standby	Now in Lead: Por 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: 0 %
LEL Sensor Calibration / Automatic High	Last Completed: 6/23/12	Plant Effluent Suspended:
LEL Shutdown Test (monthly)	Tokay 6/23/22	1045 ++ 1110
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.600 volts(monthly)	Adjustment Needed: Oor N W451.49
Verify Bridge Current between 300v-360v	Reading:0.330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time : 0819 - 0824

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20083914	(FT-505) LFG Cond. to T-530	223651
(FT-025) NBBW Influent	96069882	(FT-113) Ion Exchange Influent	1454038
(FT-012) MW-38 Inf. to HMR-30	9809305	(FT-056) Off - Site N. End Influent	46103888
(FT-042 HMR30) MW-38 Source to HMR-30	35484	(FT-810) Plant Potable Water In	30094692
(FT-043) MW-38 to RWST	3129549	(FT-026) NBBW Bypass to RWST	4581722
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8322951
(FT-012T) MW-38 to T-540/541	8704445	(FT-035) NTES Inf. to BIO	6827667
(FT-040T) MW-38N to T-540/541	1981567	(FT-035T) NTES to T-530	470881
(FT-041T) MW-38S to T-540/541	2700478	(FT-017) BIO Inf. from T-530	667979
(FT-042T) MW-38 Source to T-540/541	4094323	(FT-018) T-540/541 Influent	8747547
(FT-055) On - Site N. End Influent	102410902	(FT-352) T-352 to HMR-30	1388675

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, June 23, 2022

Inspection Date:

	Comments
6 o °F (Analog Gauge)	Outside Temp.: ~ 86 °F
2,000 Hour service date: 2/3/22 Serviced @ 62921 Hours	Coolant present in sight glass: \(\forall \) / N Next service @ 64921 Hours Current Hours @ 64680
31 %	00/000
	Date Last Changed: 2/7/21
Manually Activate(weekly)	Excessive Moisture: Y / (N)
	5
	Both cool to touch: (Y) / N
Last Done: (Blows clown frequently	Moisture at Receiver Tank: Y / N Run at max speed by bleeding air from filter
6/23/22	canister above/after air dryer for 2 hrs
Status	Comments
V	
PH	
Status	Comments
V	GC # checking UV-Ox Effluent: (
!	
	T
Status	Comments
Status	Comments Date inspected: 5/23/22 Checked and Flushed- All OK: Y)/
The same of the sa	Manually Activate(weekly) VOK ECO ON Dut has warning Last Done: (Blows clown frequent) Status

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 23, 2022
Inspection Performed by: Chris Carlson

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	2014
T-510 Pumps					
P-3301	V	1.44	35.8%	7	
P-3301A	58	_	- %	-	
NTES Pump 2000 (10R)	12/	0.48	47%	P035 P03	8 Globules Observed at TP-130: Y / Time: OSOS
T-530 P-005	513		-%		
T-540/541 P-006	~	0.30	43 %	6	Excel to P-006 Flushed V-segres e Mot
LFG COND Auto-Traps	~	0.00	NA	4	Between Cycles: (1) N 6/22/22
Reactor Feed Pumps					
P-3321	V	2.02	50.4%	3	
P-3322	V	2,80	45.1%	5	
P-3323	543		~ %		
P-3324	05	2.02	39.1%	5	
Reactor Effluent Pumps					
P-3341	V	1,78	58.5%	16	
P-3341A	13		%		

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3/16/22
B-3331	V	4.25	154	6/2022	Greased, Belt and Filter Checked: 0 / N
B-3332	58	_		1	Belt and Filter Checked: Y / (N)
B-3333	V	4.25	152		Greased, Belt and Filter Checked: () / N
B-3334		4.05	141	V	Greased, Belt and Filter Checked: (Y) / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	V	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	V	
VTP-3350	V.	PID Reading: 31.8 PPM
VTP-3360		PID Reading: 30.0 PPM

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 23, 2022
Inspection Performed by:	Chris Carlson

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	د Level: ۲۷ %	Last Cleaning (As needed, if 2" of solids accumulate): 42/15/19@ 7/14/21
T-530 LFG Condensate / NTES Tank	Level: 32%	
T-530 Mixer	V	
LFG Condensate Conveyance Line	~	Last Pressure Test: 7/19/21 Next: 7 2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 35% & 39 %	
T-540/541 Mixers	V .	
Chiller	offline	Chiller Coolant Lvl: ~ NA " Below full mark
Chiller Cooling Fins (as needed)	offline	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	V	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank		Last Back Flushing (Quarterly): 5 12122
T-3310 Sedimentation Tank	Visual Level: 0 Kqy	Last Cleaning (As Needed, use TSS info to determine): 42/2017 4 9/2021
T-3320 Blend Tank	✓ Level: 70 %	Last Cleaning (Semi Annual): 9 (0 2)
T-3331 Reactor No. 1		Digital Displays: GOOD Needs Attn
T-3332 Reactor No. 2	-	Digital Displays: GOOD Needs Attn
T-3333 Reactor No. 3		Digital Displays: GOOD Needs Attn
T-3334 Settling Tank	V .	Last Cleaning (Semi Annual): 9(16/2)
P-3334 Biosolids Pump		
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	V	3.91 gpm @ 0949
Building Containment Sump		Last Alarm Test Date (Monthly): 6 (23 (72

E. CHEMICAL FEED SYSTEM

Item	Status	Comments
Phosphorous Supply	V .	Bags: ~9.5 Gallons: ~ 95
Phosphorous Pump (P-2221)		
Caustic Supply	V	~ 155 Gallons
Caustic Pump (P-2211)	SB	Currently in acid addition mode
Acid Supply		~ 40 Gallons
Acid Pump (P-2211)		
Caustic Pump (P-2231)	✓ Leaks: Y	Last tubing tip cleaning (monthly): 6/16/22
Caustic Pump (P-2232)	✓ Leaks: Y	
Caustic Pump (P-2233)	Leaks: Y	Last tubing tip cleaning (monthly):

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 23, 2022	
Inspection Performed by:	Chris Carlson	

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments
pH-3320 Blend Tank	Today 6/23/22	Cleaned & Calibrated Fork 500
pH-3331 Reactor 1		7
pH-3332 Reactor 2		
pH-3333 Reactor 3	V	V

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	V	
Automatic Backwash	Cycle Count: (8	
BF-3340 a/b Differential Pressure	PSI: 3011 C. 1.861M	20 pri lipsi
75-micron Bags Last Cleaning	Date: 111419	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date:	
GACF-3340 Status		
GACF-3340 Differential Pressure	PSI: 10 psi e 486pm	
Last Backwash Performed	Date: 6/16/02@ 4/	29/22

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments
"BIO" Backup Generator	√	Block Heater: On OK / Off Warm Out
Electrical Surge Suppressor	√	
Motor Control Center	/	
PLC		UPS @ /31 min / 2 Events
HMI's	V	
BTS Process KWH Meter	1900 Z35 KWH	Time: 0935
Building#2 KWH Meter	544/551 KWH	Time: 0935

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V .	GC # checking BIO: 2
Alarms Enabled	V	
GC Influent Filters	1	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 23, 2022
Inspection Performed by:	Chris Carlson

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6805218	
FT-3324 Feed Spare	536567	
FT-3322 Feed to Reactor 2	11867824	
FT-3323 Feed to Reactor 3	1070773	
FT-3301 T-510 to BIO	52358772	
FT-3341 BIO Effluent	67432593	
FT-3342 BIO Recycle	56953584	

K. SAFETY

Item	Status	Comments
Building #2 Fire Extinguishers		Inspection date: 5/23/22
Building #2 Eye Wash/Shower	V	Checked and Flushed- All OK: (Y) / N

L. OTHER COMMENTS:		20		
10 1000	334400000.00	The state of the s		

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022	
Inspection Performed by:	Mike Gelwick	

A. PERIMETER COLLECTION SYSTEMS

Item	Status	Comments	
LFG Cond Automatic Trap CT-1	Sump Level: 12,80	Counter: 202424 Cycles: (83	
LFG Cond Automatic Trap CT-2	Sump Level: 8.69	Counter: 285390 Cycles: 856	
LFG Cond Automatic Trap CT-3	Sump Level: 7.32	Counter: 339 903 Cycles: 645	
CT-4 Containment/Vessel (LFG Cond)	✓ Level: 32 %	Tank Level: 3.37 Counter: (91353 - Cycles: 39 Sump: 8.62	
PM-15 Containment / Vessel	✓ Level: 66 %		
MW-51 Containment / Vessel	✓ Level: 20 %		
PM-11 Containment / Vessel	✓ Level: 15 %		
MW-38 Systems	V		
North Toe System	/		
North End Systems (Weekly)	1		
Full N. End Systems Check (Monthly)	Last Done: 6-29-22		
North End Pipeline(s)Flushing (As Needed)	V	Perform if suspended solids present Last Done: 11/15/15	
NTES line flush to T-530 (As needed)	~	Perform if suspended solids present Last Done: 10/29/21	
NTES Piping Containment	~	Monthly Sump Level: 47 21607 Date: 6-20-62	
North Boundary System P-001:	CV69.6 % @ 6.8 gpm	37.68 Hz / 2,03 Amps. / vault psi @ 18/100 lenes	
T-101 & T-102 Containment / Tank	_	Levels: 39 % & 36 %	
Raw Water Storage Tanks Piping	_		
RWST Building Temp. (TT-101)	72.6 °F	Outside Temp.: ~ 80 °F	
(P-121)or P-122	~	2,0 gpm/CV 51 %	
RWST 2ndry Cont. High Level Switch	(LSH-101) Last Test(monthly): 6.20-22		
RWST Back-Up Generator		Last Test Run(monthly): 6-20-22	

B. CHEMICAL STORAGE BAYS

Item	Status	Comments
Caustic Tote Levels		~415 Gallons Reserve = 240445
Caustic Bay Heater		OFF womas
Peroxide Tote Level	/	~ 250 Gallons Reserve = 255,20
HCL Tote Levels	1	~ 165 Gallons Reserve = 1+0% +3074
Chemical Totes and Piping Inspected	1	Leaks observed: Y / P
Emergency Shower Inspected	7	Checked and Flushed - All OK: V / N

C. PRIMARY AND SECONDARY ACID FEED SYSTEM

Item	Status	Comments		
Primary Acid Feed Pump (P-631)				
Ion Exchange Acid Feed Pump (P-632)		PI-0632 PSI: 5 Y	CV: 3 %	5
Primary Acid Retention Tank (T-510)				
All Acid Feed Lines		Leaks observed: Y	/ (N)	

D. NBBW INJECTION TRENCH

Item	Status	Comments
Injection Carbon (GAC-810)	OFFLINE	Date online: 7/20/18
Injection Rate (FT-800)	0.0 gpm	NBBW-IW-1= 0.0 NBBW-IW-2= 0.0 NBBW-IW-3= 0.0 gpm ea.
Totalizer Reading (FT-800)	105,135,774 gal	INJ. STOPPED 10/02/18 @ 1545

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022	
Inspection Performed by:	Mike Gelwick	

E. CHEMICAL PRECIPITATION SYSTEM (US FILTER HMR-30)

Item	Status	Comment
T-300A Mixer	NA	
T-300B (Caustic Mixer)	~	Last Cleaning (Qtrly): 4-7-22
T-300A/B Water Level	/	
T-300B (Caustic Mix Chamber)		Last Cleaning (Qtrly): 4-7-27
T-300A/B Overflow	/	
pH Set-point for (pH 315)	Value: 10.8	
pH 310	Value: 6.68	
pH 315	Value: 10-62	
Flocculation Chamber Paddle Wheel	~	
Precipitate Floc Quality	~	Good
Clarifier Water Quality		Oil or sheen observed: Y / N
Clarifier Effluent Piping / Water Level		
Clear-well Chamber and Water Level		
HMR PLC Panel	~	
Caustic Pump (P-270)	SB	
Caustic Pump (P-280)	V	
Polymer Pump (P-310)	~	
Polymer Tank Mixer	~	
Polymer Tank Level	Gallons: ~530	
Clear-well Transfer Pumps(P-371) 372)		
Sludge Transfer Pump (P-330)	_	Exercise Valves Weekly: Total Street School
Manual Sludge Lateral pumping		Last done (As Needed): プーバーここ
Manual Sludge Lateral Ball Valves		Exercise Weekly: 411 64
Automatic Blow-down Operations	/	

F. pH PROBES

pH Probe Location	Calibration Date	Comments: (Time done)
pH-310 HMR-30 (T-300A)	6-30-22 yaday	1408
pH-315 HMR-30 (T-300B)		
pH-365 Primary Acid Ret. Tank		
pH-113 Pre-Ion Exchange		
pH-670 Pre-UV-OX		1990
pH-740 Discharge Surge Tank	V	Discharge suspended: 140 ←► 140
Out of Hold Double Check		None in hold:
Valves Back to Normal Position		All OK: _ v d us

G. SLUDGE THICKENER, SLUDGE HOLDING TANKS, FILTER PRESS* Grease THICKENER MOTOR BEALTH, July #

Item	Status	Comments
Verify Sludge Thickener Running	/	Gauge Reading: 9 %
Sludge Thick. Transfer Pump (P-350)	V	
Sludge Holding Tank (T-351)	V	Level:~ 45 %
Sludge Holding Tank (T-352)	2	Level: 41 %
Decant Transfer Pump (P-352)	86 V	CV64 % @ Sgpm
Filter Press Pumps (P-381 / P-382)		P.382 Meets cleaning / SERA
Filter Press		Stage: PUI

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022
Inspection Performed by:	Mike Gelwick

H. ION EXCHANGE

Item	Status	Comments
Feed Tank (T-113)	Level: 30 %	
Feed Pump (P-114)	✓ Operating Press: 33.0 psi	CV@ 65 % @ 1.68 gpm
Retention Tank (T-114)	✓ Operating Press: 3 ≥ psi	pH-113 @ 3, 83
Bag Filter (BF-113)	✓ Operating Press: 35 psi	
Ion Exchange (Cage (Dor 2) + Guard	✓ Operating Press: 25 psi	Columns 45+6 + GANNA eNline
Post Ion Exchange	Operating Press: 3.0 psi	

I. FEED SURGE TANK

Item	Status	Comments
Feed Surge Tank (T-520)		Last Cleaning (As Needed, if 4" of
	✓ Level: 35 9	6 solids accumulate): 12/15/19
Feed Surge Pump (P-521 or (P-522)	Operating Press: /4	osi CV@ 56 % @ 25.9 gpm
T-520 to GAC Total (FT-675)	262847728	gal Time: //48
North End On-Site Pumping	Operating Press: 2-3	osi /2.6 gpm @ 1/43
North End Off-Site Pumping	Operating Press: 2-6	osi 8.6 gpm @ /143
Peroxide Feed Pump (P-680)	~	SPD 1.9 % / RATE 0.5
Peroxide Conc. At (TP-710)	(O PPN	1
Peroxide Conc. At (TP-740)	0.0 PPM	1

J. HAZARDOUS WASTE STORAGE

Item	Status	Comments
180 Day storage area check	/	Check sheet completed: UM/Emily
Satellite Haz. Waste Areas (BLDG #1)		Condition: Ix sampleon + man Good
Satellite Haz. Waste Area (BLDG #2)		Condition: 6250

K. UV-OXIDATION SYSTEM * New power couldness cooling than proposally today &

Item	Status	Comments
UV-Oxidation System	· *	OFF DURING THE DAY HORY FOR NEW FRON THEFAN
Annual Test Run (Calgon)	Date: 9-16-21	Next: 9-2022
Quarterly Test Run	Date: NA/Lunaras	Next: NH/Lunning
Peroxide Feed Pump (P-650)		Flow Rate: ~ > 0 cc/min.
UV-Ox Power		27.83 kVA 2637 Volts 10.5 Amps
Lamp Hours	2355 Hrs	
Crystal Condition & Wiper Status	٣	Oiler status: o4
UV-OX Bagfilters Status	Last change: 3-4-22 Cleaned: 3-4-22	10 psi In 11 psi Out
UV-OX Feed Pump ((P-600) or P-601)	V	CV@ 66 % @ 6.9 gpm
UV-OX Temperature	In(TT-670): /9.5 °C	Out(TT-710): 33.4 °C
PDU GAC (PDT-710)		Δ Pressure: Z psi
Peroxide Concentration Pre UV	(00 PPM	
Peroxide Concentration Post UV(TP-720)	ZS PPM	
Peroxide Conc. Post PDU (TP-730)	O∙• PPM	
Secondary Acid Feed Pump (P-630)		CV @ 0 %
Secondary Acid Retention Tank (T-645)	·	
Pre – UV Oxidizer Total (FT-670)	723838(6 gal	Time: 1(49
Post UV-Ox / Pre PDU	~	Pressure: / 2 psi
Post PDU		Pressure: 7 psi

Table 3.19.1 Rev 7 WTP.docx

Tables - 113

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date: Thursday, June 30, 2022

Inspection Performed by: Mike Gelwick

L. PDU AND LIQUID -PHASE GRANULAR ACTIVATED CARBON

Item	Status	Comments	
PDT-720		Δ Pressure: 8	psi
PDT-730	V	Δ Pressure: ζ	psi

M. EFFLUENT DISCHARGE

Item	Status	Comments
Effluent Surge Pump (P751) or P752)	~	CV@51.7 %
Effluent Surge Tank (T-740)		Level: 40 %
Effluent Discharge Rate (FT-770)		25.4 gpm @ 114L
POTW Line Pressure (PT-770)	/	31,3 psi
Effluent Totalizer Reading (FT-770)	257028 232 gal	Time: 1149
POTW MH17S-078 Discharge Check (Monthly)	-	Last Done: 6-20-22
4X8-Inch POTW Leak Detection Checks (Monthly)	-	Last Done:
4X8-Inch POTW Air Reliefs Checks (Monthly)		Last Done:
4X8-Inch POTW Isolation Valves Exercise (Qtrly)	/	Last Done: 5-18-22
2-Inch POTW Backup Pressure Testing (Annual)		Last Done: 7/8/21
2-In POTW Backup Air Reliefs Checks (Annual)		Last Done: 7/8/21
2-Inch POTW Isolation Valve Exercise (Annual)		Last Done: 7/8/21
Rotate Chiller Compressors	NA on Standby	Now in Lead: 1 or 2

N. LEL EFFLUENT TANK T-740

Item	Status	Comments
LEL-740 Sensor		Reading: \ %
LEL Sensor Calibration / Automatic High LEL Shutdown Test (monthly)	Last Completed: 6-23-22	Plant Effluent Suspended:
LEL Sensor Bridge Adjustment to 2.0 volts	Reading: 2.00 volts(monthly)	Adjustment Needed: Or @ 21.99
Verify Bridge Current between.300v360v	Reading: •-330 volts(monthly)	

O. WTP INFLUENT TOTALIZERS Time: 1150-1154

Source	Reading(Gallons)	Source	Reading(Gallons)
(FT-015) RWST Influent	20093834	(FT-505) LFG Cond. to T-530	274029
(FT-025) NBBW Influent	96134367	(FT-056) Off - Site N. End Influent	46192440
(FT-012) MW-38 Inf. to HMR-30	8821745	(FT-113) Ion Exchange Influent	1471046
(FT-042 HMR30) MW-38 Source to HMR-30	35 484	(FT-810) Plant Potable Water In	30095936
(FT-043) MW-38 to RWST	3129802	(FT-026) NBBW Bypass to RWST	4585914
(FT-042 RWST) MW-38 Source to RWST	72236	(FT-014) Misc. Water to RWST	8330685
(FT-012T) MW-38 to T-540/541	8714222	(FT-035) NTES Inf. to BIO	6832312
(FT-040T) MW-38N to T-540/541	1981567	(FT-035T) NTES to T-530	471104
(FT-041T) MW-38S to T-540/541	2700478	(FT-017) BIO Inf. from T-530	668024
(FT-042T) MW-38 Source to T-540/541	4104100	(FT-018) T-540/541 Influent	8150471
(FT-055) On - Site N. End Influent	102539013	(FT-352) T-352 to HMR-30	1390993

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Thursday, June 30, 2022

Inspection Date:

O Hour service date: 2-7-23 viced @ 62921 Hours	
viced @ 629zı Hours	Coolant present in sight glass: 🎾 / Next service @ 64421 Hours
viced @ 629zı Hours	S Next service @ 64921 Hours
0 %	
17 (2 noi	
re psi	
	Date Last Changed: 2-7-22
nually Activate(weekly)	Excessive Moisture: Y / W
	42
~	Both cool to touch: Ø / N
CO ON butter warms 475+0	Moisture at Receiver Tank: Y / N
t Done: 6-23-22 (Glourtal a	
V	∤o ₿ psi
hue	Comments
	Comments
tus	Comments
	GC # checking UV-Ox Effluent: # (
/	ec-cultivation + major 6-29-22
tus	Comments
_	Date inspected: 6-27-22
	Checked and Flushed- All OK: 0 /
	tus

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022
Inspection Performed by:	Mike Gelwick

A. PUMPS

Item	Status	Flow Rate (gpm)	Pump Speed (CV%)	Discharge Pressure (psi)	Comments
T-510 Pumps					
P-3301	/	1.83	41.8 %	7.0	
P-3301A	56	-	- %	-	Drive wand as
NTES Pump P-002(Sump) / P-002W(10R)	~	0.47	48 %	P035 P038	Globules Observed at TP-130: Y / N Time: (110
T-530 P-005	~	0.20	32 %	8	
T-540/541 P-006		0.19	41 %	6	
LFG COND Auto-Traps	-	0.0	NA	5.0	Between Cycles: Ø / N
Reactor Feed Pumps		2.20			
P-3321	/	2.32.	51.2 %	3.5	
P-3322	~	3.01	47.7 %	5.0	
P-3323	58	-	- %	_	
P-3324	~	2.20	43.8 %	5.0	
Reactor Effluent Pumps					
P-3341	~	2.09	56.2%	16	
P-3341A	SA	_	- %	-	

B. BLOWERS

Item	Status	Pressure (psi)	Temp (°F)	Next Scheduled Service (Qtrly)	Comments Last serviced on: 3-16-22
B-3331		4.24	156	SOON/TORNOW	Greased, Belt and Filter Checked: 60 / N
B-3332	58	1	~		Belt and Filter Checked: Y / 🕥
B-3333	~	4.26	150		Greased, Belt and Filter Checked: Ø / N
B-3334	-	3.98	138	V	Greased, Belt and Filter Checked: 🔌 / N

C. REACTOR VENTILATION

Item	Status	Comments
Vapor Carbon Contactor	V	On-line: 2/10/18
Reactor Vent Blower	V	
Reactor Vent Booster	/	
VTP-3350		PID Reading: 65.7 PPM Presh Serec
VTP-3360	/	PID Reading: 28.2 PPM + aug

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022
Inspection Performed by:	Mike Gelwick

D. TANKS / REACTORS / SUMPS / CONTAINMENTS / PIPING / Chiller

Item	Status	Comments
T-510 Post HMR-30 Mixing Tank	レ Level: 62 %	Last Cleaning (As needed, if 2" of solids accumulate): 7/14/21
T-530 LFG Condensate / NTES Tank	✓ Level: 41 %	
T-530 Mixer	~	
LFG Condensate Conveyance Line	~	Last Pressure Test: 7-19-24 Next: 7-2022 (Annual at a minimum or if flow drops off)
T-540/541 MW38 Tanks	Lvls: 85 % & 87%	
T-540/541 Mixers	~	
Chiller	Offline	Chiller Coolant Lvl: ~ N + " Below full mark
Chiller Cooling Fins (as needed)	offere	Last Cleaning: 4/20/18 (unit on Standby)
Secondary Containments	~	Heat Trace: On OK / Off Warm out
Feed Piping to Sedimentation Tank	/	Last Back Flushing (Quarterly): 5-12-22
T-3310 Sedimentation Tank	Visual Level: ok	Last Cleaning (As Needed, use TSS info to determine): 9/2021
T-3320 Blend Tank	∠ Level: 71 %	Last Cleaning (Semi Annual): 9-10-21
T-3331 Reactor No. 1	V	Digital Displays: GOOD / Needs Attn
T-3332 Reactor No. 2		Digital Displays: GOOD / Needs Attn
T-3333 Reactor No. 3	~	Digital Displays: GOOD / Needs Attn
T-3334 Settling Tank		Last Cleaning (Semi Annual): ターレーン
P-3334 Biosolids Pump	/	
T-3340 Overflow Tank	✓ Level: 30 %	
Recycle Valve to Blend Tank	V	3.98 gpm@/2/3
Building Containment Sump		Last Alarm Test Date (Monthly): 6-23-22

E. CHEMICAL FEED SYSTEM

Item	Status	Comments	
Phosphorous Supply	V	Bags: ~8.5 Gallons: ~ 80	
Phosphorous Pump (P-2221)	<u></u>		
Caustic Supply		~ /20 Gallons	
Caustic Pump (P-2211)	SB	Currently in acid addition mode	
Acid Supply	_	~ 40 Gallons	
Acid Pump (P-2211)	/		
Caustic Pump (P-2231)	Leaks: Y / W	Last tubing tip cleaning (monthly): 6-16-22	
Caustic Pump (P-2232)	Leaks: Y / 🕏	Last tubing tip cleaning (monthly):	
Caustic Pump (P-2233)	Leaks: Y / 🚱	Last tubing tip cleaning (monthly):	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022
Inspection Performed by:	Mike Gelwick

F. pH Probes

pH Probe Location	Calibration Date (Monthly)	Comments Stray 6 Pt Clean today	
pH-3320 Blend Tank	6-23-22		
pH-3331 Reactor 1	1	1	
pH-3332 Reactor 2			
pH-3333 Reactor 3	V	V	

G. FILTER SYSTEM

Item	Status	Comments
BF-3340 a/b Status	~	
Automatic Backwash	Cycle Count: / 9	20/17 22. Byen Lyse T
BF-3340 a/b Differential Pressure	PSI: 3	20/17 2 2.84m
75-micron Bags Last Cleaning	Date: 1-14-19	
75-micron Bags Last Inspection	Date:	
75-micron Bags Last Changed	Date: 🗸	
GACF-3340 Status	/	
GACF-3340 Differential Pressure	PSI: //	17/6 22,8000
Last Backwash Performed	Date: 4-29-22	

H. ELECTRICAL AND INSTRUMENTATION

Item	Status	Comments		
"BIO" Backup Generator	~	Block Heater: On OK / Off Warm Out		
Electrical Surge Suppressor	/			
Motor Control Center	~			
PLC	r	UPS @ /30 min / 8 Events		
HMI's	/			
BTS Process KWH Meter	1902256 KWH	Time: /237		
Building#2 KWH Meter	5444513 KWH			

I. GAS CHROMATOGRAPHY

Item	Status	Comments
GC Operational	V	GC # checking BIO: #2
Alarms Enabled	-	cc-californian + major 6-29-22
GC Influent Filters	/	

WEEKLY OPERATIONS AND MAINTENANCE INSPECTION CHECKLIST

Inspection Date:	Thursday, June 30, 2022	
Inspection Performed by:	Mike Gelwick	

J. TOTALIZERS

Item	Readings (gallons)	Comments
FT-3321 Feed to Reactor 1	6828110	
FT-3324 Feed Spare	559265	
FT-3322 Feed to Reactor 2	/1899615	
FT-3323 Feed to Reactor 3	1070773	
FT-3301 T-510 to BIO	52380367	
FT-3341 BIO Effluent	67461916	
FT-3342 BIO Recycle	56995546	

K. SAFETY

Item	Status	Comments	
Building #2 Fire Extinguishers	~	Inspection date: 6-27-22	
Building #2 Eye Wash/Shower		Checked and Flushed- All OK: (/ N	

. OTHER COMMENTS:	

Date: Sunday, 1/2/22			
1230 Plant operations good.			
1250 Decarit T-351 to bottom valve. Net well activate	ed water is clear no		
COLOR)		
Check TP-130 for oil globules: none obse	erved Water is very		
clear with yellow- green tint.			
Clean pH-315 probe with acid solutions.	Check HMR-30		
	down weir.		
1310 Footed 3,5 # TSP and 35 gal water 400 p	shosphorus tank.		
1430 Both 6Cs operational within limits.			
a 1500 Plant operations good.	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		
@ 0650 Check plant renotely - All Ukay.			
(a) 2030 Check plant remotely - All okax.			
(W) 1/1/22 0950 check plant remotely-All okay.	2 0950 check plant remotely-All okay		
(a) 1/1/22 2130 Check plant remotely - All okay.			
	Influent Sources and Flow Rates: @ 1245		
	NBBW - 6.4 apm		
	N. END ON-SITE - 11,9 gpm N. END OFF-SITE - 8,7 gpm RWST - 0,6 gpm		
	NTES -0.52 9FM COND/NTES T-530 - 0.0 gpm (6AM-1PM		
	daily) MW38 - 4, 0 gpm		
	T-540/541 - O. 01 gpm		
	MW113 Area – 1, 9 gpm		

operator(s) Manuela Seewald

		January 03, 2022		
Time:	0535	Plant operations good. Propore for guarterly M7-001 plant effluent so	empling. Rinse dedicate	
	composite containers, and preservitive program and colibrate volume per sample			
Time: 0535 Plant operations good. Prepare for quarterly MP-001 plant effluent sampling. Rinse of composite containers, and preservitive, program and collibrate volume per so on autosamplers.				
	0645	0645 Restart Filter press on T-351		
	0740 Blow Cours open from a good			
	0800	Mike starting both auto samplers for 24hr Flow paced sampling. Efflue	at totalizer reading	
		Mike starting both auto samplers for 24hr Flow paced sampling. Effluent 248,826,394 gallows, effluent Flowrate e 31-5 gpm and effluent 6.81 e 15.7°c.	t tank pH resching	
	1050	- Begin attly Early warning stompting. TOTAL Molybdenum, VOC3 + Low land 1, 4 from an an Aux.		
	1140	- Clean pH - 315 probe we Act Solution. Check THE HANDS O FOR OA Or SHEER: None asserted Spray Down wer.		
		- Check TP-130 For oil globules: None observed. water B very clear w/ yellow your work.		
	1150			
-	1200 - collect 1st set of timepaced grab samples 2 MP-001 sample port For Low-Level 1, 4-Brokane, voci and Nony phanols. place Samples on Fridge. 1217 - IX System performance HACH Testing with Lab split samples After 1,025,057 gal treated; TP-183 2 180 yg/K; TP-174A 2 290 yg			
700				
		TP-173A 24600 y/1; TP-170 = 5600 y/1. Runny = 1.9, pm.		
	The second secon	- Begin fligh of MPON SAMPle port and checkfor desided chlorine: None setected.		
	1600	- collect 2rd set of time paced grub samples 2 mp ool sample port for Low-Level 1, 4. proxime, voc! + No.	Dy Amarols. Place spander In	
		fridación opers.	Influent Sources and Flow Rates: @ 0910 NBBW - 6.4 gpm	
	1605	- STOP FALMANSS. NOT QUILLAN YET. Plants oper Homes Good. Autistuples on trenck.	North End On Site- //, 9 gpm North End Off-Site - 6 5 gpm	
1945 Begin MP-001 pat flush and check for residual chlorine - none detected. RWST - O			RWST - 0.6 gpm	
2000 Collect 3 th Set of time paced grab samples for low-level 1,4-Diosane, VOCS; New y/ phone 15. Place MW38 T-540/541 - 0,3 gpt				
		samples in fridge.	MW38 N & S- 1.9 gpm	
	2345 Besin MP-00) port fluit and check for strictural chlorine - none detected. COND/NTES T-530- 0.2 gpm(6am-1pm daily)			
	0000	Collect 4th Set of time paced grab samples for low level 1.4-Diosare, VUCS (Many) phenols.	MW113 Area – 1.9 gpm	
		Place samples in Fridge.		

Operator: Mike Gelwick / Chris Carlson

Date:	Tuesday	, January	04,	2022
-------	---------	-----------	-----	------

Time:	0345	- Plants operations Good. At to SAMPLES OE. LESTALT FILTERPRESS on STAGE 4.		
0350 - Begin flighor mp-001 sample port and check for desidual chlorie: None Beteched				
	0400	- Collect 5th Set of time paced grub samples 2MP-001 sample port for Low-Level 1, 4-0,000 ane, vois + NONY/plends. Place samples IX Fringe		
0415 - Workingon weekly & T3 sampling and START EFFRENCY checks. Collect TP3340 GC/Lab SALTSAMPE.				
	0455 - Collect TP-730 GC/Lab Sp 47 5 Ample and TP-7 10 and TP-740 weekly Low-Level 1, 4-0,0 xene samples.			
		- START Frep for BTS weekly Freld Kendings.		
		Blowdown operations good.		
	0800	Shutdown autosamplers ofter 24hours and 46,288 gallows discharge. ESFL	unt totalize reading	
		248,872,682 gallows - Mike collecting 6th sct of Lime paced and saup	les exter a 10 min	
		Iluch of MP-001 and check for recidual other Chloring - nave detect	d Slowly stir both	
		composite confainers and check pH's. Sodium This sulfate preserved @ 7.51	(18,000 MI of sample)	
	composite containers and check pH's. Sodium Thiosulfate preserved C 7.51 (18,000 ml of sample) and Notice preserved Q 1.83 (26,000 mls collected) both one very clear, no color. Fill lab Notiles from composites and pack all for courier /shipment to labs. O820 Filty-press full. O840 Tom sending in manual level of the NBBW sump for level transducer calibration check DTW 1 ending 27.00' = GWE 5685.55', HME reading 5685.50', No calibration recoled			
	at this time.			
	1315	Begin Flushing fines from virgin GAC units using potable water.		
	1512	- Clean pH-315 probe UlArid Solution. Check the Hook 30 for oil or Siken; None as served. Spray pour war	Influent Sources and Flow Rates: @#345 NBBW - 6.4 gpm	
		- Check TP-130 For oil globules: None observed, water sveny clear w/ yellow green + mt.	North End On Site- 11.9 gpm	
	1520	Plunts operations Gusot.	North End Off-Site – 8.4 gpm RWST – 0.5 gpm	
		3	NTES - ひら! gpm(10R only) MW38 T-540/541 - か3シ gpm(Source	
			well and 38 pumping wells mix) MW38 N & S- 1.9 gpm	
			COND/NTES T-530- 2-0 gpm(6am-	
			1pm daily) MW113 Area – <i>I.</i> 9 gpm	

Operator: Mike Gelwick / Chris Carlson

Date: Wednesday, January 05, 2022 Time: 0550 Plant operations good. Start on weekly GC maintenance and calibrations.
0730 Blundown operations good. - Decant T-351 From bottom value wat well activated water Is clear nocodor. - Clean DH-315 probe w/ Acrd 5 olution. Check + the Home 30 for oil or 5 Hern: None conserved. Some obover weir. - check TA-130 For oil globules: None observed. Water 13 very clear w/yellow-grown trat 1230 Backup WTP data to DVD : Flack Wive. Daily ONE Drive backup nocking well.
1250 Continue on flushing fines from virgin GAL with potable water (fines sent to T-351) 1600 - Cate vessels purged of Carpon Frances. heady for protects. 1615 Phents open wors and. Influent Sources and Flow Rates: @2750 NBBW- 6.5 gpm North End On Site- //-9 gpm North End Off-Site - 2.7 gpm RWST - 0.6gpm NTES - 0.51 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source well and 38 pumping wells mix) MW38 N & S- ! - # gpm COND/NTES T-530- 0.2 gpm(6am-

Operator: Mike Gelwick / Chris Carlson

1pm daily)

MW113 Area - 1.9 gpm

Date: T h	nursday.	January	06.	2022
------------------	----------	---------	-----	------

Bato: Illaioa	ty, duridary 00, 2022					
Time: 064	10: 0645 - Plants opera mons Good. Goo to Check other site systems					
0700	- Automatic Blandown operations Good.					
0830						
	- ClempH-315 prohe V/Acid solverin Check +4K HM230 For offor speces: Noneobject. Spring Down warr.					
	- Check TP-130 For oilylobules: None osserved. water 55 very clear wy ellow guess that works					
	and culterappens today.	50 E.				
0900 - REKILL polymer frank W/2 CUPS OF NALCO polymer and ZOOgal of potable water, Drain down carson vessel we Flished		ardon vessel we Flushed himes from yestuday,				
	Into thewet well.					
//30	- Refill BB phosphors TANK w/6# of TSP and Gogal of potable water.					
/325	- Suspend plant Arscharge to calthrane pH-740 probe to 4+10 pH5105					
/333	- Lesume wormal Discharge. Construce with other pH probes calibrations to 4+10 pHSTB 2 pH-113, 670, 310, 315, 4365					
1420						
1500	- Plants aperatorns (acid.					
		Influent Sources and Flow Rates: @ OSUS NBBW - 6 - 4 gpm North End On Site- 11-9 gpm North End Off-Site - 8 s gpm RWST - 2 s gpm NTES - 2.53 gpm(10R only) MW38 T-540/541 - 2.31 gpm(Source				
		well and 38 pumping wells mix) MW38 N & S- 1:9 gpm COND/NTES T-530- 0:20 gpm(6am- 1pm daily) MW113 Area - 1:9 gpm				

Operator: Mike Gelwick / Chris Carlson

Date: Friday, January 07, 2022

Time: 0745 - Plants againstras Good. Contry and alternative without againstra Good. 6830 - Gecard F-351 In bottom white. With will activitized without 5 clear notation. Radius \$1352 decedium to 0.502 pm. - Clear prists price without solvents. Check the HHHSD for of an Steen is unaddered. Sating forward without. - Clear prists price without solvents. Check the HHHSD for of an Steen is unaddered. - Clear prists price without solvents. Check the HHHSD for of an Steen is unaddered. - Clear prists price without solvents. Check the HHHSD for of an Steen is unaddered. - Clear prists price without solvents. - Clear prists price without solvents. Check the HHHSD for of an Steen is unaddered. - Clear prists price without solvents. - Clear price price without solvents. - Clear prists price without solvents. - Clear prists price withou				
-Clear Ph. 35 probe withinks every assured. Check the Holds of Far of a street in an adstruct. -Check PP-130 for of yelothes; None assured. Check the Holds of Early Clear will yolkow-green treet. O910 "worken filternass & moky. 10 45" -START workers as keeping the Sirker 2" despreage of 1300" -Torn working on washers of filternass 1315 - Plants appearating Grant. Influent Sources and Flow Rates. @ O800 NBBW - 6-4" gpm North End Offset, a gpm OND/NORTH End Offset, a gpm OND/NORTH End Set of a gpm North End Offset, a gpm OND/NORTH End Set of a gpm O	Time:	0745	- Plant operations Good. Coming out at Automaticloudown operations Good.	
- Check PP-130 for off-februs; from aggreral. waspers Very clear of yokeon-grans protes (PVC - Worker Filterans & Body. (1045 - STRETWORKING BY STREET Z "Grafter purp) 1300 - TOM wis reing on wasper of filterans. 1315 - Plants againstrug Good. Influent Sources and Flow Rates: @ QQO NBBW - L. + gpm North End Off-Site - 42 gom North End Off-Site - 42 gom RWST - a Le gpm North End Off-Site - 42 gom RWST - a Le gpm North End Off-Site - a 2 gom/Source well and 38 pumping wells mix) MY38 NS - 1-9 gpm CONNINES F-300 - 21 gpm/sam- tym daily) MY38 NS - 5-0.21 gpm/sam- tym daily)	P	0830	- DECENT T-351 TO bottom value. Wetwell activated water 13 clear mocolor. Reduce P-357 steenson t	0.50gpm.
- Check PP-130 for off-februs; your agrand. waspes Very clear of yokow-gran protes 1045 - State working on leading At 8 side & 2 "Graphing purps 1300 - TOM wis raing on waspes of of the plants 1315 - Plants agranting Good. Influent Sources and Flow Rates: @ QQO NBBW - 6 -4 gpm North End Off-Site - 4 gpm North End			- Clean PH-315 probe withink solveron. Check THE HARRED For of or Steen: wone observal. Spray Down wer.	
OPRO WORKER FIlterans Empty, 1045 - STHETWORKIN ON LEGILING MY SINGLE Z'GINDOW DIMO 1300 - There wis only on was now of filterans 1315 - Plants optimizing on was now of filterans 1315 - Plants optimizing Good. Influent Sources and Flow Rates: @ Ogo NBBW - 6-4' gpm North End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm) NORTH End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm) NORTH End Off-Site - 6-1' gpm NIES - 6-4' gpm (North End Off-Site - 6-1' gpm) NORTH End Off-Site - 6-1' gpm NORTH End Off-Site -				
1300 Tom working on washest of filterbass 1315 - Plants operations (and) Influent Sources and Flow Rates: @ 0800 NBBW - 6.4 gpm North End Offsite - 6.7 gpm (only) MW381-540/641 - 0.32 gpm(080 mix) MW381-540/641 - 0.		0910		
Influent Sources and Flow Rates: @ Ogo NBBW - 6.4 gpm North End On Site - 1.4 gpm North End On Site - 1.4 gpm RWST - ο ω gpm RWST - ο ω gpm NTES - ω ω gpm NTES - ω ω gpm NMS - ω ω gpm NMS - ω ω gpm NTES - ω ω gpm		1045	- STHAT WORKING ON LEGITING ALL SITEST Z" D'a prum prums	
Influent Sources and Flow Rates: @ Ogo- NBBW — 6.4 gpm North End On Site 1.1.9 gpm North End Off-Site — 6.7 gpm RWST — 6.4 gpm NTES — 6.4 gpm(North) MW35 T-540541 — 6.3 gpm(Source) well and 36 pumping wells mix) MW38 N & S - 1.4 gpm COND/NTES T-530-6.21 gpm(Sam- 1pm dally)		1300	- TOM working on washout so followings	
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)	555	1315	- Plants operating Grown.	
NBBW - 6.4 gpm North End On Site- 11.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T-540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				
NBBW - 6.4 gpm North End On Site- //.9 gpm North End Off-Site - 8.7 gpm RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T - 540/541 - 0.3 z gpm(Source well and 38 S-1.9 gpm MW38 N & S-1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)		-		
North End On Site- 11.9 gpm North End Off-Site − 6.1 gpm RWST − ∞ ∞ gpm NTES − ∞ ≤ 4 gpm(10R only) MW38 T-540/541 − 0.3 z gpm(Source well and 38 pumping wells mix) MW38 N & S − 1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				Influent Sources and Flow Rates: @ ⊘g∞ NBBW – 6.4 gpm
RWST - 0.6 gpm NTES - 0.54 gpm(10R only) MW38 T-540/541 - 0.3 z gpm(Source well and 38 pumping wells mix) MW38 N & S - 1.9 gpm COND/NTES T-530- 0.21 gpm(6am-1pm daily)				North End On Site- //, 9 gpm
MW38 T-540/541 − 0.3 z gpm(Source well and 38 pumping wells mix) MW38 N & S− ∤, 9 gpm COND/NTES T-530- 0.2 l gpm(6am-1pm daily)				RWST – o⋅o gpm
MW38 N & S− / , 9 gpm COND/NTES T-530- ◊-21 gpm(6am- 1pm daily)				MW38 T-540/541 - 0.3 z gpm(Source
COND/NTES T-530- 221 gpm(6am-1pm daily)				
MW113 Area – 1, 9 gpm			Fig. 1	COND/NTES T-530- 0.21 gpm(6am-
				MW113 Area – <i>I</i> , 9 gpm

Operator: Mike Gelwick

Date: Swiday,	January 09, 2022	
0845	-Plant operations good	
0955	- Decant T-351 from bottom value. Wet well activated. Water is very clear no color	
	- Check TO-130 for oil globales: None observed water is very clear of yellow that	
	- clean DH-315 probe of Acid Solution. Check HMR30 for oil or sheems: none observed	: Sprayed down we'r
1000	- Filled Phosphorus tark w/ 55 gallons 5.5 LBs TSP	•
1030	- Plant operations good	
1/8/22 0800	- Remove check Flont - Plant operations OK	
0920	- Increase bushes TO 1.30gpm. N. MW38 purply well leaded #+5 cut of point. (Removely)	
2100	- Login Removely, Allox	
1-9-22-300	day	
	- Remove by in . Allot.	and the state of t
2000	- Remove Login, Allot.	
		The state of the s
		T
		Influent Sources and Flow Rates: @0945 NBBW – 6.3 gpm N. END ON-SITE – 11.8 gpm
		N. END ON-SITE - 11.8 gpm N. END OFF-SITE - 7.9 gpm
		N. END OFF-SITE - 7.9 gpm RWST - 1.3 gpm NTES - 0.5)
		NTES - 0.5\ 760 COND/NTES T-530 - 0.20 gpm (6AM-1PM
		daily) MW38 – 1.0 gpm
		T-540/541 - 0.30 gpm MW113 Area - 1.9 gpm
		- Secretari

OPERATOR(S) 10M GILBERT

Date: Monday, January 10, 2022		
Time: 0620 Plant operations good. Propose for Lead? Lag GAC change out	with ungin bitumtous	
V actd washed GAE Scan ! Upload December 50% checklist for PCR	. ~	
0715 Reboot HMIFTVIEWI to reset temporary file space, online 0717.		
10 Man Plant over the and less than a continue to a marine our source of	tpoint at N.END ONSITE	
well MW170-EW-1 (purp beginning to wear out, level in well i	NUS Slowly rising	
at 11.8 gpm). OBIO Flow rate up to 13.0 gpm, Note: this	rate is slightly	
well MW170 FWI (purp beginning to wear out, level in well is at 11.8 gpm). OBIO flow rate up to 13.0 gpm, Note: this Faster than what the well can procluce and level Blowly.	is going back clown	
Blowly.		
0896 Shutdown plant and begin draining lead ? lag go	ac units to the wet	
well.		
Change both lead; lag GAC units with one's with new vingen.		
V GAL. Note: Units that Exme off were moved to the hazadous was		
1217 Rustart plant - work on fixing minur drips on lase connections to	process.	
Note: Units comming efflire will need to drain into the plant wet	well for a minimum	
of 72 hours per oin marrial before can be senoused and place	din supe-sacks.	
1500 Decant T-351 bottom value, wet well activated Water is clear, No	olor. Clean the HUR-30	
well and pt probe - no oil or show a bosened in the Hom 30. Chec	LETP-130 for oil globules-	
None observed water is clear, light yellow.		
1515 Plant operations good. End.	Influent Sources and Flow Rates: 0635	
	NBBW - 6.3GPM N. END ON-SITE - 11.8GPM	
	N. END OFF-SITE – 8.7GPM RWST – 1.3GPM	
	NTES - 0.52GPM COND/NTES T-530 - 0.2GPM (6AM-1PM)	
	MW38 – 1.9GPM T-540/541 – 0.3GPM	
	MW113 IX SYSTEM - 1.9GPM	
	OTHER - NA	

Date: Tuesday,	January 11, 2022	
Time: 0550	Plant operations good. Start on weekly effections y and process of	entrance sampling
0730	Blowbour operations good - Perform weekly Ton Exchange performence IP after 1,046,192 gallons treated. Flow rate at 2.0 gpm (still-extended). TP-183 e 210 us/L; TP-174A @ 360 us/L; TP-174A @ 360 us/L; TP-183 e 210 us/L; TP-174A @ 360 us/L; TP-183 e 210 us/L; TP-184A @ 360 us/L; TP-184A @ 360 us/L; TP-185A @ 360 us/L; TP-184A @ 360 us/L; TP-185A @ 360 us/L; TP-184A @ 360 us/L; TP-185A @ 360 us/L; TP-185A @ 360 us/L; TP-184A @ 360 us/L; TP-185A	restruct / lab saraling
	The after 1,046,192 gallows treated. Flow rate at 2.0 gam (still-	atter catching us From
	Vesterdays stoppage). TP-183 e 210 mg/L; TP-17-4A @ 360 ms/L; TP	1-173A e 5,500m/L 1
V	TP-170 e 5,700 ug/L.	, , , , , , , , , , , , , , , , , , ,
0915	Perhan welly BTS sampling. Then oade samples and one Yee	
1130	INCrease N. End ONSITE flow rate by Mirain, up the extraction ran	te at MWI70.EW-1
↓	(still catching up from yesterdays stoppage). Rate now at 14.0,	·/m
1330	(still catching up from yesterdays stoppage). Rate now at 14.0, Clean the HMR. 30 wetr and pH probe - No oil or show observed in &	he HMR.30. Check TP.130
	for oil globules - None observed. Wateris very class, light y	ellow.
V	Work on welly BTS field readings	
1620+425	Field readings completed	
1630 t-13	Plant operations good. End.	
		-6
		Influent Sources and Flow Rates: 0640
		NBBW – 6.3GPM N. END ON-SITE – 13.1GPM
		N. END OFF-SITE – 8.7GPM RWST – 0.6GPM
		NTES - 0.51GPM COND/NTES T-530 - 0.2GPM (6AM-1PM)
		MW38 - 1.9GPM
		T-540/541 - 0.3GPM MW113 IX SYSTEM - 2.0GPM
		OTHER - NA

Date: Wednesda	y, January 12, 2022	
Time: 0550	Plant operations good. Start on welly GC maintenance and a	alibiations.
0643	Stop MW38N: 5 extraction in properation for source well batch ext	raction.
0650	Decayt T.351 bottom value, wetwell activated. Water is clear, 1 HMR-30 weir and pH probe - No oil or show observed in the HM	vo color. Clear the
	HAMP-30 Weir and pH probe - NO oil or show observed in the HA	R.30. Check TP-130 for
V	oil globules - None observed. Water is very clear, light yellow.	
	Start filter press on T-351 (in stage)	
0712	Set RWST in Fluent to be 2.6 gpm after blowdown.	
0735	Blowdown operations good. Smitch MUBE influent from direct HMR-30 inf	luent to T-540/541
	Start up MW34 source well batch extraction to T-540/541.	•
	BACKUP plant data to Flash I DVD. Daily One Detre backup working we	
1040	Stop ION Exchange process, total volume treated 1,049,314 gal	CONS. TAKE COLUMN Z
	offline and add take columns 6 & 7 out of standby. Note: F TP-173A OFFline and taking sample porty TP-176A - IP-177A out of	Ilso taking sample port
1100	11-173A OSTINE and taking sample porty 11-176A - IP-177A out of	standby.
100	RESUART ION EXChange process.	
1020	Filter press full. Plant operations good. T-540/541 at 44%, will leave source well back	1.71 /5
1523	overight.	ELL EXTRACTION FUNNING
	our right.	
		Influent Sources and Flow Rates: 0640 NBBW – 6.3GPM
		N. END ON-SITE – 13.7GPM N. END OFF-SITE – 8.7GPM
		RWST – 0.6GPM NTES – 0.51GPM
		COND/NTES T-530 – 0.2GPM (6AM-1PM) MW38 – 1.9GPM
		T-540/541 - 0.3GPM MW113 IX SYSTEM - 2.0GPM
		OTHER - NA

Date: Thursday	, January 13, 2022	
Time: 0550	Plant operations good. Start on weekly systems checks and o	all has time
0740	Blowdow operations good. Note: RWST levels are getting low, may	weed to all alling
	and run BTS later while Finishing up with the MW38 Source well	had I and I
	Cinfluents to the HMR.30 will be low if RWST go to low and For	Caten Extraction.
V	N'is wells are off during source well batch extraction)	Zestops while Muse
0834	RINST POUR (NOW) INSTRUMENTS IN TO WILL TO THE	= 1.1. H1 1115 and
	BTS into recycle while it retills, for now.	Eyele The UV-OX
0915	Refill aborations of the will be all and the second	
0845	Refill phosphorus take with 60 gallors potable water + 616, 75 P.	
1	Tom - No decent on T-351 (below bottom value). Checked TP-130 for	oil globules - none
V	Water is clear with yellow tent. Cleaned pH-315 with acrd solu-	tion and checked
1010	Shutdown Muse sween - None observed. Sprayed down weir.	
1020	Shutdown MW38 source well batch extraction (T-540/541 e 81)	.)
1050	Reduce T-540/541 to BTS from 0.3 gram to 0.2 gram while fresh MW36	source well water present
1/	Start MW38N & 5 extraction to T-540/541, to displace source well we	eteria the pipeline
	to T-540/541	
1300	Suspend discharge for pH-740 Calibration.	
	PH. 70 calibration completed - resume discharge. Continues on ph calibration	rations at pH-113, 365,
	210, 313 9 040	
1541	All calibrators completed - All okay.	Influent Sources and Flow Rates: 0640
/543	Plant operations good.	NBBW - 6.3GPM N. END ON-SITE - 13.3GPM
1720	Kemotuly switch MW38 NSS extraction to RWSTs after 720 gallow purped	N. END OFF-SITE – 8.7GPM RWST – 2.6GPM
	Remotely switch MW38 NES extraction to RWSTs after 720 gallow purped to displace Source well water in the conveyance pipeling to T.540/541.	NTES - 0.51GPM
	Plant operations good.	COND/NTES T-530 – 0.2GPM (6AM-1PM) MW38 – 5.0GPM(source well to T540/541)
		T-540/541 – 0.3GPM MW113 IX SYSTEM – 1.9GPM
		OTHER – NA

OPERATOR(S) Chris Carlson Tom Gilbert

~1/2" SMP.M.

LOWRY WTP OPERATIONS LOG

Date: Friday, Junuary 14, 2022	
	slowdown operations good.
1100 - Decent T-351 from b	thom value - wet well activated; water is very clear
- Cleaned Ph-315 probe	ocid solution and checked HMX-30 for oil or sheens. None observed; sprayed weighburks-none observed water is very clear will be now tint
1330 - Plant operations good	TODALS 1.216 DIDE OCC MATE 12 ABY CHEM MI THE HOW HALL
10 0645 Chack plant senote restanted at 2.69	ly-All okay, RWST's pare ichilled to 15% and P-121 bas
	Influent Sources and Flow Rates: @ 1045 NBBW - 6.3 gpm N. END ON-SITE - 13.1 gpm N. END OFF-SITE - 2.5 gpm RWST - 2.6 gpm NTES - 0.51 gpm
	NTES - 0.51 gra COND/NTES T-530 - 0.19 gpm (6AM-1PM daily) MW38 - 1.8 gpm
	T-540/541 - 0.20 gpm MW113 Area - 1.9 gpm

OPERATOR(S) TOM Gilbert Chris Carlson

YOUN TANKAN 15 2022	
ON site for weakend systems checks. Plant operation and. Dropp	ring into blowdown.
Blowdown operations good. Lower RWST INFLUENT From 2.6 com to 0.6.	com and soutobe Muise.
10 3 CHICKEN TOM KWSTE TO OLIVER UMB. 30 SIFFLER H. USA TALEMAN	10 TISUALOUIL ELL
TO OF BRUN OBSERVED IN THE MINK. 30. CHECK 17-130 to oil global	30 wetr and pH probe - es - NONE observed. Water
Plant operations good. Measure 46 signals war plant for possible new	N intervet popular
6 ms Titer - Send insuration to Faston alove with Division and	release, 4/4ms Ping }
up appropriet who went buck down to wormal (lost prime or 610 50)	
Check plant reactely-Allokay.	
	Influent Sources and Flow Rates: @ 0750 NBBW - 6.3 gpm N. END ON-SITE - 13.0 gpm N. END OFF-SITE - 8.5 gpm RWST - 0.6 gpm NTES - 0.49 GPM COND/NTES T-530 - 0.2 gpm (6AM-1PM daily) MW38 - 2.1 gpm T-540/541 - 0.3 gpm MW113 Area - 1.4 gpm
	ON site for weekend systems checks. Plant operation good. Dropp Refill physhows tank with 30 gallow potable mater 2 3165 TSP. Blowdown operations good. Lower RUST INFLUENT from 2.6 gam to 0.6 g NES extraction from RUSTS to direct Home. 30 in Fluent. Plso INCIONA Tate from 0.2 gam to 0.3 gam (rosutts of TP-3750 for 1,40 i 1,20 CR to Fresh Source well water entring the system). Clean the HMR- NO oil or shown observed in the HMR-30. Chack TP-130 for oil global is very clear, light yellow. Plant operations good. Measure 46 signals Mat Plant for possible was Options, Verizon 4617 36405, 33.3 Mbos clownload. 2.44 Mbos

Date: Monday, J	anuary 17, 2022	
Time: 0630	Plant merating agent.	
0740	Bloucloud operations good - work with Mike to add ~50	gallows HCL to mail
	bay supply.	
1005	- Decant T-351 TO bottom value, west well activated, water 53 Clear Nocator.	
	Clem p14.315 probe ul Acri solveton, Chelle THE Homes & for ON or steen: None of se	ough. Strang down weem
	Check TP-130 for ollylobuly: None observal, water Is clear if yellow-green trust	
1100	- Cheeking FOTW ATT Releases and Vaults/Leak Detections and POTW Discharge Borns	MH175-078; Allot No leaver
	observed / NO ISSUES observed.	
1104	- TOM calling In Lovel for MW38-1028N-256E for QTrly tempoducer calibration chec	e. 070 251,88-5719.92 msl
	HMI Realing 5719.76 msl /- 0.16 Arthurence. NO calibration healed at this Time.	
1530	- Plants Operations Gesist.	
		Influent Sources and Flow Rates: 0930
		NBBW - 6.3GPM
		N. END ON-SITE – 12.8GPM N. END OFF-SITE – 8.2GPM
		RWST – 0.6GPM NTES – 0.51GPM
		COND/NTES T-530 – 0.2GPM (6AM-1PM) MW38 – 2.0GPM
		T-540/541 – 0.3GPM MW113 IX SYSTEM – 1.9GPM
		OTHER - NA

OPERATOR(S) Chris Parlson Mike Gelwick

OG

Date: Tuesday, January 18, 2022			LOWRY WTP OPERATIONS LO
Time:	0500	- Plants mergers 6-od	

Time:	0500	- Plants operators Good	
	0555	- collect weekly TP-730 GC/BAB Splot SHIMPLES / START EFFTRENCY Checks, collect weekly TP-740 + TP-710	
THE THERE		Low Level 1, 4-Dis xune samples.	
	07.15	Blowdown operations good.	
	0810	- Becant T-35/TOBOHOM valve. Wetwell althoused. wenter to clear accolor	
		-Clem pH-315 probe w/ Acid solution. Check THE Homeso Foroil or Steen: None observed. Spry som war.	
		- check of - Bo for oil globules: None of served, wonton B Clear w/Light yellow - green pint.	
	0845	-check of-Bo for oil globules: None observed, wontonts clear w/Light yellow-queen pint. E.T. Tech Joe 1 ? Shave on Tite to +1 Ansty. Mile working on 513 sumbling and Field healings today	
-	0920	- UC Denver on size for your and made solds schaple escleption from 873 leactors	= =====================================
	1000	- IX System performance HALH TESTING WITH Lab Spit sampling AFTer 1,065,515 gal Frented: TP-183 & 130 41/1;	
		TP-175A2150 uy/L; TP-174A2270 uy/L; TP-17025800 uy/L.	
	0938	8 -70 m calling In Level from MW38-1705-140W Josh Armorny well For ATTly TRANSLUCE CUltivation check: 1700 71,65=5	735.13
		HMI healthy 5734.99 MSL "0.14 difference. NO calibration weeled at +255 time.	
	1435	- Refill BTB phosphones TANK W/5 #OFTSP and 50 gal of potablewater.	
	1700	ET. dure wills GAC transfor to super racks - plant operations good.	
the same			
		Influent Sources and Flow Rates: NBBW – 6.3 gpm	@0540
		North End On Site- /2,7 gpm	
		North End Off-Site - 8:5 gp RWST - 060 gpm	m
		NTES - 0-50 gpm(10R only)	
		MW38 T-540/541 - all gpm(So well and 38 pumping wells mix)	ource
		MW38 N & S− ₹,⊅ gpm COND/NTES T-530- ₽-ॐO gpm	(6am
		1pm daily)	(Uall)-
		MW113 Area – l.9 gpm	

Date: Wed	nesday, January 19, 2022	
Time: 060	Plant operations good. Stort on weekly GC maintenance and calibra-	AUNE.
0	000 - Work on Getting the Spent carbon supersacks topped out and sealed t Labeled for simples	et.
10:	10 - Jecant 1-35/ 70 65+ tom valve. We twell activated. usater 55 clear No color.	
	- Clean p. A-315 probe w/Acrt Solverson Check The Hune 30 For of on 5 then; wore all	Sarved. Spray Down worm
	- Check TP-130 For oil globales: None asserved. Water 55 clear in Light yellow- your	timt.
123	B Manuela . Tom scribing in manual levels in the N.TOR area for quarterl	y transducer calibration
	B Manuela Tom scribing in manual levels in the N.TOR area for quarterly check. MPZ-12 DTWC 24.05' = 6WE 5739.04' HMT I cading 57 ofthistine.	\$38.98 - No coller & AND Needs
12	16 NTES-180W DTW @ 35.81' = GWE 5729.82', HMI reading 5729.91	1'- No calibration number
1322 NTES SUMP DYW @ 28.68' = GWE 5734.15'. HMT reading 5734.16'-No calibration 1341 MPZ-10R DTW@ 33.34' = GWE 5729.31. HMT reading 5729.13'. No calibration reading 1350 MPZ-11 DTW@ 32.12' = GWE 5734.31'. HMT reading 5734.39'. No calibration readed 1530 - Phones operations of the second of the s		elebration of & Wieli
13	11 MPZ-OR DTW & 33.34'= GWF 572931. HMI MADING 5729 13'-No Calibra	Kun har his day belling time
13:	10 MPZ-11 DTINE 32.12'= 6WE 5734.31'. HMI reading 5734.39! NI caldra 60	ruled at this time
15.	30 - Phones operators Good.	· · · · · · · · · · · · · · · · · · ·
		Influent Sources and Flow Rates: @ /055 NBBW - 6.3 gpm North End On Site- /2.6 gpm North End Off-Site - 8.2 gpm RWST - 0.6 gpm NTES - 0.52 gpm(10R only) MW38 T-540/541 - 2.50 gpm(Source
		well and 38 pumping wells mix) MW38 N & S- 2.0 gpm COND/NTES T-530- 0.20 gpm(6am- 1pm daily) MW113 Area - 1.9 gpm

Date: 1	Thursda	January 20, 2022
Time:	0600	Plant operations good. Sctup for PDU backerph. PDU backwash cd, A pressure improved from bysi to losi. Decent 7-351 to buttern value west well actually. Walters clear wocolor Clean pt. 315 probe w/ tot solution. Check the three 30 for oil or steen: None observed. Spray Down were.
		check TP-150 for oil globules: None observed. water 23 clear willight yellow-grown truth working on weekly plants systems checks and californ trons today
	/332	Suspend plant siz churge to californie pH. 740 probe to 4+10AH STAS
	1340	Resume Normal Discharge. Continue with other WTP perprobes calibrations to 4+10 pts 103 2 pt-113, 670, 315 + 365
	1420	weekly plants systems chicks and cultbrattons complete.
		Pluntsoperurous God.
		Influent Sources and Flow Rates: @ OBIC NBBW - 6,3 gpm North End On Site- /2.5 gpm North End Off-Site - 8.8 gpm RWST - 0.6 gpm NTES - 3.53 gpm(10R only) MW38 T-540/541 - 0.30 gpm(Source well and 38 pumping wells mix) MW38 N & S - 2.0 gpm
		COND/NTES T-530- 0.19 gpm(6am- 1pm daily) MW113 Area – 1,9 gpm

Date: Friday, January 21, 2022 Time: 0725 - Plants genarious and. Achount blowlown operations wood. 0330 - Decant T-357 +> bottom value wetness altrusted, water to dear mosalor. - Clean AH-315 prope uf Acrd Schuron. Check THE HUMESO For sil or & Heen: Noneasserved. Spray pown weir. -Chuk TA TED For oil ylobeles: None observed. water IS clear w/ yellow green trus. 1025 - Place 675 Into maint. Hold to Flush leactors Feed pipping. 1055 - 6T3 out of Hold. Allow. Aumps CV" + pressures BACK to Normal LAnge. 1105 - Levill BTS phosphors TANK W/4.5 HOP TSP and 45 gel of potable water. 1305 - Plants operations Good. Influent Sources and Flow Rates: @ 0147 NBBW - 6.3 gpm North End On Site- 12.5 gpm North End Off-Site - 8.9 gpm RWST - 0.6 gpm NTES - 2.53 gpm(10R only) MW38 T-540/541 - 0.19 gpm(Source well and 38 pumping wells mix) MW38 N & S-1.9 gpm COND/NTES T-530- 0.19 gpm(6am-1pm daily) MW113 Area - 1.9 gpm

Operator:	Mike Gelwick	
10 TO		

Date: SATURDAY, JANUARY 22, 2022		
Date: S#10k	CAMT, JANuary 22, 2022	
	- Plants operations Good	
0700	- Automostic blowdown operations Good. Go to check other six systems	
0805	- Reboot HMI FTUIEN 1 to taget present memory.	
0810	- HMIFTUDEW I BACKONINE	
	- Reboot ItMIZ toleset Internal memory	
0820	- HMIZ BACKON ITM.	
0830	-Decant 7-357 to be from value wet well activated water B clear nocolor	
	-Clean AH-315 proba whath solveron Check the HMLSO For off or steen: None observed. Spray down wer.	
	- Check TP=130 for Oil globules: None observat water 13 clear w/ yollow-green +ms.	
1000	- Plan 43 ofernanons Grand	
2100	- Remoking in Allok.	
Sunday, JA	numry 23, 2027	
0830	- Remote Log in Allon	
	- Kennste Log pe all or.	
	influent Sources and Flow Rates: @ 0897 NBBW - 6.3 gpm N. END ON-SITE - (7.5 gpm N. END OFF-SITE - 8.4 gpm RWST - 0.6 gpm NTES - 0.53 gpm COND/NTES T-530 - 0.18 gpm (6AM-1Pl daily) MW38 - 2.0 gpm T-540/541 - 0.31 gpm MW113 Area - (, 9 gpm	

Date: Monday, January 24, 2022

Tima	2522	Dia Lance is a f	
Time:	0530	Plant operations good.	
	0845	- Accant T-351 to bottom value, wet well actrowed wreter to clear worder.	
		- Clean p. 4-315 proteculated solution. Check THE HURE TO For oil or silven: None observed. Spray do	who were,
		- Check FB-130 For oilglobules: None observed. water Is clear w/ ye/wwyroun trut.	
		- Le Will polymer rank w/ & cups of NALCO polymer and too gal of potable water Clean 5, gett g	Cess
	1100	- 2" Diaphram pump A-381 Fr warpers studye pump Rebuilt and BACK on love. New orkings, BAHS, BAHSER	ts + Asupheams on Aif + Fluid sides.
	1230	- work on Empty set filterpress,	
	1425	- Filhe tress Emply weeds was nout.	
		- Plantsoperations Good	
011042222			
20			
			111.00
			Influent Sources and Flow Rates: @ \$955 NBBW - 6.3 gpm
			North End On Site- 12.4 gpm
			North End Off-Site – 8.4 gpm RWST – 0.6 gpm
			NTES - 0.54 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source
			well and 38 pumping wells mix)
			MW38 N & S- 2.0 gpm COND/NTES T-530- 0.2 gpm(6am-
			1pm daily) MW113 Area – /. 6 gpm
			INIAA IS VIGA - 1.0 Abu

Sport inquisi of the melting

LOWRY WTP OPERATIONS LOG

10 C	, January 25, 2022			
Time: 0450	- Plants operations Good. Prepare for TAP 730, 740+7105Ampling			
0530	- Collect TP-730 weekly GC/CABSPUT SAMPLE and Begin weekly Efficiency checks, collect TP-710+TP-	740 weekly Low Level 1,4-10,00%		
	samples.			
0840	- Decant T-351 to bottom valve, wetwell activated, water Bclean woodlor			
	- Clam pH-315 probe witherd solveron. Check The HMA30 for oil or 5 Hear: None of served spray down we	m		
	- Check TA-130 For oil globuly: None asserved. water B Clear w/ cg 4+ yellow-green +rn+.			
0845	- NO HICE MW38N. propring well HAS peached TTS Cut off point eround 8AM. Increase Lus 73 to 1.	. 3g Da to supplement Reduction		
	In Flow to the HMM20 to Aid on T-510 tank stabilization			
	- worming on BTS wronky sampling and well hearings rolay.			
1000	- IX system performance HACH resurny w/weekly cab split sampling AFTER 1084186 get treated: TP-183 2 210 ug/li;			
	TP-175AD 310 mg/L; TP-174A 2 610 mg/L; TP-170 2 5800 mg/L. Note: System Has Dropped on Flow to 1.84 pm consistently			
	Since Monday Morning 1-24-22.			
1330	- lexil BB phosphors THUE W/6# OR TSP and 60gal of potatele water.			
1518	- Recence UV-OX GC fault For High 1, 4-APOXane level. Level - 127. 68pg. UV-OX ENTO Keyele Ok.			
	- Do some traves tighting and can not find an obutous heason for the ISSUE. Will leave the UV-OX OFF FOR TONIGHT and DIVER			
	mus 18 and NOOW to the Russ TS for the estant as well NOTE: All Effecting checks were worme laday.			
	- Plants operations ok.			
1610	Remobily increase RWST in Fluent from 2.5 gpa to 3.5 gpa For the	with (Will tabe		
	advange of the UV-OX being off to test high influent rates from	Influent Sources and Flow Rates: @ 057/5 NBBW - 6.3 gpm		
	the Warriso to BTS.	North End On Site- /2-4 gpm North End Off-Site - 8.3 gpm		
		RWST - 26 gpm		
		NTES - 453 gpm(10R only) MW38 T-540/541 - 429 gpm(Source		
		well and 38 pumping wells mix) MW38 N & S- !-1 gpm		
		COND/NTES T-530-Q20 gpm(6am- 1pm daily)		
		MW113 Area - 1.8 gpm		

D-1	Date: Wednesday, January 20, 2000		
Kini Circulation 2000 Account of the Control of the	day, January 26, 2022		
Time: 0545	Plant operations good. Start on weekly GC maintenace ; Calibrations.		
	DESTITUTE OF STAUGHT TOIL, OF UTOFAME OF TUNNING WITH ON SHIPTING		
	The war is the file of the property of 3.3 gpm. Luctuse KWST INV Lucat		
	The or gen to to gen. Observe the BIS eff went pump running at a high GVI.		
	with the higher Flow - Backwash GACF-3340 while plant in blondown. Flow pressure		
V	with the higher Flow - Backwash GACF-3340 while plant in blowdown. Flow presure much improved after backwash. Switch R3 feed from P. 3323 to P. 3324.		
5000	DUNGUIN GERATIONS GOOD. WILL CONTINUE TO TUST 1273 OF Micher Flows while UV. DX; &		
	each other T-101 (419%. While T-102 e 19%. Mike to clean backet strainers trolay		
	each other T.101 (419%. While T.102 e 19%. Mike to clean backet strainers today		
V -	to improve quat.		
0850	- Place STS IND marns theld and STOP KUSTS pump to clean out Kests & Miket STOWNERS.		
0930	BTS out of Maintenance hold. Custs pump BACK TO AUTO, BASKET STravers clauded Lingts.		
1015	- We can't T-351 to bottom value wetwell activated, wanter B Clear No color.		
	- Clean p4-365 probe w/ Acrd golveron. Cheek THE HMASO For offer 54cen; None observed, spray som were,		
	- Check TP 430 For Oil globules: None OK served. water Is clear ul light yellow-green trut.		
	Detup to test run UV-04 with discharge of the UV-OX, post PDU being returned to the RWST's		
110	THAT UVIL WAShing up. 1120 Vischarging to Klust. Note: FT-670 Total reactions 21065600 gallons		
	Will allow WOX to operate like this for a while betwee taking GC sample of TP-730. Increase		
1	100) INVLUENT from 4.5 gen to 5.5 gen to Keep the high Flow testing in NBBW- 6.3 gpm to Records		
	North End Office 17 agpm		
1150	Keroxicle dusing walking well TP-730 Oppm, TP-720 Zoppm 3 Pre UV-0x 100ppm RWST - 45 gpm		
1245	GC maintenance and Codibrations completed. Run test of TP-730 an 6C1. North End Off-Site - 6.8 gpm RWST - 4.5 gpm NTES - 0.54 gpm(10R only) MW38 T-540/541 - 0.2 gpm(Source		
1300	BACKUP WIT data to Flash drive and DVD. Daily Oraprive backup was king well. MW38 N&S- 0.9 gpm (+ KNT)		
1110	Mike washing out filterpress. COND/NTES T-530- U. 2 gpm(6am- 1pm daily)		
1725 (While washing out filterpress. GCI TP 730 Result Normal. 14-Diogone at < light. Yesterday rice in 1,4-Diogone MW113 Area - 1.8 gpm (Continue)		
	(cuntianel)		

Date: Wednesday, January 26, 2022 (rentinued)

Ver possibly due to air in the peroxiele Feed line. Unit working normally now.

1449 1444 Place UV-OX in recycle to switch its chuckuse From temporary testing flow to RWSTS

I to point discharge to Feed surge tank. FT-670 Totalizer @ 21,067,190. 1,590 gal. rept to RWSTS

1453 Resume normal discharge post POV to Feed surge tank and get MUSE N'S running to

VIME-50 again. Start GCI on rext TP-730 early.

1625 Plant aperations good. OWRY WTP OPERATIONS LOG Influent Sources and Flow Rates: @ N. END OFF-SITE -COND/NTES T-530 Com (6AM-1PM MW38 -

OPERATOR(S) Chris Carlson Mike Gelnick

230 m should in draic.

LOWRY WTP OPERATIONS LOG

Date: Th	hursday	, January 27, 2022		
		- Plants operations Good. Out of Automatic blowdown ok		
	0850	- PRARIE NEW AHSTOS FOI CONTROLHOUS. CONTROLD SIZE MUST MEAN FOR USE DIVING LEL-740 CONTROLHOUS TO EN	our ObLEL In T-740 Amdrest Arm.	
th.		- working on weekly / monthly plants system chelles and californious paday		
	0925	-Decamt 9-351 to Bottom valve. wet well activated. wester 13 clear Nocolor		
		- Clean Att 315 probe w/ Acrd solveron, Check the Hand 30 for offer. None or served. Spray son	un wer.	
		-Check TP-130 for oily lobules: Noncos served, water IS clear ullight yellow-green tint.		
	1000	- START Main compressor oil moisture prevention process. Dun for 7 this mouthly at max speed.		
	1140	- Performmently BTB ANDIONES CAUBOULTONS to MEW ULIOPHITO!		
	1236	- California WTP p. probus to New 4+ 10pH STO' = pH-113, 670, 310,315 +365		
	/307	- Suspend Plant Discharge to californite pH-740 probe to New 4+10 pHOTO, and LEC-740 surper	10496LEL.	
	1316	"Plants Hut Down for High LEC 2 8% LELD Soring californition of LEC-740. High LEL	5 HUT NOWN Operations Good.	
	1324	- RESTART Plant, Lesume Normal Stocharge.		
	1330	- weekly/moushly slaws systems checks and cultbrutions complete		
	1430	- Plants operations Good.		
			Influent Sources and Flow Rates: @ 0750 NBBW - 6.3 gpm	
			North End On Site- /2.3 gpm North End Off-Site – g.7 gpm	
			RWST - (.O gpm	
			NTES - 3.51 gpm(10R only) MW38 T-540/541 - 3.30 gpm(Source	
			well and 38 pumping wells mix) MW38 N & S- 2.0 gpm	
			COND/NTES T-530- 0-20 gpm(6am-	
			─ 1pm daily) MW113 Area – <i>i</i> ⋅ 8 3 gpm	

Operator:	Mike Gelwick	

- Plant operations good Decont T-351 for from bottom value. Wet well activated. Water is clear no co	
- Decent T-361 & Com has a laborated with a live of the later of the l	
- Decor. 1-331 The flow DOTHOW VAINE, WET WE'N DEFINANCE. WATER IS CHEAR IND CO	.07
- Clean ph-315 probe with Acid Solution, check HMR30 for oil or sheens; none observed. Sorance	down Weir
- Check TP-130 for oil globules: none observed. Water is very clear w/ yellow-green that	
- Fill phosphorus tank with 5.5 LBS 55 gallons of water	
- Plant operations good.	
Check plant remotely - Note BCs taking a sample diving blow	down. Stop GC's.
secause both UV.OX: BTS Note discharing during blowdow.	
Restort GC's sampling.	
Check Plant operations (Chrotely-Allokay.	
	NAME
	-
	Influent Sources and Flow Rates: @ \\36 NBBW - 6.3 gpm N. END ON-SITE - 12.4 gpm N. END OFF-SITE - 6.9 gpm RWST - 1.0 gpm NTES -0.52 96A COND/NTES T-530 - 0.14 gpm (6AM-1PM daily) MW38 - 2.0 gpm T-540/541 - 0.31 gpm MW113 Area - 9 gpm
	-check TP-130 for all globules: name observed, water is very clear will perform stank with 5.5 LBS 55 gallons of water - Fill phosphorus tank with 5.5 LBS 55 gallons of water - Plant operations good. Check plant comotely - note 6 cstaking a sample oliving love because both UV-OX: BTS note discharging during bloundam. Restort CC's sampling. Check plant operations (camptely - RII okay.

OPERATOR(S) Tom Gilbert

Date: Saturday January 29 2022	
1830 Clean pH-315 probe W/ acid solution. Check HMR-:	30 for oil or
sheen : none observed Spray down werr.	
Chack TP-130 for oil globbiles: none observed. Water	er is very clear
with yellow orden that	J
Decant T-351. Wet well activated. Water is clear	no color.
Both 6C's operational within limits)
All blowers olkay	
Phosphorus tank (a) 82 gal.	
1530 Plant operations good.	
@ 0735 Plant checked remotely- All okay. Bloudous operations ga	xd
11W 1900 Clarell Transfer to Later 1 All All all as	
@1/30/22 0655 Check plant operations remotely - All okay.	
(W) 1600 Chuck plant operations remotely- All olegy.	
C TO STORY TO SECUL	
	nfluent Sources and Flow Rates: @ 133 C NBBW - 6,3 gpm N. END ON-SITE - 12,1 gpm N. END OFF-SITE - 8,6 gpm
	RWST - 1.0 gpm NTES - 0.52 9PM
	COND/NTES T-530 – O.0 gpm (6AM–1PM laily)
	/IW38 – 2.0 gpm Г-540/541 – 0.3 gpm
in the second of	MW113 Area - 1.8 gpm

OPERATOR(S) Manuela Seewald

Data: Manday	January 24 2000		
	January 31, 2022		
Time: 0635	Plant operations good-		
0755	Plant operations good RUSTS @ 241. reduce influent from Rus	To from 1.0 cm to 0.6 de	
1130	- Decant T-351 to bottom valve. wetwell activated. water Is clear Nocolor	1/100	
	- Clean AH-315 probe w/ Acth solv from. Check THE HAMASO From oil or steen: None observed. Spray were were	r.	
	· Check TP 130 For oil globules: None on served, water Is clear ut yellow-green trust.		
	- Work on Getarny Auto spoplers setup and cultural. Thiple I me each dedressed composine	autuma Salla of to	
	Resample arry Succi - Hexachlorocyclopentadine + Bonzidine, will Alfo be collecting voc grab resumples from MAOSI		
	For Dichloro Fluoro mechane, 1, 2, 3-Triebloro propone + O-kylene to morrow During monthly grabs.	usili stold are sematives -	
	PATOT TO START UP.	700000000000000000000000000000000000000	
	Add one full caustic tote to mass bay supply.		
1415	-BTS In to mumt wolf to flugh Leactors Feed Lowers		
1450	- 573 BACK ONLINE. WOTHOUSE HTT BOTHLES KENTY for SAMPHTY START TOMOTION.		
1605	- Plants operations God.		
		Influent Sources and Flow Rates: @ 0800 NBBW - 6.3 gpm North End On Site-12.3 gpm North End Off-Site - 6.7 gpm RWST - 0.6 gpm NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source well and 38 pumping wells mix) MW38 N & S - 2.0 gpm COND/NTES T-530- 0.2 gpm(6am-1pm daily) MW113 Area - 1.8 gpm	

Date: Tuesday, February 01, 2022

Time:	0430	- Plants operations Good.		
		- Collect TP-730 GC/Lab SNIT SAMPLE and buyon Efficiency checks. Also collect weeking TP-710+7P-74	O contend 1, 4- Aroxane surge leg.	
		- START AUTO SAMPLERS REV MA-001 MONTHLY PERMY SAMPLY LING and QTILY SUOCE RESAMPLE. TOTAL EFFLUENT & 250/68476 gal 2		
	26	31.7 g/m = 7.03 su = 15,3°C	2000 × 000	
	0805	- IX SYSTEM por Formance HACH TESTING W/ weekly Lab SALT SAMPLES AFTER 1102467 gal Treated:	TP-183 => 220 4/6;	
		TP-1754 2 230 ug/k; TP-1744 2 400 ug/k; TP-170 2 5900 ug/k. System everently Running		
		- working on weekly 675 sampling Adday.	•	
	0845	-Decant T-357 to bottom valve. wetwellactivated. water 13 clear no color.		
		- Clean p. H. 315 proke w/ Acid solveron. Check Tik Home 50 For oil or steen; None out served. Spray Down wer.		
		- Check TP130 For oilylobuly: None of served water 13 clear willight yellow green tirst.		
	1000	- WORKING ON MONTH by Early war way sampling.		
	1145			
	1200	1991 (20) (7) (8)		
		For Dichlorodifluoromethans, 1,2,3-Trichloropropune + O-Xylene. Place samples to fridge.		
8	1208	- Place BTS INTO Matrit Hold to clean p-ook y-strainer.		
	1214	- BTSONOR Hold. y-straker Aretry cloqued.		
will come and the same	1230	- Restill BTS phosphores TANK WIGH OF TSID and bogul of potable wenter working on BTS Field dealings.		
	1545	- START Flush of mt-0015 Ample port and check for residual chlorine: Nowe percent		
	1600	- collect 2nd set of time paced grub samples & mp-001 sample port for low level 1940,0x are and	Influent Sources and Flow Rates: @ osas NBBW – 6.2 gpm	
7		QTV by vocs Resample. Phase samples on Fritge with others.	North End On Site- / 2.3 gpm North End Off-Site – 8.5 gpm	
	1610	- Plants operations Goods	RWST - O. G gpm NTES - O. S gpm(10R only)	
		Start MP-00 port Flush a check for secredual chloring - none detected.	MW38 T-540/541 - 0.37gpm(Source	
	2000	Collect 3rd Set of time gace d grabs apples for lowlevel 1.4. Dioxane & atrly voc resemble.	well and 38 pumping wells mix) MW38 N & S- 2.0 gpm	
	2345	Start MP-001 poit flush and check for residual chlusine - None detacted.	COND/NTES T-530- 0-20 gpm(6am- 1pm daily)	
	0 000	Collect 4th set of tome passed grab samples for lowlevel 1-4 Diomer ; Girly voc & resample.	MW113 Área – t. ジフ gpm	
		Place in fields with others.		

~ 310 way upm-

LOWRY WTP OPERATIONS LOG

Date: Wednesday, February 02, 2022

ime:	0340	- Plants operations Good - Auto samples on teach oic.		
	0395	- START Flush or mp 001 sample port and check for lasid and chlorine; work nate cted		
		- collect 5th set of Time paced grab samples 2 as pool for Low-Level 1,4-0,0 xame and extre	, VOL Legetemple. Place strupled In Fridge	
		- Clean pH-315 prope whack solution check THE HMR 80 for oil or steen: None of served. Sp		
		- Check TR1 30 For oil globules: None observed water os clear willight yellow-grean +++++.	· ·	
	0600	-Chris work my on GC calibrations and maintenance and BATA BACKEN reday		
	0700	- ALGOMANE GLOW down operations Good.		
	0745	Bloudour operations good. Mike starting MP-UVI port Flush - check	Wing for sestellual oploring	
	0000	Mike collecting 6th and fival time preced grabs for low level 1,4. Di	ORENE & Bely VUCS (FUSAMAL)	
		& Stupping auto sumplyes after 24 hrs. Effluent to talizer reading 2	50215,000 pollows 46,524	
		Estopping auto samplers after 24 hrs. Effluent totalizer reading 250215,000 gallons, 46,524 gallons discharge over the last 24 hrs. Slowly stir composite containers, check pH's (Sodium missulfate preserved @ 7.41 ? N.tric preserved @ 1.70), Both ove very clear, no color. Mike & Tom		
		Missulfate preserved @ 7.41 & Nitric preserved @ 1.70). Both ove very clear no color. Mike & Tom		
		Filling lab boths from composites and placing samples in fricke.		
	0840	Filling lab bother from composites and placing samples in fridge. - Decant 7-351 to bottom valve, wet well activated, waser of clear to color.		
		- STOP pool pump. TANKhends & 29%. Toucold to STOP MUSS permorny wells to una batchest source well with Tuday.		
	1030	Backup plant data to flash drive & DVD. ONCE a day One Drive backup working well.		
	1330	Plant operations good.		
			Influent Sources and Flow Rates: @0340 NBBW - 6.3 gpm North End On Site- 17.3 gpm North End Off-Site - 8.4 gpm RWST - 0.6 gpm NTES - 0.51 gpm(10R only) MW38 T-540/541 - 0.30 gpm(Source well and 38 pumping wells mix) MW38 N & S - 2.0 gpm COND/NTES T-530- 0.20 gpm(6am-1pm daily) MW113 Area - 1.83 gpm	

Date:	Thursda	ay, February 03, 2022		
Time:	0615	Plant operations good. Ambient outdoor temp - 10°F this mining. BTS building bus co	pledoff	
	V	to 60°F. Reactor temperatures good, tank heaters working well.		
	0740	10 Blowdown operations good. Mike starting weekly systems wheels & valiberation.		
	0800	no Topolf bydulie oil on filtypass.		
	0900	Tom helping Mike with weekly system check & calibrations.		
		Tom helping Mike with weekly systems check & calibrations.		
	101	- BTS INTO MARMY HOW to FIUSH p-006 propray		
		- BTS OUT OF Hold. p-ook Feed whee flysed, workon Impeller & clean set check skill.		
		- Test Run pools pump. Allok, CV April 70 40% 20, Sogram. will seem of until canken a batch of source well a	sates.	
	1310	- Checked HMR30 for oil or Sheen's none observed, Sprayed down we'r		
		- Rinse PIT-315 probe with Muriatic acid Solution		
	- Checked TP.130 for oil globales or sheens: None observed, water is clear with a yellow tint -no det		debris	
	1320	- worker/chris to Ata New Chum on constic bay lot of Book.		
	1530	1530 - STOP Filter Press. Not Fill yet him townsom. Weekly Alants Systems checker mustly finished wild finish we powered. 1600 - Plants uperastions Good.		
	1600			
		Influent Sources and Flow F	50	
		North End On Site- /2,3 g	pm Z apm	
		RWST – <i>Q.4</i> gpm		
		NTES - 0.51 gpm(10R or MW38 T-540/541 - 0.0 g	pm(Source	
3		well and 38 pumping wells r MW38 N & S- /-9 gpm	mix)	
		COND/NTES T-530- 0.2. 1pm daily)	gpm(6am-	
	24.1.	MW113 Area – /. 6 gpm		

Date: Friday, February 04, 2022

Time:	0730	- Plants operations Good. Coming out of Automatic Blowdown OK. LESTART Filter Press ON T-351-574564.			
		- Clemp 14-315 prope what solvers. Chell tik HUAR 30 For of or siken: wore assessed. Solvay Down west			
		- Check TP-130 For oil gloincles (None asserve). were to clear w/Citagt yellow your trut.			
(0900	- work with tom on finishing or weekly slusts systems chedes and Ikl TRAIN Him on SH	probes californious more.		
	0905	- Suspend Plant Asscharge to calibrate pt-740 probe to 4+00,01+5705			
	0918	- Resume Normal Discharge continue w. In other physioles calibrations +84+10pHTD = PH-113, 670	310, 315+365		
	1075	- weekly plants systems challs and colibrations complete			
		- Resill BB phosphers +ANK w/4# OFTSP and 40ged of potable water.	Kalanda da d		
		-Fitter press B soll.	and the state of t		
	1400	- Plusts operations Good.			
			Influent Sources and Flow Rates: @ 3800		
			NBBW – 6, 2 gpm North End On Site- /2,3gpm		
			North End Off-Site - 8.7 gpm		
			RWST − O· 4 gpm NTES − O· ≤ 2 gpm(10R only)		
			MW38 T-540/541 – O.O. gpm(Source well and 38 pumping wells mix)		
			MW38 N & S- 1.9 gpm COND/NTES T-530- 0.27 gpm(6am-		
			1pm daily)		
	LINES COLUMN		MW113 Area - 1.63 gpm		

Operator: Mike Gelwick / Chris Carlson Tom Gilkert

Date: SATUR	Date: SATURDAY February 5, 2022				
	- Receive NTES UNSTAble Flow Alarm. Login Remorty and acknowledge. Set NTES to Sivert to				
0655	O. Sgpm. Come to site to see Et I can get It going. T-530 & 28 & and May not Have ensugacents - Set WIES unstagle flow set point to Ogna. Goto try toget AMDZ+OR garagagata. Alarm Clea - UNABLE toget MAZ-IDA going again by cycling ATV. See Decide to Swall out points 5; meeten Her - MIZ-100 - Man 5 20	redocui.			
0735 - MPZ-10R goingagain. 0745 - Set T-530 Flow Bitle to 0.20g DM, Cycle NTES to manual taget wake the Better position to Get Flow 57 0758 - Flow From NTES gratified Stabilizing. Set Bitle to Normal and Repet outstable flow to 0.30g dialogoin, 201 40 Hell Pump trench Bitle Rown. 0810 - Plants operations Good. NTES operations normal. 1155 - Decort to bottom Valve T-351. Wet Well not activated - Water is very clear - Clear PH-315 probe with Acid Solution, Check HMR30 for oil sheeps: None observed - Sprayed					
- Check Tp-130 for oil globules and sheens: None observed water is clear with light yellow that 1230 - Plant operations good 1435 - Loy on Remodely, Increase Lust Plan to 1,05 pm. T-510 thank Going Low offens Autum UVOX THE Register. 2235 - Log in Remotely. Allow		su heizele.			
2300 5011ay, Fe 0734 1530 2130	- Receive 3323 Stratus working Alwan logger Remistry and Sevisen over to 3324 street pure for surry 6, 2022 - FV-708 Fast to open UV-Ox Alwan. Chrissint Down UV-Ox Remistely, will leave out F - Login Remotely, UV-Ox Still out, All else oil - Login Remotely, Allok UV-Ox Still ofk.				

Date: Monday,	February 07, 2022		
Time: 0550 Plant operations olay - observe acid vent bood has tripped it's motor avalord,			
since sub zero weather. Will get martiff for roof Accers.		***************************************	
Observe BTS doing very well with 4.5 spm From HMR.30, incresse to 5.5 spm - 5top			
V	MW34 NFS extraction in properation for MW34 source well extraction,	to T-540/5411.	
	Start MU36 source well batch extraction to T-540/541.		
0750	Bloudown operations good. IR ensite to perform 2,000 hour compassor	service.	
0815	SiA-1 P-006 (T-T40 /541) to BTS at 0.2 spm.		
	- Decart T-351 + bottom value. We twell activated water to clear Nocotor.		
	- Clean p. + 315- probe wheld solution. Welk the HMM 50 For silar speen: None observed. Sprang do	er wer	
	- Check 17-130 For oil globales! None assert. wester 15 51,74th, cloudyer/yellow- orange +ms. An		
	-Cleum p-352 y-strainer.	20	
1/50	- work on lepair of plant potable usata sufficient Dorp on west well near Discharge pumps.		
1330	- Drith Repaired will come of overnight to let the setup well.		
1515	- Plums openiones Coook.		
1630	Check latest TP-3350 result, doing good. Sightly hish, fresh sower well has not a Elected		
	the effluent of the BTS yet.		
Mes (expense)			
		Influent Sources and Flow Rates: @ 0930 NBBW - 6.3 gpm re sures: North End On Site- 12.7 gpm North End Off-Site - 667 gpm RWST - 5.5 gpm NTES - 6.54 gpm(10R only) MW38 T-540/541 - 6.20 gpm(Source well and 38 pumping wells mix) MW38 N 8.5 5.0 gpm ro T-5465 5046 41/4 COND/NTES T-530- 6.20 gpm(6am-	
		1pm daily) MW113 Area – 1, 82 gpm	

Date:	Tuesday	, February 08, 2022			
Time:	0450	0450 - Plusts operations Good. Pref for Extremenchous street and strongle collection.			
		- Collect TP-740 + TP-710 weekly Low Lord 1, 4 A: Oxane straples. START Extricting cheeks. A	OF collecting TP-730		
		SAMPLES today, UV-OX IS OFF, TOSTING Higher Flows tith the BTS.			
	0630	Restore potable water to reparcel section of 2" piping. Refill polymer	fankwith 200 gallons		
		potable water + 2 cups polymer.			
	080	-Mikeworking on BTS weeking sampling + Freld healings malong			
		- IX System per formance HACH TESTING W/Lab Split Sampling AFTER 1,120, 982 gal Treated: T12-183 - 180 y/k;			
		TP-175A = 190 y/1; TP-174A = 490 y/k; TP-170 = 6000 y/L. system currently kimin			
		- RESTARTED MIU38 N+ Spumping wells going to T-5 40/541 until at least 600gul pumped THN pipel	INC to D. Splace any legitorel		
		source well waters. Source well Stopped 2 0900.			
	1205	- Decant 7-551 to bottom values whet well a cerusal, waster 15 clear wooder.			
		- clean pH-315 probe w/ Acrd 30 Weston. Check the Hond 30 For 0.7 or 5 Hern: None observed. Stray Down wast.			
		- chack TA-130 For offylobules: None observed usager I3 very slightly doudy w/ yellow - orange +174.			
	1230	-letill BTS phosphone TAWK W/6 #OFTSP and 60 gal of potable water. working on 57	5 hadd leadings		
		-Plunts operations Good.			
	1830	990 gallows of MW3EN ? 5 used to displace source well water to T-540/54	1. Switch MUBENIS to		
		RWSTS. Note: BTS effluent continues to transhigher for 1,2 DCA;	1,7-Dioxane, will lene		
		rate from HAR. 30 to 13TS at ~6 gen. Plant operations good.			
			Influent Sources and Flow Rates: @0525 NBBW - 6.3 gpm rowsrs		
			North End On Site- /2,3 gpm		
		(0)	North End Off-Site – &・6 gpm RWST – \$いち gpm		
			NTES – کنه gpm(10R only) MW38 T-540/541 – م ک gpm(Source		
			well and 38 pumping wells mix)		
			MW38 N-8-5 510 gpm somewell 64160 COND/NTES T-530- 0.20 gpm(6am-		
			1pm daily) MW113 Area – k 8 Z gpm		

Date: Wedne	Date: Wednesday, February 09, 2022			
Time: 054	Plant operations okay. BTS effluent still trending slowly upward for 1,2-DCA & 1,4-Dioxane with higher flow rate from Home. 30. Start on weekly GC maintenance and calib-			
V	0750 Blowdown operations god.			
075				
081.	Decant T-351 from buttom value, wet well activated water 53 clear nocoto.	a main a serve a fine		
1	- Clean p. H-315 prope wil nest solven. Cheek tok Hund 30 For oil or siken: None observal. Spray Down wall.	marine, and the same of the sa		
	- Check TP-130 For oil globules: wone observed, weeter Is very slightly cloudy whellow - armse time,			
	Replace solind UAIVE on FV-708. City of Denver mechanics here for annua	l forklift scrutce.		
100	Start UV.0x warming up. 1010 UV.0x warmup completed - discharging.	New solinoid on		
L V	FV- FUB WOCKING WELL.	AND A		
	1030 Backup WTP Olata to Flash drive ? DVD. Daily One Drive backup working well. 1456 - Suspend Alant ABcharge to Replace Discharge pumps 2" check KAHI Valves with New ones. 1506 - Resume Normal ABCharge, small leak, Dring not set correcting. 1509 - Suspend Alant ABcharge to Fix. 1520 - Resume Normal Bischarge again. No leaks, Aloa.			
*				
00000000				
1600				
	, com a open any one opposit			
		97		
		Influent Sources and Flow Rates: @ 0753 NBBW - (.3 gpm (+o Rusts)		
		North End On Site- /2, Zgpm North End Off-Site – 8.5 gpm		
a		RWST - 5.5 gpm		
		NTES - 0.52 gpm(10R only) MW38 T-540/541 - 0.2 gpm(Source		
		well and 38 pumping wells mix) MW38 N & S-I.E gpm (1. Kust)		
The transfer of the second		COND/NTES T-530- 0.2 gpm(6am- 1pm daily)		
		MW113 Area – /. 6 gpm		

Date:	ate: Thursday, February 10, 2022			
Time:	0615	Plant operations good.		
	0710 Switch From discharge pump P.751 to P.752 (New 2" check ball value because			
Mas striken alosed)				
0750 Blowdown operations good. Mike starting on weekly systems checkes and con		s and collibrations.		
0920 - Decant 7-551 from bottom value, cust well actioned. wester 23 Clear Nocolin.				
		"Clean pt-315 ppcine ut word solution. Chell the Hund To Forost or Steen: wine assert. Spray own west		
		- Check TP-130 For oil globules! None osserved, water B clearing U.S. Light yellow-green tom		
4	1140	-Chris usorung on Acid Fume vent 400d motor replacement.		
	1300	New motor; belt unkne on Actal hood went.		
	1314	1314 Reboot HMIFTVIEW to INStall latest your software update, online 1318.		
	1240 Suspend Alan + Britange to Calisane pt-740 prila to 4+10 pts 105.			
		1748 - Rosume wormed Oschurge. Continue with other proposes cultivations to 4+10p45700 204413, 670, 310, 315+365.		
	1340	- Plants Systems cheeks and calibrations complete.		
	1515	2.06 us/L) C 1333. INCrease T-540/5411 to BTS from O. 2 gen to C	ce 16.914/6 \$ 1,2-01E	
D.		2.06 m/ () @ 1333. INCOUSE T-540/5411 to BTS from 0.2 gm to 0	7.350-	
		<i>j.</i>	·	
			Influent Sources and Flow Rates: @ 1754 NBBW - 6.2 gpm	
			North End On Site- 12.3 gpm	
			North End Off-Site – g,7 gpm RWST – 2.o gpm	
			NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.2 gpm(Source	
-			well and 38 pumping wells mix) MW38 N & S- 1.9 gpm	
			COND/NTES T-530- 0.2 gpm(6am-	
1pm daily) MW113 Area – <i>1. B</i>		1pm daily) MW113 Area – <i>1. 8</i> gpm		

Date: Friday, February 11, 2022

1559500	D730	ebruary 11, 2022	HERMANIAN AND AND THE STATE OF
Time:		- Plunts opennous Good. Commy at ox blowdownox.	
	Via	- Decant T-351 to bottom valve. We twell activated water 55 clear wooder	
		- Clan pH-315 proise ut Acid Solviton. Chelk the Hand 30 for oil or steen: None asserved. Spray Down was	7
	1075	- Check 18-130 for oilylobules: None observed water Is clear w/yellow green trint	
	1020	- Ret M &TS phosphores THNK W/4# OF TSP and 40gal of potable water	
27	1035	- Place BTS IN to market wood and those hearters freed wes.	
80	1105	- BTS out of Hold. Leaving p-3324 ON line for Reactor 3, P-3323 EASB.	
9	1200	- Plums openions Good.	The state of the s
5 XX			
8			
			3
			Influent Sources and Flow Rates: @ 2750 NBBW - 6・2 gpm
			North End On Site-/2. 2 gpm North End Off-Site - 8.5 gpm
			RWST - 2,0 gpm
			NTES - 0.52 gpm(10R only) MW38 T-540/541 - 0.27 gpm(Source
			well and 38 pumping wells mix) MW38 N & S- U S gpm
ž			COND/NTES T-530- 2 19 gpm(6am-
			1pm daily) MW113 Area – /, 80 gpm

Operator: Mike Gelwick

Date: SAturday, February 12, 2022	
Date: SATURDAY, 1201407 12,2022 0630 On site for weekerd systems checks. Plant operations good. 0650 Decart T-351 bottom value, wet well disclosed activate. Water Clear the HML-30 weir and PH probe- no oil or sheen observed TP-130 for oil globules - none observed. Water is skillly close 0700 Plant dropping into blowdown - All okay. 0750 Blowling operations good.	
0650 Decart T-351 bottom value, wet well declaret activate. Water	is Clear, No color.
Clear the HULL-30 weir and PH probe- no oil or show observed	in the HULR. 30. Chack
V TP-130 For oil globules - NONE Observed. Water is skilly close	cly light yellow/ 5 rown.
0700 Plant dropping into blowdown - All okay	
0750 Blowling operations good.	
0845 ? land operations good.	
1800 Check plant remotely - All okay.	
2/13/220640 Check plant remotely - All OKAY 1845 Check Plant remotely - All okay	
1845 Chack Plantic motely - All ollay	
	Influent Sources and Flow Rates: @ 6643
	NBBW - 6 • 2 gpm N. END ON-SITE - {2 • 2 gpm
	N. END OFF-SITE - 6. J gpm
	RWST - 2.0 gpm NTES - 0.5[9/M COND/NTES T-530 - 0.21 gpm (6AM-1PM
	daily)
	MVV38 – [. B gpm T-540/541 – 0.3 1 gpm
	MW113 Area – 1.8 gpm

Date: Monday, February 14, 2022

Time:	0615	Plant operations good.	
		Bloudown operations good.	
0805 Reboot HMI FTVIEWI to reset available temporary memory, online 0810.			
	1106 Receive GC fault alam from GCI. Value of 1,10CE las an a calculation cro		.0 spm.
			alculation error
		- Fishelt came out at 1910.05 mg/C. Visually the peak look M Calibration peak at 19:01 mg/C. Other sample values look not	larger than the
		Calibration peak at 14.61 mg/c. Other sample values look not	mal. Ack and
		CLEAR CHOWN. TAKE UVIDX out of FECYCLE. WILL FUN OWNER	Mer TP-730 sample
		early to confirm the crove.	
	1123	- STOP T-530/A-005 to DEFlord/TRANSFOR a load of CT-4 condensate to T-530, 3	START TOTAL = 220802gal.
		on ft-505.	
	1215	-STOP TRANSFOR OF CT-4 Conlargate. FT-505 TOTAL -22/308 gal. ATOTAL ST SE	by al TRANSFERD to T-530.
	1240	- RESTART T-530/poor 20,20ypm 6am-1pm AATy, Cleanur setup.	
	1305	- Decent 7-351 From botton valve wet well actuated. Water Is clear Nocolor.	
		-clean pH-315 probe without solution. Chelle the Howe so For other steen: work as see	and Spray sours wer.
		- Check TP-130 For oil globules: None observed. Water IS clear whellow green that	
		Next TP-730 GCI result value Normal for 1,10CFe H39mg/L	
	1530	- Flam's opening Good	
			Influent Sources and Flow Rates: @ OSC NBBW - 6.1 gpm
			North End On Site- /2. 3 gpm North End Off-Site - 8, 6 gpm
			RWST - 2.0 gpm
			NTES - 0.52gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source
			well and 38 pumping wells mix) MW38 N & S- / gpm
			COND/NTES T-530- 0.1 gpm(6am-
			1pm daily) MW113 Area – /.Ø gpm

Date: Tuesday, February 15, 2022

Date. Tuest	lay, rebruary 15, 2022				
Time: 050	- Physis operations Good.				
051	5 - Collect TP-730 GC/Lab split stimples and START Efficiency cheeks. Also Collect weekly i	T/2-710 and TP-740 Samples			
	for Law Level 1, 4- Brokane				
06	10 RWST'S levels at 271. 261. seduce RWST in fluent from 1.0 g	sun to 0.6 gpm.			
02:	Bloudown aperations good. More working on 573 weekly sumpling + Freld Re	eathy s tolay			
095	5 - IX BY STEM per Formance HACH TESTING W/ Cab SAUT SAMPLING ACTER 1, 139, 108 gol Treater	1: TP-183 2 160 4/11;			
	TP-175A = 180 4/1; TP-174A = 710 4/1; TP-170 = 6000 4/1. System corrently	Running D 1,78 ypm.			
115	Decant 7-35! to bottom volve, wetusell actrumph water Is clear to when.				
	- Clean p. H - 315 probe wheth solution. Check THE Hume 30 For of or 5 Heen; wone assert, spray sour wer.				
	- Check TA-130 for oil globules: None 05 somed water 15 clear al golfongrown that.	Check TP-130 For oilglobules: None 05 somed. warrass clear algollowgrown Hour.			
	- Refit 1 BTS phosphons THUK of 6 Hot TSP and 60gul or potable writer.				
157	-Plunks opensions Goods				
		The second secon			
100/01/0					
		Influent Sources and Flow Rates: @ 055 NBBW – 6:3 gpm			
		North End On Site- 12.3 gpm North End Off-Site - 8.9 gpm			
		RWST – 4.0 gpm NTES – 0.52 gpm(10R only)			
		MW38 T-540/541 - 0.32gpm(Source			
		well and 38 pumping wells mix) MW38 N & Sー いき gpm			
		COND/NTES T-530- O·20 gpm(6am- 1pm daily)			
		MW113 Area – 1.79 gpm			

Date: Wednesday, February 16, 2022

		ay, i columny to, wown	
Time:	e: 0530 Plant operations good. Start on weakly GC maintenax and calibrations.		
1	0750 Blandown operations and.		
	0754 RWSTS levels at 38%: 37% (Slury wall water transfered yesterday). Increase RL		
		in Fluent from O. 6 cpm to 1.0 gpm.	
	0830	IN Fluent from O.6 span to 1.0 span. -Adda New TOTE OF Na OH ON INC DABAGENICHIS	
		- Working on Monthly POTW Leak Refection, AirRelates, Vaults checks and POTW MH175-07	B check and QTR/y
		POTW ISOlation valves Excercising. Using my WIP Laptop and mobile Phone to Log In demotely	
	V	2 each value Excercistry and lest HATTING ABCHAIGE to check for leaks each time.	20
	1015	- Checks of Potus Line complete. All ok.	
	1030	- Account 7-351 to bottom value, wet well Aid Not activate, water FS clear No color,	
	- Clean p.H-315 protes w/ Acid Solveran. Check +THE HAMRESO For sil or speen: None offered. Spray Asian water.		
	- Check TP-130 For oil globules: None observed water Is clear w/yellow-green tint		
		- TOM working an Ellempuss class out.	
	1340	- Filter pers leady to Fill.	
	1420 Reboot HMIZ - online 1423.		
3	1515 -Plans operation Good.		
3470.07.0			
			Influent Sources and Flow Rates: @ 6752 NBBW – 6.3 gpm North End On Site- /2,3 gpm North End Off-Site – 8,4 gpm RWST – 0.6 gpm NTES – 0.50 gpm(10R only) MW38 T-540/541 – 0.31 gpm(Source well and 38 pumping wells mix)
			MW38 N & S- /-8 gpm COND/NTES T-530- 0.2 gpm(6am- 1pm daily) MW113 Area - /-8 gpm

of shoot of an of the stay an

LOWRY WTP OPERATIONS LOG

Date: Thursday, February 17, 2022

Time: 0640	- Plants operations God.	
0700	- Automores Blowdawa operations Good	
970	· Decent T-851 to bettom value wetwell activated unter its clear wocolor.	
	- Clean AH-315 probe when solveron. Cheek MAMIC 30 Foroil orginem: None of served SA ay Some weir.	
	- check TP 130 For oil y lobules: None esserved: water IS clear utyellow green work	
	- START Filturaress hunting on T-351.	3
	- working on weekly Alants systems cheeks and californions today.	
1249	- Suspend plant Discharge to calisone pH-740 proper to 4 +10 pHS 705.	
1256	Resume Normal discharge. Confinue with other Plant pH probes celisostrons to 4 HopHSTAS 2 pH-113, 670, 310, 315+365	
1345	- Plants weekly systems cheeks and cultivations complete.	
1500	-STEP File Press. Finish Filling Homeson,	
1515	- Plants operations Cossi.	
		Influent Sources and Flow Rates: @ 0750
		NBBW - 6.2 gpm North End On Site- 12.2 gpm
		North End Off-Site – 3.3 gpm RWST – 1.0 gpm
		NTES - 2.5/ gpm(10R only)
		MW38 T-540/541 – ••3° gpm(Source well and 38 pumping wells mix)
		MW38 N & S- 1.8 gpm COND/NTES T-530- 019 gpm(6am-
		1pm daily) MW113 Area – 1. 79 gpm

Operator: Mike Gelwick



Date: Friday, February 18, 2022

		ebruary 18, 2022	
		- Plants open work Good, Commy out of Automatic blondown ou. Aspect File piess. In STUGE 4. From T-351	
	Voge		- 100
	13970	- Check TP430 For oil globules: Noncosserved. water of clear why alson-your true Aluce BT3 Into Maint, Hold to Flish Leactor Feed Lives	
	l l	- Restill ST3 phosphores + HANK W/4 # OXTSP and 40gal oxpertable water.	
	1045		-
,	1330	- Plants operazions Good.	
_			
			-
-			-
-72-2			1 /1
		Influent Sources and Flow Rates: @	2 1075
		NBBW - 6, 2 gpm North End On Site- /2.7 gpm	
		North End Off-Site – 9.3 gpm	ŝ
-		RWST - 1.0 gpm NTES - 0.51 gpm(10R only)	
		MW38 T-540/541 — 0.30 gpm(Sou well and 38 pumping wells mix)	rce
******		well and 38 pumping wells mix) MW38 N & S= 1. B gpm COND/NTES T-530- 0.21 gpm(6.	iam-
		1pm daily)	alli
		MW113 Area - 1. 79 gpm	

Operator: Mike Gelwick

Date: 5/41 0	RDAY, February, 19, 2022		
1 W 14 DOL 140 TROUGHTAN	- Plants operations Good, Automatic blowdown operations Good. Go to check other 5.	Le 5 y Junes	
	- Decant T-351 to bottom value. Wetwell did not activate, water 13 clear wo color		
	-Clean p. H.3 15 probe W/Acth SolvHon, Check + HMR30 for oil or sHeen: None observed. Spr	my sour weir.	
	- Check TP-130 For oil globules; None observed . water Is clear why ellow-given +tht		
	-NOtice p-006 mech, sent of Dripping. Prepare For Repair.		
0850	- Stop pool pump to Replace mech. sext.		
	- RESTART p-006/T-540-541 > 6.30 gpm. No leaks ossend.		
1040	- Plants operations Good.		
	- Cemore log to Allow	DECEMBER AND ASSESSMENT OF THE SECOND OF THE	
2100	- Remove Lon Dr. 1911 ox		
	ruary 20, 2022	WINDOWS	
0715 - Renove Log in. Allok. Automore Blandown operators Goal 0905 - GC VOC Alaim. FALSE High 1,1 DCE DUE to Hot water SAMPle. Let 160+ water AASS + 1800 and will take Another SA			
			/300
1930	- Remore Loy on, Allok.		
		Influent Sources and Flow Rates: @ O835 NBBW - 6. Z gpm N. END ON-SITE - /2.3 gpm N. END OFF-SITE - 9.1 gpm RWST - 1.0 gpm NTES - 0.5 Z GPM COND/NTES T-530 - 0.19 gpm (6AM-1PM daily) MW38 - 1.9 gpm T-540/541 - 0.30 gpm MW113 Area - 1.77 gpm	

OPERATOR(S) Mille Grehville

Date: Monday, February 21, 2022

Date. II	ionauj,	Tebluary 21, 2022			
Time: 1	0650	- Plants openings Good.			
	0700 - AL towner blowdown expensions Goal. Reduce Resolts Flow From 1.0 ypm to 0.6 ypm. TAWKS \$276.				
	1840 "Decent T-351 to bottom value wet well activated water to clear wocahor. - Clean pit-315 probe whath 5 oh Hom. Check tok HIMK 80 For all or siken: None observed Jarray Down wer.				
	- Check TA-130 For oil globules; None odservod, water Is clear and yellow years trust.				
0930 - Novimin Alarmongite For Arment fixEXT. Inspection. Gracker Alumes + Sildingularms pesting + stack + low Areventer					
	1100	- All Alwards + BARR FLOW PREVENTERS OF. A FEW FIRE EXT. AROUND STEWED Reflace by and of year. Replacements Will be	ordered		
	1545 - Plunts operanous week				
			78000		
			Life and Course and Flow Botton & as so		
7		·	Influent Sources and Flow Rates: @ 0658 NBBW - 6.2 gpm		
			North End On Site- /2.3 gpm North End Off-Site – 8.7 gpm		
			RWST - 1・ジ gpm NTES - ジ・52 gpm(10R only)		
			MW38 T-540/541 - 0.29 gpm(Source		
			well and 38 pumping wells mix) MW38 N & S- + & gpm		
			COND/NTES T-530- 0,19 gpm(6am- 1pm daily)		
			MW113 Årea – (つ) gpm		

Date: Tuesday, February 22, 2022

Time:	0530	Plant aproations good.		
	0745	Blowdown operations good. Mike preparing forweckly BTS : IX system per	Formance samplingond	
		weekly effectioner checks. Note: Testing split of TP-730 (UV-ox dischose) on 66; lab at		
		BA.M. to should varify warm water 1, LDCE GK Tosults post bloudown are falsly higher		
		due to the warner sample water taking less time to heat in GC	nater baths . Resulting	
		IN a longer period of 1, I DEE aff gassing that under normal operations	· Lalibertions of	
	V	the GC.	Ţ	
	0800	- Collect TP-730 GC/Lub Split SHAMPLE, START EXERCISE Cheeks. Refill BTS PROSPACIES THENK WI	6 # OFTSP + 60 gal or potable water.	
	0820	- Decart T-351 to bottom value. Wetwell Activated water to clear working.		
		- Clean pH-315 proberolite it solution. Check TIK HMR30 For oil or Sitem: None asserved. Stray	Down wer.	
		- Check TN. 130 for oil globales: None observed. water to clear w/ yollow-your frost		
	1015	1015 - Collect TP-710 +740 weekly Low Level 14-0:0xan samples		
	1025 - IX performance HACH testing with Lab Split sampling After 1,157,110gal Treated: TP-183 2 200 ug/k;			
		TP-175A 2 240 ug/C; TP-174A 21090 ug/C; TP-170 26300 ug/L. System currently Kunning	21,77gm.	
		- FALLESAMPLY ON The for conser and worken ST3 Frold Levelings		
	1450	- Plants operations Crosh		
	1515	1,1 DCE Off gassing test completed (Field values). LAB splits shipped today. Ol	oserved warm 8A.M.	
		TP.730 sample lowered the bath to 41.5°C during Fill cycle, then took 12M	inutes 415 seconds	
		to reach 65°c (bath sctpoint). Normal temperature TP.730 dropped both		
		temperature to 30.8°C, then took 17 minutes to reach 65°C. Warmer	North End On Site- 12.2 gpm North End Off-Site – L. & gpm	
		sample sat at 65°C For Universe and 15 secures longer than normal	RWST - 0.6 gpm	
		temperature sample. Note: Calibrations of the GC's performed to simulate	NTES - 0.53 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source	
		wormal apprations by injecting calibration standard into the bath	well and 38 pumping wells mix) MW38 N & S- / - 7 gpm	
	-V	when temperature is between 30°C 132°C.	COND/NTES T-530- 0.1 gpm(6am-1pm daily)	
		Plant operations quelle -	MW113 Area – /. & gpm	

Short pero

LOWRY WTP OPERATIONS LOG

Date: Wednesday, February 23, 2022			
Time: 0545 Plant operations acod. Observe N. End Offsite Flow is down by a possible well that is most likely from due to the extended f	16PM, will book for the		
I possible well that is most likely from due to the extended f	mzing temperatures		
V Work on weekly GC maintenance and calibrations.	, , , , , , , , , , , , , , , , , , , ,		
0740 Blowdown operations good.			
0050 Place BTS into hold for PLC UPS swap out treplacing eight year	ald LIDE reach beat of		
Clarity of the state of the sta	OLL OF SON SELECT SOLUT		
1 (24V Power supplies in the PLC did not power back up when U958 Plant short down outlowetteally due to the loss of common	DE OF THE DISINAL		
24 Power supplies in the PLC and Not power back up when	PLC did.		
0958 Plant shut down alltowatt cally due to the loss of commun	Mation botules Main		
V PLC: Bio PLC.			
1019 Restart plant ofter changing out the bad power supply. Bio o	ut of hold. Lew		
UPS and power supply working well.			
1110 Backup wtp data to Flash ? DVO. Daily ONe Dreve backup works	re well.		
1125 - Account T-351 to bottom valve. wetwell activated, water 13 clear Nowber Clean Alt-315 proper What Soutton, check the Himaso for oil orsider, Nowe observed. Spray Down wer.			
			- Check TA 130 For oil globules; None asserved. water IS slightly cloudy w/ yellow - crange A
MW 107- WI was frozen for to extend very cold tends. ONSide Able potton out and yet Gong Agam. Flow ste			
1530 - Plants operations crost.			
	Influent Sources and Flow Rates: @ 0746		
	NBBW - 6 · 2 gpm North End On Site- 12.3gpm		
	North End Off-Site - 7.3 gpm		
	RWST - 0.6 gpm NTES - 0.5/ gpm(10R only)		
	MW38 T-540/541 - 0.3 gpm(Source		
	well and 38 pumping wells mix) MW38 N & S- /- 7 gpm		
	COND/NTES T-530- 0.2 gpm(6am-		
	1pm daily)		
	MW113 Area - /, 8 gpm		

~ I'N overight

LOWRY WTP OPERATIONS LOG

Date: Thursday, February 24, 2022

	D/ 1 / /		
Time: 0545	Plant operations good.		
0700	- Au tomash Blowdown epen words Crowd.		
0830 - Mike working on weekly/ prosently & hours sign pers checks and calles acres solar			
0910	· Calibrate 572 polymeter TO 506 LEL to use During Calibration Ox LEL-740 to currer Ob LEL IN \$740.		
0918	- Decant T-351 TD bottom valve. wet well activistal, water 13 clear Noccolor		
	- Clean pet-315 prope white solveron. check the Huneso for oil or steen! None asserted. soray down weir		
	- Check TP-130 For oilybubules: None asserved. Water IS Slightly cloudy wy clow - orange +M+.		
1000	START Mouthly of mors fur prevencion hun on main compresson, 2 Hrs - Max speed.		
1145	- For form monthly 673 pt propes calledrations to 4+ 10 pt 6705 (NEW 5703 talay)		
1200	- STOP Main compressor oil prosture prevantan max lun.		
1330			
1403	33 - Suspend Alant Dischurge to califrate pt-740 to New 4+10 pets 705 and Californie LEL-740 to 48% LEL.		
1414	### ### #############################		
	UPS on HML30 PLC and KWSTS PLC with New ones while plant IS OFE.		
1427	- ROSTART Plant and Legione Normal Sistange. Take UV-OX OUT OF Lecycle.		
15 75	- Plunts openations Good.		
	Influent Sources and Flow Rates: 0630 NBBW – 6.2GPM N. END ON-SITE – 12.3GPM N. END OFF-SITE – 8.8GPM RWST – 0.6GPM ONDITIES T-530 – 0.2GPM (6AM-1PM) MW38 – 1.7GPM T-540/541 – 0.3GPM MW113 IX SYSTEM – 1.8GPM OTHER – NA		

OPERATOR(S) Chris Carlson Mike Gelwick

Date: Friday, February 25, 2022			
Time: 0249 Receive N	. TOE Flow unstable alarm. Check semotely and	(see that when T-510 level goes	
low and	BTS is Dut into hold the N. TOF Flow +	T-530 is blocked end of the	
Pipe apple	ics to be Frozen. When T. 510 sefills and Bi	Ts ont of hald flow inturns	
V to Norma	1. Will + subleshoot more when on site la	ater.	
0300 Plant ope	rations good.		
OGUE ON site -	plant one for and.		
0700 Observe 1	J. TOE Flow has stopped when it went sorts	diget to T-530. Able to than	
out the	Smallice blockage on the end of the Pipe	whit with heat gun where	
V heat tra	ce ends.		
0745 Blow don	n operations accol.		
0855 Decant 1	0955 Decart T.351 bottom value wet well actuated Water is clear No volor Clean the		
HUR.30 W	HUR. 30 Well and PH pribe - No oil or show abserved in the HWR. 30. Check TP. 130		
V for oil al	V for oil alobules - none observed. Water is cloudy light yellow / green - 0925 Reduce UV-OX Flow from 7.5 gram to 7.0 gram to help keep T-510 Full while NBIBW rate		
0925 Reduce UV	0925 Reduce UV-OX flow from 7.5 gen to 7.0 gen to help Keep T-510 full while NBBW rate		
V 15 low.			
1300 Refill phospil	www tank with 40 gallons putable water + 4/hs 7	TSP:	
1600 Plant ap	cutions good,		
		Influent Sources and Flow Rates: 0815	
	<u>u</u>	NBBW – 6.1GPM N. END ON-SITE – 12.3GPM	
		N. END OFF-SITE – 8.8GPM RWST – 0.6GPM	
		NTES - 0.51GPM COND/NTES T-530 - 0.2GPM (6AM-1PM)	
		MW38 – 1.7GPM T-540/541 – 0.3GPM	
		MW113 IX SYSTEM – 1.8GPM	
		OTHER – NA	

OPERATOR(S) Chris Carlson

Date: Saturday 2/26/2022 LOWRY WTP OPERATIONS LOG		
1300 Front operations and. 1440 Decent T-351 to bottom valve, Wet well activate clear to color. Check TP-130 for oil globules: None observe very clear by brownish tint. Clear pH-315 probe by acid solution.		
	Influent Sources and Flow Rates: @ 1300 NBBW - 6,2 gpm N. END ON-SITE - 12,3 gpm N. END OFF-SITE - 8,9 gpm RWST - 0.6 gpm NTES - 0.51 9/~ COND/NTES T-530 - 0.0 gpm (6AM-1PM daily) MW38 - 1.7 gpm T-540/541 - 0.31 gpm MW113 Area - 1,8 gpm	

OPERATOR(S) Manuela Seewald

Date: Monday	ite: Monday, February 28, 2022			
Time: 0600	Plant operations good. Start Filter press on T-351 CINSTAGE 1). Refill polymer fank with			
\bigvee	200 gallows potable water + 2 cups polymer.			
0750	0750 Bloudour operations good.			
1050	1050 - Clean SH 315 probe of Act 5 olumon, Chellethe HMETO For all of SHEEN; None asserved, SAray sour wer			
	- Check TA-130 For oil globales: None ous served water Is clear up yellow - green trasts			
	- work on setting is Autos Augstons for mouthly with sampling and SVOC' atty les Ample the	Trople Linie cach dedirected		
	composite commer.			
1135	- AUTO SAMPles Realy. WILL Add Aresenvitores JUST ANTO to START UP.			
1239	- Recent GC I VOC full Alarm. 11-DCE Leading False High 2 2037.14 pp. Distole GCI Hlarms and CC	lears and take UV 0x 0 st of		
	becycle to be able to cool water Down Betwee a NEW TA-730 SAMPLE IS STURETED, STOP FAR FORESS. In-			
1605	- STAKT a New TP-730 SAMPLE on G. Cl and Le-enable Alam.			
1610	- Plants open works (cool)			
1714	1714 GCI rwult of TP 730 recheck reading 12.88 mg/L For 1, IDCE, wormal.			
	(a)			
		Influent Sources and Flow Rates: @ 7772		
2.0		NBBW - 6.2 gpm		
	North End On Site- 12.3 gpm North End Off-Site – 4.2			
RWST - 0.6 gp NTES - 0.5 gp				
		MW38 T-540/541 - 0 · 3 gpm(Source		
well and 38 pur MW38 N & S-				
		COND/NTES T-530- 0.2 gpm(6am- 1pm daily)		
		MW113 Area – /- 8 gpm		

Date: Tuesday, March 01, 2022

		·					
Time:	Time: 0500 - Plusts operators Good. Prefare for weekly Got Split staples, Legitht Fil perpess; State 4 Kroin 7- 351,						
400-10	0575	- collect weekin TP-730 Gc/lan split simples and TP-710+740 Low Level 1, 4-Dioxane :					
	0700	- Automatic Blowdown operations Good. Add preservitions to Dedicated composite stuffe containers.					
		- START AUTOSAMPLUS FOU WIP MONTHLY permit strapling and lessample of QTrly Svocs for He:					
		to Lab QC 575ves. TO THI EFFWent 2 251,450,746gal 26,7250-215.3°C 2 32,5gp	p1,				
		- WOTKING ON 573 weeking situations, Early warring mouthly struples and IX system weeking situ					
	1000	- begin collection or monthly Early warning samples. For To Tel molyla denum + Low Level 1, 4-Dro	exace, somether In to surface.				
	1030	- IX system Performance HACH TESTING W/L-6 Split strapling After 1, 175; 126 gal Frented: TP-18	13 > 230 cy/L;				
		TP-175A 2 270 ug/L; TP-174A 2 2100 ug/L; TP-170 26200 cg/l, used High Range rest a	TP-174A Today. System converty				
		Running 21.77gpm.					
din.	1115	- PACK AUSAMPLES ON The for course PIRRUP. Retill BTS Phosphours TANKW/5 # OF TSP and	50ged of potable water				
	1150	- START Flushor MP-001 Sample port and check for residual chlorine: Nove Detected. Ok to use HCI preserved Wals					
		collect 1st set of Timepaced grab samples for Low Level 1, 4-Dioxane, warm Is very clear Nocolor, Alace SAMVLes I'm Fridge.					
	1250						
		- Check TP-130 For all globules: None asserved. writer \$5 clear why ellow yourse trut.					
	1530	- Alkerruss Ball.					
	1550	- STARTFINSH OF MP-DOISAMPLE port and check For Lesided Chlorine: None reserved.					
	1600	"Collect ? Ad Sct OK Time paced grados simples for Low (evel 1, 4-13 of ane. water 55 very clear, a	ocder, SAMPKS Into Fridge.				
	1610	· Plunts operations Good. Autosomples operations would	Influent Sources and Flow Rates: @ つらまり NBBW – 6・2 gpm				
	1945	Short MP-OUI poil flush and check for residual Chlorine - nome aletected.	North End On Site- 12.3 gpm North End Off-Site – 9.1 gpm				
	2000	Collect 3rd set of thre paced grabs samples for low level 1,4 Diviare water 1	RWST - 0.6 gpm				
		very clar, No color. Place sample in findge with others	NTES - 0.51 gpm(10R only) MW38 T-540/541 - 0.31 gpm(Source				
	The state of the s	Start MP-001 port flush and check for residual chlorine - None eletected.	well and 38 pumping wells mix) MW38 N & S- もら gpm				
	0000	Cillut 4th set of time paced grabs amples for low level 1,4 Dionane, water is	COND/NTES T-530- 0.20 gpm(6am- 1pm daily)				
		voy clear, No color. Place sample with others in the finde.	MW113 Area – 1,77 gpm				

Date: Wednesday, March 02, 2022

Time:	0330	- Plants operations Good. AutosAmplers OK.				
	0350	- START Flush of MP-00 SAMPLE port and Check for residual Chlorine: None Between				
	0400	- collect 5th set of time paced GRAB samples for Low Level 1, 4-Dioxane, water Is very clear, Nocolar, Aluce samples en Fritze with others				
	0630	- Chrisworking on weekly Calibrations and maintenance WISATA SHELLIPS Hoday				
		- SMATFLISH of MACH JAMPLE port and check for besided chlorine: None sexected				
		-STOP AUTO SAMPLES. COLLECT 6th/ Find pat of time paged grab sumbes for Low Level 1, 4-0,0	have waters very clear			
		Nocalar. A lace samples in Fridge. TOTAL Exchant 2251497638gal. Atotal of 46,892 gal treated During sumple period.				
		- Process composite samples by Greatly stirring and check my pH of each composite. SVOCS pH 27.5				
		- Fill composite sample bottles.				
	0825	Stop MN38 N35 in preparation for MW38 source well to Atch extraction (T-540/50	11 @ 24%)			
	0538	ENCRESCE RWST influent from 0.6gan to 2.3gan -				
	0848	Eviter MW38 from direct HMR-30 influent to T-540/541 and startup source well batel				
		extraction.				
	1105	The state of the s				
		- Check TA-130 For oily lobules: Nona Observed. Water Is alear W/yallow-green +-nt.				
	1232	- Receive Bib GC Alurm. BTS Into Hold. Alurm Ove to Disable timer dunning out During a blank den After calibration and carry over				
-		From calibration stranford causing starm with High concentrations, leset DISABLE times and lestinet STS.				
	1300	Broken with data to Flash drive & CD. Daily One Drive backup working well	(,			
	1610	Plant operations good.	Influent Sources and Flow Rates: @0337 NBBW – 6.7 gpm			
			North End On Site- (と3 gpm North End Off-Site – 4ル gpm			
			RWST – Ø∘ 6 gpm			
			NTES – ∅, ≦७ gpm(10R only) MW38 T-540/541 – ∅,3∅ gpm(Source			
	1		well and 38 pumping wells mix) MW38 N & S- (, 5 gpm			
			COND/NTES T-530- 0-20 gpm(6am-			
	- w 1,144		MW113 Area – 1.78 gpm			
			COND/NTES T-530- 0-20 gpm(6ar 1pm daily)			

Date: Thursday, March 03, 2022

Date.		y, maron oo, zozz				
Time:						
0700 Beain Dumpro thick student from Interest #1 # #2 during blandown.						
	0755	Lateral punging completed and HUR 30 refilled. Some of the Hickers	lucke moved over to			
Lateral #3 - will see if it will need claiming if still slow next week. le						
		clear.				
	0315	- Milleworking on weekly plants systems cheeks and calibrations today				
	<i>0</i> 83°	- CleanpH-315 probe WACID SOLUTION. Check THE HAMESO FOR DITORSHEEN: None DESERVED, 5 Pray Down were				
8		- Check TP-130 For oil globeles: Done observed. water Is clear in yellow-green +m+				
	0850	- Mw38 Source well flow went down to 1.0 gpm. Lost power 3 botteres my Have ard.				
	0940	- Chelkon mus 38 sourcement, form 1055. Cycle Drown. Able to restart.	25			
1030 - Muss & source use 11 lost 64+teny power tynen . Atteres my begetting old or the recent very cold outside toursanders may the						
3						
	1124	- START MW38 N 15 pumpmy wells gainy to TEGO/541 until at less + 600 gel Has dun thru Prelime to Displace any resisted				
Mus38 Source well westers.						
	1210	- 5US Rend Hunt Dischurge to california pH-740 probe to 4+10 pH 5103?				
Suppose and the suppose and th		- Resume Normal Discharge. consumure with other pt probes calibrations to 4+10pts TNS = pt-113, 670, 310, 3	15+365			
		- weekly Plants systems checks and califrations complete				
		-Decant 7351 to bottom valve. Wet well active hed. wenter 13 clear to color.				
		- Place BTS Into magnet. Hold to flush Reachers feed Pumps.	Influent Sources and Flow Rates: @ ce/s NBBW – 6. Z gpm			
	1500	-BTS OUT OF HOLD. OK	North End On Site- i 2.3 gpm			
	1739	€-70/gal flushed thru muss prective. Switch muss N+5 pagerny wells to cens 13, switch munual values	North End Off-Site – & 7 gpm RWST – 2-3 gpm			
		to GO to Hime 30.	NTES - 0.51 gpm(10R only) MW38 T-540/541 - 0.20 gpm(Source)			
	1745	- Plants opensions Good.	well and 38 pumping wells mix) MW38 N&S S. O gpm source well to the h			
			COND/NTES T-530- P pm(6am-			
			1pm daily) MW113 Area – 7.7∂ gpm			
45						

Operator:	Mike Gelwick / Chris Carlson	

Date: Friday, March 04, 2022

	- 1		
Time:	0600	Plant operations good.	
	0700	Observe HMR 20 studge laterals are partly clossed again - will worken	pumping out build
		up sludge from their this moving.	, , ,
	0738	Switch MW3ENSS back to cliract HOME-30 influent.	
		- Work W/Ch-i3 to for a new Tok out NaOH ONline In chamital Body.	
	0825	- Decant T-351 to bottom value, wet well activated water is clear Nocolor.	
		- Clean pH3K5 probe w/Actol solvian. Check the Hont 50 for oil or steen: Nove observed. Stray bou	en wer
		- cheek TA 130 For oily lobeles: None asserved. water Is clear uf yellow green tist.	
		- Caltistate Contal GEM 5000 SNEG506891 /Provedental ID43409 to 2.5%/50% CHy: Res	way 2.45%. For QTFly
		Buildings Methane 84Fety checks with That & Am working on haray.	
	0900	Observe latest BTS effluent GC issult from GAM looking Normal. Increase T-540/541 from	
		$[0,2,\dots, 1,0,2]$	
	0915	Work on Escing up sludge laterals and transfing extra sludge to thicker tank. Note: BTS i UV-OX going into holy / steycle while T-510 low during cleanum t.	
		UV-OX going into hold / recycle while T-510 low during cleanunt.	
	1430	> - 5:70 Buildings making specing chauss and GAS probes complete.	
	1440	0 - Plums opening Good	
		·	
			Laftered Courses and Flow Batter & Color
			Influent Sources and Flow Rates: @ &2≥3 NBBW - 6⋅3 gpm
			North End On Site- 12.3 gpm North End Off-Site – B.c. gpm
			RWST - 015 gpm
			NTES - 248 gpm(10R only) MW38 T-540/541 - 2.14 gpm(Source
			well and 38 pumping wells mix)
			- MW38 N & S 1.9 gpm COND/NTES T-530- <i>O-O</i> gpm(6am-
			1pm daily) MW113 Area – <i>I</i> , 76 gpm
			MATTO MOR - 1' VO Abut

Date: Saturday, March 5, 2022 0740 Plant operations good - Decort T-351 to bottom value. Wet well not activated, water is very clear 0800 -clean ph-315 probe with acid solution. Check HMR30 for oil or sheens: None observed. Spray Well-checked Tp-130 for oil globales: None observed water is very clear with a yellow true. - Plant operations good 0900 - Filled phosphorus tank with 6 LBS of TSP/60 gallons H20 0830 Influent Sources and Flow Rates: @0740 NBBW - **6.2** gpm N. END ON-SITE - **j2**, **3** gpm N. END ON-SITE = 72,0 gpm

N. END OFF-SITE = 7.0 gpm

RWST = 0.5 gpm

NTES = 0.52 gpm

COND/NTES T-530 = 0.0 gpm (6AM=1PM daily) MW38 -1.8 gpm T-540/541 - **D.32** gpm MW113 Area - 1, 8 gpm

OPERATOR(S)	Tom Gilbert	
0. L		

NEW P.M -

LOWRY WTP OPERATIONS LOG

Date: Monday	, March 07, 2022	9	
	Plant operations good. Setup to pump extra studye Frankfur. 30 laterals	pluing blanchour-	
0700	Shirtleins UV-0x so lamp can be chanced out. Also switching out battery and UPS.		
	Begin pumping extra sinde Note: after bloudown observed the pump not moving any sludge. After troubleshooting ditummed the was clogged. This line has a lot of colleium buildup - desice	HMR. 30's 1" 5 ludge	
	DUNG NOT MOVEN - AND Sturley After troubles houte diturn me (the	line Fudire it	
	was aloned This live has a lot of polerum builder - desich	ed to restare it	
	with New.		
	Classed at UNION laws but PLC Eviled to Doube Un - Contract	al Born Hill to	
	see about supposing and the Old (the unce al stack waters	January Mrs	
	Changedout UV. 0x lamp but PLC Failed to power up - contact see about swapping out the PLC (they were already working a Dorect logic's program to aller Bradly) (May try to rewise the C	live + lacis & to	
	an action of the second of the second of the	Bio and offer the	
VI- V-103	de externa 1 pour supply in the mean time, freque to the	540 /541 - F 500	
	don external power supply in the mean time. Propose to The Bio only after the clarific until the UV. 04 PCC issue is resolved. Will leave To 540 /541 off for		
	Now while 4h 1375 adjusts to the higher flow rates		
	New HMA30 sludge lateral line working well		
0000 000	-New Statety Status prosmiled		
1600			
	- Clean pit-315 probe w/ herd Sourton, Chek the Hund 30 For off or Steen, wore assend. Stray draw	a campita	
	- Check TP130 For of globules; None asserved. When to clear of yellow-year tout.		
1615	- Plants openanos OK.	Leftwork Common and Flow Botton Code	
		Influent Sources and Flow Rates: @ /6/6" NBBW - 6-3 gpm 104-573	
		North End On Site- 12:3 gpm North End Off-Site – 2:6 gpm	
		RWST - 4.0 gpm	
		NTES - ⊘ √ ♡ gpm(10R only) MW38 T-540/541 - ⊘ ∵ gpm(Source	
2.000		well and 38 pumping wells mix) MW38 N & S− ℓ · · · gpm · · · · · · · · · · · · · · · · · · ·	
		COND/NTES T-530- Ow gpm(6am-	
		1pm daily) MW113 Area	

Date: T	uesday,	, March 08, 2022		
Time:	0220	Plant operations o Kay with UV. Ox offline, latest TD-3350 result @ 6.7	usil for 1.41 Dioxane.	
	0600	INCREME the BILLS INTIMENT FOR YEAR TO STOM. Stort NEXT TO 2350 Council early		
	\checkmark	Brish well & effectively be sampling.	,	
	0700	Begin weekly effectively be sampling. Observe HMR 30 laterals clogged again, manually pump down lateral out ports. LAturals #1? #2 cleared clusing blockdown, #3 Still partly	clasufers using dean.	
		out ports. LAturals #1; #2 cleared during bloudown, #3 Still partly	closed and could use	
		I VIL I LIAM IVA		
	0600	Work on sluce latural #3 - 0820 Latural #3 better #1: #2 very gove	1. HMR-30 Sefulling	
		Mike working on weekly BTS ! IX performance sampling today.		
		- Collect weekly TP-740 + TP-710 samples for Low Level 1, 4-1, of ane		
	1050	- DX Acr to mance which restring while split sampling Acres 1,192, 977gul trenkd: TP-183 - 150 uy.	16; TP-175A 2 150 ug/6;	
		TP-174A 23400 ug/L; TP-170 06300 ug/L. SysAM CUTELTY RUMA, 2-1.75 pm.		
	1100	- Decent T-351 From porton value. Wetwell activated. Wester Is clear Nocober		
		- Clean \$4-315 probe cel Herd solveren. Check + the Hand 30 for oil or steen: Nove asserd, spray Down wer.		
		- Check TA130 For oil globules: Nune ossered, water is clear w/ yellow year pout.		
	1210	-working onwealing 513 field kentings. Refill 15 phosphores TAWK wis tot TSP and 50gal o	of potablewater	
	1400	BACKWARL GACF-3340. Observe latest BTS effluent GC result @ 6.	21 ug/ Cfor 1, 4-DioKone.	
	14125	Stop RWST INFluent and Hake NBBW out of divert to RUST. This will	INCREASE FLOW to	
		BT3 by ~ 1.350m.		
	1530	Punts opensions Creek	Influent Sources and Flow Rates: @ \$452 NBBW - 6.3 gpm 7>4-573	
			North End On Site- / 2-7 gpm North End Off-Site – 多の gpm	
	RWST – 5 i⇔ gpm			
			NTES - ○ . SO gpm(10R only) MW38 T-540/541 - ○ ○ gpm(Source	
			well and 38 pumping wells mix) MW38 N & S-116 gpm 72 Ame 3.3	
			COND/NTES T-530- 0 ↔ gpm(6am 4 1 pm daily)	
			MW113 Area – 1, 74 gpm	

Date:	Wedneso	day, March 09, 2022		
Time:	0550	Plant operations okay, GCZ TP3350 (BTS cffhent) up to 46 ug/c 1,40. NBBW and MW38 Nº 5 worter being sent to the HAM-30 / BTS. Start of	ioxane with All of the	
		NBBW and MW38 Nº 5 worter being sont to the HAR-30 / BTS. Start .	I weekly GC maintenance	
		0,-0-0,0,0,0		
	0700	Decant T-351 bottom value then worked clearing the HUR:30 lateral	s diving bloudown.	
	0730	All three laterals working well. Start filtrpress on T-351 (IN Stage 1) - Clem pH-315 probe wither soweron. Check the HIMESU FOR OF STREET: None OFFERENT Spray sown		
	08,40	- Clem pH-315 probe w/ Acid 30 WHON. Check the HUMESU FOR ON I HEN: None OF served spray sown	cutain,	
		- Check TA-130 For oil globules: None observed, us when 53 clear uf yellow grown trut.		
	1100	Backup with data to flash drive and DVD. Daily One Drive working well	•	
	1335	Observe latest BTS effluent be result has anatred consistant area	and 46 mg/L For 141 Dispare	
		Restart RWST INFluent at 0.6 cam.		
	1500	Restart RWST INFluent at 0.6 gpm. Shutdown Filterpress (IN Maye 4). Plant operations genel.		
2-74				
			Influent Sources and Flow Rates: @ 0855 NBBW - 6. 2 gpm	
			North End On Site- 12.3gpm	
			North End Off-Site – 9.0 gpm RWST – 0.0 gpm	
			NTES - 0.56 gpm(10R only) MW38 T-540/541 - 0.5 gpm(Source	
			well and 38 pumping wells mix)	
			MW38 N & S− 1.6 gpm COND/NTES T-530- 0.0 gpm (6am -	
			1 pm daily) MW113 Area – 1,75 gpm	
			marria and the general	

Not over the stanty.

LOWRY WTP OPERATIONS LOG

Date: Thursday.	March 10, 2022		
Time: 0555	Plant operations okay. Lastest BTS GCZTP-3350 result up to 147ug/L.	. Start GCZ early un	
<u> </u>	Next TP-3350 sample.		
0700	Wak on purposthe HAR-30 studge laturals classents ching bloodown-		
0720	lateral #1: #2 clear. #3 still partly clossed but getting better with e	very eleanout attempt.	
0900	- Working on weeking plants Systems Cheeks and Cultibrations today		
0935	- Cleary 4.315 probe what 30 h Har. Check the HIR 30 For oil or siteen: None absenced. Spray	goon wur	
***************************************	- Check TP-130 For Oil globales: None observed. water Is clear w/y ellow- green trust		
1305	- Suspend Plant Arschurge to cultorute pH-740 probe to 4+10 pASTO!		
	- Resume Normal Discharge. Continue wother proper cultbrations to 4+10pH5TO' 2 pH 113, 710, 315+	365. UV-OX OFFLINE NO california	
	2 рн-670 тызычек.		
(350	- weekly plants systems cheeks and calibrations complete.		
	Work with Dan G. on plan to test THE augmentation of the biological system to increase it's efficiency		
	to trul 1,4-Diopone during peoples pertous of low retention times Chistorically when more THF miss		
	was present the brological process was able to handle for greater flows a	and still fearere 14 Divione	
	with grat cfficiency). This " pilot test" will consist of dosing 94.49%. THE at 20	.5 ml for zerolay into	
	the Blend Tank T-3320 at 5ml doser.		
	- STOP FILM ASS. STELLART PULL JURINGE 4.		
	- Plants operations Coold.		
	[Influent Sources and Flow Rates: 0615	
	Receive call from DAN G. Going to wait on THF augmentation testing. Go about and store water to bring the BTS back to normal operations	NBBW – 6.2GPM	
	while UV-OX is down for repairs.	N. END ON-SITE – 12.2GPM N. END OFF-SITE – 8.6GPM	
	-A)	RWST – 0.6GPM NTES – 0.53GPM	
		COND/NTES T-530 – 0.0GPM MW38 – 1.6GPM	
		T-540/541 – 0.0GPM	
water the same of the same		MW113 IX SYSTEM - 1.7GPM OTHER - NA	
		1	

Date: Friday, Ma			
Time: 0450	Plant operations okay. BTS effluent at 132 ug/ 1,41-Dioxane overty b.	+. Reduce Flow to	
	Plant operations okay. BTS effluent at 132 ug/L 1,4-Dioxane overty ht. Reduce flow to BTS by switching MW34125 well to RWST and Stop RWST INFLUENT to the plant to increase		
V	reference in the BTS.		
0638	Start GCZ early un Next TP 3350 BTS effluent sample. Work on Flushing	the HMR-30 studge	
	Start GCZ early un next TP3350 BTS effluent sample. Work on Flushing leuter line using potable water and compressed oir while IN blowds	own. Start Filterpress	
V	0N 1'33 1 (1N 34A5C 4),		
0950	Lateral Flushing completed #2: #3 are very good and cheer latera	(41 still partly classed.	
0960	Latest 13TS effluent GC result at 119 mg/L for 1,4-Digrane . with 40 gallon potable water + 4165TSP. Clean the HAR. 30 weir and	Refill phosphows JAK	
1	with 40 gallows potable water + 4165TSP. Clean the HOUR. 30 weir and	paprobe - No oil or	
ļ , , , , , , , , , , , , , , , , , , ,	Sheen observed in the HUR-30. Check TP-130 for oil globules - None obse	ared Water is very	
	clear, light yellow / sien.		
1015	Decant T-351 top value, wet well activated Water & clear, No colon		
1130	0900 TP-3350 BTS efflunt result down to 65 as /L 1,4-Dioxare.		
1200	Plant operations gove.		
1737	GCZ result at 55 ug/L for TP-3350 - Plant upr g and.		
Mark Control of the C		_	
		Influent Sources and Flow Rates: 0855	
		NBBW – 6.2GPM N. END ON-SITE – 12.2GPM	
		N. END OFF-SITE – 8.7GPM RWST – 0.0GPM	
		NTES - 0.54GPM	
and the second s		COND/NTES T-530 - 0.0GPM MW38 - 0.0GPM (1.5GPM to RWST)	
		T-540/541 – 0.0GPM MW113 IX SYSTEM – 1.8GPM	
		OTHER - NA	
		<u> </u>	

OPERATOR(S) Chris Carlson

Date: Saturday,	March 12, 2022		
Time: 0600	Plant operations good. 2AM BTS effluent GC2 TP3350 result at 6/4/6 for	1.4.Dioyane	
0700	Ha Prime extra sludge and flush lateral # 1 with potable water & C		
	blandown. Clean the HAVR-30 we'r and pH probe - No oil or sheen observed		
V	Check TP-130 for vil globules - none obscived. Water is very clear light	at yellow / green.	
	All three laterals clear. Note: Decanted T-351 top value and started		
l	before blowdown. Wet well was activated, water is clear, NO CO	lor.	
	W.M. + (Anstering slurry wall mater to RWST's today.		
0900	Stop Filterpress. Decant T. 351 bottom value, wet well active to d. Wat	crischer no solos.	
	Plant operations good.		
	Laster of TP-3350 BT3 elfluent result From 1030 @ 37.96 ug/L for 1,41 Dioxan		
3/3/22 0715	(06/5 Plant time) Check plant score tely. Plant operation akay. TP-3350 up to 75 ess/L. Should		
l — —	come back clown one depart water from T. 352 has been processed (T. 357 @ 47%).		
	RUST e 68% & 67%.		
08/5	(15715 plant time) Check blandown aperations contely. Start RUST e Ggam and sent MUBBNSS to		
	HUME-30 during resill stage to shorten the time? + + takes to refill the u		
	to be clear, took NOMENNESS to setill even with the added flow.		
•	and set MUSEN'S to direct to Rast when HUK. 30 Full at 0826 (0.	18.	
1/40	(1900 planting) check remotely. GCZ TP.3350 14. Diagram & Blug 11. Decant to 1		
2025	GC2 TP33501, 4-Dionen result at 66 mg/L. Plant aprigord.	Influent Sources and Flow Rates: 0620 NBBW – 6.2GPM	
2000	och 11 5/3 o 17 or blogging (issue) all bought. Com app gott.	N. END ON-SITE – 12.2GPM N. END OFF-SITE – 8.6GPM	
		RWST = 0.0GPM NTES = 0.52GPM	
		COND/NTES T-530 – 0.0GPM MW38 – 0.0GPM (1.5GPM to RWST)	
		T-540/541 - 0.0GPM MW113 IX SYSTEM - 1.7GPM	
		OTHER - NA	

OPERATOR(S) Chris Carlson

Date: Monday, N			
Time: 0530	(0430 Plant time) On site - plant operations good (RWST's e 74% ? 73%	1., will transfer some	
V	(0430 Plant time) On site - plant operations good (RWST'S & 74%, 973%, will transfer some water to backup Frac tank today). Work on changing clocks to DST on GC CPU's trebusting them. Shutdown plant and upclate clocks on HMIS FPLC to DST. Rebust HMI's.		
0537	Shutdown plant and update clocks on HMIS FPLC to DST. Rebust b	INI's.	
0552	Kestart plant.		
0645	Decart T-351 bottom value, wet well activated. Water is clear, no	color. Clear P-352	
	y-strainer.		
07.15	Blowdown operations okay. Perform some masor cleaning of lateral #3	using the classout	
V	port while unit was in the space cycle.		
0840	Start fellerpass and T-351 (In 14age 4)		
0900	- Begin TRANSFER OF RENSTS was for to tempty ERACTANIED LINSTS TO Make LOOM IN RUSTS FOR EXTERNING	per.	
0930	- Replace buttom NaOH Total with Fresh New owes and more old ones to top Position For More Asoun a	ta later point. Replace peroxide	
	to te with a Fresh New one and Save Remandor on oldestels later use. (cc rma)		
1045	- Clam pH-315 probe whited solution. Check the Home30 for off or stken: None asserved. Spray	Distance Case, so.	
Another Title	- Check TD 130 For or 1 globales; None asserved: water IS clear w/y ellow green trut.		
1/15	- STOP LIUSTS WHEN TO FAMS FENTO FRANCIANIK (T-103), THINKS 2 16% + 56%. STITLS COMERCIAN IN FRANCIANIK T-103	IX needed After TANKS Equile.	
1345	- Collect Sem: - Annual Sluge Samples For TENORM, TCLP and RADS.		
1505	- Alums operations Grown		
		Influent Sources and Flow Rates: 0531 NBBW – 6.1GPM N. END ON-SITE – 12.2GPM N. END OFF-SITE – 8.6GPM RWST – 0.0GPM NTES – 0.52GPM COND/NTES T-530 – 0.0GPM MW38 – 0.0GPM (1.5GPM to RWST) T-540/541 – 0.0GPM MW113 IX SYSTEM – 1.7GPM OTHER – NA	

OPERATOR(S) Chris Carlson Mike Gelwick

Date: Tuesday	, March 15, 2022		
in the second se			
Time: 0600	Plant operations good. TP3350 result overright @ 704/c - Influe	ent flow to BTS	
	at 5-0 gpm. Start weekly GC effectively sampling.	ON RUST INFLUENT	
lacksquare	at 5-0 gran, Start weekly GC effectiver sampling.		
0 +00	thup extra studie tom lateral cleanouts during the ourspace	cycle of blockurs	
0730	All there laterals purping well. Temporary then an DBBC & MC 38 1 TIFIL the Home 30 quicker. December T-357 from bottom valve. wet well activated was	U's s influents to	
✓	MFill the Hall 30 publices. Decented T-357 from bottom valve wet well activally was	ter 15 class nocolor.	
0750	HUR-30 reFilled, place NBBW and MUSEN'S BACK to RUST divert.	Mike occaping For	
	welly performance sampling & Field reading 5 For STS	, , , , , , , , , , , , , , , , , , , ,	
1000	- collect TP-710+TP-740 weekly Low level 1, 4-Orothers samples.		
1010	- IX performance HACH Testing W/Lab Split sampling AFTER \$1210,401, al prested! TP-10	83 2 200 y/L;	
	TP-175A 2220 ug/L; TP-174A 23800 ug/L; TP-170 26500 ug/L. currently system knowing 2 1.77 ppm.		
1413	-Clem AH-315 probe MACH Solvern, Check the Home 30 For oil or steen; None osserved Sarry down wer		
	- Check TP-130 For Oily loboles: None asserved were poder u/ yellowyneen wat.		
1550	D - Plunts apenning hose		
		,	
		Influent Sources and Flow Rates: @ ASS NBBW - 6·2 gpm (+o kws) North End On Site- 12·2gpm North End Off-Site - 9·/ gpm RWST - 5·D gpm NTES - 0·S gpm(10R only) MW38 T-540/541 - 0·0 gpm(Source well and 38 pumping wells mix) MW38 N & S - 1·6 gpm (+o kws) COND/NTES T-530- 0·0 gpm(6am-1pm daily) MW113 Area - /.6 gpm	

Operator:	Mike Gelwick / Chris Carlson	

Date: Wednes	day, March 16, 2022	
Time: 0600	Plant operations good. BTS estiment GCZ TP-3350 1,4-Diomore result a + 22, Decent T.351 bottom value, wetwell activated. Water is clear, No	egl Start on weekly 61 maint.
0640	Decent T.351 bottom value, wet well activated. Water is clear, No	color.
0725 Bloudown operations good. All three studge laterals clear - NO extra cleanout pun 0800 Incruse RWST influent from 5.0 gpm to 5.5 gpm.		
	- Check TA180 For oil globules: None orssand. water to clear w/yellow-green trut.	
 	- he fill polymer TANK w/ 2 cups OF NALCO polymer and 200gal of potable water.	
1045	Bades are data to Flash Drive i DVD. Daily One Drove backup working u	rll,
	0940 - Working on QTrly 673 Blavers severing today. 1400 - STOP N.End ONSINE Flow to Repair a Groken value on NGSW-IW-3 Valle. NOTE: NGGWIEW 3 23 OFF CUrrowthy, Put a Phy on the cambre	
piping.		
1425	- RESTART N. END ONSIZE.	
1555	- Plants operations Good	
		20
		al .
	9	
		Influent Sources and Flow Rates: @CASD NBBW - 6.2 gpm
		North End On Site- 12,2 gpm
		North End Off-Site – 8.7 gpm RWST – 5.0 gpm
		NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.0 gpm(Source
		well and 38 pumping wells mix) MW38 N & S- 1.6 gpm(+6 RwsT)
		COND/NTES T-530- O.D gpm(Sam-
		──

WET SNOW OVER NIGHT, SDEWING STILL EGATHS SDEWING THES MANNEY, O. 54" IN I WAS C.

LOWRY WTP OPERATIONS LOG

Date: Thursday, March 17, 2022

Time: 0725	- Plants operations Good. Coming out of Automatic Slundam ok.			
0900	- Workingsh weekly Alants Systems checks and californitions today. Hall 30 studge laterals sounding very clear today			
0930	- Decant T-351 to bottom value, wet well acts water of clear NO color.			
	- Clean pH.315 probe without solution. Check tok Home 30 for oil or steer: None observed. Spray Down	work,		
	- Check TP-130 for oil globules: None observed. water IS clear w/yellow-green +1n+.			
1300	- Acrol/BASE Clean BTS p. H. probes In Preparation for cultigration went areck. - Suspend plant Oscharge to californic p. H-740 probe to 4+10 p. H 5703.			
1423	- Resume Normal Discharge. Continue with other pH probes calibrations to 42NOHSTA' 2 pH-1/3, 310, 315 STILL OFFICE DUE TO PLC ISSUES.	+365, NO pH- 670 cultbrands LIV-OX		
1500	- Weekly Plants systems checks and cultisorations couplete.			
1540	- 17 law soperations cross			
		Influent Sources and Flow Rates: @ D8/NBBW - 6.2 gpm rowsrs North End On Site- 12.2 gpm North End Off-Site - 8.7 gpm RWST - 6.0 gpm NTES - 0.50 gpm(10R only) MW38 T-540/541 - 00 gpm(Source well and 38 pumping wells mix) MW38 N & S - 1.5 gpm rowsrs COND/NTES T-530- 0.0 gpm(6am-1pm-deily) MW113 Area - 1.75 gpm		

Operator: Mike Gelwick

Date: Friday, March 18, 2022

	,	GICH 10, 2022			
Time:	0730	- Plants operations Good. Coming out of Automotic blowdown ok.			
	0810	- Recart 7-351 to bottom value wetwell activated. Weter Is clear was colon.			
		- Clean & H-315 probe WARN SOKUTON. Check THE HUMR 30 For oil or Steen: None Of Served. Strug Down	h wer		
- Check TA-130 for sily lobeles: None asserved. water 55 clear w/ yellow green +in+.					
	1057 - Put NBGU INTO NORMAL and STOP RUSTS DUMP to TRANSFER MORE RUSTS LINES TO FRACTORIES FOR STURING (T-103 +T-104)				
	1130	130 - WORK ON BACKWASH OF GACF-3340 BTS CAFBON VESCEL.			
	1200	-T-103 FRACTANIK ICH, Switch over 40 T-104 Frac HANK			
	1345	15 - STOP TRANSFER OF RUSTS waters to T-104 FRACTANIE. T-101 212%. REVIVED 15 phosphores + MNK w/4# of TSP and 40, alpoteble was			
	1400	1400 - RESTART KUSTS Klow & 6.5 gpm to HMR30 and AUTNOSEW BACK to OWERT to KUSTS.			
1520 - Plants operations crowd					
			Influent Sources and Flow Rates: @0755 NBBW - 6:2 gpm rows73 North End On Site- 12.7 gpm North End Off-Site - 6:3 gpm RWST - 6:5 gpm NTES - 0:49 gpm(10R only) MW38 T-540/541 - 0:0 gpm(Source well and 38 pumping wells mix) MW38 N & S - 1:5 gpm rows73 COND/NTES T-530- 0:0 gpm(6am-4pm.daily) MW113 Area - 1.75 gpm		

Operator:	Mike Gelwick	

Date: SATURDAY	MARCH 19	SOSS
----------------	----------	------

0800	- Pleasts operations Goal. Goto Check other 512 systems.
	- Sile systems ou Decant T-351 to bottom vulve. Wet well actuated water to clear wocolor
	- Clean \$4-315 probe w/ Act solution. Check the HMC80 for oil or steen : None of seved. Stray Down weir.
	- Check TP-130 For oil globules: None observed, water 13 clear of yellow-green fints Clean P studge mess on two from F. Hard- 1855 wellow t.
	-GCZOK. All Blowners Olly Both Afflows ystem good.
1100	- Plants operations Good
2000	- Remote by In - Allow
SUMMy,	MARCH 20, 2022
0845	- Remove Log in. P-357 Alarming But surtoff OR. ACK. Alarm. W.71 Cremy Stoner monday.
2200	- Remok log in. Allon.
	Influent Sources and Flow Rates: @ office NBBW - 6-7 gpm recent NBBW - 6-7 gpm recent NBBW - 6-7 gpm N. END ON-SITE - 6-5 gpm RWST - 6-5 gpm NTES - 6-5 gpm NTES T-530 - 6-9 gpm (6AM-1PW daily) MW38 - 1-5 gpm rotust
	T-540/541 - 0+0 gpm MW113 Area - 1,73 gpm

OPERATOR(S) Mille Chelwille

Date:	Monday,	March 21, 2022	
Time:	0600	Plant operations okay. BTS effluent overning overnight of 33 us 16 to 1/4	1-DioRAM (NAS been in
To the second		30'S All wakers ().	
		Observe HMIZ has a Windown warning about possible haddrive failu	re due to an error
		it has detacted. HMIZ appears to be operations normally other than it	his pop-up rerror
		Observe HMIZ has a Windows warning about possible hardrive failust has detected. HMIZ appears to be operating normally other than & massage. Create a restore point and backup RSVIEW TAGS / screen	ens to flashetive
	-1/	MIST IN CASE IT GLOSS CIASIS.	
		work on secluing the size of the one minute data base on fut than He	
28	<u>080</u>	Blowdown apertions good. Reduce RUST influent from 6.5 gpm to 5	
3		MW3ENSS from RUST to direct HM-30 yaftuent. This will incom	are the flow to the
		BTS by ~ 0.4 spm - Work on sludge DOX chartwaste characterization.	
	0815	-Clean p-352 y strange lastart. OK 7 636CV and 0. Sogpm.	
	- Account T-351 from bottom value. We twell activated when is clear assessor		
	-Clean AH-315 probe w/ Act Solution, Check + He Home 30 for ottor 8 Hen; Nove of serval. Spray Soun war.		
	V - Check TM 30 For oil y bobcles: None observed. water to clear w/ yokonf ren for 1.		
	0004	Stop HMIFTVIEW 1 to Start using smaller One MIN data File	
	0905 HMIFT VEW ! ONline Work on making the One Minute Bto Los fito smaller.		
7-31.	0935	J.M Barry and Field Condova of Brund Hill on site to beging to replace it	he UV-OX PLC
		Stop HMIFTULEWI to Start using smaller Biolog data File	Influent Sources and Flow Rates: @ 0805
		HMIPTUIENI ONline, Continu waste characteristics of the full sludge box.	NBBW - 6.3 gpm TOK-173 North End On Site- /2.1 gpm
		Mike has seplaced + 1k Auto Samplers Tellor toking to T-740.	North End Off-Site – 8.9 gpm
-	1545	Plant operations good. Jim Reduring tomorrows to complete programming.	RWST - 6.5 gpm NTES - 6.5 gpm(10R only)
		Reduce RUST influent from 5.5 gpm to 5.0 gpm.	MW38 T-540/541 − OO gpm(Source well and 38 pumping wells mix)
	· ·		MW38 N & S- 1.4 gpm F0 644573 COND/NTES T-530- 0.0 gpm(64m-
1			1 pm daily) MW113 Area – 1.74 gpm
			MANTIO Alea - 1.7 r gpm

Date: Tuesday, March 22, 2022 Time: 0600 Plant operations okay. Short on weckly plant efficiency checks. Setup to I'm UV-0x effluent post PDU back to the HARWST'S for texting. UV-08 Flow totalizer at start 21439567 gal JIM B. ON site to complete UV. OX programming and test / certity UV. OX alarms & shutdowns. Blowclown operations good. Mikeworking on 613 weekly sampling + Field Kentings rolling Power up UV-OX and fine tune programing (UV-OX obschooling to PLUST'S) 0835 - Decant T-351 from bottom velve. wetwell actuated, usuter IS clear wocobor Clean AH-315 probe w/ Acth solution. Check the Home 30 For off or steen: None observed. Spray Down wer check TA-130 for oil globules: None of served water Is clear wheellow- green that. 1900 - Recilors prosphers +ANK N/5# 05 TSP and 50 gil of pumble wither. - collect weekly TP-710 + 740 Low level 1,4-Oroxane samples. 1020 1035 - IX Performence HACH resting w/cab split sampling After 1,228,018 gol treated: TP-183 2 2404/6; TP-18542290466; TP- 17442 4300 ug/c; TP-170 2 6500 ug/c, system currently Running 2 1.73, pm. 1500 Jim has the UV-OX running well. Shutchan 3 Warning alwars tested RWST'S towight. Will take a few OC samples of TP-730 to confirm the units operations before duchagin, to full surge tank. 1540 Plant ups good. 1600 Chick peroxide values: Post PDU (TP-730) Oppm, Post UV. Ox (TP-720) 25 PP Influent Sources and Flow Rates: @/533 Pre UV-OX 100 ppm. NBBW - 6./gpm North End On Site- 12 . 1 gpm North End Off-Site - 8.6 gpm RWST - 5.0gpm NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.0 gpm(Source well and 38 pumping wells mix) MW38 N & S- 0.0 gpm COND/NTES T-530- 0.0 gpm(6am-1mm daily) MW113 Area - 1.73 gpm

Operator:	Mike Gelwick / Chris Carlson	

Date: Wednesday, March 23, 2022	
Date: Wednesday, March 23, 2022 Time: OSSO Plant operations good. UV. Ox operated as expected overnight in recycle to RWST (post in GCTP 730 samples taken overnight indicate the 545th is working correctly. Start on Newthy GC maintenance and calibrations. ON Westly GC maintenance and calibrations. OTOS Place UV. OX back to normal obscharge to Freed surge tank during blowdown - UV-OX totalizer reacting 21447654 gallows. Total of 8,287 gallows of UV-OX V two water returned to the RWST's. OTHO Blowdown operations good. Begin treating stored worter. No tequial likeup BTS flows the V same. Using UV-OX to treat the higher in Fluents From the RWST's. OBOS Turn up UV-OX tamp power to 28.8 KVA and increase flow from 7 span to 95. Check peroxicle of this for flow rate Post POV (TP780) e Oppm. Post UV-OX (TP-720) Q 20 ppm. and Pre UV-OX Q 100 ppm. OB'S Decant T-351 to between when we well activated water of clear rocates. -clean ph-315 probe witherd solveton. Check the knows for all or sheen: None observed. Shray down were. -check TP-130 for oil y lobeles: None observed. water of clear w/yellow-green trave. OTO - Perform more with 448" poto An Relever level senector checks and check Poto MH175-078 Norschang poors. Allok	
1320 Backup WTP Data to Flash and DVD. Daily One Dobre backup working 1450 - Phents openium wood.	Influent Sources and Flow Rates: @0847 NBBW - 6.2_gpm North End On Site- 12.2gpm North End Off-Site - 9.0 gpm RWST - 6.0 gpm NTES - 6.4 gpm(10R only) MW38 T-540/541 - 0.0 gpm(Source well and 38 pumping wells mix) MW38 N & S - 1.6 gpm COND/NTES T-530- 0.0 gpm(6am-1pm-daily) MW113 Area - 1.2 gpm

Date: Thu	sday, March 24, 2022	
	Plant operations good. UV-OX working well at Full power with flow on TP 730 GC results. UV-OX feed pump P-601 CV e 93%, 5 n Changed. RWST'S down to 37% will begin to transfer water from to them today.	ext 99pm - ND 1, 4-DioyANC vicron bags weed to be an back up reserved tanks
0	too Change out UV-OX bagfilters during blowdown,	
O.	740 Blowdown operations agod Tom Etraining) Mike Starting on we	ully exist a checke
0740 Blowdown operations good. Tom (training): Mike Starting on welly systems C. 0915 Decont T-351 from bottom valve - Wet Well activated - Water level now below bottom valve Ringe Ph-315 proble with acid Solution		
Charled TP-130 for oil or sheens-none observed water is clear will yellow tint		
5705 For use owing entrovement to 50% LEL to use owing LEL-740 cultivation to ensure 0% LEC on T-740. Packare in 5705 For use owing entrovement traing. 1000 - START monthly main compressor oil morsture prevention. Lim at max speed for -24.		EL IN T-740 Por Pare Wen 2102414
		· · · · · · · · · · · · · · · · · · ·
10	1045 - Performmenthly 675 pH probes culture wount to New 4+10 pHSTOS 1220 - STOP Main compressor oil moisture prevention dus. 1231 - Bayn weekly calibration of with pH probes using New 4+10 pHSTOS a) pH-113, 670,315, 310 +365. 1307 - Suspend plant 0:3 charge to calibrate pH-740 to 4±10 pHSTOS and LEC-740 to 49% CEC.	
12		
12		
L	35 - Plant shut Down for Holy LEL 286 LEC. Automorre SHUT Down working proporty	
	25 - RESTART Plant.	Influent Sources and Flow Rates: @ 0750
13	26 - legume Normal BB charge.	NBBW - 6.2 gpm North End On Site- 12.2gpm
	335 - weekly monthly plants systems cheeks and caltbruttons complete.	North End Off-Site - 8.7 gpm RWST - 6.0 gpm
	Plants operations Good.	NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.0 gpm(Source well and 38 pumping wells mix) MW38 N & S - /. 6 gpm COND/NTES T-530- 0 -0 gpm(6am² 1 pm dail y) MW113 Area - /. 7 gpm

Operator: Mike Gelwick / Chris Carlson / 70 M Gilbert

Date: Friday, Ma	rch 25, 2022		
Time: 0600			
	results for 1.4-Dioxene. RWSTs e 541%. 557% - will transfer more stored water from backup		
V	tanks into them this morning.		
0745	Blowclowa operations good. Decant T.351 bottom valve, wet wel	activated Water is	
	Clear, No color. Clean the HAR. BO weir and pH probe - NO oilor sh	can observed in the	
1 1	HAMASO Alexand a slow does coming from studen Interest #2 alexander	tout Port MANNER	
	to be reseated if drip continues. Check TP.130 for oilglobules - No very clear light yellow /graper.	ine observed. Water is	
V	very clear light yellow /green.		
0840	Jim Barry on site. Go through complete program to update the I the UV.OX with NEW USER control interface. Also do more	escr manual for	
1	the UV. OX with NEW USER control interface. Also do more	shutdown and	
V	worming testing - All working well. Jim Was LEFT.		
1115	Jin has left.		
1130	1130 KLUSTS up to 80%, 570p +ransfer.		
1200	1200 Plant operations quod.		
		Influent Sources and Flow Rates: 0605	
		NBBW - 6.1GPM N. END ON-SITE - 12.2GPM	
		N. END OFF-SITE – 8.6GPM RWST – 6.0GPM	
		NTES – 0.50GPM COND/NTES T-530 – 0.0GPM	
		MW38 – 1.7GPM T-540/541 – 0.0GPM	
		MW113 IX SYSTEM - 1.8GPM OTHER - NA	
		OTHER - IVA	

OPERATOR(S) Chris Carlson

Date: Saturday, March 26, 2022	
0930 Plant operations good.	
1000 Decent T-351 to bottom valve, wet well activated Water was cloudy for 2 m	ninudes then
Cleared up. 7-352 now @ 44%	
Clean HMR-30 wer and PH-315 probe with acid solution - no oil or shee	ns observed
Clean HMR-30 wer and PH-315 probe with acid solution - no oil or sheet Checked TP-130 for oil globules or Sheens - none observed water is u	By clear w/ yellow that
1140 Filled phosphorus tank with 60 gallons 6LBS TSP	
1215 Plant operations and	
@ OBJS Check plant remotely-All okay RWSTs @ 61% \$ 61%. Both the	e UV-04 and BTS eve
I workfore well at high Elow rates	
@ 1320 Chuck plant remotely - All okay, RWST c 57%: 55%.	
3/27/22 0640 Check plant remotely - All okay	
1651 Receive GCI TP730 Fault alarm. Chuck remotely the GCV	as posted a false
high value of 1774.00 us/L for Cholorform. Peak is visually	
result that is < I ugll. Take screen shot of result, clear	alam, take UV-OX
out of recycle and start GCI on Next TP730 sample early. RWST @ 331/. 4 321/.	Charle plant ups - alloke
Wist @ 33'/. 4, 72'/.	
2015 Check all result remotely. Claratura result wormal at 0.20	us/L, pesk looks to
be very simular to the last sample with the False high cale	a Cated Value.
V Plant aps good.	NBBVV - 6, 7 gpm
	N. END ON-SITE - 12.2 gpm N. END OFF-SITE - 8.7 gpm
	RWST - 6.0 gpm NTES - 0.50 gpm
	COND/NTES T-530 – 0,0 gpm (6AM–1PM daily)
	MW38 – 1.8 gpm T-540/541 – 0.0 gpm
	MW113 Area – 1,7 gpm

Date: Monday, MArch 28, 2022	
0615 Plant operations good. RWSTS at 22%. 121%. Start transfe	er of remaining stored
V water in T-103 Back to the RWSTS.	
0740 Blowdown operations good.	
0820 Reboot HMIFTUIEWI to reset tempurary memory storage,	
OBEG HMIFTVIEWI ONLINE.	
- Decart T-351 to bottom value, we twell achieved, water DS chem Nocolo	
- Clean p.H.315 prime what sources. Check the Horaso For orlar steen; wone observe	I. Stray por work.
- Check TP-130 For of globales: None observal. water Is clear of yellow-year +mot.	
0830 TIANSFER OF STORED WATER COMPLETED. RWSTS @ 50%.	
1535 - Pharts operations Good.	
	and the second s
	Influent Sources and Flow Rates: @ 0246
	NBBW - 6.2 gpm N. END ON-SITE - 60gpm (2.2
	N. END OFF-SITE - 1272 gpm 8.7 RWST - 6.0 gpm
	NTES - O. J GPM
	COND/NTES T-530 - © • pgpm (6AM-1PM daily)
	MW38 = 1.8 gpm T-540/541 = 0.0 gpm
	MW113 Area - 1.7 gpm

Date: Tuesday, March 29, 2022

Time:					
		- Plants operatory (most fret to collect TA 730, 740 +710 weathy stander Collect TA 730 weekly (ac/Lab Split stander + 5 PART Efficiency cheeps and collect TA-7	10 and FP-740 weekly Low		
		Level 1, 4-Brox and samples.			
	0740	Blowdown operations good. Mike working on STS SAMPly + Field kendings teday			
	0330				
- Clean pH-315 probe upgert solution. Check the HML30 For-oil or steem. None observed. Jaray source week					
		- Check TP-130 For of ylobules: None observed. water Is Clear wyellow- green tiret			
	1000	- IX system performance HACH Testong w/Lab split stooplying AFter 1, 245, 453 gal Treated:	TP-183 -> 240 4/1;		
	TP-175A 2 290 ug/k; TP-174A 2 4600 ug/L; TP-170 26700 ug/L. System currently dumming 21,73,000.				
	1015	5 RWST'S at 2911. 12811, reduce RWST influent from 6 gpm to 0.6 gpm, recluce UV-0x flow			
	From 9 gam to 7 gpm, recluce BTS flow from HAVE. so from 6 gpm to ~ 2 gpm. Reduce UV power from 28.8 KVA to 25.7 KVA. Returning operations to pre PLC failure settings No w				
		stored water has been treated.	AND THE RESERVE THE PARTY OF TH		
	1330	Pump RWST Secondary containment sump (SNOW melt from multiple events and 400 gallers of sNOW			
		me it from decan pad) into the RUST for treatment.			
me It from decon pad) into the RWST for treatment. 1440 Total of 2759 gallons of sciendary containment water added to RUST.			3T		
	1605 - Plants operations Good.				
			Influent Sources and Flow Rates: @ o633 NBBW - 6.3 gpm		
	•		North End On Site- 12.7gpm		
			North End Off-Site – 8.6 gpm RWST – 6.0 gpm		
		2	NTES - 0.47 gpm(10R only)		
			MW38 T-540/541 – •• gpm(Source well and 38 pumping wells mix)		
			MW38 N & S− /₁7 gpm		
			COND/NTES T-530- O gpm(6am- 1pm-daily)		
			MW113 Area – 1.71 gpm		

Date: Wednesda	ay, March 30, 2022				
	Plantoperations good. Start weekly GC maintenance and calibrations. Refill phosphor tank with Gogallons potable water + 6lbs TSP. daily (3) Start up T-530 to BTS at 0.2 gpm (pump set to operate Gen-1pm), T-530 e 38%.	us			
0630	Start up T-530 to BTS at 0.2 gam (pump set to operate Gam-1pm), T-530 e 38%.				
0730	NIONOUN ADECATIONS ADD.				
	Decant T-351 to Bottom views. Wetwell Activited. water 55 clear Nocolor.				
	- Check TP-130 Paros globales: None as served. water 53 clear of yellow your trut				
V	-Clean PH-315 probe w/Acth solution. Check THE HTMR30 For oil or steen: None OBSERVED. Stray DOWN WEN.				
1030	Backup plant data to Flash drive and DUD. Daily One Drive backup working well.				
	0 Restart T.540/541 to BTS at 0.3 gpan (tanks @ 69% & 70%)				
1510	- Plants operations God.				
		and the second second			
-					
4					
		and a second			
<u>s</u>		erekipen, i i			
	Influent Sources and Flow Rate NBBW – 6.2GPM N. END ON-SITE – 12.2GPM N. END OFF-SITE – 8.7GPM RWST – 0.6GPM NTES – 0.50GPM OND/NTES T-530 – 0.2GPM MW38 – 1.7GPM T-540/541 – 0.0GPM MW/13 IX SYSTEM – 1.7GPM OTHER – NA	(6am-1pm)			

OPERATOR(S) Chris Carlson & Mike beliebek

Date: Thursday, March 31, 2022

Time:	0150	- Plants operations Good				
	0700	- Automatil blowdown open working on weekly Alants systems checks and californiums today.				
	0815	Decant 7-351 to bottom vulve. wetwell Activated. water 53 claw Nuculor.				
		-Cleun pH-3 15 probe of Act & Solu toon. Check the HIMA 30 For of or sheen: None asserved. Spray Down west.				
		- Check TP-130 For oil globules: None observed. water Is clear w/yellow-green trut				
	1136	- SUSPEND plant Discharge to calthrale AH-740 probe to 4+10pH 5703.				
	10.00	A STATE OF THE STA				
		- Weekly Plants Systems checks and calterations complete.				
		- Worker Reputing an Att leak on MW 155-EW-1. Small propose services on Att the where these contacting Attention the day for.				
		The state of the s				
	1515	- Plants opera wons Good.				
			Influent Sources and Flow Rates: @0555			
			North End On Site- 12.2 gpm			
			North End Off-Site – 8.7 gpm RWST – 0.6 gpm			
			NTES - 0:49 gpm(10R only) MW38 T-540/541 - 0:29 gpm(Source			
			well and 38 pumping wells mix) MW38 N & S- 1.7 gpm			
			COND/NTES T-530- 0:19 gpm(6am-			
1.1.4.191			1pm daily) MW113 Area – ハフス gpm			

Operator: Mike Gelwick

Date: Friday, April 01, 2022

Time:	0645	- Plants operarious Good.	
	0700	- Ar rommer blowdown opensours Good.	
		- workingon setting up for Annual sampling on monday, Triple Ringe All containers and measures	- sources. Program and
		calibrate Auto samplers. Will add preservitues JUST AUTO- TO STARTUP. GET COMPSHEETS + COC'+Labo	
	1130	- Decart T-35 1 to bottom valve. Wet well DIA Not activate. Water 53 clear Nocolor.	
	7130	- Clemp 4-3 15 probe w/ Herd solution. Check THE HOME 30 For vil or steen: None of served. Spray down	
	1215	- Check TA130 forvil globules; None observed. Water 33 clear w/yellow tyreen treat Plants operators Good	
100	1013	- Frant's operations about	
			Influent Sources and Flow Rates: @ 0650 NBBW - 6 12 gpm
1			North End On Site- / Z-Z gpm
			North End Off-Site − <i>B</i> ⋅ 1 gpm RWST − ଡ⋅ gpm
			NTES - 9.48 gpm(10R only) MW38 T-540/541 - 0.31 gpm(Source
			well and 38 pumping wells mix)
			MW38 N & S – 4.5 gpm COND/NTES T-530- 0-21 gpm(6am-
			1pm daily)
		•	MW113 Area - 1.73 gpm

Date: April 2, 2022 SATURDAY		
1200 Plants operations good.		
1330 Decant T-1351 to Bottom valve. Wet well activated water i	s dear no color.	
Clean pH-315 probe W acid solution. Check HMR-30 for	Clean pH-315 probe W acid solution. Check HMR-30 for oil or sheen:	
none Hoservadi. Sprau down weir.		
check TP-130 for oil globules: none observed. Wa	Her is clear with	
brownish-green tirt		
Both Ge's operational within limits.		
All Blowers okon.	sate of states	
Refill phosphorus tank with 5# TSP and 500	sal batapic mater.	
SURANY APRIL 3, 2020		
0830 - Nemore Log on - Allon		
1950 - Remote Log on - Allon		
	Influent Sources and Flow Rates: @ 4230 NBBW – 6,3 gpm	
	N. END ON-SITE - 12,2 gpm N. END OFF-SITE - 8 (a gpm	
	RWST - 0. 6 gpm NTES - 0, 48 97^ COND/NTES T-530 - 0.22gpm (6AM-1PM	
	daily)	
	MW38 - 1.5 gpm T-540/541 - 0.33 gpm	
	MW113 Area − 1, ₹ gpm	

OPERATOR(S) Manuela Seewald/WilleGelling

Date: Monday, April 04, 2022

Time: 0600	Plant operations good. Observe N. Toe P-COZW pump is stalling momen	teraly from time to time			
	Will swap out pumps this morning.				
0700 Mike adding preservitues to Mp.001 composite containers. 0740 Blowlown operations good. 0800 Short both auto samplers on Mp.001. Effluent to hal reading 252,998,366 gallows, f					
				rate at startup 29.2 gpm, pH-740 e 687 @ 15.9°C.	
			0845	Mike Swapping out P-002W - Cleaned P-002W ONLINE @ 0925-	
1010					
	- clean pt-315 probe white the solution. Cheek the HMARD for offer sken; were asserved				
	- check TA-130 For oil globales! None observed, we sent slightly cloudy wil yellow-orange trans	٠,			
- Real Polymer HANK w/ 200gal or portible water and Zeupson NALCO polymer.					
1038 - begin working on Annual early warning sampling/collecting Altquots for composities. Add preserved 1150 - START Flush of MP-Ool + check for residual chilorine: No ne desected. Ok puse Helpreserved utals		-visives to composite contacte			
		'r			
1200	- collect 1st set of Time paced grado samples 2 Mp-ool sample port for VOCT Low Level 1,4-0,00x	are and NONY I phonohs,			
	Place SAMPles In Artige, water I very clear Nocolor.				
1220	- Process Early warning composites: Gently streech one and check the phydres; Succs ph	p 40 7,00 su metals RADS pHO15			
	- Fill sample bottles, All Karly wountry samples Alaced on tradge until Adekting tomorous				
1550	- START Flush out mp-001 signifle port and where for desident whome: None servered	10 10 15 01			
1600	- collect 2 at set of time paced GLAS samples for VOC, LOW Level 1, 4-0,00 kare and NONY phenots. Hace samples In Fritze	Influent Sources and Flow Rates: @ 0 NBBW - 6-2 gpm			
	WALL IS very clear No color.	North End On Site- 17, 19pm North End Off-Site – 2,9 gpm			
1610	- Plants operators Good. At tosproplers on teach	RWST - 0.6 gpm NTES - 6.5 gpm(10R only)			
	Start MP-ON port flux L and check for serrelua I chlorine - None de tected 1	MW38 T-540/541 - 0.2 gpm(Source			
200,0	allet 3'd set of time paced grab samples for vocs, lunievel 1, 4 - Divine and				
V	nonylphonols, waters vey clear No color. Place in field e with others.				
	Stort mp-our port flush and check for residual chlorone-none detect				

Date. 1000)	Collect 4th set of time paced grab samples for vocs, low level	1.4-Diornie and			
0000	CONCET THE SET OF TIME PACED AFAS SAMPLES TO TOOLS, CONTENTED	Ci (a will a lives			
	Nonyphenols. Water is very clear, No color, Place samples in	Friege With 0 the 8.			
	- Plants operations Good Preptor BTS sampling and MP-001 GAAB				
	- STHAT Flush of MA-001 sample port and cheek for restaul chlorine: None Detected				
0400	-collect 5th set of Time paced grab samples 2 mt-vol for VOCS, Low-Level 1, v1- Atoxum and wony 1 pres	uols, water to very clear wocolor			
	place samples in fridge with others.				
0415	- usorway on 673 sampling and 5 that Efficiency chells.				
0450	- Collect TP-730, Weekly GCangpert samples, Also collect TP-710 and TP-740 weekly con Level 1, 4-Drokane samples.				
	· ALL SAMPLES Placed on Fridge on M PACETAZ Caper tolay.				
0750	- START Flush as MOOI sample port and check to residual chiorne: None seteeted.				
	- Collect 6th setox time paid grabsamples DMA od Kor VOC, Low Level 1, 4- Atoxone and	Lowyphends with QC volume			
	For each, water Buery clear woulder, Alace samples on Fridge with others.				
	- STOP AV 105, timplors and process composite samples. Gently stir each composite and check pit valves.				
	- SUCCS pt 27,20 / menus lats pt 01.54. potal Explorer 2 253,044, 344gal, Atotal of 45,978 gal treated				
	Dorng sample period. Full sample Bottles				
0900	- AACU AN SAMPLES ON The For SHAPPMING to Lubs. and work on SAMPLY paper work.				
0905	- TX performance HACH TESTING W/Lab split sutespling After 1, 262, 677 get Treated TP-183 -270 mg/k; TP-17540 Ego				
	TP-174A 24800 49/6; TP-170 2 6700 49/6. corrently during 2 1.72 gpm				
1000	- Check TA-130 For Oil globules: None assemd. whents strylthy charly w/yellow-orange trut	Influent Sources and Flow Rates: @ 0350 NBBW - 64 gpm			
100-	- Decaret 7-351 from potrom value. wet well took to extreme, werker 53 claim to color	N. END ON-SITE - 12.3 gpm			
W	- Clean AH-315 probe w/ Act of solvator spray sown wetr and chelle Home so for oil orsteen; wore as sand.	N. END OFF-SITE - 8.7 gpm RWST - 0.6 gpm			
1500	- Planks operations Good.	NTES - 051 gpm COND/NTES T-530 - 02 gpm (6AM-1PM			
1300	operation (2001)	daily) MW38 – 1:5 gpm			
		T-540/541 - 0.31 gpm			
		MW113 Area – 1.72 gpm			

Date: Wednesday April 00,000			
Date: Wednesday, April 06, 2022			
ime: 0550 Plant operations good. Shorton weekly be maintenance	and efficiency checks.		
0615 Reboot HMIFTVIEW 1 to update virus software			
0745 Blowdown operations good. 0815 - Clemp 4.315 prose wither solveron. Check the Homeso For ottor steen: None 065	areal. S Duray Down west.		
- Decant 7351 to bottom valve. Wet well actuall water Is clear Nocolon			
- Check TA-130 For oilglobules: None as serval. wenter Is clear w/ yellow-gar			
0840 - working on STR Freld dealth to trope.	840 - working on STR field dealing males.		
1000 BACKUD WIF data to Flash drive and DVD. Daily One Driv	· backer working wellbut store tola		
1000 Brekup WTP data to flash drive and DVD. Daily One Driv 0938 Tom has taken a manuel level at MW38N well (MW38-LO check. DTWE 51.55'= GWE 5720.25', HMI readi	28N-25BE) for quartuly transfer		
check. DTWC 51.55'= GWE 5720.25', HMI read.	NS STO. 19' No calebration reached		
V at this time.	3		
1318 Tom has take a manuel level at MU385 well (muse check. Dtwc71.29'= 6WE 5735.47! HALT scading recalibrated to 5735.47 today.	-1705.140W) for purched y travel		
Mark. DYINC71.29'= 6WE 573-42' HART 1 cading	5735.26' Transduce 5 11 dia		
V secaliberated to 5735.47 tacker.	THE STATE OF THE S		
1615 Plant operations good.			
The Open and the Space			
	Influent Sources and Flow Rates: @07		
Cast	NBBW – 6-2 gpm North End On Site- IZ-2 gpm		
	North End Off-Site - 8, 2gpm RWST - 0.6 gpm		
	NTES - 0.5 gpm(10R only)		
	MW38 T-540/541 - 0,3 gpm(Source well and 38 pumping wells mix)		
	MW38 N & S- 1.6 gpm COND/NTES T-530- 0.2 gpm(6am-		
	1pm daily)		
	MW113 Area – 1,3 gpm		

Date: Thursday, April 07, 2022		
Time: 0615 Plant operations good. Setup For Chamber B of HOME 30 cleanout		
0700 Reboot Shutclown UV-0x and Keep Influents in divert to KUST for Chamber B class		
V/ Chamber A of ~ 6" of solids. Chamber B mixer removed eleaned and reinstalled.		
bins and decons theen equipment. Decon water als	added to studge	
161 NS liquids purped out of bins to T.351, leaving heavy	solids that will	
V be devatered and added to studge box when box has be	en emptied.	
1000 HMR-30 resilled restart UV-OX - warning up. Note: POU backwarked while	. UV. OK was Off today.	
1013 UV-OK atsicharging.		
1110 - Clean pH-315 public of Acid Solveron. Chelle tok Hord 80 for OR or SHeen: None of served	Stray Assert west.	
- Check TP-130 For oily lob vles: None observed. Wifers clear w/ yellow -green with		
-working on weeking Plants systems cheeks and cultorities,		
1345 Shop HMIZ to replace UPS and reboot to upgrade Virus soft	wore.	
1351 ONLINE - All OKZY.		
1417 - 505 pend plant AB Charge to Calterte pH-740 probe to 4 + 10 pH STDT		
1474 - Resume wormal Discharge. continue with other pt probes cultbrettons to 4+ 10 pts tot 24	4-113, 670, 310, 315 +865	
1440 - Decent T-351 to bottom vulve. we twell actually water IS clear No color.	Influent Sources and Flow Rates: @ //35	
1450 - Reduce UV-OX Flow to 6.5 gam From 7.0 g pm	NBBW - 6.7 gpm	
1505 - weekly plants systems checks and cultbrattons complete.	North End On Site- /2.3 gpm North End Off-Site - 2.6 gpm	
1515 - Plants operations Good	RWST - 0.6 gpm NTES - 0.49 gpm(10R only)	
	MW38 T-540/541 - 0:30 gpm(Source well and 38 pumping wells mix)	
	MW38 N & S- (.7 gpm	
	COND/NTES T-530- #49 gpm(6am- 1pm daily)	
	MW113 Area - 1,74 gpm	

Operator:	Mike Gelwick / Chris Carlson	

Date: Friday, April 08, 2022

Time:	0705	- UV-OX SHUT Bown For Low Flow, May be the 6. 5 gpm set to perfuduy NOT QUIT	e enough will tom 1840k
		to 7 your and see to worksout, want intil blowdown Is over and Henriso Is heribel before hestall.	
	0730	Jucien busts to 6, pm to letill Huneso Fotster.	
		- RESTARTUVOX, LESHET/www.up processok,	
		-UV-DX BACK ON Line. Wavering property.	
	0835	- HMIZ Has a blue scream message, beceived Heartheat Alarm. RESTART HINTZ. Alarm	For Hearthant Still Stewing.
©		Reboot Hurz 2 Again.	
	0907	- HUNTZ BACK ON LANCE. AlexAN FOR HEAVTHEATTS gowe Now. Allow	
	0915	- Decant 7-351 to bottom valve. We twell activated water #5 clear Nocolor.	No control of the second
		- Claum pH-315 probe w/Acid solvition. Chelkfake Hund 30 Poroil or Steen! Nove 08 Served. 3 some so	seen weir. HML30 with very clow.
		- Check TP-130 For vilglobules: None asserved water to clear wi/yellow-green trust.	
	1335	- Place 1573 Into much Hold to Flush leaster Fred Lines	and the second s
		- BTS out of Hold, on	
3	1430	- Plunts operations Greek.	(C-1111) 1.11
	•		20 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2
2016210			
160			
			Influent Sources and Flow Rates: @ かがり NBBW - 6・2 gpm
			North End On Site- /2-3 gpm North End Off-Site - 必ん gpm
			RWST - 0.6 gpm
			NTES - 0, 49 gpm(10R only) MW38 T-540/541 - 0.30 gpm(Source
X			well and 38 pumping wells mix) MW38 N & S-(. 6 gpm
			COND/NTES T-530- 0.20 gpm(6am- 1pm daily)
	N. Orbert		MW113 Area - 1.7(gpm

Operator:	Mike Gelwick	

- Calman And Code			
Date: DAMUFORY 14011 09 2022			
Date: SAturday April 09 2022 0545 ON 51te, plant operations good. Refill phosphorus tank with 40 gallows water V TSP.			
V TSP.			
OGIB PID of 7.600/601 adjusted to react quicker to Flow a feed from 7 gpm to 6.5 gpm Cwill observe how Flow	djust ments. Reduce UV.OX		
Fred fan 7 gam to 6.5 gam Cwill observe how Flow	rate stabilizes when UV-OX		
Switches From discharging to recycle churry blowdown)			
0700 P-600/601 Flow regulation working better. Flow did dip	momenterly below 5 span		
but pumps speed incremed quitally to compensate.	but away sould enjoyed quitable to commentate.		
Clean the HMR 30 were and pH probe - No oil or show observe	ed in the HMR.30. Check TP.130		
V for oil globules - None observed. Water 75 clear, light xellow	Isua.		
0820 Decart T-351 bottom value, wet well activated. Water ?	s clear , no color.		
COSO Plant operation good.			
2000 Check plant remotely - Allokay			
4/10/22 0630 Check plant remobely - Allokay			
2025 Check plant remotely - All okay.			
and the past of th			
	Influent Sources and Flow Rates: @ OGS		
	NBBW - 6.3 gpm N. END ON-SITE - \2.3 gpm		
	N. END OFF-SITE - 9.6 gpm RWST - 0.6 gpm		
	NTES - 0.5 gpm (6AM-1PM		
	daily)		
	MW38 – (, 2 gpm T-540/541 – , 0, 3 gpm		
	MW113 Area – 1.7 gpm		

OPERATOR(S) Chris Carlson

Date: Monday, April 11, 2022 Time: 0610 Plant operations good.

0750 Blowdown operations good. 0845 - Decant 7-351 to bottom value. wet well activated, water Is clear wocator. - Clean AH-315 probe w/ Act & solution. Check + the Home 30 for of lean: None observed. Spring Down were water IT very clean - Check TA-130 For oil globules: None observed. water B clear uty ellow- green trad. 1505 - Plants opening Good. Influent Sources and Flow Rates: @ 2555 NBBW - 6.2 gpm North End On Site- 12.3 gpm North End Off-Site - 2,7 gpm RWST - 0,6 gpm NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source well and 38 pumping wells mix) MW38 N & S- / ,6 gpm COND/NTES T-530- 0 · 2 gpm(6am-1pm daily)

Operator: Mike Gelwick / Chris Carlson

MW113 Area - 1.7 gpm

Date: Tuesday, April 12, 2022

Time:	0500	- Plants operations Good. Prep for TP-730,740 +7103 trapping.				
		collect TP-780 GC/Lab spinsamples and begin Efficiency chesis. Also callect TP-710 and TP.740 weekly Low Level 1, 4-10 oran				
		sumples. we ter Bury clan pocolor samples tore Fritze until processy.				
	0715	Rebust HATETUIENI when moving power to UPS connections, to accomicate Cell signal booster.				
0750 Blowdown operations good.						
	0825	"Decant T-351 to bottom value, wet well a chrosed, water to clear no color				
		-Clem AH-315 W/ACM SOWHOM. Check + HE HOWE 30 FOR OR OF SHEEN: NON DOSENNO. SAMY Some were				
		- Check TP 430 For oil y lobules: Noncobserval. water to clean my yelkow-green trut.				
		- working on 673 sumpling used well headings today.				
	1000	Jim B. on site to drup off UV-OX PLC drawings and to look at man PLC for upgrade cost estimate				
-		- Fx personance HACH Testing w/cansportsumpling After 1280054 gel Treated: T12-187 2240 49/6; 772-175A 0320 49/6;				
		TP-17440 5200 49/L; TP-170 26800 49/L. Corrently Ruming 21.70gpm.				
		- heril 1873 Phosphons TANKW/5#8475P + 50 gal or potable water				
	1313	Tom sending in manual levels of the N-TOE OVER for transducer calibration checks.				
		MPZ-11 DTW @ 32.10 = GWE 5734.33. HMI ruding 5734.44, NO calibration Need at the time				
		MPZ. a Druc 24.32 = GWE 5738.77, HME reading 5739.15. CAlibration performed at this time.				
		MPZ 10RDTW @ 34.38 = GWE 5728 .27'. HMI reading 5727.99'. Calibratur performed at this time.				
		NTES-180W DTWC 35.89 - GWE 5729.76: HMI reading 5731.15' (Marical level double checked-ok).				
		His transducer is alf by 1.39 (will observe it laterto see it i going NBBW- 6.3 gpm				
		bad) Recalbration ger to and at this time. North End On Site- 12.3 gpm North End Off-Site - 9.1 gpm				
		NTE 5- SUMP DTWE 28.63 = GENE 5734.20 : HMT reading 5734.19 . No NTES - 0.6 gpm NTES - 0.5 Ogpm(10R only)				
		Crelibration New Coll at this time. MW38 T-540/541 - 0.30 gpm(Source				
	1630	Pland apre-how good. well and 38 pumping wells mix) MW38 N & S - 1.5 gpm				
		COND/NTES T-530- Ø. ₩ gpm(6am- 1pm daily)				
		MW113 Area – 470 gpm				

Date: Wednesday, April 13, 2022

Time:	0600	Plant operations good.		
	OGIO Stop MWBEN & S extraction to propore for MWBG source well batch extraction. Short on weekly be maintenance and calibrations with Mike to serresh him o.		extraction.	
		Start on week y be moutaterance and calib-cotions with Mike	to refresh him on	
		it.		
	0615	INCRESSE RUST INFLUENT From 0.6 gpm to 2.0 spm.		
	0230	Switch MW38 from direct HMR-80 influent to T-540/541. M	ike starting up	
		MW36 source wellestrag extraction-		
6	1105	- ARCAINT T-351 to bottom value. We twell as trusted. water to clear woodon.		
3		-Clemp H-315 preter white it solv mon. Check the Hund so for all or street. None as served. Spe	ray Down west water Is clown	
		- Check TA-130 for oily lobules: None offerved, water to clear w/gellow-y-cantrus.		
		- Cultbraked Both PIDS (Lental + 5,72) to check 675 vent to compare results. Rental AIDA	440	
-		3.5 ppm 7VTP-3360, Tikseare More Normal Leasings, 5. te AID Mayweed same service. ITS headings were super		
	/130	- BACKUP GLOWIP ONTHTO Physh Drive and OUD. Reduce T-540/5411 flow to 1375 from 0.7 gpm to		
2		0.2 gpm so BTS can adjust to the Fresh Source well water.		
	1138	Receive UV. Ox warmy alarm - Crystal wiper Failed to travel the full le		
4		sciences limit. Observe the wiper would travel up but stock within		
Incressed air pressur slightly going to the proton and wiper was able		able to tracel the full		
	V	length, Piston automatic oiler working well.	Influent Sources and Flow Rates: @ 6665	
		Recien UV-ox warning for wiper again - incremed pressur a lottle more to	NBBW - 6.2 gpm	
	V	get it working well.	North End On Site- 12.2 gpm North End Off-Site - 6.9 gpm	
-	।सम्	Pertue UV-0x waring for wiper again. Solvoid value may not be tall opening - will add extra oil to the value in the morning.	RWST - 0.6gpm NTES - 0.5 gpm(10R only)	
		opening - will add extra oil to the value on the moining.	MW38 T-540/541 – 0.3 gpm(Source well and 38 pumping wells mix)	
	W 100		MW38 N & S- 1-5 gpm	
			COND/NTES T-530- 0.2 gpm(6am- 1pm daily)	
	(n 11)		MW113 Area - /.2 gpm	

Date: Thursday	April 14,	, 2022
----------------	-----------	--------

	,,,, =v==	
ne: <i>060</i> 0	Plant operations okay. Acid prematic oil inline to UV-OK wiper sour test runs, working well now but has been straking offer it	oid and do multiple
	test runs working well now but has been straking offer it	site sits beween the
	Observe the MW38 source well extraction stapped at 9138 this p	wining - Solar systm
	Observe the MW38 source well extraction stopped at 9138 this proper out of battery power. Abk to get it restarted this moving	g. T-540/541 levels
3.42	[a, 667]	
0750	Blow down operations good. UV- Ox wiper cycling normally. M	Ke Starting weekly
	545 ten Checks and Callerations.	
0848	Observe MW32 source well has again powered down due to low batterse vol T-540/541 at631. begin displacing source will make in the pipe the to T	tage will leave off,
	T-540/541 at631. begin displacing source will make in the pipe kne to T	-540/54/ USING
	Muzens S extraction wells.	
0911	- Decant T-351 to bottom valve. we twell activated. wutar Is clear receive	
	- Clean pH-315 probe which solveron. Check the Hon A 30 For oil or steen: woned served stray done	m wer, water 13 clean souler
	- [Heck TA-130 Foroil globuly ! None BS served, water IS clear w/yellow- green trut	
1240 1200	- SUSPEND Plant 0.3 charge to caltbrate pH-740 probe to 4+10 pH5 TD5.	
1248	- Resume Normal Osscharge. continue with other plant phyrobes californiums to 4+ 10 phs FB ? 2 ph	-113, 670, 310, 315+365
	- Chris performing monthly ADTW Air Relens and 4x Bir Leakenecks. Also checking POTW MH 175-078 4	
1345	- weekly Plants systems cheeks and cultbrations complete.	
1401	- 5 witch mw38 N+5 wells to HMR30 mode. 6/1 gal floshed THN MW38 processor. Reduce Kw573	Influent Sources and Flow Rates: @ ORDE NBBW - 6.2 gpm
	Flow TO 0.60gpm	North End On Site-/2 2 gpm North End Off-Site - 8.7 gpm
1446	- Plants Operations Good.	RWST - 2.0 gpm
		NTES - 4.5 gpm(10R only) MW38 T-540/541 - 6.2 gpm(Source
		well and 39 pumping wells mix) MW38 443 4.7 gpm Source well h
		COND/NTES T-530- 0.2 gpm(6am-
		1pm daily) MW113 Area – [, 7 gpm

Date: I	Friday, A	pril 15, 2022	
Time:	0720	- Пеня органом воой. Антомина вышлони органом выст.	
	0750	- Increm p-006/T-540° to 0.30,pm. GC Parults OK.	
	0930	- Accant 7-351 to bottom value. wet well activated. water Is clear wo colo	
		"Clean pH-315 probe W/ Acrd sow Horr. Chelk THE HARTO Foroilors Heen: None of serve	d. story sown weem
		- Check TP-130 For oil ylobules: None observed. weter Is clear at yellow-young to	<i>t</i> .
	1030	- Refill 1875 phosphores THNU - 14# of TSP and 40g al of potable water	8
	1120	- Plants operasous week.	
	1158	- leceive UV-OX SHUT gown and P-75 2 FAWIT Harms. Stake on 5th to check things out. Ask	to Get P-152 lese Tany
		going. Check UV-of All seems OK.	
		- RESTART UV-OX.	
	1735	- Plants operations back to wormed lok.	
			7.3224/HIP
			Influent Sources and Flow Rates: @0765 NBBW - 6.2 gpm
3			North End On Site- 12.2 gpm North End Off-Site - 6.9 gpm
			RWST - D. G gpm
***************************************			NTES - ○.4 & gpm(10R only) MW38 T-540/541 - △.3 gpm(Source
			well and 38 pumping wells mix) MW38 N & S- 1-7 gpm
			COND/NTES T-530- 0.19 gpm(6am- 1pm daily)
			MW113 Area – (、70 gpm

Operator:	Mike Gelwick

Date: SATURDAY, APRIL 16, 2022 0640 - Plants operations Good. Go to chell other 5:2 545 pans 0740 - 574 sys pems Allow. Automoste Blowdown operations entry, DR 0805 - Decart 7-351 to bottom value. we twell a cert and. water Is clear wowls - Clean SH-315 probe w/ Acrd solution check THE HARTO for ottors Heen: Work odfand SAMy Bown were waters was clear - Chelle TD-130 for oil y labeles : None asserved water 25 clear why ellow -you tret. 0945 - Pleuts operations Good Influent Sources and Flow Rates: @ 6645 NBBW - 6.2 gpm N. END ON-SITE - /2.2 gpm N. END OFF-SITE - 8.4 gpm RWST - O.6 gpm NTES - 0.5007/A COND/NTES T-530 - 020 gpm (6AM-1PM daily) MW38 - 1.7 apm

OPERATOR(S) Mike Gelwick

T-540/541 - 0.31 gpm MW113 Area - 1.71 gpm

Date: Monday, April 18, 2022 Time: 0600 Plant operations good.
0745 Blowlown operations good. - secant T-351 to bottom when wetwell actuated water po clear we colon Clamp 14-315 probe we from solverton. Check the 14mm 80 for oil or siteen: Noneossured. Spray bown were wateres very clam - Chelle TP-180 For o'll globeles: None observed. Water IS clear w/ y-ellow- green + m+. 1020 Betoot HMIFTVIEWI to update Sifture. Unline + 1025-1445 - Plums operations Good. Influent Sources and Flow Rates: @ 0758 NBBW - 6.2 gpm North End On Site- 12.3 gpm North End Off-Site - 8.6 gpm RWST - 0.6 gpm NTES - 0.51 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source well and 38 pumping wells mix) MW38 N & S- 1.7 gpm COND/NTES T-530- o.2 gpm(6am-1pm daily) MW113 Area - 1.7 gpm

Date: Tuesday, April 19, 2022

		- Plants operations Good. Fret for weekly TP-780 740+7108tomplan.				
		- collect TP-730 GC/Lab SPHTS Imples and STHAT Efficiency cheeks. Also whent TA 740 + TA710	Low Level 1,4-A, sknne samples.			
		- Decant T-351 to bottom value. Wetwell activated water T3 clear avoidor.				
		-Clean AH-315 probe w/ Acid solveron. Check Tok HMR 30 for oil or Steen: None observed. Stray Down ever. water 35 clear				
		- Check TP-130 For oil ylobules : None as served. when Is Clear w/yellow-grown tint.				
		- working on 675 weekly sumpling and Hold Readings today.				
(0900	· Revillets Phosphons TANK w/6 to TSP and 60gm of possible water				
	0955	- IXPER formance HACH Testing w/Lab split stomping After 1,297,279 gal treated: TP-183.	> 1504/1; TP-175A2 1700g/1;			
		TP-1744 25200 uy/L; TP-170 27100 uy/L. currently kinning 2 1.70gpm.				
		INCrease MW385 extraction from ~ 0.9 com to~1.2 gpm.				
1505 - Plants operatures Good						
			Influent Sources and Flow Rates: @0578 NBBW - 6.3 gpm North End On Site - 7.3 gpm North End Off-Site - 9.0 gpm RWST - 0.6 gpm NTES - 0.49 gpm(10R only) MW38 T-540/541 - 0.29 gpm(Source well and 38 pumping wells mix) MW38 N & S - 1.7 gpm COND/NTES T-530- 0.20 gpm(6am-1pm daily) MW113 Area - 1.70 gpm			

Date: Wednesday, April 20, 2022

Time:	0600	Plant upwotiens good. Mike starting on welly be maintance and ex Blowdown operations good.	al-brations -
(a)	0742	Blowdows operations good.	
	1020	- Decant T-351 to bottom value, wet well activated. Water IS Clear No color.	
	3 dispose di	"Clean pH-315 probe wy Acid solvers. Check The HIME TO Foroilor steen: wore observed	spraybown wer, water Is clear
		- Check TP-130 For oily labels: None of served. water Is clear w/ yellow- green trut	•
	1330	- WTA + GCS AATH BACKED UP TO FLAGE DAVE and DISK OK.	
		- Plants operations Good.	
0.1 1188			
	6		
			Influent Sources and Flow Rates: @ 0456
			NBBW – 6.3 gpm North End On Site- I2.2 gpm
			North End Off-Site – 8.5 gpm RWST – 0.4 gpm
			NTES - 0.5 gpm(10R only)
			MW38 T-540/541 - 0 · 3 gpm(Source well and 38 pumping wells mix)
			MW38 N & S- 2.0 gpm COND/NTES T-530- 0.2 gpm(6am-
			1pm daily)
	-15		MW113 Area - /.7 gpm

Date: Thursday, April 21, 2022

		y, April 21, 2022		
Time:	0630	Plant operations good.	1933	
	0750	Blowdown operations good. Mike starting weekly systems checks and calibrations.		
	0930 - START MUTH LOTP COMPRESSED OIL MOISHUME PREVENTION RUSH & MAK Speed For 2 Hrs.			
	0940	-Decay 7-351 to bottom valve. wetwell activited water to clear Nocalor		
		- Clean p. +- 315 probe w/ Herd solution. Check Tik Hand 80 For oil or 5 Heen: None observed. Spray Bown west. Water 15 9 43 4thy clouds many		
		- Cheek Th-180 For oil y lob wles: None observed. water 35 clear w/ yellow - green trut.		
	- Levill polymer +ANK w/Z cups out NALCO polymer and 200 gal oxpotable water			
	1130	- STOP MATH COMPRESSOR OIL MOTE PREVENTION RUN.		
	1140	- ACT / BASE Clean BTB p H probes today In preparation for calibration west week		
_8	1320 - Suspend Plant Ar3 Charge to cultibrate pt-740 to 4+10 pts 70? 1326 - Nesume wormal Ar3 charge. Continue with other ptprobes cultibrations to 4+10 pts 700, 2 pt-113, 670, 310, 315, 365.			
			70,310,315,365.	
	145 - weekly plants checks and cultbrattons complete.			
	1500			
			Influent Sources and Flow Rates: @ 0752 NBBW - 6.2 gpm	
			North End On Site- 12.2 gpm North End Off-Site – 4.0 gpm	
			RWST - 0.6 gpm	
			NTES - 0.47 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source	
			well and 38 pumping wells mix) MW38 N & S- 2.0 gpm	
			COND/NTES T-530- 0.2 gpm(6am- 1pm daily)	
	a varan		MW113 Area – /.7 gpm	

Date: Friday, April 22, 2022	
Time: 0600 Plant operations good.	
0743 Bloudour ascrations and.	***
0823 Reboot HMIFTVIEW to vodate Utrus detection Software	- online @ 0827.
0920 Refill phosphon, tank with 45 gallows potable mater + 41.5	155 TSP. Decant T.351 bofform
, value, wet well activated Water is clear, No color. Cl	can the Houl-30 weir and off probe
No oil or sheen observed in the Hara. 30. Chark TP-130	For oil globules - NONE observed
O743 Blowdown operations good. O823 Reboot HMIFTVIEW to update Utrus detection software O920 Refill phosphorn tank with 45 gallow potable mater + 4.5 Value wet well activated. Water is clear, no color. Cl. No oil or sheen observed in the Hava. 30. Check TP-130 Water is very clear, light yellow/specs.	J
1230 Plant operation good.	
0	
	Influent Sources and Flow Rates: 0650
	NBBW – 6.3GPM N. END ON-SITE – 12.2GPM
	N. END OFF-SITE - 8.9GPM
	RWST – 0.6GPM NTES – 0.50GPM
	COND/NTES T-530 – 0.2GPM (6am-1pm) MW38 – 2.0GPM
	T-540/541 - 0.3GPM MW113 IX SYSTEM - 1.7GPM
	OTHER - NA
•	

OPERATOR(S) Chris Carlson

Date: Saturday , April 23, 2022	Date:	Saturday	, April	23, 2022
---------------------------------	-------	----------	---------	----------

0845	Plant operations good
1015	Decont T-351 to bottom valve, wet well activated. Water is clear no color. LT-352 now @ 42%
	clear HUR-30 probe u/ acid solution. sprayed weir and cheked for oil or sheens: None observed
	checked Tp-130 for oil globules - none observed water is very clear with yellow green hue.
	Plant operations good
(W) 1200	Isolate potable water fixed to the WTP using the shutoff located N.W. of the DADS scale house to test if potable water usage numbers are reduced over
400 W	DADS scale house to test if potable water usage numbers are reduced over
10000000000000000000000000000000000000	Saturday P.M. and all day Sunday
4/24/22	1300 Remole lay in - Plant operations good
@ 0630	Check plant remotely - All okay.
@ 1830	Check plant remotely - Alloway.
1000	
	Lieftwart Courses and Flow Paters (2) 200
	Influent Sources and Flow Rates: @ oqual NBBW – 6.3 gpm
	N. END ON-SITE -12.2 gpm N. END OFF-SITE - 9.0 gpm
	RWST - 0.5 gpm NTES - 0.51 gpm
	NTES -0.51 3pm COND/NTES T-530 -0.20gpm (6AM-1) daily)
	MW38 - 2.0 gpm T-540/541 - 0.30 gpm
	MW113 Area – 1.7 gpm
	N. 4395/1

OPERATOR(S) TOM Gilbert

Date: Monday,	April 25, 2022	
Time: 0600	Plant operations good. Leaving potable to plant off until ~9 A. automatic meter reading takes place at the Eccu meter	n ofter the daily
	automatic meter reading takes place at the Eccu meter	at spicadilly Rd;
<u> </u>	E WUNDY HOE.	
0750	Bloudour aperations good.	
<i>ળ્</i> વાર્ક	Restore potable water to the plant. Looks like isolating this sec	How had No effect
<u> </u>	on how much water was logged at the neter.	
1230	Decart T-351 bottom value, not well actuated. Water's clear, a	o color. Clean the
<i> </i> -	Blowdown aperations good. Restore potable water to the plant. Looks like isolating this sec ON how Much water was logged at the meter. Decant T-351 bottom value, not well activated. Water's clear, or HMR-30 wet and plt probe - No oil or show observed in the HMR-oil globules - None observed. Water is clear, light yellow. Plant apoatow good.	30. Check TP-130 for
W	oil globules - None observed. Water is clear, fight yellow,	groen -
1525 +520	Plant apoatous good.	
	·	
		1
		18 ************************************
- Article		15. 0050
100		Influent Sources and Flow Rates: 0656 NBBW – 6.2GPM
		N. END ON-SITE - 12.2GPM N. END OFF-SITE - 8.9GPM
		RWST - 0.6GPM NTES - 0.50GPM
		COND/NTES T-530 – 0.2GPM (6am-1pm) MW38 – 2.0GPM
		T-540/541 = 0.3GPM MW113 IX SYSTEM = 1.7GPM
		OTHER - NA

OPERATOR(S) / Aris Carlson

Date:	Tuesday	April 26, 2022					
Time:	0450	- Plants openwork Good. Pretter weekly TP-730,710+740 strongles.					
	0515	- Collect weekly TP-730 GC/Lab Spirt stimples and START Extremy cheeks. Also collect weekly TP-710	+740 Low Level 1, 4- Doxum ordina				
	0610	Plant operations good					
	0750	Blowdown operations good. Mike working on 573 sampling and field healings tolay					
	0830	- Decemb T-35/ to bottom value. We twell activated water to clear worder					
(A)		Clean Alt-315 prote w/ de. A Solution. Check the front 30 for oil or siken: None oisserved. Spray some we. n.					
N.		- Check TP-130 For oily lobules: None osserval. waterps clear w/yellow-green +141.					
	0850	- Reptill 6TS phosphores THINK W/6 tox TSP and 60gal or pormole winter	- Annual Control of the Control of t				
0955 - IX performance HACHTESTIM W/ Lab Split SAMPLING AFTER 1, 314,336 gal Treated: TP-183 - 250 cg/6; TP-1754 - 320			(1, TP-175A - 370 4/4;				
		TIP-17\$ 426200 49/L; TP-170 2 7000 49/L					
	1525	- Plants operations Good.					
			Influent Sources and Flow Rates: @ 0525 NBBW - 6.3 gpm North End On Site- /2.3 gpm				
			North End Off-Site – ५.५ gpm RWST – ७.७ gpm NTES – ०.५७ gpm(10R only)				
			MW38 T-540/541 - 0.29 gpm(Source well and 38 pumping wells mix)				
		*	MW38 N & S− 2. ⇒ gpm				
			COND/NTES T-530- 5120 gpm(6am- 1pm daily)				
			MW113 Area - 1.70 gpm				

Date: Wednes	day, April 27, 2022	
Time: 0600	Plant operations good. Start weekly GC maintenance and calibration	
0748	Blanchum perations good. Work with mike to remove empty con	ustre and HCC toter
mentali se a sentreponanti.	Plant operations good. Start weekly GC maintenance and calibrations. 0748 Blanchum operations good. Work with mike to remove empty cocustre and HCC toter from charteal bays. Add 75gallows of peroxide to main bay supply. Also add I full tote of caustic ? HCC to main bay supply.	
	tote of caustic & HCC to main boy supply.	27 28 28 28 28 28 28 28 28 28 28 28 28 28
1050	- Decart T-351 to bottomuclue. Wetwell a ctuated . water Is clear Nocolor.	
	- Clean pit. 315 probe w/Acrd Solution. Check THE HOMESO For oilor Steen. None adserved. Spray.	down were.
	- check TP-130 for oilglobules: None osserved. water IS clear Wyelkow-yreen trut.	
1115	- 370 P MW38 N+ 5 Pumpting wells to begin a batch of MW38 source well water to T-540/50	11.
1135	- START MW38 Source well pumping to T-540/541	
	1220 - BACK UP GCS + WTP3 DATA to Flogh Drive and disk. Allok.	
1250	1250 Incress RWST influent from 0.6 g/m to 2.0 g/m while MW34Nis are off during batch made.	
1300	1300 Place P-005 in standay after surving some putable water through it to clean the impleller, T-530 e 20%. Reduce T-540/5411 to BTS from 0-3 gpm to 0.2 gpm while Fresh	
MW3B source well is entering the BTS.		
1500	1500 Plants operations Good	
Marian and a second		
0		Influent Sources and Flow Rates: @ 0746
·		NBBW - 6.2 gpm
		North End On Site- 12.2 gpm North End Off-Site – 9.6 gpm
		RWST - 0.6 gpm NTES - 0.46 gpm(10R only)
		MW38 T-540/541 - 0.3 gpm(Source
		well and 38 pumping wells mix) MW38 N & S- Z.0 gpm
		COND/NTES T-530- 0,2 gpm(6am- 1pm daily)
		MW113 Area – 1.7 gpm

Date: 1	hursda	/, April 28, 2022		
Time:	0600	Plant operations good. Observe MW38 source well batch extraction	Stopped at 0317 often	
1,376 gallons - batteries empty (7.540(54) 8587, full), Start MW38N &			BNIS extruction to	
	T.540/541 to displace the source well water to in the conveyance procline to T.540/5			
31	0750	Diological operations gove.		
	0845	345 - working on monthly/weekly Plants systems cheles and caltsmatters to day		
		- Culibrate Ste multimeter to one during LEL-740 cultivation to ensure Oil Ambreut Ar 5m T-740.		
		-create New AHSTOS (4+10) to use today During AH probes carefrances.		
	0925	-Decant T-351 to bottom vulve, wetwell a cottomed, wenter to clear wo culor.		
		- Clean pH-315 probe w/ Heid Solvion. Check THE Hand 80 For oil or 5 Heen: None offernal. Sorry down were.		
<u> </u>	- Chack TP-130 For oil globules: Noncokserved. water Is clear unly-ellow - gran trut 1120 - Perform morthly BTS p H probes cultiminary to New 4+10 pHS MET			
	1228			
	1300	- Suspend Plant Atscharge to catterate p. H. 740 to NCW 4+10pH5 170° and f. EL-740 to 49% (EL. 109 - Plant SHUTDOWN FOR High LEL 28% During cultowatern. Automote start Down Harm working properly.		
	1309			
	1347	- Switch MW38N+S pumping wills to Hum 30 mode. 672 gal Flushed then stepelme to F-540/541, Redu	ce lusts plan to 0.60 pm.	
	1500	-Plusts operations Good.		
			Influent Sources and Flow Rates: @ 0750 NBBW – 6.3 gpm	
			North End On Site- 12, 2 gpm	
			North End Off-Site – £9 gpm RWST – 2.0 gpm	
			NTES - 0.49 gpm(10R only) MW38 T-540/541 - 0, 2 gpm(Source	
			well and 38 pumping wells mix)	
	, <u>199</u>		MW38 N & S- / 3 gpm (+ /-546/54) COND/NTES T-530- 0.0 gpm(Garri	
			1pm daily(0) MW113 Area – / (7) gpm	

Date: Friday, April 29, 2022

Time:	0610	Plant operations good. Observed BTS effluent results doingwell. Incre	re T-540/541 to BTS	
		V *10m 0. 2 spn 40 0.3 spm.		
0750		Blowdown aprosations good.		
		- Decart 7-351 to bottom value wetwell actually wester to clam works		
		- Clemp 4-315 probe w/ Acrd 3 oliveron. Check the Home 30 for sil or steen: wone or second. Spray Down was	m,	
		- Check TP + 30 for oil globules : work observal, water IS dear on / y ollow - green trut,		
	1030	- location setting of and cultivising Autosompla to stuat on Monday for mentily Molybacum cisculos, to from motion !		
		-Triple druge dedicated composite container, will add presentive gras prouns stated up.		
	1130	- Place STS Dryo mum world to BACKWASh GACF 3340 and Plush Leastorteed Lines.		
	1228	W		
	1237			
	1315 - NOTICE BTS Recycle valve Not hesporting correctly and over flow tank NOT hetil try. Cycle STS EATS HILL For a min and BA			
field. Lecycle value sack to wormal and overthew take atting again.				
	1445	- Plants operations Grand.		
	11-01			
	52.00			
			Influent Sources and Flow Rates: @0753 NBBW - 6-3 gpm	
A			North End On Site- 17,1 gpm North End Off-Site - 8.7 gpm	
			RWST - O. 6 gpm	
		9	NTES - 0.46 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source	
			well and 38 pumping wells mix) MW38 N & S- 2.0 gpm	
			COND/NTES T-530- o.o gpm(6am-	
			1 pm daily) MW113 Area – /. 7 gpm	

Date: Saturo	lay, April 30, 2022		
1330	Flant appretions good.		
1500		Her is dear	
	no color.	,	
	Olean pH-315 probe by acid solution, Chock HMR-	-30 for oil or	
	sheen: None observed. Spray down wir.		
	Chock TP-130 for all albadies: none observed lubber is very		
	clear with yellow- green tint.		
	Both GCs operational within limits, GC1 (TP-730):1,1-DCE@10,25ppm		
	All Blowers okall		
	Phosphorus tank (0) 85,001.		
1530	Plant operations operations		
1950	- Nemon Log m. Allox		
Sunday	, FITTH MAY 1, 2022		
0900	- lemon Log M. Allon		
2100	- Remoh Login. Allor.		
W6.41.77			
		Influent Sources and Flow Rates: @ 4年イ〇 NBBW – し, う gpm N. END ON-SITE – 42.2 gpm	
18	i e e e e e e e e e e e e e e e e e e e		
		N. END OFF-SITE - 8, 6 gpm	
		N. END OFF-SITE - 8, 6 gpm RWST - 0, 6 gpm NTES - 0, 49 gpm CONDINTES 1-530 - 0, 0 gpm (6AM-1PM	
		N. END ON-SITE - 12,2gpm N. END ON-SITE - 2,2gpm N. END OFF-SITE - 8,6 gpm RWST - 0,6 gpm NTES - 0,49 gpm COND/NTES T-530 - 0,0gpm (6AM-1PM daily)	
		daily) MW38 - 2 O gpm	
		daily)	

DITZ"OF Kum

LOWRY WTP OPERATIONS LOG

Date: Monday, May 02, 2022

Duto. I	nonday,	Way 02, 2022			
Time:	0730	- Plunts openiums Good. Astomner Glandown openiums Good. All Withe Herd present	me to composite contamer.		
	0800	- START Auto samples for 10 tml melphonum composite from masol. Total Extluent > 2542892	14gel 2 6.9260 2157°C 2		
		30.3gpm			
	0855	- DECANT 7-351 TO bottom valve. Wetwell actuated. water 73 clear NO COLOR.	- Decant 7-351 TD bottom vulve. Wetwell actuated. Water 33 clear NO Color.		
		- Clean pH-315 poles without Solution. Check THE HUM 30 For 017 or 3 Helen: None as served spray down	wer.		
		- Check TAISO Foroil globules; None OB served. Water IS clear of yollow-green trust			
	0955	- working on monthly Eddly warning stamping for workered 14- 9. oxum and Rivel melybol.	are in .		
		-working on IX performance HACH Testing willab split strapting After 1329, wogel Trented: TP-183 2260 4, /6;			
		TP-175A 2 280 4/1; TP-174 A 25300 49/1; TP-170 27100 41/1. Corruth Running 21.			
		In to Fortye ont packing tomore to course			
	1150	- begin flush of mp-ool sample port and sheek for legibual chlorine: None netected, ok to use ACI preserved wats, water to very clear nocolon			
	1200 - collect 15+ set of Time paced goods samples from macol for monthly Low Level 1, 4-000 xare, Place stamples to Fridge w. 74 of 1550 - begin flush of macol sample port and check for regular Chlorine: None servered. Water 55 very clear word for		a fridge with a thurs.		
			-		
	1600	- collect 7ml set of Time paced grabs samples for monthly Low-Level 1, 4-10, otane. Alace samples on Friday	withothers.		
	1950	- Begin Elishor mpool stample port and checker restrict chloring None sexusal. wayen to very clear			
	2000	- collect 31d setor Time puced grub samples from MA 00 sample port for month by Low-Level 14-0-000	es. Alace strates In Fridge withosthy		
	2350	- begin this of motod sample port und check for resident chlorine; work percent water Is very cle	eur Miceler.		
	0000	- collect 4th sctor timpaced grub samples from m ADDI sample for How How Low-Lovel 1, 4-CHOKANE.	Aluce samples to atotal withorks.		
			Influent Sources and Flow Rates: @0755 NBBW - 6.72 gpm North End On Site- 12.1 gpm North End Off-Site - 9.1 gpm RWST - 0.6 gpm NTES - 0.49 gpm(10R only) MW38 T-540/541 - 0.3 Ogpm(Source well and 38 pumping wells mix) MW38 N & S - 1.9 gpm COND/NTES T-530- 0.0 gpm(6am-1pm deily) MW113 Area - 1.69 gpm		

Operator:	Mike Gelwick

Soperations Good. Propers Got for START of Efficiency checks Fligh of MP-001 SAMPLE port and Check for Lesthval Chlorine: Nove Betactod wanter IS very all to the set of time paced grab samples DMP-001 sample port for mouthly Low-Level 1, 4-000 my on 6TS weekly sampling and START Efficiency checks -e NTES Unstable Alarm. Acknowledge and Ethish 6TS sampling. Notice NTES Sump transducents when the samples and Ethish 6TS sampling. Notice NTES Sump transducents when the samples and Also collect TR740 + 710 weekly Low-L + NTES TO T-530 and START P-005/T-530 P 0.50 pm. LIKE MPZ-lok STARTED again. May Have Aranon Journ to a lechange point will check on things with	rane. Abushuplast in Fridge with st r Not Registering on either Hout, wil
Flost of M1-001 SAMPLE port and check for less toal chlorine: None Betactod woman IS very all to the set of time paced grab samples 2M1-01018 Ample port for monthly Low-Level 1, 4-01019 My on BTS weekly sampling and START Extremy checks The NTES UNSTABLE Alarm. Acknowledge and critish 6TS sampling. Notice NTES sump transduces shoot Appers sampling. Samples to to Fridge until Placeting. It weekly TP-730 GE/Lab Spilt SAMPles and Also collect TP.740 + 710 weekly Low-L + NTES TO T-530 and START p-005/T-530 2 0.50 ppm.	rane. Alucesamples to triby with a root registering on ofther HMI, will
t 5th set of time paced grub samples 2MP-0015Ample port for monthly Low-Level 1, 4-0001 my on 6TS weekly sampling and START Ethicency checas The NTES UNSTABLE Alarm Acknowledge and Emish 6TS sampling. NO tice NTES Sump transduces SHOOT Appersumpling. Samples to to Fridge until Phenony It weekly TP-730 GE/Lab SAMPles and Also collect TP.740 + 710 weekly Low-L + NTES TO T-530 and START P-005/T-530 2 0.50 pm.	rane. Alucestruples to triby with a Not Registering on without House, wi
thy on DTS weekly sampling and START REFERENCY chairs THE SUNSTABLE Alarm. Acknowledge and critish 673 sampling. NO tree NTES SUMP transduces SHOOT Appers sampling. Samples on to Fridge until Acknow The weekly TA-730 GC/Lab spilt samples and Also collect TR-740 + 710 weekly Lows-L NTES TO T-530 and START p-005/T-530 P 0.50 pm.	r Not Registering an either House, wi
the NTES unstable Alarm. Acknowledge and contil 673 sampling. Notice NTES sump transduce. Shoot Appers sampling. Samples to no Fridge until Acknowledge. TR-740 + 710 weekly Low-L + NTES TO T-530 and START p-005/T-530 2 0.50 pm.	
-3400+ Apper Sumpling. 5 Annales to no Fridge until Accessing -t weekly TA-730 GC/Lab SAIA SAMPLES and Also collect TA740 + 710 weekly Lows-L + NTES TO T-530 and START p-005/T-530 P 0.50 pm.	
+ WEEKLY TA-730 GC/Lab SAIRSAMPLES and Also collect TR740 + 710 weekly LOLS-L + NTES TO T-530 and START p-005/T-530 2 0.50 pm.	and i, 4-41 orane organistos.
NIES TO 1.530 and START p-005/T-530 7 0.50ypm	
LIKE MPZ-lok stratted one to may have around lown to a locker some will check on there is	
The state of the s	there - As there to The
matte blowdown operations Good. GO to check on NTES. All Feens wormed, will check sin	of bovel with meser to see week.
. Flush or MA-OUL SAMPLE port and check for restrive chlorine: None detected water to very c	lear uscolor
0800 - Collect 6+h/ftmal set of time paced grab samples from mostly convertely convicuel 1, 4- Aroxum. Alice sample on a 5 TOP ACHO JAMpler, Total Efferent & 254336092 pal. Atotal of 46878 gall treated Owner 5 Ample person	
TES BACK TO Normal made and STOP T-530 10-005 as un. flish w/ Potable water on m Aut to	leve on to Aen These seeded again.
RUSTS DUMANNY TANKS Q 13%, Reset NTES telements 2440 level large some Rift TS	do a brida listale de la cidada dela cidada de la cidada dela cidada de la cidada del cidada
comp manual level Reading 28.63' THIS IS THE FAMILY LAST MENTER ON 4-12-22 Will de Mars and	simple color of land the training
54 5-1-22 2-2230. PACK AM SAMPHER ON THE BOT COURT MATERIA.	John John, Lowes fire IT
	Influent Sources and Flow Rates: @0\$2
	NBBW - 6.2 gpm North End On Site- /2.2 gpm
TP-130 For Oily wholes: None observed, usutar I3 clearful wellow-green wint.	North End Off-Site - 7.1 gpm RWST - 0.0 gpm raws
my on 573 field headings.	NTES - o.SO gpm(10R only)
	MW38 T-540/541 – 6.30 gpm(Source well and 38 pumping wells mix)
or of the state of a cold of the body of the cold of t	MW38 N & S− 1. ¶ gpm COND/NTES T-530- Φ: Φ gpm(Sam-
operations Good	CONTRACT COO. ON GOIII(Beauty
2 00	THE S BACK TO NOVIMAL MORE and STOP T-530/p-005 again. Flugh w/potable water again but the Rust's pumping, TANKS & 13%. Reset NTES telemetry, sumpleved kight tenting but its sump manual level Reading 28.63°. THIS IS THE Same as last month ON 4-12-22. Will deplace 500N: ON 5-1-22 2-230. PACK ANSAMORIES ON ECCENT COURTED PREADA. At T-351 to bottom value. we two liectivated, water Isclear Nocolor. H-315 probe w/Acid Solviton. Check the HAMMESO For Oil or steen; None sourced. Sarray down went TP-30 for 0ilylobules: None observed. wanter IS clearly yellow-green tint. TM on ST3 Field Readings. (BT3 Phasphors typic wife to FT3 P and boggel of potable water.

0.25" lan overnight + Throught The day

LOWRY WTP OPERATIONS LOG

Date: Wednesday, May 04, 2022

ale. wean	esday, May 04, 2022			
ne: 072	20 - Plusts operations Good. At tomore blowdown operations Good. Working on weekly Col	C's cultisantours and muset recky		
090	10 - Decant T-351 to bottom value, wet well activated. water B Char No color.			
	- Clean Alt-315 probe whole it solvison. Check +the Home so For allo-5then: None asserted. S	pray down wer.		
	- Cheek TA-130 For oil globules : None offerved. water Bs stightly cloudy orange fort.			
1120	- AFTER Finding that MPZ-11, MTES-180W and NTES Sump TRANSJUCERS all Had a malfunction	at tik exact same tome on 5-1-22		
	E TOOK a manual Level at exhaustland kent Bratal them to the profer Level. MPZ-11 2.			
	Receirgrated; NTES-180W 335,88 07W=5729,75 HMI=5727.23 Leceirgrated; NTES SUMP 028,63 07W=5734, 20 MSL HMI=5756.			
	Accurdences; MPZ-102 Level and TRANSduce OK , 0 34,28 '0 Th = 5728,37 MSL HMF = 5728,39 NOR	eal, After becalgarassen All seem to		
#14.5-	Be Indamy + the Level FAPUT.	2 - 4 8 8 8 8 8 8 4 4 4 4 4 4 4 4 4 4 4 4		
The state of the s	2 - REBOOT HMIFTUREN 1. DIRKOT BALKUP TUREYS DATA, RESERTING TEMPORARY MEMORY. WILL SA	ick upon flush prive and bisk tomorrow.		
1450				
1550	-12 lynts operations Goals			
	· · · · · · · · · · · · · · · · · · ·			
		Influent Sources and Flow Rates: @ 0835		
		NBBW - 6. Z gpm North End On Site- / Z. (gpm		
		North End Off-Site – 9.1 gpm RWST – 0.0 gpm		
		NTES - 0.44 gpm(10R only) MW38 T-540/541 - 0.29 gpm(Source		
		well and 38 pumping wells mix)		
		MW38 N & S- 1 9 gpm COND/NTES T-530- O gpm(6 am-		
		1 pm daily) MW113 Area – į, ⊘9 gpm		

OUL NIGHT

LOWRY WTP OPERATIONS LOG

Date: Thursda	y, May 05, 2022	
Time: 08∞	- Plants operations Good. Daning of or Bloodness operations on, Ges operations Good within a	mits working on weekly Plants
	5 4 Stems Checks and calibrations tolay, NITES TRANSduces Holding Calibration ok.	
1005	- Decunt 7-351 tobottomulus, wet well activated, water to clear wocolor, Getting Stylt	by chounger at and out Ascount
	- Clean pH-315 probe of Acta gowston. Check the Home 30 Foronor steen; None asserved garage dos	we were,
AND A STATE OF THE	- Check TP-130 Foro. I globules: None osserved, water IJ stightly cloudy orange fint.	1
1340	"Suspend Plant Discharge to califrate pit-740 probe to 4+10 pt 5113.	
1351	- lesume Normal Dis charge. Continue with other plants pit probes californitons to 4 +10 pits 17020 p	H-117 670 710 710 - 1710
1430	- weekly starts 345 toms check sand colosia 40005 complete.	113,000,300,303
1450	- weekly DATA BACKUP PETORMS. BACKED UP DATA FRAMWIP +GC to Elish Some and 8/34.	
	-GUY STURTING to PUMP INTO LUSTS, STURT RUSTS pumping is 0.50 goin to HML30.	
1510	- Plants operations Good:	
		Influent Sources and Flow Rates: @ 1005 NBBW - 6.7 gpm
		North End On Site- /Z-Zgpm
		North End Off-Site – & 9 gpm
		RWST = 0.0 gpm NTES = 0.10 gpm(10R only) MW38 T-540/541 = 0.30 gpm(Source
		well and 38 pumping wells mix)
		MW38 N & S− (· 9 gpm COND/NTES T-530- □ □ gpm(6am-
		4 pm daily) MW113 Area – <i>t</i> . 6 9gpm
		Militario Alea – ti 🗸 Ogpili

Date: F	riday, N	lay 06, 2022	
Time:	0730	- Plants greatous Good. Actomatic fluidown cyperations Good.	
	0915	- Decare T-351 to bottom valve. we swell actioned water of clear vocalor, Kindow slightly clearly at a	dos securi
		"Clean Att-315 probe what solution. check the Hund 50 for oil or steen: wome on served. spray own w	erien.
		- Check 484 30 Par 0,1 globules; None as served, waters sughtly cloudy at orange that	
		- Revill 513 shosphares tanker/4 # or TS12 and 40 yel of potable water.	
	1100	-Plunts operarms Great.	
200			
			Influent Sources and Flow Rates: @ 0900
	2.4.		NBBW - 6:3 gpm North End On Site- /Z. Z gpm
			North End Off-Site — 4,1 gpm RWST – 0.50 gpm
			NTES - 0.45 gpm(10R only) MW38 T-540/541 - 0.31 gpm(Source
			well and 38 pumping wells mix)
			MW38 N & S- 1.9 gpm COND/NTES T-530- 2-2 gpm(6am- 1pm daily)
			MW113 Area – 1.70 gpm

Date: SATURDAY, MAY 7, 2022

0.	, ., .,	
0515	- Plants opensions crowl. God to Check other 5 the sigs turns.	
040	"Decem + T-351 to hottom vulve, wetwell old Not activite, water to clear Noceles,	
	- Clean p. H- 315 probe w/ Heth solv Horr. Check who Hum to Rom 0.7 or steen: wore observed	1. Savaydown wer.
	- Check TP-130 For oil globules: None asserved, when Is slightly cloudy working want.	
	- Both GC operational within limits.	
	- All Blowers OK. Momer Brit on Reactor 3 courses ensing in France. will address on marker	
	- BAY Filters open word Good,	
	-No le Fill needed on Philosphers +Ann. 290gal	·
0700	- Ar transic down operation Gost	
0145	- ismany will ontof som our	
0750	0750 Physoperations Cost	
1250 - Receive Cyc VOL High Hlava. 1,1-DC. E leaving Fit Se High > 3157, 22pp. Rese		end will rake a wens sangle Atten UU-OX Cooks
DOWN.		
	1329 - START a New Cac 1/TA-730 Satraple.	
	- SAMPLEAME OUT GOOD /OK.	
2100	- Kenose Login Allok	
	MAY 8, 2022	
0842	- Henore Log on all ox	Influent Sources and Flow Rates: @ 05
2130	- Remon Log on All ac.	NBBW - 6:3 gpm
		N. END ON-SITE − /2.72 gpm N. END OFF-SITE − /8.5 gpm
		RWST - 0.5 gpm NTES - 0.49 gpm
		COND/NTES T-530 - a 2 gpm (6AM-1
		MW38 – 2.0 gpm
Area Sea treated the books are self-limited		T-540/541 − 0⋅30 gpm

D	LOWN WIP OPERATIONS LOG		
- Take of the Amin Control	, May 09, 2022		
Time: 0545	Plant operations good.		
0610	Fusion Connet technician onsite to install and setup 46 LTEINTONE	f (replaced TI)	
0740	Bloudour operation, good	1 ().	
0755000	Start filtepress on stage 1.		
	Start 24hr Nop. 001 grab scampling For Nony (phonol (resample due to QC	" course with but	
	months sample). Effluent total reading 254610862 gallons, pH-740	- dir. 692 9 1515'	
	Flum rate 30.0 gpm.	12000	
0813	Reboot HMIFTVIEW 1 to check interest - All man - online oria		
0900	Rutart FF T530 to BTS at 28 0:2 com 6 am - 1pm (took e 314 full).		
1040	-Clean pH-315 probe at Acid solution and check the Hundso For oil or steen wone observed. Spray Downe	To de	
	- Cheek TD-130 For oily lobules: None osserved, water & Slightly cloudy who range +mt.		
	- Recill polymen topok and 2 cups on NALCO polymer and 200 gal or potable weeter.		
1150	- Seyn Flish ox mp-out sample port, water is clear worken weather y		
1200	- Collect 1st Set of time paced grab samples Impost sample port for Nowy 1 phenois Resumple Place 5 Amples	- Fred	
1545	- STEP Filterpress. Not Fell yet . Institute 4.	eur-my	
1550	-segm Fligh or mp-od symple port. weeken to very clear Nocolor.		
1600	- collect 2nd set ox time paced grab samples 2 pp-ool sample port For ATTY NONY / phenols Lesample, P	Ut Show Olad on Ende can't allegar	
16 05	- Plants operactions Good.	or the state of the original or the original ori	
1945	Best MP-001 sample post flush. Water is very clear, No color -	Influent Sources and Flow Rates: @0920	
2000	Collect 3rd set of time paced grab sample for quartely Nonylphenol resample-Place	NBBW – 6.3 gpm North End On Site- /2.1 gpm	
	sample in fittle with others.	North End Off-Site – 98 gpm RWST – 0.5 gpm	
2345	Bestw MP. 001 sample post fluch. Wateris very clear, No color.	NTES - 0.44 gpm(10R only)	
0000	Collect 4th Sctof time paced grab sample for quarterly way phenol resumple.	MW38 T-540/541 - 6 · 3 gpm(Source well and 38 pumping wells mix)	
	Place sample in forge with others	MW38 N & S- 1.9 gpm COND/NTES T-530- 0.2 gpm(6am-	
	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	1pm daily) MW113 Area – <i>1.7</i> gpm	
		ser, to Allow \$47 gpill	

Date: Tuesday, May 10, 2022

Time:	0315	- Plante operations Good. Prop GCS for Efficiency checks state of. Restate Filter Aress Enstate 4.				
	0350	- Begin flush of MP-out sample port. water to very clear No color				
	0400					
	0415					
	0450	- Collect TP-730 GC/Cub weekly split samples. Also collect weekly TP-710+TP-740 Cocolevel 1,4-814 are samples.				
		- Filterpress Full. All standes Aluced to Fridge UNII time to stew water conview				
	0510	- Clean Alt-315 probe w/ the tot 50 with Check the HIML 30 For offor siken None of served. Shray Down	wer.			
		- Chack TA130 For oily tobules! None of served, water IS clearing up again w/yellow-green +rn+ usual.				
	0750	- begin flish or mp-oul stample port, weter to very clear nocolor.				
	0800	2800 - Collect 6th/Frank set of Time packed grade sumples 2 mp and sample part for attly wavy presents ke sample. Here in the accordance				
		and Dupe). Place samples on Fridge with others. TOTAL ESTIVENT 2254,657,722gal. A fortal of 46,860gal A				
		During sample period.				
	0845	45 - IX partormance HARCH TESTING W/Lub Split sampling AFT or 1348,344 al treated: TP-183 2 250 mg/L;				
		TP-175 A 2 270 ug/L; TP-174A > 6200 ug/L; TP-170 2 7300 ug/Lo Corrently Running 2 1.69 gpm.				
	1200	- Reditlots phoisphers tANK w/6 # OF TS P and Gogal or potable water working on BTS Fred Leadings				
	1430	- Plunts opera Hons Good				
	1555	Receive FT-055 low flow alarm. MW170-EWI Submusable Jump motor drawing too many				
		amps and will need pump replacement. Leave MW170-EW-/ extracts	on system powerd			
		down for the Night. Note: This pump was installed 2/6/15 and	NBBW – 6.3 gpm			
		has pumped ~ 84 million gallons.	North End On Site- 12-1 gpm North End Off-Site – 8-4 gpm			
		. ,	RWST - 0.5 gpm NTES - 0.50 gpm(10R only)			
			MW38 T-540/541 − 0.30 gpm(Source			
			well and 38 pumping wells mix) MW38 N & S- + - 9 gpm			
			COND/NTES T-530-			
			MW113 Area – /. 69 gpm			

Date: Wednesday, May 11, 2022

	12003-20000		2			
Time:	0500	Plant operations good. Start on weekly GC maintenance and calibration	UNS. TELP FOR MWITHEWI			
		EXTRACTION DUMP SWAP.				
	0745	Blowdown were time and				
	0800	Stop MW38 N'S extraction in properation for MW38 source well batch extraction. Incress RWST in Fluent from 0.5 spon to 2.0 spon. Switch MW38 pipeline from direct				
	0817	INCRUSE POUST INFLUENT From 0.5 year to 2.0 jpm. Switch MW38 pipeline from direct				
		HMR30 YNFLUENT + T.546/541.	()			
	0840	-STARTMO38 Sourcement BAtch to 5-540/541				
	1045	- Leceive GCZ High use Alarm Due to Disable Alarms timer timing out During a Kinse blank of	the GC. Alavar working well			
		PUT BIO DATO HOLD. Leget every throng and Get GC gotes on Norman JAMILES.				
	1770	- Decant T-351 to bottomyalve. wetwell activated, water 15 clear wocator.				
		- Clean p. H-315 probe withen solveron. Check the Hond 30 For all or Solven: wore asserved. strangeles	and water			
		- Check TP130 For oilylobules: None Obsand, water & clour exyellow - green trut steen				
	1430	- Me 170 - Ever hestarted and Rummy ou.	7.50			
		- Plunts of pensyons Good.				
	12.					
			Influent Sources and Flow Rates: @0757			
			NBBW - 6.2 gpm North End On Site- 0.0 gpm			
			North End Off-Site – 8.6 gpm RWST – 0.5 gpm			
			NTES - 0.48 gpm(10R only)			
			MW38 T-540/541 – 0.7 gpm(Source well and 38 pumping wells mix)			
			MW38 N & S- 1 9 gpm COND/NTES T-530- 6.2 gpm(6am-			
			1pm daily)			
			MW113 Area - 1.7 gpm			

Date: Thursday, May 12, 2022

	101100000	Plant operations good.					
	0622	MW38 Source mail batteries died at 0120 last night, T-540/541 @ 57% - Start MW38 N'S					
	wells to desplace source well mater in the pipeline to T-510/541.						
	D930 - Decemb T-351 tobottom value. Wetwell activated. water IS Clear Nuceston.						
		-Clean p. 4-315 probe welter & southorn. Check the year 50 per offer steem : wone asserted strang Bown wet.					
	- Check TP180 For Oily lobules: None cosserved. water Is clear why Now your Host.						
- without on weekly Alors systems checks and culmstations today							
1205 - Switch mw38 N+S pumping wells to Hun30 mode. 736gal Flush + Hr mw38pipeline. Reduce MessTS F							
	1243 - Suspend Plant arzcharge to califfrante pt. 740 probe to 4+10p45705						
		- Resume normal Arschurge. Continue with other pt probes call snawous ro4+copts 500 = pt-113,670, \$10,315 + 365					
	1330 - weekly Alusts systems checks and confisherious complete						
1340 - Place BTS price maint Hold and Klush soit Piping.							
1425 - ST3 OVFOCHER . Allok							
	1430 - Welly BATA BACKET complete.						
1530 - Plant's openiums Good.							
							Influent Sources and Flow Rates: @ OSK NBBW - 6.3 gpm North End On Site- 13.4 gpm North End Off-Site - 8.7 gpm RWST - 2.0 gpm mass source at the harmonic state of the harmonic

Date: Friday, Ma	y 13, 2022	
Time: 0615	Plant operations good. Blowdown operations good. Reboot UMEFTVIEW I to reset available temporary memory, online of Decort T-351 bottom value, wet well activated. Water is clear, no con weir and pH probe- no oil or shown observed in the HMR.30. Check NO Ne observed. Water is slightly cloudy light yellow/space. Plant appratum good.	
0745	Blowdown operations good.	
0 802	Reboot HMEFTVIEWI to reset available temporary memory, online of	807.
0960	Decant T-351 bottom value wet well activated. Water is clear, No con	lor. Clean the HOME.30
	weir and pH probe- no oil or shown obscued in the HMR. 30. Chack	TP.130 for oil globules,
V	No we observed. Water is slightly douchy light yellow/ sreen.	
1250	Plant aprations good.	
Network.		
		The state of the s
		4.10
		L d and Courses and Flow Butter 2000
1000		Influent Sources and Flow Rates: 0636 NBBW – 6.2GPM
		N. END ON-SITE – 13.8GPM N. END OFF-SITE – 8.9GPM
		RWST – 0.5GPM NTES – 0.49GPM
		COND/NTES T-530 – 0.2GPM (6am-1pm) MW38 – 1.2GPM
		T-540/541 = 0.3GPM MW113 IX SYSTEM = 1.7GPM
		OTHER - NA

Date: South	volay, May 14, 2022	
0700	Plant operations good (in blowdown).	
0720	Clear the HMR. 30 weir and pH probe-no oil or show observed in the	W HMR.30 Note: All
	thru studge laterals clear and working very well. Check TP-130	for oil alobules -
	None observed. Water is clear, light yellow/green.	
0745	Blowdown completed - All oney.	
0850	Refill phosphorus tank with 55 gallows potable water + 5.5 165 TSP.	
0430	Plant operations good.	29
5/15/22	3	
०ऽ५ऽ	Check plant remotely - All okay. N. Fail on site flow clown to 13.1gp	M.\
1845	Charle plant remotely - All olegy.	
2032	Recease P-3324 Strawe- glam. Unable to get pump to Flew remobely.	Switch R3 influent
101-011-011-011-011-011-01	Lo D -3323.	
		The second secon
		Walter Co.
		Influent Sources and Flow Rates: @ 0745
		NBBW - 6 · 2gpm N. END ON-SITE - /3.4 gpm
		N. END OFF-SITE - 8,4 gpm RWST - 2,2 gpm
-		NTES - 0.5 gpm COND/NTES T-530 - 0.2 gpm (6AM-1PM
		daily) MW38 – 1. 9 gpm
		T-540/541 - ð.3 gpm
		MW113 Area – (, 7 gpm

Date: Manday May 46, 2022	
Date: Monday, May 16, 2022	
Time: 0105 Receive Heartbest error 1 alarm. Remotely acknow	ledge alow ON HMIZ. HMTFTUISE
LOU UNIESPONSINE	
0521 HMIFTUIEWI ONLINE after hard reboot. Window	us was frozen. Plant operations
OKay TP-730 Flow to GCI Slow. Clean V- Strainer	- in building and bleed are trum
0521 HMIFTUIENI ONLINE after hard reboot. Window OKay TP-730 Flow to GCI Slow. Clean y- strainer POU - Flowing good Now. Work on changing One 125 KB/5 (was having trouble syncing the larger one 0745 Blowdown porations and	Drive settings to live t unload specult
125 KB/5 (was traving trouble syncers the larger con	early Files - watering laste a unit
0815 Troubleshoot P-3324 - MOTO- OKAY but wet end not 1	Flowing, Note: This is they last of the
OBIS Troubleshoot P-3324 - Motor okay but wet end not fortganal Feed pumps, Isolate P-3324 and lockon	+ Drugs to it wails leaving +
wet end internals.	The total contract the contract of the contrac
09/5 - Decemt 7-35/ Bottom unive, wet usel acquarted, water oscion vocation	
"Clean SH-315 probe W/ Herd Scheron, Check the Hond 80 For ail or 5 Hears, Nome out In	wood. The heighten wer.
- Check TP130 For offglobales: Worke DEScent, water of clear uf yellow -	green typet.
1000 - worken Swiff out or A-3324 Pump w/New March Jump. The Empethal on the cur	TENT ONE B SHOT!
1430 - New from and pipmy tous tould a p. 3324, will come off and lex give and Three	d sealant Art overwhole t
1500 - Plants openastors Good.	
	Influent Sources and Flow Rates: @OBIO NBBW - 6.3 gpm North End On Site-13.0 gpm North End Off-Site - 4./ gpm
	RWST - 0.5 gpm NTES - 0.46 gpm(10R only)
	MW38 T-540/541 - O 3 gpm(Source well and 38 pumping wells mix)
	MW38 N & S− 2 · Ø gpm COND/NTES T-530- Ø · 2 gpm(6am-
	1pm daily)
	MW113 Ārea - /. 7 gpm

Would 2000	
	-7/04 7/10 - markly could be 11 1/40
SAMPLES. Place Samples and State of proceed enters. 18180 CONGET 11	170 + 140 weeks Low Level 1, 4 girane
	well.
Blowdown operations good. Mile working on weeking 505 sampling and freld	Lawings tealas
-IX system per Formance HACH resting with weekly cal splits After 1,365-446 gal Freehold	: TP183 2 2704/4:
TP475A - 310 ugk; TP-174A 26600 ug/L; TP+70 27100 ug/L. Systemourroutly	unny 21, 68 gam.
	gowih wern
" Check TA 130 For Oil globules; wone observed, water Is clear w/yellow-green tout,	
Things of values Gost	
	Influent Sources and Flow Rates: @ os3c NBBW - 6.3 gpm North End On Site- 12.9 gpm
	North End Off-Site - & 9 apm
	RWST - O. S gpm NTES - o. 4 8 gpm(10R only)
	MW38 T-540/541 - c, 3 t gpm(Source well and 38 pumping wells mix)
	MW38 N & Ś- Ź-O gpm COND/NTES T-530-0-₹ Ø gpm(6am-
	1pm daily) MW113 Area – <i>[.</i> 67 gpm
30000	Edy, May 17, 2022 - Plunts openations Good. Co-cellet TP-730 GC/Lab Split Shippes and STALT Efficiency chiels. Also collect TP SAMPLES. Place Springles priviles. Startup P-3324 New pump & motor as Food to R3. Working a loss bloodsown operations good. Mile wavering on working 575 string trag and field TX system for formance Harch restring with weekly Lab Splits After 1,365, 446 gal Trend TX 17574 - 310 mg/k; 77-1747 2600 mg/k; 7770 27100 mg/k. System currently & Contrat - 351 to fortion waver workwell activated water 55 clair No calor. - Clean At-315 proba wolker'd solution. Check the Hamisto for oil or silven; Nove assured. Shreys check TA150 for oil globules; None assured. Water 55 clear W/yellow-green trat. - Plunts approximas Goods.

Date:	Date: Wednesday, May 18, 2022		
100000000000000000000000000000000000000		Plant operations good. Start on weekly GC maintenance and Calibrate	<u> </u>
	C342	Blowdows operations good.	
	0803	Reboot HMIFT VIEWI to reset temperary file memory cashe - Onlike e	C C C C C C C C C C C C C C C C C C C
***************************************	0900	- worken Grenned Assets Champ.	. 0009.
		- Decant T-351 to bottom valve, wet well activately water IT clear No color.	3.0
		-Clern p 1+ 315 probe w/ Acrd solv 4000. Check the 14000 30 For ottor 5 Hear: None agreered. Shay Dou	un wer
		- Check TP +30 For of globules: None osserved. water 35 clear w/yellow grown trust.	
	1107	Receive UVOX Warning alarm - peroxide flow low. Peroxide pump Ind	Ecative the interal
		Receive UVOX warring alarm - peruxide flow low. Peroxide pump and pressure exceeded and tras stopped. Able to quickly return peruaide flow	to recover by restarting
		the pump and priming to remove some trapped air.	
		Ketil physhorus tanh with 60 gallers potable mater + 6165 TSP.	
		Mike performing quarterly 4x8 POTW divduse line inspection	and value exercising
		I DIG TONOMESE TO LES A LONGRESSE LOS LONGRES DE TIL PROPERTY DE COLONIA LOS	
	1300	BACKUP data to Flash & DVD. One Drive backup working well POTW QTry value exercising and vivil cent courses complete. Also Inspect MH175-078 Arching for	/.
	100	The I was extended and west tent cheeks complete. Also Inspect MH175-078 Araching for	nt. Allose
	1530 Plant operations good.		
			Influent Sources and Flow Rates: @ 1025
			NBBW - 6-3 gpm North End Off-Site - 2-7 gpm North End Off-Site - 8-8 gpm RWST - 0-5 gpm NTES - 0-18 gpm(10R only) MW38 T-540/541 - 0-30 gpm(Source well and 38 pumping wells mix) MW38 M&S - 1-1 gpm Direct Pecchange of the COND/NTES T-530- 0-21 gpm(6am-1pm daily) MW113 Area - 1.68 gpm

Date: Thursday, May 19, 2022 Time: 0545 Plant operations and 0700 Receive UV-0x shutdown - Low Flow (Flow drapped below 5 gpm while switching ruto recycle). Clean PDU air release and backwark POU while unit is off. 0805 Blowland operations good - HMR-20 refilled restart UV.OX. Observed a large amount of oir in the recycle system - purp was intially our locked on rulest. 0623 UV-Ox warmup completed - discharging to PDU/Feed suretark, PDU D present improved from - Clean AH-315 ANDEW Acid Solveron, check +4 Hune 30 For oil or 5 Heen: No recos served. 5 Aray Down were · Check pf-130 Cor oil globules; None asserved, water Is clear up yellow green trust. - Perform Acri / BASEClerning or 873 pH probes In preparation for califration went week 1100 1234 - SUSPEND plant 0,3 charge to calibrate AH- 740 proper to 4+10 pHSTM3. 1240 - Lesume wormal Discharge, continue with other pt probes califications to 4 +10 pt 500 3 pt-113, 620, 310, 315 + 365 13/5 - weekly shorts systems checks and culisonizers complete, costinue with plant alences. - Plunts operations Gress. 1600 2119 Receive pH-365 unstable alarm - check remotely. PH of T.510 has suddenly etapped to ~2 P-631 appears to be malfunctioning because pH rises when pump is stopped by putting in manual off. When pung placed back in outs pH dropped again - acuto Influent Sources and Flow Rates: @ 0224 O'l. CV. Leave pump off and travel to site Observe when NBBW - 6.3 gpm

Phano is place in auto the sump is stuck in any mode and is

Compile malfuntioning (note: This has happened to other pumps of this modile

GAMMAX Prominent. Observe very pump for ~ 30 minutes for lake and puper

purposes rapidly - unable to get the purpout of aux mode

after man, year of service). Change out 9.631 with an upgraded

Operator: Mike Gelwick / Chris Carlson

North End On Site- 12.7 gpm

NTES - U.49 gpm(10R only)

well and 38 pumping wells mix) MW38 N & S- / 4 gpm

RWST - 0.5 gpm

1pm daily)

North End Off-Site - 6.4 gpm

MW38 T-540/541 - 0.3 gpm(Source

COND/NTES T-530- 0-2 gpm(6am-

Date: Friday, May 20, 2022 0701 - Receive UY-OK SANDOWN Alwam for Low Flow again at blow bown. Time: 0745 - HML30 FUH. RESTHAT UV-OX. NOT very much per pr significan. Automore brondown operators Good. 0803 - UV-OK warm of complete. Resimmy wormand Discharge to ABU/Feelsurge trave 0842 - Water going to UV-Ox Hang cooled Down. Place UV-Ox Into Recycle to test It Flow drops of again. - Flow Remaind Normal Allak. 0857 - Place UV-OX proplecycle again to test It Flowdrops of F. Flow Remard Normal, Allow 1003 - STALT a GCI/TP-730 SAMPLE to test IF UV-OX Flow Drops off Indecock of Auring the GC Kill cycle 1019 - Place UV-OX Into Recycle. Allow, NO Flow Drop. 1033 - UV-OX DISCHARGING NORMALLY TO PAUL FED SURGE TANK, WORKING ON GRANNI CLEMEN OF AGENTS. 1255 - Decant T-351 to bottom valve wetwell actuated, water to clear no colon. - Clean # 4315 probe w/Acid solution. Check +4c 1+11120 For oil or steen: None asserved. Spray Down work. - Check TP-130 for oil globules; None as served. water, Is clear in/yellow given trut. 1430 - Plants operassons Cood. (D) 06 40 Check plant / P. 631 aperations of motely - Observe TP-730 GC result from 2349 5/19 at 17.05 mg/L (Normally ND, Warning alarm 100 mg/L) Short Next TP 730 sample early. Plant and New P-631 pump working well. Influent Sources and Flow Rates: @ 1035 NBBW - 6.2 gpm North End On Site- /2.6 gpm North End Off-Site - 9.2 gpm RWST - 0.5 gpm NTES - 0.48 gpm(10R only) MW38 T-540/541 - 0. 32gpm(Source well and 38 pumping wells mix) MW38 N & S- 1.6 gpm COND/NTES T-530- 0, 20 gpm/6am-1pm daily)

Operator:	Mike Gelwick	

MW113 Area - 1,68 gpm

Date: Saturday, May 21,2022 LOWRY WTP OPERATIONS LOG	
Juan Plants aparations good	
1140 Noticed slow leak in Bldg 1 from ceiling due to heavy	
snow storm from previous night. Placed bucket to collect	
snow melt water. Texted Christ. 1200 Noticed slow leak in Bio from ceiling due to snow melt. Water	
is falling into grated area. Texted Chris.	
Prosphorus tank @ 55 gal. Adobd 45 # TSP and 45 gal potable	2_
water.	
All blowers ok. Both 6Cs operational within limits.	
1310 Decent T- 1351 to bottom valve, wet well activated libiter is	
CROI no color	ے
Check TP-130 for on globules none observed water is	
very clear with yellow-varean tint.	
Clean pH-315 probles with acid solutions. Check HMR-30 for oil or sheen: more observed. Spray down w	2
1330 Plants operations and	5 <u>U</u>
@ X0241 Received UV. 04 shutdown alar - Could be power related due to the storm or possit	10
The Field Dumo losted Dring Able to transfel v Tristact UV-DX Intuent Sources and Flow Rates: @ 1	130
Adjust UV. Of flow rate for 6.5 spor to 7.0 spor and RWST influent N. END ON-SITE - 12.5 gpm	
O303 Warn up completed, UV-OR discharging vormally. RWST-1,0 gpm NTES-0,49gpm CONDINTES T-530-0,2 gpm (6AM-1)	DM
0620 Chall plant remotely-All UKay. Observe UV-ox Switch to recycle MW38-1.9 gpm	r (V)
high flow and loguritham, changes working well. MW113 Area - 1,7 gpm	
1700 Charle plant remotely-Allokay, Reduce Rust influent to 0.6gem.	

OPERATOR(S) Manuela Seewald

Date: Sunday,	May 22, 2022	
0645	Chak plant remotely - All okay P-631 dosing working well. Observe UV-OX switch to recycle for blowdown - Allokay. Chack plant remotely - Allokay.	
0700	Observe UV-OX switch to recycle for blowdown - Allokay	
1650	Chack plant remotely - Allokay	

MARIE ROLL		
		Influent Sources and Flow Rates: @
		NBSW - gpm N. ENS ON-SITE - gpm N. END ONE-SITE - gpm
		N. END ONE-SITE - gpm RWST - gpm
		NTES – pm COND/NTES 520 gpm (6AM–1PM
		daily)
		T-540/841 — gpm
		MW113 Area – gpm

Date: I	Monday	May 23, 2022	
Time:	(%3C)	Plant operations and	
	0340	Plant operations good. 31 outlors aproations good. - Decent 7-351 to bottom value Wet well afterward water to clear No colon. - Clear 14-315 Note what so water is the state of the stat	
	0835	- Decant 7-35) to bottom valve Wet well a (trunked in when a class was colon	
		- Clean p.H.315 probe w/ Acid solv won. Check to Hunk 30 for oil or siken: None asserved. Spray Down	wen
		- Check TP-130 For Oil globules; None of served water Is clear why ellow-green titt.	
	1215	- Add a 5 gal of Lamwater / Swow melt to T-530 TANK From N. Pit over Ack with Equipment In a barrel From	N. A.T Extractions. water Is very
		clear Nocober and very clear cooking with No adar. Also Add + 2gal of purge water From MW4-01 + MW4-03 Ja	templing to T-570,
	1500	- Plums operations Good.	
			M
			** ;
			Influent Sources and Flow Rates: @0603 NBBW - 6.3 gpm
			North End On Site- 12.5 gpm North End Off-Site - 8.7 gpm
			RWST - 0.6 gpm
			NTES - 0.5 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source
			well and 38 pumping wells mix) MW38 N & S- / • 9 gpm
-			COND/NTES T-530- 6.2 gpm(6am- 1pm daily)
			MW113 Area – 1.7 gpm

_Date: Tuesday	, May 24, 2022	
Time: 0450	- Plents operations Good. Prep for JAMP Ving TP-730 740+ 710.	
0515	- Collect TP-730 GC/Kan Spirt 3amples and START Efficiency cheeks Also collect TP-740+TP-760	weekl tradicial 4-A Dress Sharks
0740	Blowdown operations good. Mike ! Tom (training) working on weekly	BTS / Tool Exclusions
	performance sampling / field resdings	13 / 2003 - 2000 - 2000
0 850	- Refill BTS phosphars TANK W/5 Hot TSP and 50ged of potable water.	
1020	IX Performance HICH Tesithy w/ weekly Lab SPIT SAMINA Afron 1,382,365 and treated; TP-183	230 m/L.
	TP-175AD 2304/1; TP-174A & 6700 4g/1; TP-1700)200 4g/L, corrently kunning 5	2 1.6 7 Dan.
1050	- Decart 7-351 to bottom value, wetwell Athouse House. waser po clear vocator.	7 - 1.9
	-Clean AH-315 probenlyet & solution. Check tok AMESO Forostors Hear: None assund. stray de	own wer
	- Check TA-130 for of yobules; None observed water to clear with collow-green trut.	
1114	T-540/541 level down to 20%. Reduce flow to BTS from tanks for	m 0.3 cm to 0.3 cm
1	[Will be doing an Mh)38 Source well batch extraction overnith +).	
- a	Micho sample technicians on site for MP-OUI ZYhour souls smeeting a	910.
	AMY B. STONY L. of Metro onsite as well for Annual Pretrustment	Site Industral User
	Inspection.	
1432	- STOPMW38N +5 wells proprehation for mw38 source well got ten.	
1446	A let would be broken to the first the first terms of the first terms	RUSTINFLUNTFOR
	0.6 spon to 2-6 pm. 2.5 spon. Mike starting up MW38 source well extracti	`a~ -
1515	- Alants operations good.	Influent Sources and Flow Rates: @ 0535 NBBW - 6-3 gpm
		North End On Site- 12-4gpm
		North End Off-Site – & 6 gpm
		NTES - 0.49 gpm(10R only) MW38 T-540/541 - 0.30 gpm(Source
		well and 38 pumping wells mix)
		COND/NTES T-530- 0-20 gpm(6am-
		1pm daily) MW113 Area – <i>[,</i> 6 7 gpm

Date: Wednesday, May 25, 2022		
Time: 0535	Plant operations good. Start on weekly be maintenance and afficience	- calibrations
0745	Blowdon specations and. Obsered MW38 Source well solar system	stopped extraction
	at 0403 this murning. Will allow batteries to recharge and restart 5	ownerell batch
	extraction this afternoon. T-540 (541 covertly 845%.	
0815	- New TOTE OF Na DH put on line For Changel Sty.	
1100	- Decant T-351 tobottan value. Wetwell altivated. water to clear NOCOLOR	3.00
	-Clean pH-315 proper / Acid Sources. Check The Hunt o For all or Siken; None asserved. Spray Down.	worn
	- Cheek TR 130 For of globules: None of served. water Is clear w/yellow-great HMH.	
	- Refall Polymer Hance w/2 cups or NALCO polymer and Zeogal oxpotable water.	
1220	Citate DVD and floch file of data backup - One Drive automatic date	backery working well.
1500	- LESTART MW 30 Sourcewell Aumsing to T-540/541. TANKS - 48%	
1845	Source well batteries depleted - batch extraction stopped.	
÷		
		Influent Sources and Flow Rates: @ 0748
-		NBBW – 6.7 gpm North End On Site- 12.4 gpm
		North End Off-Site - 6.7 gpm
		RWST – 2.5 gpm NTES – 0.41 gpm(10R only)
		MW38 T-540/541 - 0.2 gpm(Source well and 38 pumping wells mix)
		MW38 N & S- 0 • gpm
		COND/NTES T-530- 6.7 gpm(6am- 1pm daily)
		MW113 Area – 1.7 gpm

Date: Thursday, May 26, 2022

Time: OS4	5 Plant appearations good. Restart privalen's sextraction to T-540 (5211 to displace Muse source
V	will yester in the pipe live to T-540/34/1.
070	O UV-0x shutglewar - Low Flow. P-600 lost prime or PID reaction time too slow. Leaving
	UV-04 off (was planning on putting it on standby while ROST level was low).
080	o J.M B. & Jon S. From Brown Hill is on site to longin vulnarability assessment of control
A1100-100	50 Howare / Marchare. Tom working on weekly / monthly Plants systems cheeks and calculations
	-START Mountly 0.1 moisture procession Run on mash with compressor. MAX speed for 2 Hos.
100	- STOP OIL MOTS ture provention Run on main compressor.
	7 - Place BTS Into Hold and STOP and fower down p-121. Some lesided power bleeding over to p-122 wiring.
	- Disconnect p-122 power with as From old pump and cap off + Iso we + ++
103	5 - BTS OUT OF HOLD. LESTART P-121.
101	5 - Decent 7-351 to bottom value, wet well activated
	- Checked HINR30 for oil or sheens: None observed -sprayed down weir
	- checked Tp-130 for oil globules: None observed - water is not clear w/ yellow-green hue
113	JONS. HAS the information he needs and bas left. Jim staying to work on minor central
	program changes and install win - all 4.21.5 verson - also
120	- Rebooting MMT FTVIEWI a few threes for Wen-all Software installations
1250	- Perform monthly BT3 pA prokes callstations to New 4+ 10 pASTOS
1330	- Calibrated WTP Drobes to 4 - 10 PH STOS P. PHII3.670.315.310.365 Influent Sources and Flow Rates: @
1424	- Suspended plant discharge to calibrate DH740 at LE1740 North End On Site- gpm
1441	- Plant Short down @ 8% LEL during Calibration of LEL740 North End Off-Site - gpm RWST - gpm
1452	NTES - gpm(10R only) MW38 T-540/541 - gpm(Source
145	+ - Resume Normal discharge - Plant and systems calibrations complete, well and 38 pumping wells mix)
	Leaving W. Ox alt average + RUIST & still low at 20%) COND/NTES T-530- gpm(6am-
1510	Suitched Muss N35 to Rust after displacing Must source well weto to T-540/54/MW113 Area - gpm
(3/0	sylvence mussers to was a star or will lack musse source west west to 13 70/39/MINTIS Area - gpm

WM

Date: Friday,	May 27, 2022		
Time: 0550	Plant operations a god		
0623	Restart UV-OX - observe P-601 is again air locked ut startup. Test low flow shutdown of UV-OX - working well. Unit shutde		
0655	Test low flow shutdown of U1-08 - wasking well . Unit shut	Come SE Standard See See	
	TO CONCEST.	1 100 13 3/2	
0755	Blandonna		
0804	OBULL HAR-30 is Full again. Restart UV-OX. P-601 pump our lacked again. Use P-600 isolate P-601 from the system. Observe No ato to the system after doing this P-601 New travelles / with 5 ml 500 lacked again.		
	isolate P-601 from the system. Observe no at the system	affer of aire this.	
	*Calibrate Pixenental GEM 5000 SN & G506894 IN#43410 to 2.5% CHy, Lending 2.6% CH	OR For Ourly Buildings	
	Me thane satety cheeks of fer new GAS frokes montorty.	-	
0906	0906 - Decare T-351 to bottom cabos we twell activated. Water IS Clear Nocator.		
	"Clem pH-315 probe withird Solution, check the Hunk TO for of or Siteen; None of served. 300	try boun wer.	
	- Check TA + 30 For 6/196beles: None Observed, water IS Clear by there - queen tring.	•	
1430	"lestill 673 phosphorus + ANE W/5th OF 751 and 50gal of potable water.		
1500	- Plants operations Gross		
		Influent Sources and Flow Rates: @ 09/5 NBBW - 6.4 gpm	
		North End On Site- 12-5 gpm North End Off-Site - 3-8 gpm	
		RWST - 0.6 gpm	
		NTES - かり gpm(10R only) MW38 T-540/541 - の3 (gpm(Source	
		well and 38 pumping wells mix) MW38 N & S- 2, 2 gpm	
		COND/NTES T-530- o.2 (gpm(6am- 1pm daily)	
		MW113 Area – I, 68 gpm	

5/28/22 0345 Denvie log in. Pient operations good LOWRY WTP OPERATIONS LOG

Date. Sulco	, May 29, 2022	
0800	- Plant operations good.	
0900	- Decont T-351 to bottom valve, wet well activated water is very clear no	color
	· Clean ph-315 probe w/ Acid Solution. Check HMR30 for oil or Sheen: n	one observed. Sprayed we'r
	-cheek TD-130 for oil globules: None observed, water is clear w/ green-yellow	hue
1000	-Plant operations good.	
5/30/22		
0900		
	Sufferday - MEC.	
0645	- Remote Login. Allow. NO UV-0XSINTAOWN.	
2015	- Remove Login, Nortee NTES /MAZ-101 Aump Has stalled. Tremen level commy up and Autovolve open	ning. Flow ou for Now, come to
	Site and see of can get going again.	
5052	- Able to get It Aumorns again. Allow.	
	- RENOR LOSTA. AHOK, WILL SWAP OUT IOR ALMA WESTWEEK.	
	- Sunday - Mec	
0542	- Leceive G.C. I VOC Fault Alarm. Log on Lamorely. 1, 2-OCA @ 763 ppb. Fallse High. Pea	LB Smaller those 9.99 cally atres
	peak. Legat GC Alarm and will take a New TA-730 JAMPle Arthr UV-0x cools gack down.	
0607	-STALT a New TA 730 SAMPLE on GCI.	
0740	- GCI Kesults Good, 1,2-Oct Down to 0,83 ph NO UV-OX LOW Flow SHUT GOVEN THEMY	Influent Sources and Flow Rates: @0850 NBBW - 6.4 gpm
THE COURSE OF TH	- Lemone Cog In Allok	N. END ON-SITE - 12.4 gpm N. END OFF-SITE - 7.6 gpm
	- Monday - MKh	RWST - 0.6 gpm
	- hemme log on. Automatablordown operations axel. UV-0x0K.	NTES - 0.50 gpm COND/NTES T-530 - 0.20 gpm (6AM-1Pi
2200	- lemostly on . Allow.	daily) MW38 – 2, i gpm
		T-540/541 - 0.30 gpm

form Cilbert / mike Calvick OPERATOR(S)_

Date: Tuesday, May 31, 2022				
		- flowers operations Grown. Are Fee - TA-730 110 +740 54 mply		
	0515	-Collect TP-730 weekly Ge/Kab Spit samples and Sym Efficiency checks. Absociated TA.	710+ FP-740 weekly	
		Low Level 1, 4-Ato have & Amoles.		
	0702	Receive UV. 0x shutclowd for low flow. P. 600 lost prime whom swith UV. 0x off dwing blowdown.	ching to sucycle, luve	
C	0800	Polandound aproprient and Rebuild P-601 wet and		
	2904	Rustart UV-OX - observed a lot of air in the system at start	tup hut wo at-	
		ONCE W. DX worm up was completed. Milleworms on weekly ors stones	+ ft-let de te	
(0955	- IX Performance HACH Testring w/ Cab SAHT SAMping AFter 1, 399, 195gel merted:	TAMAR 3 - 757 11 "	
		TP-175AD 260 cg/l; TP-174AD 6500 cg/l; TP-170 27400 cg/l. corrently kunning	7/1030 230472	
	1205	- Account T-351 to his thom vauve, we truell affected water so claw we cake.		
	-Clean pth 315 probe we faced golveron. Chelletek Henre so for at a steen: Nove of served spray four wern - Check TP-130 For 0.7 globuls: None asserved. wenter 3 stightly closely wil yellow or may + 12 + 12.			
1	1220	Rebuil MATETUEEL to seed available the		
Á	145	Reboot UMIFTVIEW 1 to reset available temperary memory, online 127 - Revillats Phosphons +AUR VI6 tox TSP + Gogal or potable unter	-3 -	
	1515	- Plants operations Grand		
	(2,3			
			Influent Sources and Flow Rates: @cs3co NBBW - 6.3 gpm North End On Site- /2.3 gpm North End Off-Site - 6.3 gpm RWST - 0.6 gpm NTES - 0.5 0gpm(10R only) MW38 T-540/541 - 0.3 0gpm(Source well and 38 pumping wells mix) MW38 N & S - 2.1 gpm COND/NTES T-530- 0.2 0gpm(6am-1pm daily) MW113 Area - 1.6 0gpm	

Stontent deline

LOWRY WTP OPERATIONS LOG

Date: Wednesday, June 01, 2022 Time: 0545 Plant operations good. Start on weekly be maintenance and calibrations. Propose 0700 Observe UV-ox when switching into recycle for blandown. P-601 lost prime due to air pocket That is formers in the recycle piping - remove our bleed value and inspect.

OFOR Stop IX system - Take Column 3 (level) off Give and place column 4 in lead. TP-174A post

Moved to post column 4 and restart IX at 0714. Contain to fromble shoot UV-OX recycle system. Ix system total volume treeted reading 1,401,409 gallons. 0815 HAR.30 refilled afto blandows. Restart W.OX, our shed working. 0830 - Decent T-35170 bottom valve. waterell activated, water to clear wo color. -ClempH-315 probe without solveron. Check the Hunt 30 forollor sheer; workedserved. Stray down user - Check TP-130 For oil globules: wore observed, waters glightly cloudy wy cylow-orange fint. Empty spent resin from Column 3 into satellite hazardows waste dum, drum is ~ 2/3 full now. 1045 - Increase p-005 flow to 0.50 you and Aut NTES INTO Divert to T-530 to swapout MAZ-102 pound will shele. 1222 - Return p-005 to 0.20, Am and NTET BACK to wormed to setimens TANK. 1515 - Alamps orenerous Good. Influent Sources and Flow Rates: @ NBBW -North End On Site-North End Off-Site – RWST -NTES gpm(10R only) MW38 T-540/541 gpm(Source well and 38 pumping wells mix) MW38 N & S-COND/NTES T-530gpm(6am-1pm daily) MW113 Area -

Date: Thursday, June 02, 2022

Dute.	maroda	, Julie 02, 2022	
Time:	0650	- Plants operations had	
0700 - Automan Bloodown operations Cood. UV-ox Kept Good Flow During 3 with over.			
	38 3965	- Tom working on weekly Alants 545 toms choices and cultifications tolay	
	0945	- Decent T-351 to bottom valve. Wet well activated. Water is clear no color	
		-clean ph-315 probe with Acid Solution, theck HMR30 for oil or sheens - none observed	- Sprayed down web
		-check Tp-130 for oil abbutes - none observed water is clear with a yellow that	
	1403	Dischage suspended to calibrate pH-740 to 4 and 10 PH STDS. 1412 Resum	e normal discharge
	1413	calibrated plt-310, ph-315, pH365, ph-113, ph-670 probes to Hand 10 PH S	TD3
	1500	weekly plants at systems charks+cali brokens complete	
	1600	- Plants operations Good.	
			Influent Sources and Flow Rates: @ & Sources NBBW - 6 - 4 gpm North End On Site- /2 - 4 gpm North End Off-Site - 8 - 9 gpm
			RWST - から gpm NTES - かけ gpm(10R only) MW38 T-540/541 - のより gpm(Source
			well and 38 pumping wells mix) MW38 N & S— 2.1 gpm
			COND/NTES T-530- 6.24 gpm(6am- 1pm daily) MW113 Area – 1.66 gpm
			well an MW38 CONDA

Operator: Mike Gelwick / Tom GABert

5 Part 1 Part 1

Date: Friday, June 03, 2022 Time: 0620 - Plants operations Good. MW38 North pumping well headed ITS OUT OF Level and STOSPER 2 1745 YESFERDAY EVENING. CLIVETHY Recharging MW38 South well from my & 1. 3 aprin. 2700 - Automatic Blowdawn openetions wind. UV-OX Flow Good During switch over. 0810 - Thereign LivsTs Place to 1. Zegam to Make us Difference of Museworth well being of the because 0915 - Decan+ T-351 to knotten valve, wet well aftered. water Is clear wocodon Clean 14-315 prose w/ Acid solution, check the Hum 80 For oil or Steen: None of general. SAVay Novem weir, - Check TP-130 For oil globules! None asserted, water 25 clear wo color. 1015 - Place 813 true min + Hold and Klish leactors Feed Arpray. 1044 - BT3 out on Hold. 1315 Calibrate and south Auto 54m stor For Monday Muniting supersting Event 5 MART. Theple King Additional Compassion for Metals/molybellower, 1500 - Plank opensions Grast. Influent Sources and Flow Rates: @ ,7625 NBBW - 6.5 gpm North End On Site- 12-4 gpm North End Off-Site - 9.6 gpm RWST - 0.6 gpm NTES - 050 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source well and 38 pumping wells mix)
MW38 X S- 1, 3 gpm COND/NTES T-530- 0.19 gpm(6am-1pm daily)

Operator:	Mike Gelwick	

MW113 Area - 1.68 gpm

Date: S/FIU/	20AY, June 4, 2022	
0630	- Plants operations Good . Go to Chack other 5, 72 5,56ms	245200000
0800	- Restill BIS plus primes tower of 5 th of TSP and stoyed of potusk winter.	A CONTRACTOR OF THE CONTRACTOR
0820	- Decant T-351 to bottom unive. Wetwell activated. water 5 clear Nocolor.	
	- Clem AH-315 protect first solution. Check THE HIRL SO FOR ONTO SIKEN: None asserved. Stray Down were	
	- check TH 430 Foroil globules: None asserved. water Is clear w/ yellow-green trut.	LOS da manda estado de la companya d
OB 30	- Flush p-005 / T-530 pump with potablewater and STOP pump, TANK 2 20% (T-530).	
	- Both Ca: operational with compts	
	- 44 slawers ou. Buy FAFS Coscale	A-AI- MARKET
0930	- Mw 38 50 Northwell lestituted. Decrease lives flow to 0.60 grim.	
1900	- Leanse Log in all OK.	
Sunday, Ju	ne 5, 2022	
0850	- Remote Login, Allot	
2700	- Remok Lagra, Allow.	
		Influent Sources and Flow Rates: @ 0630 NBBW - 6.5 gpm
		N. END ON-SITE - /Z-4 gpm N. END OFF-SITE - 8. 4 gpm
		RWST - 1.72 gpm NTES - 6.48 gpm
		COND/NTES T-530 -0.22 gpm (6AM-1PM daily)
		MW38 - 1.3 gpm
		T-540/541 – 0.31 gpm MW113 Area – 1.67 gpm

Date: Monday, June 06, 2022

Time:	0535	Plant operations good.			
		Reboot HMTFT VIEW 1 to reset temporary file nemocy carles - online	€ 0601.		
	0629	Reboot HMIZ (Mrs bun > 1 marks since lost reboot). Online @ 0631.			
	0740	Blouceum operations good. Mike adding prescrutive to MP-001 composite samp	Le centainer.		
	0800	Start up auto sampler on MP-001 Flow paced sampling. Efflored to	talizer reading		
		255, 900,098 jallon: - Work with Mike in adding Full caut	255, 900,098 jallons. Work with Mike in adding full cautic tote to main buy		
		SUPPH, IOM WORKING ON LINEAS Sledge roll off box and emptys	ing filter press_		
	0950	- begin working on monthly with Early warning signipling and weakly IX system strongling			
	1030	- IX System Per Formance HACH TESUNG WILLED Spirt SAMpling Artor 1, 413, 688 gol treated: TA. 183:	= 300 mg/L ; TP-175A = 410mg/L;		
		TP-1744 0 500 49/1 (Low Range 1454); TP-1702 7500 49/6, CUTTE 4thy System KUMMING 21.66, p.m. All Schungles Alacad The			
		Fridge un mil Atekny Tomorow For Courses,			
		- Segin Flush of mf- cil sample port and check for residual chlorine: NONE Refected, OK to use Helpresound wals			
	1200	- Collect 1st set of Time paced gamb samples DMP-out sumple port for Low Levell, 4- Hioxum, wrte	tIS very clear Nocolor, Alek		
*		Samples on thidge with others.			
	1205	- Decant T-351 to bottom were wetwell activated water to clear No Colon			
		-Clean p. 4-315 probe without solvetion. Check the Hund 30 For oil or sider. were existenced, spray sous a coster.			
<u> </u>		- Cheek TA-130 For o. Aglobules: None observed waters clean infyellow-yearn tint.			
		- By in Fligh out of ood summer port and cheletor Regident chlorine; Nowe sexcept water to ve	ry Clear No Ca har		
	1600	-Collect 2nd setof time paced goods samples From MADON SAMPLE Port For Low Lavel 14-AVOXANE. Alace	Influent Sources and Flow Rates: @ 6952 NBBW – 6.5 gpm		
		samples In fritze with others	North End On Site- 12.4 gpm North End Off-Site – 4.0 gpm		
	1605	- Plants operations Good. Autosumpler on traver. ot.	RWST – O⊶6gpm		
ļ	1945	Begin MP-101 port Flush and check for restduced chlusine - none detend.	NTES - 0.4¶gpm(10R only) MW38 T-540/541 - 6. 3 gpm(Source		
	1800	Collect 3rd set of time paced grab samples for lowlevel 1, 4-Dioxanc.	well and 38 pumping wells mix) MW38 N & S- Z.2 gpm		
		Sample is very clear, no color. Place sample in the frage with others.	COND/NTES T-530- O.O gpm(Garrie)		
	2340	Begin MP-001 post Flush and check for restderal chloring - Move detected	MW113 Area - 1. 7 gpm		

Operator: Mike Gelwick / Chris Carlson / Tom Gilburt

Date: Tueso	lay, June 07,2022		
0000	Collect 4th set of time paced grab samples for low level 1, 4. Dio	xanc. Sample is very	
	Collect 4th set of time paced grab samples for low level 1,4. Dioxane. Sample is very clear, NO color. Place sample in the fridge with others.		
0325	- Plants operanous Good.		
0350	"begin from of MP-0015 Angle port and check for Registral Chilorine; Nove Jetector, wester Is very clear a	vo cular.	
0400	- collect 5th set ox +, me puced goe's samples from MP-coll sample port For Low Level 1, 4-Broxance P	Place spandle gar Fridge with others	
0415	-working on weekly BTS sampling. STALT Efficiency Checks.		
0500	- collect TP-730 Gc/lab split strapes and TP-710+ TP-740 weekly Low-Level 1, 4-10.	Exame Jeffred 6-9.	
€220	-warking on BTS Frold Redrays taking		
0750	- Begin thishor Mp out sample port and check for lexitual chlorine; Note Defected, water Is very clear	~ Nocolor	
0800	-collect 6th/final set of time paced grab stroples from Mp-od sample port for Lowland 1, 4-0: Okane, Place strople by Forthe with orthing		
	- 5 TOP AN to sample and process composize sample of Grently strong and checking pH value. pH value is 1.9150. UK IS Il Bottle		
	- Total Epphone 2 255, 947, 642 gal. Antal of 47,544 gal treated During siting to partod. PACK All sitingles on the for		
	courier Present today		
0930	- Delant \$ 7-351 to bottom valve. wetwell activated. water B clear Nocation Clan 1-352 y STrainer		
	- Clem pH-315 prote W/Acid Solution. Cheek THE HANGO For oil or stress. Worse asserved. Spray boun wer.		
	- Check TA + 30 For oily lobules: None of seved. water Is clear w/ yallow - queen 1701.		
	- A-352 Gorny again, Allon.		
1030	Stop MW38N & s extraction to prepare for MWB4 source well batch extraction	Influent Courses and Flow Potos: @ 073.6	
	Switch MW38 from direct HMR.30; reflerent to T.540/54 ((levels @ 241.) 26%)	Influent Sources and Flow Rates: @0315 NBBW - 6.5 gpm	
1100	Shart MW38 source well batch extraction (Note: New batterness installed 6/6/22).	N. END ON-SITE – 12.4 gpm N. END OFF-SITE – 8.9 gpm	
375	-Plants o Perations Cool	RWST - 06 gpm NTES - 048gpm	
		COND/NTES T-530 – & gpm (6AM-1PM daily)	
		MW38 – ≥.1 gpm T-540/541 – •.3 • gpm	
		MW113 Area – /.67 gpm	

Date: Wednesday, June 08, 2022	
Time: 0550 Plant operations goal. MW38 source well batch extraction working well, T.	540 /541 e 62%. WOR
on welkly GC maintenance and calibrations	
0624 Receive UV-Ox worning alarm - peroxide Flow low. Internal pres	some high alorn on
1-650. Air in the system has caused the alarm - purge air bubble	5 from the pump
V Ststem - Peroxide Flow Normal & 0630, P-650 working well again.	enterre of GC maint.
0745 Blowdown operations good. Refil physhin tank with 55 gallows punct	c + 5.5165TSP.
0020 Start Filtopress on T-351 (IN 5445C1). Clum the HMR.30 well and	PH probe - No oil or
Sheen observed in the HMR-30. Check TP-130 for oil globules - N	one observed Water
V is clear, light yellow (green	
1040 Filterness full.	
1050 Weekly Flash & DVD of wordata created. One drive backup working	vetl.
6. 1 6.11.	
1520 Shutdown MUBE source and batch extraction. T. 540/54/1 @ 78	1. 280%.
1520 Shutdown MUBE source will batch extraction. T. 540/54/ @ 78 1550 Stat MWBE & source will batch extraction. T. 540/54/ @ 78	atr in the conveyance
V 1424 to 1-390/69/-	
2145 Remotely switch Musen's from T. 540/541 to RWSTs after 650 gas the source well water in the conveyance line to T. 540/541. Plant	llows purped to displace
the source well water in the conveyance line to T. 540/541. Plant	operations good.
	,
	Influent Sources and Flow Rates: 0600
	NBBW - 6.6GPM
	N. END ON-SITE – 12.5GPM N. END OFF-SITE – 8.8GPM
	RWST – 2.0GPM NTES – 0.48GPM
	COND/NTES T-530 - 0.0GPM
	MW38 – 4.8GPM (source well to T540/541) T-540/541 – 0.3GPM
	MW113 IX SYSTEM - 1.7GPM OTHER - NA
	OTTEN TOTAL

Date: Thursday, June 09, 2022	
Time: 0520 Plant operations go	od.
0540 Reduce RWST INFlue	of From 2.0 gen to 0.6 gen and switch MW38 NIS From RWSTS to dicce
HALR-30 INFLUENT, RE	duce T-540/541 influent to BTS while trush MW38 source well water
V is present so BTS	can adjust to it. Propose for wedly systems checks and calibrations.
0600 Clean the HMR.30 1	us and PH probe - No oil or show observed is the HMR.30. Chuck
TP-130 For oil glob	ules - Nove observed. Water is slightly cloudy light yellow /green.
0740 Blowlow operation	good. Startwelly system checks with Ton.
1053 Start discharge Ju	spension for pH-740 calibration
1103 plt-740 calibration	spension for pH-740 calibration completed - resume normal discharge Continue on 7H cabbrations at 310, pH-365.
V pH-113, pH-1670, pH-	310 pll·315 ; plf-365.
1138 pla calibrations compl	ted - All Okay.
1525 Phant operations good.	
	Influent Sources and Flow Rates: 0600 NBBW – 6.6GPM
	N. END ON-SITE – 12.5GPM N. END OFF-SITE – 8.7GPM
	RWST - 0.6GPM NTES - 0.49GPM
	COND/NTES T-530 – 0.0GPM MW38 – 1.9GPM
	T-540/541 – 0.2GPM MW113 IX SYSTEM – 1.7GPM
	OTHER - NA

OPERATOR(S) Chris Carlson / Tom Gilbert

Date: Friday, Ju	ıne 10, 2022	
Time: 0600	Plant operations good. Continue to troubleshoot MPZ-11 transducer - not the transcluser, sue the PCC circuit is damaged (sending 16 V DC loop, should be 24 V DC).	spea
	the PLC circuit is damaged (sending 16 VDC loop, should be 24 VDC).	
0745	Blandows operations good.	
0755	Rebot HMIFTVIEW 1 to reset available beyonery memory, online 0802.	
0901	Polant HMIFTVIEW 1 to reset available benjorary memory, online 0802. Observe HMIFTVIEW 1 is Failing to send Heartheat update to the PLC. Reboot again.	\dashv
0906	ON the - Heartbeat working.	
1040	ON twe - Heartheat working. Clear the HMR. 30 were and pH probe - No oil or sheen observed in the HMR. 30. Check TP-130	
	AT OIL ALBULES - NONE OBSEIVED	
1200	Plant gerations good.	
		-
		\dashv
		_
		\dashv
	Influent Sources and Flow Rates: 0615 NBBW – 6.6GPM	
	N. END ON-SITE – 12.5GPM	
	N. END OFF-SITE – 9.3GPM RWST – 0.6GPM	
	NTES - 0.49GPM COND/NTES T-530 - 0.0GPM	
	MW38 – 1.7GPM T-540/541 – 0.2GPM	
	MW113 IX SYSTEM – 1.7GPM OTHER – NA	
	OTHER - NA	

LOWRI WIF OFERATIONS LOG	
Date: Saturday, June 11, 2022	
0620 On site for weekend system checks. Plant operations good. Refil	1 phosphorus task with
4 5 gallons potable water + 4.5 lbs TSP.	•
0645 9700 Obsove Chen the HMR-30 weir and pH probe - No oil or show ob:	seved IN the HAVR. 30.
Check TP. 130 For oil globules - none observed. Water is very al	ear, light gran/ yellow.
0700 Observe latest GC result for TP. 3350 indicating the BTS h	as actimized to the fiesh
MW38 source well water Set P-006 (T-540/541/ + BTS) at	60.350m.
0945 Plant operations good.	
6/12/22 0635 Check plant remotely - All olay.	
1725 Chark plant remotely - All okay.	
	ALIANA AND AND AND AND AND AND AND AND AND
	2.00
	Influent Sources and Flow Rates: @ 0643 NBBW - 6.6 gpm
	N. END ON-SITE - 12.5 gpm N. END OFF-SITE - 8.7 gpm
	RWST - 0.6 gpm
	NTES - O. Wgpm COND/NTES T-530 - O O gpm (6AM-TPM
	MW38 – / 8 gpm
	T-540/541 - Q.2 gpm
	MVV113 Area – (. 2 gpm

Date: Monday,	une 13, 2022		
Time: 0550	Plant operations good.		
0628	Reboot HMIFT VIEW 1 to reset quailable temporary memory 0633 online,		
0645	Refill polymer tank with 200 callons potable water + Zever pulymer. Clean the HUR-30 weir and		
	Reboot HMIFT VIEW to reset available temporary memory, 0633 online. Refill polymer temp with 2005 allow potable water & Zeypr polymer. Clean the HUR.30 weir and pH probe - no oil or sheem observed in the HMR.30. Check TP-130 for oil globules - none observed.		
	Water is very clear, light green / yellow.		
0745	Blouchours operations good.		
1000	Tyler Tippit from Piper Electric on site to asses MW170-EW1& P.001 VFD's/		
¥	BACKUP VFD		
1130	Blowchousi operations good. Tyler Tippit from Piper Electric on site to asses MW170. EURE P.001 VFD's/ Backup VFD. Tyler is going to look up a second / possibly a third backup VFD for them, Tyler has left the site.		
↓	Tyler has lift the site.		
1500	Plant grenetim good. End.		
		Influent Sources and Flow Rates: 0602 NBBW – 6.7GPM	
		N. END ON-SITE – 12.5GPM N. END OFF-SITE – 8.8GPM	
		RWST - 0.6GPM NTES - 0.50GPM	
		COND/NTES T-530 – 0.0GPM MW38 – 1.7GPM	
		T-540/541 – 0.3GPM	
		MW113 IX SYSTEM - 1.7GPM OTHER - NA	

te: Tu <mark>esday, June 14, 202</mark>			
me: 0520 Plant open	ations good. Start on weekly plant Effec	servey checks (sampling ? UV. OX perform	
Jampling.	-		
0740 Blowdow	s operations good.		
0900 Ton work	ins on weekly BTS performance sampling.		
0045 Start 51	to occes and T-351 (instance 1). Clear the HM	12.80 were and off probe - No oil or show	
deserved	Tom working on weekly BTS performance sampling. 5 Start Filter press on T-351 (instage 1). Clear the HMR. BO we're and pH probe - No oil or she observed in the HMR. 30. Check TP-130 for oil globuler - None observed. Water is very		
1/ Olesa I	ight yellow/ 5 ran.		
1 Ame T	A distributed To Des Forman Control 1	Had readises	
1000 I am 3 tarting welly LX pertormale Bampling (Tach 1200. NS).			
Q 2.70	1000 Tom 3 to tirs weekly Ix performence sampling / Hack readings. 1010 After 1,432,761 yearled TP-183 @ 200 upl ; TP-175A @ 240 upl ; TP-174/ @@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx		
(4/600	is to the sound of the same is a same in the same in t		
	in fr Hupris (in 13052 4).		
1646 Plant op	restor) gurst. Ext.		
		Influent Sources and Flow Rates: 0625	
		NBBW – 6.7GPM N. END ON-SITE – 12.6GPM	
		N. END OFF-SITE - 8.9GPM	
		RWST – 0.6GPM NTES – 0.49GPM	
		COND/NTES T-530 - 0.0GPM MW38 - 1.7GPM	
		T-540/541 - 0.3GPM	
		MW113 IX SYSTEM – 1.7GPM OTHER – NA	

OPERATOR(S) Chris Carlson Tom Gilbert

Date: Wednesday, June 15, 2022			
Time: 0540 PL	ANT operations okay - received a UV-OX WARNING alarm ON the wa	by to the site. Peroxide	
51	flow low - observe P.680 has a local warning for pressure high (air from peroxide bubbles		
1 1/20	as built up and Dum has stopped for warning. Puto nates bleed to	rogramed is wable	
to	to overide the local purps warning / stop. Will look into having an air purse cycle		
to	to overide the local purps warning / stop. Will look into having an air purse cycle to occur at least once per day to prevent buildupletur it becomes an internal		
1 104	Duno Shutrans. Able to anally get air purgla manually and vious or personal		
1	reflered to Normal. Itact on well to be maintifued and carrelations.		
0740 BL	oudours operations good. Refill phosphorus tank with 60 gallows potes	ble weeter + 6165 TSP.	
Re	Restort Filtopress (in stage 4). Unload chanical delivery - proxide ? HCL total only		
O740 Blowdown operations good. Refill phosphorus fame with 60 gallows potable waster + 6165 TSP. Restort Filtopress (in stage 4). Unload chemical delivery - proxide it HCL total only Countie on back order (elevinery schulded for later this need). Contain and GC contactions.			
0915 Ac	0915 Add 165 gallow of peruxide to malabay supply		
1500 SI	1500 Stantown filtrocess (in class 4)		
1515 CL	1515 Clur the HAVE. 30 weir and ptt probe- no viler sheer observed is the HAVE-30. Check TP-130 for oil globules - none observed. Water is very clear, light yesterned		
C	healt TP-130 for ail globules - was observed. Water is very a	lear, light yellow	
V	ren.		
1600 P	and operations good Find.		
		Influent Sources and Flow Rates: 0806 NBBW – 6.6GPM	
		N. END ON-SITE – 12.5GPM	
		N. END OFF-SITE – 8.8GPM RWST – 0.6GPM	
		NTES – 0.49GPM COND/NTES T-530 – 0.0GPM	
		MW38 – 0.9GPM T-540/541 – 0.3GPM	
		MW113 IX SYSTEM - 1.7GPM OTHER - NA	

Date: Thursday,	June 16, 2022		
Time: 0525	Plant operations good.		
0618	Receive GC TP750 Fault alarm - UV-at in scycle, GCI has posted a	false high 1,1-DCE	
	result of 1360.73 ugll - Result put is smaller than calkration perk	of 9.9/ ug/L. Dolument	
V V	result of 1360.73 ug/L - Result puk is smaller than calkration perk forthe False calculation error and take UV.OX out of recycle	1	
0730	Start Filter Dress on T-351 (IN 54Age 4).		
0745	Blowdown operations good. Tom starting on welly cutp systems check- Decant T-351 to bottom valve, wet well activated. Water is clear of no col	les,	
1000	- Decant T-351 to bottom valve, wet we'll activated. Water is clear of no col	6 (
	-cleaned ph-315 probe with acid solution . Check HMR-30 for oil or streens - mone observ	sed -Sproyed down weir	
V	-checked Tp-130 for oil globules - none observed. Water is clear with a yellow	tint	
14130	Place a select 22 transferencias for A+740 calibrations		
1441	pH-740 Calibration completed. Resume Normal discharge. Continue on pH calibrations at		
V	011-670, 113, 310, 315 } 365		
1510	SH calibrations completed - All Okay. Note: follow up sample on GCI result read 6.89 ugl for		
	1,1-000		
530	Plant operators good End.		
-			
		Influent Sources and Flow Rates: 0535	
		NBBW - 6.6GPM N. END ON-SITE - 12.5GPM	
		N. END OFF-SITE – 8.7GPM RWST – 0.6GPM	
***************************************		NTES - 0.49GPM COND/NTES T-530 - 0.0GPM	
		MW38 – 2.6GPM T-540/541 – 0.3GPM	
		MW113 IX SYSTEM - 1.7GPM	
		OTHER - NA	

OPERATOR(S) Chris Carlson Ton Gilbert

Date: Friday, June 17, 2022		
Time: 0525 Plant operation, good		
0645 Clear the HMR.30 wet- and pHporbe- no oil or sheet observed in for oil globules - None observed. Water is very clear, light 500	the HMR:30. Check TP-130	
for oil globules - None observed. Water's very clear, light gre	en/xellow.	
0743 Blowdown operations good.		
0845 Vartex Doors on site to evaluate Causti bay aloor mechanisis	Thinks be can fix today	
V after going to pickup parts.		
0900 EDR at away? Croperlest working on putable water value that has a lesk. Cracked reducing		
Fitting under the Air/VAC VALUE Tesking aswell. They will shortday the water for a few		
MANUTER to change out sittings and local isolation valve under the Arr/Vac that will also be replaced. Chose: Eccv ming trouble with isolation of the system - unable to		
also be replaced. (Note: ECCV ming trouble with isolation of the system - Unable to		
isolate properly today and needs more staff available in case problem arise). Lask repair moved to later when ELCV has been welthird and has staff on hand.		
to later when ELCV has been welthird and has staff on hand.		
1330 Ubrtex completed repairs. Plant operations good. End.		
	Influent Sources and Flow Rates: 0600	
	NBBW – 6.6GPM N. END ON-SITE – 12.6GPM	
	N. END OFF-SITE - 8.7GPM	
	RWST – 0.6GPM NTES – 0.49GPM	
	COND/NTES T-530 – 0.0GPM MW38 – 1.7GPM	
	T-540/541 - 0.3GPM	
	MW113 IX SYSTEM - 1.6GPM OTHER - NA	

Date: Saturday, June 18, 2027 O710 ON site for weekend systems check - Plant this just dropped with bloodown - All Okay Brellwash PDU while in blowdown. A pressur improved from 4 psi to 1 psi. O748 Blowdown operations good. Clean the HMR. 30 webs and pt pale - no oil or sheen observed in the HMR. 30. Check TP-130 for oil globales - Mre observed. Water is a Clear, light green/yellow. O805 Resill phosphorus tank with 48 gallors of potable water + 4.816s TSP. O915 Decant T-35! Dottom value, wet well activated. Water is Clear, No color. O930 Plant operations good. 6/19/122066 Check plant remotely - All okay.
Backwarh PDU while an blowdown. A pressur improved from 4 psi to 1 psi. 0748 Blowdown operations good. Clean the HMR 30 weir and pt pale - no oil or streen bloserved in the HMR.30. Check TP-130 for oil globales - mre observed. Water is a Clear, 1 jht green/yellow. 0805 Refill phosphosus tank with 46 gallons of potable water + 4.616s TSP. 0915 Decant T-351 bottom value, wet well activated. Water is Clear, No color- 0930 Plantoperations good. 6 19 22 0615 Check plant remotely - All okay.
OFFICE Blowdown operations good. Clean the HMR. 30 weis and pH pale - no oil or sheen blosseved in the HMR. 30. Check TP-130 for oil globales - Mre observed. Water is a clear, light green/yellow. OBOS REFIL phosphorm task with 48 gallors of potable water + 4.8165 TSP. O915 Decant T-351 bottom value, wet well activated. Water is clear, No color-0930 Plantoperations good. 6/19/220615 Check plant remotely - All okay.
OFFICE Blowdown operations good. Clean the HMR. 30 weis and pH pale - no oil or sheen plasered in the HMR. 30. Check TP-130 for oil globales - Mre observed. Water is a clear, light green/yellow. OBOS REFIL phosphorm task with 48 gallors of potable water + 4.8165 TSP. O915 Decent T-351 bottom value, wet well activated. Water is clear, No color-0930 Plantoperations good. 6/19/22065 Check plant remotely - All okay.
OBOS Refill phosphorus tack with 48 gallows of potable water + 4.8165 TSP. O915 Decant T-351 bottom value, wet well activated. Water's Clear, No color- 0930 Plantoperations good. 6/19/22065 Check plant remotely - All okay.
Clear, light green/yellow. OBOS Refill phosphorus tank with 48 gallows of potable water + 4.8165 TSP. O915 Decant T-351 bottom value, wet well activated. Water's Clear, No color- O930 Plantoperations good. 6/19/22065 Check plant remotely - All okay.
OBOS Refill phosphorus tack with 48 gallows of potable water + 4.8165 TSP. O915 Decant T-351 bottom value, wet well activated. Water's Clear, No color- O930 Plantoperations good. 6/19/220615 Check plant remotely - All okay.
6/19/220615 Chack plant remotely - All okay.
6/19/220615 Chack plant remotely - All okay.
6/19/22065 Chack plant remotely - All okay.
1810 Theen Plant Remotery - MITORAY.
Influent Sources and Flow Rates: @@
NBBW - 6.6 gpm N. END ON-SITE -12.6 gpm
NBBW - 6.6 gpm N. END ON-SITE - 12.6 gpm N. END OFF-SITE - 89 gpm RWST - 0.6 gpm
NIES-0.40 gpm
COND/NTES T-530 −
MW38 = 1.6 gpm T-540/541 = 0.26 gpm
MW113 Area – 1.7 gpm

Date: Monday, June 20, 2022				
Time: 0620 Plant operations good.				
0710 Clean the Haye-30 well and pH pribe - No oil or sheen observed 4 m	0710 Clean the HOLE-30 well and PH probe- No oil or show observed in the HMR. 30. Chack TP-130 for			
V oil globules - none observed. Water is very clear, light yel	Low / 5 read-			
0740 Blowlown operations appl.				
1100 Decant T-351 bottom valve, wet well activated. Water is a	lear, no color.			
V Check potw discharge like voults / lask detection ports and efficient	use at COA Manhole All Okay.			
1330 Test run RWST generator and test RWST containment his	sh float switch - both good.			
V Check N. T.ES. Schoolory containment sump - Dry elb.	07.			
1445 Plant operations good. End.				
				8008 07
				Influent Sources and Flow Rates: 0630
	NBBW - 6.6GPM N. END ON-SITE - 12.6GPM			
	N. END OFF-SITE - 8.9GPM			
	RWST – 0.6GPM NTES – 0.48GPM			
	COND/NTES T-530 – 0.0GPM MW38 – 1.8GPM			
	T-540/541 - 0.3GPM MW113 IX SYSTEM - 1.6GPM			
	OTHER - NA			

Date: Tuesday,	June 21, 2022		
Time: 0545	Plant operations good. Work on weekly plant effectioney BTS performance sampling.		
0740	Blankown aperations and		
0800	Perform weekly I'm Exchange system Hach reading / lab splits. System flow rate at		
	Perform weekly For Exchange system Hack reading / lab splits. System flow rate at 1.665pm; Total volume treated 1.449, ZZI gallons. TP-183 @ 220us/L; TP-1751 @ 240us/L;		
<u> </u>	1P-174Ae 290 ms/2 and TP-170 @ +400 mg/L.		
	Unload three caustic totes from Univar truck.		
1030	Decant T-351 bottom value, wet well activated. Waterir clear, No color, Clean		
	Decant T-351 bottom value, wet well activated. Waterire class, No color, Class the HMR-30 weir and PH probe - No oil or sheet a begreed in the HMR-30. Check		
<u> </u>	TP-130 for oil globules - NONE observed. Water is Very clear, light yeller I green. Work or wrenkly BTS FEELD readings. Note: Kevin with BiB HVAC on site to mustall		
Mao	Work or weekly BTS FEELD readings. Note: Kevin with BiB HVAC on site to install		
	replacement fax on conclenser of Build#1 effice Ac/Hartler Unit.		
1510	AE repairs clone Kevin leuring.		
1550	Cheek plant operations - All okay.		
1600	ENU,		
		Influent Sources and Flow Rates: 0747 NBBW – 6.6GPM	
		N. END ON-SITE – 12.5GPM N. END OFF-SITE – 8.6GPM	
		RWST - 0.6GPM NTES - 0.48GPM	
		COND/NTES T-530 - 0.0GPM MW38 - 1.7GPM	
		T-540/541 – 0.3GPM MW113 IX SYSTEM – 1.7GPM	
		OTHER - NA	

	y, June 22, 2022	
Time: 0545	Plant operations good Observe P-006 is at 100% but maitaining setpoint. Oc maintenance and calibrations. Refill phosphown tank with 60g	Stort of weekly
	GC maintenance and calibrations. Refill phosphow tank with 60g	allow potable water +
	6 lbs TSP.	
0600	Shutdown P-006 to Clean y-strainer.	
0620	Reboot HMIFTVIEW I to reset temporary memory file space; online 06	25.
0648	P-006 y-84rair 3 Feed piping cleaned / flushed, was very clogged wit	the the iron based bio
	growth (warner temps heating up since well mater to T-540 (501)), All clar now.
₩	WORK ON BTS OUR medica solids.	
0800	BTS Frell reading completed. Go to cooperles F blue & gurney to i	solated to partable
	water so at Tuac value & piping can be replaced. Note: Ap	half crow over the
	wellered got asphalt in the value box of the isolation value - ?	took a while to
and the second s	stop water because ECCV had to bring out a small vacue	un trailer to clan
	out the box - BR's first afterpt at the organ distry work	n - will need to
	replace the entire tee assembly - water may be off until	NZPM - Let W.M
<u> </u>	KNOW. Continue on GC calibrations call weekly plant date	a backup.
1150	Clear the Home 30 weir and pt probe - No oil or sheen a bacrued in the to	MAR. 30. Check TP-130
1	for oil globules - Nore observed water is very clear light yellow / 9 12	en .
1250	Potable water restarted after repair is completed. Kunning pota	able on the grown
<u> </u>	to work the our out of the system (sent to grassy area).	Influent Sources and Flow Rates: 0555
1330	Flushing stopped so live can pressurize to test assembly - All UKay	NBBW - 6.6GPM N. END ON-SITE - 12.6GPM
	swine Flushing	N. END OFF-SITE – 8.7GPM RWST – 0.6GPM
1430	Flushing completed 2,400 gallows of potable used.	NTES - 0.48GPM COND/NTES T-530 - 0.0GPM
1530	Plant operation, good. End.	MW38 - 0.9GPM
		T-540/541 - 0.3GPM MW113 IX SYSTEM - 1.7GPM
		OTHER - NA

Date: Thursday,	June 23, 2022		
Time: 0500	Plant operations and. Decant T-351 bottom value, wet well a	ectivated. Water is	
	Plant operations good. Decant T-351 bottom value, wet well activated. Water is clear, NO color. Clear the HMR.30 weir and PH probe-No oil or shan observed in		
	the HMR-30. Check TP-130 For oil globuler - Nove observed.	Water is very clear,	
\bigvee	light yellow / green. Start weekly systems checks and co		
0745	Bloudain operations good		
1045	Place discharge IN timed suspension for LEC. 740 calibration) ,	
1057	Plant shutchers when LEL value got to 8%. when 50%. LEL calibration gas was		
	Place discharge IN timed suspension for LEC. 740 calibration. Plant shutchers when LEL value got to 8%. when 50%. LEL calibration gas was applied. LEL-740 calibration completed at 1104-All okay.		
1105	Calibrate pH-740 while plant was off.		
1110	5 Calibrate pH-740 while plant was off. 0 pH-740 calibration completed. Restart plant and discharge. Take UV-04 out		
1 1/	106 611 11614		
1115	5 Continue on pH calibration of pH-113,670,310,315 3,365.		
1145	5 9H calibrations completed - All Okay-		
	15 Plant operations good Fol.		
X			
1000000		Influent Sources and Flow Rates: 0620	
		NBBW – 6.7GPM N. END ON-SITE – 12.6GPM	
		N. END OFF-SITE - 8.8GPM	
		RWST – 0.6GPM NTES – 0.47GPM	
		COND/NTES T-530 – 0.0GPM MW38 – 0.9GPM	
		T-540/541 - 0.3GPM MW113 IX SYSTEM - 1.6GPM	
		OTHER - NA	
·			

Date: Friday, Ju		
Time: 0545	Plant operations good. Clean the HMR.30 were and pH probe observed in the HMR.30. Check TP-130 For Oil globules - No	- No oil or show
	observed in the HMR.30. Check TP-136 For Oil globules - No	we observed. Water
V	is very clear, light yellow/ green.	
0740	Bloudour operations good.	
1 300	Plant operations good	
1320	Leave for the day.	
	Return to site, internet monitor indicating the internet is down. Reboot 1	NAN'S Fortigate box
	Internet sesapred.	
1930	Plantaperations and.	
	•	
•		
	(a)	
		Influent Sources and Flow Rates: 0626 NBBW – 6.7GPM
**************************************		N. END ON-SITE – 12.6GPM N. END OFF-SITE – 8.7GPM
		RWST - 0.6GPM NTES - 0.47GPM
		COND/NTES T-530 - 0.0GPM
		MW38 – 1.8GPM T-540/541 – 0.3GPM
		MW113 IX SYSTEM - 1.7GPM OTHER - NA

OPERATOR(S) Chris Carlson

Date: JUNC 25, 2022		
1400 Plant operation	e and	
	1 to bottom valve. Wet well active	vated. Water is clear,
10 co co co	a de el alda la como alem	vod 120tos so vosia
	o for on plopules more obser	ved Water is very
Clear with	315 probe with acid soluti	CHOCK HMR-30
A OIL O	Shoot : more absorbed Shrall	OUSON MAIN
1150 Both GC'S	operational within Imuts	
All Blows	ORAL .	
Prosphorus	tent @ 50001. Adoled 5# TS	P and 50,0pl water.
1320 Plant Oper		2
10 0745 Check plant com	stely-Allokax.	
1/21/2 OULE OF THE	whely - All okay.	***************************************
1715 Check plant rem 6/26/22 04/45 Check plant of 1530 Check plant remo	Later All alay	
1330 CHELL BURITERIO	rely-nit okay.	
		7
		Influent Sources and Flow Rates: @ 1190
		N. END ON-SITE - 12,5 gpm N. END OFF-SITE - 8,9 gpm
		RWST - O, b gpm NTES - O, b gpm COND/NTES T-530 - O, Q gpm (6AM-1PM
		daily)
		MW38 - 1.8 gpm T-540/541 - 0.3 gpm
		MW113 Area – 1.7 gpm

OPERATOR(S) Manuela Seewald / Chris Carlow

Date: Monday, June 27, 2022

Time:	0600	Plant operations good.	
	0630	Reboot HMIFTUIEWI to reset available temporary memory, unline 063	7
	0745	Blowdown operations good.	•
		Add one full tote of caustic to main bay supply.	
	0940	- Decant T-35/ Bottom valver wet well activated. water 15 Clear Nocobon	15
		- Clean pH-315 probe where solveron Check the HMR JOFor 0.70- steen : Nove of see	well 3 pray Down wer.
		- Check TP-130 for oil globules ! None of served. water is very char w/Light yellow gree	
	1610	- Plants operations Good.	
2			
			N SHEETS STREET
			8
		8	
			Influent Sources and Flow Rates: @ @ @ Ros NBBW – 6.6 gpm
			North End On Site- 12.5 gpm
			North End Off-Site – 9.7 gpm RWST – 0.6 gpm
			NTES - 0.44 gpm(10R only) MW38 T-540/541 - 0.3 gpm(Source
			well and 38 pumping wells mix) MW38 N & S- 1.7 gpm
			COND/NTES T-530- 0.0 gpm(Sam
			1pm daily) MW113 Area – 1.7 gpm

Date: Tuesday, June 28, 2022

Time:	0615	- Plunts operations Good.	
	0625	- Collect weekly TP-730 GC/Lab Sphit samples and Also collect weekly TP-740+TP710 Low	Level 14- Droxane and STHET
		REFERENCY Checks, Working on \$75 weekly 84mplong + Field Feating today.	
	1000	-IX System Performance HACH TESTING W/Lab Split strapes APTER 1466166gal Treated: TP-1	(85 -300 41/K;
		TP-175A 2350 ug/k; TP-174A2470 ug/k; TP-17027200 ug/l. System currently RUAN, xy	01.66 gpm.
	1040	- Decant T-351 to bettom valve. Wet well activated. Weter IJ clear No color.	-
		-Clean pH 315 probe w/ Acid solveron. Check THE HOME 30 For Off or Steen: None of served. Stray down .	JE17
		- Check TP-130 For 01 globules: NONE observal, water 33 very clean w/ light yothow green strot.	
		-le Call polymer TANK w/2 cups of NALCO polymer and 200 gal or potable water.	
	1100	Shut foun MW38N'S extraction. Energy RWST inflact from	0.6, pm to 2.0 spm.
	1120	Switch MN38 from direct HML 30 ynfluent to T-540/541 (levels at	19% (23%,)
	ALCOHOL STANDARD	Start MW38 source well batch extraction.	
	1600	- Plants Operations Good	
		Note: Observed air in the potable water supply still present - pu	uge another 400 gallows
		Note: Observed air in the potable water supply still present - pu of potable water to remove some of it (putable sent out side of accord.	plant into a grassy
		ovica.	* 20
			Influent Sources and Flow Rates: @ 6635
			NBBW - 6.7 gpm
			North End On Site- /3.5 gpm North End Off-Site - 8.7 gpm
			RWST - 0.6 gpm NTES - 0.47 gpm(10R only)
			MW38 T-540/541 - o.29 gpm(Source well and 38 pumping wells mix)
<u></u>			MW38 N & S- (• 7 gpm
			COND/NTES T-530- OO gpm(Sam 1pm dail y)
			MW113 Area - 1.65 gpm

0.14" rain 7.M.

LOWRY WTP OPERATIONS LOG

Date: Wednesday, June 29, 2022 Time: 0510 Plant operations good. Source well botch extraction working well, T-540/541 @ 46%. Refill phosphorus tank with 45 gallows potable unter and 4.516, TSP. 0745 Blondows operations good. OSDO Observe All of the NTES transducer are producedly pegging out - locks book like the PLC is having a problem - will power cycle to see if that belos to stabilize values. 0810 - Decem 7-351 to bottom wave, wet well actioned. warm to clear wo when - Clean p.H-315 probe without solution. Check the Hum 30 For of or other . None observed. Spray some cover. - Check TB-130 For 0il ylokules: None observed. water 53 very clear white yellow-green tout 1615 - Plants operations Good, 1938 - Plant SHUTDOWN Aveto power loss. Power lestoved as I Arrived on site, Lightness and T- Storms on Area, May Have been Kason, Reset Aluma and Folded Motors. P-3301 A Detve Burnedout, SHUT OFF and will Kun A-3301 today 4+ control can Leplace Drive. 2012 - Reboot HMIZ. unable to Level Kemstely 2055 aBSI - Lebout HMIZ agoun, Hearthest Harm wouldn't clear. 2100 0900 - LESTART Plant, UV-OX In Lecycle. 2112 0412 - UV-Ox 113 charging. 2122 0022 - Plants operations back to wormal. Influent Sources and Flow Rates: @0655 NBBW - 6.7 gpm North End On Site- 12.5 gpm North End Off-Site - 8.7 gpm RWST - 2.0 gpm NTES - 0.47 gpm(10R only) MW38 T-540/541 -0-33 gpm(Source well and 38 pumping wells mix) MW38 N & 8 3.5 gpm source 1 127540541 COND/NTES T-530- OO gpm(6am-1pm daily) MW113 Area - 1,65 gpm

0.03" PM


LOWRY WTP OPERATIONS LOG

Date: Thursday, June 30, 2022

Time:	0530	ON site - observe UV. OX POWES Cabinet cooling fan has stoppe	of runing. Shutdown
		UV-OX and contact Piper Electric to swap out fan with back	of (they think they
		CAN Free up somewe today). Place GCI ON stand by while UV-O	
	0550	Reduce T-540/54/ to BTS from 0.3 gpm to 0.2 gpm UNT: 1 BTS CAN a	adjust to the Fresh
	tires as	MW3K Source well water entering the system- Sep Set T-530	to start up to BTS
		at 0.2 cm GAM-IPM daily (Tank @ 41%) Note: T-540/52	11 at 79%, solar
		well extraction good oversight. Will shutdown batch extraction ! - working on weekly slams systems challe and called whether smalley	seter this morning.
	1050	- Working on weekly slaves systems cheeks and called authors reday	
	1110	- Decement T-351 to bestroom palve, wetweel activated water is clear no color.	
		- Clean AH-315 Probe w/ Acto Sow Hor. Check THE HARBO For oil or SHEER: NORE ON Served Spray Down	wen
		- check TP-130 for oil globules: None as served. water Is very clear w/yellow- green +mt.	
	1130	Shutdown MW38 Source well batch extraction (T-540/541) & 95%. full	
	1215	John Johanson of Piper Electric on site to swap out power cabinet far	~,
		Start MW36N's to T-540/5411 to deplee some will water in the cave you	
	1310	Beloot HAT FTVIEW 1 to suit available temporary memory & to restar	4 Um siftware [WAS
		stuck while running a scan), online 1317.	
	1446	FAN replaced and working, Short UV-OX, warming up-	
	1400	- Suspend plant Discharge to calibrate pH-740 prope to 4100 pH8705	
		-lesume Normal discharge. continue with other plant pt probes calibrations to 4+10 14570 2	Influent Sources and Flow Rates: @ [[10] NBBW - 6.8 gpm 1 - 4.83
		pH-113, 670, 310, 215, +365, Cercise studge +Hickon motor searthy	North End On Site- 12.6 gpm North End Off-Site – 2.6 gpm
	1440	weekly plants system checks and collerations complete.	RWST - Z.O gpm
		- Plants operations and.	NTES - 0・47 gpm(10R only) MW38 T-540/541 - かぴ gpm(Source
	1820	- Login Remothly and Switch muse was property wells to Rusts. 610 gal Floshed + Are Aitelie	well and 38 pumping wells mix) MW38 N & S – 3 · 3 gpm s =
		to sisplace my source well wonter	COND/NTES T-530-
			MW113 Area – I.69 gpm

APPENDIX A-2

NBBW SUMP GRAPH



APPENDIX A-3

SLUDGE ANALYSIS DATA

APPENDIX A-3 WTP SLUDGE RESULTS

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Regulatory WTP SLUDGE WTP SLUDGE-1d/ WTP SLUDGE-2^{d/} WTP SLUDGE-3^{d/} Units^{a/} **Parameter Name** Method RL/Lc Lc Lc Lc $Limit^{b/}$ 3/14/2022 3/14/22 3/14/22 3/14/22 Radium-228 EPA 901.1 5^{e/} pCi/g NAn NAn 0.71 + / - 0.500.48 0.79 + / - 0.540.48 0.73 + / - 0.300.23 5e/ Radium-226 EPA 901.1 NAn NAn 0.56 ± 0.36 0.27 0.57 + / - 0.330.22 pCi/g 0.30 0.53 + / - 0.245e/ Lead-210 EPA 901.1 NAn NAn pCi/g $0.07 \pm / -0.18$ 0.15 $0.087 \pm / -0.15$ 0.12 $0.028 \pm / -0.17$ 0.13 5e/ EML Po-2 NAn Polonium-210 pCi/g NAn 0.11 + / - 0.100.014 0.13 + / - 0.120.00 0.093 +/- 0.09 0.014 Uranium-234 ASTM D2907 1590 15.82 +/- 2.29 0.024 NAnf NAn NAn NAn NAn NAn pCi/g Uranium-235 ASTM D2907 pCi/g 1800 0.61 +/- 0.26 0.013 NAn NAn NAn NAn NAn NAn Uranium-238 **ASTM D2907** 1940 11.77 +/- 1.77 0.014 NAn NAn NAn NAn NAn NAn pCi/g Plutonium-238 EPA 600/7-79-081 pCi/g 540 0.042 ± -0.07 0.22 NAn NAn NAn NAn NAn NAn Plutonium-239/240 EPA 600/7-79-081 1090 0.046 +/- 0.071 0.0065 NAn NAn NAn NAn NAn pCi/g NAn -0.008 +/- 0.033 NAn NAn Americium-241 ER110 LANL pCi/g 646 0.012 NAn NAn NAn NAn Arsenic mg/L 5 0.043 J0.5 NAn NAn NAn NAn NAn NAn TCLPg//6010B Barium TCLP/6010B mg/L 100 $0.26 \, J$ 10 NAn NAn NAn NAn NAn NAn Cadmium TCLP/6010B mg/L 0.003 J0.1 NAn NAn NAn NAn NAn NAn Chromium TCLP/6010B mg/L 6 0.5 U 0.5 NAn NAn NAn NAn NAn NAn Lead TCLP/6010B 5 0.5 U 0.5 NAn NAn NAn NAn NAn NAn mg/L Selenium TCLP/6010B 0.035 J0.25 NAn NAn NAn NAn NAn NAn mg/L 1 Silver TCLP/6010B mg/L 5 0.5 U 0.5 NAn NAn NAn NAn NAn NAn 0.2 TCLP/7470A mg/L 0.002 U 0.002 NAn NAn NAn NAn NAn NAn Mercury 2.4-D TCLP/8151A 10 0.05 U 0.05 NAn NAn NAn NAn NAn NAn mg/L 1,1-Dichloroethene TCLP/8260B 0.7 0.01 U 0.01 NAn NAn NAn mg/L NAn NAn NAn 0.5 0.01 U 1.2-Dichloroethane TCLP/8260B mg/L 0.01 NAn NAn NAn NAn NAn NAn 200 0.05 U 2-Butanone (MEK) TCLP/8260B mg/L 0.05 NAn NAn NAn NAn NAn NAn Benzene TCLP/8260B mg/L 0.5 0.01 U 0.01 NAn NAn NAn NAn NAn NAn Carbon tetrachloride TCLP/8260B 0.5 0.01 U 0.01 NAn NAn NAn NAn NAn NAn mg/L Chlorobenzene TCLP/8260B 100 0.01 U 0.01 NAn mg/L NAn NAn NAn NAn NAn Chloroform TCLP/8260B mg/L 6 0.0018 J0.01 NAn NAn NAn NAn NAn NAn Tetrachloroethene TCLP/8260B mg/L 0.7 0.01 U 0.01 NAn NAn NAn NAn NAn NAn Trichloroethene TCLP/8260B 0.5 0.01 U 0.01 NAn NAn NAn NAn NAn NAn mg/L Vinyl chloride TCLP/8260B 0.2 0.02 U 0.02 NAn NAn NAn NAn NAn NAn mg/L 1,4-Dichlorobenzene TCLP/8270C 7.5 0.02 U 0.02 NAn NAn NAn NAn NAn NAn mg/L 2,4,5-Trichlorophenol TCLP/8270C mg/L 400 0.05 U 0.05 NAn NAn NAn NAn NAn NAn 2,4,6-Trichlorophenol TCLP/8270C 2 0.05 U 0.05 NAn NAn NAn NAn mg/L NAn NAn 2,4-Dinitrotoluene TCLP/8270C 0.13 0.05 U 0.05 NAn NAn NAn NAn NAn mg/L NAn TCLP/8270C 200 0.05 U 0.05 NAn NAn NAn 2-Methylphenol mg/L NAn NAn NAn NAn 3 & 4 Methylphenol TCLP/8270C mg/L 200 0.05 U 0.05 NAn NAn NAn NAn NAn Hexachlorobenzene TCLP/8270C 0.13 0.05 U 0.05 NAn NAn NAn NAn NAn NAn mg/L Hexachlorobutadiene TCLP/8270C 0.5 0.05 U 0.05 NAn NAn NAn NAn NAn mg/L NAn

APPENDIX A-3

WTP SLUDGE RESULTS

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE

Parameter Name	Method	Units ^{a/}	Regulatory Limit ^{b/}	WTP SLUDGE 3/14/2022	RL/Lc ^{c/}	WTP SLUDGE-1 ^{d/} 3/14/22	Lc	WTP SLUDGE-2 ^{d/} 3/14/22	Lc	WTP SLUDGE-3 ^{d/} 3/14/22	Lc
Hexachloroethane	TCLP/8270C	mg/L	3	0.05 U	0.05	NAn	NAn	NAn	NAn	NAn	NAn
Nitrobenzene	TCLP/8270C	mg/L	2	0.05 U	0.05	NAn	NAn	NAn	NAn	NAn	NAn
Pentachlorophenol	TCLP/8270C	mg/L	100	0.25 U	0.25	NAn	NAn	NAn	NAn	NAn	NAn
Pyridine	TCLP/8270C	mg/L	5	0.1 U	0.1	NAn	NAn	NAn	NAn	NAn	NAn
Total Cresols	TCLP/8270C	mg/L	200	0.05 U	0.05	NAn	NAn	NAn	NAn	NAn	NAn

a/ Units = mg/L = milligrams per liter

pCi/g = picoCuries per gram

b/ 40 CFR 261.24 Toxicity Characteristic and the Updated Waste Management Plan (EMSI/Parsons 2020)

c/ RL/Lc = Reporting Limit/Critical Value

d/ Sampled for Technologically Enhanced Naturally Occurring Radioactive Material (TENORM) Assessment

e/ Exemption limit for disposal in landfills.

f/ Nan - Not analyzed for

g/ TCLP = Toxicity Characteristic Leaching Procedure

Qualifiers: U= The analyte was analyzed for and is not present above the level of the associated value.

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.

APPENDIX A-4

WTP WATER QUALITY DATA

SUMMARY OF WATER TREATMENT PLANT EFFLUENT (MP-001) WATER QUALITY

COMPLIANCE SUMMARY OF WATER TREATMENT PLANT EFFLUENT (MP-001)WATER QUALITY

1,4-DIOXANE

COMPLIANCE SUMMARY OF TREATMENT PLANT EFFLUENT (MP-001) WATER QUALITY 1,4-DIOXANE

Date→	1/3/2022	1/3/2022	1/3/2022	1/4/2022	1/4/2022	1/4/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
Compound	Conc (ug/L ^{a/})	Conc (ug/L)	Conc (ug/L)	Conc (ug/L)	Conc (ug/L)	Conc (ug/L)	Average conc (ug/L)	Volume per day ^{b/}	Total (lbs/day ^{c/})	Permit Limit (lbs/day)
1,4-Dioxane ^{d/}	14	13	13	13	13	14	13.33	46288	0.0052	0.032

Date→	2/1/2022	2/1/2022	2/1/2022	2/2/2022	2/2/2022	2/2/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
							Average			Permit
	Conc	Conc	Conc	Conc	Conc	Conc	conc	Volume	Total	Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	per day	(lbs/day)	(lbs/day)
1,4-Dioxane ^{d/}										

Date→	3/1/2022	3/1/2022	3/1/2022	3/2/2022	3/2/2022	3/2/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
							Average			Permit
	Conc	Conc	Conc	Conc	Conc	Conc	conc	Volume	Total	Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	per day	(lbs/day)	(lbs/day)
1.4-Dioxane ^{d/}	15	14	14	14	14	13	14.00	46892	0.0055	0.032

Date→	4/4/2022	4/4/2022	4/4/2022	4/5/2022	4/5/2022	4/5/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
							Average			Permit
	Conc	Conc	Conc	Conc	Conc	Conc	conc	Volume	Total	Limit
		Conc	Conc	~~~	Conc	Conc	conc	, oranic		
Compound	(ug/L ^{a/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	per day	(lbs/day)	(lbs/day)

Date→	5/2/2022	5/2/2022	5/2/2022	5/3/2022	5/3/2022	5/3/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
							Average			Permit
	Conc	Conc	Conc	Conc	Conc	Conc	conc	Volume	Total	Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	per day	(lbs/day)	(lbs/day)
1.4-Dioxane ^{d/}	17	18			17	15	16.83	46878	0.0066	0.032

Date→	6/6/2022	6/6/2022	6/6/2022	6/7/2022	6/7/2022	6/7/2022				
Time→	12:00	16:00	20:00	0:00	4:00	8:00				
							Average			Permit
	Conc	Conc	Conc	Conc	Conc	Conc	conc	Volume	Total	Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	per day	(lbs/day)	(lbs/day)
1,4-Dioxane ^{d/}	11	10	11	11	11	11	10.83	47544	0.0043	0.032

a/ ug/L = micrograms per liter

A-4.1.1 14D A-4.1.1-1

b/ Volume per day recorded on Composite Sampling Record

c/ lbs/day = pounds per day

d/1,4-Dioxane analyzed by low-level method (SW8260SIM)

COMPLIANCE SUMMARY OF WATER TREATMENT PLANT EFFLUENT (MP-001)WATER QUALITY

VOLATILE ORGANIC COMPOUNDS AND NONYLPHENOL

APPENDIX A-4.1.2 COMPLIANCE SUMMARY OF TREATMENT PLANT EFFLUENT (MP-001) WATER QUALITY VOLATILE ORGANIC COMPOUNDS AND NONYLPHENOL

	1/2/2022		1	1/4/2022					
D	1/3/2022	1/3/2022	1/3/2022	1/4/2022	1/4/2022	1/4/2022			
Date/Time→	12:00:00 PM	4:00:00 PM	8:00:00 PM	12:00:00 AM	4:00:00 AM	8:00:00 AM			
	Conc			~	~	~		Permit	Max
		Conc	Conc	Conc	Conc	Conc	Average	Limit	Value
Compound	(ug/L ^{a/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	conc (ug/L)	(ug/L)	(ug/L)
1,1,1,2-Tetrachloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA b/	0
1,1,1-Trichloroethane	8.9	9	8.9	8.7	9.3	8.7	8.92	NA	7.2
1,1,2,2-Tetrachloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
1,1,2-Trichloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
1,1-Dichloroethane	21	22	22	22	22	22	21.8	NA	22
1,1-Dichloroethene	1.1	1.1	0.97	1	1.1	1	1.0	NA	1.4
1,2-Dibromo-3-chloropropane	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
1,2-Dibromoethane	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
1,2-Dichlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
1,2-Dichloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.75 J	NA	0.81 J
1,2-Dichloroethene	5	5.2	5.1	5.3	5.2	4.9	5.12	NA	5.3
1,2-Dichloropropane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
	1 U	1 U	1 U	1 U	1 U	1 U	0		0
1,3-Dichlorobenzene		1 U	1 U				0	NA NA	0
1,3-Dichloropropene	1 U			1 U	1 U	1 U	,	NA	
1,4-Dichlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
1,4-Dioxane	20 U	20 U	20 U	20 U	20 U	20 U	0	NA	0
2-Butanone (MEK)	20 U	20 U	20 U	20 U	20 U	20 U	0	NA	0
2-Chloroethylvinylether	3 U	3 U	3 U	3 U	3 U	3 U	0	NA	0
2-Hexanone	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
4-Methyl-2-pentanone (MIBK)	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
Acetone	20 U	20 U	20 U	20 U	20 U	20 U	0	NA	0
Acrolein	20 U	20 U	20 U	20 U	20 U	20 U	0	NA	0
Acrylonitrile	20 U	20 U	20 U	20 U	20 U	20 U	0	NA	0
Benzene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Bromodichloromethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Bromoform	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Bromomethane	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Carbon Disulfide	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Carbon Tetrachloride	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Chlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA NA	0
Chloroethane	4 U	4 U	4 U	4 U	4 U	4 U	0	NA	0.52 J
Chloroform	1 U	1 U	0.44 J	0.41 J	0.4 J	0.38 J	0.27 0.00	NA	0
Chloromethane cis-1,2-Dichloroethene	2 U 5	2 U 5.2	2 U 5.1	2 U 5.3	2 U 5.2	2 U 4.9	5.12	NA NA	5.3
cis-1,3-Dichloropropene	1 U	1 U	1 U	3.3 1 U	1 U	4.9 1 U	0	NA NA	0
Dibromochloromethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA NA	0
Dibromomethane	1 U	1 U	1 U	1 U	1 U	1 U	0	NA NA	0
Ethylbenzene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Hexane	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Methylene Chloride	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
Methyl-t-butyl ether	5 U	5 U	5 U	5 U	5 U	5 U	0	NA	0
m-Xylene & p-Xylene	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Naphthalene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Styrene	1 U	1 U	1 U	1 U	1 U	1 U	0	1500	0
Tetrachloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Tetrahydrofuran	7 U	7 U	7 U	7 U	7 U	7 U	0	NA	0
Toluene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Trans-1,2-Dichloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Trans-1,3-Dichloropropene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Trichloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Trichlorofluoromethane	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
Vinyl Acetate	3 U	3 U	3 U	3 U	3 U	3 U	0	NA	0
Vinyl Chloride	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0
Xylenes, Total	2 U	2 U	2 U	2 U	2 U	2 U	0	NA NA	0
Nonylphenol	4.9 U	4.9 U	4.7 U	4.8 U	4.8 U	4.9 U	U	NA	0

	2/1/2022	2/1/2022	2/1/2022	2/2/2022	2/2/2022	2/2/2022			
Date/Time→	12:00:00 PM	4:00:00 PM	8:00:00 PM	12:00:00 AM	4:00:00 AM	8:00:00 AM			
									Daily
								Permit	Max
	Conc	Conc	Conc	Conc	Conc	Conc	Average	Limit	Value
Compound	(ug/L ^{a/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	conc (ug/L)	(ug/L)	(ug/L)
1,2,3-Trichloropropane	3 U	3 U	3 U	3 U	3 U	3 U	0	NA	0
Dichlorodifluoromethane	2 U	2 U	2 U	2 U	2 U	2 U	0	NA	0
o-Xylene	1 U	1 U	1 U	1 U	1 U	1 U	0	NA	0

	4/4/2022	4/4/2022	4/4/2022	4/5/2022	4/5/2022	4/5/2022			
Date/Time→	4/4/2022 12:00:00 PM	4/4/2022 4:00:00 PM	4/4/2022	4/5/2022 12:00:00 AM	4/5/2022 4:00:00 AM	4/5/2022 8:00:00 AM			
Date/11me→	12:00:00 PM	4:00:00 PM	8:00:00 PM	12:00:00 AM	4:00:00 AM	8:00:00 AM			Daily
								Permit	Max
	Conc	Conc	Conc	Conc	Conc	Conc	Average	Limit	Value
Compound	(ug/L ^{a/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	conc (ug/L)	(ug/L)	(ug/L)
1.1.1.2-Tetrachloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA b/	0.0
1.1.1-Trichloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA NA	0.0
1,1,2,2-Tetrachloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA NA	0.0
1,1,2-Trichloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA NA	0.0
1,1-Dichloroethane	5.6	5.8	5.9	6.9	7	6.8	6.3	NA NA	6.6
1.1-Dichloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,2,3-Trichloropropane	3 U	3 U	3 U	3 U	3 U	3 U	0.0	NA	0.0
1,2-Dibromo-3-chloropropane	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
1,2-Dibromoethane	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
1,2-Dichlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,2-Dichloroethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,2-Dichloroethene	1 U	1 U	1 U	1 U	1 U	0.22 J	0.04	NA	0.04
1,2-Dichloropropane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,3-Dichlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,3-Dichloropropene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,4-Dichlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
1,4-Dioxane	20 U	20 U	20 U	23	20 U	28	8.5	NA	8.5
2-Butanone (MEK)	20 U	20 U	20 U	20 U	20 U	20 U	0.0	NA	0.0
2-Chloroethylvinylether	3 U	3 U	3 U	3 U	3 U	3 U	0.0	NA	0.0
2-Hexanone	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
4-Methyl-2-pentanone (MIBK)	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
Acetone	20 U	20 U	20 U	20 U	20 U	20 U	0.0	NA	0.0
Acrolein	20 U	20 U	20 U	20 U	20 U	20 U	0.0	NA	0.0
Acrylonitrile	20 U	20 U	20 U	20 U	20 U	20 U	0.0	NA	0.0
Benzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Bromodichloromethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Bromoform	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Bromomethane	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Carbon Disulfide	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Carbon Tetrachloride	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Chlorobenzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Chloroethane	4 U	4 U	4 U	4 U	4 U	4 U	0.0	NA	0.0
Chloroform	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Chloromethane	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
cis-1,2-Dichloroethene	1 U	1 U	1 U	1 U	1 U	0.22 J	0.04	NA	0.04
cis-1,3-Dichloropropene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Dibromochloromethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Dibromomethane	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Dichlorodifluoromethane	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Ethylbenzene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Hexane	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Methylene Chloride	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
Methyl-t-butyl ether	5 U	5 U	5 U	5 U	5 U	5 U	0.0	NA	0.0
m-Xylene & p-Xylene	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Naphthalene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
o-Xylene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Styrene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	1500	0.0
Tetrachloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Tetrahydrofuran	0.56 J	7 U	7 U	7 U	7 U	7 U	0.0	NA	0.0
Toluene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Trans-1,2-Dichloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Trans-1,3-Dichloropropene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Trichloroethene	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA	0.0
Trichlorofluoromethane	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0
Vinyl Acetate	3 U	3 U	3 U	3 U	3 U	3 U	0.0	NA	0.0
Vinyl Chloride	1 U	1 U	1 U	1 U	1 U	1 U	0.0	NA NA	0.0
Xylenes, Total	2 U	2 U	2 U	2 U	2 U	2 U	0.0	NA	0.0

	5/9/2022	5/9/2022	5/9/2022	5/102022	5/10/2022	5/10/2022			
Date/Time→	12:00:00 PM	4:00:00 PM	8:00:00 PM	12:00:00 AM	4:00:00 AM	8:00:00 AM			
									Daily
								Permit	Max
	Conc	Conc	Conc	Conc	Conc	Conc	Average	Limit	Value
Compound	(ug/L ^{a/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	conc (ug/L)	(ug/L)	(ug/L)
Nonylphenol	4.8 U	4.8 U	4.7 U	4.7 U	4.8 U	4.9 U	0.0	NA	0.0

a/ ug/L = micrograms per liter

b/ NA = Not applicable - No permit limit Quarterly

Frequency: Volatile Organic Compounds 8260B Methods: Nonylphenol ASTM D7065

The analyte was analyzed for and is not present above the level of the associated value.

 $\label{eq:Qualifiers: U= The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.}$

The analyte was analyzed for, and was positively identified, but the associated numerical value

J= may not be consistent with the amount actually present in the environmental sample.

COMPLIANCE SUMMARY OF WATER TREATMENT PLANT EFFLUENT (MP-001) WATER QUALITY

METALS, pH AND SEMIVOLATILE ORGANIC COMPOUNDS

APPENDIX A-4.1.3 SUMMARY OF TREATMENT PLANT EFFLUENT WATER QUALITY METALS and SEMIVOLATILE ORGANIC COMPOUNDS

							-001 le Date		
				1/4/2022	2/2/2022	3/2/2022	4/5/2022	5/3/2022	6/7/2022
		Permit		8:00:00	8:00:00	8:00:00	8:00:00	8:00:00	8:00:00
Compound	Units	Limit	Frequency	AM	AM	AM	AM	AM	AM
1,2,4-Trichlorobenzene	ug/L ^{a/}	NA ^{b/}	Quarterly	3.8 U	NAn ^{c/}	NAn	3.8 U	NAn	NAn
2,4,6-Trichlorophenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
2,4-Dichlorophenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
2,4-Dimethylphenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
2,4-Dinitrophenol	ug/L	NA	Quarterly	28 U	NAn	NAn	28 U	NAn	NAn
2,4-Dinitrotoluene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
2,6-Dinitrotoluene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
2-Chloronaphthalene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
2-Chlorophenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 UJ-	NAn	NAn
2-Methylnaphthalene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
2-Nitrophenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
3,3'-Dichlorobenzidine	ug/L	NA	Quarterly	47 U	NAn	NAn	47 U	NAn	NAn
4,6-Dinitro-2-Methylphenol	ug/L	NA	Quarterly	47 U	NAn	NAn	47 U	NAn	NAn
4-Bromophenyl phenyl ether	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
4-Chloro-3-Methylphenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
4-Chlorophenyl phenyl ether	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
4-Nitrophenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Acenaphthene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Acenaphthylene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Acetophenone	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 UJ-	NAn	NAn
aniline	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Anthracene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzo(a)anthracene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzo(a)pyrene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzo(b)fluoranthene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzo(g,h,i)Perylene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzo(k)fluoranthene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Benzoic Acid	ug/L	NA	Quarterly	24 U	NAn	NAn	24 U	NAn	NAn
Bis(2-Chloroethoxy)methane	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Bis(2-Chloroethyl)Ether	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Bis(2-Chloroisopropyl) Ether	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
bis(2-Ethylhexyl)phthalate	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Butyl benzyl phthalate	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
C10	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
C18	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Carbazole	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Chrysene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Dibenz(a,h)anthracene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Diethylphthalate	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Dimethylphthalate	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Di-N-Butylphthalate	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Di-n-octylphthalate	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Fluoranthene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Fluorene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Hexachlorobenzene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Hexachlorobutadiene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Hexachlorocyclopentadiene	ug/L	NA	Quarterly	NAn	NAn	47 U	47 U	NAn	NAn
Hexachloroethane	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 UJ-	NAn	NAn

		Permit		1/4/2022	2/2/2022	3/2/2022	4/5/2022	5/3/2022	6/7/2022
Compound	Units	Limit	Frequency	8:00:00 AM	8:00:00 AM	8:00:00 AM	8:00:00 AM	8:00:00 AM	8:00:00 AM
Indeno(1,2,3-c,d)pyrene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Isophorone	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Naphthalene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Nitrobenzene	ug/L ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
N-Nitrosodimethylamine	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
N-Nitroso-Di-N-Propylamine	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 UJ-	NAn	NAn
N-Nitrosodiphenylamine	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Pentachlorophenol	ug/L	NA	Quarterly	47 U	NAn	NAn	47 U	NAn	NAn
Phenanthrene	ug/L	NA	Quarterly	3.8 U	NAn	NAn	3.8 U	NAn	NAn
Phenol	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Pyrene	ug/L	NA	Quarterly	9.5 U	NAn	NAn	9.4 U	NAn	NAn
Pyridine	ug/L	NA	Quarterly	19 U	NAn	NAn	19 U	NAn	NAn
Cadmium	ug/L	3400	Yearly	NAn	NAn	NAn	1 U	NAn	NAn
Copper	ug/L	6100	Yearly	NAn	NAn	NAn	21	NAn	NAn
Molybdenum	ug/L	430	Monthly	13	13	14	14	15	17
Nickel	ug/L	5600	Yearly	NAn	NAn	NAn	3.5	NAn	NAn
Selenium	ug/L	660	Quarterly	19	NAn	NAn	17	NAn	NAn
Zinc	ug/L	15600	Quarterly	3.1 U	NAn	NAn	3.1 UJ+	NAn	NAn
Arsenic	ug/L	330	Yearly	NAn	NAn	NAn	15 U	NAn	NAn
Chromium	ug/L	3600	Yearly	NAn	NAn	NAn	10 U	NAn	NAn
Lead	ug/L	2200	Yearly	NAn	NAn	NAn	9 U	NAn	NAn
Silver	ug/L	2900	Yearly	NAn	NAn	NAn	10 U	NAn	NAn
Mercury	ug/L	130	Yearly	NAn	NAn	NAn	0.2 U	NAn	NAn
pН	pH Units	>5	Monthly	6.81	7.03	6.72	6.87	6.92	6.77

a/ ug/L = micrograms per liter

 $\label{eq:Qualifiers: U= The analyte was analyzed for and is not present above the level of the associated value.}$

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

- UJ= The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.
- UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.
- $UJ += \ Same \ as \ UJ \ qualification \ but \ with \ an \ indication \ of \ positive \ bias \ in \ the \ sample \ concentration.$
 - J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- J-= Same as J qualification but with an indication of negative bias in the sample concentration.
- J+= Same as J qualification but with an indication of positive bias in the sample concentration.

b/ NA = Not applicable - No permit limit

c/Nan = Not analyzed

COMPLIANCE SUMMARY OF WATER TREATMENT PLANT EFFLUENT (MP-001) WATER QUALITY RADIONUCLIDES

APPENDIX A-4.1.4 SUMMARY OF TREATMENT PLANT EFFLUENT WATER QUALITY RADIONUCLIDES (MP-001)^{a/}

		10.1010	тесы	DES (MIT	001)				
								Daily	
								Maximum	Permit
			Conc				Result	Value	Limit
Isotope	Sampling Date	Frequency	(pCi/L) ^{b/}	FINAL Q	MDC ^{c/}	CSU ^{d/}	minus CSU	(pCi/L)	(pCi/L)
Americium-241	1/4/2022	Quarterly	0.013	J	0.05838	0.029	-0.016	0.013	NA ^{e/}
Alpha, Gross	1/4/2022	Quarterly	15.029	UJ+	16.6457	5.891	9.138	15.029	NA
Beta, Gross	1/4/2022	Quarterly	9.33	U	14.2814	4.408	4.923	9.33	NA
Plutonium-238	1/4/2022	Quarterly	0.083	UJ	0.07212	0.072	0.011	0.083	NA
Plutonium-239/240	1/4/2022	Quarterly	0.049	J	0.0855	0.059	-0.011	0.049	NA
Radium-226	1/4/2022	Quarterly	0.419	J	0.2999	0.357	0.062	0.419	NA
Radium-228	1/4/2022	Quarterly	1.193	J	1.2751	0.714	0.48	1.193	NA
Total Radium	1/4/2022	Quarterly	0.367	J	0.33214	0.2	0.166	0.367	NA
Americium-241	4/5/2022	Quarterly	0	UJ	0.146	0.051	-0.051	0	NA
Alpha, Gross	4/5/2022	Quarterly	37.8	J+	11.3	7.36	30.44	37.8	NA
Beta, Gross	4/5/2022	Quarterly	15.3	U	14	4.85	10.45	15.3	NA
Plutonium-238	4/5/2022	Quarterly	-0.019	UJ	0.0988	0.033	-0.052	-0.019	NA
Plutonium-239/240	4/5/2022	Quarterly	0.005	UJ	0.0808	0.03	-0.026	0.005	NA
Radium-226	4/5/2022	Quarterly	0.341		0.116	0.165	0.176	0.341	NA
Radium-228	4/5/2022	Quarterly	0.461	J	0.398	0.234	0.227	0.461	NA
Total Radium	4/5/2022	Quarterly	0.185	U	0.217	0.127	0.058	0.185	NA

a/24 hour composite

Qualifiers: U= The analyte was analyzed for and is not present above the level of the associated value.

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

- UJ= The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.
- UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.
- UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.
 - J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- J -= Same as J qualification but with an indication of negative bias in the sample concentration.
- J+= Same as J qualification but with an indication of positive bias in the sample concentration.

b/ picoCuries per liter

c/ minimum detectable concentration

d/ Combined standard uncertainty

e/ NA = Not applicable - No permit limit

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(VOLATILE ORGANIC COMPOUNDS)

INDIVIDUAL AND COMPOSITE DATA

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(Volatile Organic Compounds)

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

	Date	→				1/3/2022				
						CONCEN			a/	
	Sample		TP-110 ^{a/}	TP-120 ^{b/}	TP-140 ^{c/}	TP-150 ^{d/}	TP-160 ^{e/}	TP-170 ^{f/}	TP3310 ^{g/}	
	% of F	ow►	1.7%	21.5%	6.8%	37.6%	24.0%	5.6%	2.8%	
_	Permit									Composite
Parameter Name	Limith/	Units								Concentration
1,1,1,2-Tetrachloroethane	NA ^{i/}	ug/L ^{j/}	< 0.8	< 2	< 0.2	< 0.2	< 0.2	< 0.2	< 20	0.00
1,1,1-Trichloroethane	NA	ug/L	28	83	< 0.2	2.3	< 0.2	< 0.2	< 20	17.81
1,1,2,2-Tetrachloroethane	NA	ug/L	< 0.5	< 1.2	< 0.12	< 0.12	< 0.12	< 0.12	< 12	0
1,1,2-Trichloroethane	NA	ug/L	< 0.93	< 2.3	< 0.23	< 0.23	< 0.23	< 0.23	< 23	0.00
1,1-Dichloroethane	NA	ug/L	77	220	12	5.2	< 0.2	< 0.2	93	50.54
1,1-Dichloroethene	NA	ug/L	24	71	< 0.24	3.4	< 0.24	< 0.24	< 24	15.77
1,2,3-Trichloropropane	NA	ug/L	< 1.2	< 2.9	< 0.29	< 0.29	< 0.29	< 0.29	< 29	0.00
1,2-Dibromo-3-chloropropane	NA	ug/L	< 1.5	< 3.8	< 0.38	< 0.38	< 0.38	< 0.38	< 38	0.00
1,2-Dibromoethane	NA	ug/L	< 0.87	< 2.2	< 0.22	< 0.22	< 0.22	< 0.22	< 22	0.00
1,2-Dichlorobenzene	NA	ug/L	< 0.67	< 1.7	< 0.17	< 0.17	< 0.17	< 0.17	< 17	0.00
1,2-Dichloroethane	NA	ug/L	< 0.68	< 1.7	< 0.17	< 0.17	< 0.17	< 0.17	4800	148.80
1,2-Dichloroethene	NA	ug/L	300	890	3.7	12	< 0.15	< 0.15	< 15	186.56
1,2-Dichloropropane	NA	ug/L	< 0.72	< 1.8	< 0.18	< 0.18	< 0.18	< 0.18	< 18	0.00
1,3-Dichlorobenzene	NA NA	ug/L	< 0.65	< 1.6	< 0.16	< 0.16	< 0.16	< 0.16	< 16	0.00
1,3-Dichloropropene	NA NA	ug/L	< 0.55	< 1.4	< 0.14	< 0.14	< 0.14	< 0.14	< 14	0.00
1,4-Dichlorobenzene	NA NA	ug/L	< 0.62	< 1.6	< 0.16	< 0.16	< 0.16	< 0.16	30	0.93
2-Butanone (MEK)	NA NA	ug/L ug/L	< 5.8 < 0.84	< 14 < 2.1	< 1.4 < 0.21	< 1.4 < 0.21	< 1.4 < 0.21	< 1.4 < 0.21	1300	40.30 0.00
2-Chloroethylvinylether 2-Hexanone	NA	ug/L ug/L								0.00
	NA NA	ug/L ug/L	< 1.7	< 4.2	< 0.42	< 0.42	< 0.42	< 0.42	< 42 < 46	0.00
4-Methyl-2-pentanone (MIBK)	NA	ug/L ug/L	< 1.9 < 32	< 4.6 < 80	< 0.46 < 8	< 0.46 < 8	< 0.46 < 8	< 0.46 < 8	1400	43.40
Acetone Acrolein	NA	ug/L ug/L	< 7.2	< 18	< 1.8	< 1.8	< 1.8	< 1.8	< 180	0.00
Acrylonitrile	NA	ug/L ug/L	< 4.4	< 11	< 1.1	< 1.1	< 1.1	< 1.1	< 110	0.00
Benzene	NA	ug/L ug/L	< 0.72	< 1.8	< 0.18	< 0.18	< 0.18	< 0.18	700	0.00
Bromodichloromethane	NA	ug/L ug/L	< 0.72	< 1.5	< 0.15	< 0.15	< 0.18	< 0.15	< 15	0.00
Bromoform	NA	ug/L ug/L	< 2.7	< 6.7	< 0.13	< 0.13	< 0.13	< 0.13	< 67	0.00
Bromomethane	NA	ug/L	< 4.4	< 11	< 1.1	< 1.1	< 1.1	< 1.1	< 110	0.00
Carbon Disulfide	NA	ug/L	< 1.3	< 3.2	< 0.32	< 0.32	< 0.32	< 0.32	< 32	0.00
Carbon Tetrachloride	NA	ug/L	< 0.95	< 2.4	< 0.32	< 0.32	< 0.24	< 0.24	< 24	0.00
Chlorobenzene	NA	ug/L	< 0.7	< 1.8	< 0.18	< 0.18	< 0.18	< 0.18	< 18	0.00
Chloroethane	NA	ug/L	< 1.4	< 3.6	< 0.36	< 0.36	< 0.36	< 0.36	< 36	0.00
Chloroform	NA	ug/L	1.6	< 2.2	4.3	< 0.22	< 0.22	< 0.22	< 22	0.29
Chloromethane	NA	ug/L	< 2.3	< 5.7	< 0.57	< 0.57	< 0.57	< 0.57	< 57	0.00
cis-1,2-Dichloroethene	NA	ug/L	300	890	3.7	12	< 0.15	< 0.15	< 15	186.56
cis-1,3-Dichloropropene	NA	ug/L	< 0.55	< 1.4	< 0.14	< 0.14	< 0.14	< 0.14	< 14	0.00
Dibromochloromethane	NA	ug/L	< 0.86	< 2.1	< 0.21	< 0.21	< 0.21	< 0.21	< 21	0.00
Dibromomethane	NA	ug/L	< 0.48	< 1.2	< 0.12	< 0.12	< 0.12	< 0.12	< 12	0.00
Dichlorodifluoromethane	NA	ug/L	< 1.4	< 3.5	< 0.35	< 0.35	< 0.35	< 0.35	< 35	0.00
Ethylbenzene	NA	ug/L	< 0.72	< 1.8	< 0.18	< 0.18	< 0.18	< 0.18	140	4.34
Hexane	NA	ug/L	< 1	< 2.6	< 0.26	< 0.26	< 0.26	< 0.26	< 26	0.00
Methylene Chloride	NA	ug/L	< 0.69	< 1.7	< 0.17	< 0.17	< 0.17	< 0.17	< 17	0.00
Methyl-t-butyl ether	NA	ug/L	< 0.64	< 1.6	< 0.16	< 0.16	< 0.16	< 0.16	< 16	0.00
m-Xylene & p-Xylene	NA	ug/L	< 0.81	< 2	< 0.2	< 0.2	< 0.2	< 0.2	280	8.68
Naphthalene	NA	ug/L	< 0.41	< 1	< 0.1	< 0.1	< 0.1	< 0.1	< 10	0.00
o-Xylene	NA	ug/L	< 0.84	< 2.1	< 0.21	< 0.21	< 0.21	< 0.21	160	4.96
Styrene	NA	ug/L	< 0.86	< 2.2	< 0.22	< 0.22	< 0.22	< 0.22	< 22	0.00
Tetrachloroethene	1500	ug/L	3.1	9.2	1.1	0.83	< 0.19	< 0.19	< 19	2.25
Tetrahydrofuran	NA	ug/L	17	53	< 0.53	< 0.53	< 0.53	< 0.53	22000	693.00
Toluene	NA	ug/L	< 0.96	< 2.4	< 0.24	< 0.24	< 0.24	< 0.24	63	1.95
Trans-1,2-Dichloroethene	NA	ug/L	< 0.84	< 2.1	< 0.21	< 0.21	< 0.21	< 0.21	< 21	0.00
Trans-1,3-Dichloropropene	NA	ug/L	< 0.7	< 1.8	< 0.18	< 0.18	< 0.18	< 0.18	< 18	0.00
Trichloroethene	NA	ug/L	2.3	6.6	2.9	< 0.18	< 0.18	< 0.18	< 18	1.52
Trichlorofluoromethane	NA	ug/L	< 0.81	< 2	< 0.2	< 0.2	< 0.2	< 0.2	< 20	0.00
Vinyl Acetate	NA	ug/L	< 3.8	< 9.4	< 0.94	< 0.94	< 0.94	< 0.94	< 94	0.00
Vinyl Chloride	NA	ug/L	< 1.1	< 2.8	< 0.28	< 0.28	< 0.28	< 0.28	< 28	0.00
Xylenes, Total	NA	ug/L	< 0.81	< 2	< 0.2	< 0.2	< 0.2	< 0.2	440	13.64
Nonylphenol	NA	ug/L	NAn	NA						

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(Volatile Organic Compounds)

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

							4/4/2022			
								NCENTRA		1
	Sample 1		TP-110 ^{a/}	TP-120 ^{b/}	TP-140 ^{c/}		TP-160 ^{e/}		TP3310 ^{g/}	
	% of Fl	ow►	1.7%	19.9%	6.2%	37.0%	23.2%	9.2%	2.8%	
Parameter Name	Permit Limit ^{h/}	Units								Composite Concentration
1,1,1,2-Tetrachloroethane	NA ^{i/}	ug/L ^{j/}	< 0.2	< 0.8	< 0.2	< 0.2	< 0.2	< 0.2	< 10	0.00
1,1,1-Trichloroethane	NA	ug/L	21	69	0.24	1.7	< 0.2	< 0.2	< 10	14.52
1,1,2,2-Tetrachloroethane	NA	ug/L	< 0.12	< 0.5	< 0.12	< 0.12	< 0.12	< 0.12	< 6.2	0.00
1,1,2-Trichloroethane	NA	ug/L	0.46	1.4	< 0.23	< 0.23	< 0.23	< 0.23	< 12	0.28
1,1-Dichloroethane	NA	ug/L	62	190	11	3.6	< 0.2	0.44	< 10	40.00
1,1-Dichloroethene	NA	ug/L	15	54	0.26	2.7	< 0.24	< 0.24	< 12	11.87
1,2,3-Trichloropropane	NA	ug/L	< 0.29	< 1.2	< 0.29	< 0.29	< 0.29	< 0.29	< 15	0.00
1,2-Dibromo-3-chloropropane	NA	ug/L	< 0.38	< 1.5	< 0.38	< 0.38	< 0.38	< 0.38	< 19	0.00
1,2-Dibromoethane	NA	ug/L	< 0.22	< 0.87	< 0.22	< 0.22	< 0.22	< 0.22	< 11	0.00
1,2-Dichlorobenzene	NA	ug/L	< 0.17	< 0.67	< 0.17	< 0.17	< 0.17	< 0.17	< 8.4	0.00
1,2-Dichloroethane	NA	ug/L	2.2	2.7	0.46	< 0.17	< 0.17	< 0.17	1900	54.00
1,2-Dichloroethene	NA	ug/L	230	750	3.6	9.4	< 0.15	< 0.15	< 7.4	154.43
1,2-Dichloropropane	NA	ug/L	0.86	2.5	< 0.18	< 0.18	< 0.18	< 0.18	< 9.1	0.50
1,3-Dichlorobenzene	NA	ug/L	< 0.16	< 0.65	< 0.16	< 0.16	< 0.16	< 0.16	< 8.2	0.00
1,3-Dichloropropene	NA NA	ug/L ug/L	< 0.14	< 0.55	< 0.14	< 0.14	< 0.14	< 0.14	< 6.9	0.00
1,4-Dichlorobenzene	NA NA	Ù	< 0.16	< 0.62	< 0.16	< 0.16	< 0.16	< 0.16	< 7.8	0.00
2-Butanone (MEK)	NA NA	ug/L ug/L	< 1.4	< 5.8	< 1.4	< 1.4	< 1.4	< 1.4	1400	39.20 0.00
2-Chloroethylvinylether	NA	ug/L ug/L	< 0.21	< 0.84	< 0.21	< 0.21 < 0.42	< 0.21 < 0.42	< 0.21	< 11	0.00
2-Hexanone	NA NA	ug/L ug/L	< 0.42	< 1.7	< 0.42			< 0.42	< 21	0.00
4-Methyl-2-pentanone (MIBK) Acetone	NA NA	ug/L ug/L	< 0.46	< 1.9 < 32	< 0.46	< 0.46 < 8	< 0.46 < 8	< 0.46 < 8	< 23 1200	33.60
Acrolein	NA	ug/L ug/L	< 1.8	< 7.2	< 1.8	< 1.8	< 1.8	< 1.8	< 90	0.00
Acrylonitrile	NA	ug/L ug/L	< 1.1	< 4.4	< 1.1	< 1.1	< 1.1	< 1.1	< 55	0.00
Benzene	NA	ug/L ug/L	< 0.18	< 0.72	< 0.18	< 0.18	< 0.18	< 0.18	770	21.50
Bromodichloromethane	NA	ug/L	< 0.15	< 0.72	< 0.15	< 0.15	< 0.15	< 0.15	< 7.7	0.00
Bromoform	NA	ug/L	< 0.13	< 2.7	< 0.13	< 0.13	< 0.13	< 0.13	< 34	0.00
Bromomethane	NA	ug/L	< 1.1	< 4.4	< 1.1	< 1.1	< 1.1	< 1.1	< 55	0.00
Carbon Disulfide	NA	ug/L	< 0.32	< 1.3	< 0.32	< 0.32	< 0.32	< 0.32	< 16	0.00
Carbon Tetrachloride	NA	ug/L	< 0.24	< 0.95	< 0.24	< 0.24	< 0.24	< 0.24	< 12	0.00
Chlorobenzene	NA	ug/L	< 0.18	< 0.7	< 0.18	< 0.18	< 0.18	< 0.18	< 8.8	0.00
Chloroethane	NA	ug/L	< 0.36	< 1.4	< 0.36	< 0.36	< 0.36	< 0.36	130	3.64
Chloroform	NA	ug/L	0.96	2.5	3.5	< 0.22	< 0.22	< 0.22	15	1.09
Chloromethane	NA	ug/L	< 0.57	< 2.3	< 0.57	< 0.57	< 0.57	< 0.57	< 28	0.00
cis-1,2-Dichloroethene	NA	ug/L	230	750	3.6	9.4	< 0.15	< 0.15	< 7.4	154.43
cis-1,3-Dichloropropene	NA	ug/L	< 0.14	< 0.55	< 0.14	< 0.14	< 0.14	< 0.14	< 6.9	0.00
Dibromochloromethane	NA	ug/L	< 0.21	< 0.86	< 0.21	< 0.21	< 0.21	< 0.21	< 11	0.00
Dibromomethane	NA	ug/L	< 0.12	< 0.48	< 0.12	< 0.12	< 0.12	< 0.12	< 6	0.00
Dichlorodifluoromethane	NA	ug/L	< 0.35	< 1.4	0.99	< 0.35	< 0.35	< 0.35	< 17	0.05
Ethylbenzene	NA	ug/L	< 0.18	< 0.72	< 0.18	< 0.18	< 0.18	< 0.18	140	3.92
Hexane	NA	ug/L	< 0.26	< 1	< 0.26	< 0.26	< 0.26	< 0.26	< 13	0.00
Methylene Chloride	NA	ug/L	< 0.17	< 0.69	< 0.17	< 0.17	< 0.17	< 0.17	< 8.7	0.00
Methyl-t-butyl ether	NA	ug/L	0.36	< 0.64	< 0.16	< 0.16	< 0.16	< 0.16	< 8.1	0.01
m-Xylene & p-Xylene	NA	ug/L	< 0.2	< 0.81	< 0.2	< 0.2	< 0.2	< 0.2	260	7.28
Naphthalene	NA	ug/L	< 0.1	< 0.41	< 0.1	< 0.1	< 0.1	< 0.1	< 5.2	0.00
o-Xylene	NA	ug/L	< 0.21	< 0.84	< 0.21	< 0.21	< 0.21	< 0.21	140	3.92
Styrene	NA	ug/L	< 0.22	< 0.86	< 0.22	< 0.22	< 0.22	< 0.22	< 11	0.00
Tetrachloroethene	1500	ug/L	2.5	8	1	0.82	< 0.19	< 0.19	< 9.7	1.97
Tetrahydrofuran	NA NA	ug/L	0.61	< 2.1	< 0.53	< 0.53	< 0.53	< 0.53	21000	588.01
Toluene	NA NA	ug/L	< 0.24	< 0.96	< 0.24	< 0.24	< 0.24	< 0.24	33	0.92
Trans-1,2-Dichloroethene	NA NA	ug/L	0.52	1.4	< 0.21	< 0.21	< 0.21	< 0.21	< 10	0.28
Trans-1,3-Dichloropropene	NA NA	ug/L ug/L	< 0.18	< 0.7	< 0.18	< 0.18	< 0.18	< 0.18	< 8.8	0.00
Trichloroethene	NA NA	ug/L ug/L	1.8	4.6	2.5	0.21	< 0.18	< 0.18	< 8.9	1.13 0.00
Trichlorofluoromethane	NA NA	ug/L ug/L	< 0.2	< 0.81	< 0.2	< 0.2	< 0.2	< 0.2	< 10	0.00
Vinyl Acetate Vinyl Chloride	NA NA	ug/L ug/L	< 0.94 < 0.28	< 3.8 < 1.1	< 0.94	< 0.94 < 0.28	< 0.94	< 0.94	< 47 < 14	0.00
Xylenes, Total	NA	ug/L ug/L	< 0.28	< 0.81	< 0.28	< 0.28	< 0.28 < 0.2	< 0.28 < 0.2	400	11.20
Ayiches, rotal	1.41.7	ug/L	> ∪.∠	~ U.81	> ∪.∠	> 0.∠	< U.∠	< U.∠	400	0.00

Footnotes:

- a/ RWST Raw Water Storage Tank water
- b/ NBBW North Boundary Barrier Wall water
- c/ MW38 Area water
- d/ North End On-Site water
- e/ North End Off-Site water
- f/ MW113 Area water
- $\,$ g/ $\,$ BTS Tank 3310 influent is comprised of North Toe Extraction System water and Landfill
 - Gas Condensate
- h/ Permit Limit limit in ug/L for tetrachloroethene and pounds per day for 1,4-dioxane in discharge according to Industrial Discharge Permit No. 2360-6 issued by the Metro Wastewater Reclamation District (Metro), effective January 5, 2020.
- i/ NA Not Applicable no limit listed in the Metro permit
- $j/\ \mu g/L$ micrograms per liter

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(1,4-DIOXANE)

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(1,4-DIOXANE)

INDIVIDUAL AND COMPOSITE RESULTS

APPENDIX A-4.2.2.1 SUMMARY OF EARLY WARNING INFLUENT WATER QUALITY

1,4-Dioxane

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Date→	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022				
% of Flow→	1.9%	19.8%	6.0%	36.8%	26.6%	5.9%	3.1%				
Sample Port→	TP-110 ^{a/}	TP-120 ^{b/}	TP-140 ^{c/}	TP-150 ^{d/}	TP-160 ^{e/}	TP-170 ^{f/}	TP3310 ^{g/}				
	Conc	Conc	Conc	Conc	Conc	Conc	Conc	Composite		Total	Permit
Compound	(ug/L ^{h/})	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	Conc (ug/L)	gpm ^{i/}	(lbs/day ^{j/})	Limit ^{k/}

Date→	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022				
% of Flow→	1.9%	19.4%	6.2%	37.9%	25.9%	5.6%	3.1%				
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310				
	Conc	Composite		Total	Permit Limit						
Compound	(ug/L)	Conc (ug/L)	gpm	(lbs/day)	(lbs/day)						
1,4-Dioxane	210	670	16	10	1.8	89	15000	609.00	32.4	0.24	0.032

Date →	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022				
% of Flow→	1.9%	19.2%	5.3%	38.0%	26.9%	5.7%	3.1%				
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170 ^{1/}	TP3310				
	Conc	Conc	Conc	Conc	Conc	Conc	Conc	Composite		Total	Permit Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	Conc (ug/L)	gpm	(lbs/day)	(lbs/day)
1.4-Dioxane	310	680	18	13	2.3	100	17000	676.00	32.3	0.26	0.032

Date→	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022				
% of Flow→	1.9%	19.5%	4.7%	38.7%	27.0%	5.3%	2.8%				
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310				
	Conc	Composite		Total	Permit Limit						
Compound	(ug/L)	Conc (ug/L)	gpm	(lbs/day)	(lbs/day)						
1,4-Dioxane	340	750	18	11	1.8	100	20000	724	31.8	0.28	0.032

APPENDIX A-4.2.2.1 SUMMARY OF EARLY WARNING INFLUENT WATER QUALITY 1,4-Dioxane

Date→	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022				
% of Flow→	1.9%	19.3%	5.9%	38.0%	27.1%	5.3%	2.5%				
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310				
	Conc	Composite		Total	Permit Limit						
Compound	Conc (ug/L)	Composite Conc (ug/L)	gpm	Total (lbs/day)	Permit Limit (lbs/day)						

Date→	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022				
% of Flow→	1.8%	19.8%	6.7%	37.7%	26.5%	5.1%	2.4%				
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310				
	Conc	Composite		Total	Permit Limit						
Compound	(ug/L)	Conc (ug/L)	gpm	(lbs/day)	(lbs/day)						
1,4-Dioxane	260	670	20	10	1.4	87	12000	435	32.9	0.17	0.032

Footnotes:

a/ RWST - Raw Water Storage Tank water

b/ NBBW - North Boundary Barrier Wall water

c/ MW38 Area water

d/ North End On-Site water

e/ North End Off-Site water

f/ MW113 Area water

g/ BTS Tank 3310 influent is comprised of North Toe Extraction System water and Landfill Gas Condensate

h/ ug/L = micrograms per liter

i/ gpm = gallons per minute

j/ lbs/day = pounds per day

k/ Permit Limit - limit in ug/L for discharge according to Industrial

Discharge Permit No. 2360-6 issued by the Metro

Wastewater Reclamation District (Metro), effective January 5, 2020.


1/ 1,4-Dioxane analyzed by low-level method (SW8260SIM) and SW8260B

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(1,4-DIOXANE)

TREND ANALYSIS

APPENDIX A-4.2.2.2 1,4-DIOXANE EARLY WARNING TREND ANALYSIS



Analysis prepared using DUMPSTAT and Sen's Test for trend

Graph 1

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

MOLYBDENUM

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(MOLYBDENUM)

INDIVIDUAL AND COMPOSITE RESULTS

APPENDIX A-4.2.3.1 SUMMARY OF EARLY WARNING INFLUENT WATER QUALITY MOLYBDENUM

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Date→	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022	1/3/2022		
% of Flow→	1.9%	19.8%	6.0%	36.8%	26.6%	5.9%	3.1%		
Sample Port→	TP-110 ^{a/}	TP-120 ^{b/}	TP-140 ^{c/}	TP-150 ^{d/}	TP-160 ^{e/}	TP-170 ^{f/}	TP3310 ^{g/}		
									Permit
	Conc	Composite	Limit ^{i/}						
Compound	$(ug/L^{h/})$	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	Conc (ug/L)	(ug/L)
Molybdenum	0.67	0.65	3.6	1.9	2.1	5100	13	303	430

Date→	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022	2/1/2022		
% of Flow→	1.9%	19.4%	6.2%	37.9%	25.9%	5.6%	3.1%]	
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310	1	
									Permit
	Conc	Composite	Limit						
Compound	(ug/L)	Conc (ug/L)	(ug/L)						
Molybdenum	< 0.37	0.51	1	2	2.1	5600	9.9	315	430

Date→	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022	3/1/2022		
% of Flow→	1.9%	19.2%	5.3%	38.0%	26.9%	5.7%	3.1%]	
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170 ^{1/}	TP3310		
									Permit
	Conc	Conc	Conc	Conc	Conc	Conc	Conc	Composite	Limit
Compound	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	Conc (ug/L)	(ug/L)
Molybdenum	0.46	0.38	0.46	1.3	1.9	5800	17	332	430

APPENDIX A-4.2.3.1 SUMMARY OF EARLY WARNING INFLUENT WATER QUALITY MOLYBDENUM

Date→	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022	4/4/2022		
% of Flow→	1.9%	19.5%	4.7%	38.7%	27.0%	5.3%	2.8%	1	
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310		
Compound	Conc (ug/L)	Composite Sample Conc (ug/L)	Permit Limit (ug/L)						
Molybdenum	NA	3401/	430						

Date→	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022	5/2/2022		
% of Flow→	1.9%	19.3%	5.9%	38.0%	27.1%	5.3%	2.5%		
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310		
									Permit
	Conc	Composite	Limit						
Compound	(ug/L)	Conc (ug/L)	(ug/L)						
Molybdenum	1.8	0.54	1	3.2	1.9	6700	10	357	430

Date→	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022	6/6/2022		
% of Flow→	1.8%	19.8%	6.7%	37.7%	26.5%	5.1%	2.4%		
Sample Port→	TP-110	TP-120	TP-140	TP-150	TP-160	TP-170	TP3310		
									Permit
	Conc	Composite	Limit						
Compound	(ug/L)	Conc (ug/L)	(ug/L)						
Molybdenum	0.6	0.46	1.1	1.7	2.5	7400	9.7	379	430

Footnotes:

a/ RWST - Raw Water Storage Tank water

b/ NBBW - North Boundary Barrier Wall water

c/ MW38 Area water

d/ North End On-Site water

e/ North End Off-Site water

f/ MW113 Area water

g/ BTS Tank 3310 influent is comprised of North Toe Extraction System water and Landfill

Gas Condensate

h/ ug/L = micrograms per liter

i/ Permit Limit - limit in ug/L for discharge according to Industrial

Discharge Permit No. 2360-6 issued by the Metro

Wastewater Reclamation District (Metro), effective January 5, 2020.


j/ Concentration of 24 hr composite sample

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(MOLYBDENUM)

TREND ANALYSIS

APPENDIX A-4.2.3.2 MOLYBDENUM EARLY WARNING TREND ANALYSIS



Graph 2

Analysis prepared using DUMPSTAT and Sen's Test for trend

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

RADIONUCLIDES

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(RADIONUCLIDES)

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY RADIONUCLIDES

EARLY WARNING INFLUENT (COMPOSITE SAMPLE) JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Method	Parameter Name ^{a/}	Permit Limit b/	Units ^{c/}	4/5/2021	Final Q ^{d/}
E.900.0	Alpha, Gross	NA ^{e/}	pCi/l	16.8 +/- 5.12	J+
E.900.0	Beta, Gross	NA	pCi/l	15.1 +/- 5.17	UJ+
EPA 600/7-79-081	Plutonium-238	NA	pCi/l	-0.008 +/- 0.025	UJ+
EPA 600/7-79-081	Plutonium-239/240	NA	pCi/l	0.023 +/- 0.04	J+
EPA-RA-05	Radium-228	NA	pCi/l	0.604 +/- 0.241	
ER110 LANL	Americium-241	NA	pCi/l	0.023 +/- 0.051	J+
SM 7500-RA-B	Radium-226	NA	pCi/l	0.418 +/- 0.163	
SM 7500-RA-B	Total Radium	NA	pCi/l	0.316 +/- 0.173	UJ+

a/ Radionuclide parameter list from the Metro permit.

b/ Permit Limit - limit for discharge according to Industrial Discharge Permit No. 2360-6 issued by the Metro

Wastewater Reclamation District (Metro), effective January 5, 2020.

c/ Units : pCi/L = picoCuries per liter

d/ Qualifiers:

U= The analyte was analyzed for and is not present above the level of the associated value.

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

UJ= The analyte analyzed for was not present above the level of the associated value. The associated

numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.

UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.

UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.

J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.

J-= Same as J qualification but with an indication of negative bias in the sample concentration.


J+= Same as J qualification but with an indication of positive bias in the sample concentration.


e/ NA = Not applicable

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY


(RADIONUCLIDES)

TREND ANALYSIS







Analysis prepared using DUMPSTAT and Sen's Test for trend




Analysis prepared using DUMPSTAT and Sen's Test for trend





Graph 4



Analysis prepared using DUMPSTAT and Sen's Test for trend







SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY

(OTHER METALS AND SEMIVOLATILE ORGANIC COMPOUNDS)

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY METALS AND SVOCs

EARLY WARNING INFLUENT (COMPOSITE SAMPLE) JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Method	Parameter Name ^{a/}	Permit Limit b/	Units ^{c/}	4/5/2021 Result	Final Q ^d
Semivolatile Organic Compo			Cints	resure	T III Q
625	1,2,4-Trichlorobenzene	NA ^{e/}	ug/L	1.2	U
625	2,4,6-Trichlorophenol	NA NA	ug/L ug/L	0.53	U
625	2,4,0-1 richlorophenol	NA NA		0.55	U
625	2,4-Dienforophenol	NA NA	ug/L ug/L	11	U
625	2,4-Dinietnylphenol	NA NA	ug/L ug/L	9.4	U
625	2,4-Dinitrophenol 2.4-Dinitrotoluene	NA NA	ug/L ug/L	1.6	U
625	2,6-Dinitrotoluene	NA NA	ug/L ug/L	1.8	U
625	2,0-Dinitrotoluene 2-Chloronaphthalene	NA NA		0.5	U
625	2-Chlorophenol	NA NA	ug/L ug/L	0.91	U
625		NA NA		1	+
625	2-Methylnaphthalene	NA NA	ug/L	1.4	U
625	2-Nitrophenol	NA NA	ug/L		
	3,3'-Dichlorobenzidine		ug/L	2.9	U
625	4,6-Dinitro-2-Methylphenol	NA NA	ug/L	8.5	U
625	4-Bromophenyl phenyl ether	NA NA	ug/L	0.4	U
625	4-Chloro-3-Methylphenol	NA NA	ug/L	2.3	U
625	4-Chlorophenyl phenyl ether	NA	ug/L	1.6	U
625	4-Nitrophenol	NA	ug/L	3	U
625	Acenaphthene	NA	ug/L	0.59	U
625	Acenaphthylene	NA	ug/L	0.46	U
625	Acetophenone	NA	ug/L	0.4	U
625	aniline	NA	ug/L	1.9	U
625	Anthracene	NA	ug/L	0.39	U
625	Benzidine	NA	ug/L	47	U
625	Benzo(a)anthracene	NA	ug/L	0.85	U
625	Benzo(a)pyrene	NA	ug/L	0.68	U
625	Benzo(b)fluoranthene	NA	ug/L	1.2	U
625	Benzo(g,h,i)Perylene	NA	ug/L	0.47	U
625	Benzo(k)fluoranthene	NA	ug/L	0.43	U
625	Benzoic Acid	NA	ug/L	10	U
625	Bis(2-Chloroethoxy)methane	NA	ug/L	0.91	U
625	Bis(2-Chloroethyl)Ether	NA	ug/L	0.78	U
625	Bis(2-Chloroisopropyl) Ether	NA	ug/L	0.26	U
625	bis(2-Ethylhexyl)phthalate	NA	ug/L	2.3	U
625	Butyl benzyl phthalate	NA	ug/L	0.94	U
625	C10	NA	ug/L	0.82	U
625	C18	NA	ug/L	0.66	U
625	Carbazole	NA	ug/L	0.93	J
625	Chrysene	NA	ug/L	0.51	U
625	Dibenz(a,h)anthracene	NA	ug/L	2	U
625	Diethylphthalate	NA	ug/L	0.49	J
625	Dimethylphthalate	NA	ug/L	0.2	U
625	Di-N-Butylphthalate	NA	ug/L	1.1	U
625	Di-n-octylphthalate	NA	ug/L	3.8	U
625	Fluoranthene	NA	ug/L	0.84	U
625	Fluorene	NA	ug/L	0.29	U
625	Hexachlorobenzene	NA	ug/L	0.62	U
625	Hexachlorobutadiene	NA	ug/L	3.1	U
625	Hexachlorocyclopentadiene	NA	ug/L	2.9	U
625	Hexachloroethane	NA	ug/L	0.92	U
625	Indeno(1,2,3-c,d)pyrene	NA	ug/L	2.9	U
625	Isophorone	NA	ug/L	0.2	U
625	Naphthalene	NA	ug/L	0.29	J
625	Nitrobenzene	NA	ug/L	0.76	U
625	N-Nitrosodimethylamine	NA	ug/L	0.27	U
625	N-Nitroso-Di-N-Propylamine	NA	ug/L	0.33	U
625	N-Nitrosodiphenylamine	NA	ug/L	0.41	U

SUMMARY OF TREATMENT PLANT EARLY WARNING INFLUENT WATER QUALITY METALS AND SVOCs

EARLY WARNING INFLUENT (COMPOSITE SAMPLE) JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

		Permit Limit		4/5/2021	
Method	Parameter Name ^{a/}	b /	Units ^{c/}	Result	$Final \ Q^{d/}$
625	Pentachlorophenol	NA	ug/L	19	U
625	Phenanthrene	NA	ug/L	0.64	U
625	5 Phenol		ug/L	1.9	U
625	625 Pyrene		ug/L	0.35	U
625	Pyridine	NA	ug/L	1.6	U
Metals		•		•	•
E200.8	Molybdenum	430	ug/L	340	
E200.8	Selenium	660	ug/L	18	
E200.8	Cadmium	3400	ug/L	0.088	U
E200.8	Copper	6100	ug/L	1.9	
E200.8	Zinc	15600	ug/L	7.3	
E200.8	Nickel	5600	ug/L	4.6	
EPA 200.7 Rev 4.4	Arsenic	330	ug/L	5.7	
EPA 200.7 Rev 4.4	Lead	2200	ug/L	2.7	U
EPA 200.7 Rev 4.4	EPA 200.7 Rev 4.4 Silver		ug/L	2	U
EPA 200.7 Rev 4.4	EPA 200.7 Rev 4.4 Chromium		ug/L	0.66	U
EPA 245.1	Mercury	130	ug/L	0.027	U

a/ Parameter list from the Metro permit.

b/ Permit Limit - limit in ug/L for discharge according to Industrial Discharge Permit No. 2360-6 issued by the Metro

Wastewater Reclamation District (Metro), effective January 5, 2020.

c/ Units : μ g/L = micrograms per liter

d/ Qualifiers: U=

The analyte was analyzed for and is not present above the level of the associated value.

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

UJ= The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.

UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.

UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.

J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.

J-= Same as J qualification but with an indication of negative bias in the sample concentration.

J+= Same as J qualification but with an indication of positive bias in the sample concentration.

e/ NA = Not applicable

APPENDIX B

WASTE DISPOSAL RECORDS

APPENDIX B-1

SUMMARY OF WASTE DISPOSED

TABLE B-1

SUMMARY OF WASTE DISPOSED AND TREATED OFFSITE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Date	Manifest No.	Waste Description	Quantity	Units	Facility	EPA Authorization ^{a/}
4/6/2022	017390122FLE	Carbon From the Treatment of FO39 NTES Groundwater (Profile #	8,750	lbs ^{b/}	Clean Harbors	Yes
		CH599250)			Kimball, NE	
5/26/2022	10722502	WTP Sludge (Profile # 1004322)	15	CY ^{c/}	$\mathrm{DADS}^{\mathrm{d}/}$	Not Required by WMP ^{e/}

a/ Acceptance of the treatment and disposal facility was obtained from EPA before shipment offsite.

EPA authorizations are maintained in the project files on site and are available for review.

- b/ lbs = Pounds
- c/ CY = cubic yards
- d/ DADS = Denver Arapaho Disposal Site
- e/ WMP = Waste Management Plan

APPENDIX B-2

WASTE MANIFESTS

Generator acknowledges that no material change has occurred either in the characteristics or in the process generating the material.

PPW

D9 2108332208

enerating the material Form Approved, OMB No. 2050-0039 Please print or type. UNIFORM HAZARDOUS 1. Generator 1D Number 2. Page 1 of 3. Emergency Response Phone 3901 COD980953723 **WASTE MANIFEST** 1 (800) 483-3718 Generator's Site Address (if different than mailing address) 5. Generator's Name and Mailing Address Protection Cleanup Trust
Lowry Environmental Protection Cleanup Trust 7220 West Jefferson Avenue, Suite 406 3500 South Gun Club Road Lakewood, CO 80235 Aurora_CO 80118 Generator's Phone: (303) 940-3426 ATTN:Tim Shangraw U.S. EPA ID Number 6. Transporter 1 Company Name Clean Harbors Environmental Services, Inc. MAD039322250 U.S. EPA ID Number 7. Transporter 2 Company Name 8. Designated Facility Name and Site Address U.S. EPA ID Number Clean Harbors Environmental Services. Inc. 2247 South Highway 71 Kimball, NE 69145 NED981723513 Facility's Phone: (308) 235-4012 9b. U.S. DOT Description (including Proper Shipping Name, Hazard Class, ID Number, 10. Containers 11 Total 12. Unit 13. Waste Codes and Packing Group (if any)) Quantity Wt./Vol. нМ No. Туре NA3077, HAZARDOUS WASTE, SOLID, N.O.S., (F039), 9, PG III F039 GENERATOR \$750 14. Special Handling Instructions and Additional Information

1 CR599250 ERG#171 Contract retained by generator confers agency authority on within transporter to add or substitute additional transporters on generator's behalf for purposes of transportation efficiency.convenience.or salety 15. GENERATOR'S/OFFEROR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by the proper shipping name, and are classified, packaged, marked and labeled/placarded, and are in all respects in proper condition for transport according to applicable international and national governmental regulations. If export shipment and I am the Primary Exporter, I certify that the contents of this consignment conform to the terms of the attached EPA Acknowledgment of Consent. I certify that the waste minimization statement identified in 40 CFR 262.27(a) (If I am a large quantity generator) or (b) (if I am a small quantity generator) is true. Month Day Year Generator's/Offeror's Printed/Typed Name behaff of Loune ort of entry/exit: Import to U.S. Date leaving U.S. Transporter signature (for exports only): 17. Transporter Acknowledgment of Receipt of Materials Signature Month Year Transporter 1 Printed/Typed Name 6 TAYLUT 2 Year Transporter 2 Printed/Typed Nam 18. Discrepancy 18a. Discrepancy Indication Space ∏туре Partial Rejection __ Full Rejection Quantity Residue Manifest Reference Number: U.S. EPA ID Number 18b. Alternate Facility (or Generator) Facility's Phone: Day DESIGNATED 18c. Signature of Alternate Facility (or Generator) 19. Hazardous Waste Report Management Method Codes (i.e., codes for hazardous waste treatment, disposal, and recycling systems) H040 20. Designated Facility Owner or Operator: Certification of receipt of hazardous materials covered by the manifest except as noted in Item 18a Signature Printed/Typed Name 22 tomas **DESIGNATED** FACILITY TO EPA's e-MANIFEST SYSTEM EPA Form 8700-22 (Rev. 12-17) Previous editions are obsolete.

Clean Harbors has the appropriate permits for and will accept the waste the generator is shipping.



Land Disposal Restriction Notification Form

Page: 1 of 1

Printed Date :Apr 6, 2022

MANIFEST IN	VFOR	MATION								
Genera	ator :	Lowry Envir	onmental Protecti	on Cleanup Trust		Manifest Tracking	g Info.			
Addr	ress:	3500 South Aurora,CO	Gun Club Road 80118			017390122FLE				
EPA II			953723		Sales Order No: 2108332208					
Line Item:		ge No:	Profile No:	Treatability Gro	ity Group: LDR Disposal Category					
1.	1		CH599250	NON-WASTEW	WATER 2 (This is subject to LDR.)					
EPA Waste C F039	Code			LDR Chemical	NONE	 				
Chemical				LDIV Olientical	Underlying Hazardous Constituents	of	Contaminants Subject to Treatment			
1,1-DICHLOF TRANS-1,2-D			ENE		N N	N N	N N			
			<u>Ce</u>	ertification			Applies to Manifest Line Items			
Pursuant to 4 Part 268.	0 CFF	R 268.7(a), I	hereby notify that	this shipment conta	ins waste res	stricted under 40 CFR	1.			
Waste analys Signature : Title :	sis dat	a, where ava	ailable, is attached	Print No	ame 7 .	-60 ff Hs an b	ehalf of Larry			



NON-HAZARDOUS MANIFEST 2277

NON WATER TO A	1. Generator	s US EPA ID No.	Manifest Doc	No.	2. Page 1	of	A 1 a	l	
NON-HAZARDOUS MANIFEST	COD	98095372	2		2.1 age .		UOL	983	7
3. Generator's Mailing Address: LOWRY ENVIRONMENTAL PR 3500 S GUN CLUB RD		Generator's Site Address (n				est Number	10	722502	
	710-9419	City, state up Cour					Generato		
5. Transporter 1 Company Name		6. US EPA	ID Number		(Indianical)				
Trous Que 15 cmpany Name		115 - 6 4				Fransporter's I			orier (D
7. Transporter 2 Company Name				- W	D. Transp	orter's Phone	e Trai	ispalier.	1 Пърта
Transport+ 2 Con pany Name			ID Number		E. State Transporter's ID Late Lasponter II				
9. Designated Facility Name and Site DENVER ARAPAHOE DISPOSA		10. US EPA	ID Number			orter's Phone		ispence.	2 Filone Elimen
3500 S GUNCLUB RD		Lin Lya			G. State F			= Facility	
AURORA, CO 80018		(1960) - (1960) - (1960)			H. State F	acility Phone	720	-876-26	20
	37				The second second				
11. Description of Waste Materials			12. Co No.	ntainers	13. Total	14. Unit		Misc. Comm	ente
a. NON-REGULATED SOLID – V	WATER TREATM	IENT PLANT SLUDGE	RIGOL	RM-	Quantity	vt./vol.	10	Conysten	-
1	ofile # 100432	22					1102		157
b. Waste Name			Parties	Type	Total	Wt./vol.		Commen	+ 1
WM Profile #	VIII Prolie	Number						- Pulls	
c. Waste Name				Espa	- Yetal One.	Phylye		Commen	ts is
WM Profile # REGULATORY AGENCY:	MM Profile	Nitialiser					Barra III	and the	
Colorado Department of Public I 4300 Cherry Creek Drive South Denver, CO 80222-1530	dealth and Envi	ironment	file.	-vpi	Fotal Grv.	MAL / Vision	(
J. Additional Descriptions for Mater	rials Listed About		All III	7/12/11/11/11					
		OFESSIONAL GROUP		al Location					
			Cell Grid		27 (1	Level		
15. Special Handling Instructions and	Additional Inform	nation	Gild		1				100000
Special Handing Instructions Purchase Order # Purchase Order		EMERGENCY CO	NTACT / PHO	ONE NO :	1-800-42	4-9300 241	JP TOU	FDFF	
16. GENERATOR'S CERTIFICATE:									
I hereby certify that the above-descril accurately described, classified and particles of the printed Name	bed materials are ackaged and are i ackaged and are i	n proper condition for transpo	rtation accor	art 261 or a ding to app	ny applicable licable regul	e state law, ha ations.	ive been fi	ully and	
	of the Low	y Trot Alex	l€of"				Month 5	Day 17	Year 2.2
Printed Name		Signature		1					
18. Transporter 2 Acknowledgement	FOLEY of Receipt of Mat	(1)	y Ju	ley			Month 9	26	Year 22
Printed Name	,	Signature					Month	Day	Year
19. Certificate of Final Treatment/Dis	noral								
I certify, on behalf of the above listed applicable laws, regulations, permits a	treatment facility nd licenses on th	e dates listed above.				s managed in	complianc	ce with all	
20. Facility Owner or Operator: Certif	ication of receipt	of non-hazardous materials co	overed by thi	s manifest.		1000		1	
Printed Name	Mou	Signature		1_	_		Month	Day	Year
White-TREATMENT STORAGE DISON	CAL FACILITY COR	w/\	1				1	4	111

Blue- GENERATOR #2 COPY

Yellow- GENERATOR #1 COPY

APPENDIX C

GROUNDWATER

APPENDIX C-1

NEW MONITORING WELL LOGS

NO NEW MONITORING WELLS WERE INSTALLED FROM JANUARY THROUGH JUNE $2022\,$

APPENDIX C-2 MONITORING WELL HYDROGRAPHS

See folder Appendix C-2

APPENDIX C-3

COMPLIANCE EVALUATION STATISTICAL TESTING AND ANALYTE STATISTICAL TREND ANALYSIS PLOTS

The material contained in this appendix represents the output of the statistical evaluations completed EPA's ProUCL Software and manual calculations for regression analysis.

APPENDIX C-3.1

COMPLIANCE EVALUATION STATISTICAL TESTING

Data Summary Table

TABLE C-3.1 COMPLIANCE WELL DATA FOR STATISTICS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
B-313 ^{c/}	1,4-Dioxane	4/16/2019	14		ug/L	0.9
B-313 ^{c/}	1,4-Dioxane	7/16/2019	2.3		ug/l	0.9
B-313 ^{c/}	1,4-Dioxane	10/15/2019	7.2		ug/l	0.9
B-313 ^{c/}	1,4-Dioxane	1/28/2020	20		ug/L	0.9
B-313 ^{c/}	1,4-Dioxane	4/28/2020	21		ug/L	0.9
B-313 ^{c/}	1,4-Dioxane	7/28/2020	18		ug/L	0.9
B-313 ^{c/}	1,4-Dioxane	12/9/2020	17		ug/L ug/L	0.9
B-313 ^{c/}	,	2/17/2021				
B-313 ^{c/}	1,4-Dioxane		16		ug/L	0.9
	1,4-Dioxane	5/18/2021	15		ug/L	0.9
B-313 ^{c/}	1,4-Dioxane	11/16/2021	17		ug/L	0.9
B-313 ^{c/}	Nitrogen, Nitrate	1/3/2019	21000		ug/L	5000
B-313 ^{c/}	Nitrogen, Nitrate	4/16/2019	22000		ug/L	10000
B-313 ^{c/}	Nitrogen, Nitrate	7/16/2019	47000		ug/L	10000
B-313 ^{c/}	Nitrogen, Nitrate	10/17/2019	40000		ug/L	2500
B-313 ^{c/}	Nitrogen, Nitrate	1/28/2020	30000		ug/L	2500
B-313 ^{c/}	Nitrogen, Nitrate	4/28/2020	28000		ug/L	10000
B-313 ^{c/}	Nitrogen, Nitrate	7/28/2020	32000		ug/L	2500
B-313 ^{c/}	Nitrogen, Nitrate	2/17/2021	22000		ug/L	2500
B-313 ^{c/}	Nitrogen, Nitrate	5/18/2021	39000	J	ug/L	500
B-313 ^{c/}	Nitrogen, Nitrate	8/12/2021	55000	J	ug/L	2500
B-326-UD	1,4-Dioxane	2/12/2020	7.7	,	ug/L ug/L	0.9
B-326-UD	1,4-Dioxane	5/27/2020	6.9		ug/L ug/L	0.9
B-326-UD	1,4-Dioxane	9/2/2020	6.7		ug/L	0.9
B-326-UD	1,4-Dioxane	12/10/2020	6.4		ug/L	0.9
B-326-UD	1,4-Dioxane	2/4/2021	6.7		ug/L	0.9
B-326-UD	1,4-Dioxane	6/1/2021	6		ug/L	0.9
B-326-UD	1,4-Dioxane	8/30/2021	6.1		ug/L	0.9
B-326-UD	1,4-Dioxane	10/12/2021	5		ug/L	0.9
B-326-UD	1,4-Dioxane	2/8/2022	4.5		ug/L	0.9
B-326-UD	1,4-Dioxane	4/14/2022	4.6		ug/L	0.9
B-326-UD	Nitrogen, Nitrate	4/28/2015	19000		ug/L	2500
B-326-UD	Nitrogen, Nitrate	5/1/2017	40000		ug/L	2500
B-326-UD	Nitrogen, Nitrate	7/31/2018	66000		ug/L	5000
B-326-UD	Nitrogen, Nitrate	3/21/2019	49000		ug/L	2500
B-326-UD	Nitrogen, Nitrate	6/17/2019	9300		ug/L	500
B-326-UD	Nitrogen, Nitrate	8/26/2019	990		ug/L	500
B-326-UD	Nitrogen, Nitrate	12/11/2019	700		ug/L	500
B-326-UD	Nitrogen, Nitrate	2/12/2020	730		ug/L	500
B-326-UD	Nitrogen, Nitrate	9/2/2020	90	U	ug/L	500
B-326-UD	Nitrogen, Nitrate	2/4/2021	90	U	ug/L	500
B-326-WD	1,4-Dioxane	2/12/2020	10		ug/L	0.9
B-326-WD	1,4-Dioxane	5/28/2020	11		ug/L	0.9
B-326-WD B-326-WD	1,4-Dioxane	8/26/2020 11/23/2020	3.5		ug/L	0.9
B-326-WD B-326-WD	1,4-Dioxane	2/3/2021	17		ug/L ug/L	0.9
B-326-WD	1,4-Dioxane	6/1/2021	7.5		ug/L ug/L	0.9
B-326-WD	1,4-Dioxane	8/30/2021	0.77	J	ug/L ug/L	0.9
B-326-WD	1,4-Dioxane	10/12/2021	1	3	ug/L ug/L	0.9
B-326-WD	1,4-Dioxane	2/8/2022	3.6		ug/L ug/L	0.9
B-326-WD	1,4-Dioxane	4/14/2022	3.2		ug/L ug/L	0.9
BM-11X-100N	Tetrachloroethene	10/20/2017	4.6		ug/L ug/L	1
BM-11X-100N	Tetrachloroethene	4/17/2018	5.9		ug/L	1

TABLE C-3.1 COMPLIANCE WELL DATA FOR STATISTICS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
BM-11X-100N	Tetrachloroethene	10/12/2018	6.3		ug/L	1
BM-11X-100N	Tetrachloroethene	4/23/2019	6.5		ug/L	1
BM-11X-100N	Tetrachloroethene	10/14/2019	6.8		ug/L	1
BM-11X-100N	Tetrachloroethene	4/30/2020	6.9		ug/L	1
BM-11X-100N	Tetrachloroethene	11/16/2020	7.2		ug/L	1
BM-11X-100N	Tetrachloroethene	5/6/2021	6	J	ug/L	1
BM-11X-100N	Tetrachloroethene	10/28/2021	5.4		ug/L	1
BM-11X-100N	Tetrachloroethene	5/18/2022	4.9		ug/L	1
BM-11X-100N	Trichloroethene	10/20/2017	3.6		ug/L	1
BM-11X-100N	Trichloroethene	4/17/2018	4.7		ug/L	1
BM-11X-100N	Trichloroethene	10/12/2018	4.5		ug/L	1
BM-11X-100N	Trichloroethene	4/23/2019	4.3		ug/L	1
BM-11X-100N	Trichloroethene	10/14/2019	4.9		ug/L	1
BM-11X-100N	Trichloroethene	4/30/2020	5		ug/L	1
BM-11X-100N	Trichloroethene	11/16/2020	5.7		ug/L	1
BM-11X-100N	Trichloroethene	5/6/2021	5.5		ug/L	1
BM-11X-100N	Trichloroethene	10/28/2021	4.8		ug/L	1
BM-11X-100N	Trichloroethene	5/18/2022	4.4		ug/L	1
BM-15N6	Nitrogen, Nitrate	10/24/2017	43000		ug/L	2500
BM-15N6	Nitrogen, Nitrate	4/23/2018	42000		ug/L	5000
BM-15N6	Nitrogen, Nitrate	10/19/2018	49000		ug/L	10000
BM-15N6	Nitrogen, Nitrate	4/26/2019	35000	_	ug/L	10000
BM-15N6	Nitrogen, Nitrate	12/12/2019	42000	J	ug/L	500
BM-15N6	Nitrogen, Nitrate	5/13/2020	35000		ug/L	2500
BM-15N6	Nitrogen, Nitrate	2/23/2021	32000		ug/L	5000
BM-15N6	Nitrogen, Nitrate	4/22/2021	31000		ug/L	2500
BM-15N6	Nitrogen, Nitrate	10/13/2021	30000		ug/L	5000
BM-15N6 GW-109 ^{d/}	Nitrogen, Nitrate	4/25/2022	34000		ug/L	5000
	1,4-Dioxane	5/31/2016	2.1		ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	11/2/2016	3.3		ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	5/10/2017	0.76	J	ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	10/27/2017	0.95		ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	5/4/2018	0.54	J	ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	7/31/2018	0.54	J	ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	1/3/2019	0.53	J	ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	4/16/2019	9.7		ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	3/2/2020	41		ug/L	0.9
GW-109 ^{d/}	1,4-Dioxane	6/1/2020	20		ug/L	0.9
GW-109 ^{d/}	Bromodichloromethane	11/16/2015	2.8		ug/L	1
GW-109 ^{d/}	Bromodichloromethane	5/31/2016	0.44	J	ug/L	1
GW-109 ^{d/}		11/2/2016		1		
GW-109 ^{d/}	Bromodichloromethane		0.17	U	ug/L	1
	Bromodichloromethane	5/10/2017	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	10/27/2017	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	5/4/2018	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	7/31/2018	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	1/3/2019	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	4/16/2019	0.17	U	ug/L	1
GW-109 ^{d/}	Bromodichloromethane	6/1/2020	0.17	U	ug/L	1
GW-109 ^{d/}	Chloroform	11/16/2015	4.4		ug/L	1
GW-109 ^{d/}	Chloroform	5/31/2016	0.81	J	ug/L	1
GW-109 ^{d/}	Chloroform	11/2/2016	0.3	J	ug/L	1
GW-109 ^{d/}	Smorotomi	5/10/2017	0.5	U	∽ 5/ L	+

TABLE C-3.1 COMPLIANCE WELL DATA FOR STATISTICS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Reporting Limit
GW-109 ^{d/}	Chloroform	10/27/2017	0.16	U	ug/L	1
GW-109 ^{d/}	Chloroform	5/4/2018	0.16	U	ug/L	1
GW-109 ^{d/}	Chloroform	7/31/2018	0.16	U	ug/L	1
GW-109 ^{d/}	Chloroform	1/3/2019	0.16	U	ug/L	1
GW-109 ^{d/}	Chloroform	4/16/2019	0.16	U	ug/L ug/L	1
GW-109 ^{d/}		6/1/2020	0.16	U		1
MW106-UD	Chloroform 1.4-Dioxane		0.16	U	ug/L	<u> </u>
MW106-UD MW106-UD	1,4-Dioxane	11/21/2006	6.5	U	ug/l	5
MW106-UD MW106-UD	1,4-Dioxane	2/28/2007 5/25/2007	0.5	U	ug/l ug/l	5
MW106-UD	1,4-Dioxane	8/12/2009	0.5	U	ug/l	5
MW106-UD	1,4-Dioxane	7/26/2011	0.5	U	ug/l	5
MW106-UD	1,4-Dioxane	8/1/2013	0.5	U	ug/l	5
MW106-UD	1,4-Dioxane	7/13/2015	0.5	U	ug/l	5
MW106-UD	1,4-Dioxane	7/26/2017	0.15	U	ug/L	0.9
MW106-UD	1,4-Dioxane	8/9/2018	0.15	U	ug/L ug/L	0.9
MW106-UD	1,4-Dioxane	8/26/2020	0.09	U	ug/L ug/L	0.9
MW23-C-SD	1,4-Dioxane	3/15/2006	0.5	U	ug/L ug/l	5
MW23-C-SD	1,4-Dioxane	8/21/2007	0.5	UJ	ug/l	5
MW23-C-SD	1,4-Dioxane	8/19/2009	0.5	U	ug/l	5
MW23-C-SD	1,4-Dioxane	8/11/2011	0.5	U	ug/l	5
MW23-C-SD	1,4-Dioxane	8/27/2013	0.5	U	ug/l	5
MW23-C-SD	1,4-Dioxane	9/2/2015	0.15	U	ug/L	0.9
MW23-C-SD	1,4-Dioxane	8/1/2017	0.15	U	ug/L ug/L	0.9
MW23-C-SD	1,4-Dioxane	7/31/2018	0.15	U	ug/L ug/L	0.9
MW23-C-SD	1,4-Dioxane	9/15/2020	1.4		ug/L ug/L	0.9
MW23-C-SD	1,4-Dioxane	2/18/2021	0.09	U	ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	11/1/2017	12		ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	4/26/2018	9.3		ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	8/7/2018	13		ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	5/1/2019	7.1		ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	10/22/2019	2.4		ug/l	0.9
MW38-830N-230E	1,4-Dioxane	1/28/2020	2		ug/L	0.9
MW38-830N-230E	1,4-Dioxane	11/12/2020	2.1		ug/L ug/L	0.9
MW38-830N-230E	1,4-Dioxane	4/15/2021	4.5		ug/L	0.9
MW38-830N-230E	1,4-Dioxane	10/14/2021	4.6		ug/L	0.9
MW38-830N-230E	1,4-Dioxane	4/13/2022	4.2		ug/L ug/L	0.9
MW38-830N-230E	Chloroform	11/1/2017	6.9		ug/L ug/L	1
MW38-830N-230E	Chloroform	4/26/2018	6.2		ug/L	1
MW38-830N-230E	Chloroform	8/7/2018	5.9		ug/L	1
MW38-830N-230E	Chloroform	5/1/2019	5.4		ug/L	1
MW38-830N-230E	Chloroform	10/22/2019	2.1		ug/L	1
MW38-830N-230E	Chloroform	1/28/2020	2.1		ug/L	1
MW38-830N-230E	Chloroform	11/12/2020	2.6		ug/L	1
MW38-830N-230E	Chloroform	4/15/2021	4.3		ug/L	1
MW38-830N-230E	Chloroform	10/14/2021	3.7		ug/L	1
MW38-830N-230E	Chloroform	4/13/2022	3.8		ug/L	1
MW62-WDR	1,4-Dioxane	3/7/2018	3.9		ug/L	0.9
MW62-WDR	1,4-Dioxane	5/10/2018	4.2		ug/L	0.9
MW62-WDR	1,4-Dioxane	7/31/2018	3.8		ug/L	0.9
MW62-WDR	1,4-Dioxane	5/14/2019	3.9		ug/L	0.9
MW62-WDR	1,4-Dioxane	12/17/2019	3.5		ug/l	0.9
MW62-WDR	1,4-Dioxane	5/14/2020	3.4		ug/L	0.9
MW62-WDR	1,4-Dioxane	11/11/2020	3.2		ug/L	0.9

TABLE C-3.1

COMPLIANCE WELL DATA FOR STATISTICS JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

						Reporting
Well ID	Constituent/Parameter	Date Sampled	Result	Qualifier ^{a/}	Units ^{b/}	Limit
MW62-WDR	1,4-Dioxane	4/27/2021	3.3		ug/L	0.9
MW62-WDR	1,4-Dioxane	10/27/2021	3.2		ug/L	0.9
MW62-WDR	1,4-Dioxane	4/19/2022	2.9		ug/L	0.9
MW62-WDR	Nitrogen, Nitrate	3/7/2018	110000		ug/L	10000
MW62-WDR	Nitrogen, Nitrate	5/10/2018	120000		ug/L	25000
MW62-WDR	Nitrogen, Nitrate	7/31/2018	120000		ug/L	10000
MW62-WDR	Nitrogen, Nitrate	5/14/2019	120000		ug/L	10000
MW62-WDR	Nitrogen, Nitrate	12/17/2019	120000		ug/L	10000
MW62-WDR	Nitrogen, Nitrate	5/14/2020	130000		ug/L	10000
MW62-WDR	Nitrogen, Nitrate	11/11/2020	130000	J	ug/L	2500
MW62-WDR	Nitrogen, Nitrate	4/27/2021	120000		ug/L	25000
MW62-WDR	Nitrogen, Nitrate	10/27/2021	110000		ug/L	25000
MW62-WDR	Nitrogen, Nitrate	4/19/2022	120000		ug/L	25000
MW62-WDR	Nitrogen, Nitrite	3/7/2018	5400		ug/L	1000
MW62-WDR	Nitrogen, Nitrite	5/10/2018	4000		ug/L	500
MW62-WDR	Nitrogen, Nitrite	7/31/2018	2400		ug/L	1000
MW62-WDR	Nitrogen, Nitrite	5/14/2019	1900		ug/L	1000
MW62-WDR	Nitrogen, Nitrite	12/17/2019	980	U	ug/L	10000
MW62-WDR	Nitrogen, Nitrite	5/14/2020	1500	J	ug/L	10000
MW62-WDR	Nitrogen, Nitrite	11/11/2020	890		ug/L	500
MW62-WDR	Nitrogen, Nitrite	4/27/2021	1800		ug/L	1000
MW62-WDR	Nitrogen, Nitrite	10/27/2021	2200		ug/L	500
MW62-WDR	Nitrogen, Nitrite	4/19/2022	2100	J	ug/L	2500
MW77-WD	1,4-Dioxane	10/26/2017	5.3		ug/L	0.9
MW77-WD	1,4-Dioxane	5/3/2018	9		ug/L	0.9
MW77-WD	1,4-Dioxane	8/2/2018	2.6		ug/L	0.9
MW77-WD	1,4-Dioxane	5/2/2019	3		ug/L	0.9
MW77-WD	1,4-Dioxane	10/22/2019	12		ug/l	0.9
MW77-WD	1,4-Dioxane	5/4/2020	5		ug/L	0.9
MW77-WD	1,4-Dioxane	10/28/2020	16		ug/L	0.9
MW77-WD	1,4-Dioxane	4/21/2021	4.3		ug/L	0.9
MW77-WD	1,4-Dioxane	10/27/2021	11		ug/L	0.9
MW77-WD	1,4-Dioxane	4/18/2022	12		ug/L	0.9

a/ Final Q definitions:

The associated value is the method detection limit as required by the statistical procedure in the GWMP J= The analyte was analyzed for, and was positively identified, but the associated numerical value

may not be consistent with the amount actually present in the environmental sample.

U= The analyte was analyzed for and is not present above the level of the associated value. The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.


b/ μ g/L = micrograms per liter

c/ B-313 is listed here because it exceeded the performance standard for 1,4-dioxane and nitrate in the last 10 samples collected. Statistics were not performed because the well was dry and no sample could be collected in 1st and 2nd quarter 2022.


d/ GW-109 is listed here because it exceeded the performance standard for 1,4-dioxane, bromodichloromethane, and chloroform in the last 10 samples collected. Statistics were not performed because the well was dry and no sample could be collected in 1st and 2nd quarter 2022. This well has been dry since 3rd quarter 2020.

APPENDIX C-3.2 COMPLIANCE EVALUATION STATISTICAL TESTING Mann-Kendall Trend Analysis


	Α	В	С	D	E	F	G	Н		J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options									
3	Dat	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	21:04 AM						
4			From File	COMPLIAN	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK.x	ds		
5		Ful	I Precision	OFF				•				
6		Confidence	Coefficient	0.95								
7		Level of Si	ignificance	0.05								
8												
33		1,4-[Dioxane-b-32	26-ud								
34												
35			eneral Statist									
36				Reported (m)	10							
37				ssing Events	0							
38				Events Used	10							
39		Nun	nber Values I	Reported (n)	10							
40				Minimum	4.5							
41 42				Maximum	7.7							
42				Mean	6.06							
44			Geo	metric Mean	5.973							
45			0+	Median	6.25							
46				ard Deviation	1.055							
47			Coemicien	t of Variation	0.174							+
48		Ma	nn-Kendall 1	Toet								+
49		IVIA		est Value (S)	-38							
50				ated p-value	0							
51				eviation of S	11.14							
52				d Value of S	-3.323							
53				mate p-value								
54			, (pp. 0/iii	op raido								+
	Statistically	significant e	vidence of a	decreasing								
	trend at the	specified lev	vel of signific	cance.								
											1	




	Α	В	С	D	Е	F	G	Н		J	K	L
1			-	Mann-Kenda	all Trend Te	st Analysis		-				
2		User Selecte	ed Options			-						
3		e/Time of Co		ProUCL 5.2	8/5/2022 8:2	29:40 AM						
4			From File	COMPLIAN	CE DATA by	Constituent	1H2022 Pro	UCL Input M	IJS for MK_c	.xls		
5		Ful	II Precision	OFF								
6		Confidence	Coefficient	0.95								
7		Level of S	ignificance	0.05								
8												
33 34 35		Nitroge	en, Nitrate-b-	326-ud								
34												
35			eneral Statist									
36 37			er of Events F		10							
37			lumber of Mis		0							
38			or Reported I		10							
39 40		Nun	nber Values I		10							
40				Minimum	45							
41					66000							
42 43			0	Mean								
44			Geo	metric Mean	2735							
45			Ctondo	Median rd Deviation	5145							
46				t of Variation	1.313							
47			Coemicien	OI Vallation	1.313							
48		Ma	nn-Kendall 1	Teet								
49		IVIG		est Value (S)	-32							
49 50				ated p-value	0.001							
51				eviation of S	11.14							
52 53			Standardize		-2.784							
53				nate p-value	0.00269							
54			:	p raido								
55	Statistically	significant e	evidence of a	decreasing								
56	trend at the	specified lev	vel of signific	ance.								
-00	u enu at tile	Sharillen ia	vei oi sigiiillo	alice.								




	Α	В	С	D	Е	F	G	Н	l	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			_						
3	Dat	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:2	21:04 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK.>	ds		
5			I Precision	OFF								
6		Confidence (Coefficient	0.95								
7		Level of Si	gnificance	0.05								
8												
57		1,4-C	Dioxane-b-32	2 <mark>6-wd</mark>								
58												
59			eneral Statist									
60				Reported (m)	10							
61				ssing Events	0							
62				Events Used	10							
63		Nun	nber Values I	Reported (n)	10							
64				Minimum	0.77							
65 66				Maximum	17							
67				Mean	6.147							
68			Geo	metric Mean	4.198							
69			Ctanda	Median ard Deviation	3.75 5.171							
70				t of Variation	0.841							
71			Coemicien	t Of Variation	0.041							
72		Ma	nn-Kendall 1	Test .								
73		IVIC		est Value (S)	-17							
74				ated p-value	0.078							
75				eviation of S	11.18							
76				d Value of S	-1.431							
77				nate p-value	0.0762							
78												
79	Insufficient of	evidence to	identify a sid	nificant								
80	trend at the	specified le	vel of signific	cance.								
	Jila at tilo	IV	· · · · · · · · · · · · · · · · · · ·			1				-	1	




	Α	В	С	D	Е	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			_						
3	Date	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:3	32:58 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	IJS for MK_e	e.xls		
5			I Precision	OFF								
6		Confidence (0.95								
7		Level of Si	gnificance	0.05								
8												
9		Tetrachlor	oethene-bm	-11x-100n								
10												
11			neral Statist									
12 13				Reported (m)	10							
14				ssing Events	0							
15				Events Used	10							
16		Nun	nber values i	Reported (n) Minimum	10							
17				Maximum	4.6 7.2							
18				Mean	6.05							
19			Geo	metric Mean	5.991							
20			Geo	Median	6.15							
21			Standa	ard Deviation	0.866							
22				t of Variation	0.143							
23			30007011		JJ							
24		Ma	nn-Kendall 1	Test .								
25 26			M-K Te	est Value (S)	5							
26			Tabul	ated p-value	0.364							
27			Standard D	eviation of S	11.18							
28			Standardize	d Value of S	0.358							
29			Approxir	mate p-value	0.36							
30												
	Insufficient e											
32	trend at the	specified le	vel of signification	cance.								




	Α	В	С	D	Е	F	G	Н		J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options									
3	Date	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:1	8:09 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK_	f.xls		
5			I Precision	OFF								
6		Confidence (Coefficient	0.95								
7		Level of Si	gnificance	0.05								
8												
9		Trichloro	ethene-bm-	11x-100n								
10												
11			eneral Statist									
12				Reported (m)	10							
13				ssing Events	0							
14				Events Used	10							
15		Nun	nber Values I	Reported (n)	10							
16 17				Minimum	3.6							
18				Maximum	5.7							
19			0	Mean	4.74							
20			Geo	metric Mean	4.705 4.75							
21			Standa	Median ard Deviation	0.602							
22				t of Variation	0.002							
23			Coemicien	t or variation	0.127							
24		Ma	nn-Kendall 1	Test .								
25		IVIC		est Value (S)	15							
26				ated p-value	0.108							
27				eviation of S	11.18							
28				d Value of S	1.252							
29				mate p-value	0.105							
30												
31	Insufficient e	evidence to	identify a sig	ınificant								
32	trend at the	specified le	vel of signifi	cance.								
									1		1	




1				_	E	F	G	Н		J 3	K	L L
$\overline{}$				Mann-Kenda	all Trend Tes	st Analysis						
2		User Selecte	ed Options			_						
3	Date	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:2	9:40 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK_d	c.xls		
5			l Precision	OFF								
6		Confidence (Coefficient	0.95								
7		Level of Si	gnificance	0.05								
8												
57		Nitroge	n, Nitrate-bi	m-15n6								
58												
59			neral Statist									
60				Reported (m)	10							
61				ssing Events	0							
62				Events Used	10							
63		Num	iber Values I	Reported (n)	10							
64 65				Minimum								
66					49000							
67			Coo	Mean metric Mean								
68			Geo	Median								
69			Standa	ard Deviation	6290							
70				t of Variation	0.169							
71			Cocincient	t or variation	0.103							
72		Mai	nn-Kendall 1	Test								
73		.,,,,		est Value (S)	-31							
74				ated p-value	0.002							
75				eviation of S	11.09							
76				d Value of S	-2.705							
77			Approxir	mate p-value	0.00342							
78												
79	Statistically	significant e	vidence of a	decreasing								
80	trend at the	specified lev	el of signific	cance.								




	Α	В	С	D	Е	F	G	Н		J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			-						
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	21:04 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/IJS for MK.x	ls		
5			I Precision	OFF								
6		Confidence	Coefficient	0.95								
7		Level of S	ignificance	0.05								
8												
129		1,4-D	ioxane-mw2	3-c-sd								
130												
131			eneral Statist									
132				Reported (m)	10							
133		N	umber of Mis	ssing Events	0							
134				Events Used	10							
133		Nun	nber Values	Reported (n)	10							
127				Minimum	0.045							
132				Maximum	1.4							
130			Coo	Mean metric Mean	0.292 0.174							
129 130 131 132 133 134 135 136 137 138 139 140 141 142			Geo	Median	0.174							
141			Standa	ard Deviation	0.25							
142				t of Variation	1.369							
143			Occincient	t or variation	1.000							
144		Ma	nn-Kendall	Гest								
145				est Value (S)	-16							
146				ated p-value	0.078							
147				eviation of S	10.23							
143 144 145 146 147 148			Standardize	ed Value of S	-1.466							
149			Approxir	mate p-value	0.0713							
150				•								
151	Insufficient	evidence to	identify a sig	nificant								
152	trend at the	specified le	vel of signifi	cance.								




1		Α	В	С	D	Е	F	G	Н		J	K	L
Date/Time of Computation	1				Mann-Kenda	all Trend Tes	st Analysis						
From File COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS for MK.xls			User Selecte	ed Options			_						
Second Confidence Coefficient 0.95		Date	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:2	1:04 AM						
6 Confidence Coefficient 0.95 1 Level of Significance 0.05 8 153				From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input I	MJS for Mk	√.xls		
Table Tabl			Ful	I Precision	OFF								
Standard Deviation Standar			Confidence (
153			Level of Si	gnificance	0.05								
158	8												
158	153		1,4-Dioxa	ane-mw38-8	30n-230e								
158	154												
158	155												
158	156												
165 Standard Deviation 4.063	15/												
165 Standard Deviation 4.063	158												
165 Standard Deviation 4.063	159		Nun	nber Values I									
165 Standard Deviation 4.063	160												
165 Standard Deviation 4.063	161												
165 Standard Deviation 4.063	162			0									
165 Standard Deviation 4.063	164			Geo									
169 M-K Test Value (S) -19 170 Tabulated p-value 0.054 171 Standard Deviation of S 11.18 172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 Insufficient evidence to identify a significant	165			Standa									
169 M-K Test Value (S) -19 170 Tabulated p-value 0.054 171 Standard Deviation of S 11.18 172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 Insufficient evidence to identify a significant	166												
169 M-K Test Value (S) -19 170 Tabulated p-value 0.054 171 Standard Deviation of S 11.18 172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 Insufficient evidence to identify a significant	167			Coemicient	oi valiau011	0.004							
169 M-K Test Value (S) -19 170 Tabulated p-value 0.054 171 Standard Deviation of S 11.18 172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 Insufficient evidence to identify a significant	168		Ma	nn-Kendall 1	Test .								
170 Tabulated p-value 0.054 171 Standard Deviation of S 11.18 172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 175 Insufficient evidence to identify a significant	169		IVIC			-19							
172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 175 Insufficient evidence to identify a significant	170												
172 Standardized Value of S -1.61 173 Approximate p-value 0.0537 174 175 Insufficient evidence to identify a significant	171												
175 Insufficient evidence to identify a significant	172												
175 Insufficient evidence to identify a significant	173												
175 Insufficient evidence to identify a significant				•									
176 trand at the enseified level of significance	175	Insufficient e	evidence to	identify a sig	nificant								
170 Iteliu at tile specificu level of significatice.	176	trend at the	specified le	vel of signific	cance.								




1 2 3 4 5 6 6 7 8 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48	Date	Full Confidence C Level of Sig Chlorofor Ger Number Number of	mputation From File Precision Coefficient gnificance m-mw38-83 neral Statist of Events F umber of Mis r Reported		8/5/2022 8:2	28:23 AM	1H2022 Pro	UCL Input N	AJS for MK	b.xls	
3 4 5 6 7 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47	Date	E/Time of Con Full Confidence C Level of Sig Chlorofor Gel Number Nu	mputation From File Precision Coefficient gnificance m-mw38-83 neral Statist of Events F umber of Mis r Reported	ProUCL 5.2 8 COMPLIANO OFF 0.95 0.05 30n-230e tics Reported (m) ssing Events Events Used Reported (n) Minimum	8/5/2022 8:2 CE DATA by 10 0 10 10 2.1	28:23 AM	: 1H2022 Pro	UCL Input N	AJS for MK	b.xls	
4 5 6 7 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47		Full Confidence C Level of Sig Chlorofor Ger Number Number of	From File Precision Coefficient gnificance m-mw38-83 neral Statist of Events F umber of Mis r Reported	COMPLIANO OFF 0.95 0.05 30n-230e tics Reported (m) ssing Events Events Used Reported (n) Minimum	10 0 10 10 2.1		: 1H2022 Pro	UCL Input N	AJS for MK	_b.xls	
5 6 7 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47	C	Full Confidence C Level of Sig Chlorofor Ger Number Number of	Precision Coefficient gnificance m-mw38-83 neral Statis of Events F umber of Mis r Reported	OFF 0.95 0.05 30n-230e tics Reported (m) ssing Events Events Used Reported (n) Minimum	10 0 10 10 2.1	y Constituent	: 1H2022 Pro	UCL Input N	AJS for MK	_b.xls	
6 7 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47	C	Confidence C Level of Sig Chlorofor Ger Number Nu Number of	coefficient gnificance m-mw38-83 neral Statist of Events F umber of Mis r Reported	0.95 0.05 30n-230e tics Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
7 8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47	C	Chlorofor Ger Number Number of	m-mw38-83 m-mw38-83 meral Statist of Events F umber of Mis r Reported	0.05 30n-230e tics Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
8 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48		Chlorofor Ger Number Nu	m-mw38-83 neral Statist of Events F umber of Mis r Reported I	tics Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48		Gei Number Nu Number o	neral Statis of Events F umber of Mis r Reported I	tics Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
38 39 40 41 42 43 44 45 46 47		Gei Number Nu Number o	neral Statis of Events F umber of Mis r Reported I	tics Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
38 39 40 41 42 43 44 45 46 47		Number Nu Number o	of Events F Imber of Mis r Reported	Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
38 39 40 41 42 43 44 45 46 47		Number Nu Number o	of Events F Imber of Mis r Reported	Reported (m) ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
38 39 40 41 42 43 44 45 46 47		Number o	ımber of Mis r Reported I	ssing Events Events Used Reported (n) Minimum	0 10 10 2.1						
38 39 40 41 42 43 44 45 46 47		Number o	r Reported I	Events Used Reported (n) Minimum	10 10 2.1						
40 41 42 43 44 45 46 47				Reported (n) Minimum	10 2.1						
40 41 42 43 44 45 46 47		Num	ber Values	Minimum	2.1						
42 43 44 45 46 47 48											
42 43 44 45 46 47 48				Maximum	69						
43 44 45 46 47 48											
44 45 46 47 48			0	Mean	4.3 3.959						
45 46 47 48			Geo	metric Mean Median	4.05						
46 47 48			Standa	ard Deviation	1.742						
47				t of Variation	0.405						
48			COCINCIEN	it or variation	0.403						
		Mar	n-Kendall	Test							
49		iviai		est Value (S)	-20						
50				lated p-value	0.036						
51				Deviation of S	11.14						
52 53 54				ed Value of S	-1.706						
53				mate p-value	0.044						
54			• •	•							
55 Statist											
56 trend a	tically s	significant ev	idence of a	a decreasing							




	Α	В	С	D	Е	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			-						
3	Date	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	1:04 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK.	.xls		
5			I Precision	OFF								
6		Confidence (Coefficient	0.95								
7		Level of Si	ignificance	0.05								
8												
177		1,4-D	ioxane-mw6	2-wdr								
178												
179 180 181 182 183			eneral Statist									
100				Reported (m)	10							
101				ssing Events	0							
183				Events Used	10 10							
184		inuri	nber values i	Reported (n) Minimum	2.9							-
185				Maximum	4.2							
186				Mean	3.53							
187			Geo	metric Mean	3.509							
184 185 186 187 188 189			aco	Median	3.45							
189			Standa	rd Deviation	0.406							
190				t of Variation	0.115							
191 192 193 194 195												
192		Ma	nn-Kendall 1	est								
193			M-K Te	est Value (S)	-37							
194			Tabul	ated p-value	0							
195			Standard D	eviation of S	11.09							
196				d Value of S	-3.246							
197			Approxir	mate p-value	5.8517E-4							
198												
199	Statistically	significant e	vidence of a	decreasing								
200	trend at the	specified lev	vel of signific	ance.								




	Α	В	С	D	Е	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			-						
3	Dat	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 8:3	2:04 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	IJS for MK	d.xls		
5		Ful	I Precision	OFF	_			•				
6		Confidence (Coefficient	0.95								
7		Level of Si	gnificance	0.05								
8												
9		Nitroge	n, Nitrite-mv	v62-wdr								
10												
11			eneral Statist									
12				Reported (m)	10							
13				ssing Events	0							
14				Events Used	10							
15		Num	nber Values I	Reported (n)	10							
16				Minimum	490							
17				Maximum	5400							
18				Mean	2268							
19 20			Geo	metric Mean	1875							
21			0. 1	Median	2000							
22				ard Deviation	1448							
23			Coefficient	t of Variation	0.638							
24		11-	nn-Kendall 1	Fact								
25		Ma			-15							
25 26				est Value (S) ated p-value	0.108							
27				eviation of S	11.18							
28				ed Value of S	-1.252							
29				mate p-value	0.105							
30			Approxii	nate p-value	0.105							
	Insufficient (avidence to	identify a sig	nificant								
			vel of signific									
5	uena at the	specified le	vei oi signili	Carice.								




	Α	В	С	D	Е	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			-						
3	Dat	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	29:40 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK_c	c.xls		
5			I Precision	OFF								
6		Confidence	Coefficient	0.95								
7		Level of S	ignificance	0.05								
8						I					I	
81		Nitroge	<mark>n, Nitrate-m</mark> v	w62-wdr								
81 82 83 84 85												
83			eneral Statist		- 10							
04 0E				Reported (m)	10							
00				ssing Events	0							
86 87				Events Used	10 10							
88		inun	nber Values	Minimum								
88 89				Maximum								
90					120000							
91			Geo	metric Mean								
92			ae0	Median								
93 94			Standa	ard Deviation	6667							
94				t of Variation	0.0556							
95 96			0000.0		0.0000							
96		Ma	nn-Kendall	Test								
97			M-K Te	est Value (S)	6							
98			Tabul	ated p-value	0.3							
99			Standard D	eviation of S	9.73							
97 98 99 100			Standardize	d Value of S	0.514							
101			Approxir	mate p-value	0.304							
102												
103	Insufficient e	evidence to	identify a sig	<u>Inificant</u>								
104	trend at the	specified le	vel of signifi	cance.								



	Α	В	С	D	Е	F	G	Н		J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	ed Options			-						
3	Dat	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	21:04 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/JS for MK.x	ls		
5			I Precision	OFF								
6		Confidence (0.95								
7		Level of Si	ignificance	0.05								
8						I				1		
201		1,4-D	Dioxane-mw7	77-wd								
202												
203			eneral Statist		10							
204				Reported (m)	10 0							
206				ssing Events Events Used	10							
207				Reported (n)	10							
208		inuii	ibei vaiues i	Minimum	2.6							
209				Maximum	16							
210				Mean	8.02							
211			Geo	metric Mean	6.772							
212				Median	7.15							
213			Standa	ard Deviation	4.596							
214			Coefficient	t of Variation	0.573							
215												
216		Ma	nn-Kendall 1									
21/				est Value (S)	14							
218				ated p-value	0.108							
201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 220 220 221				eviation of S	11.14							
220				d Value of S	1.167							
221			Approxir	mate p-value	0.122							
	la austi al aust		idonaide o o oire	ifit								
224	insumicient	evidence to	identify a sig	initicant								
224	treng at the	specified le	vel of signific	cance.								



	Α	В	С	D	Е	F	G	Н		,	J	K	L		
1				Mann-Kenda	n-Kendall Trend Test Analysis										
2		User Selecte	ed Options		CL 5.2 8/5/2022 8:21:04 AM										
3	Date	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 8:2	1:04 AM									
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input I	MJS for MK	(.xls					
5		Ful	I Precision	OFF											
6	(Confidence (0.95											
7															
8															
105 106	1,4-Dioxane-mw106-ud														
106	6														
107 108 109			eneral Statist												
100			r of Events F		10										
110			umber of Mis		0										
110 111			or Reported E		10 10										
112		inuri	nber Values I	Minimum	0.045										
112 113				Maximum	6.5										
114				Mean	0.82										
114 115 116			Geo	metric Mean	0.02										
116			aco	Median	0.25										
117			Standa	rd Deviation	1.998										
118				of Variation	2.438										
119															
119 120 121 122 123 124 125 126		Ma	nn-Kendall 1	Test											
121			M-K Te	est Value (S)	-27										
122				ated p-value	0.008										
123				eviation of S	9.781										
124			Standardize	d Value of S	-2.658										
125			Approxir	nate p-value	0.00393										
127	Statistically	significant e	vidence of a	decreasing											
128	trend at the	specified lev	vel of signific	ance.											



APPENDIX C-3.3 COMPLIANCE EVALUATION STATISTICAL TESTING

Goodness-of-Fit Testing

	Α		В	С	D	E	F	G	Н	<u> </u>	J	K	L
1					Goodness-	of-Fit Test S	tatistics for U	Incensored	Full Data Se	ts without N	on-Detects		
2				ted Options									
3	С	ate/	Time of Co	omputation		8/5/2022 10		41.10					
4				From File		ICE DATA by	y Constituent	1H2022 Pro	UCL Input I	MJS.xls			
5				II Precision	OFF								
6		Сс	onfidence	Coefficient	0.95								
7								1				1	
98	4 4 5 '		000										
99	1,4-Díoxa	ne (t	o-326-wd)	<u> </u>									
100				De 01	tetletiss								
101					tatistics per of Valid (Theonieties	10						
102													
103				Number	of Distinct C								
104						Minimum Maximum							
105					Maan	of Raw Data							
106				Standa	rd Deviation								
107				Statitual	a Deviduoli	Khat							
108						Theta hat							
109						Kstar							
110						Theta star							
111				Mean	of Log Trans								
112			Standa	rd Deviation									
113			Otariaai	ia Deviation	or Log Trans	ioimea Bata	1.002						
114		Normal GOF Test Results											
115		Hornial Col. Tool Neoullo											
116		Correlation Coefficient R					0.939						
117 118					hapiro Wilk								
118					Wilk Critical								
120					ate Shapiro \								
				11		Test Statistic							
121 122				Lillie	efors Critical								
	D <mark>ata app</mark> e	ear A	pproxima	te Normal at									
124													
125			(Gamma GOF	Test Result	ts							
126													
127					Correlation (Coefficient R	0.987						
128					A-D	Test Statistic	0.302						
129					A-D Critical	(0.05) Value	0.74						
130					K-S	Test Statistic	0.188						
131					K-S Critical	(0.05) Value	0.271						
	Data appo	ear G	amma Di	stributed at ((0.05) Signifi	icance Level							
133													
134			Lo	ognormal GO	F Test Resu	ılts							
135													
136					Correlation (
137					hapiro Wilk								
138					Wilk Critical	<u> </u>							
139				Approxim	ate Shapiro \								
140						Test Statistic							
141					efors Critical		0.262						
142	Data appo	ear L	ognormal	at (0.05) Sig	nificance Le	evel							
143								C-3.3-1					
								· · ·					

	Α	В	С	D	E	F	G	Н	I	J	K	L
1				Goodness-o	f-Fit Test St	atistics for U	Incensored F	Full Data Set	s without No	n-Detects		
2		User Selec	ted Options									
3	Da	ite/Time of Co	omputation	ProUCL 5.2	8/5/2022 10	:33:08 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input M	/IJS_e.xls			
5		Ful	II Precision	OFF								
6		Confidence	Coefficient	0.95								
7												
8												
9	Tetrachloro	ethene (bm-	11x-100n)									
10		•										
11			Raw St	tatistics								
12			Numb	ber of Valid O	bservations	10						
13			Number	r of Distinct O	bservations	10						
14					Minimum	4.6						
15					Maximum	7.2						
16				Mean o	of Raw Data	6.05						
17			Standar	rd Deviation of	of Raw Data	0.866						
18					Khat							
19					Theta hat	0.117						
20					Kstar	36.15						
21					Theta star	0.167						
22			Mean	of Log Transf	ormed Data	1.79						
23		Standaı		of Log Transf		0.149						
24												
23 24 25		ı	Normal GOF	Test Results	3							
26												
27				Correlation C	oefficient R	0.983						
28			S	hapiro Wilk T	est Statistic							
28 29				Wilk Critical (
30				ate Shapiro V		0.812						
31					est Statistic	0.131						
32			Lillie	efors Critical (0.262						
33	Data appea	ar Normal at (icance Level								
34			,,									
35		(Gamma GOF	Test Results	S							
36		-										
37				Correlation C	oefficient R	0.973						
38					est Statistic							
39				A-D Critical (0.724						
40					est Statistic	0.147						
41				K-S Critical(0.266						
42	Data appea	ar Gamma Di	stributed at ((0.05) Signific	cance Level							
43												
44		Lo	ognormal GO	F Test Resul	lts							
45												
46				Correlation C	oefficient R	0.974						
47				hapiro Wilk T								
48			Shapiro	Wilk Critical ((0.05) Value	0.842						
49				ate Shapiro V		0.597						
50					est Statistic	0.159						
51			l illie	efors Critical (0.262						†
52	Data annes	ar Lognormal		nificance Lev		0.202						†
		Eogiloiiidi	<u> (0.00) Olg</u>	iodiloo Eo			•	-	1	1		1

	Α	В	С	D	E	F	G	Н		J	K	L
1				Goodness-o	f-Fit Test St	tatistics for U	Incensored F	Full Data Se	ts without No	n-Detects		
2		User Sel	lected Options									
3	Γ	Date/Time of	Computation	ProUCL 5.2	8/5/2022 10	:34:15 AM						
4			From File	COMPLIANO	CE DATA by	Constituent	1H2022 Pro	UCL Input N	MJS_f.xls			
5		F	Full Precision	OFF	_							
6			ce Coefficient	0.95								
7												
8												
9	Trichloro	ethene (bm-1	11x-100n)									
10		(
11			Raw Sf	tatistics								
12			Numb	ber of Valid O	bservations	10						
13			Number	r of Distinct O	bservations	10						
14					Minimum	+						
15					Maximum							
16				Mean o	of Raw Data	+						
17			Standa	rd Deviation of								
18 19			0.0001		Khat					1		
19					Theta hat	+						
20					Kstar							
21					Theta star							
22			Mean	of Log Transf								
23		Stand	dard Deviation									
24		<u> </u>	adia Dovidation	or Log Transi	onnoa Data	0.10						
25			Normal GOF	Test Results	1							
26			Troilliai GOI	1 Cot 1 Courts	2							
22 23 24 25 26 27				Correlation C	`nefficient R	0.982						
28				hapiro Wilk T								
29				Wilk Critical (
30				ate Shapiro V								
31			прргодин		est Statistic							
32			l illie	efors Critical (
	Data ann	ear Normal s	at (0.05) Signific			0.202						
34	Data app	Cai Normai a	it (0.00) Olgilli	Carice Level								
35			Gamma GOF	Toet Recults	•							
36			Gairina GOF	i eat i teault	<u> </u>					+		
37				Correlation C	nefficient P	0.98				+		
38					est Statistic					+		
39				A-D Critical (-						
40					est Statistic					+		
41				K-S Critical(+		
	Data ann	ear Gamma	Distributed at ((0.05) Signific	cance I evel	0.200				+		
43	Data app	cai Gaillilla	Distributed at ((0.00) Olgrillic	Salice Level							
44			Lognormal GO	F Test Recul	lte					+		
45			Logiloiniai GO	i restricsul	ILO					+		
46				Correlation C	nefficient R	0.974						
47				hapiro Wilk T						+		+
48				Wilk Critical (+		+
49				ate Shapiro V						+		+
50					est Statistic					+		+
51			1 :01: 2			+				+		
	Doto one	oor Loans	nal at (0.05) Sig	efors Critical ((U.US) value	0.202				+		
IJΖ	vata app	ear Lognorm	<u>iai at (0.05) 510</u>	imicance re	vei				1			

	А		В	С	D	E	F	G	Н	I	J	K	L
1					Goodness-	of-Fit Test S	tatistics for l		Full Data Se	ts without N	on-Detects		
2				cted Options									
3		Date	Time of Co	omputation	ProUCL 5.2	8/5/2022 10):23:05 AM						
4				From File	COMPLIAN	ICE DATA b	y Constituen	t 1H2022 Pro	o UCL Input N	MJS.xls			
5			Ful	II Precision	OFF								
6		С	onfidence	Coefficient	0.95								
7													
282													
283	1,4-Diox	ane (<mark>(mw38-83</mark> 0	<mark>n-230e)</mark>									
284													
285				Raw S	tatistics								
286				Num	ber of Valid (Observations	10						
287				Numbe	r of Distinct (Observations	10						
288						Minimum	2						
289						Maximum							
290						of Raw Data							
291				Standa	rd Deviation	of Raw Data	4.063						
292						Kha	t 2.535						
293						Theta ha							
294						Ksta	r 1.841						
295						Theta sta	3.324						
296				Mean	of Log Trans	formed Data	1.602						
297			Standa	rd Deviation	of Log Trans	formed Data	0.697						
298													
299			I	Normal GOF	Test Result	s							
300													
301					Correlation	Coefficient F	0.946						
302				S	Shapiro Wilk	Test Statistic	0.876						
303				Shapiro	Wilk Critical	(0.05) Value	0.842						
304				Approxim	ate Shapiro	Wilk P Value	0.165						
305					Lilliefors	Test Statistic	0.246						
306				Lillie	efors Critical	(0.05) Value	0.262						
307	Data app	oear	Normal at ((0.05) Signif	icance Level		-						
308													
309			(Gamma GOF	Test Resul	ts							
310													
311					Correlation	Coefficient F	0.971						
312					A-D	Test Statistic	0.38						
313					A-D Critical	(0.05) Value	0.734						
314					K-S	Test Statistic	0.187						
315					K-S Critical	-							
	Data app	oear	Gamma Di	istributed at	(0.05) Signif	icance Leve	l						
317													
318			Lo	ognormal GC	F Test Resu	ılts							
319													
320					Correlation	Coefficient F	0.972						
321				S	Shapiro Wilk	Test Statistic	0.919						
322				Shapiro	Wilk Critical	(0.05) Value							
323				Approxim	ate Shapiro	Wilk P Value							
324					Lilliefors	Test Statistic	0.151						
325				Lillie	efors Critical	(0.05) Value	0.262						
	Data app	oear	Lognormal	at (0.05) Sig	gnificance Le	evel							
327								C-3 3-4					
													

1	•	Goodness-of-Fit Test Sta	atistics for U	ncensored F	ull Data Sets	s without No	n-Detects					
2	User Selected Options											
3	Date/Time of Computation	ProUCL 5.2 8/5/2022 10:	UCL 5.2 8/5/2022 10:30:35 AM MPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS_d.xls									
4	From File	COMPLIANCE DATA by	MPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS_d.xls									
5	Full Precision	OFF										
6	Confidence Coefficient	0.95										
7												
8												
9	Nitrogen, Nitrite (mw62-wdr)											
10												
11	Raw S	tatistics										
12	Numl	per of Valid Observations	10									
13	Number	of Distinct Observations	10									
14		Minimum	890									
15		Maximum	5400									
16		Mean of Raw Data	2317									
17	Standa	rd Deviation of Raw Data	1388									
18		Khat	3.665									
19		Theta hat	632.2									
20		Kstar	2.632									
21		Theta star	880.2									
22	Mean	of Log Transformed Data	7.605									
23	Standard Deviation	of Log Transformed Data	0.555									
24												
25	Normal GOF	Test Results										
26												
27		Correlation Coefficient R	0.916									
28		hapiro Wilk Test Statistic	0.847									
29		Wilk Critical (0.05) Value	0.842									
30	Approxim	ate Shapiro Wilk P Value	0.045									
31		Lilliefors Test Statistic	0.276									
32		efors Critical (0.05) Value	0.262									
33	Data appear Approximate Normal at	(0.05) Significance Level	<u> </u>									
34												
35	Gamma GOF	Test Results										
36												
37		Correlation Coefficient R	0.971									
38		A-D Test Statistic	0.361									
39		A-D Critical (0.05) Value	0.73									
40		K-S Test Statistic	0.204									
41		K-S Critical(0.05) Value	0.268									
42	Data appear Gamma Distributed at	(0.05) Significance Level										
43												
44	Lognormal GC	F Test Results										
45		<u> </u>	0.0=0									
46		Correlation Coefficient R	0.978									
47		hapiro Wilk Test Statistic	0.955									
48		Wilk Critical (0.05) Value	0.842									
49	Approxim	ate Shapiro Wilk P Value	0.721									
50		Lilliefors Test Statistic	0.174									
51		efors Critical (0.05) Value	0.262									
52	Data appear Lognormal at (0.05) Sig	jniticance Level										

K

Α

В

С

	Α		В	С	D	Е	F	G	Н	I	J	K	L
1					Goodness-o	f-Fit Test St	atistics for U	ncensored F	ull Data Set	s without No	n-Detects		
2	ļ			cted Options									
3		Date/	Time of Co	omputation	ProUCL 5.2								
4	ļ			From File		CE DATA by	Constituent	1H2022 Pro	UCL Input M	/IJS_c.xls			
5				Il Precision	OFF								
6 7			onfidence	Coefficient	0.95								
8								T	T				
143													
144	Nitroge	n Nitra	ate (mw62	2-wdr)									
145	Maogo	ii, ivide	210 (IIIWO2	- war,									
146				Raw S	tatistics								
147				Numl	per of Valid O	bservations	10						
148				Number	of Distinct O	bservations	3						
149						Minimum	110000						
150						Maximum							
151						of Raw Data							
152				Standa	rd Deviation o								
153 154	<u> </u>					Khat							
155						Theta hat							
156						Kstar Theta star							
157				Mean	of Log Transf								
158			Standa		of Log Transf		0.0557						
159			Otanaa	ia Deviation	or Log Transi	orrica Bata	0.0007						
160				Normal GOF	Test Results	;							
161													
162					Correlation C	oefficient R	0.903						
163				S	hapiro Wilk T	est Statistic	0.815						
164					Wilk Critical (
165				Approxim	ate Shapiro V		0.0222						
166	ļ					est Statistic							
167	D-4	NI		Lillie	efors Critical (0.05) Value	0.262						
169	Data no	ot Norn	naı at (U.U	5) Significan	ce Level								
170				Gamma GOE	Test Results	•							
171				Gaillilla GOI	rest nesults	•							
172					Correlation C	oefficient R	0.904						
173						est Statistic	1.034						
174					A-D Critical (0.724						
175					K-S T	est Statistic	0.307						
176					K-S Critical(0.05) Value	0.266						
177	Data no	ot Gam	ma Distrib	outed at (0.0	5) Significano	e Level							
178	ļ												
179 180			Lo	ognormal GO	F Test Resul	ts							
180					Correlation	oofficient D	0.000						
182					Correlation C hapiro Wilk T		0.902 0.815						
182 183					Wilk Critical (
184				Approxim	ate Shapiro V	Vilk P Value	0.0217						
184 185				, approxim		est Statistic							
186				Lillie	efors Critical (
187	Data no	ot Logn	ormal at ((0.05) Signific	cance Level	,							
188													
189	Non-pa	rametr	ic GOF Te	est Results									
190													
191	Data do	not fo	llow a dis	cernible distr	ribution at (0.	05) Level of	Significance						

	Α		В	С	D	Е	F	G	Н	I	J	K	L
1					Goodness-o	f-Fit Test S	Statistics for	Uncensored F	Full Data Set	ts without No	on-Detects		
2				ted Options									
3		Date	/Time of Co		ProUCL 5.2								
4				From File	COMPLIANO	CE DATA b	y Constituen	t 1H2022 Pro	UCL Input N	∕IJS.xls			
5			Ful	II Precision	OFF								
6		C	Confidence	Coefficient	0.95								
7													
372													
373		ane	(mw77-wd))									
374													
375				Raw St	tatistics								
376				Numb	per of Valid O	bservation	s 10						
377				Number	of Distinct O	bservation	s 9						
378						Minimur	n 2.6						
379						Maximur	n 16						
380					Mean o	of Raw Dat	a 8.02						
381				Standar	rd Deviation o	of Raw Dat	a 4.596				+		
382						Kha	at 3.112						
383						Theta ha	at 2.577						
384						Ksta	r 2.245						
385						Theta sta	ır 3.572		+				
386				Mean	of Log Transf	ormed Dat	a 1.913						
387			Standaı		of Log Transf								
388													
389			I	Normal GOF	Test Results	 }							
390					Correlation C	Coefficient F	R 0.964						
391					hapiro Wilk T								
392					Wilk Critical (
393					ate Shapiro V								
394				Аррголин	Lilliefors T								
395				l illic	efors Critical (
396		near	Normal at /		cance Level		0.202						
007		poui	itorniai at ((o.oo) Olgiliii	Darioo Lovoi								
398				Samma GOF	Test Results	•							
399					. 55. 1 105416								
400					Correlation C	Coefficient F	R 0.965						
401						est Statisti							
402					A-D Critical (
403						est Statisti							
404					K-S Critical(
405	Data on	neer	Cammo Di		0.05) Signific								
400	vata ap	hegi	daniina Di	ou iduled at (v.voj aignific	Janue Leve	71						
407			1 -	anormal CO	F Test Resul	lte							
408			LO	gnormal GO	r i est kesul	ແຮ							
409					Correlation C	`oofficiant '	0 0074						
410					Correlation C								
411					hapiro Wilk T								
412					Wilk Critical (
413				Approxima	ate Shapiro V								
414					Lilliefors T								
415					efors Critical (e 0.262						
416	Data ap	pear	Lognormal	at (0.05) Sig	nificance Lev	vel							

APPENDIX C-3.4 COMPLIANCE EVALUATION STATISTICAL TESTING

Outlier Testing

	Α	В	С	D	E	F	G	Н		J	K	L
1					Outlier Test	ts for Selecte	d Uncensore	ed Variables	3			
2				cted Options								
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:4	47:15 AM						
4				From File	COMPLIAN	ICE DATA by	Constituent	1H2022 Pro	UCL Input N	IJS.xls		
5			Fu	II Precision	OFF							
6												
31												
32	Dixo	n's Outlier Te	est for 1,4-D	ioxane (b-32	6-ud)							
33												
34		Observations										
35		value: 0.409)									
36	5% critical v											
37	1% critical v	ralue: 0.597										
38												
39	1. Observa	tion Value 7	.7 is a Poter	ntial Outlier (l	Jpper Tail)?							
40												
41	Test Statisti	c: 0.258										
42												
43	_	nificance lev										
44	_	ificance leve										
45	For 1% sign	ificance leve	el, 7.7 is not a	an outlier.								
46												
47	2. Observat	ion Value 4.	5 is a Poten	tial Outlier (L	ower Tail)?							
48												
49	Test Statisti	c: 0.042										
50												
51	_	nificance lev										
52	_	ificance leve										
53	For 1% sign	ificance leve	el, 4.5 is not a	an outlier.								
54												

	Α	В	С	D	E	F	G	Н		J	K	L
1					Outlier Test	s for Selecte	d Variables	replacing no	ndetects with	n 1/2 the Det	ection Limit	
2	1		User Selec	ted Options								
3	Date	e/Time of Co	omputation	ProUCL 5.2								
4	1			From File	COMPLIAN ⁶	CE DATA by	Constituent	1H2022 Pro	UCL Input M	IJS_c.xls		
5			Ful	II Precision	OFF							
6												
34	1											
35	1											
36	Dixon's	Outlier Test	t for Nitroger	n, Nitrate (b-3	326-ud)							
37	1											
38	Total N = 10											
39	Number NDs	s = 2										
	Number Det											
41	Number Data	a (n) = 10										
42	10% critical	value: 0.409										
	5% critical va											
	1% critical va											
45	Note: NDs re	eplaced by D	L/2 in Outlie	r Test								
46												
47	1. Data Val	ue 66000 is	a Potential (Outlier (Uppe	r Tail)?							
48												
49	Test Statistic	c: 0.258										
50												
51	For 10% sign	nificance lev	el, 66000 is	not an outlier	·							
52	For 5% signi	ificance leve	l, 66000 is n	ot an outlier.								
53	For 1% signi	ificance leve	l, 66000 is n	ot an outlier.								
54	<u></u>											
55	2. Data Valu	ue 45 is a Po	tential Outli	er (Lower Ta	il)?							
56												
	Test Statistic	c: 0.000										
58	I											
59	For 10% sigi	nificance lev	el, 45 is not	an outlier.								
60	For 5% signi	ificance leve	l, 45 is not a	n outlier.								
61	For 1% signi	ificance leve	l, 45 is not a	n outlier.								
62	I											
63												

		Outlier Tests for Se	elected Uncer	sored Varia	bles	•			
User Selec	ted Options								
Date/Time of Computation									
	From File	COMPLIANCE DA	TA by Constitu	uent 1H2022	Pro UCL In	put MJS.xls			
Full	Precision	OFF							
	'								
Dixon's Outlier Test for 1,4	4-Dioxane (b	-326-wd)							
1% critical value: 0.597									
1. Observation Value 17 is a Potent	ial Outlier (U	pper Tail)?							
Test Statistic: 0.375									
For 1% significance level, 17 is not ar	n outlier.								
2. Observation Value 0.77 is a Poter	ntial Outlier (l	Lower Tail)?							
Test Statistic: 0.022									
For 1% significance level, 0.77 is not	an outlier.								
	Dixon's Outlier Test for 1,4 Dixon's Outlier Test for 1,4 Number of Observations = 10 10% critical value: 0.409 5% critical value: 0.477 1% critical value: 0.597 1. Observation Value 17 is a Potent Test Statistic: 0.375 For 10% significance level, 17 is not ar For 5% significance level, 17 is not ar For 1% significance level, 17 is not ar 2. Observation Value 0.77 is a Poter Test Statistic: 0.022 For 10% significance level, 0.77 is not For 5% significance level, 0.77 is not	User Selected Options Date/Time of Computation ProUCL 5.2 From File Full Precision Dixon's Outlier Test for 1,4-Dioxane (b Number of Observations = 10 10% critical value: 0.409 5% critical value: 0.477 1% critical value: 0.597 1. Observation Value 17 is a Potential Outlier (U Test Statistic: 0.375 For 10% significance level, 17 is not an outlier. For 5% significance level, 17 is not an outlier. For 1% significance level, 17 is not an outlier. 2. Observation Value 0.77 is a Potential Outlier (II	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 A From File COMPLIANCE DA Full Precision OFF Dixon's Outlier Test for 1,4-Dioxane (b-326-wd) Number of Observations = 10 10% critical value: 0.409 5% critical value: 0.477 1% critical value: 0.597 1. Observation Value 17 is a Potential Outlier (Upper Tail)? Test Statistic: 0.375 For 10% significance level, 17 is not an outlier. For 5% significance level, 17 is not an outlier. 2. Observation Value 0.77 is a Potential Outlier (Lower Tail)? Test Statistic: 0.022 For 10% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier.	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM From File COMPLIANCE DATA by Constitute Full Precision OFF Dixon's Outlier Test for 1,4-Dioxane (b-326-wd) Number of Observations = 10 10% critical value: 0.409 5% critical value: 0.477 1% critical value: 0.597 1. Observation Value 17 is a Potential Outlier (Upper Tail)? Test Statistic: 0.375 For 10% significance level, 17 is not an outlier. For 1% significance level, 17 is not an outlier. 2. Observation Value 0.77 is a Potential Outlier (Lower Tail)? Test Statistic: 0.022 For 10% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier.	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM	Date/Time of Computation From File From File Full Precision Dixon's Outlier Test for 1,4-Dioxane (b-326-wd) Number of Observations = 10 10% critical value: 0.409 5% critical value: 0.597 1. Observation Value 17 is a Potential Outlier (Upper Tail)? For 10% significance level, 17 is not an outlier. For 1% significance level, 17 is not an outlier. C. Observation Value 0.77 is a Potential Outlier (Lower Tail)? Test Statistic: 0.022 For 10% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier. For 5% significance level, 0.77 is not an outlier.	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM From File COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls Full Precision OFF Dixon's Outlier Test for 1,4-Dioxane (b-326-wd)	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM From File COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls Full Precision OFF Precision OFF OFF	Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls OFF COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls COMPLIANCE DATA by C

F

G

Н

J

K

L

Α

В

С

D

Е

	Α	В	С	D	Е	F	G	Н		J	K	L
1					Outlier Tests for Selec	ted Uncenso	red Variable	es				
2			User Selec	ted Options								
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:50:22 AM							
4			•	From File	COMPLIANCE DATA	by Constituer	nt 1H2022 Pr	o UCL Input	MJS e.xls			
5			Ful		OFF	•		•				
6												
7												
8	Dixo	n's Outlier To	est for Tetrac	chloroethene	(bm-11x-100n)							
9					•							
10	Number of 0	Observations	s = 10									
11	10% critical	value: 0.409)									
12	5% critical v	value: 0.477										
13	1% critical v	alue: 0.597										
14												
15	1. Observa	tion Value 7	.2 is a Poten	tial Outlier (l	Jpper Tail)?							
16					•							
17	Test Statisti	c: 0.130										
18												
19	For 10% sig	nificance lev	el, 7.2 is not	an outlier.								
20	For 5% sign	ificance leve	el, 7.2 is not a	n outlier.								
			el, 7.2 is not a									
22												
23	2. Observat	ion Value 4.	6 is a Potent	ial Outlier (L	ower Tail)?							
24				_	·							
25 26	Test Statisti	c: 0.130										
27	For 10% sig	nificance lev	el, 4.6 is not	an outlier.								
28	For 5% sign	ificance leve	el, 4.6 is not a	n outlier.								
29	For 1% sign	ificance leve	el, 4.6 is not a	n outlier.								
30												

	Α	В	С	D	E	F	G	Н	I	J	K	L
1					Outlier Tests	for Selected	Uncensored	Variables	•	•		
2			User Selec	ted Options								
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:50	:58 AM						
4			•	From File	COMPLIANC	E DATA by C	onstituent 1	H2022 Pro L	JCL Input MJ	S f.xls		
5			Ful	II Precision	OFF	•			•			
6												
7												
8	Dixon's	Outlier Test	for Trichloro	ethene (bm-	11x-100n)							
9												
	Number of C	Observations	s = 10									
	10% critical	value: 0.409)									
	5% critical v	alue: 0.477										
	1% critical v	alue: 0.597										
14												
15	1. Observa	tion Value 5	.7 is a Poten	ntial Outlier (l	Jpper Tail)?							
16												
	Test Statisti	c: 0.143										
18												
19	For 10% sig	nificance lev	/el, 5.7 is not	an outlier.								
20			el, 5.7 is not a									
21	For 1% sign	ificance leve	el, 5.7 is not a	an outlier.								
22												
23	2. Observat	tion Value 3.	6 is a Potent	tial Outlier (L	ower Tail)?							
24												
25 26	Test Statisti	c: 0.368										
27	For 10% sig	inificance lev	/el, 3.6 is not	an outlier.								
			el, 3.6 is not a									
29	For 1% sign	ificance leve	el, 3.6 is not a	an outlier.								
30												

	Α	В	С	D	E	F	G	Н	I	J	K	L
1					Outlier Tests for Select	ted Uncenso	red Variable	S				
2				ted Options								
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:51:31 AM							
4				From File	COMPLIANCE DATA b	y Constituen	t 1H2022 Pro	o UCL Input	MJS_c.xls			
5			Ful	I Precision	OFF							
6												
7												
55												
56	Di	ixon's Outlie	r Test for Nit	rogen, Nitrat	e (bm-15n6)							
57												
		Observations										
		value: 0.409										
	5% critical v											
61	1% critical v	alue: 0.597										
62												
63	1. Observa	tion Value 4	9000 is a Po	tential Outlie	r (Upper Tail)?							
64												
65	Test Statistic	c: 0.333										
66												
67	For 10% sig	nificance lev	el, 49000 is	not an outlier								
60	For 5% sign	ificance leve	el, 49000 is n	ot an outlier.								
69 70	For 1% sign	ificance leve	el, 49000 is n	ot an outlier.								
	0.01		D .		// T !!\0							
72	2. Observat	ion value 30	DUUU IS a Pot	ential Outliel	(Lower Tail)?							
	T1 01-1:-1:	0.077										
74	Test Statistic	C: U.U//										
	For 100/ -:-	nificance la	.al 20000 :-	not on out!:								
76	For FO Sig	inincance lev	rel, 30000 is	not an outlier								
			el, 30000 is n el, 30000 is n									
78	rui 1% sign	ilicance leve	i, suuuu is n	ot all outlier.								
79												
, ,												

1	
Date/Time of Computation ProUCL 5.2 8/5/2022 9:47:15 AM	
From File COMPLIANCE DATA by Constituent 1H2022 Pro UCL Input MJS.xls	
5 Full Precision OFF 6 127 128 Dixon's Outlier Test for 1,4-Dioxane (mw23-c-sd) 129 130 Number of Observations = 10 131 10% critical value: 0.409 132 5% critical value: 0.477 133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
6 127 128	
127 128	
128 Dixon's Outlier Test for 1,4-Dioxane (mw23-c-sd) 129 130 Number of Observations = 10 10% critical value: 0.409 131 5% critical value: 0.477 132 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720 138 139 139 139 130	
129 130 Number of Observations = 10 131 10% critical value: 0.409 132 5% critical value: 0.477 133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
130 Number of Observations = 10 10% critical value: 0.409 132 5% critical value: 0.477 133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720 137 140 150	
131 10% critical value: 0.409 132 5% critical value: 0.477 133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
132 5% critical value: 0.477 133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
133 1% critical value: 0.597 134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720 138	
134 135 1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
1. Observation Value 1.4 is a Potential Outlier (Upper Tail)? 136 137 Test Statistic: 0.720	
136 137 Test Statistic: 0.720	
Test Statistic: 0.720	
107	
120	
138	
For 10% significance level, 1.4 is an outlier.	
For 5% significance level, 1.4 is an outlier.	
For 1% significance level, 1.4 is an outlier.	
142	
2. Observation Value 0.09 is a Potential Outlier (Lower Tail)?	
144	
Test Statistic: 0.146	
146	
For 10% significance level, 0.09 is not an outlier.	
For 5% significance level, 0.09 is not an outlier.	
For 1% significance level, 0.09 is not an outlier.	
150	

	Α	В	С	D	E	F	G	Н		J	K	L
1					Outlier Tests for Sel	ected Uncer	nsored Varia	bles				
2				ted Options								
3	Dat	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:47:15 AM							
4				From File	COMPLIANCE DATA	A by Constitu	uent 1H2022	Pro UCL Inp	out MJS.xls			
5			Ful	II Precision	OFF							
6												
151												
152	Dixon	's Outlier Te	est for 1,4-Di	oxane (mw3	8-830n-230e)							
153												
104	Number of C											
155	10% critical	value: 0.409										
156	5% critical v	alue: 0.477										
	1% critical v											
158												
159	1. Observa	tion Value 1	3 is a Potent	tial Outlier (L	lpper Tail)?							
160												
161	Test Statistic	c: 0.092										
162												
	For 10% sig	nificance lev	el, 13 is not	an outlier.								
			el, 13 is not a									
165	For 1% sign	ificance leve	el, 13 is not a	n outlier.								
166												
	2. Observat	ion Value 2	is a Potentia	l Outlier (Lov	ver Tail)?							
168												
	Test Statistic	c: 0.010										
170												
171			el, 2 is not a									
172	For 5% sign	ificance leve	el, 2 is not an	outlier.								
173	For 1% sign	ificance leve	el, 2 is not an	outlier.								
174												

	Α	В	С	D	E	F	G	Н	I	J	K	L
1					Outlier Test	s for Selecte	d Uncensor	ed Variables		-		
2			User Selec	ted Options								
3	Dat	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:5	52:36 AM						
4							Constituent	1H2022 Pro	UCL Input M	IJS b.xls		
5			Fu	II Precision	OFF				•	_		
6												
31												
32	Dixon's (Outlier Test f	for Chlorofor	m (mw38-83	0n-230e)							
33												
	Number of 0	Observations	s = 10									
	10% critical)									
	5% critical v	alue: 0.477										
37	1% critical v	alue: 0.597										
38												
39	 Observa 	tion Value 6	.9 is a Poter	ntial Outlier (l	Jpper Tail)?							
40												
	Test Statisti	c: 0.146										
42												
			/el, 6.9 is not									
			el, 6.9 is not a									
45	For 1% sign	ificance leve	el, 6.9 is not a	an outlier.								
46												
47	2. Observat	ion Value 2.	1 is a Poten	tial Outlier (L	ower Tail)?							
48												
	Test Statisti	c: 0.000										
50	- 100/ :											
			/el, 2.1 is not									
			el, 2.1 is not a									
53 54	⊢or 1% sign	ificance leve	el, 2.1 is not a	an outlier.								
54												

	Α	В	С	D	Е	F	G	Н		J	K	L
1					Outlier Tests for Sel	ected Uncer	nsored Varia	bles				
2				ted Options								
3	Dat	e/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:47:15 AM							
4				From File	COMPLIANCE DATA	A by Constitu	uent 1H2022	Pro UCL Inp	out MJS.xls			
5			Ful	I Precision	OFF							
6												
175												
176	Di	ixon's Outlie	er Test for 1,4	1-Dioxane (m	nw62-wdr)							
177												
178	Number of C	Observations	s = 10									
179	10% critical	value: 0.409										
180	5% critical v	alue: 0.477										
181	1% critical v	alue: 0.597										
182												
183	1. Observa	tion Value 4	.2 is a Poten	tial Outlier (l	Jpper Tail)?							
184												
185	Test Statistic	c: 0.300										
186												
187			el, 4.2 is not									
188	For 5% sign	ificance leve	el, 4.2 is not a	an outlier.								
189	For 1% sign	ificance leve	el, 4.2 is not a	an outlier.								
190												
	2. Observat	ion Value 2.	9 is a Potent	tial Outlier (L	ower Tail)?							
192												
	Test Statistic	c: 0.300										
194												
195			el, 2.9 is not									
196	For 5% sign	ificance leve	el, 2.9 is not a	n outlier.								
			el, 2.9 is not a									
198												
								ı				

	Α	В	С	D	E	F	G	Н		J	K	L
1	Outlier Tests for Selected Variables replacing nondetects with 1/2 the Detection Limit											
2			User Selec	ted Options								
3	Dat	e/Time of Co	mputation	ProUCL 5.2	8/5/2022 9:3	0:27 AM						
4				From File	COMPLIAN	CE DATA by	Constituent	1H2022 Pro	UCL Input M	IJS_d.xls		
5			Ful	I Precision	OFF							
6												
7												
8	Dixon's	Outlier Test	for Nitrogen	, Nitrite (mw	62-wdr)							
9												
	Total N = 10											
	Number ND:											
	Number Det											
	Number Dat											
	10% critical											
	5% critical v											
	1% critical v											
	Note: NDs re	eplaced by D	L/2 in Outlie	r Test								
18												
19	1. Data Val	ue 5400 is a	Potential O	utlier (Upper	Tail)?							
20												
21 22	Test Statistic	c: 0.310										
-												
			el, 5400 is n									
			I, 5400 is no									
25 26	⊦or 1% sign	ificance leve	I, 5400 is no	t an outlier.								
	0.5. \(\)	400: 5		//	****							
27 28	2. Data Valu	ie 490 is a F	otentiai Out	lier (Lower T	all)?							
$\overline{}$	-	0.444										
30	Test Statistic	c: 0.114										
	F100/ :	: <i>6</i> :	-1 400 :-									
			el, 490 is no									
			I, 490 is not									
33 34	⊢or 1% sign	ificance leve	I, 490 is not	an outlier.								
34												

	Α	В	С	D	E	F	G	Н	I	J	K	L
1					Outlier Test	s for Selecte	d Uncensor	ed Variables		-		
2			User Selec	cted Options								
3	Dat	te/Time of Co		ProUCL 5.2	8/5/2022 9:5	51:31 AM						
4			•	From File	COMPLIAN	CE DATA by	Constituent	1H2022 Pro	UCL Input M	IJS c.xls		
5			Fu	II Precision	OFF				•	_		
6												
79												
80	Dixon's	Outlier Test	for Nitroger	n, Nitrate (mw	/62-wdr)							
81												
	Number of 0											
	10% critical)									
	5% critical v											
85	1% critical v	alue: 0.597										
86												
87	 Observa 	tion Value 1	30000 is a F	Potential Outl	ier (Upper Ta							
88												
	Test Statisti	c: 0.000										
90												
				s not an outli								
				not an outlier								
93 94	For 1% sign	ificance leve	ei, 130000 is	not an outlie	ſ <u>.</u>							
	0 Observed	ian Valua 41	10000 : D	stantial Outi	/l T-							
96	∠. ∪bservat	ion value i	IUUUU IS a P	otential Outli	er (Lower Ta							
97	Test Statisti	o: 0 000										
98	resi Statisti	C. U.UUU										
	For 10% sig	nificance lev	ا 110000 ا	s not an outli								
100	For 5% sign	ificance leve	1100001	not an outlie	·							
101	For 1% sign	ificance leve	110000 is	not an outlier	•							
102	. 51 170 Sigil		21, 7 10000 13	not an oatho								
						1		1		1	1	

1			Outlier Tests for Selec	ted Uncensored Varia	ables		
2	User Select	-					
3	Date/Time of Computation		8/5/2022 9:47:15 AM				
4		From File	COMPLIANCE DATA I	by Constituent 1H2022	Pro UCL Input MJS.x	ls	
5	Full	Precision	OFF				
6							
199							
200	Dixon's Outlier Test for 1,4	-Dioxane (m	w77-wd)				
201							
	Number of Observations = 10						
	10% critical value: 0.409						
204	5% critical value: 0.477						
205	1% critical value: 0.597						
206							
207	1. Observation Value 16 is a Potenti	al Outlier (U	oper Tail)?				
208							
209	Test Statistic: 0.308						
210							
	For 10% significance level, 16 is not a						
212	For 5% significance level, 16 is not ar	outlier.					
213	For 1% significance level, 16 is not an	outlier.					
214							
215	2. Observation Value 2.6 is a Potenti	al Outlier (Lo	ower Tail)?				
216							
217	Test Statistic: 0.043						
218							
219	For 10% significance level, 2.6 is not	an outlier.					
	For 5% significance level, 2.6 is not a						
221	For 1% significance level, 2.6 is not a	n outlier.					
222							
						_	

Н

K

Α

В

С

D

	Α	В	С	D	Е	F	G	Н	I	J	K	L		
1					Outlier Test	s for Selecte	d Uncensore	ed Variables						
2			User Selec	cted Options										
3	Date	te/Time of Co	omputation	ProUCL 5.2	8/5/2022 9:4	17:15 AM								
4				From File	COMPLIAN	CE DATA by	Constituent	1H2022 Pro	UCL Input N	/IJS.xls				
5	5 Full Precision OFF													
6														
103														
104	Dixon'	's Outlier Te	st for 1,4-Did	oxane (mw10)6-ud)									
105														
106	Number of C	Observations	s = 10											
107	10% critical	value: 0.409)											
108	5% critical va	alue: 0.477												
109	1% critical va	alue: 0.597												
110	·													
111	1. Observat	tion Value 6	.5 is a Poten	ntial Outlier (l	Jpper Tail)?									
112	·													
113	Test Statistic	c: 0.945												
114														
115	For 10% sign	nificance lev	vel, 6.5 is an	outlier.										
116	For 5% signi	ificance leve	el, 6.5 is an o	utlier.										
			el, 6.5 is an o											
118	·													
	2. Observati	ion Value 0.	09 is a Poter	ntial Outlier (Lower Tail)?									
120	·													
121	Test Statistic	c: 0.146												
122														
	For 10% sign	nificance lev	vel, 0.09 is no	ot an outlier.										
124			el, 0.09 is not											
125	For 1% signi	ificance leve	el, 0.09 is not	an outlier.										
126														
126														

APPENDIX C-3.5

COMPLIANCE EVALUATION STATISTICAL TESTING

Linear Regression Analysis

B-326-UD 1,4-DIOXANE

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:08:16 AM

From File COMPLIANCE DATA 2H2021.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9
Display Regresion Diagnostics True
Display Regresion Tables True

Display Prediction Band

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9

Display Confidence Band True

Dependendant Variable (Y-Data) 1,4-Dioxane_b-326-ud

Number Reported (Y values) 10

True

Independent Variable (x-data) Sample Date_b-326-ud

Number Reported (x-values) 10

Regression Estimates and Inference Table

 Parameter
 Estimates
 Std. Error
 T-values
 p-values

 intercept
 173.6
 19.5
 8.902
 2.0090E-5

 mple Date_b-326
 -0.00378
 4.4030E-4
 -8.591
 2.6053E-5

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	9.044	1	9.044	73.8	0.0000
Error	0.98	8	0.123		
Total	10.02	9			
	R Square	0.902			
Adjusted	0.89				
Sqrt(MS	0.35				


Regression Table

Obs	Y Vector	Yhat	Residuals	Res/Scale
1	7.7	7.624	0.0759	0.217
2	6.9	7.227	-0.327	-0.934
3	6.7	6.856	-0.156	-0.446
4	6.4	6.482	-0.0818	-0.234
5	6.7	6.27	0.43	1.229
6	6	5.827	0.173	0.493
7	6.1	5.487	0.613	1.751
8	5	5.324	-0.324	-0.926
9	4.5	4.874	-0.374	-1.069
10	4.6	4.628	-0.0283	-0.0809

	Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1		43873	7.7	7.624	0.213	0.41	7.228	8.02	6.862	8.386	0.0759
2		43978	6.9	7.227	0.175	0.391	6.901	7.553	6.499	7.955	-0.327
3		44076	6.7	6.856	0.144	0.379	6.588	7.125	6.152	7.56	-0.156


4	44175	6.4	6.482	0.121	0.37	6.257	6.707	5.793	7.171	-0.0818
5	44231	6.7	6.27	0.113	0.368	6.059	6.481	5.586	6.954	0.43
6	44348	6	5.827	0.114	0.368	5.615	6.039	5.143	6.512	0.173
7	44438	6.1	5.487	0.129	0.373	5.247	5.727	4.793	6.181	0.613
8	44481	5	5.324	0.14	0.377	5.064	5.585	4.623	6.025	-0.324
9	44600	4.5	4.874	0.177	0.392	4.545	5.203	4.145	5.604	-0.374
10	44665	4.6	4.628	0.2	0.403	4.256	5	3.879	5.378	-0.0283

Residual
0.0759
-0.327
-0.156
-0.0818
0.43
0.173
0.613
-0.324
-0.374
-0.0283



CONSTANT

Yhat	Residuals
7.624	0.0759
7.227	-0.327
6.856	-0.156
6.482	-0.0818
6.27	0.43
5.827	0.173
5.487	0.613
5.324	-0.324
4.874	-0.374
4.628	-0.0283



CONSTANT

Shapiro-Wilks Test for Normality

		•				
	Residuals	Residuals	Column C-	Coeffiicien		
1	-0.374	0.613	0.987	0.5739	0.566439	
2	-0.327	0.43	0.757	0.3291	0.249129	
3	-0.324	0.173	0.497	0.2141	0.106408	
4	-0.156	0.0759	0.2319	0.1224	0.028385	
5	-0.0818	-0.0283	0.0535	0.0399	0.002135	
6	-0.0283	-0.0818	-0.0535	b=	0.952495	
7	0.0759	-0.156	-0.2319	StdDev=	0.265178	
8	0.173	-0.324	-0.497	SW=	1.433532	
9	0.43	-0.327	-0.757	Critical pt =	0.842	
10	0.613	-0.374	-0.987			

SW= Shapiro-Wilk Statistic

5%

Assume Normal

B-326-UD NITRATE

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:11:55 AM

From File COMPLIANCE DATA 2H2021_b.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9
Display Regresion Diagnostics True
Display Regresion Tables True

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9
Display Confidence Band True
Display Prediction Band True

Dependendant Variable (Y-Data) Nitrogen, Nitrate_b-326-ud

Number Reported (Y values) 10

Independent Variable (x-data) Sample Date_b-326-ud

Number Reported (x-values) 10

Regression Estimates and Inference Table

 Parameter
 Estimates
 Std. Error
 T-values
 p-values

 intercept
 801102
 533370
 1.502
 0.172

 mple Date_b-326
 -17.98
 12.26
 -1.467
 0.18

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	1.135E+9	1	1.135E+9	2.153	0.1805
Error	4.216E+9	8	5.270E+8		
Total	5.351E+9	9			

R Square 0.212
Adjusted R Square 0.114
Sqrt(MSE) = Scale 22957


Regression Table

	Obs	Y Vector	Yhat	Residuals	Res/Scale
1		19000	43659	-24659	-1.074
2		40000	30460	9540	0.416
3		66000	22260	43740	1.905
4		49000	18070	30930	1.347
5		9300	16488	-7188	-0.313
6		990	15229	-14239	-0.62
7		700	13305	-12605	-0.549
8		730	12172	-11442	-0.498
9		90	8522	-8432	-0.367
10)	90	5735	-5645	-0.246

	Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1		42122	19000	43659	18564	29523	9138	78180	-11241	98559	-24659
2		42856	40000	30460	10870	25400	10247	50673	-16772	77692	9540
3		43312	66000	22260	7678	24207	7982	36539	-22753	67274	43740


4	43545	49000	18070	7268	24080	4555	31586	-26707	62848	30930
5	43633	9300	16488	7400	24120	2728	30248	-28364	61340	-7188
6	43703	990	15229	7612	24186	1074	29385	-29746	60204	-14239
7	43810	700	13305	8104	24345	-1765	28375	-31966	58576	-12605
8	43873	730	12172	8475	24471	-3588	27933	-33333	57678	-11442
9	44076	90	8522	9989	25036	-10054	27098	-38034	55077	-8432
10	44231	90	5735	11378	25622	-15424	26893	-41910	53380	-5645

X Vector	Residual
42122	-24659
42856	9540
43312	43740
43545	30930
43633	-7188
43703	-14239
43810	-12605
43873	-11442
44076	-8432
44231	-5645



NOT CONSTANT

Yhat	Residuals
43659	-24659
30460	9540
22260	43740
18070	30930
16488	-7188
15229	-14239
13305	-12605
12172	-11442
8522	-8432
5735	-5645



NOT CONSTANT

Shapiro-Wilks Test for Normality

Residuals	Residuals	Column C-I	Coeffiicien	
ascending	descendin		t	
1 -24659	43740	68399	0.5739	39254.19
2 -14239	30930	45169	0.3291	14865.12
3 -12605	9540	22145	0.2141	4741.245
4 -11442	-5645	5797	0.1224	709.5528
5 -8432	-7188	1244	0.0399	49.6356
6 -7188	-8432	-1244	b=	59619.74
7 -5645	-11442	-5797	StdDev=	16164.59
8 9540	-12605	-22145	SW=	1.511499
9 30930	-14239	-45169	Critical pt =	0.842
10 43740	-24659	-68399		

SW= Shapiro-Wilk Statistic

5%

Assume Normal

BM-15N6 NITRATE

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:11:55 AM

From File COMPLIANCE DATA 2H2021_b.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9

Display Regresion Diagnostics True

Display Regresion Tables True

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9

Display Confidence Band True
Display Prediction Band True

Dependendant Variable (Y-Data) Nitrogen, Nitrate_bm-15n6

Number Reported (Y values) 10

Independent Variable (x-data) Sample Date_bm-15n6

Number Reported (x-values) 10

Regression Estimates and Inference Table

 Parameter
 Estimates
 Std. Error
 T-values
 p-values

 intercept
 429321
 105765
 4.059
 0.00364

 mple Date_bm-1!
 -8.936
 2.411
 -3.707
 0.00598

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	2.251E+8	1	2.251E+8	13.74	0.0060
Error	1.310E+8	8	16379610		
Total	3.561E+8	9			
	R Square	0.632			
Adjust	0.586				
Sqrt(N	ISE) = Scale	4047			


Regression Table

Obs	Y Vector	Yhat	Residuals	Res/Scale
1	43000	44796	-1796	-0.444
2	42000	43179	-1179	-0.291
3	49000	41579	7421	1.834
4	35000	39890	-4890	-1.208
5	42000	37835	4165	1.029
6	35000	36468	-1468	-0.363
7	32000	33912	-1912	-0.473
8	31000	33394	-2394	-0.592
9	30000	31839	-1839	-0.454
10	34000	30106	3894	0.962

Summary Table for Prediction and Confidence Limits


Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1	43032	43000	44796	2393	4702	40346	49247	36053	53540	-1796
2	43213	42000	43179	2038	4531	39389	46969	34753	51605	-1179
3	43392	49000	41579	1724	4399	38374	44784	33399	49759	7421
4	43581	35000	39890	1458	4302	37179	42602	31891	47890	-4890
5	43811	42000	37835	1288	4247	35440	40230	29937	45733	4165
6	43964	35000	36468	1299	4251	34052	38884	28564	44372	-1468
7	44250	32000	33912	1573	4342	30988	36837	25838	41987	-1912
8	44308	31000	33394	1658	4374	30311	36477	25261	41527	-2394
9	44482	30000	31839	1951	4493	28211	35468	23484	40194	-1839
10	44676	34000	30106	2325	4667	25783	34429	21427	38785	3894

X Vector	Residuals
43032	-1796
43213	-1179
43392	7421
43581	-4890
43811	4165
43964	-1468
44250	-1912
44308	-2394
44482	-1839
44676	3894



NOT CONSTANT

Yhat	Residuals
44796	-1796
43179	-1179
41579	7421
39890	-4890
37835	4165
36468	-1468
33912	-1912
33394	-2394
31839	-1839
30106	3894



NOT CONSTANT

Shapiro-Wilks Test for Normality

	Residuals ascending	Residuals (descendin	Column C-E	Coeffiicien t		SW= Shapiro-Wilk Statistic
1	-4890	7421	12311	0.5739	7065.283	
2	-2394	4165	6559	0.3291	2158.567	
3	-1912	3894	5806	0.2141	1243.065	
4	-1839	-1179	660	0.1224	80.784	
5	-1796	-1468	328	0.0399	13.0872	
6	-1468	-1796	-328	b=	10560.79	
7	-1179	-1839	-660	StdDev=	2954.793	
8	3894	-1912	-5806	SW=	1.419371	
9	4165	-2394	-6559	Critical pt =	0.842	5%
10	7421	-4890	-12311			
					Assume N	Normal

MW38-830N-230E CHLOROFORM

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:10:48 AM

From File COMPLIANCE DATA 2H2021_a.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9

Display Regresion Diagnostics True

Display Regresion Tables True

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9
Display Confidence Band True
Display Prediction Band True

Dependendant Variable (Y-Data) Chloroform_mw38-830n-230e

Number Reported (Y values) 10

Independent Variable (x-data) Sample Date_mw38-830n-230e

Number Reported (x-values) 10

Regression Estimates and Inference Table

 Parameter intercept
 Estimates 92.28
 Std. Error 37.43
 T-values 2.466
 0.039

 Date_mw38-830
 -0.00201
 8.5369E-4
 -2.351
 0.0466

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	11.16	1	11.16	5.527	0.0466
Error	16.16	8	2.02		
Total	27.32	9			
	R Square	0.409			
Adjusted R Square		0.335			
Sqrt(MS	SE) = Scale	1.421			

Regression Table


Obs	Y Vector	Yhat	Residuals	Res/Scale
1	6.9	5.9	1	0.703
2	6.2	5.547	0.653	0.459
3	5.9	5.34	0.56	0.394
4	5.4	4.805	0.595	0.419
5	2.1	4.455	-2.355	-1.657
6	2.1	4.259	-2.159	-1.519
7	2.6	3.679	-1.079	-0.759
8	4.3	3.37	0.93	0.655
9	3.7	3.004	0.696	0.49
10	3.8	2.641	1.159	0.816


Summary Table for Prediction and Confidence Limits

Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1	43040	6.9	5.9	0.816	1.639	4.384	7.417	2.853	8.947	1
2	43216	6.2	5.547	0.695	1.582	4.254	6.84	2.605	8.489	0.653
3	43319	5.9	5.34	0.631	1.555	4.168	6.513	2.449	8.232	0.56
4	43586	5.4	4.805	0.498	1.506	3.878	5.731	2.004	7.605	0.595
5	43760	2.1	4.455	0.454	1.492	3.611	5.3	1.681	7.23	-2.355
6	43858	2.1	4.259	0.45	1.491	3.422	5.095	1.487	7.031	-2.159
7	44147	2.6	3.679	0.521	1.514	2.709	4.648	0.864	6.494	-1.079
8	44301	4.3	3.37	0.599	1.542	2.256	4.483	0.502	6.237	0.93
9	44483	3.7	3.004	0.711	1.589	1.682	4.327	0.0492	5.959	0.696
10	44664	3.8	2.641	0.837	1.649	1.085	4.197	-0.426	5.708	1.159

X Vector Residuals


Residuals v. Time for MW38-830N-230E CFM






ANT

NOT CONSTANT





NOT CONSTANT

5%

Shapiro-Wilks Test for Normality

	Residuals	Residuals	Column C-l	Coefficien	
	ascending	descendin		t	
1	-2.355	1.159	3.514	0.5739	2.016685
2	-2.159	1	3.159	0.3291	1.039627
3	-1.079	0.93	2.009	0.2141	0.430127
4	0.56	0.696	0.136	0.1224	0.016646
5	0.595	0.653	0.058	0.0399	0.002314
6	0.653	0.595	-0.058	b=	3.505399
7	0.696	0.56	-0.136	StdDev=	1.353959
8	0.93	-1.079	-2.009	SW=	0.744768
9	1	-2.159	-3.159	Critical pt =	0.842
10	1.159	-2.355	-3.514		

SW= Shapiro-Wilk Statistic

MW62-WDR 1,4-DIOXANE

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:08:16 AM

From File COMPLIANCE DATA 2H2021.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9
Display Regresion Diagnostics True
Display Regresion Tables True

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9

Display Confidence Band True

Display Prediction Band True

Dependendant Variable (Y-Data) 1,4-Dioxane_mw62-wdr

Number Reported (Y values) 10

Independent Variable (x-data) Sample Date_mw62-wdr

Number Reported (x-values) 10

Regression Estimates and Inference Table

 Parameter
 Estimates
 Std. Error
 T-values
 p-values

 intercept
 34.75
 3.861
 9.001
 1.8522E-5

 sple Date_mw62 - 7.116E-4
 8.7990E-5
 -8.087
 4.0403E-5

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	1.32	1	1.32	65.4	0.0000
Error	0.161	8	0.0202		
Total	1.481	9			
	R Square	0.891			
Adjusted R Square		0.877			
Sqrt(MS	SE) = Scale	0.142			


Regression Table

Obs	Y Vector	Yhat	Residuals	Res/Scale
1	3.9	4.032	-0.132	-0.928
2	4.2	3.986	0.214	1.504
3	3.8	3.928	-0.128	-0.901
4	3.9	3.724	0.176	1.241
5	3.5	3.569	-0.0693	-0.488
6	3.4	3.463	-0.0633	-0.446
7	3.2	3.335	-0.135	-0.947
8	3.3	3.216	0.0843	0.593
9	3.2	3.085	0.115	0.806
10	2.9	2.962	-0.0617	-0.434

	Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1		43166	3.9	4.032	0.0766	0.161	3.889	4.174	3.732	4.332	-0.132
2		43230	4.2	3.986	0.0721	0.159	3.852	4.12	3.69	4.283	0.214
3		43312	3.8	3.928	0.0666	0.157	3.804	4.052	3.636	4.22	-0.128


4	43599	3.9	3.724	0.0509	0.151	3.629	3.818	3.443	4.004	0.176
5	43816	3.5	3.569	0.0452	0.149	3.485	3.653	3.292	3.847	-0.0693
6	43965	3.4	3.463	0.0457	0.149	3.378	3.548	3.186	3.741	-0.0633
7	44146	3.2	3.335	0.051	0.151	3.24	3.429	3.054	3.615	-0.135
8	44313	3.3	3.216	0.0594	0.154	3.105	3.326	2.929	3.502	0.0843
9	44496	3.2	3.085	0.071	0.159	2.953	3.217	2.79	3.381	0.115
10	44670	2.9	2.962	0.0834	0.165	2.807	3.117	2.655	3.268	-0.0617

X Vector	Residuals
43166	-0.132
43230	0.214
43312	-0.128
43599	0.176
43816	-0.0693
43965	-0.0633
44146	-0.135
44313	0.0843
44496	0.115
44670	-0.0617



CONSTANT

Yhat	Residuals
4.032	-0.132
3.986	0.214
3.928	-0.128
3.724	0.176
3.569	-0.0693
3.463	-0.0633
3.335	-0.135
3.216	0.0843
3.085	0.115
2.962	-0.0617



CONSTANT

Shapiro-Wilks Test for Normality

	•			
Residuals	Residuals	Column C-	l Coeffiicien	
ascending	descendin		t	
1 -0.135	0.214	0.349	0.5739	0.200291
2 -0.132	0.176	0.308	0.3291	0.101363
3 -0.128	0.115	0.243	0.2141	0.052026
4 -0.0693	0.0843	0.1536	0.1224	0.018801
5 -0.0633	-0.0617	0.0016	0.0399	6.38E-05
6 -0.0617	-0.0633	-0.0016	b=	0.372545
7 0.0843	-0.0693	-0.1536	StdDev=	0.117722
8 0.115	-0.128	-0.243	SW=	1.112748
9 0.176	-0.132	-0.308	Critical pt =	0.842
10 0.214	-0.135	-0.349		

SW= Shapiro-Wilk Statistic

Assume Normal

5%

MW106-UD 1,4-DIOXANE

Ordinary Least Squares Linear Regression Output Sheet

User Selected Options

Date/Time of Computation ProUCL 5.11/24/2022 10:08:16 AM

From File COMPLIANCE DATA 2H2021.xls

Full Precision OFF

Display Limits True

Confidence Level for Intervals 0.9
Display Regresion Diagnostics True
Display Regresion Tables True

Title For Y vs X Plots Classical Regression

Confidence Level for Regression Line 0.9

Display Confidence Band True
Display Prediction Band True

Dependendant Variable (Y-Data) 1,4-Dioxane_mw106-ud

Number Reported (Y values) 10

Independent Variable (x-data) Sample Date_mw106-ud

Number Reported (x-values) 10

Regression Estimates and Inference Table

Parameter	Estimates	Std. Error	T-values	p-values
intercept	20.8	13.53	1.538	0.163
nple Date_mw10	-4.806E-4	3.2788E-4	-1.466	0.181

OLS ANOVA Table

Source of Variation	SS	DOF	MS	F-Value	P-Value
Regression	7.203	1	7.203	2.149	0.1809
Error	26.82	8	3.352		
Total	34.02	9			
	R Square	0.212			
Adjuste	d R Square	0.113			
Sqrt(MS	SE) = Scale	1.831			


Regression Table

	Obs	Y Vector	Yhat	Residuals	Res/Scale
	1	0.5	2.036	-1.536	-0.839
2	2	6.5	1.989	4.511	2.464
;	3	0.5	1.948	-1.448	-0.791
4	4	0.5	1.558	-1.058	-0.578
ţ	5	0.5	1.216	-0.716	-0.391
(6	0.5	0.861	-0.361	-0.197
-	7	0.5	0.52	-0.0196	-0.0107
8	3	0.15	0.162	-0.012	-0.00658
,	9	0.15	-0.0201	0.17	0.0929
1	0	0.09	-0.38	0.47	0.256

Obs	X Vector	Y Vector	Yhat	s(Yhat)	s(pred)	LCL	UCL	LPL	UPL	Residuals
1	39042	0.5	2.036	0.92	2.049	0.326	3.747	-1.774	5.847	-1.536
2	39141	6.5	1.989	0.895	2.038	0.325	3.653	-1.801	5.778	4.511
3	39227	0.5	1.948	0.873	2.029	0.323	3.572	-1.825	5.72	-1.448


4	40037	0.5	1.558	0.697	1.959	0.262	2.855	-2.085	5.201	-1.058
5	40750	0.5	1.216	0.599	1.927	0.101	2.33	-2.367	4.798	-0.716
6	41487	0.5	0.861	0.586	1.922	-0.227	1.95	-2.713	4.436	-0.361
7	42198	0.5	0.52	0.662	1.947	-0.711	1.75	-3.101	4.14	-0.0196
8	42942	0.15	0.162	0.808	2.001	-1.341	1.665	-3.56	3.884	-0.012
9	43321	0.15	-0.0201	0.9	2.04	-1.693	1.653	-3.814	3.773	0.17
10	44069	0.09	-0.38	1.099	2.135	-2.423	1.663	-4.35	3.591	0.47

X Vector	Residual
39042	-1.536
39141	4.511
39227	-1.448
40037	-1.058
40750	-0.716
41487	-0.361
42198	-0.0196
42942	-0.012
43321	0.17
44069	0.47



NOT CONSTANT

Yhat	Residuals
2.036	-1.536
1.989	4.511
1.948	-1.448
1.558	-1.058
1.216	-0.716
0.861	-0.361
0.52	-0.0196
0.162	-0.012
-0.0201	0.17
-0.38	0.47



SW= Shapiro-Wilk Statistic

NOT CONSTANT

Shapiro-Wilks Test for Norm	nality			
	Residuals descendin	Column C-	Coeffiicien t	
1 -1.536	4.511	6.047	0.5739	3.470373
2 -1.448	0.47	1.918	0.3291	0.631214
3 -1.058	0.17	1.228	0.2141	0.262915
4 -0.716	-0.012	0.704	0.1224	0.08617
5 -0.361	-0.0196	0.3414	0.0399	0.013622
6 -0.0196	-0.361	-0.3414	b=	4.464293
7 -0.012	-0.716	-0.704	StdDev=	0.725263
8 0.17	-1.058	-1.228	SW=	4.209896
9 0.47	-1.448	-1.918	Critical pt =	0.842

-6.047

-1.536

10 4.511

Assume Normal

APPENDIX C-3.6 COMPLIANCE EVALUATION STATISTICAL TESTING

Upper Control Limit Analysis for Data Without Trends

	А	В	С	D	Е	F	G		Н		I	J	k	〈	L
1				No	ormal UCL S	Statistics for I	Uncensored	Full [Data Se	ets					
2															
3			cted Options												
4	Dat	te/Time of Co		ProUCL 5.2	8/5/2022 10	:57:43 AM									
5			From File	COMPLIANO	CE DATA by	/ Constituent	1H2022 Pro) UCL	Input N	/JS.x	ls				
6			II Precision	OFF											
7		Confidence	Coefficient	90%											
8															
67															
68	1,4-Dioxane	(b-326-wd)													
69															
70							Statistics								
71			Total	Number of O	bservations	10						r of Distinc			10
72										1	Number	r of Missing			0
73					Minimum									Mean	6.147
74					Maximum			Median 3.75 SD of logged Data 1.00							
75					SD							SD			1.002
76				Coefficient	of Variation	0.841							Skev	vness	1.093
77															
78							GOF Test								
79				hapiro Wilk T							-	lk GOF Te			
80			1% St	napiro Wilk C				Da	ata appe			t 1% Signif		evel	
81					est Statistic							GOF Test			
82			1'	% Lilliefors C			40/ 01 10			ear No	ormal a	t 1% Signit	licance Le	evel	
83					Data appe	ar Normal at	1% Signific	ance	Level						
84							151.0								
85			000/ 11	11101	As	suming Norr	mai Distribut	lion	000/		/A !!				
86			90% No	ormal UCL		0.400						sted for SI			
87				90% Stud	dent's-t UCL	8.409					•	ed-CLT UC	•		8.646
88										90%	Modifie	ed-t UCL (、	Johnson-	19/8)	8.503
89															
90							UCL to Use								
91				Recom	mendation	Provided onl	y tor 95% Co	onfide	ence Co	oeffici	ent				
92															

	А	В	С	D	Е	F	G	Н		ı		J		K	L
1				Nor	rmal UCL S	Statistics for I	Uncensored	Full Data S	Sets						
2															
3			cted Options												
4	D	ate/Time of Co		ProUCL 5.2 8											
5			From File	COMPLIANC	E DATA b	y Constituent	1H2022 Pro	UCL Input	MJS_	_e.xls					
6			II Precision	OFF											
7		Confidence	Coefficient	90%											
8															
9															
10	Tetrachlor	roethene (bm-	-11x-100n)												
11															
12							Statistics								
13			Tota	al Number of Ob	servations	10				Numbe					10
14										Numbe	r of M	issing (0
15					Minimum									Mean	6.05
16					Maximum									ledian	6.15
17					SD							SD of	flogged		0.149
18				Coefficient	of Variation	0.143							Skev	wness	-0.468
19															
20							GOF Test								
21				Shapiro Wilk Te						apiro Wi					
22			1% S	Shapiro Wilk Cr				Data ap					ance L	evel	
23				Lilliefors Te						illiefors.					
24				1% Lilliefors Cr				Data ap		Normal a	it 1%	Signific	ance L	evel	
25	4				Data appe	ear Normal at	1% Significa	ance Leve	l						
26															
27			000/ 11		A:	ssuming Norr	mal Distributi			. ,,			,		
28			90% N	lormal UCL		0.400		90		Ls (Adju					0.070
29				90% Stude	ent's-t UCL	6.429				Adjuste			•		6.372
30									90%	% Modifi	ed-t L	JCL (Jo	nnson-	19/8)	6.422
31						0									
32							UCL to Use								
33				Recomm	mendation	Provided onl	y tor 95% Co	ontidence	Coeffic	cient					
34		N	1.71.1			4	(Cl	1.1		-					
35		Note: For		atively-skewed									nay not	. De	
36			reliable.	Chen's and Jo	nnson's m	etnoas provid	de adjustmer	its for posi	itvely	skewed	data	sets.			
37															

	Α	В	С	D	Е		F	G	ŀ					J		K	L	
1				No	rmal U	CL S	tatistics for I	Uncensored	Full Da	ata Se	ts							
2																		
3			cted Options															
4	Dat	e/Time of Co		ProUCL 5.2														
5			From File	COMPLIANO	CE DAT	A by	Constituent	1H2022 Pro	UCL I	nput N	IJS_	f.xls						
6			II Precision	OFF														
7		Confidence	Coefficient	90%														
8																		
9			100)															
10	Trichloroeth	ene (bm-11)	x-100n)															
11								O										
12			.	N 1 10				Statistics					(D.				40	
13			I otal	Number of O	bservati	ons	10					Number					10	
14					N di i		2.0					Number	Of IVII	ssing (Doser		0	
15					Minin		3.6 5.7									Mean Median	4.74 4.75	
16					Maxin	SD								CD of				
17				Coefficient	of \/orio		0.602 0.127							20 01		d Data wness	0.13 -0.174	
18				Coemicient	oi valia	uon	0.127								SKE	wiless	-0.172	+
19							Normal (GOF Test										
20			9	hapiro Wilk T	act Stat	ictic		JOF 1631			Shr	apiro Wi	ᆘᄋ	E Toct				
21				napiro Wilk Ci			0.781		Date	a anne		lormal a				evel		
22			170 3	Lilliefors T			0.133		Date	а арре		illiefors			arice i	Levei		
23			1	% Lilliefors C			0.304		Data	a anne		lormal a			ance l	evel		
24			•	70 20.0.0				1% Signific					,	J.g				
25 26								,										
26 27						As	suming Norr	mal Distribut	ion									
28			90% No	rmal UCL						90%	UCI	Ls (Adju	sted f	or Ske	wness	3)		
29				90% Stud	lent's-t l	JCL	5.003				90%	Adjuste	ed-CL	T UCL	(Chen	-1995)	4.97	7
30											90%	6 Modifie	ed-t U	CL (Jo	hnson	-1978)	5.00	2
31							I	<u> </u>										
32							Suggested	UCL to Use										
33				Recom	mendat	ion l	Provided onl	y for 95% Co	onfider	nce Co	effic	cient						
34																		
35		Note: For	highly negat	ively-skewed	data, c	onfic	dence limits	(e.g., Chen,	Johnso	on, Lo	gnor	mal, an	d Gan	nma) n	nay no	t be		
36			reliable.	Chen's and Jo	ohnson's	s me	thods provid	de adjustmei	nts for	positv	ely s	skewed	data s	sets.				
37																		

	Α	В	С	D	Е		F	G	Н			J	K	L
1				N	ormal U	JCL S	tatistics for	Uncensored	Full Data S	ets				
2														
3			cted Options											
4	Dat	e/Time of Co		ProUCL 5.2										
5			From File		ICE DA	TA by	Constituent	1H2022 Pro	UCL Input	MJS.	xls			
6			II Precision	OFF										
7		Confidence	Coefficient	90%										
8														
171														
172	1,4-Dioxane	(mw38-830	<mark>)n-230e)</mark>											
173														
174								Statistics						- 10
175			Total	Number of 0	Observa	itions	10					r of Distinct C		
176									Number of Missing Observation					
177						mum	2		Mean					
178					Maxi		13		Median					
179						SD	4.063		SD of logged Data					
180				Coefficien	t of Vari	ation	0.664						Skewnes	s 0.747
181														
182								GOF Test						
183				hapiro Wilk			0.876				•	lk GOF Test		
184			1% SI	hapiro Wilk (0.781		Data ap			t 1% Signific	ance Level	
185				Lilliefors			0.246			_		GOF Test		
186			1	% Lilliefors (0.304	40/ 01 10			Normal a	t 1% Signific	ance Level	
187					Data	appe	ar Normal at	1% Significa	ance Level					
188														
189			000/ N			AS	suming Nori	mal Distributi		v 110	l - /A -!!-	-4- d f Ol		
190			90% No	ormal UCL	-11- 4	1101	7 007		90			sted for Ske	· -	7 000
191				90% Stu	dent's-t	UCL	7.897				•	ed-CLT UCL	•	1
192										90%	6 Moaitie	ed-t UCL (Jo	nnson-1978	7.948
193														
194				D		.al				\ #	-1			
195				Recor	nmenda	ition i	Provided onl	y for 95% Co	ontidence (Joeπic	cient			
196														

	Α	В	С	D	Е	F	G	Н	l	J	K	L		
1				Nort	mal UCL St	atistics for I	Data Sets wit	h Non-Detec	cts					
2														
3			cted Options											
4	Dat	te/Time of Co	<u> </u>	ProUCL 5.2 8										
5			From File	COMPLIANC	E DATA by	Constituent	1H2022 Pro	UCL Input N	IJS_d.xls					
6			Il Precision	OFF										
7		Confidence		90%										
8	Number o	of Bootstrap	Operations	2000										
9	Nitrogon N	itrite (mw62-	wdr)											
10	ividogen, iv	itilite (IIIWOZ-	wui j											
11						General	Statistics							
12			Total	Number of Ob	servations	10			Numbe	r of Distinct (Observations	10		
13			10101		of Detects	9			Tunibo	Number of Non-Detects 1				
14			N	umber of Distir		9			Numbe		Non-Detects	 1		
15					um Detect	890			- Tunib		Non-Detect	980		
16					um Detect	5400					Non-Detect	980		
17					ce Detects						Non-Detects	10%		
18	Mean Detects					2466					SD Detects	1385		
19 20	Median Detects Median Detects					2100					CV Detects	0.562		
21	Skewness Detects				ss Detects	1.422				Kurt	tosis Detects	1.76		
22				Mean of Logge	ed Detects	7.685				SD of Log	ged Detects	0.524		
23														
24	Normal GOF Test on Detects Only													
25	Shapiro Wilk Test Statistic 0.851 Shapiro Wilk GOF Test													
26	1% Shapiro Wilk Critical Value 0.764 Detected Data appear Normal at 1% Significance Level													
27	Lilliefors Test Statistic 0.297 Lilliefors GOF Test													
28			1	% Lilliefors Cri	tical Value	0.316	De	etected Data	appear Norr	mal at 1% Sig	gnificance Lev	/el		
29				Dete	cted Data a	ppear Norn	nal at 1% Sig	nificance Le	vel					
30				Note (GOF tests r	may be unre	eliable for sm	all sample s	izes					
31														
32			Kaplan-	Meier (KM) Sta			ritical Values	and other N	lonparametr					
33					KM Mean	2308					KM Variance	444.8		
34					KM SD	1326			KI		rror of Mean			
35				·	BCA) UCL	3060					/ (BCA) UCL	3277		
36					KM (t) UCL	2923					otstrap) UCL	2864		
37					M (z) UCL	2878					otstrap t UCL	3429		
38				90% KM Cheby		3642					ebyshev UCL	4247		
39			97	.5% KM Cheby	snev UCL	5086				99% KIVI Che	ebyshev UCL	6734		
40						פ מי וח	tatistics							
41			ו פיו וח	Normal		טטע פ	าเสนอแบช		DI /2 I og 3	ransformed				
42			ושטע	Mean in Oriç	ninal Scale	2268			PUZ LOY-I		in Log Scale	7.536		
43					ginal Scale	1448					in Log Scale	0.683		
44 45			90% † 1	JCL (Assumes		2901					H-Stat UCL	3552		
45				is not a recom			ded for comp	arisons and	historical re		0.0. 002			
46 47			222			p. 071		und						
47						Sugaested	UCL to Use							
48 49				Recomn			ly for 95% Co	onfidence Co	efficient					
														
50														

	Α	В	С	D	E	F	G	Н		I	J	K	L
1				Nonparar	netric UC	L Statistics	for Uncenso	red Full	Data	Sets			
2													
3			cted Options										
4	Da	te/Time of Co		ProUCL 5.2 8/5									
5			From File	COMPLIANCE	DATA by	Constituent	1H2022 Pro	UCL In	put M	JS_c.xls			
6			II Precision	OFF									
7		Confidence		90%									
8	Number	of Bootstrap	Operations	2000									
9													
100	.												
101													
102	O constant of the constant of												
103													
104			lotai	ervations	10							0	
105				Minimum	110000				Numbe	r of Missing C		120000	
106					Maximum							Median	
107	SE										C+4 E		
108	SD 6667 Std. Error of Mean 2108 Coefficient of Variation 0.0556 Skewness 0												
109	M (I ID) 4400							0.0557					
110				wearr or logg	ged Data	11.03					3D 0I	logged Data	0.0337
111				No	nnarame	etric Distribut	tion Free UC	I Statis	tics				
112					•		ted at 1% Si			evel			
113 114								3					
115					As	suming Norr	nal Distributi	on					
116			90% No	ormal UCL					90%	UCLs (Adju	sted for Ske	wness)	
117				90% Student	t's-t UCL	122916					ed-CLT UCL		122702
118											ed-t UCL (Jo	` ′	
119						1	1						
120					Nonpa	rametric Dist	ribution Free	UCLs					
121				90% C	CLT UCL	122702					90% BCA Bo	otstrap UCL	N/A
122			90%	Standard Bootst	trap UCL	N/A					90% Boo	tstrap-t UCL	N/A
123			9	0% Hall's Bootst	trap UCL	N/A				90%	Percentile Bo	otstrap UCL	N/A
124			90% Ch	ebyshev(Mean,	Sd) UCL	126325				95% Cł	nebyshev(Me	an, Sd) UCL	129189
125			97.5% Ch	ebyshev(Mean,	Sd) UCL	133166				99% Cł	nebyshev(Me	an, Sd) UCL	140976
126													
127						Suggested	UCL to Use						
128				Data ap	pear No	rmal, May wa	ant to try Nor	mal Dis	stribut	tion			
129													

1		Normal UCL St	atistics for U	Incensored Full Data Sets						
2										
3	User Selected Options									
4	'	ProUCL 5.2 8/5/2022 10:								
5		•	Constituent	1H2022 Pro UCL Input MJS.xls						
6		OFF								
7	Confidence Coefficient	90%								
8										
223										
224	1,4-Dioxane (mw77-wd)									
225										
226			General S							
227	Total	Number of Observations	10	Number of Distinct Observations	9					
228				Number of Missing Observations	0					
229		Minimum	2.6	Mean	8.02					
230		Maximum	16	Median	7.15					
231		SD	4.596	SD of logged Data	0.637					
232		Coefficient of Variation	0.573	Skewness	0.396					
233										
234			Normal G							
235		napiro Wilk Test Statistic	0.914	Shapiro Wilk GOF Test						
236	1% Sh	apiro Wilk Critical Value	0.781	Data appear Normal at 1% Significance Level						
237		Lilliefors Test Statistic	0.223	Lilliefors GOF Test						
238	19	6 Lilliefors Critical Value	0.304	Data appear Normal at 1% Significance Level						
239		Data appea	ar Normal at	1% Significance Level						
240										
241			suming Norm	nal Distribution						
242	90% No	rmal UCL		90% UCLs (Adjusted for Skewness)						
243	90% Student's-t UCL 10.03 90% Adjusted-CLT UCL (Chen-1995) 10.01									
244				90% Modified-t UCL (Johnson-1978)	10.06					
245										
246			Suggested I							
247		Recommendation P	rovided only	r for 95% Confidence Coefficient						
248										

G

Н

J

K

Α

В

С

D

Ε

APPENDIX C-4 EFFECTIVENESS ASSESSMENT

APPENDIX C-4.1 EFFECTIVENESS ASSESSMENT


Determination of Hydraulic Gradients (PM-1I & X through PM-15I & X)

MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-1I	7/15/2020	5771.40	PM-1X	7/15/2020	5772.50	-1.10
PM-1I	10/8/2020	5771.57	PM-1X	10/8/2020	5772.23	
PM-1I	1/11/2021	5771.36	PM-1X	1/11/2021	5771.72	
PM-1I	4/5/2021	5770.76		4/5/2021	5771.07	-0.31
PM-1I	7/14/2021	5771.24	PM-1X	7/14/2021	5774.02	-2.78
PM-1I	10/7/2021	5771.72		10/7/2021	5773.19	
PM-1I	1/18/2022	5771.43	PM-1X	1/18/2022	5772.15	
PM-1I	4/6/2022	5770.70	PM-1X	4/6/2022	5771.33	-0.63

Mean Interior Water Level Mean Exterior Water Level	5771.27 5772.28	Minimum Maximum Avg. Diff Diff of the Means	-2.78 -0.31 -1.00 -1.00
Sum of the Squares of Deviations			
Interior	0.93		
Exterior	6.60		
Standard Deviation (pooled)	0.73		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.33	80% LCL	-1.33
95% Confidence Interval	0.69	95% UCL	-0.31

Data Sufficiency

PM-1 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-2I	7/13/2020	5770.2	PM-2X	7/13/2020	5777.21	-7.01
PM-2I	10/5/2020	5770.11	PM-2X	10/5/2020	5777.09	-6.98
PM-2I	1/6/2021	5770.08	PM-2X	1/6/2021	5777.06	-6.98
PM-2I	4/6/2021	5770.31	PM-2X	4/6/2021	5777.40	-7.09
PM-2I	7/6/2021	5769.95	PM-2X	7/6/2021	5776.96	-7.01
PM-2I	10/1/2021	5769.92	PM-2X	10/1/2021	5776.91	-6.99
PM-2I	1/6/2022	5770	PM-2X	1/6/2022	5777.02	-7.02
PM-2I	4/8/2022	5769.82	PM-2X	4/8/2022	5776.84	-7.02

Mean Interior Water Level Mean Exterior Water Level	5770.05 5777.06	Minimum Maximum Avg. Diff Diff of the Means	-7.09 -6.98 -7.01 -7.01
Sum of the Squares of Deviations			
Interior	0.18		
Exterior	0.22		
Standard Deviation (pooled)	0.17		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.08	80% LCL	-7.09
95% Confidence Interval	0.16	95% UCL	-6.85

Data Sufficiency

PM-2 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-3I	7/13/2020	5779.12	PM-3X	7/13/2020	5778.40	0.72
PM-3I	10/5/2020	5778.96	PM-3X	10/5/2020	5778.24	0.72
PM-3I	1/6/2021	5778.91	PM-3X	1/6/2021	5778.18	0.73
PM-3I	4/6/2021	5779.22	PM-3X	4/6/2021	5778.57	0.65
PM-3I	7/6/2021	5778.64	PM-3X	7/6/2021	5778.07	0.57
PM-3I	10/1/2021	5778.60	PM-3X	10/1/2021	5778.13	0.47
PM-3I	1/6/2022	5778.74	PM-3X	1/6/2022	5778.39	0.35
PM-3I	4/8/2022	5778.46	PM-3X	4/8/2022	5778.29	0.17

		Minimum	0.17
		Maximum	0.73
Mean Interior Water Level	5778.83	Avg. Diff	0.55
Mean Exterior Water Level	5778.28	Diff of the Means	0.55
Sum of the Squares of Deviations			
Interior	0.49		
Exterior	0.19		
Standard Deviation (pooled)	0.22		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.10	80% LCL	0.45
95% Cpnfidence Interval	0.21	95% UCL	0.76

Effectiveness Decision
Outward Gradient exists

Data Sufficiency

PM-3 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-4I	7/13/2020	5793.65	PM-4X	7/13/2020	5793.92	-0.27
PM-4I	10/5/2020	5793.41	PM-4X	10/5/2020	5793.70	-0.29
PM-4I	1/6/2021	5793.32	PM-4X	1/6/2021	5793.65	-0.33
PM-4I	4/6/2021	5793.43	PM-4X	4/6/2021	5793.77	-0.34
PM-4I	7/6/2021	5793.2	PM-4X	7/6/2021	5793.59	-0.39
PM-4I	10/1/2021	5793.14	PM-4X	10/1/2021	5793.52	-0.38
PM-4I	1/6/2022	5793.37	PM-4X	1/6/2022	5793.80	-0.43
PM-4I	4/8/2022	5793.31	PM-4X	4/8/2022	5793.85	-0.54

Mean Interior Water Level Mean Exterior Water Level	5793.35 5793.73	Minimum Maximum Avg. Diff Diff of the Means	-0.54 -0.27 -0.37 -0.37
Sum of the Squares of Deviations			
Interior	0.17		
Exterior	0.13		
Standard Deviation (pooled)	0.15		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.0653	80% LCL	-0.44
95% Confidence Interval	0.1380	95% UCL	-0.23

Data Sufficiency

PM-4 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-5I	7/13/2020	5799.19	PM-5X	7/13/2020	5799.54	-0.35
PM-5I	10/5/2020	5798.65	PM-5X	10/5/2020	5799.71	-1.06
PM-5I	1/6/2021	5798.24	PM-5X	1/6/2021	5799.46	-1.22
PM-5I	4/7/2021	5798.07	PM-5X	4/7/2021	5799.17	-1.10
PM-5I	7/6/2021	5799.84	PM-5X	7/6/2021	5799.81	0.03
PM-5I	10/1/2021	5799.04	PM-5X	10/1/2021	5799.93	-0.89
PM-5I	1/6/2022	5798.61	PM-5X	1/6/2022	5799.84	-1.23
PM-5I	4/8/2022	5798.17	PM-5X	4/8/2022	5799.29	-1.12

		Minimum Maximum	-1.23 0.03
Mean Interior Water Level	5798.73	Avg. Diff	-0.87
Mean Exterior Water Level	5799.59	Diff of the Means	-0.87
Sum of the Squares of Deviations			
Interior	2.55		
Exterior	0.53		
Standard Deviation (pooled)	0.47		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.21	80% LCL	-1.08
95% Confidence Interval	0.44	95% UCL	-0.42

Data Sufficiency

PM-5 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Diffe	rence
PM-6I	7/13/2020	5797.64	PM-6X	7/13/2020	5793.81		3.83
PM-6I	10/5/2020	5797.67	PM-6X	10/5/2020	5793.70		3.97
PM-6I	1/6/2021	5797.62	PM-6X	1/6/2021	5793.53		4.09
PM-6I	4/7/2021	5797.73	PM-6X	4/7/2021	5793.65		4.08
PM-6I	7/8/2021	5797.80	PM-6X	7/8/2021	5793.81		3.99
PM-6I	10/1/2021	5797.76	PM-6X	10/1/2021	5793.76		4
PM-6I	1/6/2022	5797.99	PM-6X	1/6/2022	5793.98		4.01
PM-6I	4/8/2022	5797.80	PM-6X	4/8/2022	5793.65		4.15

		Minimum Maximum	3.83 4.15
Mean Interior Water Level	5797.75	Avg. Diff	4.02
Mean Exterior Water Level	5793.74	Diff of the Means	4.01
Sum of the Squares of Deviations			
Interior	0.10		
Exterior	0.13		
Standard Deviation (pooled)	0.13		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.06	80% LCL	3.96
95% Cpnfidence Interval	0.12	95% UCL	4.14
50 / Opiniacinoc interval	0.12	00 /0 OOL	7.17

Effectiveness Decision
Outward Gradient exists

Data Sufficiency

PM-6 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-7I	7/13/2020	5811.07	PM-7X	7/13/2020	5818.49	-7.42
PM-7I	10/5/2020	5811.04	PM-7X	10/5/2020	5818.22	-7.18
PM-7I	1/6/2021	5810.84	PM-7X	1/6/2021	5817.72	-6.88
PM-7I	4/7/2021	5810.75	PM-7X	4/7/2021	5817.29	-6.54
PM-7I	7/8/2021	5810.82	PM-7X	7/8/2021	5818.26	-7.44
PM-7I	10/1/2021	5810.79	PM-7X	10/1/2021	5818.13	-7.34
PM-7I	1/6/2022	5811.03	PM-7X	1/6/2022	5818.07	-7.04
PM-7I	4/8/2022	5810.48	PM-7X	4/8/2022	5817.1	-6.62

Mean Interior Water Level Mean Exterior Water Level	5810.85 5817.91	Minimum Maximum Avg. Diff Diff of the Means	-7.44 -6.54 -7.06 -7.06
Sum of the Squares of Deviations			
Interior	0.27		
Exterior	1.71		
Standard Deviation (pooled)	0.38		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.17	80% LCL	-7.23
95% Cpnfidence Interval	0.36	95% UCL	-6.70

Data Sufficiency

PM-7 well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-8I	7/13/2020	5817.07	PM-8X	7/13/2020	5826.39	-9.32
PM-8I	10/5/2020	5816.29	PM-8X	10/5/2020	5825.01	-8.72
PM-8I	1/6/2021	5815.59	PM-8X	1/6/2021	5824.34	-8.75
PM-8I	4/7/2021	5815.75	PM-8X	4/7/2021	5825.92	-10.17
PM-8I	7/8/2021	5816.84	PM-8X	7/8/2021	5826.77	-9.93
PM-8I	10/1/2021	5816.29	PM-8X	10/1/2021	5825.60	-9.31
PM-8I	1/6/2022	5816.07	PM-8X	1/6/2022	5825.26	-9.19
PM-8I	4/8/2022	5815.20	PM-8X	4/8/2022	5824.58	-9.38

		Minimum	-10.17
		Maximum	-8.72
Mean Interior Water Level	5816.14	Avg. Diff	-9.35
Mean Exterior Water Level	5825.48	Diff of the Means	-9.35
Sum of the Squares of Deviations			
Interior	2.74		
Exterior	5.08		
Standard Deviation (pooled)	0.75		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.33	80% LCL	-9.68
95% Cpnfidence Interval	0.71	95% UCL	-8.64

Data Sufficiency

PM-8 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-9I	7/13/2020	5816.45	PM-9X	7/13/2020	5825.56	-9.11
PM-9I	10/5/2020	5815.96	PM-9X	10/5/2020	5824.30	
PM-9I	1/6/2021	5815.58	PM-9X	1/6/2021	5823.35	-7.77
PM-9I	4/7/2021	5815.89	PM-9X	4/7/2021	5826.79	-10.90
PM-9I	7/8/2021	5816.62	PM-9X	7/8/2021	5826.89	-10.27
PM-9I	10/1/2021	5816.02	PM-9X	10/1/2021	5824.98	-8.96
PM-9I	1/6/2022	5815.73	PM-9X	1/6/2022	5824.09	-8.36
PM-9I	4/8/2022	5815.33	PM-9X	4/8/2022	5823.48	-8.15

Mean Interior Water Level	5815.95	Minimum Maximum Avg. Diff	-10.90 -7.77 -8.98
Mean Exterior Water Level	5824.93	Diff of the Means	-8.98
Sum of the Squares of Deviations			
Interior	1.28		
Exterior	13.40		
Standard Deviation (pooled)	1.02		
t-statistics degrees of freedom =	7		
α = 5%	1.89		
α = 20%	0.90		
80% Confidence Interval	0.46	80% LCL	-9.44
95% Confidence Interval	0.97	95% UCL	-8.01

Data Sufficiency

PM-9 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-10I	7/13/2020	5814.87	PM-10X	7/13/2020	5820.08	-5.21
PM-10I	10/5/2020	5814.27	PM-10X	10/5/2020	5818.66	-4.39
PM-10I	1/6/2021	5813.83	PM-10X	1/6/2021	5817.19	-3.36
PM-10I	4/7/2021	5813.87	PM-10X	4/7/2021	5818.60	-4.73
PM-10I	7/8/2021	5815.01	PM-10X	7/8/2021	5820.68	-5.67
PM-10I	10/1/2021		PM-10X	10/1/2021	5818.97	-4.69
PM-10I	1/6/2022		PM-10X	1/6/2022		-3.64
PM-10I	4/8/2022	5813.27	PM-10X	4/8/2022	5816.34	-3.07

	Minimum	-5.67
	Maximum	-3.07
5814.16	Avg. Diff	-4.35
5818.51	Diff of the Means	-4.35
2.32		
14.85		
1.11		
7		
1.89		
0.90		
0.50	80% LCL	-4.84
1.05	95% UCL	-3.30
	2.32 14.85 1.11 7 1.89 0.90	Maximum Avg. Diff 5818.51 Diff of the Means 2.32 14.85 1.11 7 1.89 0.90 0.50 80% LCL

Data Sufficiency

PM-10 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-11I	7/8/2020	5773.47	PM-11X	7/8/2020	5795.36	-21.89
PM-11I	10/12/2020	5773.37	PM-11X	10/12/2020	5794.84	-21.47
PM-11I	1/6/2021	5773.40	PM-11X	1/7/2021	5794.24	-20.84
PM-11I	4/9/2021	5773.73	PM-11X	4/9/2021	5793.74	-20.01
PM-11I	7/9/2021	5773.53	PM-11X	7/9/2021	5795.56	-22.03
PM-11I	10/5/2021	5773.39	PM-11X	10/5/2021	5794.85	-21.46
PM-11I	1/14/2022	5773.53	PM-11X	1/13/2022	5793.55	-20.02
PM-11I	4/7/2022	5773.74	PM-11X	4/7/2022	5792.79	-19.05

Mean Interior Water Level Mean Exterior Water Level	5773.52 5794.37	Minimum Maximum Avg. Diff Diff of the Means	-22.03 -19.05 -20.85 -20.85
Sum of the Squares of Deviations			
Interior	0.15		
Exterior	6.43		
Standard Deviation (pooled)	0.69		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.31	80% LCL	-21.15
95% Confidence Interval	0.65	95% UCL	-20.20

Data Sufficiency

PM-11 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-12I	7/8/2020	5763.08	PM-12X	7/8/2020	5767.99	-4.91
PM-12I	10/12/2020	5762.96	PM-12X	10/12/2020	5767.89	-4.93
PM-12I	1/7/2021	5762.91	PM-12X	1/7/2021	5768.02	-5.11
PM-12I	4/9/2021	5762.93	PM-12X	4/9/2021	5767.73	-4.80
PM-12I	7/9/2021	5762.86	PM-12X	7/9/2021	5767.15	-4.29
PM-12I	10/5/2021	5762.69	PM-12X	10/5/2021	5767.00	-4.31
PM-12I	1/13/2022	5762.65	PM-12X	1/13/2022	5767.38	-4.73
PM-12I	4/7/2022	5762.63	PM-12X	4/7/2022	5767.27	-4.64

Mean Interior Water Level Mean Exterior Water Level	5762.84 5767.55	Minimum Maximum Avg. Diff Diff of the Means	-5.11 -4.29 -4.72 -4.71
Sum of the Squares of Deviations			
Interior	0.19		
Exterior	1.13		
Standard Deviation (pooled)	0.31		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.14	80% LCL	-4.85
95% Confidence Interval	0.29	95% UCL	-4.42

Data Sufficiency

PM-12 Well Pair Hydrographs



MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev		Difference
PM-13I	7/8/2020	dry	PM-13X	7/8/2020	dry	not	calculated
PM-13I	10/12/2020	dry	PM-13X	10/12/2020	dry	not	calculated
PM-13I	1/7/2021	dry	PM-13X	1/7/2021	dry	not	calculated
PM-13I	4/9/2021	dry	PM-13X	4/9/2021	5752.16	not	calculated
PM-13I	7/9/2021	dry	PM-13X	7/9/2021	dry	not	calculated
PM-13I	10/5/2021	dry	PM-13X	10/5/2021	5752.11	not	calculated
PM-13I	1/13/2022	dry	PM-13X	1/13/2022	5752.11	not	calculated
PM-13I	4/7/2022	dry	PM-13X	4/7/2022	5752.29	not	calculated

		Minimum	not calculated
		Maximum	not calculated
Mean Interior Water Level	not calculated	Avg. Diff	not calculated
Mean Exterior Water Level	not calculated	Diff of the Means	not calculated

Sum of the Squares of Deviations

Interior not calculated
Exterior not calculated
Standard Deviation (pooled) not calculated

t-statistics degrees of freedom = 7


 $\alpha = 5\%$ 1.89 $\alpha = 20\%$ 0.90

80% Confidence Interval not calculated 80% LCL not calculated 95% Confidence Interval not calculated 95% UCL not calculated

<u>Effectiveness Decision</u> <u>Data Sufficiency</u>

Unable to calculate gradient

PM-13 Well Pair Hydrographs




MASTER LOC	Date	Water Elev	MASTER LOC	Date	Water Elev	Difference
PM-14I	7/8/2020	5748.94	PM-14X	7/8/2020	5747.78	1.16
PM-14I	10/12/2020	5748.76	PM-14X	10/12/2020	5747.69	1.07
PM-14I	1/7/2021	5748.91	PM-14X	1/7/2021	5747.88	1.03
PM-14I	4/9/2021	5748.96	PM-14X	4/9/2021	5747.91	1.05
PM-14I	7/9/2021	5748.97	PM-14X	7/9/2021	5747.90	1.07
PM-14I	10/5/2021	5749.09	PM-14X	10/5/2021	5748.11	0.98
PM-14I	1/13/2022	5749.19	PM-14X	1/13/2022	5748.23	0.96
PM-14I	4/7/2022	5748.99	PM-14X	4/7/2022	5747.98	1.01

Mean Interio	or Water Level	5748.98	Minimum Maximum Avg. Diff	0.96 1.16 1.04
			•	
Mean Exterio	or Water Level	5747.94	Diff of the Means	1.04
Sum of the S	Squares of Deviations			
	Interior	0.11		
	Exterior	0.21		
Standard Deviation (pooled)		0.15		
t-statistics	degrees of freedom =	7		
	$\alpha = 5\%$	1.89		
	α = 20%	0.90		
80% Confidence Interval		0.07	80% LCL	0.97
95% Cpnfide	ence Interval	0.14	95% UCL	1.18

Effectiveness Decision
Outward Gradient exists

Data Sufficiency

PM-14 Well Pair Hydrographs




MASTER LOC	Date		MASTER LOC	Date	Water Elev	Difference
PM-15I	7/8/2020		PM-15X	7/9/2020		
PM-15I	10/12/2020	5723.62	PM-15X	10/12/2020	5735.83	
PM-15I	1/6/2021	5723.63	PM-15X	1/7/2021	5735.76	
PM-15I	4/9/2021		PM-15X	4/9/2021	5735.50	
PM-15I	7/9/2021		PM-15X	7/9/2021	5736.91	-13.3
PM-15I	10/5/2021		PM-15X	10/5/2021	5737.04	
PM-15I	1/14/2022		PM-15X	1/13/2022	5736.48	-13.27
PM-15I	4/7/2022	5723.47	PM-15X	4/7/2022	5735.96	-12.49

Mean Interior Water Level Mean Exterior Water Level	5723.50 5736.17	Minimum Maximum Avg. Diff Diff of the Means	-13.84 -11.87 -12.67 -12.67
Sum of the Squares of Deviations			
Interior	0.24		
Exterior	2.28		
Standard Deviation (pooled)	0.42		
t-statistics degrees of freedom =	7		
$\alpha = 5\%$	1.89		
α = 20%	0.90		
80% Confidence Interval	0.19	80% LCL	-12.86
95% Confidence Interval	0.40	95% UCL	-12.27

Data Sufficiency

PM-15 Well Pair Hydrographs





APPENDIX C-4.2


EFFECTIVENESS ASSESSMENT


Trend Analysis for Wells with Outward Gradients (PM-3X, PM-6X, PM-13X, and PM-14X)


(Baseline Data Set)














Analysis prepared using DUMPSTAT and Sen's Test for trend Analysis prepared using DUMPSTAT and Sen's Test for trend



Analysis prepared using DUMPSTAT and Sen's Test for trend Analysis prepared using DUMPSTAT and Sen's Test for trend



Analysis prepared using DUMPSTAT and Sen's Test for trend Analysis prepared using DUMPSTAT and Sen's Test for trend



APPENDIX C-4.3

EFFECTIVENESS ASSESSMENT

Shewhart-CUSUM Test for Wells with Outward Gradients (PM-3X, PM-6X, PM-13X, and PM-14X)

Table 1

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Туре	Conf	П
1,1,1-trichloroethane	ug/L	PM-13X	16	22	38	1.4538	0.5385	0.1600	0.2000	1.4538	1.4538	3.8770	normal		
1,1,1-trichloroethane	ug/L	PM-14X	36	4	40			0.1600	0.1600			1.0000	nonpar	.99	**
1,1,1-trichloroethane	ug/L	PM-3X	36	1	37			1.0000	0.1600			1.0000	nonpar	.99	**
1,1,1-trichloroethane	ug/L	PM-6X	36	3	39			0.1600	0.1600			1.0000	nonpar	.99	**

N(back) and N(mon) = Non-outlier measurements in the background and monitoring periods.

N(tot) = All independent measurements for that constituent and well.
For transformed data, mean and SD in transformed units and control limit in original units.

Conf = confidence level for passing initial test or one verification resample (nonparametric test only).

^{* -} Insufficient Data. ** - Detection Frequency < 25%.

^{*** -} Zero Variance.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result	Outlier	CUSUM	Adjusted
1.1.1-trichloroethane	ug/L	PM-13X	09/22/2005		2.2000	- Cumor		rajuotou
1,1,1-trichloroethane		PM-13X	12/20/2005	yes	2.2000			
1,1,1-trichloroethane	ug/L	PM-13X	03/23/2006	yes	1.9000			
1,1,1-trichloroethane	ug/L	PM-13X	06/02/2006	yes	0.8600			
' '	ug/L	PM-13X	07/28/2006	yes	1.5000			
1,1,1-trichloroethane	ug/L			yes				
1,1,1-trichloroethane	ug/L	PM-13X	11/28/2006	yes	1.7000			
1,1,1-trichloroethane	ug/L	PM-13X	02/06/2007	yes	2.0000			
1,1,1-trichloroethane	ug/L	PM-13X	06/08/2007	yes	0.8100			
1,1,1-trichloroethane	ug/L	PM-13X	11/05/2007	yes	2.0000			
1,1,1-trichloroethane	ug/L	PM-13X	05/16/2008	yes	1.9000			
1,1,1-trichloroethane	ug/L	PM-13X	12/08/2008	yes	0.5900			
1,1,1-trichloroethane	ug/L	PM-13X	05/12/2009	yes	1.1000			
1,1,1-trichloroethane	ug/L	PM-13X	11/25/2009	yes	1.0000			
1,1,1-trichloroethane	ug/L	PM-13X	06/11/2010	yes	1.0000			
1,1,1-trichloroethane	ug/L	PM-13X	11/19/2010	yes	1.4000			
1,1,1-trichloroethane	ug/L	PM-13X	06/07/2011	yes	1.1000			
1,1,1-trichloroethane	ug/L	PM-13X	12/09/2011		1.1000		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/21/2012		0.7400		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/10/2012		0.8000		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/18/2013		0.8500		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/19/2013		0.8600		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/18/2014		0.7200		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/22/2014		0.5800		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/02/2015		0.7600		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/21/2015		0.8300		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/21/2016		0.6900		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/20/2016		0.6000		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/29/2017		0.5300		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	10/17/2017		0.4700		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/20/2018		0.4900		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	10/30/2018		0.5000		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/11/2019		0.4300		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	12/18/2019		0.1700		1.4538	
1,1,1-trichloroethane	ug/L	PM-13X	06/08/2020		0.9200		1.4538	

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1.1.1-trichloroethane	ug/L	PM-13X	12/21/2020		0.1600	ND		1.4538		
1,1,1-trichloroethane	ug/L	PM-13X	06/09/2021		0.1600	ND		1.4538		
1,1,1-trichloroethane	ug/L	PM-13X	11/03/2021		0.1600	ND		1.4538		
1,1,1-trichloroethane	ug/L	PM-13X	05/05/2022		0.2000			1.4538		
1,1,1-trichloroethane	ug/L	PM-14X	06/15/2004	yes	0.3100					
1,1,1-trichloroethane	ug/L	PM-14X	06/08/2005	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	08/26/2005	yes	0.2300					
1,1,1-trichloroethane	ug/L	PM-14X	11/21/2005	yes	0.2200					
1,1,1-trichloroethane	ug/L	PM-14X	02/21/2006	yes	0.1700					
1,1,1-trichloroethane	ug/L	PM-14X	06/12/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	07/26/2006	yes	0.1700					
1,1,1-trichloroethane	ug/L	PM-14X	11/28/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	02/05/2007	yes	0.2000					
1,1,1-trichloroethane	ug/L	PM-14X	08/02/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	10/17/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	05/05/2008	yes	0.1900					
1,1,1-trichloroethane	ug/L	PM-14X	10/29/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/16/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/11/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/27/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/02/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	05/04/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/29/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	05/21/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	10/25/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/23/2013	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	10/15/2013	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/24/2014	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	10/27/2014	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/20/2015	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/02/2015	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/20/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/01/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/20/2017	yes	0.1600	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
							Outilei	COSOW	_	****
1,1,1-trichloroethane	ug/L	PM-14X	10/13/2017	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/18/2018	yes	0.1600	ND			1.0000	
1,1,1-trichloroethane	ug/L	PM-14X	10/19/2018	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	04/26/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	11/07/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	05/13/2020	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-14X	12/15/2020		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-14X	05/20/2021		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-14X	10/26/2021		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-14X	04/21/2022		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-3X	06/13/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	08/01/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/12/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	02/08/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/08/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	08/10/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	10/23/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	02/22/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	05/09/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/11/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	05/12/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	11/25/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	05/27/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	11/19/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/02/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/08/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/12/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/05/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	05/28/2013	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/19/2013	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/18/2014	yes	0.1600	ND			1.0000	****
1.1.1-trichloroethane	ug/L	PM-3X	12/29/2014	yes	0.1600	ND			1.0000	****
1.1.1-trichloroethane	ug/L	PM-3X	06/03/2015	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/21/2015	yes	0.1600	ND			1.0000	****
	<u>, J</u>			, ,			1			1

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Comptituent	I I mida	VA/II	Dete	Daalamaaad	Daguill		041:	CUSUM	A al:a4a al	
Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,1,1-trichloroethane	ug/L	PM-3X	06/27/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/29/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/29/2017	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	10/17/2017	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/22/2018	yes	0.1600					
1,1,1-trichloroethane	ug/L	PM-3X	11/01/2018	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/11/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/18/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/08/2020	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	12/18/2020	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	06/08/2021	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	11/03/2021	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-3X	05/05/2022		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-6X	06/15/2004	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	09/22/2005	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/20/2005	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	03/23/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/02/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	07/28/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	11/28/2006	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	02/06/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	08/10/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	10/23/2007	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	05/09/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/08/2008	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	05/05/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	11/25/2009	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	05/27/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	11/19/2010	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/02/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/07/2011	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/21/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/05/2012	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	05/28/2013	yes	0.1600	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,1,1-trichloroethane	ug/L	PM-6X	12/16/2013	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/17/2014	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/22/2014	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/02/2015	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/23/2015	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/21/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/20/2016	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/29/2017	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	10/17/2017	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/21/2018	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	10/16/2018	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/12/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/18/2019	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/08/2020	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	12/18/2020	yes	0.1600	ND			1.0000	****
1,1,1-trichloroethane	ug/L	PM-6X	06/08/2021	-	0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-6X	11/03/2021		0.1600	ND				
1,1,1-trichloroethane	ug/L	PM-6X	05/05/2022		0.1600	ND				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.




Table 1

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Type	Conf	
1,1-dichloroethane	ug/L	PM-13X	19	19	38	36.2105	7.3905	22.0000	18.0000	36.2105	36.2105	69.4679	normal		
1,1-dichloroethane	ug/L	PM-14X	24	16	40	3.7500	0.4263	4.0000	3.0000	3.7500	3.7500	5.6684	normal		T
1,1-dichloroethane	ug/L	PM-3X	12	25	37	0.3617	0.2034	0.3700	0.5400	0.5947	0.6205	1.2770	normal		
1,1-dichloroethane	ug/L	PM-6X	36	3	39			0.2200	0.2200			1.0000	nonpar	.99	**

N(back) and N(mon) = Non-outlier measurements in the background and monitoring periods.

N(tot) = All independent measurements for that constituent and well.
For transformed data, mean and SD in transformed units and control limit in original units.

- * Insufficient Data.

 ** Detection Frequency < 25%.
- *** Zero Variance.

Table 2 **Analytical Data and CUSUM Summary**

	T								
Constituent	Units	Well	Date	Background	Result	Outlier	CUSUM	Adjusted	
1,1-dichloroethane	ug/L	PM-13X	09/22/2005	yes	44.0000				
1,1-dichloroethane	ug/L	PM-13X	12/20/2005	yes	40.0000				
1,1-dichloroethane	ug/L	PM-13X	03/23/2006	yes	41.0000				
1,1-dichloroethane	ug/L	PM-13X	06/02/2006	yes	21.0000				
1,1-dichloroethane	ug/L	PM-13X	07/28/2006	yes	34.0000				
1,1-dichloroethane	ug/L	PM-13X	11/28/2006	yes	41.0000				
1,1-dichloroethane	ug/L	PM-13X	02/06/2007	yes	43.0000				
1,1-dichloroethane	ug/L	PM-13X	06/08/2007	yes	35.0000				
1,1-dichloroethane	ug/L	PM-13X	11/05/2007	yes	43.0000				
1,1-dichloroethane	ug/L	PM-13X	05/16/2008	yes	46.0000				
1,1-dichloroethane	ug/L	PM-13X	12/08/2008	yes	18.0000				
1,1-dichloroethane	ug/L	PM-13X	05/12/2009	yes	33.0000				
1,1-dichloroethane	ug/L	PM-13X	11/25/2009	yes	33.0000				
1,1-dichloroethane	ug/L	PM-13X	06/11/2010	yes	39.0000				
1,1-dichloroethane	ug/L	PM-13X	11/19/2010	yes	41.0000				
1,1-dichloroethane	ug/L	PM-13X	06/07/2011	yes	39.0000				
1,1-dichloroethane	ug/L	PM-13X	12/09/2011	yes	32.0000				
1,1-dichloroethane	ug/L	PM-13X	06/21/2012	yes	32.0000				
1,1-dichloroethane	ug/L	PM-13X	12/10/2012	yes	33.0000				
1,1-dichloroethane	ug/L	PM-13X	06/18/2013	_	35.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	12/19/2013		37.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/18/2014		32.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	12/22/2014		28.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/02/2015		31.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	12/21/2015		33.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/21/2016		34.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	12/20/2016		30.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/29/2017		27.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	10/17/2017		29.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/20/2018		30.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	10/30/2018		23.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/11/2019		26.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	12/18/2019		27.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/08/2020		29.0000		36.2105		

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result	Outlier	CUSUM	Adjusted	
1,1-dichloroethane	ug/L	PM-13X	12/21/2020		14.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	06/09/2021		24.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	11/03/2021		22.0000		36.2105		
1,1-dichloroethane	ug/L	PM-13X	05/05/2022		18.0000		36.2105		
1,1-dichloroethane	ug/L	PM-14X	06/15/2004	yes	4.6000				
1,1-dichloroethane	ug/L	PM-14X	06/08/2005	yes	3.9000				
1,1-dichloroethane	ug/L	PM-14X	08/26/2005	yes	3.9000				
1,1-dichloroethane	ug/L	PM-14X	11/21/2005	yes	3.9000				
1,1-dichloroethane	ug/L	PM-14X	02/21/2006	yes	3.2000				
1,1-dichloroethane	ug/L	PM-14X	06/12/2006	yes	4.2000				
1,1-dichloroethane	ug/L	PM-14X	07/26/2006	yes	3.7000				
1,1-dichloroethane	ug/L	PM-14X	11/28/2006	yes	4.3000				
1,1-dichloroethane	ug/L	PM-14X	02/05/2007	yes	3.7000				
1,1-dichloroethane	ug/L	PM-14X	08/02/2007	yes	4.1000				
1,1-dichloroethane	ug/L	PM-14X	10/17/2007	yes	4.5000				
1,1-dichloroethane	ug/L	PM-14X	05/05/2008	yes	3.7000				
1,1-dichloroethane	ug/L	PM-14X	10/29/2008	yes	3.1000				
1,1-dichloroethane	ug/L	PM-14X	04/16/2009	yes	3.1000				
1,1-dichloroethane	ug/L	PM-14X	11/11/2009	yes	3.9000				
1,1-dichloroethane	ug/L	PM-14X	04/27/2010	yes	3.5000				
1,1-dichloroethane	ug/L	PM-14X	11/02/2010	yes	3.2000				
1,1-dichloroethane	ug/L	PM-14X	05/04/2011	yes	3.2000				
1,1-dichloroethane	ug/L	PM-14X	11/29/2011	yes	3.8000				
1,1-dichloroethane	ug/L	PM-14X	05/21/2012	yes	3.7000				
1,1-dichloroethane	ug/L	PM-14X	10/25/2012	yes	3.8000				
1,1-dichloroethane	ug/L	PM-14X	04/23/2013	yes	4.1000				
1,1-dichloroethane	ug/L	PM-14X	10/15/2013	yes	3.6000				
1,1-dichloroethane	ug/L	PM-14X	04/24/2014	yes	3.3000				
1,1-dichloroethane	ug/L	PM-14X	10/27/2014	_	4.0000		3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/20/2015		3.0000		3.7500		
1,1-dichloroethane	ug/L	PM-14X	11/02/2015		2.9000		3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/20/2016		3.0000		3.7500		
1,1-dichloroethane	ug/L	PM-14X	11/01/2016		2.6000		3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/20/2017		3.0000		3.7500		

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,1-dichloroethane	ug/L	PM-14X	10/13/2017		2.8000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/18/2018		2.6000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	10/19/2018		2.5000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/26/2019		2.5000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	11/07/2019		4.0000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	05/13/2020		3.0000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	12/15/2020		3.3000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	05/20/2021		3.5000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	10/26/2021		4.0000			3.7500		
1,1-dichloroethane	ug/L	PM-14X	04/21/2022		3.0000			3.7500		
1,1-dichloroethane	ug/L	PM-3X	06/13/2006	yes	0.3300					
1,1-dichloroethane	ug/L	PM-3X	08/01/2006	yes	0.2600					
1,1-dichloroethane	ug/L	PM-3X	12/12/2006	yes	0.2800					
1,1-dichloroethane	ug/L	PM-3X	02/08/2007	yes	0.2900					
1,1-dichloroethane	ug/L	PM-3X	06/08/2007	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-3X	08/10/2007	yes	0.3400					
1,1-dichloroethane	ug/L	PM-3X	10/23/2007	yes	0.3000					
1,1-dichloroethane	ug/L	PM-3X	02/22/2008	yes	0.2600					
1,1-dichloroethane	ug/L	PM-3X	05/09/2008	yes	0.2800					
1,1-dichloroethane	ug/L	PM-3X	12/11/2008	yes	0.3500					
1,1-dichloroethane	ug/L	PM-3X	05/12/2009	yes	0.3100					
1,1-dichloroethane	ug/L	PM-3X	11/25/2009	yes	0.3400					
1,1-dichloroethane	ug/L	PM-3X	05/27/2010	,	0.3800			0.3617		
1,1-dichloroethane	ug/L	PM-3X	11/19/2010		0.4800			0.3617		
1,1-dichloroethane	ug/L	PM-3X	06/02/2011		0.5100			0.3617		
1,1-dichloroethane	ug/L	PM-3X	12/08/2011		0.4000			0.3617		
1,1-dichloroethane	ug/L	PM-3X	06/12/2012		0.4200			0.3617		
1,1-dichloroethane	ug/L	PM-3X	12/05/2012		0.4700			0.3617		
1,1-dichloroethane	ug/L	PM-3X	05/28/2013		0.4900			0.3617		
1,1-dichloroethane	ug/L	PM-3X	12/19/2013		0.4700			0.3617		
1,1-dichloroethane	ug/L	PM-3X	06/18/2014		0.4100			0.3617		
1,1-dichloroethane	ug/L	PM-3X	12/29/2014		0.3200			0.3617		
1,1-dichloroethane	ug/L	PM-3X	06/03/2015		0.5000			0.3617		
1,1-dichloroethane	ug/L	PM-3X	12/21/2015		0.4500			0.3617		

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1.1-dichloroethane	ug/L	PM-3X	06/27/2016	3	0.5000			0.3617	.,	
1.1-dichloroethane	ug/L	PM-3X	12/29/2016		0.2200	ND		0.3617		
1.1-dichloroethane	ug/L	PM-3X	06/29/2017		0.3300			0.3617		
1.1-dichloroethane	ug/L	PM-3X	10/17/2017		0.4000			0.3617		
1.1-dichloroethane	ug/L	PM-3X	06/22/2018		0.5700			0.4174		
1.1-dichloroethane	ug/L	PM-3X	11/01/2018		0.4400			0.3617		
1,1-dichloroethane	ug/L	PM-3X	06/11/2019		0.3700			0.3617		
1.1-dichloroethane	ug/L	PM-3X	12/18/2019		0.2200	ND		0.3617		
1.1-dichloroethane	ug/L	PM-3X	06/08/2020		0.6000			0.4474		
1.1-dichloroethane	ug/L	PM-3X	12/18/2020		0.5900			0.5232		
1,1-dichloroethane	ug/L	PM-3X	06/08/2021		0.7300			0.7390		
1,1-dichloroethane	ug/L	PM-3X	11/03/2021		0.3700			0.5947		
1,1-dichloroethane	ug/L	PM-3X	05/05/2022		0.5400			0.6205		
1,1-dichloroethane	ug/L	PM-6X	06/15/2004	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	09/22/2005	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/20/2005	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	03/23/2006	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/02/2006	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	07/28/2006	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	11/28/2006	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	02/06/2007	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	08/10/2007	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	10/23/2007	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	05/09/2008	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/08/2008	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	05/05/2009	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	11/25/2009	yes	0.1600	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	05/27/2010	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	11/19/2010	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/02/2011	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/07/2011	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/21/2012	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/05/2012	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	05/28/2013	yes	0.2200	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,1-dichloroethane	ug/L	PM-6X	12/16/2013	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/17/2014	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/22/2014	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/02/2015	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/23/2015	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/21/2016	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/20/2016	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/29/2017	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	10/17/2017	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/21/2018	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	10/16/2018	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/12/2019	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/18/2019	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/08/2020	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	12/18/2020	yes	0.2200	ND			1.0000	****
1,1-dichloroethane	ug/L	PM-6X	06/08/2021	-	0.2200	ND				
1,1-dichloroethane	ug/L	PM-6X	11/03/2021		0.2200	ND				
1,1-dichloroethane	ug/L	PM-6X	05/05/2022		0.2200	ND				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.




Table 1

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Туре	Conf	
1,4-dioxane	ug/L	PM-13X	8	2	10								nonpar *		**
1,4-dioxane	ug/L	PM-3X	8	2	10								nonpar *		**
1,4-dioxane	ug/L	PM-6X	8	2	10								nonpar *		**

N(back) and N(mon) = Non-outlier measurements in the background and monitoring periods.

N(tot) = All independent measurements for that constituent and well.
For transformed data, mean and SD in transformed units and control limit in original units.

^{* -} Insufficient Data.

^{** -} Detection Frequency < 25%.
*** - Zero Variance.

Table 1

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Type	Conf	
1,4-dioxane	ug/L	PM-14X	32	5	37			0.0900	0.0900			0.9000	nonpar	.99	**

 $N(back) \ and \ N(mon) = Non-outlier \ measurements \ in \ the \ background \ and \ monitoring \ periods.$ $N(tot) = All \ independent \ measurements \ for \ that \ constituent \ and \ well.$

For transformed data, mean and SD in transformed units and control limit in original units.

- * Insufficient Data.
- ** Detection Frequency < 25%.
- *** Zero Variance.

Table 2 **Analytical Data and CUSUM Summary**

		T								
Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,4-dioxane	ug/L	PM-14X	06/08/2005	yes	0.1900	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	08/26/2005	yes	0.1900	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/21/2005	yes	0.1900	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	02/21/2006	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	07/26/2006	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	02/05/2007	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	08/02/2007	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/17/2007	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	05/05/2008	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/29/2008	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/16/2009	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/11/2009	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/27/2010	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/02/2010	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	05/04/2011	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/29/2011	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	05/21/2012	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/25/2012	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/23/2013	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/15/2013	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/23/2014	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/27/2014	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/20/2015	yes	0.5000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/02/2015	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/20/2016	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/01/2016	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/20/2017	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/13/2017	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/18/2018	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	10/19/2018	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	04/26/2019	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	11/07/2019	yes	0.4000	ND			0.9000	****
1,4-dioxane	ug/L	PM-14X	05/13/2020		0.0900	ND				
1,4-dioxane	ug/L	PM-14X	12/15/2020		0.1000					

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2

Analytical Data and CUSUM Summary

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,4-dioxane	ug/L	PM-14X	05/20/2021		0.0900	ND				
1,4-dioxane	ug/L	PM-14X	10/26/2021		0.0900	ND				
1,4-dioxane	ug/L	PM-14X	04/21/2022		0.0900	ND				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

							a			
Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
1,4-dioxane	ug/L	PM-13X	10/17/2017	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	06/20/2018	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	10/30/2018	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	06/11/2019	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	12/18/2019	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	06/08/2020	yes	0.3500					****
1,4-dioxane	ug/L	PM-13X	12/21/2020	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-13X	06/09/2021	yes	0.0900	ND			0.9000	^^^^
1,4-dioxane	ug/L	PM-13X	11/03/2021		0.0900	ND				
1,4-dioxane	ug/L	PM-13X	05/05/2022		0.0900	ND				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
ì										
1										
1										
1										
1,4-dioxane	ug/L	PM-3X	10/17/2017	yes	0.1500	ND			0.9000	****
1.4-dioxane	ug/L	PM-3X	06/22/2018	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	11/01/2018	ves	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	06/11/2019	yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	12/18/2019	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	06/08/2020	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	12/18/2020	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	06/08/2021	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-3X	11/03/2021		0.0900	ND				
1,4-dioxane	ug/L	PM-3X	05/05/2022		0.0900	ND			0.0000	****
1,4-dioxane	ug/L	PM-6X PM-6X	10/17/2017 06/21/2018	yes	0.1500	ND ND			0.9000 0.9000	****
1,4-dioxane 1,4-dioxane	ug/L	PM-6X	10/16/2018	yes	0.1500 0.1500	ND			0.9000	****
1,4-dioxane	ug/L ug/L	PM-6X	06/12/2019	yes yes	0.1500	ND			0.9000	****
1,4-dioxane	ug/L ug/L	PM-6X	12/18/2019	yes	0.0900	ND			0.9000	****
1.4-dioxane	ug/L	PM-6X	06/08/2020	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-6X	12/18/2020	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-6X	06/08/2021	yes	0.0900	ND			0.9000	****
1,4-dioxane	ug/L	PM-6X	11/03/2021	,	0.0900	ND				
1,4-dioxane	ug/L	PM-6X	05/05/2022		0.0900	ND				


^{* -} Outlier for that well and constituent.


** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.


*** - ND value replaced with median RL.


**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.









Graph 1

Table 1

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Type	Conf	
Tetrachloroethene	ug/L	PM-13X	32	6	38	1.0941	0.4070	0.3000	0.6900	1.0941	1.0941	2.9255	normal		
Tetrachloroethene	ug/L	PM-14X	36	4	40			0.2000	0.2000			1.0000	nonpar	.99	**
Tetrachloroethene	ug/L	PM-3X	36	1	37	0.6694	0.2947	1.0000	0.3200		0.6694	1.9954	normal		
Tetrachloroethene	ug/L	PM-6X	36	3	39			0.2000	0.2000			1.0000	nonpar	.99	**

N(back) and N(mon) = Non-outlier measurements in the background and monitoring periods.

N(tot) = All independent measurements for that constituent and well.
For transformed data, mean and SD in transformed units and control limit in original units.

- * Insufficient Data.

 ** Detection Frequency < 25%.

 *** Zero Variance.

Table 2 **Analytical Data and CUSUM Summary**

	1	1	T	I			I		
Constituent	Units	Well	Date	Background	Result	Outlier	CUSUM	Adjusted	
Tetrachloroethene	ug/L	PM-13X	09/22/2005	yes	0.8200				
Tetrachloroethene	ug/L	PM-13X	12/20/2005	yes	0.9400				
Tetrachloroethene	ug/L	PM-13X	03/23/2006	yes	0.9000				
Tetrachloroethene	ug/L	PM-13X	06/02/2006	yes	0.5400				
Tetrachloroethene	ug/L	PM-13X	07/28/2006	yes	0.7900				
Tetrachloroethene	ug/L	PM-13X	11/28/2006	yes	1.1000				
Tetrachloroethene	ug/L	PM-13X	02/06/2007	yes	1.7000				
Tetrachloroethene	ug/L	PM-13X	06/08/2007	yes	1.3000				
Tetrachloroethene	ug/L	PM-13X	11/05/2007	yes	2.0000				
Tetrachloroethene	ug/L	PM-13X	05/16/2008	yes	1.2000				
Tetrachloroethene	ug/L	PM-13X	12/08/2008	yes	0.4800				
Tetrachloroethene	ug/L	PM-13X	05/12/2009	yes	1.0000				
Tetrachloroethene	ug/L	PM-13X	11/25/2009	yes	0.8300				
Tetrachloroethene	ug/L	PM-13X	06/11/2010	yes	1.2000				
Tetrachloroethene	ug/L	PM-13X	11/19/2010	yes	1.6000				
Tetrachloroethene	ug/L	PM-13X	06/07/2011	yes	0.9300				
Tetrachloroethene	ug/L	PM-13X	12/09/2011	yes	0.8700				
Tetrachloroethene	ug/L	PM-13X	06/21/2012	yes	0.7000				
Tetrachloroethene	ug/L	PM-13X	12/10/2012	yes	0.4800				
Tetrachloroethene	ug/L	PM-13X	06/18/2013	yes	1.0000				
Tetrachloroethene	ug/L	PM-13X	12/19/2013	yes	0.8200				
Tetrachloroethene	ug/L	PM-13X	06/18/2014	yes	1.2000				
Tetrachloroethene	ug/L	PM-13X	12/22/2014	yes	0.6200				
Tetrachloroethene	ug/L	PM-13X	06/02/2015	yes	1.6000				
Tetrachloroethene	ug/L	PM-13X	12/21/2015	yes	1.7000				
Tetrachloroethene	ug/L	PM-13X	06/21/2016	yes	1.0000				
Tetrachloroethene	ug/L	PM-13X	12/20/2016	yes	1.3000				
Tetrachloroethene	ug/L	PM-13X	06/29/2017	yes	1.6000				
Tetrachloroethene	ug/L	PM-13X	10/17/2017	yes	0.5900				
Tetrachloroethene	ug/L	PM-13X	06/20/2018	yes	1.0000				
Tetrachloroethene	ug/L	PM-13X	10/30/2018	yes	1.6000				
Tetrachloroethene	ug/L	PM-13X	06/11/2019	yes	1.6000				
Tetrachloroethene	ug/L	PM-13X	12/18/2019		1.3000		1.0941		
Tetrachloroethene	ug/L	PM-13X	06/08/2020		1.2000		1.0941		
		•	-	•		-			

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Canadituant	I I mida	VA/II	Doto	Deelemannel	Daguila		041	CHICHIM	Adlinatad	
Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Tetrachloroethene	ug/L	PM-13X	12/21/2020		0.8700			1.0941		
Tetrachloroethene	ug/L	PM-13X	06/09/2021		0.2700			1.0941		
Tetrachloroethene	ug/L	PM-13X	11/03/2021		0.3000			1.0941		
Tetrachloroethene	ug/L	PM-13X	05/05/2022		0.6900			1.0941		
Tetrachloroethene	ug/L	PM-14X	06/15/2004	yes	0.2600	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	06/08/2005	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	08/26/2005	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/21/2005	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	02/21/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	06/12/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	07/26/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/28/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	02/05/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	08/02/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/17/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	05/05/2008	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/29/2008	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/16/2009	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/11/2009	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/27/2010	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/02/2010	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	05/04/2011	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/29/2011	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	05/21/2012	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/25/2012	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/23/2013	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/15/2013	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/24/2014	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/27/2014	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/20/2015	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/02/2015	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/20/2016	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/01/2016	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/20/2017	ves	0.2000	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

	T	1	T	I			I			
Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Tetrachloroethene	ug/L	PM-14X	10/13/2017	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/18/2018	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	10/19/2018	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	04/26/2019	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	11/07/2019	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	05/13/2020	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-14X	12/15/2020	-	0.2000	ND				
Tetrachloroethene	ug/L	PM-14X	05/20/2021		0.2000	ND				
Tetrachloroethene	ug/L	PM-14X	10/26/2021		0.2000	ND				
Tetrachloroethene	ug/L	PM-14X	04/21/2022		0.2000	ND				
Tetrachloroethene	ug/L	PM-3X	06/13/2006	yes	1.0000					
Tetrachloroethene	ug/L	PM-3X	08/01/2006	yes	1.3000					
Tetrachloroethene	ug/L	PM-3X	12/12/2006	yes	1.2000					
Tetrachloroethene	ug/L	PM-3X	02/08/2007	yes	1.0000					
Tetrachloroethene	ug/L	PM-3X	06/08/2007	yes	0.4600					
Tetrachloroethene	ug/L	PM-3X	08/10/2007	yes	0.5400					
Tetrachloroethene	ug/L	PM-3X	10/23/2007	yes	0.4800					
Tetrachloroethene	ug/L	PM-3X	02/22/2008	yes	0.8600					
Tetrachloroethene	ug/L	PM-3X	05/09/2008	yes	0.9900					
Tetrachloroethene	ug/L	PM-3X	12/11/2008	yes	0.6000					
Tetrachloroethene	ug/L	PM-3X	05/12/2009	yes	0.2100					
Tetrachloroethene	ug/L	PM-3X	11/25/2009	yes	0.4600					
Tetrachloroethene	ug/L	PM-3X	05/27/2010	yes	1.0000					
Tetrachloroethene	ug/L	PM-3X	11/19/2010	yes	0.6500					
Tetrachloroethene	ug/L	PM-3X	06/02/2011	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-3X	12/08/2011	yes	0.5700					
Tetrachloroethene	ug/L	PM-3X	06/12/2012	yes	0.8200					
Tetrachloroethene	ug/L	PM-3X	12/05/2012	yes	0.3900					
Tetrachloroethene	ug/L	PM-3X	05/28/2013	yes	0.6500					
Tetrachloroethene	ug/L	PM-3X	12/19/2013	yes	0.4200					
Tetrachloroethene	ug/L	PM-3X	06/18/2014	yes	0.3800					
Tetrachloroethene	ug/L	PM-3X	12/29/2014	yes	0.3900					
Tetrachloroethene	ug/L	PM-3X	06/03/2015	yes	0.3200					
Tetrachloroethene	ug/L	PM-3X	12/21/2015	yes	0.5500					

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Tetrachloroethene	ug/L	PM-3X	06/27/2016	ves	0.6300					
Tetrachloroethene	ug/L	PM-3X	12/29/2016	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-3X	06/29/2017	yes	0.4200					
Tetrachloroethene	ug/L	PM-3X	10/17/2017	yes	0.2700					
Tetrachloroethene	ug/L	PM-3X	06/22/2018	yes	0.7700					
Tetrachloroethene	ug/L	PM-3X	11/01/2018	yes	0.7700					
Tetrachloroethene	ug/L	PM-3X	06/11/2019	yes	0.3300					
Tetrachloroethene	ug/L	PM-3X	12/18/2019	yes	0.2400					
Tetrachloroethene	ug/L	PM-3X	06/08/2020	yes	0.7300					
Tetrachloroethene	ug/L	PM-3X	12/18/2020	yes	1.1000					
Tetrachloroethene	ug/L	PM-3X	06/08/2021	yes	0.6000					
Tetrachloroethene	ug/L	PM-3X	11/03/2021	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-3X	05/05/2022		0.3200			0.6694		
Tetrachloroethene	ug/L	PM-6X	06/15/2004	yes	0.2600	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	09/22/2005	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/20/2005	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	03/23/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/02/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	07/28/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	11/28/2006	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	02/06/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	08/10/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	10/23/2007	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	05/09/2008	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/08/2008	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	05/05/2009	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	11/25/2009	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	05/27/2010	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	11/19/2010	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/02/2011	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/07/2011	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/21/2012	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/05/2012	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	05/28/2013	yes	0.2000	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Tetrachloroethene	ug/L	PM-6X	12/16/2013	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/17/2014	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/22/2014	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/02/2015	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/23/2015	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/21/2016	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/20/2016	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/29/2017	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	10/17/2017	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/21/2018	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	10/16/2018	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/12/2019	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/18/2019	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/08/2020	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	12/18/2020	yes	0.2000	ND			1.0000	****
Tetrachloroethene	ug/L	PM-6X	06/08/2021	_	0.2000	ND				
Tetrachloroethene	ug/L	PM-6X	11/03/2021		0.2000	ND				
Tetrachloroethene	ug/L	PM-6X	05/05/2022		0.2000	ND				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.




Table 1

Summary Statistics and Intermediate Computations for Combined Shewhart-Cusum Control Charts

Constituent	Units	Well	N(back)	N(mon)	N(tot)	Mean	SD	R(i-1)	R(i)	S(i-1)	S(i)	Limit	Туре	Conf	
Trichloroethene	ug/L	PM-13X	36	2	38	1.4019	0.3279	0.6600	0.9200	1.4019	1.4019	2.8775	normal		
Trichloroethene	ug/L	PM-14X	36	4	40	0.7989	0.3534	0.1600	0.1600	0.7989	0.7989	2.3894	normal		
Trichloroethene	ug/L	PM-3X	36	1	37	0.4044	0.2673	1.0000	0.1900		0.4044	1.6074	normal		
Trichloroethene	ug/L	PM-6X	36	3	39			0.1600	0.1600			1.0000	nonpar	.99	**

N(back) and N(mon) = Non-outlier measurements in the background and monitoring periods.

N(tot) = All independent measurements for that constituent and well.
For transformed data, mean and SD in transformed units and control limit in original units.

Conf = confidence level for passing initial test or one verification resample (nonparametric test only).

- * Insufficient Data.

 ** Detection Frequency < 25%.

 *** Zero Variance.

Table 2 **Analytical Data and CUSUM Summary**

On matitude of t	I I mild :	\A/e.II	Doto	De elsements d	Desuit	041	CHCHI	A alivoto -1	
Constituent	Units	Well	Date	Background	Result	Outlier	CUSUM	Adjusted	
Trichloroethene	ug/L	PM-13X	09/22/2005	yes	1.3000				
Trichloroethene	ug/L	PM-13X	12/20/2005	yes	1.4000				
Trichloroethene	ug/L	PM-13X	03/23/2006	yes	1.3000				
Trichloroethene	ug/L	PM-13X	06/02/2006	yes	0.7700				
Trichloroethene	ug/L	PM-13X	07/28/2006	yes	1.2000				
Trichloroethene	ug/L	PM-13X	11/28/2006	yes	1.4000				
Trichloroethene	ug/L	PM-13X	02/06/2007	yes	1.9000				
Trichloroethene	ug/L	PM-13X	06/08/2007	yes	1.6000				
Trichloroethene	ug/L	PM-13X	11/05/2007	yes	2.3000				
Trichloroethene	ug/L	PM-13X	05/16/2008	yes	1.7000				
Trichloroethene	ug/L	PM-13X	12/08/2008	yes	1.1000				
Trichloroethene	ug/L	PM-13X	05/12/2009	yes	1.4000				
Trichloroethene	ug/L	PM-13X	11/25/2009	yes	1.5000				
Trichloroethene	ug/L	PM-13X	06/11/2010	yes	1.7000				
Trichloroethene	ug/L	PM-13X	11/19/2010	yes	1.7000				
Trichloroethene	ug/L	PM-13X	06/07/2011	yes	1.7000				
Trichloroethene	ug/L	PM-13X	12/09/2011	yes	1.4000				
Trichloroethene	ug/L	PM-13X	06/21/2012	yes	1.0000				
Trichloroethene	ug/L	PM-13X	12/10/2012	yes	0.9900				
Trichloroethene	ug/L	PM-13X	06/18/2013	yes	1.4000				
Trichloroethene	ug/L	PM-13X	12/19/2013	yes	1.4000				
Trichloroethene	ug/L	PM-13X	06/18/2014	yes	1.5000				
Trichloroethene	ug/L	PM-13X	12/22/2014	yes	1.0000				
Trichloroethene	ug/L	PM-13X	06/02/2015	yes	1.7000				
Trichloroethene	ug/L	PM-13X	12/21/2015	yes	1.9000				
Trichloroethene	ug/L	PM-13X	06/21/2016	yes	1.4000				
Trichloroethene	ug/L	PM-13X	12/20/2016	yes	1.6000				
Trichloroethene	ug/L	PM-13X	06/29/2017	yes	1.7000				
Trichloroethene	ug/L	PM-13X	10/17/2017	yes	1.0000				
Trichloroethene	ug/L	PM-13X	06/20/2018	yes	1.4000				
Trichloroethene	ug/L	PM-13X	10/30/2018	yes	1.5000				
Trichloroethene	ug/L	PM-13X	06/11/2019	yes	1.0000				
Trichloroethene	ug/L	PM-13X	12/18/2019	yes	1.2000				
Trichloroethene	ug/L	PM-13X	06/08/2020	yes	1.5000				

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Trichloroethene	ug/L	PM-13X	12/21/2020	yes	0.9200					
Trichloroethene	ug/L	PM-13X	06/09/2021	yes	0.9900					
Trichloroethene	ug/L	PM-13X	11/03/2021		0.6600			1.4019		
Trichloroethene	ug/L	PM-13X	05/05/2022		0.9200			1.4019		
Trichloroethene	ug/L	PM-14X	06/15/2004	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	06/08/2005	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	08/26/2005	yes	0.1700					
Trichloroethene	ug/L	PM-14X	11/21/2005	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	02/21/2006	yes	0.2100					
Trichloroethene	ug/L	PM-14X	06/12/2006	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	07/26/2006	yes	0.1700					
Trichloroethene	ug/L	PM-14X	11/28/2006	yes	0.2000					
Trichloroethene	ug/L	PM-14X	02/05/2007	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	08/02/2007	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	10/17/2007	yes	0.2200					
Trichloroethene	ug/L	PM-14X	05/05/2008	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	10/29/2008	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/16/2009	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	11/11/2009	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/27/2010	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	11/02/2010	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	05/04/2011	yes	0.1900					
Trichloroethene	ug/L	PM-14X	11/29/2011	yes	0.2000					
Trichloroethene	ug/L	PM-14X	05/21/2012	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	10/25/2012	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/23/2013	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	10/15/2013	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/24/2014	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	10/27/2014	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/20/2015	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	11/02/2015	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/20/2016	yes	0.1700					
Trichloroethene	ug/L	PM-14X	11/01/2016	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	04/20/2017	yes	0.1600	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Trichloroethene	ug/L	PM-14X	10/13/2017	ves	0.1600	ND			1.0000	****
Trichloroethene	ug/L ug/L	PM-14X	04/18/2018	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L ug/L	PM-14X	10/19/2018	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L ug/L	PM-14X	04/26/2019	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	11/07/2019	yes	0.1000	IND			1.0000	
Trichloroethene	ug/L ug/L	PM-14X	05/13/2020	yes	0.2300	ND			1.0000	****
Trichloroethene	ug/L	PM-14X	12/15/2020	ycs	0.1600	ND		0.7989	1.0000	
Trichloroethene	ug/L	PM-14X	05/20/2021		0.1600	ND		0.7989		
Trichloroethene	ug/L	PM-14X	10/26/2021		0.1600	ND		0.7989		
Trichloroethene	ug/L ug/L	PM-14X	04/21/2022		0.1600	ND		0.7989		
Trichloroethene	ug/L ug/L	PM-3X	06/13/2006	yes	0.1000	IND		0.7909		
Trichloroethene	ug/L	PM-3X	08/01/2006	yes	0.3900					
Trichloroethene	ug/L	PM-3X	12/12/2006	yes	0.4200					
Trichloroethene	ug/L	PM-3X	02/08/2007	yes	0.3300					
Trichloroethene	ug/L	PM-3X	06/08/2007	yes	0.2400					
Trichloroethene	ug/L	PM-3X	08/10/2007	yes	0.2800					
Trichloroethene	ug/L	PM-3X	10/23/2007	yes	0.3300					
Trichloroethene	ug/L	PM-3X	02/22/2008	yes	0.3200					
Trichloroethene	ug/L	PM-3X	05/09/2008	yes	0.3400					
Trichloroethene	ug/L	PM-3X	12/11/2008	yes	0.3200					
Trichloroethene	ug/L	PM-3X	05/12/2009	yes	0.1600					
Trichloroethene	ug/L	PM-3X	11/25/2009	yes	0.2200					
Trichloroethene	ug/L	PM-3X	05/27/2010	yes	0.4800					
Trichloroethene	ug/L	PM-3X	11/19/2010	yes	0.2400					
Trichloroethene	ug/L	PM-3X	06/02/2011	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-3X	12/08/2011	yes	0.2200					
Trichloroethene	ug/L	PM-3X	06/12/2012	yes	0.3300					
Trichloroethene	ug/L	PM-3X	12/05/2012	yes	0.2600					
Trichloroethene	ug/L	PM-3X	05/28/2013	yes	0.6300					
Trichloroethene	ug/L	PM-3X	12/19/2013	yes	0.2000					
Trichloroethene	ug/L	PM-3X	06/18/2014	yes	0.1600					
Trichloroethene	ug/L	PM-3X	12/29/2014	yes	0.1700					
Trichloroethene	ug/L	PM-3X	06/03/2015	yes	0.2800					
Trichloroethene	ug/L	PM-3X	12/21/2015	yes	0.2600					

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Trichloroethene	ug/L	PM-3X	06/27/2016	yes	0.2700					
Trichloroethene	ug/L	PM-3X	12/29/2016	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-3X	06/29/2017	yes	0.2400					
Trichloroethene	ug/L	PM-3X	10/17/2017	yes	0.1700					
Trichloroethene	ug/L	PM-3X	06/22/2018	yes	0.3700					
Trichloroethene	ug/L	PM-3X	11/01/2018	yes	0.3000					
Trichloroethene	ug/L	PM-3X	06/11/2019	yes	0.1700					
Trichloroethene	ug/L	PM-3X	12/18/2019	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-3X	06/08/2020	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-3X	12/18/2020	yes	0.3800					
Trichloroethene	ug/L	PM-3X	06/08/2021	yes	0.6400					
Trichloroethene	ug/L	PM-3X	11/03/2021	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-3X	05/05/2022		0.1900			0.4044		
Trichloroethene	ug/L	PM-6X	06/15/2004	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	09/22/2005	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/20/2005	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	03/23/2006	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/02/2006	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	07/28/2006	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	11/28/2006	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	02/06/2007	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	08/10/2007	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	10/23/2007	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	05/09/2008	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/08/2008	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	05/05/2009	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	11/25/2009	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	05/27/2010	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	11/19/2010	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/02/2011	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/07/2011	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/21/2012	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/05/2012	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	05/28/2013	yes	0.1600	ND			1.0000	****

^{* -} Outlier for that well and constituent.

** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Table 2 **Analytical Data and CUSUM Summary**

Constituent	Units	Well	Date	Background	Result		Outlier	CUSUM	Adjusted	
Trichloroethene	ug/L	PM-6X	12/16/2013	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/17/2014	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/22/2014	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/02/2015	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/23/2015	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/21/2016	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/20/2016	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/29/2017	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	10/17/2017	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/21/2018	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	10/16/2018	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/12/2019	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/18/2019	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/08/2020	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	12/18/2020	yes	0.1600	ND			1.0000	****
Trichloroethene	ug/L	PM-6X	06/08/2021	-	0.1600	ND				
Trichloroethene	ug/L	PM-6X	11/03/2021		0.1600	ND				
Trichloroethene	ug/L	PM-6X	05/05/2022		0.1600	ND				

^{* -} Outlier for that well and constituent.


** - Non-outlier detected sample Result and / or CUSUM value exceeds limit.

*** - ND value replaced with median RL.

**** - ND value replaced with manual RL.

ND = Not detected, Result = detection limit.

Intra-Well Control Charts / Prediction Limits



APPENDIX C-5 VERTICAL MIGRATION ASSESSMENT

APPENDIX C-5.1 VERTICAL MIGRATION ASSESSMENT

Vertical Migration Well Data

TABLE C-5.1 VERTICAL MIGRATION WELL DATA

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

О	Date	1,1,1-Trichloroethane	1,1,2,2-Tetrachloroetha	1,1,2-Trichloroethane	1,1-Dichloroethane	1,1-Dichloroethene	1,2-Dichloroethane	1,2-Dichloropropane	ane				Bromodichloromethan	ırm	æ	Carbon Tetrachloride	Chlorobenzene	ırm	cis-1,2-Dichloroethene	Dibromochloromethan	Ethylbenzene	Methylene Chloride	lene	Nitrogen, Nitrate	Nitrogen, Nitrite	Tetrachloroethene		Trans-1,2-Dichloroethe	Trichloroethene	Vinyl Chloride
Group-ID	Sample Date	1-Tri	2,2-T	2-Tri	Dich	Dich	Dich	Dich	1,4-Dioxane	Acetone	Arsenic	Benzene	pom	Bromoform	Cadmium	pon-	orob	Chloroform	1,2-D	rome	ylber	thyle	Naphthalene	oger.	nego.	rachl	Toluene	ms-1,	chlor	yl Cl
Gro	San	1,1,	1,1,	1,1,	1,1-	1,1	1,2-	1,2-	1,4-	Ace	Ars	Ben	Bro	Bro	Cad	Car	Chl	Chl	cis-	Dib	Eth	Met	Nap	Nit.	Nit	Tetı	Tol	Tra	Tri	Vin
B-504A	9/9/2002										10 U				5 U															
B-504A	5/11/2005										10 U				5 U									500 U	500 U					1
B-504A	9/13/2005	1 U	1 U	1 U	5.6	0.26 J	1 U	1 U	0.5 U	6.9 J		1 U	1 U	1 U		1 U	1 U	1 U	0.24 J	1 U	1 U	1 U	1 U	500 U	500 U	1 U	0.31 J	0.5 U	1 U	2 U
B-504A	12/12/2005	1 U	1 U	1 U	4.5	0.2 J	1 U	1 U	0.5 U	2.4 J		1 U	1 U	1 U		1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	90 J	500 U			0.5 U		2 U
B-504A	3/6/2006	1 U	1 U	1 U	4.8	0.19 J	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	0.4 J	1 U			1 U	0.21 J	0.5 U	1 U	2 U
B-504A	6/16/2006	1 U	1 U	1 U	3.1	0.15 J	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.33 J	500 U	500 U	1 U	0.18 J	0.5 U	1 U	2 U
B-504A	7/26/2006	1 U	1 U	1 U	4.9	0.24 J	1 U	1 U	5 U	2.4 J	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	0.17 J	1 U	1 U	1 U	1 U	500 U	500 U	1 U	0.22 J	0.5 U	1 U	2 U
B-504A	12/1/2006	1 U	1 U	1 U	11	0.47 J	1 U	1 U	5 U	3.6 J	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	0.37 J	1 U	1 U	1 U	1 U	500 U	500 U	1 U	0.53 J	0.5 U	1 U	0.39 J
B-504A	3/14/2007	1 U	1 U	1 U	3.9	0.17 J	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	0.17 J	1 U	1 U	0.42 J	1 U	500 U	500 U	1 U	0.19 J	0.5 U	1 U	2 U
B-504A	8/19/2010	1 U	1 U	1 U	5.6	0.29 J	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	0.32 J	0.5 U	1 U	2 U
B-504A	7/30/2015	1 U	1 U	1 U	11	1 U	1 U	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	0.19 J	1 U	1 U	1 U	1 U	500 U	500 U	1 U	0.77 J	0.5 U	1 U	0.28 J
B-504A	8/15/2018	1 U	1 U	1 U	1.5	1 U	1 U	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	7/24/2006	1 U	1 U	1 U	1 U	1 U	0.56 J	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	3/1/2007	1 U	1 U	1 U	1 U	1 U	0.47 J	1 U	0.95 J	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 UJ	1 U	110 J	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	5/29/2007	1 U	1 U	1 U	1 U	1 U	0.2 J	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	8/17/2009	1 U	1 U	1 U	1 U	1 U	0.63 J	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	7/21/2011	1 U	1 U	1 U	1 U	1 U	0.53 J	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	8/8/2013	1 U	1 U	1 U	1 U	1 U	0.71 J	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	7/27/2015	1 U	1 U	1 U	1 U	1 U	0.62 J	1 U	0.9 U	10 U	7.6 J	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	42 J	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	7/28/2017	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	8/21/2018	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	54 J	500 U	1 U	1 U	0.5 U	1 U	2 U
B-712-LD	9/2/2020	1 U	1 U	1 U	1 U	1 U	0.48 J	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.56 J	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
C-702P3	9/12/2002	1 U	1 U	1 U	1 U	1 U	1 U	1 U			10 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U				1 U	1 U	0.5 U	1 U	2 U
C-702P3	5/12/2005	1 U	1 U	1 U	1 U	1 U	1 U	1 U		10 U	10 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
C-702P3	9/14/2005								0.5 U															40 J	500 U					
C-702P3	12/5/2005								0.5 U															500 U	500 U					
C-702P3	3/8/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	0.38 J	1 U			1 U	1 U	0.5 U	1 U	2 U
C-702P3	5/24/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U		10 U		1 U	1 U	1 U		1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U			1 U	1 U	0.5 U	1 U	2 U
C-702P3	6/15/2006								5 U		15 U				5 U									500 U	500 U					
C-702P3	7/26/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U

TABLE C-5.1

VERTICAL MIGRATION WELL DATA

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

roup-ID	Sample Date	1,1,1-Trichloroethane	1,1,2,2-Tetrachloroetha	1,1,2-Trichloroethane	1,1-Dichloroethane	1,1-Dichloroethene	,2-Dichloroethane	,2-Dichloropropane	1,4-Dioxane	Acetone	Arsenic	Benzene	Bromodichloromethan	Bromoform	Cadmium	Carbon Tetrachloride	Chlorobenzene	Chloroform	-1,2-Dichloroethene	Dibromochloromethan	Ethylbenzene	Methylene Chloride	Naphthalene	Nitrogen, Nitrate	Nitrogen, Nitrite	Tetrachloroethene	Toluene	ans-1,2-Dichloroethe	Trichloroethene	Vinyl Chloride
C-702P3	2 11/27/2006		•			1 U	1 U	1 U	1 .	₹ 10 U	_ `				<u> </u>	ပိ 1 U	_	<u>ວ</u> 1 U	1 U		五 1 U	2 1 U	ż 1 U	500 U	500 U	1 U		. ⊑ 0.5 U		2 U
C-702F3	2/28/2007	_		_	_	1 U	1 U	1 U	5 U	10 U		_	1 U		5 U	1 U	1 U	1 U	1 U	-	1 U	1 UJ	1 U	500 U	500 U	1 U		0.5 U		2 U
			1 U	-				1 U	5 U	10 U		_	_									1 U		-					-	
C-702P3	8/19/2010		_		_	1 U	1 U					_			5 U	1 U	1 U	1 U		-	1 U		1 U	500 U	500 U	1 U	1 U	0.5 U	-	2 U
C-702P3	7/14/2015			1 U		1 U	1 U	1 U	5 U	10 U			1 U		5 U	1 U		1 U		_	1 U	1 U	1 U	87 J	500 U	1 U		0.5 U	_	2 U
C-702P3	8/15/2018	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.9 U	10 U		1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	59 J	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	9/12/2002										10 U				5 U															
GW-113	5/24/2005										10 U				5 U									500 UJ	500 UJ					
GW-113	9/13/2005	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.5 U	10 U	10 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	47 J	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	12/13/2005	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.5 U	10 U		1 U	1 U	1 U		1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	140 J	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	3/14/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U		1 U	1 U	1 U		1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U			1 U	1 U	0.5 U	1 U	2 U
GW-113	6/19/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	270 J	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	7/26/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	42 J	500 U	1 U		0.5 U		2 U
GW-113	11/27/2006	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	43 J	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	3/1/2007	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U	2.1 J	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 UJ	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	8/23/2010	1 U	1 U	1 U	1 U	1 U	1 U	1 U	5 U				1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	50 J	1 U	1 U	0.5 U	1 U	2 U
GW-113	7/27/2015	1 U	1 U	1 U	1 U	1 U	1 U	1 U	0.9 U	10 U	15 U	1 U	1 U	1 U	5 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	1 U	500 U	500 U	1 U	1 U	0.5 U	1 U	2 U
GW-113	8/16/2018	-		1 U		1 U	1 U	1 U		10 U		_			5 U	1 U	1 U	1 U	1 U	_	1 U	1 U	1 U	57 J	500 U	1 U		0.5 U	-	2 U

Units= µg/L

Highlighted cell indicates a detected compound

Qualifiers: U= The analyte was analyzed for and is not present above the level of the associated value.

The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.

UJ= The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.

UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.

UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.

J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.


J-= Same as J qualification but with an indication of negative bias in the sample concentration.

J+= Same as J qualification but with an indication of positive bias in the sample concentration.


APPENDIX C-5.2 VERTICAL MIGRATION ASSESSMENT

Trend Analysis


	Α	В	С	D	Е	F	G	Н	J	K	L
1				Mann-Kenda	II Trend Te	st Analysis					
2		User Select	-								
3	Dat	te/Time of Co	-	ProUCL 5.13		3:53 AM					
4			From File	VERT MIG D	ATA.xls						
5			II Precision	OFF							
6		Confidence		0.95							
7		Level of S	ignificance	0.05							
8									 		
9		1,1-Dic	chloroethane-	-b-504a							
10											
11			eneral Statist								
12				Reported (m)	10						
13				ssing Events	0						
14			-	Events Used	10						
15		Nur	mber Values I	Reported (n)	10						
16				Minimum	1.5						
17				Maximum	11						
18				Mean	5.59						
19			Geo	metric Mean	4.855						
20				Median	4.85						
21				ard Deviation	3.102						
22			Coefficient	t of Variation	0.555						
23											
24		Ма	nn-Kendall T								
25				est Value (S)	1						
26				ated p-value	0.5						
27				eviation of S	11.09						
28				ed Value of S	0						
29			Approxir	mate p-value	0.5						
30											
31			identify a sigr								
32	trend at the	specified le	vel of signific	cance.							




	Α	В	С	D	E	F	G	Н	I	J	K	L
1				Mann-Kenda	III Trend Te	st Analysis						
2		User Select	-									
3	Dat	te/Time of Co	•	ProUCL 5.13		0:09 AM						
4			From File	VERT MIG D	OATA_a.xls							
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8												
9		1,1-Dic	chloroethene-	-b-504a								
10												
11			eneral Statist									
12				Reported (m)	10							
13				ssing Events	0							
14			-	Events Used	10							
15		Nur	nber Values	Reported (n)	10							
16				Minimum	0.115							
17				Maximum	0.47							
18				Mean	0.22							
19			Geo	metric Mean	0.201							
20				Median	0.195							
21				ard Deviation	0.105							
22			Coefficient	t of Variation	0.479							
23												
24		Ма	ann-Kendall T									
25				est Value (S)	-14							
26				lated p-value	0.108							
27				eviation of S	11.14							
28				ed Value of S	-1.167							
29			Approxir	mate p-value	0.122							
30												
31			identify a sigi									
32	trend at the	specified le	vel of signific	cance.								




	Α		В	С	D	Е	F	G	Н	l	J	K	L
1					Mann-Kenda	all Trend Te	st Analysis						
2				ted Options									
3		Date/	Time of C	Computation	ProUCL 5.13		28:31 AM						
4				From File	VERT MIG D	DATA_d.xls							
5				ıll Precision	OFF								
6				Coefficient	0.95								
7			Level of S	Significance	0.05								
8													
9				Acetone-b-50	4a)								
10													
11				eneral Statis									
12					Reported (m)	10							
13					issing Events	0							
14				-	Events Used	10							
15			Nu	mber Values	Reported (n)	10							
16					Minimum	0.95							
17					Maximum	6.9							
18					Mean	2.1							
19				Geo	ometric Mean	1.593							
20					Median	0.95							
21					ard Deviation	1.927							
22				Coefficien	nt of Variation	0.917							
23													
24			Ma	ann-Kendall ⁻									
25					est Value (S)	-17							
26					lated p-value	0.078							
27					Deviation of S	9.781							
28					ed Value of S	-1.636							
29				Approxi	mate p-value	0.0509							
30		-											
31				identify a sig									
32	trend at t	he s	pecified le	evel of signific	cance.								




	Α		В	С	D	E	F	G	Н	ı	J	K	L
1					Mann-Kenda	III Trend Te	st Analysis						
2				ted Options									
3	Da	ate/	Time of C	Computation	ProUCL 5.13		7:07 AM						
4				From File	VERT MIG D	ATA_f.xls							
5				ıll Precision	OFF								
6				Coefficient	0.95								
7			Level of S	Significance	0.05								
8													
9			cis-1,2-[Dichloroether	ne-b-504a								
10													
11				eneral Statis									
12					Reported (m)	10							
13					issing Events	0							
14				-	Events Used	10							
15			Nu	mber Values	Reported (n)	10							
16					Minimum	0.075							
17					Maximum	0.37							
18					Mean	0.152							
19				Geo	ometric Mean	0.128							
20					Median	0.123							
21					ard Deviation	0.0983							
22				Coefficier	nt of Variation	0.649							
23													
24			M	ann-Kendall									
25					est Value (S)	0							
26					ılated p-value	0.5							
27				Standard [Deviation of S	10.36							
28				Standardiz	ed Value of S	N/A							
29				Approxi	imate p-value	N/A							
30					<u> </u>								
31				identify a sig									
32	trend at th	he sp	pecified le	evel of signifi	cance.								




	Α	В	С	D	E	F	G	Н	I	J	K	L				
1				Mann-Kenda	III Trend Te	st Analysis										
2		User Select	-													
3	Dat	te/Time of Co	•	ProUCL 5.13		26:14 AM										
4			From File	VERT MIG D	ATA_g.xls											
5			II Precision	OFF												
6		Confidence		0.95												
7		Level of S	ignificance	0.05	.05											
8																
9		Methyl	ene Chloride	-b-504a												
10																
11			eneral Statist													
12				Reported (m)	10											
13				ssing Events	0											
14			-	Events Used	10											
15		Nur	nber Values	Reported (n)	10											
16				Minimum	0.16											
17				Maximum	0.42											
18				Mean	0.21											
19			Geo	metric Mean	0.193											
20				Median	0.16											
21				ard Deviation	0.106											
22			Coefficient	t of Variation	0.502											
23																
24		Ма	ann-Kendall T													
25				est Value (S)	-1											
26				ated p-value	0.5											
27				eviation of S	7.724											
28				ed Value of S	0											
29			Approxir	mate p-value	0.5											
30																
31			identify a sigi													
32	trend at the	specified le	vel of signific	cance.												




	Α	В	С	D	E	F	G	Н	I	J	K	L			
1				Mann-Kenda	III Trend Te	st Analysis									
2		User Select	-												
3	Dat	te/Time of Co	•	ProUCL 5.13		:5:41 AM									
4			From File	VERT MIG D	ATA_h.xls										
5			II Precision	OFF											
6		Confidence		0.95											
7		Level of S	ignificance	0.05	5										
8															
9		Nap	ohthalene-b-5	504a											
10															
11			eneral Statist												
12				Reported (m)	10										
13				ssing Events	0										
14			-	Events Used	10										
15		Nur	nber Values	Reported (n)	10										
16				Minimum	0.11										
17				Maximum	0.33										
18				Mean	0.132										
19			Geo	metric Mean	0.123										
20				Median	0.11										
21				ard Deviation	0.0696										
22			Coefficient	t of Variation	0.527										
23															
24		Ма	ann-Kendall T												
25				est Value (S)	-3										
26				ated p-value	0.431										
27				eviation of S	5.745										
28				ed Value of S	-0.348										
29			Approxir	mate p-value	0.364										
30															
31			identify a sigi												
32	trend at the	specified le	vel of signific	cance.											




	Α	В	С	D	Е	F	G	Н	J	K	L
1				Mann-Kenda	II Trend Te	st Analysis					
2		User Select	-								
3	Dat	te/Time of Co	•	ProUCL 5.13		24:11 AM					
4			From File	VERT MIG D	ATA_i.xls						
5			II Precision	OFF							
6		Confidence		0.95							
7		Level of S	ignificance	0.05							
8									 		
9		Nitrog	gen, Nitrate-b	o-504a							
10											
11			eneral Statist								
12				Reported (m)	10						
13				ssing Events	0						
14			-	Events Used	10						
15		Nur	nber Values	Reported (n)	10						
16				Minimum	10						
17				Maximum	90						
18				Mean	25.7						
19			Geo	metric Mean	20.94						
20				Median	21						
21				ard Deviation	23.05						
22			Coefficient	t of Variation	0.897						
23											
24		Ma	ann-Kendall T								
25				est Value (S)	9						
26				ated p-value	0.242						
27				eviation of S	8.926						
28				ed Value of S	0.896						
29			Approxir	mate p-value	0.185						
30											
31			identify a sigi								
32	trend at the	specified le	vel of signific	cance.							




	Α	В	С	D	E	F	G	Н		J	K	L				
1				Mann-Kenda	III Trend Te	st Analysis										
2		User Select	-													
3	Dat	te/Time of Co	•	ProUCL 5.13		22:52 AM										
4			From File	VERT MIG D	ATA_k.xls											
5			II Precision	OFF												
6		Confidence		0.95												
7		Level of S	ignificance	0.05	05											
8																
9			oluene-b-50	4a)												
10																
11			eneral Statist													
12				Reported (m)	10											
13				ssing Events	0											
14			-	Events Used	10											
15		Nur	nber Values	Reported (n)	10											
16				Minimum	0.085											
17				Maximum	0.77											
18				Mean	0.305											
19			Geo	metric Mean	0.257											
20				Median	0.225											
21				ard Deviation	0.202											
22			Coefficient	t of Variation	0.662											
23																
24		Ма	ann-Kendall T													
25				est Value (S)	-1											
26				ated p-value	0.5											
27				eviation of S	11.18											
28				ed Value of S	0											
29			Approxir	mate p-value	0.5											
30																
31			identify a sigi													
32	trend at the	specified le	vel of signific	cance.												




	Α	В	С	D	E	F	G	Н	J	K	L
1				Mann-Kenda	II Trend Te	st Analysis					
2			ted Options								
3	Da	ate/Time of C	Computation	ProUCL 5.13		21:39 AM					
4			From File	VERT MIG D	ATA_l.xls						
5			ull Precision	OFF							
6			e Coefficient	0.95							
7		Level of S	Significance	0.05							
8											
9		Vin	yl Chloride-b-	504a							
10											
11			General Statist								
12			er of Events F		10						
13			Number of Mis	_	0						
14			r or Reported		10						
15		Nu	ımber Values		10						
16				Minimum	0.05						
17				Maximum	0.39						
18				Mean	0.175						
19			Geo	metric Mean	0.147						
20				Median	0.19						
21				ard Deviation	0.105						
22			Coefficien	t of Variation	0.599						
23											
24		М	lann-Kendall 1								
25				est Value (S)	-3						
26				lated p-value	0.431						
27				eviation of S	10.85						
28				ed Value of S	-0.184						
29			Approxir	mate p-value	0.427						
30											
31			identify a sig		-						
32	trend at the	e specified l	evel of signific	cance.							




Α	В	С	D			G	Н		J	K	L
			Mann-Kenda	II Trend Te	st Analysis						
		•									
Dat	e/Time of Co	•									
				ATA - B-71	12-LD ONLY.	xls					
	Level of S	ignificance	0.05								
	1,2-Dich	nloroethane-	b-712-ld								
			. ,								
		-									
	Nun	nber Values	,								
		Geo									
		Coefficien	t of Variation	0.547							
	Ma										
			-								
		Approxir	mate p-value	0.265							
trend at the	specified le	vel of signific	cance.								
	Data de la constant d	User Select Date/Time of Confidence Level of S 1,2-Dict Number Number Nur Ma	User Selected Options Date/Time of Computation From File Full Precision Confidence Coefficient Level of Significance 1,2-Dichloroethane- General Statis Number of Events I Number of Mi Number or Reported Number Values Geo Standar Coefficien Mann-Kendall M-K To Tabu Standard D	User Selected Options Date/Time of Computation ProUCL 5.12 From File VERT MIG D Full Precision OFF Confidence Coefficient 0.95	User Selected Options Date/Time of Computation ProUCL 5.12/19/2021 1 From File VERT MIG DATA - B-7 Full Precision OFF Confidence Coefficient Level of Significance General Statistics Number of Events Reported (m) Number of Missing Events Number or Reported Events Used Number Values Reported (n) Number Values Reported (n) Minimum 0.065 Maximum 0.71 Mean 0.433 Geometric Mean 0.331 Median Median 0.505 Standard Deviation Coefficient of Variation Mann-Kendall Test M-K Test Value (S) Standard Deviation of S Tabulated p-value 0.242 Standard Deviation of S Approximate p-value 0.265 Insufficient evidence to identify a significant	User Selected Options Date/Time of Computation From File Full Precision Confidence Coefficient Level of Significance 1,2-Dichloroethane-b-712-ld General Statistics Number of Events Reported (m) Number of Missing Events Number or Reported Events Used Number Values Reported (n) Minimum Number Values Reported (n) Mean 0.433 Geometric Mean 0.331 Median 0.505 Standard Deviation Coefficient of Variation Mann-Kendall Test M-K Test Value (S) Approximate p-value 0.265 Insufficient evidence to identify a significant	Mann-Kendall Trend Test Analysis User Selected Options Date/Time of Computation From File VERT MIG DATA - B-712-LD ONLY.xls Full Precision Confidence Coefficient Level of Significance 1,2-Dichloroethane-b-712-ld General Statistics Number of Events Reported (m) Number of Missing Events Number or Reported Events Used Number Values Reported (n) Number Values Reported (n) Minimum Minimum 0.065 Maximum 0.71 Mean 0.433 Geometric Mean 0.331 Median 0.505 Standard Deviation 0.237 Coefficient of Variation Menn-Kendall Test M-K Test Value (S) Approximate p-value 0.265 Insufficient evidence to identify a significant Insufficient evidence to identify a significant	Mann-Kendall Trend Test Analysis	Mann-Kendall Trend Test Analysis User Selected Options Date/Time of Computation From File VERT MIG DATA - B-712-LD ONLY.xls Full Precision Confidence Coefficient Level of Significance 0.05 1.2-Dichloroethane-b-712-ld General Statistics Number of Events Reported (m) Number of Missing Events Number of Reported Events Used Number or Reported Events Used Number Values Reported (n) Minimum 0.065 Maximum 0.71 Mean 0.433 Geometric Mean 0.331 Geometric Mean Median 0.505 Standard Deviation 0.237 Coefficient of Variation 0.547 Mann-Kendall Test M-K Test Value (S) Raturdard Deviation Standard Deviation 0.242 Standard Deviation Standard Deviation Standard Deviation 0.265 Approximate p-value 0.265 Insufficient evidence to identify a significant	User Selected Options Date/Time of Computation ProUCL 5.12/19/2021 10.41:55 AM From File From File Full Precision Confidence Coefficient Level of Significance General Statistics Number of Events Reported (m) Number of Missing Events Number or Reported Events Used Number Values Reported (n) 10 Minimum 0.065 Maximum 0.71 Mean 0.433 Geometric Mean Median 0.505 Standard Deviation Coefficient of Variation Mann-Kendall Test M-K Test Value (S) Approximate p-value Insufficient evidence to identify a significant Insufficient evidence to identify a significant	Mann-Kendall Trend Test Analysis User Selected Options Date/Time of Computation From File Full Precision Confidence Coefficient Level of Significance 1,2-Dichloroethane-b-712-ld General Statistics Number of Events Reported (m) Number of Missing Events Number of Reported Events Used Number of Reported Events Used Number Values Reported (n) Number Values Reported (n) Number Values Reported (n) Minimum 0.065 Maximum 0.71 Mean 0.433 Geometric Mean 0.331 Geometric Mean 0.505 Standard Deviation 0.237 Coefficient of Variation 0.547 Mann-Kendall Test Man-Kendall Test Man-Kendall Test Mandardized Value of S 11.14 Standardized Value of S Approximate p-value 0.265 Approximate p-value Insufficient evidence to Identify a significant




	Α	В	С	D	E	F	G	Н	I	J	K	L
1				Mann-Kenda	II Trend Tes	st Analysis						
2		User Select	•									
3	Da	te/Time of Co	•	ProUCL 5.12								
4			From File	VERT MIG D	ATA - B-71	2-LD ONLY_	b.xls					
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8												
9		A	rsenic-b-712	-ld								
10												
11			eneral Statist									
12				Reported (m)	10							
13				ssing Events	0							
14			•	Events Used	10							
15		Nur	nber Values	Reported (n)	10							
16				Minimum	2.2							
17				Maximum	7.6							
18				Mean	2.74							
19			Geo	metric Mean	2.49							
20				Median	2.2							
21				ard Deviation	1.708							
22			Coefficien	t of Variation	0.623							
23												
24		Ma	nn-Kendall 1									
25				est Value (S)	3							
26				lated p-value	0.431							
27				eviation of S	5.745	_	_	_				
28				ed Value of S	0.348							
29			Approxi	mate p-value	0.364							
30												
31	Insufficient	evidence to i	identify a sig	nificant								
32	trend at the	e specified le	vel of signific	cance.								




	Α	В	С	D	E	F	G	Н		J	K	L
1				Mann-Kenda	II Trend Te	st Analysis						
2		User Select										
3	Dat	te/Time of C	-	ProUCL 5.12								
4			From File		ATA - B-71	2-LD ONLY_	d.xls					
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	Significance	0.05								
8								Ī	T	1		
9		Nap	hthalene-b-7	12-ld								
10												
11			eneral Statis									
12				Reported (m)	11							
13				ssing Events	0							
14			•	Events Used	11							
15		Nur	mber Values	Reported (n)	11							
16				Minimum	0.11							
17				Maximum	0.56							
18				Mean	0.151							
19			Geo	metric Mean	0.128							
20				Median	0.11							
21				ard Deviation	0.136							
22			Coefficien	t of Variation	0.899							
23												
24		Ma	ann-Kendall		10							
25				est Value (S)	10							
26				lated p-value	0.223							
27				Deviation of S	6.325							
28				ed Value of S	1.423							
29			Approxi	mate p-value	0.0774							
30												
31			identify a sig									
32	trend at the	specified le	evel of signific	cance.								




	Α	В	С	D	E	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Selecte	•									
3	Dat	e/Time of Co		ProUCL 5.12								
4			From File	VERT MIG D	DATA - B-71	12-LD ONLY_	_c.xls					
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of Significance 0.05										
8							1	T	Ī	1	T	
9		Nitroge	en, Nitrate-b-	-712-ld								
10		One and Obstation										
11			eneral Statist									
12				Reported (m)	10							
13				ssing Events	0							
14			-	Events Used	10							
15		Nun	nber Values I	Reported (n) Minimum	10 21							
16				Maximum	110							
17				Mean	37.7							
18			Coo	metric Mean	31.5							
19			Geo	Median	21							
20			Standa	ard Deviation	28.36							
21				t of Variation	0.752							
22				t or variation	0.702							
23		Ma	nn-Kendall T	Test								
24 25				est Value (S)	10							
26				ated p-value	0.19							
27				eviation of S	9.832							
28			Standardize	d Value of S	0.915							
29			Approxir	mate p-value	0.18							
30												
31	Insufficient e	evidence to i	identify a sigr	nificant								
32	trend at the	specified le	vel of signific	ance.								
<u> </u>						1	1	1	l	1	1	




	Α	В	С	D	E	F	G	Н		J	K	L
1				Mann-Kenda	II Trend Te	st Analysis						
2		User Select	-									
3	Dat	te/Time of Co	•	ProUCL 5.12								
4			From File	COMPLIANC	E DATA Fo	or TREND- 1	H2020.xls					
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8									 			
81		1,4-	Dioxane-b-7	12-ld								
82												
83			eneral Statist									
84				Reported (m)	10							
85				ssing Events	0							
86			-	Events Used	10							
87		Nur	nber Values	Reported (n)	10							
88				Minimum	0.045							
89				Maximum	0.95							
90				Mean	0.247							
91			Geo	metric Mean	0.168							
92				Median	0.25							
93				ard Deviation	0.263							
94			Coefficien	t of Variation	1.066							
95												
96		Ma	nn-Kendall									
97				est Value (S)	-30							
98				lated p-value	0.002							
99		Standard Devia			10.23							
100		Standardized Value of S -2.8										
101		Approximate p-value 0.00229										
102												
103												
104	trend at the	specified lev	vel of signific	ance.								




	Α	В	С	D	Е	F	G	Н	I	J	K	L
1				Mann-Kenda	III Trend Te	st Analysis						
2		User Select	-									
3	Dat	te/Time of Co	•	ProUCL 5.13		:6:14 AM						
4			From File	VERT MIG D	ATA_g.xls							
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8												
33		Methylene Chloride-c-702p3										
34		Consumi Chabintina										
35			eneral Statist									
36		Number of Events Reported (m) 10										
37		Number of Missing Events 0										
38		Number or Reported Events Used 10										
39		Number Values Reported (n) 10										
40				Minimum	0.16							
41				Maximum	0.43							
42				Mean	0.209							
43			Geo	metric Mean	0.193							
44				Median	0.16							
45				ard Deviation	0.104							
46			Coefficient	t of Variation	0.497							
47												
48		Ма	nn-Kendall T									
49				est Value (S)	-15							
50		Tabulated p-value 0.108										
51		Standard Deviation of S 7.724										
52		Standardized Value of S -1.812										
53		Approximate p-value 0.035										
54												
55			identify a sigr									
56	trend at the	specified le	vel of signific	cance.								




	Α	В	С	D	E	F	G	Н	l	J	K	L
1				Mann-Kenda	II Trend Te	st Analysis						
2		User Selecte	•									
3	Dat	te/Time of Co	•	ProUCL 5.13		4:11 AM						
4			From File	VERT MIG D	ATA_i.xls							
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8						1	1	1		T		
57		Nitrog	en, Nitrate-c	-702p3								
58												
59			eneral Statist		10							
60				Reported (m)	10							
61				ssing Events	0							
62			•	Events Used	10							
63		Nun	nber Values	Reported (n)	10							
64				Minimum	10							
65				Maximum	87							
66			0	Mean metric Mean	32.2 26.58							
67			Geo	Median	26.58							
68			Ctondo	ard Deviation	23.64							
69				t of Variation	0.734							
70			Coemicien	t or variation	0.734							
71		Ma	nn-Kendall 1	Foet								
72		IVIA		est Value (S)	16							
73				ated p-value	0.078							
74				eviation of S	9.832							
75	Standardized Value of S 1.526											
76	Approximate p-value 0.0635											
77	Approximate p-value 0.0033											
78	Insufficient	evidence to i	identify a sign	nificant								
79	A											
80		- CPCCITICA TO	. Or Or Signation								<u> </u>	




	Α		В	С	D	Е	F	G	Н	l	J	K	L
1					Mann-Kenda	III Trend Te	st Analysis						
2				ed Options									
3		Date/	Time of C	omputation	ProUCL 5.13								
4				From File	VERT MIG D	ATA_d.xls							
5				II Precision	OFF								
6				Coefficient	0.95								
7			Level of S	Significance	0.05								
8													
9													
33			A	cetone-gw-1	13								
34													
35				eneral Statist									
36		Number of Events Reported (m) 10											
37		3				0							
38		Number or Reported Events Used 10 Number Values Reported (n) 10											
39			Nur	mber Values	/	10							
40					Minimum	0.95							
41					Maximum	2.1							
42					Mean	1.065							
43				Geo	metric Mean	1.028							
44					Median	0.95							
45					ard Deviation	0.364							
46				Coefficien	t of Variation	0.341							
47													
48			Ma	ann-Kendall 1									
49					est Value (S)	3							
50		Tabulated p-value 0.431											
51		Standard Deviation of S 5.745											
52		Standardized Value of S 0.348											
53		Approximate p-value 0.364											
54													
55		nsufficient evidence to identify a significant											
56	trend at	the s	pecified le	vel of signific	cance.								



	Α	В	С	D	Е	F	G	Н	J	K	L
1				Mann-Kenda	III Trend Te	st Analysis					
2		User Select	-								
3	Dat	te/Time of Co	•	ProUCL 5.13		23:27 AM					
4			From File	VERT MIG D	ATA_j.xls						
5			II Precision	OFF							
6		Confidence		0.95							
7		Level of S	ignificance	0.05							
8									 		
9		Nitrog	gen, Nitrite-g	w-113							
10		Conoral Otaticalica									
11			eneral Statist								
12				Reported (m)	10						
13		Number of Missing Events 0									
14		Number or Reported Events Used 10									
15		Number Values Reported (n) 10									
16				Minimum	15						
17				Maximum	50						
18				Mean	25.15						
19			Geo	metric Mean	23.85						
20				Median	24.5						
21				ard Deviation	9.583						
22			Coefficient	t of Variation	0.381						
23											
24		Ма	ann-Kendall T								
25				est Value (S)	19						
26		Tabulated p-value 0.054									
27		Standard Deviation of S 8.926									
28		Standardized Value of S 2.017									
29			Approxir	mate p-value	0.0219						
30											
31			identify a sigi								
32	trend at the	specified le	vel of signific	cance.							



	Α	В	С	D	E	F	G	Н	I	J	K	L
1				Mann-Kenda	all Trend Te	st Analysis						
2		User Select	-									
3	Dat	te/Time of Co	•	ProUCL 5.13		24:11 AM						
4			From File	VERT MIG D	DATA_i.xls							
5			II Precision	OFF								
6		Confidence		0.95								
7		Level of S	ignificance	0.05								
8												
81		Nitrog	jen, Nitrate-g	w-113								
82												
83			eneral Statist									
84			er of Events F		10							
85		Number of Missing Events 0										
86		Number or Reported Events Used 10										
87		Number Values Reported (n) 10										
88				Minimum	10							
89				Maximum	270							
90				Mean	67.2							
91			Geo	metric Mean	41.96							
92				Median	42.5							
93			Standa	ard Deviation	80.16							
94			Coefficient	t of Variation	1.193							
95												
96		Ma	nn-Kendall T	Test Test								
97			M-K Te	est Value (S)	-4							
98		Tabulated p-value 0.364										
99		Standard Deviation of S 11.02										
100		Standardized Value of S -0.272										
101	Approximate p-value 0.393											
102												
103	Insufficient (evidence to i	identify a sigr	nificant								
104	trend at the	specified le	vel of signific	cance.								



APPENDIX C-5.3 VERTICAL MIGRATION ASSESSMENT

Dixon's Test for Outliers

	Α		В	С	D	Е	F	G	Н		J	K	L
1						Outlier Test	s for Selecte	d Variables ı	replacing non	detects with	1/2 the Dete	ection Limit	
2					cted Options								
3	D	ate/1	Time of Co	omputation	ProUCL 5.12								
4					From File		DATA - B-71	2-LD ONLY	FOR DIXON'	S.xls			
5				Fu	II Precision	OFF							
6													
7	0:		O Miss T			N-1-1\\							
8	אוט	(on s	Outlier 1	est for 1,4-D	ioxane (b-712	<u>(-1a)</u>							
9	Total N =	10											
10	Number N		· 0										
	Number N												
12	Number D												
	10% critica)									
14 15	5% critical			,									
	1% critical												
16 17				DL/2 in Outlie	er Test								
18													
19	1. Data V	alue	0.95 is a	Potential Ou	ıtlier (Upper T	ail)?							
20						<u> </u>							
21	Test Statis	stic: (0.800										
22													
23	For 10% s	ignifi	icance lev	vel, 0.95 is a	n outlier.								
24	For 5% sig	gnific	ance leve	el, 0.95 is an	outlier.								
25	For 1% sig	gnific	ance leve	el, 0.95 is an	outlier.								
26													
27	2. Data Va	alue (0.045 is a	Potential O	utlier (Lower ⁻	Tail)?							
28													
29	Test Statis	stic: (0.146										
30			-										
31		-			not an outlier.								
32		5% significance level, 0.045 is not an outlie											
33	For 1% sig	gnific	ance leve	el, 0.045 is no	ot an outlier.								
34													

APPENDIX C-6 NORTH END MONITORING AND RESPONSE ACTIONS

APPENDIX C-6.1 NORTH END – ALL ORGANICS AND NITRATE DATA

APPENDIX C-6.1 NORTH END - ALL ORGANICS AND NITRATE JANUARY THROUGH JUNE 22 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	LOWRY LANDFILL SUPERFU Parameter Name	Date Sampled	Result (µg/L) ^{a/}	Qualifier ^{b/}
31	B-314	Nitrogen, Nitrate	4/13/2022	890	
31	B-314	Nitrogen, Nitrite	4/13/2022	500	U
31	B-314	1,4-Dioxane	4/13/2022	0.9	U
31	B-314	1.1.1-Trichloroethane	4/13/2022	1	U
31	B-314	1,1,2,2-Tetrachloroethane	4/13/2022	1	U
31	B-314	1,1,2-Trichloroethane	4/13/2022	1	U
31	B-314	1,1-Dichloroethane	4/13/2022	1.5	0
31	B-314	1,1-Dichloroethene	4/13/2022	1	U
31	B-314	1.2-Dichloroethane	4/13/2022	1	U
31	B-314	1,2-Dichloropropane	4/13/2022	1	U
31	B-314	1,4-Dioxane	4/13/2022	200	U
31	B-314	Acetone	4/13/2022	10	U
31	B-314	Benzene	4/13/2022	1	U
31	B-314	Bromodichloromethane	4/13/2022	1	U
31	B-314	Bromoform	4/13/2022	1	U
31	B-314	Carbon Tetrachloride	4/13/2022	1	U
31	B-314	Chlorobenzene	4/13/2022	1	U
31	B-314	Chloroform	4/13/2022	1	U
31	B-314	cis-1,2-Dichloroethene	4/13/2022	1	U
31	B-314	Dibromochloromethane	4/13/2022	1	U
31	B-314	Ethylbenzene	4/13/2022	1	U
31	B-314	Methylene Chloride	4/13/2022	1	U
31	B-314	Naphthalene	4/13/2022	1	U
31	B-314	Tetrachloroethene	4/13/2022	1	U
31	B-314	Toluene	4/13/2022	1	U
31	B-314	Trans-1,2-Dichloroethene	4/13/2022	0.5	U
31	B-314	Trichloroethene	4/13/2022	1	U
31	B-314	Vinyl Chloride	4/13/2022	2	U
31	B-326-UD	1,4-Dioxane	2/8/2022	4.5	
31	B-326-UD	1,4-Dioxane	4/14/2022	4.6	
31	B-326-WD	Nitrogen, Nitrate	4/14/2022	360	J
31	B-326-WD	Nitrogen, Nitrite	4/14/2022	500	U
31	B-326-WD	1,4-Dioxane	2/8/2022	3.6	
31	B-326-WD	1,4-Dioxane	4/14/2022	3.2	
31	B-326-WD	1,1,1-Trichloroethane	4/14/2022	1	U
31	B-326-WD	1,1,2,2-Tetrachloroethane	4/14/2022	1	U
31	B-326-WD	1,1,2-Trichloroethane	4/14/2022	1	U
31	B-326-WD	1,1-Dichloroethane	4/14/2022	1	U
31	B-326-WD	1,1-Dichloroethene	4/14/2022	1	U
31	B-326-WD	1,2-Dichloroethane	4/14/2022	1	U
31	B-326-WD	1,2-Dichloropropane	4/14/2022	1	U
31	B-326-WD	1,4-Dioxane	4/14/2022	200	U
31	B-326-WD	Acetone	4/14/2022	10	U
31	B-326-WD	Benzene	4/14/2022	1	U
31	B-326-WD	Bromodichloromethane	4/14/2022	1	U
31	B-326-WD	Bromoform	4/14/2022	1	U
31	B-326-WD	Carbon Tetrachloride	4/14/2022	1	U
31	B-326-WD	Chlorobenzene	4/14/2022	1	U
31	B-326-WD	Chloroform	4/14/2022	1	U
31	B-326-WD	cis-1,2-Dichloroethene	4/14/2022	1	U
31	B-326-WD	Dibromochloromethane	4/14/2022	1	U
31	B-326-WD	Ethylbenzene	4/14/2022	1	U
31	B-326-WD	Methylene Chloride	4/14/2022	1	U

APPENDIX C-6.1 NORTH END - ALL ORGANICS AND NITRATE JANUARY THROUGH JUNE 22 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	LOWRY LANDFILL SUPERFU Parameter Name	Date Sampled	Result (µg/L) ^{a/}	Qualifier ^{b/}
31	B-326-WD	Naphthalene	4/14/2022	1	U
31	B-326-WD	Tetrachloroethene	4/14/2022	1	U
31	B-326-WD	Toluene	4/14/2022	1	U
31	B-326-WD	Trans-1,2-Dichloroethene	4/14/2022	0.5	U
31	B-326-WD	Trichloroethene	4/14/2022	1	U
31	B-326-WD	Vinyl Chloride	4/14/2022	2	U
31	MW05-WD	1,4-Dioxane	3/1/2022	3.6	
31	MW113-EW-1	Nitrogen, Nitrate	1/25/2022	210	J
31	MW113-EW-1	Nitrogen, Nitrate	4/19/2022	150	J
31	MW113-EW-1	1,4-Dioxane	1/25/2022	99	
31	MW113-EW-1	1,4-Dioxane	4/19/2022	89	
31	MW113-UD	1,4-Dioxane	1/25/2022	59	
31	MW113-UD	1,4-Dioxane	5/17/2022	57	
31	MW113-WD	1,4-Dioxane	5/3/2022	36	
31	MW114-WD	1,4-Dioxane	1/20/2022	0.96	
31	MW114-WD	1,4-Dioxane	5/9/2022	0.89	J
31	MW117-WD	1,4-Dioxane	1/20/2022	1.3	
31	MW117-WD	1,4-Dioxane	5/9/2022	1.2	
31	MW118-WD	1,4-Dioxane	1/20/2022	0.28	J
31	MW118-WD	1,4-Dioxane	5/9/2022	0.22	J
31	MW121-WDR	1,4-Dioxane	1/26/2022	0.77	J
31	MW122-WDR	1,4-Dioxane	1/26/2022	1.9	
31	MW123-WD	1,4-Dioxane	1/26/2022	1.7	
31	MW124-WD	1,4-Dioxane	1/27/2022	0.48	J
31	MW125-WD	1,4-Dioxane	1/27/2022	0.34	J
31	MW129-WD	1,4-Dioxane	2/28/2022	4.7	
31	MW132-WD	1,4-Dioxane	1/31/2022	15	
31	MW132-WD	1,4-Dioxane	5/10/2022	10	
30	MW135-WD	1,4-Dioxane	2/23/2022	5.1	
30	MW141-WD	1,4-Dioxane	2/15/2022	2.2	
19	MW142-WD	1,4-Dioxane	2/23/2022	1.4	
24	MW144-WD	1,4-Dioxane	2/15/2022	0.9	U
31	MW151-WD	1,4-Dioxane	1/31/2022	4.8	
31	MW151-WD	1,4-Dioxane	5/16/2022	1.8	
31	MW153-EW-1	1,4-Dioxane	1/27/2022	3.3	
31	MW153-EW-1	1,4-Dioxane	4/27/2022	2.3	
31	MW154-EW-1	1,4-Dioxane	1/27/2022	1.7	
31	MW154-EW-1	1,4-Dioxane	4/28/2022	2.6	
31	MW155-EW-1	1,4-Dioxane	1/31/2022	0.49	J
31	MW155-EW-1	1,4-Dioxane	5/2/2022	1.5	
31	MW156-EW-1	1,4-Dioxane	2/9/2022	0.45	J
31	MW156-EW-1	1,4-Dioxane	5/2/2022	0.6	J
31	MW156-WD	1,4-Dioxane	2/10/2022	0.19	J
31	MW156-WD	1,4-Dioxane	5/16/2022	0.51	J
31	MW157-WD	1,4-Dioxane	2/10/2022	0.9	U
31	MW157-WD	1,4-Dioxane	5/16/2022	0.9	U
31	MW160-WD	1,4-Dioxane	1/31/2022	3.7	
31	MW160-WD	1,4-Dioxane	4/26/2022	2.9	
13	MW176-DEN	1,4-Dioxane	2/15/2022	0.52	J
31	MW179-UDEN	1,4-Dioxane	3/1/2022	0.9	U
19	Private Well 1	1,4-Dioxane	6/7/2022	0.9	U
30	Private Well 2	1,4-Dioxane	6/7/2022	0.9	U
31	PTP-12	1,4-Dioxane	2/14/2022	7.1	

NORTH END - ALL ORGANICS AND NITRATE

JANUARY THROUGH JUNE 22 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	Parameter Name	Date Sampled	Result (µg/L) ^{a/}	Qualifier ^{b/}
31	PTP-12	1,4-Dioxane	5/11/2022	4.8	
31	PTP-13	1,4-Dioxane	3/1/2022	8.2	
31	PTP-13	1,4-Dioxane	5/12/2022	6.3	

a/ μ g/L = micrograms per liter

b/ Final Q definitions:

 $\textbf{Qualifiers:} \ \ U= \ \ \text{The analyte was analyzed for and is not present above the level of the associated value.}$

- UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.
- UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.
- UJ= The analyte analyzed for was not present above the level of the associated value. The associated
- J= The analyte was analyzed for, and was positively identified, but the associated numerical value

 The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.
- J-= Same as J qualification but with an indication of negative bias in the sample concentration.
- J+= Same as J qualification but with an indication of positive bias in the sample concentration.

APPENDIX C-6.2 MW77 AREA – ALL ORGANICS AND NITRATE DATA

TABLE C-6.2 MW77 AREA - ALL ORGANICS AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	Parameter Name	Date Sampled	Result (ug/L) ^{a/}	Qualifier
31	MW102-WD	1,4-Dioxane	1/24/2022	0.92	
31	MW102-WD	1,4-Dioxane	4/28/2022	1.2	
31	MW103-WD	1,4-Dioxane	2/7/2022	0.35	J
31	MW103-WD	1,4-Dioxane	5/9/2022	0.27	J
31	MW170-EW-1	1,1,1-Trichloroethane	1/25/2022	1.8	
31	MW170-EW-1	1,1,1-Trichloroethane	5/10/2022	1.3	
31	MW170-EW-1	1,1,2,2-Tetrachloroethane	1/25/2022	1	U
31	MW170-EW-1	1,1,2,2-Tetrachloroethane	5/10/2022	1	U
31	MW170-EW-1	1,1,2-Trichloroethane	1/25/2022	1	U
31	MW170-EW-1	1,1,2-Trichloroethane	5/10/2022	1	U
31	MW170-EW-1	1,1-Dichloroethane	1/25/2022	3.7	
31	MW170-EW-1	1,1-Dichloroethane	5/10/2022	3.3	
31	MW170-EW-1	1,1-Dichloroethene	1/25/2022	3	
31	MW170-EW-1	1,1-Dichloroethene	5/10/2022	2.4	
31	MW170-EW-1	1,2-Dichloroethane	1/25/2022	1	U
31	MW170-EW-1	1,2-Dichloroethane	5/10/2022	1	Ü
31	MW170-EW-1	1,2-Dichloropropane	1/25/2022	1	U
31	MW170-EW-1	1,2-Dichloropropane	5/10/2022	1	U
31	MW170-EW-1	1,4-Dioxane	1/25/2022	14	
31	MW170-EW-1	1,4-Dioxane	1/25/2022	200	U
31	MW170-EW-1	1,4-Dioxane	5/10/2022	11	Ŭ
31	MW170-EW-1	1,4-Dioxane	5/10/2022	200	U
31	MW170-EW-1	Acetone	1/25/2022	10	U
31	MW170-EW-1	Acetone	5/10/2022	4.4	J
31	MW170-EW-1	Benzene	1/25/2022	1	U
31	MW170-EW-1	Benzene	5/10/2022	1	U
31	MW170-EW-1	Bromodichloromethane	1/25/2022	1	U
		Bromodichloromethane	_		U
31	MW170-EW-1		5/10/2022	1	U
31	MW170-EW-1	Bromoform	1/25/2022		
31	MW170-EW-1	Bromoform	5/10/2022	1	U
31	MW170-EW-1	Carbon Tetrachloride	1/25/2022	1	U
31	MW170-EW-1	Carbon Tetrachloride	5/10/2022	1	U
31	MW170-EW-1	Chlorobenzene	1/25/2022	1	U
31	MW170-EW-1	Chlorobenzene	5/10/2022	1	U
31	MW170-EW-1	Chloroform	1/25/2022	1	U
31	MW170-EW-1	Chloroform	5/10/2022	1	U
31	MW170-EW-1	cis-1,2-Dichloroethene	1/25/2022	9	
31	MW170-EW-1	cis-1,2-Dichloroethene	5/10/2022	8.2	
31	MW170-EW-1	Dibromochloromethane	1/25/2022	1	U
31	MW170-EW-1	Dibromochloromethane	5/10/2022	1	U
31	MW170-EW-1	Ethylbenzene	1/25/2022	1	U
31	MW170-EW-1	Ethylbenzene	5/10/2022	1	U
31	MW170-EW-1	Methylene Chloride	1/25/2022	1	U
31	MW170-EW-1	Methylene Chloride	5/10/2022	1	U
31	MW170-EW-1	Naphthalene	1/25/2022	1	U
31	MW170-EW-1	Naphthalene	5/10/2022	1	U
31	MW170-EW-1	Nitrogen, Nitrate	1/25/2022	11000	
31	MW170-EW-1	Nitrogen, Nitrate	5/10/2022	9700	
31	MW170-EW-1	Nitrogen, Nitrite	5/10/2022	500	U
31	MW170-EW-1	Tetrachloroethene	1/25/2022	1.2	
31	MW170-EW-1	Tetrachloroethene	5/10/2022	0.7	J
31	MW170-EW-1	Toluene	1/25/2022	1	U
31	MW170-EW-1	Toluene	5/10/2022	1	U
31	MW170-EW-1	Trans-1,2-Dichloroethene	1/25/2022	0.5	U

TABLE C-6.2 MW77 AREA - ALL ORGANICS AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	Parameter Name	Date Sampled	Result (ug/L) ^{a/}	Qualifier
31	MW170-EW-1	Trans-1,2-Dichloroethene	5/10/2022	0.5	U
31	MW170-EW-1	Trichloroethene	1/25/2022	0.49	J
31	MW170-EW-1	Trichloroethene	5/10/2022	0.51	J
31	MW170-EW-1	Vinyl Chloride	1/25/2022	2	U
31	MW170-EW-1	Vinyl Chloride	5/10/2022	2	U
31	MW23-UPPER-C	1,1,1-Trichloroethane	4/20/2022	1	U
31	MW23-UPPER-C	1,1,2,2-Tetrachloroethane	4/20/2022	1	U
31	MW23-UPPER-C	1,1,2-Trichloroethane	4/20/2022	1	U
31	MW23-UPPER-C	1,1-Dichloroethane	4/20/2022	1	U
31	MW23-UPPER-C	1,1-Dichloroethene	4/20/2022	1	U
31	MW23-UPPER-C	1,2-Dichloroethane	4/20/2022	1	U
31	MW23-UPPER-C	1,2-Dichloropropane	4/20/2022	1	U
31	MW23-UPPER-C	1,4-Dioxane	4/20/2022	0.9	U
31	MW23-UPPER-C	1,4-Dioxane	4/20/2022	200	U
31	MW23-UPPER-C	Acetone	4/20/2022	10	U
31	MW23-UPPER-C	Benzene	4/20/2022	1	U
31	MW23-UPPER-C	Bromodichloromethane	4/20/2022	1	U
31	MW23-UPPER-C	Bromoform	4/20/2022	1	U
31	MW23-UPPER-C	Carbon Tetrachloride	4/20/2022	1	Ü
31	MW23-UPPER-C	Chlorobenzene	4/20/2022	1	U
31	MW23-UPPER-C	Chloroform	4/20/2022	1	Ü
31	MW23-UPPER-C	cis-1.2-Dichloroethene	4/20/2022	1	U
31	MW23-UPPER-C	Dibromochloromethane	4/20/2022	1	Ü
31	MW23-UPPER-C	Ethylbenzene	4/20/2022	1	U
31	MW23-UPPER-C	Methylene Chloride	4/20/2022	1	U
31	MW23-UPPER-C	Naphthalene	4/20/2022	1	U
31	MW23-UPPER-C	Nitrogen, Nitrate	4/20/2022	120	J
31	MW23-UPPER-C	Nitrogen, Nitrite	4/20/2022	340	J
31	MW23-UPPER-C	Tetrachloroethene	4/20/2022	1	U
31	MW23-UPPER-C	Toluene	4/20/2022	1	U
31	MW23-UPPER-C	Trans-1,2-Dichloroethene	4/20/2022	0.5	U
31	MW23-UPPER-C	Trichloroethene	4/20/2022	1	U
31	MW23-UPPER-C	Vinyl Chloride	4/20/2022	2	U
31	MW77-EW-1	1,4-Dioxane	1/24/2022	2.5	U
31		1,4-Dioxane		2.7	
	MW77-EW-1	/	4/28/2022		T
31	MW77-EW-2	1,4-Dioxane	1/24/2022	0.09	J
31	MW77-EW-2	1,4-Dioxane	4/28/2022	0.9	U
31	MW77-WD	1,1,1-Trichloroethane	4/18/2022	1	1
31	MW77-WD	1,1,2,2-Tetrachloroethane	4/18/2022	1	U
31	MW77-WD	1,1,2-Trichloroethane	4/18/2022	1	U
31	MW77-WD	1,1-Dichloroethane	4/18/2022	1	U
31	MW77-WD	1,1-Dichloroethene	4/18/2022	0.66	J
31	MW77-WD	1,2-Dichloroethane	4/18/2022	1	U
31	MW77-WD	1,2-Dichloropropane	4/18/2022	1	U
31	MW77-WD	1,4-Dioxane	4/18/2022	12	* * *
31	MW77-WD	1,4-Dioxane	4/18/2022	200	U
31	MW77-WD	Acetone	4/18/2022	10	U
31	MW77-WD	Benzene	4/18/2022	1	U
31	MW77-WD	Bromodichloromethane	4/18/2022	1	U
31	MW77-WD	Bromoform	4/18/2022	1	U
31	MW77-WD	Carbon Tetrachloride	4/18/2022	1	U
31	MW77-WD	Chlorobenzene	4/18/2022	1	U
31	MW77-WD	Chloroform	4/18/2022	1	U
31	MW77-WD	cis-1,2-Dichloroethene	4/18/2022	1	U

TABLE C-6.2 MW77 AREA - ALL ORGANICS AND NITRATE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Section	Well ID	Parameter Name	Date Sampled	Result (ug/L) ^{a/}	Qualifier ^{b/}
31	MW77-WD	Dibromochloromethane	4/18/2022	1	U
31	MW77-WD	Ethylbenzene	4/18/2022	1	U
31	MW77-WD	Methylene Chloride	4/18/2022	1	U
31	MW77-WD	Naphthalene	4/18/2022	1	U
31	MW77-WD	Nitrogen, Nitrate	4/18/2022	13000	J
31	MW77-WD	Nitrogen, Nitrite	4/18/2022	500	U
31	MW77-WD	Tetrachloroethene	4/18/2022	0.74	J
31	MW77-WD	Toluene	4/18/2022	1	U
31	MW77-WD	Trans-1,2-Dichloroethene	4/18/2022	0.5	U
31	MW77-WD	Trichloroethene	4/18/2022	1	U
31	MW77-WD	Vinyl Chloride	4/18/2022	2	U
31	MW98-WD	1,4-Dioxane	1/24/2022	5.9	
31	MW98-WD	1,4-Dioxane	4/28/2022	7.8	

a/ ug/L = micrograms per liter

- b/ Qualifiers: U= The analyte was analyzed for and is not present above the level of the associated value.
 - The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.
 - UJ= The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.
 - UJ-= Same as UJ qualification but with an indication of negative bias in the sample concentration.
 - UJ+= Same as UJ qualification but with an indication of positive bias in the sample concentration.
 - J-= Same as J qualification but with an indication of negative bias in the sample concentration.
 - J+= Same as J qualification but with an indication of positive bias in the sample concentration.
 - J= The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.

WELL PERMIT INVENTORY WITHIN FIVE MILES OF THE SITE

OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth Completed Well	gBottom	PerforatedCasin gTop
758	434	277683-	3629584O	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	25	25	10
745	476	276337-	3624266F	Owner	Well Constructed	AURORA CITY OF	5	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	16	6
63	536	42559-MH	0042559A	Owner	Well Constructed	US GEOLOGICAL SURVEY	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	23	13
756	549	277679-	3629584K	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	21	11
613	573	55021-F	0469523A	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	8	Well (Construction Report)	General Purpose	LOWER ARAPAHOE	Commercial, Industrial	1663	1620	1420
744	578	276336-	3624266E	Owner	Well Constructed	AURORA CITY OF	8	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	16	6
667	584	250517-	0514425C	Owner	Well Constructed	US GEOLOGICAL SURVEY	8	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	28	18
67	640	42699-MH	42699	Owner	Well Constructed	US GEOLOGICAL SURVEY	32	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	25	15
761	667	277686-	3629584R	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	16	13	3
759	698	277684-	3629584P	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	28	18
61	799	42224-MH	42224	Owner	Well Constructed	US GEOLOGICAL SURVEY	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	9
750	929	276343-	3624266L	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	36	30	20
661	930	59432-F	505380	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	General Purpose	UPPER ARAPAHOE		2285		
64	940	42561-MH	42561	Owner	Well Constructed	US GEOLOGICAL SURVEY	4	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	38	38	28
118	987	276381-	0047606X	Owner	Well Constructed	AURORA CITY OF	28	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling		13	8
757	991	277681-	3629584M	Owner	Well Constructed	AURORA CITY OF	33	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling		35	25
101		2,,,,,,	5525501111	S HIM	constructed			(Application Fermin)	South Auton					20
752	1042	277671-	3629584C	Owner	Well Constructed	AURORA CITY OF	28	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	26	16

		1												
												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
66	1064	42563-MH	42563	Owner	Well Constructed	US GEOLOGICAL SURVEY	9	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	28	18
										ALL IDDIAMED				
762	1085	277687-	3629584S	Owner	Well Constructed	SANCHEZ, JOSE D.	4	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	22	12
749	1113	276342-	3624266K	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	15	5
62	1177	42238-MH	0042238A	Owner	Well Constructed	US GEOLOGICAL SURVEY	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	48	48	39
						EAST CHERRY CREEK			Monitoring Hole (Notice of					
141	1178	52455-MH	52455	Owner	Well Constructed	VALLEY WSD	16	Well (Application/Permit)	Intent)	DAWSON	Monitoring/Sampling	73	73	63
751	1254	277670-	3629584B	Owner	Well Constructed	AURORA CITY OF	3	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	18	8
830	1278	68772A	3676249	Owner	Well Constructed	THOMPSON, LEO I	22	Well (Application/Permit)	Residential	DENVER	Domestic	415	415	335
795	1317	78279A	3655678	Owner	Well Constructed	GLENN, ALYSSA	22	Well (Application/Permit)	Residential	DENVER	Domestic	485	485	305
797	1344	70905A	3657129	Owner	Well Constructed	HANCOCK, DALE	22	Well (Application/Permit)	Residential	DENVER	Domestic	380	380	320
748	1367	276341-	3624266J	Owner	Well Constructed	AURORA CITY OF	22	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	15	5
142	1380	52456-MH	52456	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WSD	15	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling	25	25	15
						US GEOLOGICAL			Monitoring Hole (Notice of	ALL UNNAMED				
56	1387	42218-MH	42218	Owner	Well Constructed	SURVEY	3	Well (Application/Permit)	Intent)	AQUIFERS	Monitoring/Sampling	38	37	27
760	1432	277685-	3629584Q	Owner	Well Constructed	AURORA CITY OF	27	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	21	11
			-					, == /	_					
188	1473	98064-	0089396A	Owner	Well Constructed	ANNA TRUST	22	Well (Application/Permit)	Residential	DENVER	Domestic	280	280	220
206	1473	105123-	101907	Owner	Well Constructed	KRUKOV, DANILA	22	Well (Application/Permit)	Residential	DENVER	Domestic	190	190	160
									Monitoring Hole (Notice of	ALL UNNAMED				
82	1496	46392-MH	46392	Owner	Well Constructed	AURORA CITY OF	34	Well (Application/Permit)		AQUIFERS	Monitoring/Sampling	18	18	8
747	1497	276340-	3624266I	Owner	Well Constructed	AURORA CITY OF	34	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	26	18	8
/4/	177/	4/0340-	30272001	OWILL	Well Collstructed	AURORA CITT OF	37	Tren (Application/Termit)	1410111101111g/OUSCI VALIOII	ALLUVIAL	1410mormg/Samping	40	10	U

OID	Map ID ^{a/}	D	D int	A Town	D	ContactNone	S	Location Towns	Dit C. da		Had			PerforatedCasin
ОП	мар пл	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
743	1573	276335-	3624266D	Owner	Well Constructed	AURORA CITY OF	3	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	15	5
143	1575	52457-MH	52457	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WSD	10	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	13	13	8
234	1583	122785-	219886	Owner	Well Constructed	BROWN, KATHLEEN A.	. 22	Well (Construction Report)	Residential	DENVER	Domestic	370	370	210
235	1583	122785-	219886	Owner	Well Constructed	BROWN, ROBERT H.	22	Well (Construction Report)	Residential	DENVER	Domestic	370	370	210
1019	1591	94021-	9007730	Owner	Well Constructed	HAM J GARY & LOU R	27	Well (Construction Report)	Residential	LOWER DAWSON	Domestic			
753	1609	277673-	3629584E	Owner	Well Constructed	AURORA CITY OF	27	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	27	17
144	1652	52458-MH	52458	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WSD	11	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling	38	38	23
588	1672	52128-F	0445522C	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SAN DST	11	Well (Construction Report)	General Purpose	ARAPAHOE	Municipal	1670	1650	1116
803	1689	291854-	3660285C	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	44	44	24
805	1692	291856-	3660285E	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	39	39	24
807	1695	291858-	3660285G	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	38	38	18
804	1703	291855-	3660285D	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	39	39	24
806	1705	291857-	3660285F	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS		30	30	15
802	1711	291853-	3660285B	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	34	34	19
801	1715	291852-	3660285A	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS			34	16
145	1721	52792-MH	52792	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WSD		Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling	38	38	23
746	1749	276339-	3624266Н	Owner	Well Constructed	AURORA CITY OF	35	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling		11	6

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
	,					2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2					2222		g=	g- vp
115	1762	276375-	0047606R	Owner	Well Constructed	AURORA CITY OF	26	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	26	19	9
				_										_
113	1772	276373-	0047606P	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	23	15	5
111	1774	276362-	0047606E	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	46	38	28
114	1777	276374-	0047606Q	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	26	19	9
212	1787	108742-	106239	Owner	Well Constructed	THOMPSON, LOGAN R.	. 26	Well (Application/Permit)	Residential	DAWSON	Domestic	505	505	405
						,		/ 11						
4	1793	129785-	8319	Owner	Well Constructed	BLAIR, DAVID	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	460	430	330
100	1794	46672-MH	46672	Owner	Well Constructed	AURORA CITY OF	26	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	24	14
100	1794	400/2-MH	40072	Owner	wen Constructed			wen (Application/Permit)		AQUIFERS	Montoring/Sampling	31	24	14
146	1798	52793-МН	52793	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WSD	11	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling	20	20	10
248	1823	131345-	235418	Owner	Well Constructed	COOK, JACK	26	Well (Application/Permit)	Residential	DAWSON	Domestic	480	480	440
766	1825	279154-	3634514C	Owner	Well Constructed	AURORA CITY OF	26	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	26	23	13
						EAST CHERRY CREEK VALLEY WATER &		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		LOWER				
663	1831	59422-F	507052	Owner	Well Constructed	SAN	2	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1630		
808	1836	291669-	3660478	Owner	Well Constructed	EDIGER, CLAY	26	Well (Application/Permit)	Residential	DENVER	Domestic	480	480	400
000	1030	271007-	3000476	Owner	wen constructed	,	20	wen (Application/Termit)	Residential	DENVER	Domestic	400	400	400
193	1854	97709-	90027	Owner	Well Constructed	WHALEN PETER & RUTH	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	415	415	245
						EAST CHERRY CREEK			Monitoring Hole (Notice of					
147	1874	52795-MH	52795	Owner	Well Constructed	VALLEY WSD	2	Well (Application/Permit)	Intent)	DAWSON	Monitoring/Sampling	45	45	25
										ALL UNNAMED				
968	1879	79792-	9007471	Owner	Well Constructed	HEINTZ, F E	11	Well (Construction Report)	Residential	AQUIFERS	Domestic			
754	1925	277677-	3629584I	Owner	Well Constructed	AURORA CITY OF	24	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	16	8	3

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
97	1932	46579-MH	46579	Owner	Well Constructed	AURORA CITY OF	24	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	19	19	14
50	1936	41782-MH	41782	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	22
116	1948	276377-	0047606T	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	31	26	21
764	1950	279152-	3634514A	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	14	4
765	1966	279153-	3634514B	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	15	5
755	1967	277678-	3629584J	Owner	Well Constructed	AURORA CITY OF	24	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	21	16	11
117	2027	276378-	0047606U	Owner	Well Constructed	AURORA CITY OF	19	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Samplin	31	23	18
873	2046	13203-F	9006038	Owner	Well Constructed	BEILHARTZ LUCILLE M & WILLIAM E	18	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	22	22	12
784	2056	284096-	3647360	Owner	Well Constructed	GARCIA SERGIO & OLGA	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1100	1100	926
658	2059	244862-	496440	Owner	Well Constructed	DMYTRYK PETER & KAEKO O	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1000	1000	920
660	2070	55457A	504336	Owner	Well Constructed	WEBBER, SHAWN	18	Well (Application/Permit)	Residential	DENVER	Domestic	880	880	795
933	2135	51343-	9007097	Owner	Well Constructed	WELTER ADRIAN D & J KAREN	18	Well (Application/Permit)	Residential	DENVER	Domestic			
740	2138	276332-	3624266A	Owner	Well Constructed	AURORA CITY OF	18	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	15	5
789	2140	287615-	3653757A	Owner	Well Constructed	FREUND, LINDA J	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock			
662	2141	249188-	505897	Owner	Well Constructed	YEE, KINNEY	18	Well (Application/Permit)	Residential	DENVER	Household use only	480	480	360
964	2144	76321-	9007423	Owner	Well Constructed	HIGGINS W JACQUE	18	Well (Application/Permit)	Residential	DENVER	Domestic			

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
778	2202	283005-	3644688E	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	40	40	35
779	2222	283006-	3644688F	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling			
742	2285	276334-	3624266C	Owner	Well Constructed	AURORA CITY OF	30	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	36	27	17
229	2295	117733-	209970	Owner	Well Constructed	WEILAND ELIZABETH ANN	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic, Stock	1080	1080	820
197	2323	98976-	91837	Owner	Well Constructed	JONES, NORMAN L	7	Well (Application/Permit)	Residential	DENVER	Domestic	634	634	234
218	2338	110844-	109772	Owner	Well Constructed	PATE, R W	7	Well (Application/Permit)	Residential	DENVER	Domestic			
796	2367	289274-	3656821	Owner	Well Constructed	JONES ARTHUR AND DIANE	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1100	110	930
213	2368	109090-	106550	Owner	Well Constructed	JONES, A L	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic			
810	2369	293059-	3662327	Owner	Well Constructed	ADUAN, NORALDINE	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1030	1020	900
767	2384	279916-	3637606	Owner	Well Constructed	JETTER, JUDITH A	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1060	915
112	2390	276371-	0047606N	Owner	Well Constructed	AURORA CITY OF	19	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	26	19	14
49	2399	99307A	0040796A	Owner	Well Constructed	POOR, DONALD	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1003	1003	820
293	2404	141969-	259082	Owner	Well Constructed	WALKER, VICTOR	7	Well (Application/Permit)	Residential	DENVER	Domestic	700	680	500
741	2414	276333-	3624266B	Owner	Well Constructed	AURORA CITY OF	7	Well (Application/Permit)	Monitoring/Observation	ALLUVIAL	Monitoring/Sampling	21	12	7
268	2431	136118-	245731	Owner	Well Constructed	ANDERSON, ALBERT L.	7	Well (Construction Report)	Residential	DENVER	Domestic	650	650	590
43	2453	40582-MH	40582	Owner	Well Constructed	WASTE, MANAGEMENT	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	32	23	13
41	2471	40580-MH	40580	Owner	Well Constructed	WASTE, MANAGEMENT	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	20	20	10

												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
972	2519	83240-	9007519	Owner	Well Constructed	SMITH MARVIN E & BARBARA F	29	Well (Application/Permit)	Residential	DENVER	Domestic	707	707	476
976	2540	85519-	9007563	Owner	Well Constructed	SMITH, PAUL H	20	Well (Application/Permit)	Residential	DENVER	Domestic	705		
231	2567	120499-	215107	Owner	Well Constructed	SMITH, E G	28	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	640	640	400
768	2578	281421-	3637674A	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	24	14
770	2579	281423-	3637674C	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	35	34	24
771	2583	281424-	3637674D	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	24	14
769	2598	281422-	3637674B	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	24	14
791	2616	287561-	3654042A	Owner	Well Constructed	AURORA CITY OF	15	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	156	146	136
792	2630	287562-	3654042B	Owner	Well Constructed	AURORA CITY OF	14	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	98	88	78
793	2631	287563-	3654042C	Owner	Well Constructed	AURORA CITY OF	14	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	36	33	23
1	2680	102873-	3789	Owner	Well Constructed	ZERFOSS, JESSEY S.	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	280	280	240
2	2681	102873-	3789	Owner	Well Constructed	BEER ZERFOSS, ASHLEY	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	280	280	240
3	2682	128814-	8199	Owner	Well Constructed	BANKENSTEIN ROBERT & SHARON	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic, Stock	600	600	440
5	2684	133281-	9126	Owner	Well Constructed	STOPA, HILDA A	22	Well (Application/Permit)	Residential	DAWSON	Domestic	380	380	300
6	2685	132837-	9127	Owner	Well Constructed	BRIDGEMAN DAVID W /DEBRA E COOK	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	398	400	260
7	2686	141363-	10683	Owner	Well Constructed	HULTS, CLARENCE	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1100	1100	970
8	2687	141967-	10732	Owner	Well Constructed	CONNER WARREN & RAMONA	7	Well (Application/Permit)	Residential	DENVER	Domestic	932	932	800

APPENDIX C-7 SUMMARY OF PERMITTED WATER WELLS LOCATED WITHIN FIVE MILES OF THE SITE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STA LOWRY LANDFILL SUPERFUND SITE

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
9	2688	119294-	13354	Owner	Well Constructed	SUTTON, DONALD O	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1160		
10	2689	89425-VE	15363	Owner	Well Constructed	GLENN, MIKE	27	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	320	320	280
11	2690	15619-MH	0015619A	Owner	Well Constructed	MDC LAND CORP	22	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling			
12	2691	90038-VE	15810	Owner	Well Constructed	CUNNINGHAM, GEORGE	26	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	337	337	277
13	2692	104061-	17157	Owner	Well Constructed	THACKER, ELBERT	12	Well (Application/Permit)	Residential	DENVER	Domestic	220	220	180
14	2693	178112-	0022500D	Owner	Well Constructed	STATE BOARD OF LAND COMMISSIONERS	2	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	80	80	20
15	2694	94122-VE	22741	Owner	Well Constructed	SMITH, WILBUR	17	Well (Application/Permit)	Unknown	UPPER ARAPAHOE	Domestic, Stock	1040	1040	920
16	2695	94230-VE	23087	Owner	Well Constructed	EVERHART, JERRY	22	Well (Application/Permit)	Unknown	DENVER	Domestic, Stock	325	325	285
17	2696	27025-MH	27025	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	6	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	51	51	41
18	2697	27027-MH	27027	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	7	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	49	48	39
19	2698	27028-MH	27028	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	6	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED	Monitoring/Sampling		58	39
20	2699	27029-MH	27029	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	6	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	53	53	33
21	2700	27030-MH	27030	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	7	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED	Monitoring/Sampling		60	30
22	2700	27030-WH	27031	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVICES	6	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED	Monitoring/Sampling		67	47
23	2701	28319-MH	28319	Owner	Well Constructed	CO DEPT MILITARY AFFAIRS	15	Well (Application/Permit) Well (Application/Permit)	Monitoring Hole (Notice of	ALL UNNAMED	Monitoring/Sampling		57	47
							13		Unknown					
24	2703	96318-VE 96355-VE	28632 28854	Owner Owner	Well Constructed Well Constructed	WHITE, BARBARA MCCONVILLE, TOM	7	Well (Application/Permit) Well (Application/Permit)	Unknown	ARAPAHOE ALL UNNAMED AQUIFERS	Domestic Domestic	720 727	720 727	560

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
26	2705	96369-VE	28915	Owner	Well Constructed	LITTLESTONE, RICHARD	26	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	457	457	377
27	2706	29306-МН	29306	Owner	Well Constructed	AURORA CITY OF	8	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	20	10
28	2707	96520-VE	29640	Owner	Well Constructed	QUICK, ELEANORE	18	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Stock	350	350	220
29	2708	96519-VE	29641	Owner	Well Constructed	QUICK, ELANA	7	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	630	630	350
30	2709	97027-VE	29962	Owner	Well Constructed	ALPERT, LELAND	21	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	605	605	505
31	2710	97131-VE	30556	Owner	Well Constructed	ASCHENBRENNER, CRYSTAL M	26	Well (Application/Permit)	Unknown	ALL UNNAMED AQUIFERS	Domestic	420	420	300
32	2711	114231A	0031737A	Owner	Well Constructed	LACRUE, TRACI	7	Well (Application/Permit)	Residential	DENVER	Domestic	630	630	530
33	2712	211517-	0033595I	Owner	Well Constructed	COLO DEPT OF MILITARY AFFAIRS	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	60	58	48
34	2713	50392-F	0033889A	Owner	Well Constructed	STATE BOARD OF LAND COMMISSIONERS	33	Well (Construction Report)	General Purpose	ARAPAHOE	Municipal	1520	1500	990
35	2714	35788-MH	35788	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN	12	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	LARAMIE FOX HILLS	Monitoring/Sampling	216	2110	1945
36	2715	38001-MH	38001	Owner	Well Constructed	WASTE MANAGEMENT OF CO	31	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	25	9
37	2716	54367-F	0038715B	Owner	Well Constructed	STATE BOARD OF LAND COMMISSIONERS	14	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1628	1548	1055
38	2717	40128-MH	40128	Owner	Well Constructed	CONOCO INC	3	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	15	5
39	2718	40578-MH	40578	Owner	Well Constructed	WASTE, MANAGEMENT	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	44	44	24
40	2719	40579-MH	40579	Owner	Well Constructed	WASTE, MANAGEMENT	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	17	7
42	2721	40581-MH	40581	Owner	Well Constructed	WASTE, MANAGEMENT	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	53	52	32
44	2723	40657-MH	40657	Owner	Well Constructed	DENVER CITY & COUNTY OF	32	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	58	56	46

ove	a/	D. MAY I	D		P. Maria	G 4 N	G .:		D. Maria				PerforatedCasin	
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
45	2724	40699-MH	40699	Owner	Well Constructed	DENVER CITY & COUNTY OF	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	36	35	20
46	2725	40700-MH	40700	Owner	Well Constructed	DENVER CITY & COUNTY OF	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	80	79	39
47	2726	40701-MH	40701	Owner	Well Constructed	DENVER CITY & COUNTY OF	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	35	35	15
						DENVER CITY &			Monitoring Hole (Notice of	ALL UNNAMED				
48	2727	40702-MH	40702	Owner	Well Constructed	COUNTY OF	5	Well (Application/Permit)	Intent)	AQUIFERS	Monitoring/Sampling	25	25	10
51	2730	17500-F	0042174A	Owner	Well Constructed	SMOKY HILLS VENTURE CO	23	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2410	2320	2032
52	2731	17499-F	0042174B	Owner	Well Constructed	SMOKY HILLS VENTURE CO	16	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2286	2286	1969
53	2732	17498-F	0042174C	Owner	Well Constructed	SMOKY HILLS VENTURE CO	16	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2331	2331	2007
54	2733	17494-F	0042174G	Owner	Well Constructed	SMOKY HILLS VENTURE CO	14	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2291	2231	1994
55	2734	17485-F	0042174N	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WTR & SAN	22	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2326	2296	1967
57	2736	42219-MH	42219	Owner	Well Constructed	US GEOLOGICAL SURVEY	2	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	23	13
58	2737	42220-MH	42220	Owner	Well Constructed	US GEOLOGICAL SURVEY	10	Well (Application/Permit)	Monitoring Hole (Notice of Intent)				28	18
59	2738	42222-MH	42222	Owner	Well Constructed	US GEOLOGICAL SURVEY	14	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	23	13
60	2739	42223-MH	42223	Owner	Well Constructed	US GEOLOGICAL SURVEY	15	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	42	41	32
65	2744	42562-MH	42562	Owner	Well Constructed	US GEOLOGICAL SURVEY	3	Well (Application/Permit)	Monitoring Hole (Notice of Intent)				43	33
68	2747	44732-MH	44732	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling		30	
69	2748	44733-MH	0044733A	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	DAWSON	Monitoring/Sampling		40	30
70	2749	44739-MH	0044739A	Owner	Well Constructed	7 ELEVEN	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)				40	10

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
71	2750	45132-MH	45132	Owner	Well Constructed	7 ELEVEN INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	10
72	2751	45288-MH	45288	Owner	Well Constructed	7 ELEVEN INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	12	12	4
73	2752	45667-MH	0045667A	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	50	50	30
74	2753	45669-MH	0045669A	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	35	30	25
75	2754	45670-MH	45670	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	59	59	49
76	2755	45997-MH	45997	Owner	Well Constructed	ARAPAHOE COUNTY	2	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	31	21
77	2756	45998-MH	45998	Owner	Well Constructed	ARAPAHOE COUNTY	2	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	20
78	2757	45999-MH	45999	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	20	10
79	2758	46388-MH	46388	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	20
80	2759	46389-MH	46389	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	15	15	5
81	2760	46390-MH	46390	Owner	Well Constructed	AURORA CITY OF	22	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	15	15	5
84	2763	46396-MH	46396	Owner	Well Constructed	AURORA CITY OF	5	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	16	16	6
85	2764	46408-MH	46408	Owner	Well Constructed	AURORA CITY OF	8	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	16	16	6
86	2765	46409-MH	46409	Owner	Well Constructed	AURORA CITY OF	3	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	15	15	5
87	2766	46410-MH	46410	Owner	Well Constructed	AURORA CITY OF	30	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	AQUIFERS	Monitoring/Sampling	27	27	17
88	2767	46411-MH	46411	Owner	Well Constructed	AURORA CITY OF	7	Well (Application/Permit)	Monitoring Hole (Notice of Intent) Monitoring Hole (Notice of	AQUIFERS	Monitoring/Sampling	12	12	7
89	2768	46412-MH	46412	Owner	Well Constructed	AURORA CITY OF	18	Well (Application/Permit)	Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	15	15	8

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
90	2769	46414-MH	46414	Owner	Well Constructed	AURORA CITY OF	19	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	19	14
91	2770	46481-MH	46481	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	27	17
93	2772	46575-MH	46575	Owner	Well Constructed	AURORA CITY OF	26	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	19	19	9
94	2773	46576-MH	46576	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	19	9
95	2774	46577-MH	46577	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	46	38	28
96	2775	46578-MH	46578	Owner	Well Constructed	AURORA CITY OF	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	20	10
98	2777	46581-MH	46581	Owner	Well Constructed	AURORA CITY OF	23	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	15	5
99	2778	46665-MH	46665	Owner	Well Constructed	AURORA CITY OF	28	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	16	13	8
101	2780	46980-MH	46980	Owner	Well Constructed	AURORA CITY OF	3	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	8
102	2781	46981-MH	46981	Owner	Well Constructed	AURORA CITY OF	28	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	26	16
103	2782	46983-MH	46983	Owner	Well Constructed	AURORA CITY OF	27	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	27	27	17
104	2783	47002-MH	47002	Owner	Well Constructed	AURORA CITY OF	24	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	16	8	3
105	2784	47003-MH	0047003A	Owner	Well Constructed	AURORA CITY OF	24	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	21	16	11
106	2785	47315-MH	47315	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	26	21	11
107	2786	47366-MH	47366	Owner	Well Constructed	AURORA CITY OF	33	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	36	35	25
108	2787	47371-MH	47371	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	30	28	18

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
109	2788	47372-MH	47372	Owner	Well Constructed	AURORA CITY OF	27	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	26	21	11
110	2789	47374-MH	47374	Owner	Well Constructed	AURORA CITY OF	32	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	13	13	3
119	2798	48012-MH	48012	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	21	14	4
120	2799	48013-MH	0048013A	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	21	15	5
121	2800	48014-MH	0048014A	Owner	Well Constructed	AURORA CITY OF	26	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	26	23	13
122	2801	282758-	0049083T	Owner	Well Constructed	STATE BOARD OF LAND COMMISSIONERS	11	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	32	31	26
123	2802	49537-MH	49537	Owner	Well Constructed	MATRIX GROUP INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	20	10
124	2803	51330-MH	51330	Owner	Well Constructed	UNITED WATER & SANITATION DISTRICT	14	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	65	65	55
125	2804	51331-MH	51331	Owner	Well Constructed	UNITED WATER & SANITATION DISTRICT	14	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	67	67	57
126	2805	51675-MH	51675	Owner	Well Constructed	7-ELEVEN INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	15
127	2806	51713-MH	51713	Owner	Well Constructed	BRADLEY PETROLUEM INC	10	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling	22		
128	2807	293774-	0052301R	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	38	38	13
129	2808	293775-	0052301S	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	34	34	9
130	2809	293776-	0052301T	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	34	34	9
131	2810	293777-	0052301U	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	39	39	14
132	2811	293778-	0052301V	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	65	65	25

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
133	2812	293779-	0052301W	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	59	59	25
134	2813	293780-	0052301X	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	33	33	13
135	2814	293781-	0052301Y	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	16	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	39	39	9
136	2815	293782-	0052301Z	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	16	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	35	35	10
137	2816	293784-	0052302A	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	34	34	9
138	2817	293785-	0052302B	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	31	6
139	2818	293786-	0052302C	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	70	70	35
140	2819	293787-	0052302D	Owner	Well Constructed	BUCKLEY AFB SCOTT WILSON	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	60	60	45
148	2827	53131-MH	53131	Owner	Well Constructed	ARAPAHOE COUNTY WATER & WASTEWATER AUTH	26	Well (Application/Permit)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling		19	9
149	2828	53132-MH	53132	Owner	Well Constructed	ARAPAHOE COUNTY WATER & WASTEWATER AUTH	27	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	14	14	4
150	2829	53139-MH	53139	Owner	Well Constructed	ACWWA	26	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling		22	12
151	2830	53591-MH	53591	Owner	Well Constructed	7 ELEVEN INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED AQUIFERS	Monitoring/Sampling		30	15
152	2831	54350-MH	54350	Owner	Well Constructed	AURORA CITY OF	14	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED			154	139
153	2832	54351-MH	54351	Owner	Well Constructed	AURORA CITY OF	22	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED	Monitoring/Sampling		19	9
154	2833	55224-MH	55224	Owner	Well Constructed	7-ELEVEN INC	29	Well (Application/Permit)	Monitoring Hole (Notice of Intent)	ALL UNNAMED	Monitoring/Sampling		31	18
155	2834	305253-	0056645G	Owner	Well Constructed	BUCKLEY, AFB	14	Well (Construction Report)		ALL UNNAMED AQUIFERS				

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
156	2835	305254-	0056645Н	Owner	Well Constructed	BUCKLEY, AFB	15	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	19		
157	2836	305255-	00566451	Owner	Well Constructed	BUCKLEY, AFB	15	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	40		
158	2837	305256-	0056645J	Owner	Well Constructed	BUCKLEY, AFB	15	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20		
159	2838	305258-	0056645L	Owner	Well Constructed	BUCKLEY, AFB	23	Well (Construction Report)		ALL UNNAMED AQUIFERS	Monitoring/Sampling	55		
160	2839	57531-MH	57531	Owner	Well Constructed	CITY OF AURORA	4	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	50		
161	2840	58556-MH	58556	Agent	Well Constructed	AURORA WATER	25	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	20		
162	2841	58556-MH	58556	Agent	Well Constructed	BRIERLEY ASSOCIATES (BAILEY, SEAN)	25	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	20		
163	2842	58559-MH	58559	Agent	Well Constructed	AURORA WATER BRIERLEY	24	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	40		
164	2843	58559-MH	58559	Agent	Well Constructed	ASSOCIATES (BAILEY, SEAN)	24	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	40		
165	2844	59071-MH	59071	Owner	Well Constructed	7-ELEVEN INC (STORE #19075)	29	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	22		
166	2845	59485-MH	59485	Owner	Well Constructed	ARAPAHOE PARKS AND RECREATION DISTRICT	1	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	22		
167	2846	59766-MH	59766	Owner	Well Constructed	SOUTH METRO WATER SUPPLY AUTHORITY	9	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	30		
168	2847	60005-MH	60005	Owner	Well Constructed	SOUTH METRO WATER SUPPLY AUTHORITY	18	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	30		
169	2848	60012-MH	60012	Owner	Well Constructed	SOUTH METRO WATER SUPPLY AUTHORITY	18	Well (Construction Report)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	30		
170	2849	60238-MH	60238	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	47		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
OID	Мар ІБ	T CT III CT VAIII DCT	песере	rissuc Type	1 CI IIII Status	Contactivanic	Section	LocationType	Termicategory	aquirei i_name	0301	Бери	gDottom	grop
									Monitoring Hole (Notice of					
171	2850	60243-MH	60243	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Intent)		Monitoring/Sampling	30		
172	2851	60765-MH	60765	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring Hole (Notice of Intent)	DENVER	Monitoring/Sampling	100		
173	2852	61137-MH	61137	Owner	Well Constructed	CITY OF AURORA	16	Well (Construction Report)	Monitoring Hole (Notice of Intent)	QUATERNARY ALLUVIUM	Monitoring/Sampling	37		
								1 /	Monitoring Hole (Notice of		2 1 2			
174	2853	61417-MH	61417	Owner	Well Constructed	CITY OF AURORA	8	Well (Construction Report)			Monitoring/Sampling	20		
175	2854	62220-MH	62220	Owner	Well Constructed	SERENITY RIDGE HOA	29	Well (Construction Report)	Monitoring Hole (Notice of Intent)		Monitoring/Sampling	6		
175	2034	02220-ivii1	02220	Owner	wen constructed	SERENTT RIDGETTOA	2)	wen (Construction Report)	Monitoring Hole (Notice of		Womoning/Samping	U		
176	2855	62895-MH	62895	Owner	Well Constructed	CITY OF AURORA	9	Well (Construction Report)		ALLUVIAL	Monitoring/Sampling	35		
177	2056	(2100) 411	(2100		William	CIVITAS RESOURCES	1.7	W.H.G	Monitoring Hole (Notice of		M :	1056	1700	(00
177	2856	63108-MH	63108	Owner	Well Constructed	INC	17	Well (Construction Report)	ŕ	HILLS	Monitoring/Sampling	1856	1780	680
178	2857	63313-MH	63313	Owner	Well Constructed	SMITH, DEVIN	3	Well (Construction Report)	Monitoring Hole (Notice of Intent)	ALLUVIAL	Monitoring/Sampling	25		
						CHRISTIANSON LES &								
179	2858	90942-	80556	Owner	Well Constructed	LINDA	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
180	2859	91710-	81740	Owner	Well Constructed	ROBERTS, J	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	217	207	177
										LOWER				
181	2860	91750-	81972	Owner	Well Constructed	RODAN, J	27	Well (Application/Permit)	Residential	DAWSON	Domestic	220	220	200
182	2861	92479-	82563	Owner	Well Constructed	NOSEWICZ LEONARD A & PATRICIA V	26	Well (Application/Permit)	Residential	DENVER	Domestic			
102		2-112						(
183	2862	93815-	84383	Owner	Well Constructed	PIERCE DONALD JR	22	Well (Application/Permit)	Residential	DENVER	Domestic	250	250	220
104	20/2	04772	0.6174	0	W-II C- + + 1	STAUCH THOMAS &	26	W-11 (A1: / /D /)	Parit (1)	LOWER	Daw C			
184	2863	94773-	86174	Owner	Well Constructed	ANITA	26	Well (Application/Permit)	Residential	DAWSON	Domestic			
185	2864	95722-	87223	Owner	Well Constructed	MAHR, CLAIR	9	Well (Application/Permit)	Residential	DENVER	Domestic			

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
186	2865	96648-	0088271B	Owner	Well Constructed	HENDERSON ROGER A & VONICA F	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	204	204	154
187	2866	97044-	0088648A	Owner	Well Constructed	SHEILA ELLERBRUCH ELDON S	26	Well (Application/Permit)	Residential	DENVER	Domestic			
189	2868	101936-	89481	Owner	Well Constructed	BASHOR, THOMAS C	26	Well (Application/Permit)	Residential	DENVER	Domestic	344	344	304
190	2869	97706-	90024	Owner	Well Constructed	JOHNSON MAUREEN ANN	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	320	320	240
191	2870	97707-	90025	Owner	Well Constructed	BUCKLEY, NICHOLAS M.	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	273	273	193
192	2871	97707-	90025	Owner	Well Constructed	BUCKLEY, JENNIFER G.	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	273	273	193
194	2873	98162-	90789	Owner	Well Constructed	SMITH, GARY E	22	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	415	415	255
195	2874	98450-	91085	Owner	Well Constructed	EDLING KEVIN & STACY	22	Well (Application/Permit)	Residential	DAWSON	Domestic	295	295	255
196	2875	98635-	91736	Owner	Well Constructed	WHEELER, C R	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	500	500	400
198	2877	99114-	0092091C	Owner	Well Constructed	STEPHENS, ARTHUR	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	324	324	264
199	2878	100827-	92815	Owner	Well Constructed	FREUND MICHAEL R & TAMARA STOFFEL	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	264	264	204
200	2879	101686-	95768	Owner	Well Constructed	COWGILL COURTNEY & JOHN EDWARD CASE	22	Well (Application/Permit)	Residential	DENVER	Domestic	310	310	270
201	2880	102288-	0096950B	Owner	Well Constructed	HARTMAN DAVID & ROBIN	26	Well (Application/Permit)	Residential	DENVER	Domestic	354	354	294
202	2881	102290-	0096950D	Owner	Well Constructed	HILINE BLDR IN	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	300	300	260
203	2882	101542-	0097056B	Owner	Well Constructed	SEYBOLD JEFFREY G & MARISA	7	Well (Application/Permit)	Residential	DENVER	Domestic	690	650	550
204	2883	103727-	99324	Owner	Well Constructed	CHANG MAN HO	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock		324	180
205	2884	103739-	99384	Owner	Well Constructed	RAPP WILLIAM M & CAROLYN	7	Well (Application/Permit)	Residential	DENVER	Domestic	729	729	629

												CompletedWell		PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
207	2886	104869-	101938	Owner	Well Constructed	WOLTHUIS, REBECCA F.	22	Well (Application/Permit)	Residential	DENVER	Household use only	420	420	280
208	2887	105877-	102425	Owner	Well Constructed	OLIVA, MICHAEL	22	Well (Application/Permit)	Residential	DENVER	Domestic	334	334	214
209	2888	105701-	102909	Owner	Well Constructed	ADAMS, MELVIN D	7	Well (Application/Permit)	Residential	DENVER	Domestic	750	750	630
210	2889	106749-	103482	Owner	Well Constructed	BULLOCK, MICHAEL	22	Well (Application/Permit)	Residential	DENVER	Domestic	200	200	150
211	2890	107417-	104270	Owner	Well Constructed	VINNES, WILLIAM B	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	240	240	180
214	2893	109074-	107180	Owner	Well Constructed	BONO, RICHARD	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	480	480	380
215	2894	109363-	107498	Owner	Well Constructed	SCHAUMBURG, ARTHUR	22	Well (Construction Report)	Residential	LOWER DAWSON	Domestic	354	354	314
216	2895	110342-	108703	Owner	Well Constructed	SMITH, C E	22	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock			
217	2896	110150-	108741	Owner	Well Constructed	FESTER, M	25	Well (Application/Permit)	Residential	DENVER	Domestic	564		
219	2898	113710-	202753	Owner	Well Constructed	GUERRERO, ERIK	27	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic	373	373	300
220	2899	113710-	202753	Owner	Well Constructed	GUERRERO, TANISHA M.	27	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic	373	373	300
221	2900	115848-	206531	Owner	Well Constructed	MCKISSICK, KEITH	7	Well (Construction Report)	Residential	DENVER	Domestic	670	670	630
222	2901	115848-	206531	Owner	Well Constructed	MCKISSICK, JACKIE	7	Well (Construction Report)	Residential	DENVER	Domestic	670	670	630
223	2902	115848-	206531	Owner	Well Constructed	MCKISSICK, BRYAN	7	Well (Construction Report)	Residential	DENVER	Domestic	670	670	630
224	2903	116021-	206923	Owner	Well Constructed	MOORE, J M	22	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	370		
225	2904	116831-	208548	Owner	Well Constructed	WEBSTER RONALD P & CARLA D WILLIAMS	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	350	350	250
226	2905	116832-	208548	Owner	Well Constructed	VIGIL, RAYMOND B	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	402	402	302

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
227	2906	23891-F	0209430A	Owner	Well Constructed	E CHERRY CRK V	13	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	462	400	222
228	2907	23888-F	0209430B	Owner	Well Constructed	E CHERRY CRK V	13	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	1100	970	711
230	2909	117661-	210084	Owner	Well Constructed	ESTATE OF RALPH WILBUR NELSON JR. (NELSON, DENNIS)	7	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	755	755	700
232	2911	121288-	217459	Owner	Well Constructed	ADAMS DANNY R & PATRICIA M	18	Well (Application/Permit)	Residential	DENVER	Domestic	520	460	350
233	2912	121687-	217909	Owner	Well Constructed	RAINS, D E	29	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	640	640	400
236	2915	123645-	221488	Owner	Well Constructed	DOBLER, B	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	342	342	182
237	2916	124300-	221908	Owner	Well Constructed	MACDONALD, D D	24	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	460		
238	2917	128343-	227577	Owner	Well Constructed	DENNY ENTERPEISES INC	26	Well (Application/Permit)	Residential	DENVER	Domestic	490	490	450
239	2918	127399-	228783	Owner	Well Constructed	HEDDEN JERRY J JR & LIZA I	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	300	300	200
240	2919	128207-	229878	Owner	Well Constructed	PARADIS, GREGORY J.	22	Well (Application/Permit)	Residential	DENVER	Domestic	320	320	220
241	2920	128766-	230537	Owner	Well Constructed	ALEXANDER, J	22	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	320
242	2921	128511A	231394	Owner	Well Constructed	MCDANIEL, ELVIN	11	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic	560	560	340
244	2923	130378-	234600	Owner	Well Constructed	SUMMERS, C F	24	Well (Construction Report)	Residential	DENVER	Household use only	403	403	303
245	2924	28491-F	0234728A	Owner	Well Constructed	ALPERT CORP	3	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1600	1516	1025
246	2925	27523-F	0234728C	Owner	Well Constructed	EAST CHERRY CREEK VALLEY W & S DIST	3	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2052	2022	1632
247	2926	29939-F	0234728D	Owner	Well Constructed	ALPERT CORP	3	Well (Application/Permit)	General Purpose	DENVER	Municipal	939	914	556
249	2928	131497-	235428	Owner	Well Constructed	MARTIN, JOHN L	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	820	820	620

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Completed Well Depth	PerforatedCasin gBottom	PerforatedCasin gTop
250	2929	131538-	236049	Owner	Well Constructed	GUERIN STEPHEN A & BRIDGET K DUGAN	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	440	440	340
251	2930	131304-	236277	Owner	Well Constructed	MOORE REX & JULIE	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	1100	1100	900
252	2931	131757-	236447	Owner	Well Constructed	HARTER, ART	26	Well (Application/Permit)	Residential	DAWSON	Domestic	298	298	160
253	2932	131775-	236725	Owner	Well Constructed	BYRNE, JOSEPH F.	26	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	360
254	2933	132966-	238242	Owner	Well Constructed	VERNON, P B	27	Well (Application/Permit)	Residential	DENVER	Domestic	417	417	337
255	2934	97627A	238648	Owner	Well Constructed	SHIRACK MICHAEL D & DIANE J	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	383	383	283
256	2935	133261-	239483	Owner	Well Constructed	BLAIR, DAVID	26	Well (Application/Permit)	Residential	DAWSON	Domestic	523	523	423
257	2936	133947-	241184	Owner	Well Constructed	SCHOECK WILLIAM W & CHRISTINE	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	300	300	260
258	2937	27142-F	241351	Owner	Well Constructed	MELODY HOMES	10	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1610	1090	1530
259	2938	138283-	242849	Owner	Well Constructed	REID, LEROY	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	720	720	540
260	2939	134905-	243938	Owner	Well Constructed	ORILEY PATRICK M & GOULDMAN BEVERLY S	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	810	810	650
261	2940	135429-	244575	Owner	Well Constructed	RONNE, D W	18	Well (Construction Report)	Residential	DENVER	Domestic	500	500	280
262	2941	135946-	245266	Owner	Well Constructed	CHAMPLIN, DAVID	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	320	320	280
263	2942	135946-	245266	Owner	Well Constructed	CHAMPLIN, ELIZABETH A.	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	320	320	280
264	2943	136116-	245532	Owner	Well Constructed	STONE BRADLEY & KAREN	27	Well (Application/Permit)	Residential	DENVER	Domestic	390	390	290
265	2944	28406-F	0245547A	Owner	Well Constructed	TRUSSELL, HUGH H	29	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Domestic	285		
266	2945	28406-F-R	0245547B	Owner	Well Constructed	TRUSSELL, HUGH H	29	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	358		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
267	2946	135522-	245603	Owner	Well Constructed	SAZERA, VINCE	26	Well (Application/Permit)	Residential	DAWSON	Domestic	300	300	270
		1000=2						(41)						_,,
270	2949	136411-	246089	Owner	Well Constructed	HODACK, JUDE T.	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	380	380	160
271	2950	136411-	246089	Owner	Well Constructed	HODACK, WENDI R.	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	380	380	160
272	2951	137505-	247761	Owner	Well Constructed	FLUGUM, JAMES I	24	Well (Application/Permit)	Residential	DENVER	Domestic	581	582	422
273	2952	139517-	253199	Owner	Well Constructed	BOTVINICK, JORI L.	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	400	400	200
274	2953	139517-	253199	Owner	Well Constructed	TRAHAN, ROBERT L.	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	400	400	200
275	2954	139215-	253307	Owner	Well Constructed	MASIH EDWARD J & AMRITPAL	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1000	1000	820
276	2955	28213-M	0253335E	Owner	Well Constructed	DENVER CITY & COUNTY OF	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	85	80	60
277	2956	28209-M	0253335F	Owner	Well Constructed	DENVER CITY & COUNTY OF	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	180	160	140
278	2957	28207-M	0253335L	Owner	Well Constructed	DENVER CITY & CNTY OF	6	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling	120	115	95
279	2958	28199-M	0253335S	Owner	Well Constructed	DENVER CITY & COUNTY OF	6	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling	55	53	43
280	2959	28200-M	0253335T	Owner	Well Constructed	DENVER CITY & CNTY OF	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	60	58	48
281	2960	139216-	0253439A		Well Constructed	ISOM, ANDREW	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic Domestic	1040	1040	830
201	2900	139210-	0233437A	Owner	wen constructed	150W, ANDREW	- /	wen (Construction Report)	Residential	AKAFAHUE	Domestic	1040	1040	630
282	2961	139653-	253743	Owner	Well Constructed	ELDRED, RON	26	Well (Application/Permit)	Residential	DAWSON	Domestic	280	280	240
283	2962	139978-	254399	Owner	Well Constructed	LEARY, B	25	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	400	400	320
284	2963	139977-	254632	Owner	Well Constructed	WAHL, JOY	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	600	600	500
285	2964	140171-	255042	Owner	Well Constructed	ORRELAS, ALICIA	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1160	1160	900

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
286	2965	140291-	255761	Owner	Well Constructed	MASIH EDWARD J & AMRITPAL	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic, Stock	1000	1000	800
287	2966	140785-	256951	Owner	Well Constructed	CURRY, T	25	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	260	260	100
288	2967	140923-	257222	Owner	Well Constructed	PAPROSKI JOE & JANET	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1003	1003	875
289	2968	140924-	257488	Owner	Well Constructed	BATES, STEPHEN C	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	405	405	390
290	2969	141092-	257756	Owner	Well Constructed	WOOTERS, R	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	650	640	500
291	2970	141097-	257873	Owner	Well Constructed	REDDY, KAY A	26	Well (Application/Permit)	Residential	DAWSON	Domestic	281	281	201
292	2971	31259-F	0258188A	Owner	Well Constructed	ALPERT CORP	3	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2070	2052	1600
294	2973	29606-F	261260	Owner	Well Constructed	EAST CHERRY CREEK WATER & SAN DIST	13	Well (Application/Permit)	General Purpose	LARAMIE FOX HILLS	Municipal	2365		
295	2974	66892A	261328	Owner	Well Constructed	MARKER, EDWIN	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	620	620	500
296	2975	142865-	261689	Owner	Well Constructed	BONIS, TOM	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	240	240	180
297	2976	98635A	262144	Owner	Well Constructed	BRUSH, DEBORAH	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	700	700	460
298	2977	143868-	262249	Owner	Well Constructed	HURD, SUMNER K	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1030	1030	930
299	2978	144232-	263767	Owner	Well Constructed	KARAUS, MITCHELL	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	375	475	375
300	2979	144232-	263767	Owner	Well Constructed	WATSON, BRENDA	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	375	475	375
301	2980	144227-	263911	Owner	Well Constructed	DEHERRERA GUILLERMO A & ROSEMARY Y	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS		513	820	520
302	2981	30322-F	0263986B	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	DENVER	Municipal	1220	1150	373
303	2982	30322-F	0263986C	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	DENVER	Municipal	1235	1153	397

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
304	2983	30324-F	0263986D	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)		ADADAHOE	Municipal	1757	1686	1245
304	2983	30324-Г	0203980D	Owner	well Constructed	AURORA CITT OF	21	wen (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1/3/	1080	1243
305	2984	30325-F	0263986E	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1690	1660	1226
306	2985	30326-F	0263986F	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1739	1680	1239
									1	ALL UNNAMED	1			
307	2986	144683-	265179	Owner	Well Constructed	HANNEMAN, DUANE	7	Well (Application/Permit)	Residential	AQUIFERS	Household use only	800	800	500
308	2987	144797-	265420	Owner	Well Constructed	BROCK L/BOONE C	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	400	400	280
309	2988	145734-	265842	Owner	Well Constructed	FLEITH JR STEFAN	27	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	240	240	140
310	2989	145743-	268177	Owner	Well Constructed	SMITH, MALLORY	18	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	475	475	375
311	2990	30501-M	0268221A	Owner	Well Constructed	CHEMICAL WASTE MANAGEMENT	32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	116	16	76
312	2991	30500-M	0268221B	Owner	Well Constructed	CHEMICAL WASTE MANAGEMENT	32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling		123	103
313	2992	30499-M	0268221C		Well Constructed	CHEMICAL WASTE MANAGEMENT				DAWSON	Monitoring/Sampling		128	78
313	2992	30499-W	0208221C	Owner	well Constructed		32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	128	120	78
314	2993	30496-M	0268221F	Owner	Well Constructed	CHEMICAL WASTE MANAGEMENT	32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	20	22	17
315	2994	30493-M	02682211	Owner	Well Constructed	CHEMICAL WASTE MANAGEMENT	32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	25	25	20
316	2995	30492-M	0268221J	Owner	Well Constructed	CHEMICAL WASTE MANAGEMENT	32	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	52	52	47
							-			UPPER				
317	2996	146567-	269057	Owner	Well Constructed	ANDERSON E DINA	-7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1015		
318	2997	147380-	269769	Owner	Well Constructed	BENTZONI, TOM	26	Well (Application/Permit)	Residential	DENVER	Domestic	410	410	350
319	2998	146758-	270822	Owner	Well Constructed	WOLFF, CHARLES	26	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	620	620	520
320	2999	31171-M	0271774A	Owner	Well Constructed	CHEMICAL, WASTE	32	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling	69	69	64

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
				, T		DENVER CITY &		J.F.				- A	9	9 1
321	3000	31800-M	275993	Owner	Well Constructed	COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	35	35	30
322	3001	31809-M	02759931	Owner	Well Constructed	DENVER CITY AND COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	107	107	56
323	3002	31819-M	0275993S	Owner	Well Constructed	DENVER CITY AND COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	20	20	5
324	3003	31827-M	275994	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	100	100	90
325	3004	31829-M	0275994B	Owner	Well Constructed	DENVER CITY AND COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	201	201	196
326	3005	31830-M	0275994C	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	52	52	47
327	3006	31832-M	0275994E	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DENVER	Monitoring/Sampling	229	229	219
328	3007	31839-M	0275994L	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	83	83	68
329	3008	31843-M	0275994P	Owner	Well Constructed	DENVER CITY AND COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	132	132	122
330	3009	31845-M	0275994R	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling		115	105
331	3010	31851-M	0275994X	Owner	Well Constructed	DENVER CITY & COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	69	69	64
332	3011	31852-M	0275994Y	Owner	Well Constructed	DENVER CITY AND COUNTY	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	98	98	93
333	3012	148399A	0276096B	Owner	Well Constructed	GRIMM, ALBERT F	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	780	780	680
334	3013	148555-	276757	Owner	Well Constructed	BELTEZORE, LISA L.	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1028	920
335	3014	148555-	276757	Owner	Well Constructed	SHENGLE, CAROLINE A.	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1028	920
336	3015	149075-	276776	Owner	Well Constructed	LADO FRANCIS & RENEE	25	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	520	520	420
337	3016	32333-F	279391	Owner	Well Constructed	MONROE, HELEN	18	Well (Application/Permit)	General Purpose	UPPER ARAPAHOE	Domestic, Stock	1040	1038	920

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
OID	мар по	reimulambei	кесеірі	Associype	rermitstatus	Contactivame	Section	Location 1 ype	remitCategory	aquiter 1_name	Osei	Deptii	goottom	grop
338	3017	149921-	281269	Owner	Well Constructed	MC COWAN BRADFORD	18	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	500
								, ,,						
339	3018	150224-	282735	Owner	Well Constructed	GLAU, DEAN	22	Well (Application/Permit)	Residential	DENVER	Domestic	380	380	280
340	3019	150732-	285483	Owner	Well Constructed	LA FOE JAMES	22	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	340	340	290
341	3020	151120-	286755	Owner	Well Constructed	TOBEY, CAROL M	22	Well (Application/Permit)	Residential	DENVER	Domestic	370	370	160
342	3021	151476-	287364	Owner	Well Constructed	OLETA PROPERTIES, LLC (MUELLER, SUSAN P.)	26	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	400	400	300
3.2	3021	101170	207501		West designation		20	vi en (12ppneumen 1 enmi)	1100.000.000	ngen zne	D OM COM		.00	200
343	3022	151466-	288128	Owner	Well Constructed	CHRISTENSEN DAVID & JUDITH	26	Well (Construction Report)	Residential	DENVER	Domestic	560	560	480
344	3023	151885-	289947	Owner	Well Constructed	PEMBROOK, JAMES	18	Well (Application/Permit)	Residential	DENVER	Domestic	560	560	260
345	3024	141967A	291265	Owner	Well Constructed	CONNER, WARREN	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	900	900	605
										ALL UNNAMED				
346	3025	23609-F	0291544A	Owner	Well Constructed	PARK, FUNDING	23	Well (Application/Permit)	General Purpose	AQUIFERS	Domestic, Stock	992	965	606
347	3026	23610-F	0291544B	Owner	Well Constructed	PARK, FUNDING	23	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Domestic, Stock	1053	1030	600
348	3027	23611-F	0291544C	Owner	Well Constructed	PARK, FUNDING	24	Well (Application/Permit)	General Purpose	DENVER	Domestic, Stock	957	950	698
349	3028	23612-F	0291544D	Owner	Well Constructed	PARK, FUNDING	24	Well (Application/Permit)	General Purpose	DENVER	Domestic, Stock	1040	990	807
350	3029	34248-F	293107	Owner	Well Constructed	EAST CHERRY CREEK VALLEY	10	Well (Application/Permit)	General Purpose	LARAMIE FOX HILLS	Municipal	2121	2061	1914
330	3023	J7240-I	2/310/	OWIN	Well Collstructed		10	men (Application/1 crinit)	General 1 urpose	HILLES	wumcipai	2121	2001	1714
351	3030	153261-	294978	Owner	Well Constructed	HOLLADAY, NICHOLAS L.	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	590	510
						HOLLADAY, TIFFANY								
352	3031	153261-	294978	Owner	Well Constructed	L.	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	590	510
353	3032	153427-	296666	Owner	Well Constructed	LAMBERT, JOEY	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	441	480	220
333	3032	13342/-	290000	Owner	wen constructed	LAMBERT, JOET	- 1	wen (Application/Fernit)	Residential		Household use offly	741	700	220
354	3033	23889-F	0297564A	Owner	Well Constructed	SMOKY HILL LAND CO	14	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	860	810	679

	,											CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
355	3034	23886-F	0297564C	Owner	Well Constructed	SMOKY HILL LAND CO	13	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	1012	974	843
355	3031	230001	02)/3010	o wher	Well Collisiration	SMOKT THEE EARLY CO	13	wen (rippieution)	General Larpose		Wallerpar	1012	371	0.13
356	3035	23885-F	0297564D	Owner	Well Constructed	SMOKY HILL LAND CO	14	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	940	870	738
257	2026	22004 5	00075646		W. H. G.	GMONATHIN I TOND GO	.,	W. H. C. F. C. D. C.	G IN	ALL UNNAMED		465	420	261
357	3036	23894-F	0297564G	Owner	Well Constructed	SMOKY HILL LAND CO	14	Well (Application/Permit)	General Purpose	AQUIFERS	Municipal	465	430	361
358	3037	23892-F	0297564I	Owner	Well Constructed	SMOKY HILL LAND CO	13	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	272	240	200
359	3038	23895-F	0297564J	Owner	Well Constructed	SMOKY HILL LAND CO	14	Well (Application/Permit)	General Purpose	DAWSON	Municipal	592	572	366
360	3039	23893-F	0297564K	Owner	Well Constructed	SMOKY HILL LAND CO	13	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	632	534	262
300	3037	23073 1	02) / 30 HL	o wher	Well Collisiration	SMOKT THEE EARLY CO	13	wen (rippheution)	General Larpose		Walnespar	032	331	202
361	3040	23896-F	0297564L	Owner	Well Constructed	SMOKY HILL LAND CO	24	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Municipal	573	537	238
2.62	2044		200020			nortarno roanny	_		5 · · · · ·	ALL UNNAMED		4400		222
362	3041	154567-	300828	Owner	Well Constructed	POLICHIO, JOSEPH	7	Well (Application/Permit)	Residential	AQUIFERS	Domestic	1100	1100	922
363	3042	158007-	304218	Owner	Well Constructed	AURORA GUN CLUB	13	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Commercial	738	738	638
										ALL UNNAMED				
364	3043	155427-	305040	Owner	Well Constructed	MAXSON, LISA L	27	Well (Application/Permit)	Residential	AQUIFERS	Domestic	320	320	280
						EAST CHERRY CREEK								
365	3044	17492-F-R	305091	Owner	Well Constructed	VALLEY WTR	14	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1700	1626	1152
										ALL UNNAMED				
366	3045	155823-	306389	Owner	Well Constructed	WEBSTER, JAMES M	26	Well (Application/Permit)	Residential	AQUIFERS	Domestic	420	420	300
										ALL UNNAMED				
367	3046	156529-	310135	Owner	Well Constructed	LOO, PHIL	18	Well (Application/Permit)	Residential	AQUIFERS	Domestic	586	586	476
						WASTE,								
368	3047	36612-M	311912	Owner	Well Constructed	MANAGEMENT	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	58	57	47
369	3048	158034-	312932	Owner	Well Constructed	HSU, ANNIE	26	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	425	425	285
307	2010	10001	312/32	C .viici	on constructed	·			TOOLOGITHI		2 omestic	.23	.23	
370	3049	157767-	313386	Owner	Well Constructed	CUMMINGHAM JR GEORGE S	26	Well (Application/Permit)	Residential	DENVER	Domestic	337	337	277
						GRIDLEY JASON &				ALL UNNAMED		_		
371	3050	158416-	315111	Owner	Well Constructed	AMY	25	Well (Application/Permit)	Residential	AQUIFERS	Domestic	525	525	460

OID	Map ID ^{a/}	PermitNumber	Possint.	Acceptance	PermitStatus	ContactName	S-4	LacationTomo	PermitCategory		Heet	CompletedWell Depth	PerforatedCasin	
OID	Мар по	rerimitivumber	Receipt	AssocType	refinitstatus	Contactivame	Section	LocationType	reruntCategory	aquifer1_name	Use1	Deptil	gBottom	gTop
372	3051	158866-	318532	Owner	Well Constructed	MYERS CHARLES B & VICKI L	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1080	1065	950
								/ /						
373	3052	17491-F-R	319344	Owner	Well Constructed	EAST CHERRY CREEK VLY WTR-SAN DIST	16	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1654		
						DEELENA DAVID & CONNIE				ALL UNNAMED				
374	3053	159106-	320065	Owner	Well Constructed	SCHULTEJANN	25	Well (Application/Permit)	Residential	AQUIFERS	Domestic	420	420	320
						WASTE MANAGEMENT OF				ALL UNNAMED				
375	3054	38733-M	0322682A	Owner	Well Constructed	COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	25		
						WASTE MANAGEMENT OF				ALL UNNAMED				
376	3055	38734-M	0322682B	Owner	Well Constructed	COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	26		
						WASTE MANAGEMENT OF				ALL UNNAMED				
377	3056	38735-M	0322682C	Owner	Well Constructed	COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	26		
						WASTE MANAGEMENT OF				ALL UNNAMED				
378	3057	38736-M	0322682D	Owner	Well Constructed	COLORADO INC WASTE	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	31		
						MANAGEMENT OF				ALL UNNAMED				
379	3058	38737-M	0322682E	Owner	Well Constructed	COLORADO INC WASTE	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	40		
						MANAGEMENT OF				ALL UNNAMED				
380	3059	38738-M	0322682F	Owner	Well Constructed	COLORADO INC WASTE	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	16		
201	2060	20720 M	02226026		W II C	MANAGEMENT OF	21	W 11 (A 1: (/D ')	M '' ' ' ' (01 ' '	ALL UNNAMED	M '4 ' /G 1'	17		
381	3060	38739-M	0322682G	Owner	Well Constructed	COLORADO INC WASTE	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	17		
382	3061	38740-M	0322682Н	Owner	Well Constructed	MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	15		
362	3001	36740-WI	032208211	Owner	Wen Constructed	WASTE	31	wen (Application/1 crinit)	Wolltoring/Observation		Wolltoring/Sampling	13		
383	3062	38741-M	0322682I	Owner	Well Constructed	MANAGEMENT OF COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	13		
			***************************************			WASTE		· · · · · (- PP · · · · · · · · · · · · · · · · ·						
384	3063	38742-M	0322682J	Owner	Well Constructed	MANAGEMENT OF COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	12		
385	3064	159931-	323664	Owner	Well Constructed	COLLINS MITCHELL & MICHELLE	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	397	397	287
										ALL UNNAMED				
386	3065	159914-	324034	Owner	Well Constructed	ALLEN, LEESANNE	18	Well (Application/Permit)	Residential	AQUIFERS	Domestic	470	470	370
										ALL UNNAMED				
387	3066	159914-	324034	Owner	Well Constructed	BECKER, DEREK	18	Well (Application/Permit)	Residential	AQUIFERS	Domestic	470	470	370
						WASTE MANAGEMENT OF								
388	3067	39071-M	0324061B	Owner	Well Constructed	COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	145		

												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
389	3068	39072-M	0324061C	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	183		
390	3069	39073-M	0324061D	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	55		
391	3070	39075-M	0324061F	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	6	Well (Application/Permit)	Monitoring/Observation	DAWSON		70		
391	3071	39075-M	0324061G	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling Monitoring/Sampling			
393	3072	39077-M	0324061Н	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	30		
394	3073	39078-M	03240611	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	45		
395	3074	39079-M	0324061J	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	21		
396	3075	39080-M	0324061K	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	58		
397	3076	39081-M	0324061L	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	103		
398	3077	39082-M	0324061M	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	56		
399	3078	39354-M	0326384C	Owner	Well Constructed	CHERRY CREEK SCHOOL DIST #5	8	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31		
400	3079	160962-	326674	Owner	Well Constructed	CHILDS, DAVID W	22	Well (Construction Report)	Residential	ALL UNNAMED AQUIFERS	Domestic	380	380	280
401	3080	161324-	327387	Owner	Well Constructed	PEABODY, MARGARET	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	695	695	595
402	3081	161324-	327387	Owner	Well Constructed	PEABODY, BRIAN	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	695	695	595
403	3082	161419-	328169	Owner	Well Constructed	BEEN KARL & ROSEMARY	26	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	440	440	280
404	3083	161920-	328931	Owner	Well Constructed	KRAUS, GEORGE T.	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic			
405	3084	162112-	330070	Owner	Well Constructed	CITY CORP MORTGAGE	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	790	790	530

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
406	3085	162287-	331540	Owner	Well Constructed	CARTER NORM OR KAREN	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1060	940
407	3086	41219-F	334203	Owner	Well Constructed	MDC LAND CORPORATION	22	Well (Application/Permit)	General Purpose	DENVER	Municipal	1000	975	753
408	3087	163305-	0335693Н	Owner	Well Constructed	VOLTURA SCOTT A & NANCY LEE LIVING TRUST	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	980		
409	3088	163304-	03356931	Owner	Well Constructed	FREUND INVESTMENTS	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1070		
410	3089	163857-	337067	Owner	Well Constructed	SHELTON, DEVELOPMENT	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	420	420	260
411	3090	171246-	337114	Owner	Well Constructed	FARRINGTON MICHAIL & KAYLEIGH	18	Well (Construction Report)	Residential	DENVER	Domestic	590	580	320
412	3091	163876-	337117	Owner	Well Constructed	SEXTON AMY MANERBINO	26	Well (Application/Permit)	Residential	DENVER	Domestic	340	340	282
413	3092	164215-	337157	Owner	Well Constructed	YOUNG FRANK C & SHARON R	24	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	500	500	420
414	3093	165211-	339822	Owner	Well Constructed	PETERSON SCOTT & JERILEE	26	Well (Application/Permit)	Residential	DENVER	Domestic	460	460	400
415	3094	165151-	0340004A	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	19	9
416	3095	165152-	0340004B	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	39	25	15
417	3096	165154-	0340004D	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	84	82	62
418	3097	165157-	0340005C	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	24	9
419	3098	165158-	0340005D	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	24	9
420	3099	165159-	0340005E	Owner	Well Constructed	WASTE MGMT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	40	35	20
421	3100	165378-	340204	Owner	Well Constructed	SHAH, MABEL	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1080	1080	940
422	3101	165533-	341219	Owner	Well Constructed	BRADSHAW, GERALD	18	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	270

												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
423	3102	41421-F	0341379A	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	2	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1554	1500	1028
	3102	111211	00 110 / 211	5 W.LC2	West Constitution	EAST CHERRY CR VALLEY WATER &		were (rappression received)	34.14.12.41.2.41.2.41	LARAMIE-FOX	i i i i i i i i i i i i i i i i i i i	1001	1500	1020
424	3103	41420-F	0341379B	Owner	Well Constructed	SAN DIST	2	Well (Application/Permit)	General Purpose	HILLS	Municipal	2069	2029	1874
425	3104	166200-	0342056A	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	38	38	28
426	3105	166201-	0342056В	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	8
427	3106	166202-	0342056C	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	47	47	37
428	3107	166203-	0342056D	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	28	28	18
429	3108	166204-	0342056E	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	53	53	43
430	3109	166205-	0342056F	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	33	33	23
431	3110	166206-	0342056G	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	8
432	3111	166207-	0342056Н	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	23	13
433	3112	166208-	0342056I	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	38	38	28
434	3113	166209-	0342056J	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	58	58	48
435	3114	166210-	0342056K	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	8
426	2115	165070	242271		Wall Count of	DROWN POPERT C	7	Well (Amiliantia (D. 11)	D:1:1	UPPER	Domesi	1050	1050	020
436	3115	165972-	342271	Owner	Well Constructed	BROWN, ROBERT G	1	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1050	1050	930
437	3116	166815-	343880	Owner	Well Constructed	ARAPAHOE CUSTOM HOMES	25	Well (Construction Report)	Residential	DENVER	Domestic	525	525	445
438	3117	166540-	343915	Owner	Well Constructed	SEWARD, FREDERICK W	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic, Stock	1005	1005	900
439	3118	166857-	344800	Owner	Well Constructed	HORNE, TERRY	25	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	401	401	321

Comparison Proceedings Provided Comparison Proceeding Provided Comparison Proceeding Proceding Proceding															
Add	OVD	a/	B 427 1	D		D tige		a		D 110		** 4			
441 3120	OID	Map ID	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	Location 1 ype	PermitCategory	aquiter1_name	Use1	Depth	gBottom	glop
13 13 13 14 15 15 15 15 15 15 15	440	3110	167513	03452144	Owner	Wall Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	12	4
Add 3129	440	3119	10/313-	0343214A	Owner	Well Collstructed	COUNTION	0	wen (Application/1 erinit)	Worldornig/Observation	AQUITERS	Womtoring/Sampling	13	13	4
According Acco	441	3120	167514-	0345214B	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation		Monitoring/Sampling	13	13	3
13		0.120	30,000						· · · · · (-4f1)						
Add Add	442	3121	167515-	0345214C	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
1875 167516 03457141 Owner Well Constructed COINTY OF 6 Well Capplication Permit) Monitoring Observation ACQUITERS Monitoring Sampling 13 13 3 3 3 3 3 3 3															
DENVER CITY & COUNTY OF 6 Well (Application-Permit) Monitoring-Observation AULLENNAMED Monitoring-Sangular 13 13 3 3 3 445 3124 167519- 03452141 Owner Well Constructed DENVER CITY & COUNTY OF 6 Well (Application-Permit) Monitoring-Observation Monitoring-Sangular 13 13 3 3 3 3 3 446 3125 167519- 03452141 Owner Well Constructed DENVER CITY & COUNTY OF 6 Well (Application-Permit) Monitoring-Observation Monitoring-Sangular 13 13 3 3 3 3 3 3 3	443	3122	167516-	0345214D	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
144 3123 167517. 03452148 Owner Well Constructed COUNTY OF 6 Well (Application Permit) Monitoring Observation AQLIFERS Monitoring Stampling 13 13 3 3 3 3 3 3 3							DENIVED OUTV 0								
145 3124 167518- 0345214F Owner Well Constructed COUNTY OF 6 Well (Application Permit) Monitoring Observation AQUIFERS Monitoring Sampling 13 13 3	444	3123	167517-	0345214E	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
145 3124 167518- 0345214F Owner Well Constructed COUNTY OF 6 Well (Application Permit) Monitoring/Observation AQUIFERS Monitoring/Sampling 13 13 3							DENIVED CITY &				ALL LINNAMED				
Add 3125 167519- 0345214G Owner Well Constructed COUNTY OF 6 Well (Application Permit) Monitoring Observation Adjuster Ad	445	3124	167518-	0345214F	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
Add 3125 167519- 0345214G Owner Well Constructed COUNTY OF 6 Well (Application Permit) Monitoring Observation Adjuster Ad							DENVER CITY &				ALL UNNAMED				
Additional Control of the Control	446	3125	167519-	0345214G	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
Additional Control of the Control							DENVER CITY &				ALL UNNAMED				
Also 3127 167521- 03452141 Owner Well Constructed COUNTY OF 6 Well (Application/Permit) Monitoring/Observation AQUIFERS Monitoring/Sampling 13 13 3	447	3126	167520-	0345214H	Owner	Well Constructed		6	Well (Application/Permit)	Monitoring/Observation			13	13	3
Add							DENVER CITY &				ALL UNNAMED				
449 3128 167864- 346252 Owner Well Constructed & AMY E 22 Well (Application/Permit) Residential DENVER Domestic 400 400 220	448	3127	167521-	0345214I	Owner	Well Constructed	COUNTY OF	6	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	13	13	3
Association							STORMER MICHAEL S								
450 3129 167867- 346504 Owner Well Constructed US HOUSING TECH 18 Well (Application/Permit) Residential AQUIFERS Household use only 455 455 200	449	3128	167864-	346252	Owner	Well Constructed	& AMY E	22	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	220
451 3130 167895- 34638 Owner Well Constructed BURGESON BENJAMIN A & MONICA D 26 Well (Application/Permit) Residential DAWSON Domestic 240 240 180															
451 3130 167895- 346638 Owner Well Constructed A & MONICA D 26 Well (Application/Permit) Residential DAWSON Domestic 240 240 180 452 3131 169251- 348675 Owner Well Constructed G 7 Well (Application/Permit) Residential DAWSON Domestic 240 240 180 453 3132 170097- 349471 Owner Well Constructed MINIKUS, MICKEY G 18 Well (Application/Permit) Residential ALL UNNAMED AQUIFERS Household use only 890 890 660 454 3133 169983- 349491 Owner Well Constructed KIMBERLY 26 Well (Application/Permit) Residential DENVER Domestic 360 360 300 455 3134 170155- 351411 Owner Well Constructed PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	450	3129	167867-	346504	Owner	Well Constructed	US HOUSING TECH	18	Well (Application/Permit)	Residential	AQUIFERS	Household use only	455	455	200
452 3131 169251- 348675 Owner Well Constructed SHANKSTER, THOMAS 7 Well (Application/Permit) Residential ARAPAHOE Domestic 1055 1055 940			4.5=00=		_										
452 3131 169251- 348675 Owner Well Constructed G 7 Well (Application/Permit) Residential ARAPAHOE Domestic 1055 1055 940 453 3132 170097- 349471 Owner Well Constructed MINIKUS, MICKEY G 18 Well (Application/Permit) Residential ALL UNNAMED AQUIFERS Household use only 890 890 660 454 3133 169983- 349491 Owner Well Constructed AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 360 360 300 455 3134 170155- 351411 Owner Well Constructed PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 456 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 457 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 458 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 459 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339 450 AKERS JOHN K H & FRAN	451	3130	167895-	346638	Owner	Well Constructed	A & MONICA D	26	Well (Application/Permit)	Residential	DAWSON	Domestic	240	240	180
453 3132 170097- 349471 Owner Well Constructed MINIKUS, MICKEY G 18 Well (Application/Permit) Residential ALL UNNAMED AQUIFERS Household use only 890 890 660 454 3133 169983- 349491 Owner Well Constructed KIMBERLY 26 Well (Application/Permit) Residential DENVER Domestic 360 360 300 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	450	2121	160251	249675	0	W-II C			W-11 (A 11 12 12	Deside de la		Dti	1055	1055	040
453 3132 170097- 349471 Owner Well Constructed MINIKUS, MICKEY G 18 Well (Application/Permit) Residential AQUIFERS Household use only 890 890 660	452	3131	169251-	3480/3	Owner	weir Constructed	G	7	well (Application/Permit)	Residential	AKAPAHUE	Domestic	1055	1055	940
454 3133 169983- 349491 Owner Well Constructed KIMBERLY 26 Well (Application/Permit) Residential DENVER Domestic 360 360 300 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	453	3122	170097	349471	Owner	Well Constructed	MINIKUS MICKEV C	19	Well (Application/Permit)	Recidential			800	800	660
454 3133 169983- 349491 Owner Well Constructed KIMBERLY 26 Well (Application/Permit) Residential DENVER Domestic 360 360 300 AKERS JOHN K H & FRANCINE M PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	433	3132	1/009/-	3434/1	Owner	wen Constructed		10	weii (Application/Perinit)	Residential	AQUITERS	Household use only	890	690	000
455 3134 170155- 351411 Owner Well Constructed PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	454	3133	169983-	349491	Owner	Well Constructed		26	Well (Application/Permit)	Residential	DENVER	Domestic	360	360	300
455 3134 170155- 351411 Owner Well Constructed PLOURDE 26 Well (Application/Permit) Residential DENVER Domestic 399 399 339	137	3133	10,703	517771	O WHEI	TO CONSTRUCTED	AKERS JOHN K H &	20	on (rippioution)	residential	DETTER	Bomestic	300	300	330
	455	3134	170155-	351411	Owner	Well Constructed		26	Well (Application/Permit)	Residential	DENVER	Domestic	399	399	339
I I I I I I I I I I I I I I I I I I I									(11 ===================================						
456 3135 42398-F 0351634A Owner Well Constructed VLY WTR & SAN DIST 25 Well (Application/Permit) General Purpose ARAPAHOE Municipal 1686 1656 1251	456	3135	42398-F	0351634A	Owner	Well Constructed		25	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1686	1656	1251

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
457	3136	42399-F	0351634B	Owner	Well Constructed	EAST CHERRY CRK VLY WTR & SAN DIST	25	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2373	2343	2104
458	3137	42400-F	0351634C	Owner	Well Constructed	EAST CHERRY CRK VLY WTR & SAN DIST	13	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Municipal	2160	2120	2070
459	3138	42401-F	0351634D	Owner	Well Constructed	EAST CHERRY CRK VLY WTR & SAN DIST	13	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1657	1625	1199
460	3139	42402-F	0351634E	Owner	Well Constructed	EAST CHERRY CRK VLY WTR & SAN DIST	22	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1770	1740	1323
461	3140	42403-F	0351634F	Owner	Well Constructed	EAST CHERRY CRK VLY WTR & SAN DIST	22	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	2455	2425	2103
462	3141	81536A	351755	Owner	Well Constructed	MADDOX DAVID & LINDA	22	Well (Application/Permit)	Residential	DENVER	Domestic	400	320	260
463	3142	171645-	353201	Owner	Well Constructed	JACKSON, KENDRY T.	22	Well (Application/Permit)	Residential	DENVER	Domestic	418	418	298
464	3143	171645-	353201	Owner	Well Constructed	JACKSON, STEPHANIE M.	22	Well (Application/Permit)	Residential	DENVER	Domestic	418	418	298
465	3144	171897-	355632	Owner	Well Constructed	GARNER, LYNN J	22	Well (Construction Report)	Residential	DENVER	Domestic	400	400	300
466	3145	172503-	0357826A	Owner	Well Constructed	ARAPAHOE CUSTOM HOMES	26	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	360
467	3146	172504-	0357826B	Owner	Well Constructed	YEAGER BRAD & LISA	26	Well (Application/Permit)	Residential	DENVER	Domestic	325	325	225
468	3147	173691-	358188	Owner	Well Constructed	FRAHM, STAN	27	Well (Application/Permit)	Residential	DENVER UPPER	Domestic	360	360	260
469	3148	177254-	358690	Owner	Well Constructed	MICKENS ALBERT JR	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1104	1100	980
470	3149	172934-	358988	Owner	Well Constructed	DENEAU, GERALD O FORTUNA, TERRANCE	22	Well (Application/Permit)	Residential	DENVER UPPER	Domestic	405	405	345
471	3150	172919-	359206	Owner	Well Constructed	J.	7	Well (Construction Report)	Residential	ARAPAHOE UPPER	Domestic, Stock	1043	1043	923
472 473	3151	172919- 174815-	359206 359773	Owner Owner	Well Constructed Well Constructed	FORTUNA, ETSUKO PARSONS, PAUL	18	Well (Construction Report) Well (Application/Permit)	Residential Residential	UPPER ARAPAHOE	Domestic, Stock Domestic	1100	1043	923 975

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
474	3153	173878-	360801	Owner	Well Constructed	LUND RONALD & RITA & JASON	18	Well (Application/Permit)	Residential	DENVER	Domestic	580	580	460
								(11						
475	3154	174373-	361151	Owner	Well Constructed	KUCHARSKI JIM OR GAIL	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1040	1040	910
476	3155	173967-	0361348A	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	55	40	2
477	3156	173968-	0361348B	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS		68	54	2
477	3130	173700-	0301340D	Owner	well constructed	DENVER CITY &		weii (Аррисацов т стин)	Wolfforing Observation	ALL UNNAMED		00	34	2
478	3157	173969-	0361348C	Owner	Well Constructed	COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	28	28	2
479	3158	173970-	0361348D	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	71	50	3
480	3159	173971-	0361348E	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	105	89	2
481	3160	173972-	0361348F	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	75	55	2
482	3161	173973-	0361348G	Owner	Well Constructed	DENVER CITY & COUNTY OF	7	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	16	2
483	3162	175284-	361899	Owner	Well Constructed	THOMAS BRAD AND SUE	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic, Stock	1070	1070	940
403	3102	1/3204-	301077	Owner	well constructed	TRAVIS BRIAN E &	,	weir (Construction Report)	Residential	AKAI AHOL	Domestic, Stock	1070	1070	740
484	3163	176182-	362519	Owner	Well Constructed	DENIELLE C	22	Well (Application/Permit)	Residential	DENVER	Domestic	325	325	305
405	2164	17/702	264062		WIIC	CMITH LAWEDNA	26	W 11 (A 1: 4: /D ::)	D :1 ::1	DEMMED	D (: G) 1	41.5	41.5	205
485	3164	176782-	364062	Owner	Well Constructed	SMITH, LAVERNA	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	415	415	295
486	3165	75258A	364530	Owner	Well Constructed	JACOBSEN, ROY	22	Well (Application/Permit)	Residential	DENVER	Domestic	350	350	210
						*								
487	3166	178378-	365362	Owner	Well Constructed	HOMBURGER, KEITH	22	Well (Application/Permit)	Residential	DENVER	Domestic	320	320	200
488	3167	177877-	365800	Owner	Well Constructed	BROCK, LOGAN	7	Well (Application/Permit)	Residential	DENVER	Domestic	830	830	690
						233 233 23 23 23 23 23 23 23 23 23 23 23		(
489	3168	177877-	365800	Owner	Well Constructed	BROCK, JENNIFER	7	Well (Application/Permit)	Residential	DENVER	Domestic	830	830	690
490	3169	178534-	366640	Owner	Well Constructed	LINDEMANIS, DENISE R	18	Well (Application/Permit)	Residential	DENVER	Domestic	585	585	565

												CompletedWell	PerforatedCasin	
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
491	3170	178721-	366772	Owner	Well Constructed	REVERCOMB, MATTHEW S.	26	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	520
492	3171	178721-	366772	Owner	Well Constructed	REVERCOMB, LONI T.	26	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	520
493	3172	179024-	367217	Owner	Well Constructed	MOUNTAIN PLAIN HOMES INC	18	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	280
494	3173	44252-F	0368769A	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal			
495	3174	44253-F	0368769B	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal			
496	3175	44254-F	0368769C	Owner	Well Constructed	AURORA CITY OF	21	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal			
497	3176	180372-	369428	Owner	Well Constructed	TOMASSI, HECTOR V	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1050	1050	930
498	3177	181828-	370272	Owner	Well Constructed	SMITH, ALMA S	17	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1040	1040	920
499	3178	180431-	371265	Owner	Well Constructed	MEIER CHRISTOPHER & CHRISTINE	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1020	1020	920
500	3179	133281A	371555	Owner	Well Constructed	NEW HOPE MINISTRIES	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	400	257	137
300	3179	133261A	3/1333	Owner	wen constructed	WIINISTRIES	22	wen (Application/Termit)	Residential	DENVER	Domestic, Stock	400	231	137
501	3180	94247-VE	0371555A	Owner	Well Constructed	LOBENSTEIN, JAMES	22	Well (Application/Permit)	Unknown	DENVER	Domestic	400	257	217
502	3181	81715A	371989	Owner	Well Constructed	EVERHART, JERRY	22	Well (Application/Permit)	Residential	DENVER	Domestic	325	325	175
503	3182	184214-	372564	Owner	Well Constructed	SIMONS WILLIAM & VERNA	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	1010	1010	900
504	3183	182102-	373582	Owner	Well Constructed	OLIVER THOMAS KENT	7	Well (Application/Permit)	Residential	DENVER	Domestic	780	840	660
505	3184	182187-	373974	Owner	Well Constructed	GOODSON, GLENN	18	Well (Application/Permit)	Residential	DENVER	Domestic	394	394	294
506	3185	183851-	376593	Owner	Well Constructed	KARSH, JOSHUA M.	18	Well (Construction Report)	Residential	DENVER	Domestic	440	440	280
507	3186	183851-	376593	Owner	Well Constructed	KARSH, CARIE N.	18	Well (Construction Report)	Residential	DENVER	Domestic	440	440	280

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
508	3187	184063-	377104	Owner	Well Constructed	MCGARRAHAN, PETER	22	Well (Construction Report)	Residential	DENVER	Domestic	380	380	260
509	3188	184188-	377359	Owner	Well Constructed	LUNDE, TODD	18	Well (Application/Permit)	Residential	DENVER	Domestic	570	570	460
510	3189	184188-	377359	Owner	Well Constructed	LUNDE, ANDREA	18	Well (Application/Permit)	Residential	DENVER	Domestic	570	570	460
511	3190	184042-	377528	Owner	Well Constructed	HARRIS, JOHN	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1020	1020	920
512	3191	44466-F	378406	Owner	Well Constructed	KRUPA, JOHN	18	Well (Construction Report)	General Purpose	UPPER ARAPAHOE	Irrigation	1035	1035	903
513	3192	185463-	380186	Owner	Well Constructed	ARAPAHOE CUSTOM HOMES	25	Well (Application/Permit)	Residential	DENVER	Domestic	640	640	340
514	3193	185092-	380261	Owner	Well Constructed	MONARCH HOMES	18	Well (Application/Permit)	Residential	DENVER	Domestic	440	440	260
515	3194	185345-	380511	Owner	Well Constructed	PUREWAL, GURMIT	18	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	540
516	3195	185325-	381356	Owner	Well Constructed	DAHL, GARY	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1083	1083	963
517	3196	186150-	381930	Owner	Well Constructed	MERIDIAN HOMES LLC	24	Well (Application/Permit)	Residential	DENVER	Domestic	640	640	420
518	3197	186356-	383179	Owner	Well Constructed	MCDONALD STEVEN & MONDRA	18	Well (Application/Permit)	Residential	DENVER	Domestic	443	443	283
519	3198	186823-	383294	Owner	Well Constructed	VELASQUEZ, FRANCISCO	18	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	280
520	3199	187632-	383781	Owner	Well Constructed	CAMPBELL AUGUST A JANICE L	7	Well (Application/Permit)	Residential	DENVER	Domestic	830	830	722
521	3200	187269-	384035	Owner	Well Constructed	MOUNTAIN PLAIN HOMES	18	Well (Application/Permit)	Residential	DENVER	Domestic	580	580	300
522	3201	191053-	389593	Owner	Well Constructed	MUILENBURG, MARK	18	Well (Construction Report)	Residential	DENVER	Domestic	697	657	400
523	3202	191838-	392581	Owner	Well Constructed	BECKER, DAVID W	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1060	960
524	3203	193290-	396395	Owner	Well Constructed	SHANNON, ROBERT	25	Well (Application/Permit)	Residential	DENVER	Domestic	461	461	381

												CompletedWell	Powfowated Casin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
525	3204	68439A	396810	Owner	Well Constructed	REUL, GHEORGHE	22	Well (Application/Permit)	Residential	DENVER	Domestic	380	380	215
						DENVER ENVIRONMENTAL				ALL UNNAMED				
526	3205	194022-	0397828B	Owner	Well Constructed	SERVICES	7	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	61	60	30
						DENVER ENVIRONMENTAL				ALL UNNAMED				
527	3206	194023-	0397828C	Owner	Well Constructed	SERVICES	7	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	49	49	39
						DENVER ENVIRONMENTAL				ALL UNNAMED				
528	3207	194024-	0397828D	Owner	Well Constructed	SERVICES	6	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	68	67	48
						DENVER ENVIRONMENTAL				ALL UNNAMED				
529	3208	194026-	0397828F	Owner	Well Constructed	SERVICES	6	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	59	59	39
						DENVER ENVIRONMENTAL				ALL UNNAMED				
530	3209	194027-	0397828G	Owner	Well Constructed	SERVICES	6	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	51	51	41
						DENVER ENVIRONMENTAL				ALL UNNAMED				
531	3210	194029-	0397828I	Owner	Well Constructed	SERVICES	6	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	17	17	7
						GONZALEZ ROBERTO								
532	3211	196184-	400936	Owner	Well Constructed	M & HILDA M	18	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	305
										ALL UNNAMED				
533	3212	196187-	401049	Owner	Well Constructed	COPE, FRANKLIN	18	Well (Application/Permit)	Residential	AQUIFERS	Household use only	715	695	555
						HELLING WILHELM III								
534	3213	196990-	402084	Owner	Well Constructed	& BRENDA J	18	Well (Application/Permit)	Residential	DENVER	Domestic	560	560	300
						BUEHLER STANLEY &								
535	3214	197063-	402099	Owner	Well Constructed	JENNIFER	18	Well (Application/Permit)	Residential	DENVER	Domestic	503	503	360
						TRAN ANH & THUY								
536	3215	197829-	403295	Owner	Well Constructed	NGA	18	Well (Application/Permit)	Residential	DENVER	Domestic	380	380	240
										LIDDED				
537	3216	197828-	403301	Owner	Well Constructed	JONES, JONI	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1020	1020	930
						DI ATTENDA								
538	3217	197582-	0403813B	Owner	Well Constructed	PLATTE RIVER CONSTRUCTORS LTD	13	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	32	32	22
539	3218	97800A	403846	Owner	Well Constructed	WHITE, BARBARA	7	Well (Construction Report)	Residential	DENVER	Domestic	720	720	560
540	3219	198274-	404708	Owner	Well Constructed	BARRETT IV, THOMAS R.	26	Well (Application/Permit)	Residential	DENVER	Domestic	433	433	393
								· • • · · · · · · · · · · · · · · · · ·						
541	3220	198274-	404708	Owner	Well Constructed	BARRETT, TARA F.	26	Well (Application/Permit)	Residential	DENVER	Domestic	433	433	393

OID	M ID ^a /	P	Descript	Acceptance	D	ContactNone	S4	LocationTown	Provide Account		H-s1	-	PerforatedCasin	
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
542	3221	198510-	404843	Owner	Well Constructed	WEAVER, RANDALL	26	Well (Construction Report)	Residential	DENVER	Domestic	457	457	377
543	3222	198514-	404918	Owner	Well Constructed	OPPERUD, BEV	18	Well (Application/Permit)	Residential	DENVER	Domestic	405	405	330
544	3223	109366A	404977	Owner	Well Constructed	VILLARREAL RUDY & SARAH	7	Well (Application/Permit)	Residential	DENVER	Domestic	727	727	580
545	3224	198908-	405613	Owner	Well Constructed	PORRAS, JESUS R.	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1060	1060	960
						FERGUSON, JESSICA	-			UPPER				
546	3225	199220-	406352	Owner	Well Constructed	M. FERGUSON, ANTHONY	7	Well (Application/Permit)	Residential	ARAPAHOE UPPER	Domestic	1045	1045	970
547	3226	199220-	406352	Owner	Well Constructed	L.	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1045	1045	970
548	3227	199203-	406517	Owner	Well Constructed	CAM, RICHARD D	18	Well (Application/Permit)	Residential	DENVER	Domestic	465	465	335
549	3228	200448-	408140	Owner	Well Constructed	PLATTE RIVER CONSTRUCTORS LTD	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Commercial	680	680	340
550	3229	199938-	408298	Owner	Well Constructed	KIRKPATRICK ROBERT D & KAREN L	7	Well (Application/Permit)	Residential	DENVER	Domestic	835	835	680
551	3230	200111-	408517	Owner	Well Constructed	SAVIAGE, TIFFANY N.	22	Wall (Amiliantian/Dameit)	Residential	DENVER	Domestic	405	405	260
331	3230	200111-	408317	Owner	well Constructed	SAVIAGE, HFFANT N.	22	Well (Application/Permit)	Residential	DENVER	Domestic	403	403	200
552	3231	189727A	408621	Owner	Well Constructed	QUICK, ELEANOR	7	Well (Application/Permit)	Residential	DENVER	Domestic	630	630	350
553	3232	200744-	408622	Owner	Well Constructed	QUICK, ELEANOR	18	Well (Application/Permit)	Residential	DENVER	Stock	350	350	220
554	3233	47700-F	0409358A	Owner	Well Constructed	STATE BOARD OF LAND COMMISSIONERS	15	Well (Application/Permit)	General Purpose	ARAPAHOE	Commercial, Municipal			
555	3234	200896-	410185	Owner	Well Constructed	MURATA PERRY & SHIGEKO	26	Well (Application/Permit)	Residential	DENVER	Domestic	438	438	318
556	3235	201927-	411843	Owner	Well Constructed	ACJ PARTNERSHIP	21	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	605	605	505
557	3236	48145-F	413437	Owner	Well Constructed	RANGEVIEW METRO DIST	11	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Industrial	25		
558	3237	202973-	414067	Owner	Well Constructed	LANDSIEDEL ROGER & FRISBIE ALICIA	18	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	340

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
559	3238	203685-	415023	Owner	Well Constructed	ASCHENBRENNER, CRYSTAL M	26	Well (Application/Permit)	Residential	DENVER	Domestic	420	420	300
560	3239	204742-	416555	Owner	Well Constructed	AURORA PUBLIC SCHOOLS	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1035	1035	900
561	3240	205527-	418899	Owner	Well Constructed	MUILENBURG, MARK	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	620	400
562	3241	205225-	418968	Owner	Well Constructed	HOTT ROBERT T & GRUEL-HOTT RONDA	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	590	590	210
563	3242	205260-	420672	Owner	Well Constructed	RISHAVY JIM & JOY	26	Well (Application/Permit)	Residential	DENVER	Domestic	577	577	437
564	3243	207461-	0422455E	Owner	Well Constructed	AURORA UTILITIES DEPT	8	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	20	10
565	3244	49395-F	0423253A	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WTR & SAN	15	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS		2480	2440	2112
566	3245	49396-F	0423253B	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WTR & SAN	15	Well (Application/Permit)	General Purpose	ARAPAHOE		1755	1724	1278
567	3246	49667-F	424943	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER	1	Well (Application/Permit)	General Purpose	ARAPAHOE	Municipal	1581	1551	1110
568	3247	208051-	424972	Owner	Well Constructed	NGUYEN DUY TIEN & PHI PHI HOANG	18	Well (Application/Permit)	Residential	DENVER	Domestic	440	440	360
569	3248	209655-	429343	Owner	Well Constructed	STURTZ, MICHAEL E	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1080	1080	960
570	3249	211505-	430333	Owner	Well Constructed	BRANDT PAUL R & JENNIE W	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1023	1023	843
571	3250	211266-	431672	Owner	Well Constructed	MUILENBURG, MARK	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	600	320
572	3251	212997-	432444	Owner	Well Constructed	PROGRESS CIRCLE TRUST	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	560	560	360
573	3252	50579-F	0433513A	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	14	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Irrigation, Municipal	2470	2409	2071
574	3253	50580-F	0433513B	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	14	Well (Application/Permit)	General Purpose	ARAPAHOE	Irrigation, Municipal	1748	1698	1266
575	3254	50581-F	0433513C	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND		Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Irrigation, Municipal	2510	2460	2100

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
576	3255	50582-F	0433513D	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	13	Well (Application/Permit)	General Purpose	ARAPAHOE	Irrigation, Municipal	1798	1748	1277
577	3256	50583-F	0433513E	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	16	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Irrigation, Municipal	2259	2219	2030
578	3257	50584-F	0433513F	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	16	Well (Application/Permit)	General Purpose	ARAPAHOE	Irrigation, Municipal	1686	1636	1215
579	3258	213653-	0435307A	Owner	Well Constructed	MOORE, DANIEL	26	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1160	1160	1000
580	3259	213652-	0435307B	Owner	Well Constructed	ARABADJIEV, ROSSEN	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	740	740	660
581	3260	213652-	0435307B	Owner	Well Constructed	ARABADJIEV, ASYA	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	740	740	660
582	3261	214570-	436857	Owner	Well Constructed	HOMESTEAD LAND LEASE INC	18	Well (Application/Permit)	Residential	DENVER	Domestic	510	510	350
583	3262	214559-	437488	Owner	Well Constructed	GHORI, SHOAIB	18	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	300
584	3263	214554-	438460	Owner	Well Constructed	KRAUS, TIMOTHY D	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1100	1100	990
585	3264	216026-	440409	Owner	Well Constructed	JAHNKE, DEMAR W	27	Well (Application/Permit)	Residential	DENVER	Domestic	440	440	280
586	3265	216807-	442459	Owner	Well Constructed	CROWLEY, LARRY E	18	Well (Construction Report)	Residential	DENVER	Domestic	500	500	400
587	3266	51681-F	442658	Owner	Well Constructed	EAST CHERRY CREEK VALLEY W&S DIST	12	Well (Application/Permit)	General Purpose	LARAMIE FOX HILLS	Commercial, Municipal	2160		
589	3268	52129-F	0445522D	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SAN DST	11	Well (Application/Permit)	General Purpose	LARAMIE FOX HILLS	Municipal	2357	2340	1955
590	3269	217528-	0445582A	Owner	Well Constructed	WILSEY LYNN & SUZANNE	16	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	280		
591	3270	217528A	0445582B	Owner	Well Constructed	ROBLES, PATRICIA	16	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	478	458	398
592	3271	217528A	0445582B	Owner	Well Constructed	HERNANDEZ, VICTOR	16	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	478	458	398
593	3272	218427-	445616	Owner	Well Constructed	FAKHARZADEH, JALAL	27	Well (Application/Permit)	Residential	DENVER	Domestic	523	523	383

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
594	3273	219000-	446581	Owner	Well Constructed	TOWNS, HARRY	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	535	535	375
595	3274	220518-	450176	Owner	Well Constructed	WOODS DAVID E & JANET I	26	Well (Application/Permit)	Residential	DENVER	Domestic	398	398	278
										UNCONFINED SAN LUIS VALLEY				
596	3275	222013-	0450484K	Owner	Well Constructed	ATC ASSOCIATES INC	15	Well (Application/Permit)	Monitoring/Observation	AQUIFER UNCONFINED SAN LUIS	Monitoring/Sampling	17	17	2
597	3276	222014-	0450484L	Owner	Well Constructed	ATC ASSOCIATES INC	15	Well (Application/Permit)	Monitoring/Observation	VALLEY AQUIFER	Monitoring/Sampling	19	19	4
598	3277	222015-	0450484M	Owner	Well Constructed	ATC ASSOCIATES INC	15	Well (Application/Permit)	Monitoring/Observation	UNCONFINED SAN LUIS VALLEY AQUIFER	Monitoring/Sampling	19	19	4
599	3278	222016-	0450484N	Owner	Well Constructed	ATC ASSOCIATES INC	15	Well (Application/Permit)	Monitoring/Observation	UNCONFINED SAN LUIS VALLEY AQUIFER	Monitoring/Sampling	25	25	15
600	3279	222017-	0450484O	Owner	Well Constructed	ATC ASSOCIATES INC	15	Well (Application/Permit)	Monitoring/Observation	UNCONFINED SAN LUIS VALLEY AQUIFER	Monitoring/Sampling	25	25	15
601	3280	222480-	452854	Owner		DUFFY RYAN & KELLY	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1062	1062	940
602	3281	223190-	454660	Owner	Well Constructed	KELLY, JERRY	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1057	1057	906
603	3282	53201-F	455229	Owner	Well Constructed	FREUND & COMPANY/FREUND INVESTMENTS	18	Well (Application/Permit)	General Purpose	UPPER ARAPAHOE	Commercial, Industrial	1034	1034	907
604	3283	223174-	455384	Owner	Well Constructed	SCHOONHOOVEN, ALEXANDER	18	Well (Application/Permit)	Residential	DENVER	Domestic	460	460	300
605	3284	224904-	0458136E	Owner	Well Constructed	PEC MIDWEST LLC	36	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	15		
606	3285	78897A	461046	Owner	Well Constructed	THIEMES, SAM	22	Well (Application/Permit)	Residential	DENVER	Domestic	480	480	180
607	3286	226534-	461961	Owner	Well Constructed	BARNES JEANNETTE M & DUNCAN E	22	Well (Application/Permit)	Residential	DENVER	Domestic	443	443	343
608	3287	72418A	462224	Owner	Well Constructed	KINGHT, MICHAEL T	22	Well (Application/Permit)	Residential	DENVER	Domestic	400	400	325

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
OID	мар по	1 et illitivullibet	Кесеірі	Associype	Termitstatus	Contactivame	Section	Location 1 ype	1 er mit Categor y	aquiter 1_name	Osei	Бери	gDottom	grop
609	3288	228817-	465151	Owner	Well Constructed	SOMA, ANDREW	27	Well (Application/Permit)	Residential	DENVER	Domestic	518	518	398
610	3289	229172-	465695	Owner	Well Constructed	NGUYEN, JOHN T	26	Well (Application/Permit)	Residential	DENVER	Domestic	538	538	318
(11	3290	220210	0468041B	0	Wall Constructed	WALKER, DOUGLAS	22	W-11 (A :: :1: - 4: - :: /D-::::4)	Davidantial	DENIZED	Damadia	410	410	210
611	3290	230319- 17488-F-R	469231	Owner	Well Constructed Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	22	Well (Application/Permit) Well (Application/Permit)	Residential General Purpose	DENVER ARAPAHOE	Domestic Commercial, Industrial	2000	1960	310
614	3293	55022-F	0469523B	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	8	Well (Application/Permit)	General Purpose	UPPER	Commercial, Industrial		1339	1157
615	3294	55023-F	0469523C	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	8	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Commercial, Industrial	2409	2355	2010
616	3295	230527-	470332	Owner	Well Constructed	PAPPAS JAMES & PAPADIMITPPOULOS MADELINE	26	Well (Application/Permit)	Residential	DENVER	Domestic	583	583	303
617	3296	55867-F	0470416C	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	2	Well (Application/Permit)	General Purpose	ARAPAHOE	Commercial, Industrial	1630	1555	1204
618	3297	55864-F	0470416D	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	2	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Commercial, Industrial	2315	2254	1874
619	3298	55865-F	0470416E	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	12	Well (Application/Permit)	General Purpose	ARAPAHOE	Commercial, Industrial	1720	1620	1191
620	3299	55866-F	0470416F	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	12	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Commercial, Industrial	2360	2320	1924
621	3300	232007-	472852	Owner	Well Constructed	SCHIVELY GARY J & CHERI D	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1085	1090	950
622	3301	233242-	474017	Owner	Well Constructed	DUFF, LARRY	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1085	1085	940
623	3302	234171-	475379	Owner	Well Constructed	WASTE MANAGEMENT OF CO	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	30	10
624	3303	234446-	478716	Owner	Well Constructed	BIBEAU, JOHN	22	Well (Application/Permit)	Residential	DENVER	Domestic	518	518	418
625	3304	115632A	478862	Owner	Well Constructed	JERNIGON, DAVE	18	Well (Application/Permit)	Residential	DAWSON	Domestic	740	640	265
626	3305	56280-F	479417	Owner	Well Constructed	DENVER CITY & COUNTY OF	31	Well (Application/Permit)	General Purpose	LOWER ARAPAHOE	Industrial, Irrigation	1470	1550	50

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
627	3306	235779-	479743	Owner	Well Constructed	HASKELL PAUL K & DARLENE M	22	Well (Application/Permit)	Residential	DENVER	Domestic	275	275	285
628	3307	235090-	479947	Owner	Well Constructed	MALCHOW-WEBER, BENJAMIN	22	Well (Application/Permit)	Residential	DENVER	Domestic	720		
629	3308	235090-	479947	Owner	Well Constructed	MALCHOW-WEBER, SHANNON	22	Well (Application/Permit)	Residential	DENVER	Domestic	720		
630	3309	97708A	482746	Owner	Well Constructed	CRUM ROBERT & LISA	26	Well (Application/Permit)	Residential	DENVER	Domestic	598		
631	3310	115622A	482761	Owner	Well Constructed	VALENZUELA- GARDEA, CRISTIAN	18	Well (Application/Permit)	Residential	DENVER	Domestic	905	901	421
632	3311	115622A	482761	Owner	Well Constructed	COB OS MENDEZ, SERGIO R.	18	Well (Application/Permit)	Residential	DENVER	Domestic	905	901	421
633	3312	236752-	0482931A	Owner	Well Constructed	COMPTON, JIMMIE L	11	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic			
										ALL UNNAMED				
634	3313	236752A	0482931B	Owner	Well Constructed	COMPTON, JIMMIE L	11	Well (Application/Permit)	Residential	AQUIFERS	Domestic	60	60	23
635	3314	236751-	482947	Owner	Well Constructed	MEYER, DAVID A	22	Well (Application/Permit)	Residential	DENVER	Domestic	200	540	260
636	3315	238177-	0484623A	Owner	Well Constructed	BUCKLEY AIR FORCE BASE	11	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	25	16
637	3316	238178-	0484623B	Owner	Well Constructed	BUCKLEY AIR FORCE BASE	11	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	20
638	3317	238179-	0484623C	Owner	Well Constructed	BUCKLEY AIR FORCE BASE	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	45	45	35
639	3318	238180-	0484623D	Owner	Well Constructed	BUCKLEY AIR FORCE BASE	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	45	43	33
640	3319	238189-	485361	Owner	Well Constructed	QUINONES, MARTA	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1102		
641	3320	58192-F	0485544A	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SAN	22	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Industrial, Municipal	2477		
642	3321	58191-F	0485544C	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SANITATION	22	Well (Application/Permit)	General Purpose	ARAPAHOE	Industrial, Municipal	1725		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
643	3322	239555-	488433	Owner	Well Constructed	NEWTON PATRICK M AND ASHLEY M	22	Well (Application/Permit)	Residential	DENVER	Domestic	540	540	320
043	3322	239333-	400433	Owner	wen Constructed			wen (Application/Fermit)	Residential	DENVER	Domestic	340	340	320
644	3323	57308-F	489058	Owner	Well Constructed	RACING ASSOCIATION OF CO LTD	17	Well (Application/Permit)	General Purpose	ARAPAHOE	Industrial, Municipal	1755	1755	515
645	3324	57719-F	493198	Overmon.	Well Constructed	ST SIMEON CEMETARY ASSOCIATION	12	Well (Application/Permit)	Company Drumness	UPPER ARAPAHOE		990	980	910
043	3324	3//19-F	493198	Owner	well Constructed	WASTE	13	well (Application/Permit)	General Purpose			990	980	910
646	3325	242713-	493271	Owner	Well Constructed	MANAGEMENT OF COLORADO	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	58	56	46
.	2226	244252	0.40220.64			DENVER DEPT OF	_			ALL UNNAMED			2.5	
647	3326	244959-	0493286A	Owner	Well Constructed	PUBLIC HEALTH	5	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	35	35	15
648	3327	242725-	0493286B	Owner	Well Constructed	DENVER DEPT OF PUBLIC HEALTH	5	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	36	35	20
610	2220	242526	0.40220.65			DENVER DEPT OF	_		W 1: 1: (01 ::	ALL UNNAMED				
649	3328	242726-	0493286C	Owner	Well Constructed	PUBLIC HEALTH	5	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	0		
650	3329	244960-	0493286D	Owner	Well Constructed	DENVER DEPT OF PUBLIC HEALTH	5	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	65	65	40
(51	2220	244061	0.4022975		W.H.C.	DENVER DEPT OF	-	Will (A. II. of (B. Ca)	M : (01)	ALL UNNAMED	M ' ' ' (C 1'	00	70	20
651	3330	244961-	0493286E	Owner	Well Constructed	PUBLIC HEALTH	5	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	80	79	39
652	3331	241645-	493593	Owner	Well Constructed	STOLL, BENTON L.	22	Well (Application/Permit)	Residential	DENVER	Domestic	463	463	343
						,		(11 /						
653	3332	241645-	493593	Owner	Well Constructed	HAMOR, SHARON R.	22	Well (Application/Permit)	Residential	DENVER	Domestic	463	463	343
										UPPER				
654	3333	243820-	495642	Owner	Well Constructed	LORENZ, MATTHEW J	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic, Stock	1106	1106	956
655	3334	243705-	495698	Owner	Well Constructed	RICHART, GEORGE	25	Well (Application/Permit)	Residential	DENVER	Domestic	618	618	498
656	3335	65782A	495734	Owner	Well Constructed	MADDOX, LOUISE	22	Well (Application/Permit)	Residential	DENVER	Domestic	398	398	218
657	3336	61226-F	496044	Owner	Well Constructed	RANGEVIEW METROPLITAN DIST	33	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS		19		
		012201		- S.Miei	The Constructed		33	(sppicutour citie)	urpose	THE OTHER				
659	3338	94812A	496723	Owner	Well Constructed	WARD ROBERT & HIROKO	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	360	260	180
	22.42	50424 F	507054	0	Wall Carry	EAST CHERRY CREEK VALLEY WATER &		Wall (Amalia di /D di)	Consul P	LARAMIE-FOX	Manifest	2205		
664	3343	59424-F	507054	Owner	Well Constructed	SAN	2	Well (Application/Permit)	General Purpose	HILLS	Municipal	2295		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
665	3344	250415-	508208	Owner	Well Constructed	MADERA, ABEL	7	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	1035	1035	915
		251922	512494	0	W.II.C 1	WASTE MANAGEMENT OF	22		M : (0)	ALL UNNAMED	M :: (G 1:	42		
666	3345	251833-	512484	Owner	Well Constructed	COLORADO	32	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	43	43	33
668	3347	252659-	0514426D	Owner	Well Constructed	US GEOLOGICAL SURVEY	16	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	48	48	39
669	3348	252660-	0514426E	Owner	Well Constructed	US GEOLOGICAL SURVEY	16	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	18	18	9
670	3349	248439-	0514426G	Owner	Well Constructed	US GEOLOGICAL SURVEY	15	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	42	42	32
671	3350	252662-	0514426Н	Owner	Well Constructed	US GEOLOGICAL SURVEY	14	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	23	23	13
672	3351	252663-	0514426I	Owner	Well Constructed	US GEOLOGICAL SURVEY	10	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	28	28	18
673	3352	252664-	0514426J	Owner	Well Constructed	US GEOLOGICAL SURVEY	2	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS		23	23	13
0,0				2 11000		US GEOLOGICAL		· · · · (- - 		ALL UNNAMED				
674	3353	249240-	0514426K	Owner	Well Constructed	SURVEY	3	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	37	37	30
675	3354	252936-	515342	Owner	Well Constructed	MOULD FRED B & BARBARA J	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1090	1090	960
676	3355	253956-	517120	Owner	Well Constructed	NGUYEN THUY & LAN LE	18	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1100	1100	970
677	3356	256340-	0518177A	Owner	Well Constructed	US GEOLOGICAL SURVEY	5	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling			
678	3357	254402-	0518177B	Owner	Well Constructed	US GEOLOGICAL SURVEY	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26	25	15
						US GEOLOGICAL			-	ALL UNNAMED				
679	3358	254403-	0518177C	Owner	Well Constructed	SURVEY	4	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	38	38	28
680	3359	254404-	0518177D	Owner	Well Constructed	US GEOLOGICAL SURVEY	3	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	43	43	33
681	3360	254405-	0518177E	Owner	Well Constructed	US GEOLOGICAL SURVEY	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	29	28	18
682	3361	61038-F	523605	Owner	Well Constructed	AURORA CITY OF	25	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	36		

														PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
						COLSON DAVID A &								
683	3362	258132-	524899	Owner	Well Constructed	JESSICA B	26	Well (Application/Permit)	Residential	DENVER	Domestic	620	620	300
684	3363	258581-	526481	Owner	Well Constructed	ANDERSON DAMON & CHRISTIE	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic			
004	3303	230301-	320461	Owner	Well Collstructed	CHRISTIE	,	well (Application/Termit)	Residential	AKAI AITOE	Domestic			
695	2264	250422	527745	0	W-11 Countries to 4	PEACEMAKER,	10	W-11 (A1:	D idential	UPPER	Domostic	1062	2065	020
685	3364	259432-	527745	Owner	Well Constructed	RICHARD W	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1062	2065	920
686	3365	262996-	537937	Owner	Well Constructed	HANRAHAN DENNIS & JEANIE	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1046	1046	896
						DE A CEMAKED				ALL IDDIANCED				
687	3366	265471-	0538343A	Owner	Well Constructed	PEACEMAKER, RICHARD	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	55		
								, 11						
688	3367	264051-	540047	Owner	Well Constructed	GILLARD, ELIZABETH	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1090	1090	950
000	3307	201031	210017	Owner	Wen constructed	GIEE/ II(E), EEIE/ IDE III	,	wen (rippheation remit)	residential	7 HC H 7 H 1 G E	Domestic	1000	1000	730
689	3368	265101-	540458	Owner	Well Constructed	ASHBY JR DONALD	22	Well (Application/Permit)	Residential	DENVER	Domestic	598	458	298
007	3300	203101-	340436	Owner	Well Constructed	ASIIDI JK DONALD	22	wen (Application/Termit)	Residential	DLIVVER	Domestic	376	730	276
690	3369	265192-	540682	0	W-11 Constructed	HILLSIDE COUNTRY HOMES	10	Well (Construction Report)	Residential	DENVER	Domostic	495	475	225
690	3309	263192-	340082	Owner	Well Constructed	HOMES	18	well (Construction Report)	Residential	DENVER	Domestic	493	4/3	335
						WASTE				ALL UNNAMED				
691	3370	265296-	540883	Owner	Well Constructed	MANAGEMENT OF CO	32	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	31	31	21
692	3371	265421-	541554	Owner	Well Constructed	MCCARTHY, TRICIA	25	Well (Application/Permit)	Residential	DENVER	Domestic	550	550	315
693	3372	138283A	542654	Owner	Well Constructed	REID, ANN	18	Well (Application/Permit)	Residential	DENVER	Domestic	900	900	360
						WILMER STANLEY E &				UPPER				
694	3373	266627-	544152	Owner	Well Constructed	CHERYL A	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1050	1050	920
						LIGHTHOUSE,								
695	3374	265920-	544265	Owner	Well Constructed	BUILDERS	22	Well (Application/Permit)	Residential	DENVER	Domestic	398	398	278
								-						
696	3375	265898-	544318	Owner	Well Constructed	KIM, THOMAS M.	22	Well (Construction Report)	Residential	DENVER	Domestic	398	398	338
								, 19						-
697	3376	265898-	544318	Owner	Well Constructed	KIM, REBECCA K.	22	Well (Construction Report)	Residential	DENVER	Domestic	398	398	338
0,77	3310	203070	511510	O WHEI	,, en constructed	STATE BOARD OF		on (construction report)	residential	DENVER	Domosie	370	370	550
(00	3377	62402 E	545120	Ow	Well Construct	LAND COMMISSIONERS	2	Well (Amaliantina /Dama is)	Company 1 Pro	ARAPAHOE	Industrial Marris 1	1538	1,400	007
698	33//	63493-F	545128	Owner	Well Constructed	COMINIESSIONERS	3	Well (Application/Permit)	General Purpose	AKAPAHUE	Industrial, Municipal	1338	1498	996
				_										
699	3378	267553-	546659	Owner	Well Constructed	DAVIDSON, GREGORY	18	Well (Application/Permit)	Residential	DENVER	Domestic	598	598	318

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
700	3379	98930A	547294	Owner	Well Constructed	LAVERENZ, BETH	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	420	420	380
701	3380	94212 F	10000150	0	Wall Canadan da I	EDELIND VENNETH I	11	Well (Construction Process)	Consul Province	UPPER ARAPAHOE	Augmentation, Commercial, Fire, Industrial, Irrigation,	1020		
701 702	3380	84212-F 317418-	10000159	Owner Owner	Well Constructed Well Constructed	FREUND, KENNETH J. 7-ELEVEN INC (STORE #26803)	29	Well (Construction Report) Well (Construction Report)	General Purpose Monitoring/Observation	ARAPAHUE	Other Monitoring/Sampling	1020		
702	3301	317110	10003010	o wher	Well constructed	1120003)	2)	wen (construction report)	Womening Good varion		Tromoring Sumpring			
703	3382	319268-	10005966	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	30		
704	3383	319269-	10005967	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	47		
705	3384	319270-	10005968	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Samplin	45		
											Monitoring/Samplin			
706	3385	319272-	10005969	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		g	35		
707	3386	319273-	10005970	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	35		
708	3387	319274-	10005971	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	20		
709	3388	319275-	10005972	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Samplin g	18		
710	3389	319656-	10005973	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	35		
711	3390	319725-	10007055	Owner	Well Constructed	BEHM, ROSS	18	Well (Construction Report)	Residential	DENVER	Domestic	420		
712	3391	320175-	10007667	Owner	Well Constructed	CITY OF AURORA	8	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	20		
713	3392	68752A	10009993	Owner	Well Constructed	FOLKERDS, JOSHUA	22	Well (Construction Report)	Residential	LOWER DAWSON	Domestic	235	235	35

OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
714	3393	321423-	10010195	Owner	Well Constructed	GILCHRIST, PHILIP	26	Well (Construction Report)	Residential	DENVER	Domestic	340		
715	3394	321423-	10010195	Owner	Well Constructed	TESANOVIC, BARBARA	26	Well (Construction Report)	Residential	DENVER	Domestic	340		
713	3374	321423-	10010173	Owner	Well Constructed	DANDAKA	20	wen (construction report)	Residential	DEIVVER	Donestic	340		
716	3395	321096-	10010488	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	22		
717	3396	322403-	10011151	Owner	Well Constructed	MADDOX, LOUISE	22	Well (Construction Report)	Residential	DENVER	Domestic	345		
718	3397	69255A	10018351	Owner	Well Constructed	VINCENT, ELAINE	18	Well (Construction Report)	Residential	DENVER	Domestic	690		
719	3398	50985A	10021339	Owner	Well Constructed	BROADHURST, KENNETH L.	22	Well (Construction Report)	Residential	DENVER	Domestic	480		
720	3399	74891A	3608855	Owner	Well Constructed	GOLDEN BRIAN J & MARILYN E	22	Well (Application/Permit)	Residential	DENVER	Domestic	578	558	478
721	3400	271458-	3609262	Owner	Well Constructed	MARGINEANU GHEORGHE CORNELIU	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	865	1080	940
,,,,	3.00	271.00	300)202	S Wales	THE COMPANIES	WASTE MANAGEMENT OF	,	, en (r.ppneauour enne)	100,000,000	ALL UNNAMED			1000	7.0
722	3401	271109-	3609585	Owner	Well Constructed	COLORADO	31	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	29	27	17
723	3402	271433-	3610296A	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	30	30	20
724	3403	271434-	3610296B	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	35	35	25
725	3404	271435-	3610296C	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	40	39	24
123	3404	2/1433-	30102700	Owner	wen constructed	ACKORA CITT OI	10	wen (Application) emility	Womoning Oosel vacion	DAWSON	Womtoring/Sampling	40	37	27
726	3405	271436-	3610296D	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	60	60	50
727	3406	271441-	3610296I	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	40	40	30
728	3407	271442-	3610296J	Owner	Well Constructed	AURORA CITY OF	16	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	50	40	30
							9		-					
729	3408	271443-	3610296K	Owner	Well Constructed	AURORA CITY OF	9	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	25	25	15
730	3409	273574-	3614833	Owner	Well Constructed	GLAU, DEAN	22	Well (Application/Permit)	Residential	DENVER	Domestic	365	365	325

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
012	Map 15		песере	1155001, pc	Termostatus	WASTE	Section	LocationType	Termiventegory	uquiter 1_nume	0.001	Берен	goottom	grop
731	3410	274153-	3617896A	Owner	Well Constructed	MANAGEMENT OF COLORADO INC	5	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	55	44	24
/31	3410	2/4133-	3017890A	Owner	Well Constitucted	WASTE	3	wen (Application/Fernit)	Wolltoring/Ooservation	DAWSON	Wolntoring/Sampling	33	44	24
500			24,50045			MANAGEMENT OF	_			D. WIGON				
732	3411	274154-	3617896B	Owner	Well Constructed	COLORADO INC WASTE	5	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	25	17	7
						MANAGEMENT OF								
733	3412	274155-	3617896C	Owner	Well Constructed	COLORADO INC	5	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	51	20	10
734	3413	274156-	3617896D	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	5	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	61	52	32
						WASTE					5 1 5			
735	3414	274157-	3617896E	Owner	Well Constructed	MANAGEMENT OF COLORADO INC	5	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	35	23	13
733	3414	2/413/-	3017070L	Owner	Well Collstructed	COLORADO INC		wen (Application/1 crinit)	Wontornig/Observation	DAWSON	Wolffornig/Sampring	33	23	13
726	2415	146700 A	2610042	Ovv	Wall Constructed	DI ANEV MADGITALI	24	Wall (Amuliantian/Domnit)	Davidantial	DENVED	Hayaahald yaa auly	563	562	442
736	3415	146709A	3619942	Owner	Well Constructed	BLANEY, MARSHALL	24	Well (Application/Permit)	Residential	DENVER	Household use only	303	563	443
										UPPER				
737	3416	275451-	3621679	Owner	Well Constructed	CHAPMAN, WENDELL	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1080	1080	925
						GEORGE MIKE &								
738	3417	275812-	3621946	Owner	Well Constructed	PATTY	22	Well (Construction Report)	Residential	DENVER	Domestic	545	545	325
										UPPER				
739	3418	276285-	3624196	Owner	Well Constructed	CRUICKSHANK, JAMES	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1100	1100	970
763	3442	123652A	3631987	Owner	Well Constructed	LUCERO, DONALD	22	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	340
						STATE BOARD OF								
772	3451	67968-F	3638215	Owner	Well Constructed	LAND COMMISSIONERS	11	Well (Application/Permit)	General Purpose	ALLUVIAL	Industrial	43	38	11
773	3452	282102-	3643157	Owner	Well Constructed	STREETMAN, NANCY	26	Well (Application/Permit)	Residential	LOWER DAWSON	Household use only			
773	3132	202102	3013137	O WHEI	Well Collisiance	STREETIMEN, WHITE		vien (rippheation)	residential	Brivisori	Trousenora use only			
774	3453	70012 F	26446994	0	Wall Constructed	NEMEC IEEE	10	W-11 (A1:4:/D:4)	C1 P	ALL UNNAMED	Other	40	46	26
//4	3433	70012-F	3644688A	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	General Purpose	AQUIFERS	Other	48	46	26
	_									ALL UNNAMED				
775	3454	70013-F	3644688B	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	General Purpose	AQUIFERS	Other	45	45	25
										ALL UNNAMED				
776	3455	70014-F	3644688C	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	General Purpose	AQUIFERS	Other			
										ALL UNNAMED				
777	3456	70015-F	3644688D	Owner	Well Constructed	NEMEC, JEFF	19	Well (Construction Report)	General Purpose	AQUIFERS	Other	38	35	15
										ALL UNNAMED				
780	3459	283007-	3644688G	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	Monitoring/Observation	AQUIFERS	Monitoring/Sampling	49	49	44

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
781	3460	283008-	3644688Н	Owner	Well Constructed	NEMEC, JEFF	19	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	50	50	45
782	3461	69656-F	3645723A	Owner	Well Constructed	DENVER CITY & CNTY DEPT OF ENV HEALTH	6	Well (Application/Permit)	General Purpose	ALLUVIAL	Other			
783	3462	69657-F	3645723B	Owner	Well Constructed	DENVER CITY & CNTY DEPT OF ENV HEALTH	31	Well (Application/Permit)	General Purpose	ALLUVIAL	Other			
785	3464	60327A	3647743	Owner	Well Constructed	TRUE CREEK LLC (ROEPKE, AMY L.)	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	55	55	19
786	3465	285176-	3649160	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	25	15
787	3466	285874-	3650534	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO INC	31	Well (Application/Permit)	Monitoring/Observation	DAWSON	Monitoring/Sampling	49	49	39
788	3467	75887-F	3653309	Owner	Well Constructed	FREUND LINDA J & KENNETH J FREUND, SR	18	Well (Application/Permit)	General Purpose	UPPER ARAPAHOE	Industrial, Municipal	1034		
790	3469	287616-	3653757B	Owner	Well Constructed	FREUND KENNETH J SR	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	27		
798	3477	290508-	3659064A	Owner	Well Constructed	WEMLINGER WATER TREATMENT PLANT	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	25	25	15
799	3478	290509-	3659064B	Owner	Well Constructed	WEMLINGER WATER TREATMENT PLANT	9	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	21	21	10
800	3479	290510-	3659064C	Owner	Well Constructed	WEMLINGER WATER TREATMENT PLANT	4	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31	31	20
809	3488	77650-F	3661872B	Owner	Well Constructed	ARAPAHOE COUNTY OPEN SPACE	8	Well (Application/Permit)	General Purpose	UPPER ARAPAHOE	Industrial, Irrigation	1345	1305	1180
811	3490	293423-	3663433	Owner	Well Constructed	CARNAHAN, BENJAMIN K.	18	Well (Application/Permit)	Residential	DENVER	Domestic			
812	3491	293423-	3663433	Owner	Well Constructed	CARNAHAN, RACHEL L.	18	Well (Application/Permit)	Residential	DENVER	Domestic			
813	3492	77883-F	3663460	Owner	Well Constructed	RANGEVIEW METROPOLITAN DISTRICT	11	Well (Application/Permit)	General Purpose	LARAMIE-FOX HILLS	Industrial, Municipal	2047	2000	1790
814	3493	294215-	3664287	Owner	Well Constructed	GOOD BRIAN & CASSIE	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1085	1085	940
815	3494	236034A	3665429	Owner	Well Constructed	NELSON GARY AND KAREN	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1110	1110	945

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
816	3495	296780-	3668174	Owner	Well Constructed	7-ELEVEN INC - STORE #20909	29	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30	30	15
817	3496	230526A	3668176	Owner	Well Constructed	REID. MARIO S.	22	Well (Application/Permit)	Residential	DENVER	Domestic	460	460	400
						,								
818	3497	230526A 296831-	3668176 3668284	Owner	Well Constructed Well Constructed	CONNER, SHAUNA S. BAIRD GAIL & LAWRENCE	18	Well (Application/Permit) Well (Application/Permit)	Residential Residential	DENVER UPPER ARAPAHOE	Domestic	1106	460 1106	400 980
820	3499	297322-	3668829Н	Owner	Well Constructed	EAST CHERRY CR VALLEY WATER & SAN DIST	2	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	45	45	25
821	3500	79010-F	3669230	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SAN	24	Well (Application/Permit)	General Purpose	ARAPAHOE	Industrial, Municipal, Other	1944		
822	3501	297458-	3669473	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER AND	24	Well (Application/Permit)	Monitoring/Observation	ARAPAHOE	Monitoring/Sampling	1957		
824	3503	298210A	3670682B	Owner	Well Constructed	HERNANDEZ CUTBERTO & MARTHA	11	Well (Construction Report)	Residential	DENVER	Domestic	580	580	420
825	3504	300339-	3673311	Owner	Well Constructed	ACEVEDO MARIO & JUANA	18	Well (Construction Report)	Residential	ARAPAHOE	Domestic	10		
826	3505	300594-	3673388A	Owner	Well Constructed	PETROLEUM (BRADLEY PETROLEUM)	10	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	22		
827	3506	300595-	3673388B	Owner	Well Constructed	PETROLEUM (BRADLEY PETROLEUM)	10	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	22		
828	3507	302207-	3675246	Owner	Well Constructed	CMH HOMES INC DBA	7	Well (Construction Report)	Residential	DENVER	Domestic	860		
829	3508	138725A	3676105	Owner	Well Constructed	HULL DONALD & CYNTHIA	7	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	1110	1110	870
831	3510	302794-	3676343	Owner	Well Constructed	SMITH, JERRY E	26	Well (Application/Permit)	Residential	DENVER	Domestic	680	680	560
832	3511	303413-	3676388	Owner	Well Constructed	WASTE MANAGEMENT OF COLORADO	32	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	99		
833	3512	304010-	3677074D	Owner	Well Constructed	7-ELEVEN INC (STORE #26803)	29	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30		
834	3513	304011-	3677074E	Owner	Well Constructed	7-ELEVEN INC (STORE #26803)	29	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
835	3514	304012-	3677074F	Owner	Well Constructed	7-ELEVEN INC (STORE #26803)	29	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30		
836	3515	304013-	3677074G	Owner	Well Constructed	7-ELEVEN INC (STORE #26803)	29	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	30		
837	3516	307537-	3683428	Owner	Well Constructed	GUZMAN, JOSE J.	18	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1108		
838	3517	308060-	3683715	Owner	Well Constructed	YOHN, CODY	18	Well (Construction Report)	Residential		Domestic, Stock	1109		
839	3518	165972A	3684192	Owner	Well Constructed	MARTINEZ, JASON	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1080		
840	3519	17489-F-R	3685945	Owner	Well Constructed	EAST CHERRY CREEK VALLEY WATER & SANITATION	23	Well (Construction Report)	General Purpose	АКАРАНОЕ	Commercial, Domestic, Fire, Fishery, Industrial, Irrigation, Municipal, Recreation, Stock, Wildlife	1724		
841	3520	271458A	3688129	Owner	Well Constructed	CORNELIU, MARGINEANU G.	7	Well (Construction Report)	Residential	UPPER ARAPAHOE	Domestic	1050		
842	3521	311804-	3688683	Owner	Well Constructed	HENRY, WILLIAM	23	Well (Construction Report)	Residential	UPPER DAWSON	Domestic	380		
843	3522	313871-	3690290A	Owner	Well Constructed	CITY OF AURORA	7	Well (Construction Report)	Monitoring/Observation	DENVER	Monitoring/Sampling	36		
844	3523	313874-	3690290D	Owner	Well Constructed	CITY OF AURORA	8	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	26		
845	3524	313876-	3690290F	Owner	Well Constructed	CITY OF AURORA	8	Well (Construction Report)	Monitoring/Observation	DENVER	Monitoring/Sampling	41		
846	3525	313884-	3690290N	Owner	Well Constructed	CITY OF AURORA	20	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	41		
847	3526	313885-	3690290O	Owner	Well Constructed	CITY OF AURORA	21	Well (Construction Report)	Monitoring/Observation	DAWSON	Monitoring/Sampling	41		
848	3527	313886-	3690290P	Owner	Well Constructed	CITY OF AURORA	28	Well (Construction Report)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	31		
849	3528	37665-F-R	3691563	Owner	Well Constructed	CITY & COUNTY OF DENVER DEPT OF PUBLIC HEALTH & EN (DELILLIO, DIANE)	6	Well (Construction Report)	General Purpose	UPPER ARAPAHOE	Industrial	1260		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
OID	Map 15	1 Climer (uniper	песен	rissoc Type	Termitistatus	Contact vanie	Section	LocationType	renmedicigory	aquiter 1_nume	Osci	Бери	gBottom	grop
850	3529	320953-	3691716A	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	35		
851	3530	320954-	3691716B	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	27		
852	3531	320955-	3691716C	Owner	Well Constructed	CITY OF AURORA	13	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	25		
853	3532	320956-	3691716D	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	38		
854	3533	320957-	3691716E	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	42		
855	3534	320958-	3691716F	Owner	Well Constructed	CITY OF AURORA	24	Well (Construction Report)	Monitoring/Observation		Monitoring/Sampling	33		
856	3535	314851-	3693665	Owner	Well Constructed	LOERA, MAURO	15	Well (Construction Report)	Residential	LOWER DAWSON	Domestic	505	505	425
857	3536	97703A	3693670	Owner	Well Constructed	POLADSKY, JULIA	22	Well (Construction Report)	Residential	DENVER	Domestic	580		
858	3537	97703A	3693670	Owner	Well Constructed	DRISCOLL, MICHAEL	22	Well (Construction Report)	Residential	DENVER	Domestic	580		
859	3538	230-	9005311	Owner	Well Constructed	CIVIL AERONAUTCS ADM	29	Well (Application/Permit)	Residential	DENVER	Domestic			
860	3539	667-	9005351	Owner	Well Constructed	PRUTTING, KENNETH C	23	Well (Application/Permit)	Residential	DENVER	Domestic	425	425	225
										ALL UNNAMED				
861	3540	2406-F	9005464	Owner	Well Constructed	US GOVERNMENT	5	Well (Application/Permit)	General Purpose	AQUIFERS	Other	1570		
862	3541	3080-	9005529	Owner	Well Constructed	MILLER, BERT	15	Well (Application/Permit)	Residential	DENVER	Domestic	490		
863	3542	3201-	9005539	Owner	Well Constructed	COOPER, H E	18	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	790		
864	3543	4821-F	9005654	Owner	Well Constructed	SMITH, WILBUR W	17	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	25		

0.00	3/	5 45			D 100				D 110					PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
865	3544	6671-	9005756	Owner	Well Constructed	MAYS, WILLIE	19	Wall (Amuliantian/Domnit)	Residential	DENVER	Domostio	595		
803	3344	00/1-	9003736	Owner	well Constructed	MAYS, WILLIE	19	Well (Application/Permit)	Residential	DENVER	Domestic	393		
866	3545	10401-	9005904	Owner	Well Constructed	ABRAHAMSEN, MARTIN	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	45		
800	3343	10401-	7003704	Owner	Well Collstracted	WAKTIIV	12	wen (Application) termit)	Residential		Stock	73		
867	3546	11192-F	9005947	Owner	Well Constructed	FREUND & COMPANY	18	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	27	27	17
								\ 11	<u>.</u>		<u> </u>			
868	3547	12763-	9006010	Owner	Well Constructed	MAYES, WILLIE	19	Well (Application/Permit)	Residential	DENVER	Domestic	237		
869	3548	12883-	9006016	Owner	Well Constructed	WILLIAMS, KATHLEEN	28	Well (Application/Permit)	Residential	DENVER	Domestic	612		
870	3549	13027-	9006022	Owner	Well Constructed	DAVIDSON, HOWARD	24	Well (Application/Permit)	Residential	DENVER	Stock	185		
										ALL UNNAMED				
871	3550	13179-	9006036	Owner	Well Constructed	SMITH, PAUL	20	Well (Application/Permit)	Residential	AQUIFERS	Stock	44		
872	3551	13180-	9006037	Owner	Well Constructed	CASSELL, BOB	3	Well (Application/Permit)	Residential	DENVER	Domestic	223		
										ALL				
874	3553	13445-	9006055	Owner	Well Constructed	CHAPPELL, CHARLES W	11	Well (Application/Permit)	Residential	UNNAMED AQUIFERS	Domestic	40		
								. 11		ALL IDDIAMED				
875	3554	13447-F	9006056	Owner	Well Constructed	SMITH, WILBAR	17	Well (Application/Permit)	General Purpose	ALL UNNAMED AQUIFERS	Irrigation	27		
										ALL UNNAMED				
876	3555	14344-	9006099	Owner	Well Constructed	DIXON, LESTER	4	Well (Application/Permit)	Residential	AQUIFERS	Domestic	95		
						WEST ARAPAHOE SOIL				QUATERNARY				
877	3556	14661-	9006113	Owner	Well Constructed	CONSERVA	25	Well (Application/Permit)	Residential	ALLUVIUM	Stock	57		
						SMOKY HILLS				ALL UNNAMED				
878	3557	17491-F	9006272	Owner	Well Constructed	VENTURE CO	16	Well (Application/Permit)	General Purpose	AQUIFERS	Municipal	1688		
						SMOKY HILLS				ALL UNNAMED				
879	3558	17492-F	9006273	Owner	Well Constructed	VENTURE CO AURORA PUBLIC	14	Well (Application/Permit)	General Purpose	AQUIFERS	Municipal	1687		
222	2550	20102 5	000/207		W. II G	SCHOOLS (AURORA	20	****	G 17	ALL UNNAMED		1260		
880	3559	20192-F	9006395	Owner	Well Constructed	PUBLIC SCHOOLS)	28	Well (Application/Permit)	General Purpose	AQUIFERS	Irrigation	1360		
001	2560	20027	0006444	Overse	Wall Constructs 1	APNOLD VIDGILE	10	Woll (Appliestion/Downit)	Panidantial	DENVED	Domestic	600		
881	3560	20987-	9006444	Owner	Well Constructed	ARNOLD, VIRGIL E	19	Well (Application/Permit)	Residential	DENVER	Domestic	600		

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
882	3561	22246-	9006472	Owner	Well Constructed	BUCKLEY INVESTMENT COMP	30	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	70		
883	3562	22724-	9006481	Owner	Well Constructed	COOPER, THOMAS	18	Well (Application/Permit)	Residential	DENVER	Domestic	665	662	553
884	3563	23500-	9006509	Owner	Well Constructed	LLOYD, FRANCIS	1	Well (Application/Permit)	Residential	DENVER	Stock	270		
885	3564	27087-	9006582	Owner	Well Constructed	DOELL, RICHARD	18	Well (Application/Permit)	Residential	DENVER	Domestic	735	697	560
886	3565	27284-	9006592	Owner	Well Constructed	HUBBARD, H S	11	Well (Application/Permit)	Residential	DENVER	Domestic	100		
887	3566	27387-	9006593	Owner	Well Constructed	SMITH, B E	12	Well (Application/Permit)	Residential	DENVER	Domestic	140		
888	3567	28195-M	9006619	Owner	Well Constructed	DENVER ENVIRONMENTAL SRVCS	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	20	28	18
889	3568	28210-M	9006625	Owner	Well Constructed	DENVER ENVIRONMENTAL SRVCS	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	355	350	310
890	3569	28212-M	9006627	Owner	Well Constructed	DENVER ENVIRONMENTAL SRVCS	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	100	95	75
891	3570	28214-M	9006629	Owner	Well Constructed	DENVER ENVIRONMENTAL SRVCS	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling	155	145	125
892	3571	31068-	9006674	Owner	Well Constructed	MILLER, BURT	29	Well (Application/Permit)	Residential	UPPER DAWSON	Stock	224		
893	3572	31073-	9006675	Owner	Well Constructed	NEMNICK, LOUIS A	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	40	40	20
894	3573	31351-	9006683	Owner	Well Constructed	MOSS, HOWARD	29	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	1007		
895	3574	31356-	9006684	Owner	Well Constructed	WILEY, BERTHA	11	Well (Application/Permit)	Residential	DENVER	Domestic	250		
896	3575	31822-M	9006714	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVCE	31	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling			
897	3576	31826-M	9006718	Owner	Well Constructed	DENVER ENVIRONMENTAL SERVCE	6	Well (Application/Permit)	Monitoring/Observation	ALL UNNAMED AQUIFERS	Monitoring/Sampling			

												CompletedWell	PerforatedCasin	Doufoueted Cosin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
898	3577	31905-	9006735	Owner	Well Constructed	VINCENT MURPHY CHEV CO INC	8	Well (Application/Permit)	Residential	LOWER DAWSON	Stock	356		
899	3578	32277-	9006743	Owner	Well Constructed	BIG BAIT CO INC	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	30		
900	3579	34195A	9006773A	Owner	Well Constructed	CITY OF AURORA (GODWIN, JOSHUA)	35	Well (Construction Report)	Residential	DENVER	Domestic	400		
901	3580	34482-	9006776	Owner	Well Constructed	NASH, BENNIE	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	35	35	5
902	3581	35635-	9006798	Owner	Well Constructed	SMITH, PAUL H	16	Well (Application/Permit)	Residential	DENVER	Stock	688		
903	3582	36105-	9006802	Owner	Well Constructed	RIPPE, EMIL	25	Well (Application/Permit)	Residential	DENVER	Stock	541		
904	3583	36817-	9006822	Owner	Well Constructed	SEELEY HARVEY E JR	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	30	30	10
905	3584	37743-	9006832	Owner	Well Constructed	MILLER, VERNON S	14	Well (Application/Permit)	Residential	DENVER	Domestic	570		
906	3585	37867-	9006834	Owner	Well Constructed	EAST BAYAUD PARTNERS LLC	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	45	45	18
907	3586	40172-	9006866	Owner	Well Constructed	STARLING RYAN C & LORI L MCNEILLY	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	703	690	361
908	3587	40228-	9006868	Owner	Well Constructed	BECKER, HERBERT	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock	32	070	301
909	3588	41075-	9006895	Owner	Well Constructed	SMITH, MARVIN E	30	Well (Application/Permit)	Residential	DENVER	Domestic Domestic	573		
910	3589	42112-	9006918	Owner	Well Constructed	FIX, MAURICE J	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	42		
911	3590	42163-	9006919	Owner	Well Constructed	TAYLOR, DAVID D	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	40		
													022	((0)
912	3591	42926-	9006935	Owner	Well Constructed	MONROE, HELEN	18	Well (Application/Permit)	Residential	DENVER	Domestic	822	822	668
913	3592	43732-	9006947	Owner	Well Constructed	ARMATO, MIKE	28	Well (Application/Permit)	Residential	DENVER	Domestic	635		
914	3593	44424-	9006960	Owner	Well Constructed	GRIMM, ALBERT	23	Well (Application/Permit)	Residential	DENVER	Domestic	748		

OID	Map ID ^{a/}	PermitNumber	Receipt	A	PermitStatus	ContactName	G4	LocationType	Provide Assessment		Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin
OID	Map 1D	rerinitivumber	Кесеірі	AssocType	rermitstatus	Contactivame	Section	LocationType	PermitCategory	aquifer1_name	Usei	Бери	gbottom	gTop
915	3594	44768-	9006965	Owner	Well Constructed	WICKHAM, J E	15	Well (Application/Permit)	Residential	DENVER	Domestic	550		
916	3595	45116-	9006971	Owner	Well Constructed	JOHNSON, NORMAN D	16	Well (Application/Permit)	Residential	DENVER	Domestic	351		
917	3596	45188-	9006972	Owner	Well Constructed	TORRES, MAX D	12	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	54		
918	3597	45276-	9006974	Owner	Well Constructed	TEPPER, EUGENE X	29	Well (Application/Permit)	Residential	UPPER DAWSON	Domestic	228		
919	3598	45338-	9006977	Owner	Well Constructed	HENDRICK, K E	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic			
920	3599	46126-	9006996	Owner	Well Constructed	MUNOZ, ROGELIO	18	Well (Application/Permit)	Residential	DENVER	Domestic	840	840	320
921	3600	48010-	9007028	Owner	Well Constructed	RAINS, DONALD	29	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	36		
922	3601	48177-	9007030	Owner	Well Constructed	ELVEAN, CLYDE W	18	Well (Application/Permit)	Residential	DENVER	Domestic	600	600	540
923	3602	48208-	9007031	Owner	Well Constructed	SMITH, PAUL H	20	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	32		
723	3002	40200	7007031	Owner	wen constructed	SMITH, TAGE II	20	wen (Applications) emility	residential	AQUII ERO	Domestic	32		
924	3603	48417-	9007034	Owner	Well Constructed	WELLS, RAYMOND R	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	670	670	320
925	3604	48820-	9007045	Owner	Well Constructed	BUCHER, JACK E	23	Well (Application/Permit)	Residential	DENVER	Domestic	200		
926	3605	49186-	9007060	Owner	Well Constructed	SEELEY HARVEY E JR	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	28	28	15
927	3606	49187-	9007061	Owner	Well Constructed	SEELEY HARVEY E JR	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	28	28	9
928	3607	49851-	9007069	Owner	Well Constructed	JACKSON J M & BETTY	15	Well (Application/Permit)	Residential	DENVER	Domestic	454	454	334
929	3608	49876-	9007070	Owner	Well Constructed	ATTEBERRY, HAROLD	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Stock	30	30	10
930	3609	50228-	9007077	Owner	Well Constructed	HAINES, CARL J	14	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	713		
931	3610	50376-	9007078	Owner	Well Constructed	KIBBLE, ALBERT F	15	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic	630		

APPENDIX C-7 SUMMARY OF PERMITTED WATER WELLS LOCATED WITHIN FIVE MILES OF THE SITE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT

LOWRY LANDFILL SUPERFUND SITE

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1 name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
OID	Wap ID	rerinitivumber	Кесеірі	Associype	refinitstatus	Contactivame	Section	LocationType	refinitCategory	aquirer i_name	USEI	Depth	gBottom	grop
022	2611	50001	0007006		W. II G	EAST IOE S	10	W 11 (A 1: (* (B ::)	B 11 11	DEMED	.	722	722	620
932	3611	50801-	9007086	Owner	Well Constructed	EAST, JOE C LUNA-LLANES	18	Well (Application/Permit)	Residential	DENVER	Domestic	733	733	630
						REALTY LLC (LUNA-								
934	3613	56580-	9007158	Owner	Well Constructed	LLANES, FERNANDO)	18	Well (Application/Permit)	Residential	DENVER	Domestic	605	605	350
935	3614	58067-	9007172	Owner	Well Constructed	MCCLURE, JOHN E	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	620	450
936	3615	61239-	9007204	Owner	Well Constructed	ALLMAN, JOHN H	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	620	450
						BILLERA CHARLES &								
937	3616	63258-	9007236	Owner	Well Constructed	DEBORAH	22	Well (Application/Permit)	Residential	DENVER	Domestic	280	280	120
938	3617	63491-	9007241	Owner	Well Constructed	MANN, ROBERT B	18	Well (Application/Permit)	Residential	DENVER	Domestic	630	630	500
						CAMERON, DUNCAN								
939	3618	63894-	9007248	Owner	Well Constructed	W	19	Well (Application/Permit)	Residential	DENVER	Domestic	527	527	240
940	3619	66570-	9007267	Owner	Well Constructed	MUELLER, LYNA	22	Well (Application/Permit)	Residential	DENVER	Domestic	250	250	140
941	3620	66879-	9007276	Owner	Well Constructed	ESPINOZA, RAFAEL R.	18	Well (Application/Permit)	Residential	DENVER	Domestic	750	750	485
						VARELA, MARIA DE								
942	3621	66879-	9007276	Owner	Well Constructed	ROCIO V.	18	Well (Application/Permit)	Residential	DENVER	Domestic	750	750	485
943	3622	66892-	9007277	Owner	Well Constructed	MCCLURE, JOHN E	18	Well (Application/Permit)	Residential	DENVER	Domestic	620	620	360
944	3623	67504-	9007283	Owner	Well Constructed	NASH, BENNIE E	18	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	720	720	310
						KARCZEWSKI CASMIR								
945	3624	67524-	9007284	Owner	Well Constructed	& MARIA	18	Well (Application/Permit)	Residential	DENVER	Domestic			
946	3625	67859-	9007291	Owner	Well Constructed	POOL, ROBERT L	18	Well (Construction Report)	Residential	DENVER	Domestic			
947	3626	68350-	9007298	Owner	Well Constructed	CARPENTER, PATSY P	18	Well (Application/Permit)	Residential	DENVER	Stock			
948	3627	68576-	9007304	Owner	Well Constructed	MOCK, EDWARD F	22	Well (Application/Permit)	Residential	DENVER	Domestic			
										LOWER				
949	3628	68620-	9007306	Owner	Well Constructed	FOSTER, DAVID I	22	Well (Application/Permit)	Residential	DAWSON	Domestic			

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
950	3629	68750-	9007308	Owner	Well Constructed	MORTON, JOHN W.	22	Well (Application/Permit)	Residential	DENVER	Domestic			
951	3630	68751-	9007309	Owner	Well Constructed	FERGUSON DAVID & KATHY	22	Well (Application/Permit)	Residential	DENVER	Domestic			
952	3631	68753-	9007311	Owner	Well Constructed	BERRY LYNDON G & BERRY CHARLOTTE A	22	Well (Application/Permit)	Residential	DENVER	Domestic			
953	3632	69255-	9007320	Owner	Well Constructed	VINCENT ELAINE F & BEATRICE M	18	Well (Application/Permit)	Residential	DENVER	Domestic			
954	3633	69964-	9007331	Owner	Well Constructed	HOLWELL RAYMOND V JR	22	Well (Application/Permit)	Residential	DENVER	Domestic	240	240	160
955	3634	71155-	9007347	Owner	Well Constructed	FIGG, IRIS J	11	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Domestic, Stock			
956	3635	71335-	9007351	Owner	Well Constructed	PASTERNAK RONALD C & ELSIE L	22	Well (Construction Report)	Residential	DENVER	Domestic			
957	3636	71350-	9007352	Owner	Well Constructed	BONO, RICHARD J	18	Well (Application/Permit)	Residential	DENVER	Domestic			
958	3637	72417-	9007362	Owner	Well Constructed	SHACKELFORD W MONTE	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
959	3638	72555-	9007366	Owner	Well Constructed	OVERSTREET, ROBERT L	18	Well (Application/Permit)	Residential	DENVER	Domestic	489	480	400
960	3639	74043-	9007384	Owner	Well Constructed	TORLUEMKE, G D	22	Well (Application/Permit)	Residential	DENVER	Domestic	220	220	120
961	3640	74774-	9007391	Owner	Well Constructed	LONG, JOHN G	18	Well (Application/Permit)	Residential	ALL UNNAMED AQUIFERS	Household use only	30	30	10
962	3641	75107-	9007400	Owner	Well Constructed				Residential	DENVER	Domestic			
963	3642	75491-	9007409	Owner	Well Constructed	QUICK, CALVIN J	30	Well (Application/Permit)	Residential	UPPER DAWSON	Stock			
965	3644	76356-	9007425	Owner	Well Constructed	COLORADO PARKS AND WILDLIFE	17	Well (Application/Permit)	Residential	UPPER DAWSON	Domestic	182		
966	3645	79290-	9007465	Owner	Well Constructed	LOEHR JAMES & CYNTHIA	22	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	130	130	100
967	3646	79295-	9007466	Owner	Well Constructed	SAS HEALTH SERVICES LLC	7	Well (Application/Permit)	Residential	DENVER	Domestic	605	605	325

				<u> </u>		<u> </u>				1 1		1		
	-1											CompletedWell		PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
969	3648	80116-	9007475	Owner	Well Constructed	CRANE, DONALD	22	Well (Application/Permit)	Residential	DENVER	Domestic	275		
						MADDOX DAVID &								
970	3649	81536-	9007499	Owner	Well Constructed	LYNDA	22	Well (Application/Permit)	Residential	DENVER	Domestic	280	280	240
971	3650	81715-	9007502	Owner	Well Constructed	KLEIN, SIGI	22	Well (Application/Permit)	Residential	DENVER	Domestic	320	320	300
973	3652	83399-	9007523	Owner	Well Constructed	MOSS, HAROLD B	22	Well (Application/Permit)	Residential	DENVER	Domestic	328	328	288
974	3653	84987-	9007556	Owner	Well Constructed	HERMES, TIMOTHY	22	Well (Application/Permit)	Residential	DENVER	Domestic	368		
						,		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \						
975	3654	84989-	9007557	Owner	Well Constructed	HERMES, KENNETH J	22	Well (Application/Permit)	Residential	DENVER	Domestic	315		
		1 1111	, , , , , , , ,	2				· · · · · (
977	3656	86189-	9007571	Owner	Well Constructed	OLIVARES, GABRIEL P.	. 22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
211	3030	00107-	7007371	Owner	wen constructed	OLIVARES, GABRIEL I	. 22	wen (Application/1 crinit)	Residential	BLIVVER	Domestic, Stock			
079	2657	97190	0007571	0	W-11 Countries to 1	OLIVARES,	22	W-11 (A1:4:/D4)	D: 14:-1	DENIVER	D			
978	3657	86189-	9007571	Owner	Well Constructed	CATHERINE S.	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
979	3658	86313-	9007575	Owner	Well Constructed	MILLER, STEVEN G	22	Well (Application/Permit)	Residential	DENVER	Domestic			
						CARLEVATO,								
980	3659	86378-	9007576	Owner	Well Constructed	NORMAN J	27	Well (Application/Permit)	Residential	DENVER	Domestic	-		
										LOWER				
981	3660	86379-	9007577	Owner	Well Constructed	SMALL, BONNIE	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
						HADDON WILLIAM R				LOWER				
982	3661	86380-	9007578	Owner	Well Constructed	& CATHY R	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
983	3662	86381-	9007579	Owner	Well Constructed	RADI, MOHAMED	26	Well (Application/Permit)	Residential	DENVER	Domestic			
984	3663	86443-	9007580	Owner	Well Constructed	MUNDHENKE, HANS	22	Well (Application/Permit)	Residential	DENVER	Domestic			
								/						
985	3664	86717-	9007583	Owner	Well Constructed	MILES, LEONARD V	22	Well (Application/Permit)	Residential	DENVER	Domestic			
7.55						, 555,555,5								
986	3665	87449-	9007592	Owner	Well Constructed	FLORER, DICK	7	Well (Application/Permit)	Residential	DENVER	Domestic			
760	3003	0/17/	7001372	Owner	Well Collisiration	- LOILLI, DICK		on (Application) remite)	residential	DERVER	Domestic			
007	2000	07503	0007505	0-	W-II C- 1 1	MOEEITT WILLIAMS	26	W-11 (A nulline) /D (A	D:1 (1.1	LOWER	Dan C	275	275	225
987	3666	87593-	9007595	Owner	Well Constructed	MOFFITT, WILLIAM M	26	Well (Application/Permit)	Residential	DAWSON	Domestic	275	275	235

												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
988	3667	87626-	9007596	Owner	Well Constructed	HAMNER, ROBERT J	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock			
										LOWER				
989	3668	87834-	9007604	Owner	Well Constructed	CARLSON, LEE M	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
990	3669	88037-	9007609	Owner	Well Constructed	CARLSON, DOUGLAS	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic			
991	3670	88366-	9007613	Owner	Well Constructed	LOPEZ, PERRY	22	Well (Application/Permit)	Residential	DENVER	Domestic			
992	3671	88367-	9007614	Owner	Well Constructed	BRANTLEY ELIZABETH A & FAULK DANIEL	22	Well (Application/Permit)	Residential	DENVER	Domestic			
993	3672	89040-	9007624	Owner	Well Constructed	HENDERSON, ALLEN G	22	Well (Construction Report)	Residential	DENVER	Domestic			
994	3673	89133-	9007625	Owner	Well Constructed	SULTANOF, HARRY	27	Well (Application/Permit)	Residential	DENVER	Domestic			
995	3674	89138-	9007626	Owner	Well Constructed	SEDBROOK, JOHN	27	Well (Construction Report)	Residential	DENVER	Domestic			
996	3675	89540-	9007636	Owner	Well Constructed	PREESE JASON R & JANIS L	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic			
997	3676	89775-	9007641	Owner	Well Constructed	WALLNER, FRED	22	Well (Application/Permit)	Residential	DENVER	Domestic			
											2 cmesure			
998	3677	89836-	9007645	Owner	Well Constructed	HERNDON, DUSTIN J.	26	Well (Application/Permit)	Residential	DAWSON	Domestic	415		
999	3678	89836-	9007645	Owner	Well Constructed	HERNDON, AMANDA J.	26	Well (Application/Permit)	Residential	DAWSON	Domestic	415		
1000	3679	89836-	9007645	Owner	Well Constructed	SHIRACK, MICHAEL D.	26	Well (Application/Permit)	Residential	DAWSON	Domestic	415		
1001	3680	90939-	9007663	Owner	Well Constructed	SIPP PEGGY & JOHNSON VANCE M	22	Well (Application/Permit)	Residential	DENVER	Domestic			
1002	3681	90940-	9007664	Owner	Well Constructed	PIXLER, WILLIAM	22	Well (Construction Report)	Residential	DENVER	Domestic			
1003	3682	90941-	9007665	Owner	Well Constructed	BENSON, FRED	22	Well (Application/Permit)	Residential	DENVER	Domestic			
1004	3683	91175-	9007676	Owner	Well Constructed	MEAD, JOAN S	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic			

					1					1				
												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
1005	3684	91705-	9007682	Owner	Well Constructed	GROSVENOR, TODD	27	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
1006	3685	91705-	9007682	Owner	Well Constructed	GROSVENOR, DANNA	27	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
						POLLOCK JAMES E &								
1007	3686	91707-	9007683	Owner	Well Constructed	CARROL SUE	22	Well (Application/Permit)	Residential	DENVER	Domestic			
1000				_		KUSCHNEREIT RODY				LOWER				
1008	3687	91709-	9007684	Owner	Well Constructed	& CONNIE	26	Well (Application/Permit)	Residential	DAWSON	Domestic			
1000	2600	01711	0007606		W.H.C. 4 4 1	SWINNEY ROGER &	26	777 11 (A 1: 4: /D ::)	D 11 411	DEMED	D (
1009	3688	91711-	9007686	Owner	Well Constructed	CHRISTINE	26	Well (Application/Permit)	Residential	DENVER	Domestic			
1010	3689	92256-	9007698	Owner	Well Constructed	POPE JR JAMES E	18	Well (Application/Permit)	Residential	DENVER	Domestic			
1010	3007	72230-	7007070	Owner	wen constructed	TOTE SK SAMES E	10	wen (Application Fernit)	Residential	BLIVVER	Domestic			
1011	3690	92901-	9007708	Owner	Well Constructed	ANDERS, WILLIAM J	27	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic			
1011	3070	72701	7007700	o wher	Wen constructed		21	vven (rappheations remite)	residential	Brivisori	Bomosic			
1012	3691	92947-	9007711	Owner	Well Constructed	SCHLAGETER VALERIE & GARY	22	Well (Application/Permit)	Residential	DENVER	Domestic			
1013	3692	93173-	9007714	Owner	Well Constructed	MABIE BRENDA K & PHILLIP G	7	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	604	604	464
										LOWER				
1014	3693	93671-	9007719	Owner	Well Constructed	GILL, JASON	27	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock			
										LOWER				
1015	3694	93671-	9007719	Owner	Well Constructed	GILL, SHARON	27	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock			
1016	3695	93673-	9007720	Owner	Well Constructed	SCHEEL, DENNIS	26	Well (Application/Permit)	Residential	DAWSON	Domestic	404	404	204
						ZUKOWSKI, BARBARA				LOWER				
1017	3696	93816-	9007724	Owner	Well Constructed	J	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
										LOWER				
1018	3697	94020-	9007729	Owner	Well Constructed	BUSBY, RICHARD C	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
1020	3699	94022-	9007731	Owner	Well Constructed	BIGHORN, GINA R.	27	Well (Application/Permit)	Residential	DENVER	Domestic	1		
1021	3700	94022-	9007731	Owner	Well Constructed	BIGHORN, DANIEL C.	27	Well (Application/Permit)	Residential	DENVER	Domestic			
										LOWER				
1022	3701	94041-	9007734	Owner	Well Constructed	RACHAL, ROBERT M.	26	Well (Application/Permit)	Residential	DAWSON	Domestic			

		<u> </u>										<u> </u>		
												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID a/	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
1023	3702	94457-	9007740	Owner	Well Constructed	SLAGLE ELRIE VAN	16	Well (Application/Permit)	Residential	DENVER	Domestic			
1024	3703	95393-	9007754	Owner	Well Constructed	REED, JOHN	29	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
1024	3703	93393-	9007734	Owner	well Collstructed	REED, JOHN	29	wen (Application/Fermit)	Residential	DENVER	Domestic, Stock			
1025	3704	95907-	9007763	Owner	Well Constructed	POWERS, EDWARD D	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock			
1026	3705	96292-	9007777	Owner	Well Constructed	CLYMER, DON	26	Well (Application/Permit)	Residential	DENVER	Domestic			
						NIXON DAVE								
1027	3706	96548-	9007780	Owner	Well Constructed	&NORMA	26	Well (Application/Permit)	Residential	DAWSON	Domestic	344	344	304
1000	2505	26554	0005501			G1 (VT) 1 V . 1 TPD	2.5	*******	5 11 11	LOWER				
1028	3707	96554-	9007781	Owner	Well Constructed	SMITH, WALTER	27	Well (Application/Permit)	Residential	DAWSON	Domestic			
1029	3708	96647-	9007786	Owner	Well Constructed	PIETZ, RUSSELL	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	324	324	164
		7 4 4 1 7						· · · · (4 F · · · · · · · · · · · · · · · · · ·						
1030	3709	97045-	9007800	Owner	Well Constructed	PERRY JR LOUIS & JULIE	26	Well (Construction Report)	Residential	DENVER	Domestic			
						FALISE KHRISTOPHER								
1031	3710	97201-	9007803	Owner	Well Constructed	J & JESSICA A	26	Well (Application/Permit)	Residential	DAWSON	Domestic	204	204	164
										LOWER				
1032	3711	97425-	9007811	Owner	Well Constructed	SECTION 16 LTD	26	Well (Application/Permit)	Residential	DAWSON	Domestic	310	310	180
1033	3712	97629-	9007816	Owner	Well Constructed	HERNANDEZ, JOEL	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	398	398	358
1033	3/12	97029-	9007810	Owner	wen constructed	HERNANDEZ, JOEL	20	well (Application/Termit)	Residential	DENVER	Domestic, Stock	396	376	336
1034	3713	97629-	9007816	Owner	Well Constructed	HERNANDEZ, ERIKA	26	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	398	398	358
1035	3714	97703-	9007819	Owner	Well Constructed	HOLFORD, DAVID L	22	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	205	205	150
1036	3715	97710-	9007824	Owner	Well Constructed	CYR, PAMELA	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	360	360	200
1027	2714	00226	0007046		W II C	DADGONG TANK	10	W II /A P T	n :1 :	DEMES	P	105	105	205
1037	3716	98326-	9007846	Owner	Well Constructed	PARSONS, PAUL	18	Well (Application/Permit)	Residential	DENVER	Domestic	495	495	395
1038	3717	98927-	9007859	Owner	Well Constructed	KUNTAE, KIM	7	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	684	684	484
1000								(
1039	3718	98965-	9007863	Owner	Well Constructed	KLEIN, JACQUELINE	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic, Stock	324	324	244

												CompletedWell	PerforatedCasin	PerforatedCasin
OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
1040	3719	100133-	9007897	Owner	Well Constructed	MALONE, JAMES R	26	Well (Application/Permit)	Residential	DAWSON	Domestic, Stock	354	354	304
				_										
1041	3720	100162-	9007898	Owner	Well Constructed	YOHN, SONNY L.	18	Well (Application/Permit)	Residential	DENVER	Domestic	641	641	580
1042	3721	100162-	9007898	Owner	Well Constructed	SCMIDT, JESSICA	18	Well (Application/Permit)	Residential	DENVER	Domestic	641	641	580
1042	3/21	100102-	9007696	Owner	Well Collstructed	SCMID1, JESSICA	10	wen (Application/Fermit)	Residential	DENVER	Domestic	041	041	380
1043	3722	100165-	9007899	Owner	Well Constructed	LUCAS, MICHAEL	26	Well (Application/Permit)	Residential	LOWER DAWSON	Domestic	265	265	205
						THORP RICK & DON								
1044	3723	100552-	9007905	Owner	Well Constructed	BLAIR	7	Well (Application/Permit)	Residential	DAWSON	Domestic	657	657	420
1045	3724	101008-	9007910	Owner	Well Constructed	GUZMAN, JOSE J.	18	Well (Application/Permit)	Residential	DENVER	Domestic	490	490	410
						RESIDENTIAL								
1046	3725	101541-	9007914	Owner	Well Constructed	FRAMING INC	7	Well (Application/Permit)	Residential	DENVER	Domestic	610	610	450
10.45	2526	101500	0007000			LANDWEHR JOHN &	10	****	5	I DI DIVION				500
1047	3726	101792-	9007920	Owner	Well Constructed	CHRISTY	18	Well (Application/Permit)	Residential	ARAPAHOE	Domestic	655	635	500
1048	3727	101793-	9007921	Owner	Well Constructed	DURKIN, THOMAS F	7	Well (Application/Permit)	Residential	DENVER	Domestic	708	708	566
1046	3121	101793-	9007921	Owner	Wen Constructed	DORRIN, THOMAS I	/	wen (Application/Termit)	Residential	DENVER	Domestic	708	708	300
1049	3728	101794-	9007922	Owner	Well Constructed	IMES JOHN S & SUSAN	7	Well (Application/Permit)	Residential	DENVER	Domestic	631	631	451
								\ 11						
1050	3729	101802-	9007925	Owner	Well Constructed	MOTHERSHED, ROBERT L.	26	Well (Application/Permit)	Residential	DENVER	Domestic	382	382	322
						MOTHERSHED,								
1051	3730	101802-	9007925	Owner	Well Constructed	GEEHAE L.	26	Well (Application/Permit)	Residential	DENVER	Domestic	382	382	322
1052	3731	102118-	9007927	Owner	Well Constructed	DOXEY, LAWRY E	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	325	325	290
						HILLMAN ROBERT I &								
1053	3732	102133-	9007931	Owner	Well Constructed	KATHRYN M	22	Well (Application/Permit)	Residential	DENVER	Domestic	355	355	335
1054	3733	102329-	9007942	Owner	Well Constructed	PASILLAS ESTEBAN & SILVIA	18	Well (Application/Permit)	Residential	DENVER	Domestic			
1034	3133	102329	7007742	Owner	wen constructed	SILVIA	10	Well (Application/Terrillt)	Residential	DENVER	Doniestic			
1055	3734	102885-	9007945	Owner	Well Constructed	HANSEN, HAROLD	8	Well (Application/Permit)	Residential	DENVER	Domestic			
						,		(11						
1056	3735	102890-	9007946	Owner	Well Constructed	HANSEN, HAROLD	8	Well (Application/Permit)	Residential	DENVER	Domestic			

OVD	Map ID ^{a/}	D. CAV. I	D		D ::6:4	C 4 N			D 26			-		PerforatedCasin T
OID	Map ID	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	Depth	gBottom	gTop
1057	3736	103040-	9007948	Owner	Well Constructed	BERGNER, BROOKS B	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	220	220	160
			, , , , , ,					(TI					,	
1058	3737	104266-	9007956	Owner	Well Constructed	ALCALA AUGIE & LOMA J	7	Well (Application/Permit)	Residential	DENVER	Domestic	709	709	609
						INGRAM FRANKLIN &								
1059	3738	110966-	9007993	Owner	Well Constructed	GLADYS D	7	Well (Application/Permit)	Residential	DENVER	Domestic	655		
1060	3739	114231-	9008005	Owner	Well Constructed	BRALEY, ROBERT J	7	Well (Application/Permit)	Residential	DENVER	Domestic			
1061	3740	123271-	9008054	Owner	Well Constructed	GORMELY, JOHN E	24	Well (Application/Permit)	Residential	DENVER	Domestic	440		
10.62	2544	125(10)	000004			av. av.	22	****	5	DEL TIED		2.50		
1062	3741	125610-	9008061	Owner	Well Constructed	SU, CHI	22	Well (Application/Permit)	Residential	DENVER	Domestic, Stock	352		
1063	3742	136562-	9008089	Owner	Well Constructed	JAMES RALPH & MCDOWELL CAROL	18	Well (Construction Report)	Residential	DENVER	Domestic			
1003	3142	130302-	7000007	Owner	Well Constructed		10	wen (construction report)	Residential	DERVER	Domestic			
1064	3743	141968-	9008099	Owner	Well Constructed	BOWERS LESTER & LESTER MRS	7	Well (Application/Permit)	Residential	DENVER	Household use only	666		
										LIDDED				
1065	3744	143860-	9008105	Owner	Well Constructed	LOMBARDO, MARC A	7	Well (Application/Permit)	Residential	UPPER ARAPAHOE	Domestic	1030	1030	930
									Colorado Water	ALL UNNAMED				
1066	3745	40-WCB	C030040	Owner	Well Constructed	PELTON, GEORGE A	22	Well (Application/Permit)	Conservation Board	AQUIFERS	Domestic	170	170	116
									Colorado Water	ALL UNNAMED				
1067	3746	43-WCB	C030043	Owner	Well Constructed	MALONE, FLORA L	26	Well (Application/Permit)	Conservation Board	AQUIFERS		82		
									Colorado Water	ALL UNNAMED				
1069	3748	136-WCB	C030136	Owner	Well Constructed	MALONE, J B	29	Well (Application/Permit)	Conservation Board	AQUIFERS		149		
1070	3749	280-WCB	C030280	Owner	Well Constructed	HAINES, O J	14	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		713		
10/0	3/49	260-WCB	C030280	Owner	well Collstitucted	HAINES, O J	14	wen (Application/Fernint)		AQUITERS		/13		
1071	3750	332-WCB	C030332	Owner	Well Constructed	HANSEN, HAROLD	8	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		272		
						,								
1072	3751	418-WCB	C030418	Owner	Well Constructed	QUICK, WILLIAM V	19	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS	_	120		
						ROUNTREE, RUSSELL			Colorado Water	ALL UNNAMED				
1073	3752	430-WCB	C030430	Owner	Well Constructed	E E	19	Well (Application/Permit)	Conservation Board	AQUIFERS		350		
									Colorado Water	ALL UNNAMED				
1075	3754	435-WCB	C030435	Owner	Well Constructed	MALONE, FLORA L	26	Well (Application/Permit)	Conservation Board	AQUIFERS		90		

SUMMARY OF PERMITTED WATER WELLS LOCATED WITHIN FIVE MILES OF THE SITE JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

OID	Map ID ^{a/}	PermitNumber	Receipt	AssocType	PermitStatus	ContactName	Section	LocationType	PermitCategory	aquifer1_name	Use1	CompletedWell Depth	PerforatedCasin gBottom	PerforatedCasin gTop
1076	3755	535-WCB	C030535	Owner	Well Constructed	CLINKINBEARD, F L	12	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		585		
1077	3756	550-WCB	C030550	Owner	Well Constructed	GUNTHER, ROBERT	3	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		420		
1078	3757	552-WCB	C030552	Owner	Well Constructed	GIBSON, JAMES L	30	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS	Domestic	246	244	158
1079	3758	565-WCB	C030565	Owner	Well Constructed	ANDERSON, KEITH	13	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		1192		
1080	3759	590-WCB	C030590	Owner	Well Constructed	SETCHELL, FRED	24	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS		424		
1081	3760	716-WCB	C030716	Owner	Well Constructed	SMITH, HAROLD H	21	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS	Domestic, Stock	29		
1082	3761	388-WCB	C620388	Owner	Well Constructed	TRAUTWEIN, A H	7	Well (Application/Permit)	Colorado Water Conservation Board	ALL UNNAMED AQUIFERS	Domestic	77		

a/ Location number on Figure 4.43
In drainage basin

On Figure 4.43

APPENDIX D

LANDFILL GAS

LFG QUALITY AND EXTRACTION WELL PRESSURES

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

		Methane	Carbon Dioxide	0	Dalama	Initial Temperature	Initial Static Pressure	Adjusted Static	Header	Initial Flow	Barometric Pressure	
ID	Date/Time	(%) ^{a/}	Dioxide (%)	Oxygen (%)	Balance (%)	(°F) ^{b/}	("H ₂ O) ^{c/}	Pressure ("H ₂ O)	Pressure ("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWEW30A	1/13/22 8:01	56.1	35.2	0.7	8.0	77.3	-1.36	-1.48	-11.49	9.0	24.66	Inc. Flow/Vac.
LOWEW30A	2/25/22 12:42	52.4	33.8	0.5	13.3	75.4	-0.30	-0.29	-24.75	8.0	24.34	No Adj. Made
LOWEW30A	3/29/22 8:37	46.0	33.2	0.0	20.8	76.0	-0.57	-0.56	-24.98	13.0	23.81	No Adj. Made
LOWEW30A	4/25/22 12:15	37.3	29.7	0.0	33.0	76.8	-0.33	-0.29	-24.06	13.0	24.43	No Adi, Made
LOWEW30A	5/20/22 9:34	44.5	33.1	0.0	22.4	74.5	-1.19	-1.18	-24.55	14.0	24.00	No Adj. Made
LOWEW30A	6/6/22 10:26	40.5	30.3	0.0	29.2	77.4	-0.93	-0.90	-24.33	14.0	24.20	No Adj. Made
LOWEW34A	1/13/22 8:37	54.0	32.2	0.8	13.0	59.8	-4.50	-5.10	-7.31	3.2	24.20	Inc. Flow/Vac.
LOWEW34A	2/25/22 13:13	39.5	30.3	0.0	30.2	62.4	-3.63	-3.63	-24.11	5.8	24.32	No Adj. Made
LOWEW34A	3/29/22 8:58	38.5	29.6	0.1	31.8	60.5	-3.55	-3.52	-21.67	5.7	23.80	No Adj. Made
LOWEW34A	4/26/22 9:53	40.6	28.9	0.0	30.5	65.8	-3.05	-3.06	-20.94	6.1	24.32	No Adj. Made
LOWEW34A	5/20/22 10:02	41.2	30.5	0.0	28.3	60.0	-4.52	-4.46	-22.54	8.1	24.01	Dec. Flow/Vac.
LOWEW34A	6/6/22 10:50	40.0	28.3	0.0	31.7	71.4	-3.69	-3.65	-19.84	6.4	24.20	No Adj. Made
LOWEW40A	1/11/22 10:03	53.1	39.1	1.0	6.8	55.6	-0.96	-1.09	-11.70	3.2	24.31	Inc. Flow/Vac.
LOWEW40A	2/25/22 11:25	48.9	38.4	0.2	12.5	53.4	-1.29	-1.27	-26.34	4.4	24.38	No Adj. Made
LOWEW40A	3/23/22 9:28	45.8	37.5	0.1	16.6	54.4	-0.91	-0.88	-25.02	4.8	24.22	No Adj. Made
LOWEW40A	4/25/22 10:48	39.2	35.6	0.0	25.2	58.5	-1.09	-1.06	-24.37	4.4	24.45	No Adj. Made
LOWEW40A	5/18/22 12:20	45.9	36.2	0.0	17.9	83.7	-0.68	-0.63	-24.28	4.7	24.30	No Adj. Made
LOWEW40A	6/6/22 9:32	46.5	37.2	0.0	16.3	72.5	-1.58	-1.57	-23.86	4.8	24.21	No Adj. Made
LOWREW01	1/13/22 10:19	14.9	29.8	0.2	55.1	61.8	-0.30	-0.50	-13.36	1.4	24.22	No Adj. Made
LOWREW01	2/28/22 10:15	19.0	29.6	0.0	51.4	60.6	-0.10	-0.08	-28.97	2.6	24.46	No Adj. Made
LOWREW01	3/29/22 10:29	15.1	29.9	0.0	55.0	51.9	-0.28	-0.22	-25.78	2.6	23.76	No Adj. Made
LOWREW01	4/26/22 11:18	15.6	27.3	0.4	56.7	67.6	-0.33	-0.30	-25.76	2.5	24.33	No Adj. Made
LOWREW01	5/20/22 11:12	15.6	30.5	0.0	53.9	49.9	-0.84	-0.79	-26.89	2.7	24.01	No Adj. Made
LOWREW01	6/6/22 11:58	15.7	26.0	0.0	58.3	79.0	-0.31	-0.29	-24.62	2.4	24.21	No Adj. Made
LOWREW02	1/13/22 10:14	6.5	27.9	0.3	65.3	64.9	-0.87	-0.95	-12.44	1.9	24.22	No Adj. Made
LOWREW02	2/28/22 10:12	7.1	25.0	0.6	67.3	67.2	-0.04	-0.04	-27.94	2.1	24.45	No Adj. Made
LOWREW02	3/29/22 10:26	7.2	27.1	0.0	65.7	57.1	-0.07	-0.07	-26.26	2.0	23.76	No Adj. Made
LOWREW02	4/26/22 11:15	6.5	24.1	0.3	69.1	69.8	-0.34	-0.30	-25.52	1.9	24.33	No Adj. Made
LOWREW02	5/20/22 11:09	3.9	24.3	1.6	70.2	56.8	-0.70	-0.66	-25.30	2.2	24.01	No Adj. Made
LOWREW02	6/6/22 11:56	5.9	23.1	0.5	70.5	80.6	-0.29	-0.27	-25.29	1.9	24.21	No Adj. Made
LOWREW03	1/13/22 10:09	24.0	33.9	0.4	41.7	60.9	-0.70	-0.70	-9.43	1.5	24.22	No Adj. Made
LOWREW03	2/28/22 10:08	23.7	31.3	0.0	45.0	62.5	-0.08	-0.07	-25.24	2.9	24.46	No Adj. Made
LOWREW03	3/29/22 10:24	21.0	31.8	0.0	47.2	57.2	-0.28	-0.22	-24.46	3.3	23.76	No Adj. Made
LOWREW03	4/26/22 11:12	19.5	28.5	0.0	52.0	71.7	-0.13	-0.12	-21.76	3.5	24.33	No Adj. Made
LOWREW03	5/20/22 11:05	19.4	31.3	0.0	49.3	54.6	-0.50	-0.55	-23.02	3.5	24.00	No Adj. Made
LOWREW03	6/6/22 11:53	18.7	27.1	0.0	54.2	79.5	-0.26	-0.24	-22.20	3.3	24.20	No Adj. Made
LOWREW04	1/13/22 10:05	23.1	33.4	0.6	42.9	54.9	-0.09	-0.03	-10.11	2.1	24.22	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW04	2/28/22 10:05	16.4	28.4	0.1	55.1	59.6	-0.09	-0.09	-26.36	1.9	24.45	No Adj. Made
LOWREW04	3/29/22 10:21	18.3	30.7	0.0	51.0	51.9	-0.17	-0.11	-23.78	2.0	23.76	No Adj. Made
LOWREW04	4/26/22 11:09	15.7	27.2	0.4	56.7	69.8	-0.21	-0.17	-23.61	1.7	24.33	No Adj. Made
LOWREW04	5/20/22 11:01	12.3	28.4	0.0	59.3	48.0	-0.77	-0.77	-22.81	2.2	24.01	No Adj. Made
LOWREW04	6/6/22 11:50	12.6	25.4	0.0	62.0	80.8	-0.33	-0.31	-21.45	1.7	24.20	No Adj. Made
LOWREW05	1/13/22 9:56	27.0	32.1	0.8	40.1	57.6	-0.20	-0.30	-10.06	1.8	24.22	No Adj. Made
LOWREW05	2/28/22 9:58	23.4	29.8	0.0	46.8	60.7	-0.09	-0.09	-25.45	4.2	24.45	No Adj. Made
LOWREW05	3/29/22 10:15	24.3	31.7	0.0	44.0	57.5	-0.07	-0.09	-23.12	1.4	23.76	No Adj. Made
LOWREW05	4/26/22 11:02	19.2	27.6	0.0	53.2	67.0	-0.16	-0.12	-21.68	1.7	24.33	No Adj. Made
LOWREW05	5/20/22 10:55	21.9	30.9	0.0	47.2	44.7	-0.90	-0.87	-22.58	1.8	24.00	No Adj. Made
LOWREW05	6/6/22 11:45	21.8	28.2	0.0	50.0	77.1	-0.35	-0.32	-21.43	1.4	24.21	No Adj. Made
LOWREW06	1/13/22 9:51	7.8	22.6	3.9	65.7	58.0	-0.70	-0.83	-9.95	1.5	24.21	No Adj. Made
LOWREW06	2/28/22 9:54	10.1	25.5	0.2	64.2	64.1	-0.03	-0.03	-25.72	2.2	24.45	No Adj. Made
LOWREW06	3/29/22 10:12	11.8	27.6	0.0	60.6	53.6	-0.10	-0.06	-22.22	2.0	23.76	No Adj. Made
LOWREW06	4/26/22 10:59	10.0	24.6	0.0	65.4	68.4	-0.25	-0.24	-21.68	2.0	24.33	No Adj. Made
LOWREW06	5/20/22 10:51	7.6	25.7	0.2	66.5	51.5	-0.77	-0.74	-22.56	2.9	24.00	No Adj. Made
LOWREW06	6/6/22 11:42	8.9	23.4	0.0	67.7	76.6	-0.37	-0.33	-22.19	1.9	24.20	No Adj. Made
LOWREW07	1/13/22 9:46	31.1	34.0	0.1	34.8	54.3	-0.10	-0.10	-10.14	2.3	24.22	No Adj. Made
LOWREW07	2/28/22 9:50	37.4	33.4	0.0	29.2	60.1	-0.24	-0.21	-25.54	4.9	24.45	No Adj. Made
LOWREW07	3/29/22 10:09	35.5	35.1	0.0	29.4	54.2	-0.15	-0.10	-22.37	2.5	23.76	No Adj. Made
LOWREW07	4/26/22 10:55	36.5	32.8	0.5	30.2	65.6	-0.23	-0.21	-21.80	2.5	24.32	No Adj. Made
LOWREW07	5/20/22 10:47	30.7	33.1	0.0	36.2	46.0	-0.89	-0.87	-22.04	2.5	24.00	No Adj. Made
LOWREW07	6/6/22 11:39	33.9	31.8	0.2	34.1	73.6	-0.38	-0.35	-21.45	1.9	24.20	No Adj. Made
LOWREW08	1/13/22 8:47	16.7	29.2	0.7	53.4	52.4	-0.64	-0.65	-9.30	1.8	24.19	No Adj. Made
LOWREW08	2/25/22 13:24	20.8	30.9	0.0	48.3	51.2	-0.05	-0.03	-24.59	3.3	24.32	No Adj. Made
LOWREW08	3/29/22 9:04	18.1	29.7	0.0	52.2	50.6	-0.19	-0.16	-22.67	2.9	23.80	No Adj. Made
LOWREW08	4/26/22 10:03	19.1	28.5	0.0	52.4	63.8	-0.16	-0.13	-21.31	3.0	24.32	No Adj. Made
LOWREW08	5/20/22 10:08	17.4	28.8	0.0	53.8	48.0	-1.02	-0.96	-22.20	3.1	23.99	No Adj. Made
LOWREW08	6/6/22 10:55	16.9	26.9	0.0	56.2	75.0	-0.58	-0.62	-21.86	2.6	24.20	No Adj. Made
LOWREW09	1/13/22 8:42	2.7	23.8	1.9	71.6	48.4	-0.10	-0.10	-9.54	0.6	24.18	Fully Closed
LOWREW09	2/28/22 11:19	0.7	19.6	1.5	78.2	71.0	-0.03	0.00	-24.03	5.6	24.42	Fully Closed
LOWREW09	3/29/22 9:02	10.4	25.0	0.2	64.4	48.4	-0.36	0.03	-21.82	3.3	23.80	Fully Closed
LOWREW09	4/29/22 10:26	6.9	21.3	1.3	70.5	72.9	-0.16	-0.02	-21.52	2.8	23.89	Fully Closed
LOWREW09	5/19/22 11:59	4.7	21.5	0.9	72.9	95.0	-0.05	-0.02	-21.78	5.1	23.93	Fully Closed
LOWREW09	6/6/22 10:53	2.3	19.0	1.0	77.7	78.4	-0.19	-0.01	-20.86	3.2	24.20	Fully Closed
LOWREW10	1/11/22 10:57	9.1	20.2	4.6	66.1	68.8	-0.69	-0.61	-9.90	3.4	24.29	Fully Closed
LOWREW10	2/28/22 11:03	9.3	25.4	0.4	64.9	74.7	-0.09	-0.01	-25.52	3.1	24.42	Fully Closed

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

		Methane	Carbon			Initial Temperature	Initial Static	Adjusted Static	Header	Initial Flow	Barometric Pressure	
ID	Date/Time	(%) ^{a/}	Dioxide (%)	Oxygen (%)	Balance (%)	(°F) ^{b/}	Pressure ("H ₂ O) ^{c/}	Pressure ("H ₂ O)	Pressure ("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW10	3/23/22 10:03	5.2	21.1	6.0	67.7	62.5	-0.61	-0.01	-24.02	8.7	24.21	Fully Closed
LOWREW10	4/29/22 10:20	10.8	24.1	0.0	64.8	78.1	-0.01	-0.01	-24.02	1.7	23.89	Fully Closed
LOWREW10	5/19/22 11:30	10.8	23.6	0.5	65.2	91.1	-0.14	-0.02	-23.20	0.6	23.92	Fully Closed Fully Closed
LOWREW10	6/6/22 10:03	5.9	19.1	4.2	70.8	85.2	-0.22	-0.03	-23.01	3.9	24.20	Fully Closed Fully Closed
LOWREW11	1/11/22 10:51	18.6	28.1	0.1	53.2	64.3	-0.60	-0.60	-19.84	1.1	24.28	No Adj. Made
LOWREW11	2/25/22 12:05	14.4	28.0	0.1	57.5	57.3	-0.06	-0.05	-10.08	2.7	24.28	No Adj. Made
LOWREW11	3/23/22 12:03	14.4	27.8	0.1	57.7	53.3	-0.00	-0.03	-24.29	2.7	24.33	No Adj. Made
LOWREW11	4/25/22 11:26	15.0	25.8	0.1	59.2	64.0	-0.23	-0.21	-23.75	2.1	24.20	No Adj. Made
LOWREW11	5/19/22 11:25	15.0	26.6	0.0	58.1	86.3	-0.07	-0.09	-23.73	1.7	23.92	No Adj. Made
LOWREW11	6/6/22 9:59	12.6	25.2	0.1	62.2	77.0	-0.03	-0.08	-23.96	2.0	23.92	No Adj. Made
LOWREW11 LOWREW12	1/11/22 10:41	20.2	28.9	1.0	49.9	56.5	-0.51	-0.46	-24.23	2.0	24.19	No Adj. Made
LOWREW12 LOWREW12	2/25/22 11:53	14.7	28.9	0.0	58.2	49.3	-1.32	-1.72	-10.01	2.2	24.29	No Adj. Made
LOWREW12	3/23/22 11.33	13.6	26.7	0.0	59.6	48.0	-2.09	-2.06	-24.30	2.0	24.21	No Adj. Made
LOWREW12 LOWREW12	4/25/22 11:18	11.9	25.0	0.1	63.1	58.4	-2.09	-2.06	-24.10	1.9	24.21	No Adj. Made
LOWREW12 LOWREW12	5/19/22 11:14	14.2	25.0	0.0	60.8	86.2	-1.78	-1.77	-23.77	1.9	23.92	No Adj. Made
LOWREW12 LOWREW12	6/6/22 9:52	12.6	23.6	0.0	63.8	78.7	-1.78	-1./3	-24.03	1.8	23.92	No Adj. Made
LOWREW12 LOWREW13	1/11/22 10:35	29.2	32.0	0.6	38.2	63.5	-0.40	-0.40	-23.38 -9.74	5.9	24.19	J
LOWREW13	2/25/22 11:49	29.2	29.1	0.6	49.9	58.4	-0.40	-0.40	-9.74	1.8	24.29	No Adj. Made No Adj. Made
LOWREW13	3/23/22 11:49	18.7	28.7	0.1	52.6	54.8	-0.16	-0.17	-22.30	2.2	24.33	No Adj. Made
LOWREW13	4/25/22 11:10	17.8	26.9	0.0	55.3	62.6	-0.23	-0.24	-21.91	1.8	24.21	No Adj. Made
LOWREW13	5/19/22 11:11	17.3	27.4	0.0	55.3	84.2	-0.20	-0.18	-21.93	2.5	24.43	No Adj. Made
LOWREW13	6/6/22 9:50	16.9	26.8	0.0	56.3	78.5	-0.07	-0.03	-23.90	2.2	24.00	No Adj. Made
LOWREW13	1/11/22 9:31	34.2	31.7	0.0	33.3	59.0	-0.48	-0.47	-23.90	2.7	24.19	No Adj. Made
LOWREW14 LOWREW14	2/25/22 10:59	26.2	30.0	0.8	43.7	56.0	-0.38	-0.38	-10.40	2.8	24.29	No Adj. Made
LOWREW14	3/23/22 9:13	23.2	29.3	0.1	47.4	50.3	-0.20	-0.25	-23.91	2.5	24.21	No Adj. Made
LOWREW14 LOWREW14	4/25/22 10:30	21.8	27.0	0.1	51.2	58.0	-0.30	-0.25	-23.36	2.5	24.21	No Adj. Made
LOWREW14 LOWREW14	5/18/22 11:55	22.2	27.5	0.0	50.1	82.0	-0.42	-0.36	-23.30	2.6	24.43	No Adj. Made
LOWREW14	6/6/22 9:15	22.3	26.5	0.2	51.2	74.7	-0.73	-0.66	-24.11	2.7	24.29	No Adj. Made
LOWREW15	1/11/22 9:25	34.0	29.4	0.0	36.5	56.3	-0.73	-0.70	-10.70	1.2	24.29	No Adj. Made
LOWREW15	2/25/22 10:53	22.2	27.5	0.1	50.3	56.2	-0.70	-0.70	-24.76	2.0	24.29	No Adj. Made
LOWREW15	3/23/22 9:11	22.4	27.8	0.0	49.7	51.5	-0.31	-0.32	-24.76	1.7	24.22	No Adj. Made
LOWREW15	4/25/22 10:27	21.6	25.7	0.1	52.7	58.4	-0.31	-0.25	-24.14	2.0	24.22	No Adj. Made
LOWREW15	5/18/22 11:52	22.1	25.0	0.0	52.7	84.5	-0.26	-0.23	-23.04	1.4	24.44	No Adj. Made
LOWREW15	6/6/22 9:13	21.2	24.8	0.0	54.0	74.8	-0.03	-0.05	-24.12	2.6	24.30	No Adj. Made
LOWREW15	1/11/22 9:15	32.3	33.4	0.0	34.0	56.2	-0.61	-0.62	-24.07	2.3	24.29	No Adj. Made
LOWREW16	2/25/22 10:45	23.2	31.0	0.2	45.7	50.5	-0.30	-0.02	-24.79	4.1	24.29	No Adj. Made
LOWREW16	3/23/22 9:05	21.5	30.5	0.1	48.0	46.9	-0.30	-0.23	-24.79	1.8	24.30	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

		Methane	Carbon Dioxide	Oxygen	Balance	Initial Temperature	Initial Static Pressure	Adjusted Static Pressure	Header Pressure	Initial Flow	Barometric Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	$(scfm)^{d/}$	("Hg) ^{e/}	Comments
LOWREW16	4/25/22 10:20	18.6	26.6	0.0	54.8	58.1	-0.19	-0.16	-23.63	1.7	24.45	No Adj. Made
LOWREW16	5/18/22 11:45	20.2	28.0	0.0	51.8	85.2	-0.06	-0.03	-23.48	1.5	24.31	No Adj. Made
LOWREW16	6/6/22 9:07	19.5	27.3	0.0	53.2	74.6	-0.60	-0.53	-22.07	1.6	24.20	Dec. Flow/Vac.
LOWREW17	1/11/22 9:04	16.1	27.7	0.5	55.7	55.3	-0.80	-0.80	-11.35	1.3	24.18	No Adj. Made
LOWREW17	2/25/22 10:36	9.2	24.8	0.1	65.9	54.1	-0.23	-0.22	-25.29	2.6	24.37	No Adj. Made
LOWREW17	3/23/22 9:00	8.7	24.2	0.2	66.9	52.1	-0.39	-0.37	-24.74	3.0	24.24	No Adj. Made
LOWREW17	4/25/22 10:13	7.6	22.0	0.0	70.4	59.6	-0.19	-0.18	-23.96	3.3	24.45	No Adj. Made
LOWREW17	5/18/22 11:39	7.3	22.0	0.2	70.5	78.4	-0.27	-0.25	-23.98	2.2	24.31	No Adj. Made
LOWREW17	6/6/22 9:01	7.3	22.7	0.0	70.0	70.3	-0.42	-0.38	-24.21	3.4	24.21	No Adj. Made
LOWREW18	1/11/22 8:53	12.5	26.8	0.9	59.8	52.2	-0.51	-0.56	-11.37	2.4	24.32	No Adj. Made
LOWREW18	2/23/22 12:03	9.1	24.3	0.0	66.6	43.8	-0.09	-0.12	-15.73	3.5	24.21	No Adj. Made
LOWREW18	3/23/22 8:54	8.4	23.9	0.0	67.7	47.1	-0.31	-0.26	-25.49	2.1	24.26	No Adj. Made
LOWREW18	4/25/22 10:04	7.6	22.5	0.0	69.9	55.5	-0.34	-0.30	-24.37	2.1	24.47	No Adj. Made
LOWREW18	5/18/22 11:31	7.8	21.7	0.4	70.1	82.4	-0.38	-0.31	-23.93	1.9	24.33	No Adj. Made
LOWREW18	6/6/22 8:54	7.6	22.7	0.0	69.7	72.3	-0.36	-0.33	-24.25	2.0	24.02	No Adj. Made
LOWREW19	1/11/22 8:48	13.9	26.7	0.6	58.8	51.3	-0.20	-0.20	-11.46	1.2	24.32	No Adj. Made
LOWREW19	2/23/22 11:57	20.9	29.4	0.0	49.7	48.3	-0.03	-0.03	-15.65	2.2	24.22	No Adj. Made
LOWREW19	3/23/22 8:52	19.3	27.2	0.3	53.2	47.2	-0.16	-0.10	-25.23	2.2	24.26	No Adj. Made
LOWREW19	4/25/22 10:00	17.6	27.5	0.0	54.9	57.5	-0.29	-0.21	-23.19	1.2	24.48	No Adj. Made
LOWREW19	5/18/22 11:28	18.9	27.5	0.6	53.0	87.7	-0.14	-0.11	-22.67	0.8	24.33	No Adj. Made
LOWREW19	6/6/22 8:51	17.1	27.3	0.0	55.6	72.6	-0.23	-0.22	-22.97	1.1	24.23	No Adj. Made
LOWREW20	1/11/22 8:42	20.8	27.9	0.2	51.1	55.1	-0.14	-0.13	-10.65	2.7	24.38	No Adj. Made
LOWREW20	2/23/22 11:51	39.9	35.8	0.1	24.2	50.2	-0.04	-0.04	-15.74	2.7	24.22	No Adj. Made
LOWREW20	3/23/22 8:49	25.6	27.4	0.3	46.7	48.0	-0.08	-0.01	-24.05	1.8	24.27	No Adj. Made
LOWREW20	4/25/22 9:56	22.7	28.9	0.0	48.4	55.2	-0.03	-0.03	-23.08	2.2	24.49	No Adj. Made
LOWREW20	5/18/22 11:25	29.5	31.4	0.3	38.8	80.1	-0.30	-0.21	-22.82	2.0	24.42	No Adj. Made
LOWREW20	6/6/22 8:48	20.3	27.8	0.1	51.8	68.6	-0.26	-0.21	-22.81	2.1	24.27	No Adj. Made
LOWREW21	1/13/22 9:23	21.3	33.4	0.4	44.9	56.7	-0.10	-0.10	-11.83	2.3	24.20	No Adj. Made
LOWREW21	2/28/22 9:26	18.3	30.2	0.1	51.4	63.3	-0.19	-0.19	-26.51	4.0	24.44	No Adj. Made
LOWREW21	3/29/22 9:48	23.8	35.3	0.2	40.7	58.4	-0.14	-0.14	-24.58	2.3	23.76	No Adj. Made
LOWREW21	4/26/22 10:34	19.4	30.6	0.3	49.7	67.9	-0.04	-0.02	-23.02	2.2	24.32	No Adj. Made
LOWREW21	5/20/22 10:34	15.4	30.3	0.0	54.3	50.3	-0.92	-0.88	-24.98	2.6	24.00	No Adj. Made
LOWREW21	6/6/22 11:19	15.5	26.0	0.0	58.5	75.0	-0.43	-0.38	-24.65	2.4	24.20	No Adj. Made
LOWREW22	1/13/22 9:28	14.3	30.2	0.5	55.0	58.0	-0.13	-0.18	-9.39	3.1	24.22	No Adj. Made
LOWREW22	2/28/22 9:29	17.5	29.1	0.0	53.4	63.7	-0.27	-0.22	-24.12	5.8	24.45	No Adj. Made
LOWREW22	3/29/22 9:52	27.9	35.0	0.0	37.1	61.4	-0.02	-0.01	-23.94	3.3	23.76	No Adj. Made
LOWREW22	4/26/22 10:37	20.5	29.5	0.0	50.0	68.4	-0.14	-0.10	-22.76	1.0	24.32	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW22	5/20/22 10:38	16.3	29.5	0.0	54.2	49.7	-0.73	-0.73	-22.98	2.9	24.00	No Adj. Made
LOWREW22	6/6/22 11:22	10.0	24.3	0.0	65.7	73.8	-0.36	-0.32	-22.15	1.9	24.20	No Adj. Made
LOWREW23	1/13/22 9:33	4.5	22.0	14.7	58.8	91.3	-0.90	-0.60	-9.76	6.4	24.21	Fully Closed
LOWREW23	2/28/22 11:29	10.4	24.2	0.5	64.9	102.9	-0.07	0.01	-24.31	7.4	24.42	Fully Closed
LOWREW23	3/29/22 9:59	21.5	33.4	0.0	45.1	93.8	-0.37	0.01	-22.77	6.0	23.76	Fully Closed
LOWREW23	4/29/22 10:39	12.3	22.7	2.7	62.3	92.8	-0.22	-0.02	-21.53	2.6	23.90	Fully Closed
LOWREW23	5/19/22 12:09	10.5	21.4	1.7	66.4	101.3	-0.06	-0.01	-21.65	18.6	23.92	Fully Closed
LOWREW23	6/6/22 11:30	2.0	16.7	7.1	74.2	100.8	-0.48	-0.02	-20.88	1.5	24.20	Fully Closed
LOWREW24	1/13/22 9:37	17.8	29.9	0.9	51.4	57.1	-0.90	-0.89	-8.66	1.1	24.21	No Adj. Made
LOWREW24	2/28/22 9:43	11.2	27.5	0.0	61.3	62.5	-0.04	-0.05	-21.20	1.6	24.44	No Adj. Made
LOWREW24	3/29/22 10:04	28.5	33.6	0.0	37.9	60.4	-0.11	-0.06	-20.20	1.9	23.76	No Adj. Made
LOWREW24	4/26/22 10:48	14.6	27.3	0.4	57.7	68.4	-0.13	-0.12	-17.65	2.4	24.32	No Adj. Made
LOWREW24	5/20/22 10:41	13.5	29.2	0.0	57.3	50.1	-0.91	-0.90	-19.52	2.9	24.00	No Adj. Made
LOWREW24	6/6/22 11:33	9.2	25.4	0.0	65.4	76.8	-0.33	-0.28	-17.42	3.0	24.20	No Adj. Made
LOWREW25	1/13/22 9:42	6.7	26.6	0.2	66.5	51.6	-0.70	-0.80	-10.21	0.6	24.21	Inc. Flow/Vac.
LOWREW25	2/28/22 9:47	7.7	25.6	0.0	66.7	58.5	-0.15	-0.14	-24.58	3.0	24.44	No Adj. Made
LOWREW25	3/29/22 10:06	8.2	26.7	0.0	65.1	53.2	-0.18	-0.15	-22.87	2.9	23.76	No Adj. Made
LOWREW25	4/26/22 10:51	6.8	23.7	0.0	69.5	65.6	-0.26	-0.23	-20.86	2.8	24.32	No Adj. Made
LOWREW25	5/20/22 10:44	7.0	25.7	0.0	67.3	51.4	-0.72	-0.72	-22.71	2.9	24.00	No Adj. Made
LOWREW25	6/6/22 11:36	7.0	23.3	0.0	69.7	74.5	-0.41	-0.39	-21.77	2.9	24.20	No Adj. Made
LOWREW26	1/13/22 9:19	35.8	36.5	0.4	27.3	60.6	-0.26	-0.37	-12.28	1.9	24.19	No Adj. Made
LOWREW26	2/28/22 9:22	27.1	32.6	0.0	40.3	63.5	-0.40	-0.39	-28.56	3.7	24.44	No Adj. Made
LOWREW26	3/29/22 9:37	27.8	34.7	0.0	37.5	59.2	-0.10	-0.02	-26.62	3.7	23.75	No Adj. Made
LOWREW26	4/26/22 10:30	23.9	31.1	0.2	44.8	67.0	-0.19	-0.14	-25.42	4.4	24.31	No Adj. Made
LOWREW26	5/20/22 10:30	25.9	33.0	0.0	41.1	55.6	-1.20	-1.20	-25.88	4.1	23.99	No Adj. Made
LOWREW26	6/6/22 11:16	24.8	30.7	0.0	44.5	72.2	-0.66	-0.64	-25.94	4.3	24.19	No Adj. Made
LOWREW27	1/13/22 9:10	22.8	32.7	0.5	44.0	59.0	-0.50	-0.50	-9.52	1.9	24.19	No Adj. Made
LOWREW27	2/28/22 9:11	14.2	28.8	0.0	57.0	61.4	-0.56	-0.53	-24.87	5.5	24.45	No Adj. Made
LOWREW27	3/29/22 9:32	19.0	31.4	0.3	49.3	58.1	-0.04	-0.02	-22.34	2.2	23.77	No Adj. Made
LOWREW27	4/26/22 10:24	12.0	26.4	0.7	60.9	65.2	-0.14	-0.10	-21.97	4.3	24.32	No Adj. Made
LOWREW27	5/20/22 10:24	14.4	29.7	0.0	55.9	55.4	-1.25	-1.21	-22.22	4.4	23.99	No Adj. Made
LOWREW27	6/6/22 11:11	12.4	26.5	0.2	60.9	71.2	-0.61	-0.58	-20.89	2.5	24.19	No Adj. Made
LOWREW28	1/13/22 9:00	14.3	30.0	0.4	55.3	56.4	-0.33	-0.36	-9.69	2.4	24.18	No Adj. Made
LOWREW28	2/28/22 9:03	14.3	28.1	0.1	57.5	60.4	-0.56	-0.51	-24.67	3.6	24.45	No Adj. Made
LOWREW28	3/29/22 9:26	31.8	32.9	0.0	35.3	55.2	-0.25	-0.21	-22.96	3.5	23.78	No Adj. Made
LOWREW28	4/26/22 10:14	24.6	29.3	0.0	46.1	64.9	-0.11	-0.09	-21.68	3.4	24.31	No Adj. Made
LOWREW28	5/20/22 10:18	9.1	26.3	0.0	64.6	52.8	-1.41	-1.35	-22.32	4.0	23.99	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW28	6/6/22 11:04	7.1	24.3	0.0	68.6	71.9	-0.73	-0.72	-21.77	2.5	24.19	No Adj. Made
LOWREW29	1/13/22 8:51	43.8	34.3	0.8	21.1	55.8	-0.70	-0.70	-10.79	1.2	24.19	No Adj. Made
LOWREW29	2/25/22 13:31	28.1	30.3	0.0	41.6	56.8	-0.08	-0.09	-24.04	3.1	24.32	No Adj. Made
LOWREW29	3/29/22 9:21	27.2	30.5	0.0	42.3	53.8	-0.24	-0.19	-22.64	2.6	23.80	No Adj. Made
LOWREW29	4/26/22 10:07	26.7	28.6	0.2	44.5	62.9	-0.01	-0.03	-21.22	2.6	24.31	No Adj. Made
LOWREW29	5/20/22 10:11	19.9	28.9	0.0	51.2	53.2	-1.45	-1.38	-22.57	2.6	24.00	No Adj. Made
LOWREW29	6/6/22 10:58	11.8	25.0	0.0	63.2	71.7	-0.98	-0.49	-22.21	2.2	24.07	No Adj. Made
LOWREW30	1/13/22 7:56	43.1	35.3	0.6	21.0	66.8	-0.71	-0.71	-11.62	1.8	24.31	No Adj. Made
LOWREW30	2/25/22 12:39	28.1	31.4	0.3	40.2	64.0	-0.04	-0.04	-25.12	4.4	24.35	No Adj. Made
LOWREW30	3/29/22 8:35	25.5	28.2	0.1	46.2	67.7	-0.39	-0.26	-24.84	4.8	23.81	No Adj. Made
LOWREW30	4/25/22 12:13	25.8	30.1	0.0	44.1	68.4	-0.10	-0.05	-23.46	3.8	24.54	No Adj. Made
LOWREW30	5/20/22 9:32	22.2	30.5	0.1	47.2	56.7	-0.76	-0.71	-24.42	2.9	24.15	No Adj. Made
LOWREW30	6/6/22 10:24	22.3	28.0	0.0	49.7	74.1	-0.55	-0.50	-23.64	1.8	24.21	No Adj. Made
LOWREW31	1/13/22 8:05	40.0	33.4	0.2	26.4	69.1	-0.90	-0.80	-9.38	1.8	24.30	No Adj. Made
LOWREW31	2/25/22 12:47	18.5	29.1	0.8	51.6	67.7	-0.18	-0.17	-22.57	3.7	24.34	No Adj. Made
LOWREW31	3/29/22 8:39	29.3	30.0	0.0	40.7	63.9	-0.36	-0.29	-22.50	3.5	23.81	No Adj. Made
LOWREW31	4/26/22 9:21	17.9	28.7	0.3	53.1	68.9	-0.13	-0.09	-21.52	1.4	24.33	No Adj. Made
LOWREW31	5/20/22 9:39	21.4	29.7	0.0	48.9	51.4	-0.97	-0.95	-20.41	2.7	24.00	No Adj. Made
LOWREW31	6/6/22 10:29	15.9	27.3	0.0	56.8	75.5	-0.73	-0.67	-21.16	1.5	24.20	No Adj. Made
LOWREW32	1/13/22 8:14	34.5	33.6	0.4	31.5	64.6	-0.98	-1.04	-7.61	3.5	24.20	No Adj. Made
LOWREW32	2/25/22 12:55	26.2	30.3	0.6	42.9	68.4	-0.05	-0.06	-19.26	3.7	24.33	No Adj. Made
LOWREW32	3/29/22 8:46	35.7	32.3	0.0	32.0	68.2	-0.59	-0.20	-19.24	3.5	23.81	No Adj. Made
LOWREW32	4/26/22 9:35	27.7	30.4	0.2	41.7	71.6	-0.16	-0.12	-18.56	3.2	24.34	No Adj. Made
LOWREW32	5/20/22 9:46	21.5	30.5	0.0	48.0	67.0	-1.25	-1.21	-21.37	3.5	24.00	No Adj. Made
LOWREW32	6/6/22 10:35	19.2	28.0	0.0	52.8	74.9	-0.81	-0.80	-19.36	2.6	24.20	No Adj. Made
LOWREW33	1/13/22 8:24	32.8	32.5	0.2	34.5	66.8	-0.70	-0.70	-11.17	7.1	24.20	No Adj. Made
LOWREW33	2/25/22 13:02	27.9	29.8	0.7	41.6	65.1	-0.20	-0.19	-22.09	5.4	24.33	No Adj. Made
LOWREW33	3/29/22 8:51	26.3	29.3	0.0	44.4	63.2	-0.37	-0.34	-22.59	4.8	23.80	No Adj. Made
LOWREW33	4/26/22 9:44	25.2	29.4	0.0	45.4	70.7	-0.13	-0.10	-22.22	4.7	24.31	No Adj. Made
LOWREW33	5/20/22 9:52	23.6	29.4	0.0	47.0	61.6	-1.28	-1.24	-23.36	4.8	24.00	No Adj. Made
LOWREW33	6/6/22 10:41	22.4	27.4	0.2	50.0	74.1	-0.58	-0.57	-22.63	4.6	24.19	No Adj. Made
LOWREW34	1/13/22 8:33	14.6	28.1	0.7	56.6	58.9	-0.04	-0.10	-7.33	2.4	23.98	No Adj. Made
LOWREW34	2/25/22 13:09	9.4	25.9	0.0	64.7	59.8	-0.06	-0.06	-24.04	3.2	24.33	No Adj. Made
LOWREW34	3/29/22 8:56	12.4	25.6	0.1	61.9	58.8	-0.33	-0.26	-21.46	2.6	23.79	No Adj. Made
LOWREW34	4/26/22 9:51	9.8	25.0	0.0	65.2	66.3	-0.24	-0.20	-21.07	1.6	24.31	No Adj. Made
LOWREW34	5/20/22 9:59	11.1	26.4	0.0	62.5	53.4	-0.84	-0.80	-22.29	2.3	24.00	No Adj. Made
LOWREW34	6/6/22 10:47	10.1	24.0	0.0	65.9	74.0	-0.41	-0.38	-20.30	1.5	24.19	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW35	1/11/22 11:02	19.4	26.6	0.6	53.4	61.5	-0.90	-0.90	-10.06	0.7	24.29	No Adj. Made
LOWREW35	2/25/22 12:15	15.4	29.0	0.0	55.6	57.5	-0.23	-0.21	-24.11	1.9	24.35	No Adj. Made
LOWREW35	3/23/22 10:07	21.3	29.6	0.0	49.1	57.3	-0.36	-0.33	-23.93	2.2	24.24	No Adj. Made
LOWREW35	4/25/22 11:40	13.2	22.1	0.0	64.7	65.3	-0.49	-0.45	-21.91	2.0	24.43	No Adj. Made
LOWREW35	5/19/22 11:35	28.4	29.3	0.0	42.3	76.7	-0.15	-0.15	-20.91	0.8	23.92	No Adj. Made
LOWREW35	6/6/22 10:06	14.1	24.5	0.0	61.4	67.1	-0.94	-0.89	-22.02	5.7	24.20	No Adj. Made
LOWREW36	1/11/22 11:29	43.0	35.4	0.6	21.0	68.5	-0.35	-0.37	-11.58	3.9	24.31	No Adj. Made
LOWREW36	2/25/22 12:34	34.6	33.5	0.4	31.5	64.5	-0.14	-0.14	-26.87	4.7	24.35	No Adj. Made
LOWREW36	3/23/22 10:24	33.9	33.2	0.1	32.8	63.0	-0.61	-0.45	-26.15	4.5	24.23	No Adj. Made
LOWREW36	4/25/22 11:56	36.9	31.6	0.0	31.5	65.5	-0.21	-0.17	-25.14	3.2	24.43	No Adj. Made
LOWREW36	5/19/22 11:53	36.8	31.6	0.0	31.6	85.1	-0.09	-0.09	-24.12	1.8	23.93	No Adj. Made
LOWREW36	6/6/22 10:21	30.7	29.8	0.0	39.5	70.6	-0.57	-0.55	-24.93	3.2	24.21	No Adj. Made
LOWREW37	1/11/22 11:18	41.3	34.7	0.8	23.2	64.6	-0.50	-0.50	-12.25	2.4	24.30	No Adj. Made
LOWREW37	2/25/22 12:27	35.9	34.5	0.0	29.6	59.2	-0.07	-0.08	-24.01	3.9	24.34	No Adj. Made
LOWREW37	3/23/22 10:19	36.1	34.1	0.0	29.8	59.7	-0.40	-0.37	-22.01	3.9	24.22	No Adj. Made
LOWREW37	4/25/22 11:48	31.3	30.1	0.0	38.6	66.1	-0.36	-0.30	-23.20	3.9	24.43	No Adj. Made
LOWREW37	5/19/22 11:46	40.3	30.5	0.0	29.2	83.1	-0.17	-0.17	-23.30	3.6	23.92	No Adj. Made
LOWREW37	6/6/22 10:15	32.8	30.8	0.0	36.4	72.5	-0.75	-0.69	-24.15	4.2	24.21	No Adj. Made
LOWREW38	1/11/22 11:08	46.2	33.0	0.1	20.7	69.1	-1.34	-1.34	-10.15	3.1	24.29	No Adj. Made
LOWREW38	2/25/22 12:20	41.4	32.7	0.0	25.9	61.4	-0.07	-0.07	-20.38	4.7	24.34	No Adj. Made
LOWREW38	3/23/22 10:10	46.4	33.3	0.0	20.3	60.9	-0.18	-0.15	-22.37	4.8	24.21	No Adj. Made
LOWREW38	4/25/22 11:43	40.4	31.3	0.0	28.3	67.0	-0.25	-0.19	-23.17	4.8	24.44	No Adj. Made
LOWREW38	5/19/22 11:39	58.3	33.2	0.0	8.5	83.6	-0.07	-0.09	-23.70	4.4	23.92	No Adj. Made
LOWREW38	6/6/22 10:10	31.3	29.8	0.0	38.9	74.2	-0.65	-0.60	-25.63	4.8	24.20	No Adj. Made
LOWREW39	1/11/22 10:46	50.2	35.6	0.3	13.9	64.6	-1.20	-1.20	-10.23	3.2	24.29	No Adj. Made
LOWREW39	2/25/22 11:59	49.4	35.0	0.0	15.6	59.8	-0.12	-0.11	-24.58	5.0	24.35	No Adj. Made
LOWREW39	3/23/22 9:56	40.8	34.7	0.0	24.5	59.6	-0.17	-0.13	-23.47	4.5	24.22	No Adj. Made
LOWREW39	4/25/22 11:24	43.1	33.5	0.0	23.4	64.5	-0.36	-0.32	-23.25	4.5	24.42	No Adj. Made
LOWREW39	5/19/22 11:21	42.6	33.5	0.1	23.8	78.8	-0.19	-0.19	-24.58	3.4	23.91	No Adj. Made
LOWREW39	6/6/22 9:56	39.2	33.2	0.0	27.6	73.0	-0.87	-0.79	-23.69	4.3	24.19	No Adj. Made
LOWREW40	1/11/22 9:58	29.5	33.5	0.3	36.7	56.2	-0.16	-0.17	-11.73	1.7	24.30	No Adj. Made
LOWREW40	2/25/22 11:22	20.5	31.1	0.0	48.4	51.3	-0.10	-0.10	-26.20	1.7	24.38	No Adj. Made
LOWREW40	3/23/22 9:27	22.3	31.9	0.0	45.8	48.5	-0.11	-0.09	-24.84	1.9	24.23	No Adj. Made
LOWREW40	4/25/22 10:46	19.1	29.1	0.0	51.8	60.1	-0.29	-0.25	-24.26	1.7	24.45	No Adj. Made
LOWREW40	5/18/22 12:19	20.9	29.8	0.0	49.3	90.3	-0.03	-0.04	-24.43	1.4	24.30	No Adj. Made
LOWREW40	6/6/22 9:30	18.6	29.4	0.0	52.0	77.4	-0.49	-0.45	-24.54	1.6	24.21	No Adj. Made
LOWREW41	1/11/22 10:14	28.7	33.0	0.9	37.4	59.1	-1.20	-1.20	-11.78	0.5	24.31	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW41	2/25/22 11:34	18.4	29.7	0.0	51.9	53.7	-0.19	-0.27	-25.68	1.9	24.38	No Adj. Made
LOWREW41	3/23/22 9:37	24.7	31.1	0.2	44.0	51.0	-0.19	-0.19	-25.05	2.0	24.22	No Adj. Made
LOWREW41	4/25/22 10:56	20.5	27.5	0.0	52.0	61.0	-0.30	-0.29	-24.47	1.9	24.44	No Adj. Made
LOWREW41	5/18/22 12:32	21.6	28.3	0.1	50.0	89.1	-0.03	-0.01	-24.62	1.8	24.29	No Adj. Made
LOWREW41	6/6/22 9:38	15.5	26.2	0.0	58.3	70.7	-0.77	-0.74	-24.50	1.8	24.21	No Adj. Made
LOWREW42	1/11/22 10:25	25.7	31.2	0.9	42.2	72.1	-0.76	-0.77	-5.94	4.3	24.30	No Adj. Made
LOWREW42	2/25/22 11:41	17.1	28.4	0.0	54.5	68.5	-0.23	-0.22	-21.09	1.5	24.37	No Adj. Made
LOWREW42	3/23/22 9:42	22.5	29.4	0.1	48.0	63.4	-0.27	-0.16	-21.37	3.2	24.22	No Adj. Made
LOWREW42	4/25/22 11:02	17.8	26.3	0.0	55.9	68.9	-0.21	-0.20	-19.69	1.9	24.44	No Adj. Made
LOWREW42	5/18/22 12:41	18.9	26.1	0.1	54.9	87.1	-0.18	-0.14	-17.51	1.4	24.28	No Adj. Made
LOWREW42	6/6/22 9:44	12.7	26.0	0.0	61.3	82.2	-0.57	-0.55	-19.29	4.1	24.20	No Adj. Made
LOWREW43	1/11/22 10:30	30.0	31.6	0.2	38.2	62.2	-0.90	-0.90	-8.85	0.6	24.30	No Adj. Made
LOWREW43	2/25/22 11:45	23.9	28.6	0.0	47.5	59.0	-0.18	-0.18	-21.49	2.3	24.37	No Adj. Made
LOWREW43	3/23/22 9:45	41.5	32.5	0.0	26.0	57.2	-0.02	-0.02	-21.52	3.0	24.21	No Adj. Made
LOWREW43	4/25/22 11:05	20.6	26.6	0.0	52.8	63.0	-0.13	-0.15	-20.31	2.2	24.44	No Adj. Made
LOWREW43	5/18/22 12:45	35.3	29.4	0.0	35.3	80.1	-0.07	-0.05	-20.84	2.0	24.28	No Adj. Made
LOWREW43	6/6/22 9:47	18.9	26.6	0.0	54.5	75.0	-0.68	-0.63	-22.55	2.7	24.20	No Adj. Made
LOWREW44	1/11/22 9:36	45.8	36.8	0.6	16.8	57.6	-1.09	-1.08	-6.76	2.4	24.28	No Adj. Made
LOWREW44	2/25/22 11:08	38.4	35.3	0.0	26.3	55.9	-0.34	-0.34	-22.40	3.7	24.36	No Adj. Made
LOWREW44	3/23/22 9:16	35.0	33.5	0.1	31.4	53.1	-0.07	-0.06	-20.98	3.7	24.21	No Adj. Made
LOWREW44	4/25/22 10:35	31.1	30.7	0.0	38.2	59.5	-0.20	-0.20	-20.20	3.3	24.43	No Adj. Made
LOWREW44	5/18/22 12:00	36.0	32.4	0.0	31.6	78.1	-0.07	-0.01	-20.56	3.3	24.30	No Adj. Made
LOWREW44	6/6/22 9:19	34.3	33.2	0.0	32.5	71.8	-0.81	-0.75	-19.16	3.3	24.20	No Adj. Made
LOWREW45	1/11/22 9:52	35.9	34.3	0.2	29.6	59.3	-1.00	-1.00	-11.40	0.8	24.30	No Adj. Made
LOWREW45	2/25/22 11:18	27.1	32.7	0.0	40.2	55.9	-0.14	-0.13	-26.10	1.8	24.38	No Adj. Made
LOWREW45	3/23/22 9:24	26.4	32.6	0.0	41.0	52.4	-0.15	-0.12	-25.28	3.3	24.22	No Adj. Made
LOWREW45	4/25/22 10:43	25.6	29.8	0.0	44.6	61.4	-0.06	-0.06	-24.24	3.4	24.44	No Adj. Made
LOWREW45	5/18/22 12:15	27.9	31.1	0.0	41.0	84.0	-0.05	-0.01	-24.86	1.8	24.30	No Adj. Made
LOWREW45	6/6/22 9:26	22.7	28.6	0.0	48.7	72.5	-0.50	-0.45	-23.07	2.4	24.21	No Adj. Made
LOWREW46	1/11/22 9:47	40.5	35.9	0.5	23.1	62.0	-0.18	-0.18	-11.79	2.5	24.29	No Adj. Made
LOWREW46	2/25/22 11:14	34.2	33.6	0.0	32.2	57.0	-0.17	-0.16	-26.47	2.7	24.37	No Adj. Made
LOWREW46	3/23/22 9:21	34.6	34.2	0.0	31.2	53.9	-0.14	-0.05	-25.04	2.6	24.21	No Adj. Made
LOWREW46	4/25/22 10:40	29.1	30.0	0.0	40.9	62.5	-0.26	-0.22	-24.51	2.9	24.44	No Adj. Made
LOWREW46	5/18/22 12:08	33.5	32.1	0.0	34.4	76.6	-0.03	-0.06	-24.65	1.1	24.29	No Adj. Made
LOWREW46	6/6/22 9:24	28.3	29.1	0.0	42.6	70.7	-0.49	-0.46	-25.04	2.9	24.20	No Adj. Made
LOWREW47	1/11/22 9:41	29.8	33.2	0.7	36.3	53.3	-0.60	-0.60	-11.64	0.6	24.29	No Adj. Made
LOWREW47	2/25/22 11:11	21.9	30.6	0.0	47.5	51.4	-0.23	-0.22	-26.49	2.6	24.36	No Adj. Made

APPENDIX D-1

LANDFILL GAS EXTRACTION WELL MONITORING
JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT
LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW47	3/23/22 9:19	23.6	31.0	0.0	45.4	50.6	-0.07	-0.05	-25.81	2.8	24.21	No Adj. Made
LOWREW47	4/25/22 10:37	22.4	28.8	0.0	48.8	59.7	-0.32	-0.28	-24.10	2.1	24.43	No Adj. Made
LOWREW47	5/18/22 12:05	21.8	28.9	0.2	49.1	83.5	-0.05	-0.05	-24.57	0.7	24.29	No Adj. Made
LOWREW47	6/6/22 9:21	22.7	27.9	0.0	49.4	75.0	-0.58	-0.55	-25.04	2.0	24.20	No Adj. Made
LOWREW48	1/11/22 8:58	19.9	29.3	0.1	50.7	58.0	-0.71	-0.71	-11.37	2.3	24.31	No Adj. Made
LOWREW48	2/25/22 10:33	13.8	28.4	0.3	57.5	59.0	-0.14	-0.16	-26.01	2.9	24.37	No Adj. Made
LOWREW48	3/23/22 8:57	20.7	29.6	0.1	49.6	53.5	-0.23	-0.19	-25.57	2.5	24.25	No Adj. Made
LOWREW48	4/25/22 10:10	12.7	25.1	0.0	62.2	61.9	-0.25	-0.22	-24.35	2.3	24.46	No Adj. Made
LOWREW48	5/18/22 11:36	17.9	27.7	0.2	54.2	80.1	-0.19	-0.16	-24.40	2.2	24.32	No Adj. Made
LOWREW48	6/6/22 8:58	9.9	25.6	0.0	64.5	72.8	-0.41	-0.38	-24.49	2.3	24.21	No Adj. Made
LOWREW49	1/11/22 9:09	25.3	31.7	0.9	42.1	57.3	-0.30	-0.30	-10.74	1.1	24.31	No Adj. Made
LOWREW49	2/25/22 10:40	16.5	29.1	0.0	54.4	57.0	-0.31	-0.30	-25.24	1.8	24.37	No Adj. Made
LOWREW49	3/23/22 9:02	23.4	30.1	0.1	46.4	52.6	-0.18	-0.16	-25.11	2.3	24.25	No Adj. Made
LOWREW49	4/25/22 10:17	13.1	24.8	0.0	62.1	61.3	-0.11	-0.10	-23.75	2.3	24.45	No Adj. Made
LOWREW49	5/18/22 11:42	23.1	28.3	0.3	48.3	83.0	-0.16	-0.12	-24.11	1.7	24.31	No Adj. Made
LOWREW49	6/6/22 9:05	14.7	26.2	0.0	59.1	73.7	-0.41	-0.40	-24.26	2.6	24.20	No Adj. Made
LOWREW50	1/11/22 9:20	22.0	30.0	0.3	47.7	64.6	-0.93	-0.96	-10.09	3.3	24.29	No Adj. Made
LOWREW50	2/25/22 10:49	25.5	30.7	0.0	43.8	59.6	-0.44	-0.45	-24.40	1.7	24.36	No Adj. Made
LOWREW50	3/23/22 9:08	33.5	33.1	0.0	33.4	58.0	-0.57	-0.50	-23.32	3.2	24.22	No Adj. Made
LOWREW50	4/25/22 10:23	28.3	28.6	0.0	43.1	64.5	-0.47	-0.45	-20.96	3.3	24.44	No Adj. Made
LOWREW50	5/18/22 11:49	33.6	30.2	0.1	36.1	82.8	-0.31	-0.26	-23.14	3.4	24.29	No Adj. Made
LOWREW50	6/6/22 9:10	25.2	28.3	0.0	46.5	76.6	-0.88	-0.85	-19.30	3.1	24.19	No Adj. Made
LOWREW55	1/11/22 10:08	53.4	37.8	0.2	8.6	68.4	-1.90	-2.00	-11.72	2.9	24.31	No Adj. Made
LOWREW55	2/25/22 11:30	50.6	37.7	0.0	11.7	66.7	-2.11	-2.08	-26.80	9.8	24.38	No Adj. Made
LOWREW55	3/23/22 9:35	49.5	37.3	0.0	13.2	66.5	-1.45	-1.43	-25.20	10.9	24.24	No Adj. Made
LOWREW55	4/25/22 10:54	44.5	34.3	0.0	21.2	69.1	-1.72	-1.72	-24.04	11.1	24.45	No Adj. Made
LOWREW55	5/18/22 12:29	46.7	35.8	0.2	17.3	76.4	-1.18	-1.19	-24.95	8.5	24.33	No Adj. Made
LOWREW55	6/6/22 9:36	44.0	33.2	0.0	22.8	72.3	-2.33	-2.31	-24.52	11.7	24.21	No Adj. Made
LOWREW56	1/11/22 10:19	36.7	32.9	0.2	30.2	66.3	-1.00	-0.99	-6.62	2.3	24.30	No Adj. Made
LOWREW56	2/25/22 11:38	35.0	32.7	0.0	32.3	64.2	-0.57	-0.55	-22.93	5.1	24.37	No Adj. Made
LOWREW56	3/23/22 9:40	40.8	34.5	0.1	24.6	59.6	-0.39	-0.34	-20.22	2.8	24.23	No Adj. Made
LOWREW56	4/25/22 10:59	26.1	28.3	0.0	45.6	65.7	-0.57	-0.49	-19.44	3.7	24.44	No Adj. Made
LOWREW56	5/18/22 12:36	38.1	32.0	0.0	29.9	83.0	-0.10	-0.05	-20.44	2.4	24.29	No Adj. Made
LOWREW56	6/6/22 9:41	26.9	28.2	0.0	44.9	73.2	-0.92	-0.89	-20.57	2.5	24.20	No Adj. Made
LOWREW57	1/11/22 11:24	51.3	35.8	0.8	12.1	73.5	-3.00	-2.90	-11.83	3.6	24.31	No Adj. Made
LOWREW57	2/25/22 12:30	48.8	36.2	0.0	15.0	73.4	-1.19	-1.19	-26.95	5.8	24.35	No Adj. Made
LOWREW57	3/23/22 10:22	46.1	35.3	0.1	18.5	71.5	-1.31	-1.23	-25.69	6.0	24.23	No Adj. Made

APPENDIX D-1 LANDFILL GAS EXTRACTION WELL MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

			Carbon			Initial	Initial Static	Adjusted Static	Header	Initial	Barometric	
		Methane	Dioxide	Oxygen	Balance	Temperature	Pressure	Pressure	Pressure	Flow	Pressure	
ID	Date/Time	(%) ^{a/}	(%)	(%)	(%)	(°F) ^{b/}	("H ₂ O) ^{c/}	("H ₂ O)	("H ₂ O)	(scfm) ^{d/}	("Hg) ^{e/}	Comments
LOWREW57	4/25/22 11:53	43.9	32.4	0.0	23.7	74.1	-1.03	-0.98	-24.94	5.3	24.44	No Adj. Made
LOWREW57	5/19/22 11:50	47.5	33.9	0.0	18.6	87.4	-0.14	-0.14	-24.70	3.1	23.93	No Adj. Made
LOWREW57	6/6/22 10:19	46.2	34.6	0.0	19.2	77.7	-2.04	-1.98	-25.56	6.9	24.21	No Adj. Made
LOWREW58	1/11/22 11:13	39.8	31.1	0.8	28.3	68.6	-0.24	-0.24	-11.96	3.4	24.30	No Adj. Made
LOWREW58	2/25/22 12:23	30.7	30.2	0.0	39.1	63.5	-0.05	-0.05	-24.19	4.3	24.27	No Adj. Made
LOWREW58	3/23/22 10:13	30.0	29.7	0.1	40.2	61.4	-0.36	-0.26	-23.23	2.6	24.21	No Adj. Made
LOWREW58	4/25/22 11:45	28.0	27.2	0.0	44.8	68.5	-0.21	-0.18	-22.14	2.4	24.43	No Adj. Made
LOWREW58	5/19/22 11:42	31.8	27.6	0.0	40.6	87.5	-0.12	-0.12	-23.47	2.6	23.92	No Adj. Made
LOWREW58	6/6/22 10:13	29.8	27.2	0.0	43.0	73.4	-0.76	-0.72	-22.10	7.2	24.20	No Adj. Made
LOWREW59	1/13/22 8:19	49.4	34.4	1.0	15.2	61.9	-1.00	-0.90	-10.55	3.2	24.20	No Adj. Made
LOWREW59	2/25/22 12:59	39.3	31.5	0.4	28.8	64.0	-0.06	-0.08	-23.09	8.9	24.33	No Adj. Made
LOWREW59	3/29/22 8:48	42.0	32.1	0.0	25.9	64.0	-0.34	-0.29	-24.18	6.2	23.80	No Adj. Made
LOWREW59	4/26/22 9:40	36.3	30.1	0.5	33.1	68.1	-0.05	-0.04	-21.40	4.7	24.32	No Adj. Made
LOWREW59	5/20/22 9:50	40.9	32.6	0.0	26.5	61.9	-1.34	-1.23	-22.99	6.2	24.00	No Adj. Made
LOWREW59	6/6/22 10:38	40.7	30.3	0.0	29.0	72.7	-0.69	-0.65	-22.33	4.6	24.20	No Adj. Made
LOWREW5A	1/13/22 10:00	29.8	35.0	0.8	34.4	53.6	-0.17	-0.18	-10.09	2.0	24.23	No Adj. Made
LOWREW5A	2/28/22 10:01	30.7	31.5	0.0	37.8	57.2	-0.20	-0.21	-25.49	1.7	24.45	No Adj. Made
LOWREW5A	3/29/22 10:17	26.8	33.4	0.0	39.8	54.9	-0.26	-0.20	-22.81	1.9	23.76	No Adj. Made
LOWREW5A	4/26/22 11:04	26.8	30.3	0.2	42.7	64.2	-0.28	-0.25	-22.34	1.8	24.33	No Adj. Made
LOWREW5A	5/20/22 10:57	25.8	32.4	0.0	41.8	46.7	-1.33	-1.29	-22.06	2.0	24.00	No Adj. Made
LOWREW5A	6/6/22 11:47	25.8	28.0	0.0	46.2	77.0	-0.62	-0.60	-21.42	1.7	24.20	No Adj. Made
LOWREW60	1/13/22 8:10	57.8	36.9	1.0	4.3	62.3	-0.80	-0.80	-8.79	3.4	24.30	No Adj. Made
LOWREW60	2/25/22 12:52	45.5	33.9	0.6	20.0	64.1	-0.21	-0.20	-21.77	1.7	24.34	No Adj. Made
LOWREW60	3/29/22 8:42	44.7	33.4	0.0	21.9	62.2	-0.30	-0.26	-22.11	5.0	23.81	No Adj. Made
LOWREW60	4/26/22 9:30	43.8	33.4	0.0	22.8	70.2	-0.10	-0.04	-20.81	2.6	24.32	No Adj. Made
LOWREW60	5/20/22 9:42	42.7	34.4	0.0	22.9	57.0	-1.22	-1.18	-21.02	3.4	24.00	No Adj. Made
LOWREW60	6/6/22 10:31	40.3	32.3	0.0	27.4	74.1	-0.77	-0.72	-20.74	2.6	24.20	No Adj. Made
LOWREW61	1/13/22 8:56	43.5	33.3	0.1	23.1	63.6	-1.21	-1.25	-9.66	5.0	24.19	No Adj. Made
LOWREW61	2/28/22 8:57	43.6	33.0	0.2	23.2	65.5	-0.47	-0.46	-23.61	6.7	24.45	No Adj. Made
LOWREW61	3/29/22 9:23	40.7	32.6	0.0	26.7	62.3	-0.12	-0.09	-22.60	6.0	23.78	No Adj. Made
LOWREW61	4/26/22 10:11	40.1	31.3	0.2	28.4	67.9	-0.04	-0.05	-21.58	3.3	24.31	No Adj. Made
LOWREW61	5/20/22 10:15	40.5	33.1	0.0	26.4	60.8	-1.38	-1.32	-24.13	6.2	24.00	No Adj. Made
LOWREW61	6/6/22 11:01	41.3	31.5	0.0	27.2	70.5	-0.69	-0.58	-21.69	3.3	24.19	No Adj. Made
LOWREW62	1/13/22 8:28	46.4	32.3	0.3	21.0	61.0	-1.40	-1.40	-7.28	2.6	24.20	No Adj. Made
LOWREW62	2/25/22 13:06	40.6	31.3	0.0	28.1	63.3	-0.36	-0.29	-23.79	6.4	24.32	No Adj. Made
LOWREW62	3/29/22 8:53	41.0	31.0	0.0	28.0	57.6	-0.44	-0.42	-22.63	1.3	23.80	No Adj. Made
LOWREW62	4/26/22 9:47	41.3	29.7	0.4	28.6	69.5	-0.11	-0.07	-20.17	1.6	24.31	No Adj. Made

APPENDIX D-1 LANDFILL GAS EXTRACTION WELL MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

ID	Date/Time	Methane	Carbon Dioxide (%)	Oxygen (%)	Balance (%)	Initial Temperature (°F) ^{b/}	Initial Static Pressure ("H ₂ O) ^{c/}	Adjusted Static Pressure ("H ₂ O)	Header Pressure ("H ₂ O)	Initial Flow (scfm) ^{d/}	Barometric Pressure ("Hg) ^{e/}	Comments
LOWREW62	5/20/22 9:55	39.6	31.2	0.0	29.2	56.4	-1.53	-1.50	-22.52	3.1	24.00	No Adj. Made
LOWREW62	6/6/22 10:44	40.2	29.2	0.0	30.6	76.0	-0.76	-0.74	-20.66	2.1	24.19	No Adj. Made
LOWREW63	1/13/22 9:14	35.4	37.4	0.0	27.2	58.0	-0.47	-0.47	-12.45	3.9	24.19	No Adj. Made
LOWREW63	2/28/22 9:16	40.1	37.0	0.0	22.9	60.9	-0.91	-0.85	-28.67	4.9	24.44	No Adj. Made
LOWREW63	3/29/22 9:34	39.1	38.2	0.0	22.7	52.9	-0.09	-0.06	-26.28	3.4	23.76	No Adj. Made
LOWREW63	4/26/22 10:27	39.5	36.6	0.4	23.5	63.5	-0.15	-0.09	-25.51	3.4	24.31	No Adj. Made
LOWREW63	5/20/22 10:27	29.8	34.8	0.0	35.4	51.1	-1.73	-1.69	-25.01	4.0	23.99	No Adj. Made
LOWREW63	6/6/22 11:13	28.4	30.6	0.0	41.0	71.5	-1.01	-0.98	-25.78	2.7	24.19	No Adj. Made
LOWREW64	1/13/22 9:05	41.4	38.9	0.2	19.5	54.8	-1.50	-1.40	-9.83	1.4	24.19	No Adj. Made
LOWREW64	2/28/22 9:07	42.1	37.6	0.0	20.3	59.5	-2.35	-2.35	-24.69	3.8	24.45	No Adj. Made
LOWREW64	3/29/22 9:28	39.2	37.4	0.0	23.4	53.6	-1.75	-1.69	-21.63	3.7	23.78	No Adj. Made
LOWREW64	4/26/22 10:18	37.9	35.4	0.5	26.2	65.6	-1.44	-1.40	-21.55	3.9	24.31	No Adj. Made
LOWREW64	5/20/22 10:21	37.9	37.6	0.0	24.5	51.2	-3.55	-3.49	-23.47	4.4	24.00	No Adj. Made
LOWREW64	6/6/22 11:07	37.6	36.0	0.0	26.4	72.0	-2.51	-2.50	-21.75	3.0	24.19	No Adj. Made

a/ % = Percent

b/ Deg F = Degrees Fahrenheit

c/ "H2O = Inches of water

d/ scfm = Standard cubic feet per minute

e/ " Hg = Inches of mercury

FLARE/GAS-TO-ENERGY PLANT STATION MONITORING

APPENDIX D-2.1

FLARE STATION MONITORING LOWRY INLET

APPENDIX D-2.1 FLARE STATION MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

Lowry Inlet

					lowry finet	Static	_		Current *	
Cample Daint	Date and Time	% Methane	% Carbon Dioxide	0/ Overgon	% Balance Gas	Pressure	Temp (°F) ^{b/}	Flow (scfm) ^{c/}	Power (BTU/h) ^{d/}	Comments
Sample Point						("H ₂ O) ^{a/}	` '		, ,	Comments
LOWRINLT	1/5/2022 13:35	31.3	30.0	2.2	36.5	-12.80	49.0	138	2622.74	
LOWRINLT	1/14/2022 15:53	25.1	27.2	3.0	44.7	-21.11	49.0	184	2804.29	
LOWRINLT	1/21/2022 13:23	24.4	27.8	3.2	44.6	-34.65	48.0	224	3318.71	
LOWRINLT	1/27/2022 14:42	25.3	26.8	3.0	44.9	-32.08	47.2	218	3342.9	
LOWRINLT	1/31/2022 14:02	37.3	30.0	2.1	30.6	-34.28	46.6	219	4964.2	
LOWRINLT	2/4/2022 14:28	31.8	29.6	1.5	37.1	-33.41	46.4	218	4210.1	
LOWRINLT	2/8/2022 15:31	32.9	29.2	1.3	36.6	-33.72	49.0	216	4313.8	
LOWRINLT	2/14/2022 14:54	37.2	30.0	1.7	31.1	-34.86	45.6	226	5106.4	
LOWRINLT	2/18/2022 14:29	27.4	23.8	3.6	45.2	-33.53	45.6	227	3777.2	
LOWRINLT	2/23/2022 15:10	32.4	27.1	2.4	38.1	-19.26	45.0	204	4018.2	
LOWRINLT	2/24/2022 14:58	30.7	27.9	2.3	39.1	-34.81	44.9	224	4169.7	
LOWRINLT	2/28/2022 15:09	36.9	29.6	1.5	32.0	-34.89	45.1	214	4794.3	
LOWRINLT	3/7/2022 15:14	34.8	29.4	1.4	34.4	-34.98	45.1	215	4521.45	
LOWRINLT	3/10/2022 14:26	30.0	27.6	3.2	39.2	-33.83	45.0	216	3930.1	
LOWRINLT	3/14/2022 14:43	26.9	26.0	2.5	44.6	-34.24	45.0	217	3540.2	
LOWRINLT	3/22/2022 16:08	25.7	26.0	2.6	45.7	-33.03	44.9	211	3298.3	
LOWRINLT	3/25/2022 12:15	24.1	27.1	2.4	46.4	-32.98	45.0	206	3020.6	
LOWRINLT	4/6/2022 15:50	23.9	25.6	2.8	47.7	-32.54	46.4	191	2767.2	
LOWRINLT	4/8/2022 16:01	30.6	29.2	1.3	38.9	-31.46	46.6	194	3604.4	
LOWRINLT	4/15/2022 17:14	26.7	26.9	2.5	43.9	-31.15	47.4	186	3014.9	
LOWRINLT	4/22/2022 15:31	33.4	30.5	1.4	34.7	-30.80	48.3	183	3715.5	
LOWRINLT	4/29/2022 13:49	26.2	26.8	2.8	44.2	-30.51	49.4	183	2914.8	
LOWRINLT	5/3/2022 16:35	30.6	28.4	2.1	38.9	-35.89	49.8	191	3551.1	
LOWRINLT	5/6/2022 15:32	29.4	28.1	2.0	40.5	-35.88	50.1	194	3468.4	
LOWRINLT	5/9/2022 16:00	26.8	27.1	2.5	43.6	-35.52	50.4	184	2995.6	
LOWRINLT	5/13/2022 16:16	27.4	29.2	1.8	41.6	-35.40	51.1	190	3163.4	
LOWRINLT	5/16/2022 16:01	30.1	27.9	2.1	39.9	-35.65	51.6	192	3514.9	
LOWRINLT	5/19/2022 15:36	32.4	29.2	1.5	36.9	-33.49	52.1	196	3859.1	
LOWRINLT	5/23/2022 16:01	28.0	27.9	2.0	42.1	-33.75	53.1	201	3412.9	
LOWRINLT	5/26/2022 14:34	27.0	25.4	2.1	45.5	-33.04	53.3	200	3282.5	
LOWRINLT	5/31/2022 15:43	23.4	26.2	2.5	47.9	-30.92	53.7	198	2810.3	
LOWRINLT	6/3/2022 12:56	28.2	26.6	1.8	43.4	-30.61	54.0	196	3351.7	
LOWRINLT	6/6/2022 14:43	31.1	28.0	1.5	39.4	-31.51	54.4	194	3664.4	
LOWRINLT	6/14/2022 16:27	28.1	25.5	2.8	43.6	-29.60	55.9	191	3254.8	

APPENDIX D-2.1 FLARE STATION MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

Lowry Inlet

Sample Point	Date and Time	% Methane	% Carbon Dioxide	% Oxygen	% Balance Gas	Static Pressure ("H ₂ O) ^{a/}	Temp (°F) ^{b/}	Flow (scfm) ^{c/}	Current * Power (BTU/h) ^{d/}	Comments
LOWRINLT	6/16/2022 16:03	31.8	25.2	1.7	41.3	-29.00	56.4	184	3553.7	
LOWRINLT	6/24/2022 15:22	27.6	27.2	2.2	43.0	-28.68	58.4	177	2963.3	

* Note: The BTU calculation is based upon a methane value of 1009.7 BTU/scf at standard conditions. This data is taken from the petroleum industry book

[&]quot;Gas Processors Association Engineering Data Book", Ninth Edition, Tulsa OK, 1972.

a/ "H₂O=inches of water

b/ °F= Degrees Fahrenheit

c/ scfm= standard cubic feet per minute

d/ BTU/h= British Thermal Unit per hour

APPENDIX D-2.2

FLARE STATION MONITORING DADS BLOWER FLARE

APPENDIX D-2.2 GAS-TO-ENERGY PLANT MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

DADS Blower Flare

				Carbon		Balance	Initial Static	Initial	Initial	Initial	
			Methane	Dioxide	Oxygen	Gas	Pressure	Temperature	Flow	Power	
Location	Sample Point	Date and Time	(%)	(%)	(%)	(%)	(" H2O) ^{a/}	(° F) ^{b/}	(scfm) ^{c/}	$(BTU/h)^{d/}$	Comments
DADS Blower Flare	DASPFLR1	1/5/2022 13:42	42.4	35.3	0.4	21.9	7.30	80	501	12898.4	
DADS Blower Flare	DASPFLR1	1/27/2022 14:55	32.6	32.4	1.3	33.7	7.04	91	503	9968.0	
DADS Blower Flare	DASPFLR1	2/4/2022 14:43	39.5	33.6	0.5	26.4	7.50	34	513	12305.2	
DADS Blower Flare	DASPFLR1	2/8/2022 15:43	41.3	33.5	0.4	24.8	7.23	32	513	12864.9	
DADS Blower Flare	DASPFLR1	2/14/2022 15:44	49.1	35.0	0.6	15.3	7.49	97	507	15121.4	
DADS Blower Flare	DASPFLR1	2/18/2022 14:41	36.0	30.0	0.8	33.2	7.41	97	504	11012.3	
DADS Blower Flare	DASPFLR1	2/23/2022 15:23	43.4	33.6	0.6	22.4	7.13	76	494	13028.2	
DADS Blower Flare	DASPFLR1	3/7/2022 15:24	43.4	34.1	0.5	22.0	7.47	98	501	13198.0	
DADS Blower Flare	DASPFLR1	3/14/2022 14:51	34.3	30.7	0.7	34.3	7.68	102	500	10400.8	
DADS Blower Flare	DASPFLR1	3/22/2022 16:19	34.9	31.5	0.8	32.8	7.09	93	497	10531.1	
DADS Blower Flare	DASPFLR1	3/25/2022 12:23	34.1	31.7	0.6	33.6	7.37	102	498	10299.6	
DADS Blower Flare	DASPFLR1	4/6/2022 15:58	31.1	30.6	0.9	37.4	7.44	97	497	9394.5	
DADS Blower Flare	DASPFLR1	4/8/2022 16:07	41.2	34.4	0.0	24.4	7.62	99	504	12623.6	
DADS Blower Flare	DASPFLR1	4/22/2022 15:39	44.3	35.0	0.5	20.2	7.84	100	499	13435.1	
DADS Blower Flare	DASPFLR1	5/3/2022 16:42	41.7	33.8	0.7	23.8	7.60	109	499	12630.1	
DADS Blower Flare	DASPFLR1	5/6/2022 15:39	38.4	32.7	0.6	28.3	7.51	110	503	11721.2	
DADS Blower Flare	DASPFLR1	5/9/2022 16:07	34.9	31.7	0.8	32.6	7.51	112	501	10625.4	
DADS Blower Flare	DASPFLR1	5/13/2022 16:22	34.6	34.0	0.5	30.9	7.85	114	500	10497.0	
DADS Blower Flare	DASPFLR1	5/19/2022 15:42	43.3	33.8	0.6	22.3	7.67	110	498	13096.0	
DADS Blower Flare	DASPFLR1	5/23/2022 16:08	36.7	32.4	0.7	30.2	7.51	107	505	11267.9	
DADS Blower Flare	DASPFLR1	5/26/2022 14:40	34.9	29.0	0.8	35.3	7.84	112	504	10684.1	
DADS Blower Flare	DASPFLR1	6/3/2022 13:05	37.6	30.9	0.5	31.0	7.85	0.1	497	11336.5	
DADS Blower Flare	DASPFLR1	6/6/2022 14:51	38.8	30.8	0.5	29.9	7.55	108	497	11703.2	
DADS Blower Flare	DASPFLR1	6/16/2022 16:10	41.1	30.0	0.6	28.3	7.83	110	506	12630.4	
DADS Blower Flare	DASPFLR1	6/24/2022 15:30	35.9	31.8	0.7	31.6	7.67	106	506	11022.0	

* Note: The BTU calculation is based upon a methane value of 1009.7 BTU/scf at standard conditions. This data is taken from the petroleum industry book

"Gas Processors Association Engineering Data Book", Ninth Edition, Tulsa OK, 1972.

a/ " $H_2O=$ inches water

b/ ° F= Degrees Fahrenheit

c/ scfm= standard cubic feet per minute

d/ BTU/h= British Thermal Unit per hour

APPENDIX D-2.3

FLARE STATION MONITORING FLARE STATION 3

APPENDIX D-2.3 GAS-TO-ENERGY PLANT MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

Flare Station 3 - Candlestick Flare

				Carbon		Balance	Initial Static	Initial	Initial	Initial	
			Methane	Dioxide	Oxygen	Gas	Pressure	Temperature	Flow	Power	
Location	Sample Point	Date Time	(%)	(%)	(%)	(%)	(" H2O) ^{a/}	(° F) ^{b/}	(scfm) ^{c/}	$(BTU/h)^{d/}$	Comments
Flare Station 3	DASPFLR3	1/5/2022 13:49	48.7	37.3	0.7	13.3	3.94	84	883	26110.9	
Flare Station 3	DASPFLR3	1/21/2022 13:31	32.9	32.3	1.2	33.6	7.32	96	507	10128.3	
Flare Station 3	DASPFLR3	1/27/2022 15:11	47.7	39	1.2	12.1	15.28	92	1862	34140.8	
Flare Station 3	DASPFLR3	2/4/2022 14:58	48.5	38.6	0.5	12.4	3.09	53	932	27473.6	
Flare Station 3	DASPFLR3	2/8/2022 15:56	49.6	37.9	0.5	12	3.19	79	951	28642.0	
Flare Station 3	DASPFLR3	2/14/2022 15:59	52.2	37.9	0.6	9.3	3.12	84	937	29698.7	
Flare Station 3	DASPFLR3	2/18/2022 14:53	44	33.3	0.5	22.2	2.8	78	807	21536.3	
Flare Station 3	DASPFLR3	3/7/2022 15:34	51.4	38.6	0.5	9.5	7.28	81	1322	34140.8	
Flare Station 3	DASPFLR3	3/14/2022 15:06	46.7	36.7	0.6	16	6.36	87	1187	33667.6	
Flare Station 3	DASPFLR3	3/22/2022 16:30	45.3	37	1	16.7	5.92	75	1153	31696.1	
Flare Station 3	DASPFLR3	3/25/2022 12:39	44.5	36.5	0.6	18.4	5.61	85	1152	31113.8	
Flare Station 3	DASPFLR3	4/6/2022 16:06	41.6	34.2	0.9	23.3	4.33	79	954	24121.8	
Flare Station 3	DASPFLR3	4/8/2022 16:15	49.9	37.7	0	12.4	4.97	90	1100	33334.8	
Flare Station 3	DASPFLR3	4/22/2022 15:55	50.6	36.8	0.6	12	5.64	97	1127	34140.8	
Flare Station 3	DASPFLR3	5/3/2022 16:50	46.2	36.3	0.7	16.8	5.85	87	1116	31293.6	
Flare Station 3	DASPFLR3	5/6/2022 15:49	46.4	36.3	0.6	16.7	4.28	96	1051	29613.4	
Flare Station 3	DASPFLR3	5/9/2022 16:16	45.6	35.7	0.8	17.9	4.23	93	986	27301.2	
Flare Station 3	DASPFLR3	5/13/2022 16:33	42.1	38	0.6	19.3	4.9	96	1048	26779.6	
Flare Station 3	DASPFLR3	5/19/2022 15:50	48.9	35.3	1	14.8	9.69	103	1381	34140.8	
Flare Station 3	DASPFLR3	5/23/2022 16:18	42.8	34	1.3	21.9	4.13	88	1047	27226.1	
Flare Station 3	DASPFLR3	5/26/2022 14:48	42.2	31.1	0.7	26	4.7	100	1030	26399.5	
Flare Station 3	DASPFLR3	6/3/2022 13:14	43.7	32.9	0.5	22.9	5.12	99	1067	27008.6	
Flare Station 3	DASPFLR3	6/6/2022 15:00	47.7	36.6	0.3	15.4	4.71	99	1030	29836.3	
Flare Station 3	DASPFLR3	6/16/2022 16:19	50.9	33.9	0.4	14.8	4.86	100	1044	32290.7	
Flare Station 3	DASPFLR3	6/24/2022 15:40	42.7	34.7	0.7	21.9	5.15	98	967	25063.2	

* Note: The BTU calculation is based upon a methane value of 1009.7 BTU/scf at standard conditions. This data is taken from the petroleum industry book "Gas Processors Association Engineering Data Book", Ninth Edition, Tulsa OK, 1972

a/ "H2O= inches water

b/ ° F= Degrees Fahrenheit

c/ scfm= standard cubic feet per minute

d/ BTU/h= British Thermal Unit per hour

APPENDIX D-2.4

FLARE STATION MONITORING COMBINED SOURCES AT GAS-TO-ENERGY PLANT

APPENDIX D-2.4 GAS-TO-ENERGY PLANT MONITORING JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE REPORT LOWRY LANDFILL SUPERFUND SITE

Gas-to-Energy Plant

				Carbon	is-to-Ener	Balance	Initial Static	Initial	Initial		
			Methane	Dioxide	Oxygen	Gas	Pressure	Temperature	Flow	Initial Power	
Location	Sample Point	Date and Time	(%)	(%)	(%)	(%)	(" H ₂ O) ^{a/}	(° F) ^{b/}	(scfm) ^{c/}	(BTU/h) ^{d/}	Comments
Gas Plant	DASPGAP1	1/5/2022 13:55	54.0	39.7	0.4	5.9	69.25	86.0	1013	33201.9	
Gas Plant	DASPGAP1	1/21/2022 13:46	40.0	35.4	1.1	23.5	2.30	71.0	747	18143.1	
Gas Plant	DASPGAP1	1/21/2022 13:51	49.7	38.9	0.9	10.5	69.86	95.0	1084	32718.8	
Gas Plant	DASPGAP1	2/4/2022 15:08	56.3	40.3	0.4	3.0	70.24	91.9	1010	34140.8	
Gas Plant	DASPGAP1	2/8/2022 16:07	56.3	40.1	0.4	3.2	69.19	97.1	1004	34140.8	
Gas Plant	DASPGAP1	2/14/2022 16:07	58.8	40.7	0.5	0.0	69.33	75.0	1030	34140.8	
Gas Plant	DASPGAP1	2/18/2022 14:59	55.0	37.6	0.3	7.1	67.82	109.0	1012	33784.9	
Gas Plant	DASPGAP1	2/23/2022 15:43	56.3	38.8	0.3	4.6	65.66	56.6	972	33221.1	
Gas Plant	DASPGAP1	3/7/2022 15:44	56.5	40.6	0.5	2.4	67.77	95.7	842	28893.0	
Gas Plant	DASPGAP1	3/14/2022 15:12	52.8	39.5	0.5	7.2	56.18	93.3	1059	33968.0	
Gas Plant	DASPGAP1	3/22/2022 16:37	48.3	38.0	1.1	12.6	67.16	64.9	1072	31419.4	
Gas Plant	DASPGAP1	3/25/2022 12:46	49.2	38.5	0.6	11.7	66.98	88.5	1058	31621.8	
Gas Plant	DASPGAP1	4/6/2022 16:16	47.4	38.2	0.7	13.7	66.41	79.7	1106	31810.5	
Gas Plant	DASPGAP1	4/8/2022 16:22	52.4	39.6	0.0	8.0	66.79	82.0	1025	32620.5	
Gas Plant	DASPGAP1	4/22/2022 16:02	52.2	38.6	0.5	8.7	66.37	96.7	1026	32553.1	
Gas Plant	DASPGAP1	5/3/2022 16:55	50.6	38.5	0.6	10.3	66.59	69.0	1107	33978.9	
Gas Plant	DASPGAP1	5/6/2022 15:55	49.2	37.6	0.5	12.7	66.52	80.1	1067	31857.0	
Gas Plant	DASPGAP1	5/9/2022 16:25	48.8	37.7	0.8	12.7	64.92	73.5	1090	32294.8	
Gas Plant	DASPGAP1	5/13/2022 16:38	45.8	40.0	0.5	13.7	67.17	74.8	1073	29849.7	
Gas Plant	DASPGAP1	5/19/2022 15:55	50.6	37.1	1.0	11.3	67.12	85.1	791	24321.6	
Gas Plant	DASPGAP1	5/23/2022 16:24	47.9	36.3	1.4	14.4	66.35	72.0	1143	33269.2	
Gas Plant	DASPGAP1	5/26/2022 14:54	47.6	34.5	0.6	17.3	67.13	81.8	1063	30689.3	
Gas Plant	DASPGAP1	6/3/2022 13:25	48.6	35.3	0.4	15.7	0.22	77.4	1050	30998.3	-
Gas Plant	DASPGAP1	6/6/2022 15:07	51.1	38.3	0.2	10.4	64.98	92.0	1050	32584.7	
Gas Plant	DASPGAP1	6/16/2022 16:23	53.1	35.5	0.3	11.1	66.90	95.7	1081	34140.8	
Gas Plant	DASPGAP1	6/24/2022 15:46	46.7	36.4	0.6	16.3	63.33	81.4	1110	31492.8	<u>-</u>

58.8

^{*} Note: The BTU calculation is based upon a methane value of 1009.7 BTU/scf at standard conditions. This data is taken from the petroleum industry book "Gas Processors Association Engineering Data Book", Ninth Edition, Tulsa OK, 1972.

a/ "H2O= inches water

b/ ° F= Degrees Fahrenheit

c/ scfm= standard cubic feet per minute

d/ BTU/h= British Thermal Unit per hour

APPENDIX D-2.5 FLARE STATION MONITORING DAILY FIELD NOTES

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/4d/yy)			92/05/22		
	Lowry Hea	der - Monitoring	7 /		
Firme (hh mm)			1333		
Technician (Initials)		<u> </u>	0		
Control Panel - Digital Recorder	~				
Flow Rate (scrm)			138		
Gas Temperature (F)			49.0		
	Flare 2	- Monitoring			
Time (bh:mm)			1338		
Technician (Initials)			05-	1	
Control Panel					-
*Indicator Lights OK (Check for Yes)			L		
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)			U		
Cantral Panel - Touchscreen - Process Overview			or took property and a second of the second		
*Gas Handling Skid Inlet Pressure (Inwc)			101		
*Flare DP (InWC)		1	5.08		
*Flare Flame Temperature (F)			2006		
Control Panel - Touchscreen (Press Next)		In the second se			L
Panel Temperature (F)			1 71		
*Gas Handling Skid Inlet Temperature (F)					
*Recirculation Valve Position (sclosed)			52		
Control Panel - Touchscreen - Flore Flow Data (Press	Back to Story Story				
*Flow Rate (scrm)	i aoc≡ ∠x, riare Flow De	naf	1		
*Total Flow (MMSCF)			1861.88 C:2		
*Flow Pressure (Inwc)			1661.88		
			Ci2		- 4
*Flow Temperature (r)		1	80		
Control Panel - Touchscreen (Press Resettable Flow History	, Analog Data Menu, B	lower Data)			
*Resettable Total Flow (MMscF)			718.22		
*Reset Date/Time (mm/dd/yy bh.mm.ss)					
Control Panel - Touchscreen - Blower Data (Press Ma	in)				
*Blower 301 Runtime (Hours)			39662		
*Blower 301 Vibration (In/Sec)			0.21		
*Blower 301 Speed (xmax)			70		1
*Blower 301 Inlet Bearing Temp (F)			441		
*Blower 301 Outlet Bearing Temp (r)			011		
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)		l	10.3		
Gas Handling Skid	o constant y t to the gallety had a				
*Demister Inlet Pressure (Inwc)			-15.6		politica divide an Marin additional and sussess
*Demister Outlet Pressure (Inwc)		***************************************	-708		
*Demister DP (towc)			1777		
*Flame Arrester Inlet Pressure (IAWC)	The same depleting in		1777	-	
*Flame Arrester Outlet Pressure (nwc)			14421		
•Flame Arrester DP (Inwc)			ナップ		
Flore		1			
*Visible Emissions (Yes/No. If yes explain)		1	100		
*Spiralator Position (Kopen)			N. Committee		
*Manual Louver 1 Position (xopen)	-	_	20		
*Manual Louver 2 Position (xopen)			En		
Other					
Heat Trace OK (Check for Yes)					
*Propane Tank Level OK (11 12 (Check for Yea))		10 1 1 1	14		
	Flare 3	- Monitoring			
Time (hh.mm)			1344		
Technician (Initials)		1	05		
Control Panel			/		
*Indicator Lights OK (Check for Yes)					
*Heating/Cooling OK (check for Yes)			I V		
Control Panel - Digital Recorder					
*Remote Recorder On (Check for Yes)		7,000	The second secon		

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
ontrol Panel - Touchscreen - Analog Data Menu	- Process Overview	v			Accessed to the second
Gas Handling Skid Inlet Vacuum (Inwc)			39.8		100
Gas Handling Skid Inlet Temperature (F)			59		
Panel Temperature (F)			75		
Recirculation Valve Position (school)			100		The same of the sa
Flare Flame Temperature (F)			1325		
Flame Arrestor Temperature (r)			EI		
Control Panel - Touchscreen - Blower Data (Press)	lack, Blower Menu, Select (Current Blowerj	0-1		
*Blower Runtime (Blower Runtime (Hours))	And the far-free for the first	1	302-370		T -
*Blower Speed (Blower Speed (KMax))			44		
*Blower Vibration (Blower Vibration (In/Sec))		111111111111111111111111111111111111111	0.01		1
*Blower Current (Nower Current (Amps))		1	28.0	1	
Control Panel - Touchscreen - Flare Flow Data (P	ess Back X2, Flare Flow Da	tel	0.6		1
*Flow Rate (SCFM)			853		
*Total Flow (MMscr)			1112 (1		
*Flow Pressure (inwc)			442.CD 3.Z 84		
*Flow Temperature (F)			811		
*Flow DP (Inwc)			100	<u>-</u>	
Control Panel - Touchscreen (Press Resettable)	-		1.89		
*Resettable Total Flow (MMSCF)			111210		
Reset Date/Time (mm/dd/yy hh·mm:ss)	I	***************************************	442.40		
Control Panel - Touchscreen - Alarm History (Pres.					
*Alarm History (Check box if no afarm)	(Main)		T 500 T		pag.
Gas Handling Skid					
*Demister Inlet Pressure (Inwc)	,				
			-40,4		
*Demister Outlet Pressure (Inwc)			-41.3		
*Demister DP (InWC)			+0.0		
*Flame Arrester Inlet Pressure (Inwc)			-13,9		
*Flame Arrester Outlet Pressure (Inwc)			+3,5		
*Flame Arrester DP (Inwc)			+0.4		
*Fail-Close Valve Air Pressure (pil)		and the second second	105		
Flare				10000	
*Visible Emissions (Yes/No, If yes explain)			V.C		
Spiralator Position (xopen)			57		
*Manual Louver 1 Position (Kopen)			50		
*Manual Louver 2 Position (Xopen)			50		
Other					
*Heat Trace OK (Check for Yes)			j		
Propane Tank Level OK (T1 T2 (Check for Yes))			L		
	Engine Plan	t 1 - Monitorin			
Tirne (hh mm)			1351		
Technician (Initials)			Ph-		
Engine Control Panel	*		2-01-01-01-01-01-01-01-01-01-01-01-01-01-		
*Power Setpoint (kWh) (Engine #4 #3)			103 700		1
Power Setpoint (NWh) (Engine #2 #1)		P	1801 101		
Control Room - Loptop	land remarks In market sure	dent martin timerus and annual and a	W-1 C-11		**
*Flow Total (MSCF)			(ATT)(V)	Angelephonegophic subbushe	
*Flow Rate (scrw)	<u> </u>		503268.2		
*Discharge Gas Temperature (F)	d and it intermediate resource constructions are constructions and constructions are constructions.		8/11		SHEET ST.
Engine Bay/Control Room Window		Antonia	0410		
*Inlet Gas Pressure (Inwc)			86.0		
Other			1-42.2	The state of the s	
			127		
*Visible Emissions (Yes/No, If yes explain)			W		
Note * Collect during device operation only	-				
G ANTONOMIA PROPERTY AND A SPECIAL PROPERTY A	R	emarks			
defendence property and the second se			-		
Agentia States and Agentia	- consideration - Andrews			P-7000 P-8000000	
to garden and the state of the					
			78.25		

Day of Week Date (mm/dd/yr)	Monday	Tuesday	Wednesday	Thursday	Friday
	Lowry Hen	der - Monitoring			6-1/1-1/h
Time (bh mm)	20077	aci monitoring			1857
Technician (totuls)					13/15
Control Panel - Digital Recorder	1				-i(-E)
Flow Rate (scrm)		4-4	- 1		1611
Gas Temperature (F)					Per
	Flare 2	- Manitoring	-		1 71
Fime (hh:mm)					1550
Technician (Intela)					73
Control Panel	ī				02
Indicator Lights OK (Check for Yes)		i in			1
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder	1, , L.				
Local Recorder On (Check for Yes)		1			6
Control Panel - Touchscreen - Process Overview	i	!		U	
*Gas Handling Skid Inlet Pressure (Inwc)	1000	1			701
*Flare DP (lawe)	skills der der			4	
*Flare Flame Temperature (F)	1.000				Sin
Control Panel - Touchscreen (Press Nest)		<u> </u>		reference de promissión de altres constituis federana	1910
	1			-W-W162	100
Panel Temperature (r)					42
Gas Handling Skid Inlet Temperature (r)				125	45
*Recirculation Valve Position (xclosed)		<u> </u>			70
Control Panel - Touchscreen - Flare Flow Data (P	ress Back 2x, Flare Flow Do	oto)			
*Flow Rate (SCFM)				r st	561
*Total Flow (MMSCF)					16:5.44
*Flow Pressure (Inwc)			-		G3
*Flow Temperature (r)					79
Control Panel - Touchscreen (Press Resettable Flow Hist	ory, Analog Data Menu, B	lawer Data)			
*Resettable Total Flow (MMSCF)					724.77
*Reset Date/Time (mm/dd/yy hh.mm:ss)					-
Control Panel - Tauchscreen - Blower Data (Press	Mainj				
*Blower 301 Runtime (Hours)					37881
*Blower 301 Vibration (In/Sec)					O.cc
*Blower 301 Speed (XMax)					77
*Blower 301 Inlet Bearing Temp (F)					36-
*Blower 301 Outlet Bearing Temp (r)			· · · · · · · · · · · · · · · · · · ·		62-
Control Panel - Blower Keypad					- Q
*Blower 301 Current (Amps)	[Į.		}	1172
Gas Handling Skid		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			1.010
*Demister Inlet Pressure (mwc)					-27/
*Demister Outlet Pressure (Inwc)					-319
*Demister DP (tnwc)		1		· · · · · · · · · · · · · · · · · · ·	44.3
*Flame Arrester Inlet Pressure (Inwc)			1		+1,0
*Flame Arrester Outlet Pressure (hwc)			1		+42
*Flame Arrester DP (Inwc)		to the days of the days		1	174
Figre	<u> </u>	1	*	A read to according to the contract of the con	
*Visible Emissions (Yes/No, II yes explain)					11/1
*Spiralator Position (Nopen)	1		<u> </u>	*	75
*Manual Louver 1 Position (xopen)			1		27
*Manual Louver 2 Position (xopen)		1		1	20
Other				1	50
Heat Trace OK (Check for Yes)					17
*Propane Tank Level OK (T1 12 (Check for Yes))					The Contract of the Contract o
110hane 1907 read Or (11 [15 [crest lot Jet]]	Eleve 3	- Monitoring		i Li LL	
Time (hh:mm)	Flore 3	- wontering			11.07
Technician (tokists)		al astro	a-ster		100
Control Panel	1	.1	1	-	02
*Indicator Lights OK (Check for Yes)		T		1 1-1	
*Heating/Cooling OK (check for Yes)	Ш.			L L.	
Control Panel - Digital Recorder *Remote Recorder On (Check for Yes)					

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Menu	Process Overview				II Policy and a second second
Gas Handling Skid Inlet Vacuum (Inwc)					371
*Gas Handling Skid Inlet Temperature (F)					-84
Panel Temperature (r)					マク
Recirculation Valve Position (xclosed)					95
*Flare Flame Temperature (F)		** ***			1770
Flame Arrestor Temperature (r)					15-6-1
Control Panel - Touchscreen - Blower Data (Press Bo	ck, Blower Meny, Select Cur	rent Bloweri			45
Blower Runtime (Slower Runtime (Hours))					200 016
*Blower Speed (Blower Speed (%Max))	i			4- W-10-1-	362 998
*Blower Vibration (Blower Vibration (In/Sec))					30
Blower Current (Slower Current (Amps))					60
Control Panel - Touchscreen - Flare Flow Data (Pre	to Book V2 Class Class Constitution				74.3
*Flow Rate (SCFM)	11 DOCT WE' LINE LINE DOLD!				
Total Flow (MMSCF)				1000000000	45-9
Flow Pressure (Inwe)					451,45
Flow Temperature (F)					12
Flow DP (Inwc)					Lili
					1.15
Control Panel - Touchscreen (Press Resettable)		711			
Resettable Total Flow (MMSCF)					451.05
Reset Date/Time (mm/dd/yy hh:mm:13)					المدائمة المدائمة المدائمة
Control Panel - Touchscreen - Alarm History (Press	Main)				
'Alarm History (Check box If no aterm)					U
Sas Hondling Skid			1		- Land
Demister Inlet Pressure (Inwc)					-111-7
Demister Outlet Pressure (Inwc)	***				1-111
Demister DP (InWc)					7/1
Flame Arrester Inlet Pressure (Inwc)				and the same of th	170,4
Flame Arrester Outlet Pressure (Inwc)					16.8
Flame Arrester DP (InWC)					17/5
Fail-Close Valve Air Pressure (psi)		9.4			+0,2
Flore	dy-mility-polyment do 1	The state of the s			105
Visible Emissions (Yes/No, If yes explain)			-		a Ar.
Spiralator Position (xopen)				nt stightsteamen.	W
Manual Louver 1 Position (Kopen)					150
Manual Louver 2 Position (Kopen)	-				50
Other		Address of the Party of the Par			50
	-				
Heat Trace OK (Check for Yes)					i
Propane Tank Level OK (72 72 (Check for Yes))					UU
	Engine Plant .	l - Monitoring		The second second	
IME (hh mm)					1/218
echnician (Initials)					65
ngine Control Panel					
Power Setpoint (LWh) (Engine #4 #3)			1		1.92 1.00
Power Setpoint (LWh) (Engine #2 #1)					647 100
ontrol Room - Loptop			7		011008
Flow Total (MSCF)		-		-	- 7-311-
Flow Rate (scrm)					3115402
Discharge Gas Temperature (F)					11625
ingine Bay/Control Room Window			1,		41.0
		-	1		
Inlet Gas Pressure never					-40.1
The state of the s			·		# t A
Other					1)//
Ither Visible Emissions (Yes/No, If yes explain)					
Ither Visible Emissions (Yes/No, If yes explain)					100
Ither Visible Emissions (Yes/No, If yes explain)	Ren	ıarks			
Pther Visible Emissions (Yes/No, If yes explain)	Ren	ıarks			
Inlet Gas Pressure (Inwc) Other Visible Emissions (Yes/No, If yes explain) late * Collect during device operation only	Ren	narks			
Other Visible Emissions (Yes/No, If yes explain)	Ren	narks			
Other Visible Emissions (Yes/No, If yes explain)	Ren	narks			
Ither Visible Emissions (Yes/No, If yes explain)	Ren	narks			
Ither Visible Emissions (Yes/No, If yes explain)	Ren	narks			

Day of Week Date (mm/dd/yy)	Monday	Tuesday	Wednesday	Thursday	Friday
Per per Printity more \$31	I numer blan	der - Monitoring			(11/24/22
Time (bh mm)	Lowly ned	der - Wonitaring			1210
Technician (Inkluts)					1354
Control Panel - Digital Recorder		-		-	
Flow Rate (scrm)	-	, .			-17-7
Gas Temperature (F)					er:
gas remperatore (F)					478.
	Flare 2	- Manitoring			
Time (hh:mm)					1869
Technician (Initials)		ļ <u> </u>	=		12-
Control Panel	To the same of the	Salara Salar			
*Indicator Lights OK (Check for Yes)					
Heating/Cooling OK (Check for Yes)					4
Control Panel - Digital Recorder					1000
Local Recorder On (Check for Yes)					
Control Panel - Touchscreen - Process Overview					
*Gas Handling Skid Inlet Pressure (Inwc)					1 42.5
*Flare DP (Inwc)					R.35
*Flare Flame Temperature (r)		1	1		il at
Control Panel - Touchscreen (Press Next)		er strenge of the servings of		-1 life to the second process of an age	
Panel Temperature (F)			347		1.7
• Gas Handling Skid Inlet Temperature (r)					46
*Recirculation Valve Position (xclosed)	i				5/7
Control Panel - Touchscreen - Flare Flow Data (Press Back 2v Slave Slow D	etel			10
*Flow Rate (scrm)					- Marie
*Total Flow (MMSCF)					1022-26
*Flow Pressure (Inwc)					10/257
*Flow Temperature (r)			w		61.5
		1			10
Control Panel - Touchscreen (Press Resettable Flow His	tary, Analog Data Menu, E	lawer Data)			and a-
*Resettable Total Flow (MMSCF)			·		169.15
*Reset Date/Time (mm/dd/yy hh.mm.11)					-
Control Panel - Touchscreen - Blower Data (Press	Main)				1
*Blower 301 Runtime (Hours)					40040
*Blower 301 Vibration (In/Sec)					0.27
*Blower 301 Speed (MMax)	1				87
*Blower 301 Inlet Bearing Temp (r)	1				31
*Blower 301 Outlet Bearing Temp (r)	M 25 255	1			52
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)					133
Gas Handling Skid	d to the state of				
*Demister Inlet Pressure (nwc)					-42.7
*Demister Outlet Pressure (Inwc)			THE RESERVE AND ADDRESS OF THE PARTY OF		-45,1
*Demister DP (Inwc)		***		A com	T24
*Flame Arrester Inlet Pressure (Inwc)	the large of the same of the designation				1-50
*Flame Arrester Outlet Pressure (INVC)					Till
*Flame Arrester DP (Inwc)		-			777
Flare		1			T-C-5
Visible Emissions (Yes/No, II yes explain)			reference of the state of the s		110
*Spiralator Position (Nopen)					NU
					50
*Manual Louver 1 Position (Kopen)					Xi-
*Manual Louver 2 Position (Nopen)					5
Other					
Heat Trace OK (Check for Yes)					
Propane Tank Level OK (T1 12 (Check for Yes))	1 4 1 4 -				
There is 44.5	Flare	3 - Monitoring			1 100 100
Time (hh.mm)	-	No de mile repr	* ***	9	1555
Technician (minats)					C2
Control Panel	7 (44)	7	Frence		
Stadleston Helde OV and the con-		1		0)1	
*Indicator Lights OK (Check for Yes)		- 100	Paris		
*Heating/Cooling OK (Check for Yes) *Heating/Cooling OK (Check for Yes) Control Panel - Digital Recorder					

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Men	u - Process Overviev	V			
Gas Handling Skid Inlet Vacuum (Inwc)		1			404
*Gas Handling Skid Inlet Temperature (F)					54
Panel Temperature (F)					
*Recirculation Valve Position (sclosed)					100
Flare Flame Temperature (r)	Pillat de apparent				1249
Flame Arrestor Temperature (F)				-	11/1
Control Panel - Touchscreen - Blower Data (Press	Back, Blower Menu, Select	Current Blower)		-	614
Blower Runtime (Blower Runtime (Hours))			<u> </u>		302 3588
Blower Speed (Blower Speed (KMax))					1 60
Blower Vibration (Blower Vibration (In/Sec))					1 27
Blower Current (Blower Current (Amps))	1				1 2110
Control Panel - Touchscreen - Flare Flow Data (#	ress Back X2, Flore Flow Do	ta)			- 24.8
Flow Rate (scrm)					747
Total Flow (MMSCF)					115721
Flow Pressure (Inwc)					401.0
'Flow Temperature (F)			-		1.4
Flow DP (InWc)	1) ************************************				130
Control Panel - Touchscreen (Press Resettoble)	-	1		1	1.62
Resettable Total Flow (MMSCF)			-		110000
Reset Date/Time (mm/dd/yy hh mm sz)			-		21.21
Control Panel - Touchscreen - Alarm History (Pres	t Mole!		000		
'Alarm History (Check box if no alarm)	is waiti)		-		
Gas Handling Skid	1 11				
Demister Inlet Pressure (Inwc)					
Demister Outlet Pressure (Inwe)					-404
Demister DP (Inwo)		*****			-41.5
Flame Arrester Inlet Pressure (mwc)					-t 1.
Flame Arrester Outlet Pressure (inwc)					T2.4
Flame Arrester DP (Inwc)					+2.0
Fail-Close Valve Air Pressure (psl)					+0.4
Flore				hater-browner than a special pro-	105
Visible Emissions (Yes/No, If yes explain)		***************************************			
Spiralator Position (xopen)	-		1.00		10
					0
Manual Louver 1 Position (Kopen)					10
Manual Louver 2 Position (Nopen)		F-5 F			30
Other	4				
Heat Trace OK (Check for Yes)					
Propane Tank Level OK (71 T2 (Check for Yes))					2
	Engine Plat	t 1 - Monitoring			_
Time (M mm)				-	1348
fechnician (Initials)			Alder de ge distinsted		M
Engine Control Panel					
Power Setpoint (kWh) (Engine #4 #3)	l l	1			195198
Power Setpoint (kWh) (Engine #2 #1)					103 1.80
Control Room - Laptop					(=)
*Flow Total (MSCF)			-2		5778116
Flow Rate (scrm)					T084.7
Discharge Gas Temperature (r)		t			450
Engine Bay/Control Room Window		4			
'Inlet Gas Pressure (Inwc)		i .	Ti	*	42+
Other					المال المالي المالي
Visible Emissions (Yes/No, If yes explain)					111
Note * Collect during device operation only					No
600 maniferative dipplementally. And the maniferative requirement of the later dependence of the later	R	emarks			
and the second s					
to the state of th	-			* *************************************	
				The Angular Street Street Street Street	

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)				1/27/22	
Chirties reproductive control of the	Lowry Head	der - Monitoring			
Time (hh mm)				1440	
echnician (minis)				DB	
Control Panel - Digital Recorder					
Flow Rate (scrm)		***	-	218	
Gas Temperature (F)				47.2	
	Flore 2	- Manitoring		-1-1-0	
Time (bh:mm)	THEE	momtoring		1445	
Technician (Inthisis)				DR	
Control Panel				D 2	
	-				
*Indicator Ughts OK (check for Yes)					
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)				N N	
Control Panel - Touchscreen - Process Overview					
Gas Handling Skid Inlet Pressure (Inwc)			•	39,6	
*Flare DP (Inwc)				5,19	
*Flare Flame Temperature (F)			*	1160	41111
Control Panel - Touchscreen (Press Next)	high as		na managan managan		
Panel Temperature (r)			TER.	64	
*Gas Handling Skid Inlet Temperature (F)			*	38	
*Recirculation Valve Position (xclosed)				70	
Control Panel - Touchscreen - Flare Flow Data (Pre	ss Bock 2x. Flore Flow Co	ital			
*Flow Rate (scrin)			4	503	
*Total Flow (MMSCF)		-	*		
*Flow Pressure (Inwc)				1077,76	
*Flow Temperature (r)			7	6.2	
		1	#	91	
Control Panel - Touchscreen (Press Resettable Flow Histor	ry, Analog Data Menu, B	lower Dato)			
*Resettable Total Flow (MMSCF)				734.0937	
*Reset Date/Tirrie (mm/dd/yy hh.mm:ss)			1		
Control Panel - Touchscreen - Blower Data (Press M	lain)				
*Blower 301 Runtime (Hours)	Antonio e labello de la labell			40191	
*Blower 301 Vibration (In/Sec)				0.21	
*Blower 301 Speed (XMAII)				84	
*Blower 301 Inlet Bearing Temp (F)				31	
*Blower 301 Outlet Bearing Temp (n)		}		86	
Control Panel - Blower Keypad		****	·	· · · · · · · · · · · · · · · · · · ·	
*Blower 301 Current (Amps)			(13.2	
Gas Handling Skid		The strategic transfer and the strategic transfe			
*Demister Inlet Pressure (inwc)				-39,95	
*Demister Outlet Pressure (Inwc)	*****			-42.55	
*Demister DP (inwc)			7	Contraction (Contraction)	
*Flame Arrester Inlet Pressure (Inwc)			·	+ 7.6	
*Flame Arrester Outlet Pressure (Inwc)		-	1	7.39	
The state of the s		-		+4.60	
*Flame Arrester DP (Inwc)			>	+2,79	
Flare					
*Visible Emissions (Yes/No, If yes explain)				10	-
*Spiralator Position (XOpen)				50	
*Manual Louver 1 Position (Kopen)				50	
*Manual Louver 2 Position (xopen)	0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 -			56	
Other				increased of continue	
Heat Trace OK (Check for Yes)		ALCOHOL L		×	
*Propane Tank Level OK (11 12 (Check for Yes))				XX	1 =
1	Flare 3	- Monitoring			
Time (hh.mm)				1500	
Technician (Inklats)		-		DB.	
Control Panel				p 70	
*Indicator Lights OK (Check for Yes)		TET	1 [77]	i ki	
moreorou nights ov (ruser ib) jet)	L.,		<u> </u>	K	
*Heating/Cooling CV in the in the					
*Heating/Cooling OK (check for Yes) Control Panel - Digital Recorder			ليا	251	1

	-
4	92
S.	- 1
4	02
	150

Blower Menu, Select	Current Blower)	Wednesday	Thursday 38.4 555 51 100 1169 88 3734 83 0.03 5617 1862 468.16 13.0	Friday
ack XZ, Flare Flow Da			55 51 100 1169 88 3734 83 0.03 567 1862 468.16 13.0	
ack XZ, Flare Flow Da			55 51 100 1169 88 3734 83 0.03 567 1862 468.16 13.0	
ack XZ, Flare Flow Da			100 1169 88 3734 83 0.03 567 1862 46816 13.0	
ack XZ, Flare Flow Da			100 1169 88 3734 83 0.03 567 1862 46816 13.0	
ack XZ, Flare Flow Da			1169 88 3734 83 0.03 567 1862 468.16 13.0	
ack XZ, Flare Flow Da			88 3734 83 0.03 567 1862 46816 13.0	
ack XZ, Flare Flow Da			3734 83 0.03 587 1862 46816 13.0	1
ack XZ, Flare Flow Da			83 0.03 58:7 1862 468:16 13.0	1 1 1
	ta)		83 0.03 58:7 1862 468:16 13.0	1
	ta)	/	0.03 58.7 1862 468.16 13.0	
	sta)	/	7817 1862 46816 13.0	1
	ota)	/	1862 46816 13.0	
		/	13.0 92	
at at		/	13.0 92	
at at		/	13.0 92	
nt o		i.	92	
		See the second s		
1				
71			8,21	-
n!			TIES INC	
al			4681587	
n1				
A.	The second second			
			8	
mana-y- by		100	-39.27	
			-42.05	
		-	+ 2.2	
		(2000)	+14.41	
			+13.18	
		/		3.70
		-		
The Control Springers and Control		44		
		-	NU	
			50	
to the state of th	-			1-1-1
refre drawns				
		-by-ed		
			12	
			X	
Ennine Dia	at 1 - Monitorine			
engine riui	i. 2 - Monitoring			
			\	
4				a Herman
	1			
	ted Minutility at the party through the			

		errore en en electron de taller trabassimole mais	SD FUR MAINT	<u>, , , , , , , , , , , , , , , , , , , </u>
R	emarks	ter som motorestationalisment come come ages		
				-
		S-10-Maliabada may		
	the first control of the state			
	and the state of t			
4 884	TOOLS for shortest distributation seems apaging			The streeting appropriate
		Engine Plant 1 - Monitoring Remarks	Engine Plant 1 - Monitaring	-34.27 -42.05 + 2.8 -14.41 +13.18 / +1.23 105 NU 50 50 50 50 50 50 50 50 50 50 50 50 50

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	1/31/22				
		er - Monitorin	7		
Time (hh mm)	14:00				
Fechnician (Inklais)	DR				
Control Panel - Digital Recorder					
Flow Rate (scrm)	219				
Sas Temperature (F)	46.6				
	Flare 2 -	Monitoring			
fime (hh:mm)	14:05				
Technician (Initials)	178				
Control Panel					
Indicator Lights OK (Check for Yes)	Z				
Heating/Cooling OK (Chick for Yes)	i S				100
Control Panel - Digital Recorder				<u> </u>	
Local Recorder On (Check for Yes)	T X T				
Control Panel - Touchscreen - Process Overview					
Gas Handling Skid Inlet Pressure (Inwc)	419				
*Flare DP (Inwc)	5.10	hazari dali middali middali dhazararid			
*Flare Flame Temperature (F)					
Control Panel - Touchscreen (Press Next)	1270				L
	89				
Panel Temperature (r)	me ju				
*Gas Handling Skid Inlet Temperature (F)	20		1		
*Recirculation Valve Position (xclosed)	70				
Control Panel - Touchscreen - Flare Flow Data		o)			
*Flow Rate (scrm)	493		Today (replication for the control of the control o	i I	
*Total Flow (MMSCF)	1080.62				
*Flow Pressure (Inwc)	6.7				
*Flow Temperature (r)	102				
Control Panel - Touchscreen (Press Resentable Flow H	istory, Analog Data Menu, Bio	wer Data)		12 2 7 Mas. 1	
*Resettable Total Flow (MMSCF)	736.9570				
*Reset Date/Time (mm/dd/yy hh.mm:ss)					
Control Panel - Touchscreen - Blower Data (Pres	z Main)				
*Blower 301 Runtime (Hours)	40286				
*Blower 301 Vibration (In/Sec)	0.24			1	
*Blower 301 Speed (XMax)	90				
*Blower 301 Inlet Bearing Temp (r)	54				1
*Blower 301 Outlet Bearing Temp (r)	112				
Control Panel - Blower Keypad				1	
*Blower 301 Current (Amps)	13.4			-	}
Gas Handling Skid	(3,-1	here taskatarih-dadadaderi sandras-dikar-asarasihrisara sp se		1	
*Demister Inlet Pressure (Inwc)	-42.3			1	
*Demister United Pressure (Inwc)					1
	-45.1 + Z.8			The same allowered to	
*Demister DP (mwc)	The state of the s			Į.	
*Flame Arrester Inlet Pressure (inwc)	+7.40				
*Flame Arrester Outlet Pressure (Inwc)	14.65			4	
*Flame Arrester DP (Inwc)	+2.75		1		
Flare		philosophysia on should be a property of the state of the	7-		
*Visible Emissions (Yes/No, II yes explain)	NO				
*Spiralator Position (xopen)	50	21-21-2 A 21-24-1-2		4	
*Manual Louver 1 Position (Xopen)	50			<u> </u>	
*Manual Louver 2 Position (xopen)	50			1	
Other					
Heat Trace OK (Check for Yes)	X				
*Propane Tank Level OK (T1 T2 (Check for Yes))	XIX				1
	Flare 3	- Monitoring			
Time (hh.mm)	14:20				
Technician (tokials)	26	-			+
Control Panel	1 20		1	1-0-0-00	-
*Indicator Lights OK (Check for Yes)	T K	[[]		1 [1	
*Heating/Cooling OK (Check for Yes)	<u> </u>				
A A TOTAL CONTRACT A STREET OF THE PARTY OF THE TARREST CONTRACT OF THE TARRES	1794				1
Control Panel - Digital Recorder			-4		*

Control Panel - Touchscreen - Analog Data M	Monday	Tuesday	Wednesday	Thursday	Friday
Gas Handling Skid talas Maarris	enu - Process Overview				
Gas Handling Skid Inlet Vacuum (inwc)			1		
Gas Handling Skid Inlet Temperature (F) Panel Temperature (F)	58		_		
	79				
Recirculation Valve Position (xGosed)	100	7 - 44			
Flare Flame Temperature (F)	1313				
Flame Arrestor Temperature (F)	89				
Control Panel - Touchscreen - Blower Data (Pi		arrent Blower)			
Blower Runtime (Blower (Runtime (Hours))	302 13829		1		1
'Blower Speed (Blower Speed (%Max))	1 66	1	!		1
Blower Vibration (Blower Vibration (In/Sec))	0,01				
Blower Current (Blower Current (Amps))	131.0	1		1	
Control Panel - Touchscreen - Flare Flow Date	(Press Back X2, Flare Flow Date	:)			
Flow Rate (scrm)	1076	- in-terms to aphylogy			
Total Flow (MMscr)	475.59				
Flow Pressure (Inwc)	4.3				
Flow Temperature (F)	9,				
Flow DP (inwc)	2,96	170			
Control Panel - Touchscreen (Press Resettable)	-1.6		Annual property of the second		
Resettable Total Flow (MMSCF)	475.5925	The state of the s			
Reset Date/Time (mm/dd/yy hh:mm sz)	77.7/65	-			
Control Panel - Touchscreen - Alarm History					
Alarm History (Check box If no alarm)					
Alarm History (Check box if no alarm) Sas Hondling Skid	× .				
Demister Inlet Pressure (Inwc)	-40.60				
Demister Outlet Pressure (Inwc)	-41,60				
Demister DP (InWc)	41.0				
Flame Arrester Inlet Pressure (Inwc)	+5,60				
Flame Arrester Outlet Pressure (Inwc)	+5.13				
Flame Arrester DP (Inwc)	+0.47				
Fail-Close Valve Air Pressure (psi)	107		Special Specia		
iore			-		
Visible Emissions (Yes/No, If yes explain)	NU	1771			
Spiralator Position (xopen)	50				
Manual Louver 1 Position (Kopen)	50	-			
Manual Louver 2 Position (Kopen)	50			-	
Other	50			(44-	
Heat Trace OK (Check for Yes)	X				
Propane Tank Level OK (T2 T2 (Check for Yes))					
1 to harte aguy react ou (11 13 (cuscs tot Asti))	the same that th				
		1 - Monitoring			
ime (ht mm) echnician (Intials)	14:30				
econocian dattata	DB				17/
The state of the s					
ngine Control Panel			l.		1
ngine Control Panel Power Setpoint (twh) (Engine #4 #3)	668 698				
ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1)	668 688	1			1
ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Control Room - Laptop	693 688				
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF)	693 688				
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Fontrol Room - Loptop Flow Total (MSCF) Flow Rate (SCFM)	693 688				
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF)	693 688				The state of the s
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Fontrol Room - Loptop Flow Total (MSCF) Flow Rate (SCFM)	693 688 537015.8 966.3 69.1				
Ingine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Loptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F)	693 688 537015.8 966.3 69.1				
Ingine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Loptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Ingine Bay/Control Room Window	693 688				
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Pontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Ingine Bay/Control Room Window Inlet Gas Pressure (Inwc)	693 688 537015.8 966.3 69.1				
Ingine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Pontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Ingine Bay/Control Room Window Inlet Gas Pressure (Inwc)	693 688 537015.8 966.3 69.1				

lay of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Tate (mm/dd/yy)					2/4/22
	Lowry Hea	nder - Monitoring	7	Barried -	
Time (bh mm)					1+30
(echnician (mitiala)					DB
Control Panel - Digital Recorder		7			7.44
low Rate (scrm)			<u></u>		218
Sas Temperature (F)	****				46.4
	Flare 2	- Monitoring			
lime (hh:mm)					छिन्छ । ४३
Technician (Interis)					DE
Control Panel					
Indicator Lights OK (Check for Yes)					X
Heating/Cooling OK (Check for Yes)	لبيا		-1		
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)		li	1		1
Control Panel - Touchscreen - Process Overview		i		1	41,1
*Gas Handling Skid Inlet Pressure (Inwc) *Flare DP (Inwc)					5.20
*Flare Flame Temperature (r)				1	
Control Panel - Touchscreen (Press Nest)		4 441	.1		1190
Panel Temperature (f)				<u> </u>	69
*Gas Handling Skid Inlet Temperature (r)					34
*Recirculation Valve Position (xdased)					70%
Control Panel - Touchscreen - Flare Flow Data (Pr	ere Book 3u. Elean Eleve f	Total	4		702
*Flow Rate (scrm)	ESS BUCK 43, FROM FROM (Julay			513
*Total Flow (MMSCF)		+	1		1083,52
*Flow Pressure (Inwc)		1			6.4
*Flow Temperature (F)		<u>:</u>			96
Control Panel - Touchscreen (Press Resettable Flow Histo	uru Analaa Data Menu	Blower Catal			
*Resettable Total Flow (MMscF)	The second section in the second	- Charles Committee of the control o		}	739.8548
*Reset Date/Time (mm/dd/yy hh.mm.ss)					
Control Panel - Touchscreen - Blower Data (Press)	l	mela napang gang sapang na na san	and the second s	1	
*Blower 301 Runtime (Hours)					40383
*Blower 301 Vibration (In/Sec)					0.24
*Blower 301 Speed (MMax)	1			1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	852
*Blower 301 Inlet Bearing Temp (F)					40
*Blower 301 Outlet Bearing Temp (r)			**************************************		76
Control Panel - Blower Keypad		9.46 90 0000000			4
*Blower 301 Current (Amps)					13.2
Gas Handling Skid		y a column dy modulum of t	Andrea and an ang	,	
*Demister Inlet Pressure (Inwc)					-40.5
*Demister Outlet Pressure (InWC)		1	***************************************		-42.5
*Demister DP (tnWc)					+2.0
*Flame Arrester Inlet Pressure (Inwc)				rigi (des visitadi -u d-un-rismatali)	+ 7.6
*Flame Arrester Outlet Pressure (Inwc)					14.7
*Flame Arrester DP (tnwc)					+ 2.9
Flore		-			
"Visible Emissions (Yes/No, If Yes explain)					שע
*Spiralator Position (xopen)					50 .
*Manual Louver 1 Position (Kopen)					50
*Manual Louver 2 Position (xopen)					70
Other					
Heat Trace OK (Check for Yes)					25
*Propane Tank Level OK (T1 T2 (Check for Yes))					XX
processing companying designs according to the same forms and the same shapes.	Flare	3 - Monitoring			
Time (hh.mm)		4.			1450
Technician (musis)	4			- Martin Control - Andrews	DB
Control Panel	-		parties.	1 amore	
*Indicator Lights OK (Check for Yes)					K
	7,000				
*Heating/Cooling OK (Check for Yes) Control Panel - Digital Recorder					×

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Menu	- Process Overview				
Gas Handling Skid Inlet Vacuum (Inwc)					41.2
Gas Handling Skid Inlet Temperature (F)					53
Panel Temperature (F)		The state of the s			63
Recirculation Valve Position (school)					100.6
*Flare Flame Temperature (F)			-		1153
Flame Arrestor Temperature (r)			Webselle Sellin and a		73
Control Panel - Touchscreen - Blower Data (Press t	lack, Blower Menu, Select Cu	errent Blower)	The state of the state of	7	
Blower Runtime (Blower Runtime (Hours))		1	1		302 3926
Blower Speed (Blower Speed (MMax))		the store store of the store of		Bridge of the State of the Stat	1616
Blower Vibration (Blower Vibration (In/Sec))					10,01
Blower Current (Blower Current (Amps))		1		70	The state of the s
Control Panel - Touchscreen - Flare Flow Data (Pi	ess Back X2. Flare Flow Data	J			26.7
*Flow Rate (scrm)		-			932
*Total Flow (MMscn					
*Flow Pressure (Inwc)				+	480.78
*Flow Temperature (F)			-		2.0
Flow DP (Inwe)	* * *				76
Control Panel - Touchscreen (Press Resettable)				-	202
*Resettable Total flow (MMSCF)	-				
					480,7836
Reset Date/Time (mm/dd/yy hh mm 13)					
Control Panel - Touchscreen - Alarm History (Pres	(Main)	- was highly an analysis and a			
*Alarm History (Check box If no starm)					×
Gas Handling Skid					
*Demister Inlet Pressure (Inwc)					-39.90
*Demister Outlet Pressure (mwc)				_	-40.70
*Demister DP (InWc)				and the second	+0.80
*Flame Arrester Inlet Pressure (Inwc)					14.05
*Flame Arrester Outlet Pressure (Inwc)		1 4			+2.80
Flame Arrester DP (inwc)				-brownia -bryon	+1.25
Fail-Close Valve Air Pressure (psl)					116
Flare					110
Visible Emissions (Yes/No, If yes explain)	1		and the same of		A Lei
Spiralator Position (Nopen)	-				NJ
Manual Louver 1 Position (Kopen)		***************************************			52
Manual Louver 2 Position (Kopen)					50
Other	1-10-10-10-10-10-10-10-10-10-10-10-10-10	* ******	transmission of a	2 200 Consumer	50
Heat Trace OK (Check for Yes)					
The second secon					Y
Propane Tank Level OK (T1 T2 (Check for Yes))					X
And a second of the second of	Engine Plant	1 - Monitoring			
Time (Nh mm)					1500
Fechnician (Initials)					DB
Engine Control Panel			111		
Power Setpoint (LWh) (Engine #4 #1)	1		1		679 697
Power Setpoint (kWh) (Engine #2 [#1)		2 agrangement	1		692 683
Control Room - Laptop	from attention or recommended and				0 - 003
Flow Total (MSCF)					1611.5 945.
Flow Rate (SCFM)		1 d			1010,4
Discharge Gas Temperature (F)					91.9
Engine Bay/Control Room Window			-		11.7
Inlet Gas Pressure (Inwc)		-		7 h	//3-7
Other					-43.7
DAFFE					
Visible Emissions was the W			PRESENT AND ADDRESS OF THE ADDRESS O		1
					Held - West-retrained amount amounting
	Rei	marks			
	Rei	marks	Annual of Association and Asso	de Plando, anno, annogo, oponio prosp., no generalis,	V9
*Visible Emissions (Yes/No, If yes explain) Note * Collect during device aperation only	Re	marks		the Publish communication of printing and gravity and	A
	Re	marks		Berleich aus einige gest der sein gestellt geweite geweite der der der der der der der der der de	
	Re	marks			
	Re	marks			

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Tate (mm/dd/yy)		2/8/22			
	Lowry He	ader - Monitoring			
ime (hh mm)		OB			
echnician (Initialis)		1530			
Control Panel - Digital Recorder					
low Rate (SCFM)		216			
Sas Temperature (F)		49.0			
	Flare	2 - Manitoring			
Time (hh:mm)		1535			
Fechnician (Initials)		PB			
Control Panel					
*Indicator Lights OK (Check for Yes)		N N	H		Ц
Heating/Cooling OK (Oteck for Yes)	ь	×	l. l.d.		
Control Panel - Digital Recorder		10			
Local Recorder On (Check for Yes)		1	Ш		
Control Panel - Touchscreen - Process Overview		11.0			
*Gas Handling Skid Inlet Pressure (nwc)		-41.8			
*Flare DP (Inwc)		-41.8 5.15 1256			
*Flare Flame Temperature (F) Control Panel - Touchscreen (Fress Nest)	5 6	1256	L		
The state of the s			1		
Panel Temperature (f) *Gas Handling Skid Inlet Temperature (f)		77			9936
*Recirculation Valve Position (sclosed)		70'6			
- Kecirculation valve Position (Koosed) Control Panel - Touchscreen - Flore Flow Data (P.	ner Back to Place #1		-		
*Flow Rate (scrw)	ress BOCK 22, Flore Flow	513			
*Total Flow (MASCE)		1001.412			
*Flow Pressure (Inwc)		1006.43	1		
*Flow Temperature (r)		96			
Control Ponel - Touchscreen (Press Resettable Flow Hist	man Annine Sure 44				1
*Resettable Total Flow (MMscF)	ork, whose para went	742.7681	7		1
*Reset Date/Time (mm/dd/yy hh:mm:ss)		742,7601			
Control Panel - Tauchscreen - Blower Data (Press	Atolal		-		
*Blower 301 Runtime (Hours)	The state of the s	40480			1
*Blower 301 Vibration (In/Sec)		0.27			
*Blower 301 Speed (XMM)		85%	1		
*Blower 301 Inlet Bearing Temp (r)	-	42			-
*Blower 301 Outlet Bearing Temp (r)		94			ļ
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)		13.3		T	
Gas Handling Skid		ALCOHOL: NAME OF THE OWN			
*Demister Inlet Pressure (nwc)		-40,5			
*Demister Outlet Pressure (hwc)		-42.0			
*Demister DP (tnwc)		+1.5			
*Flame Arrester Inlet Pressure (wwc)		+7.40			F
*Flame Arrester Outlet Pressure pawcy	A	+4.55	Terry Personal		
*Flame Arrester DP (snwc)		12.85			
Flare					
"Visible Emissions (Yes/No, II yes explain)		٥٥			
*Spiralator Position (Nopes)		50	1		
*Manual Louver 1 Position (Kopen)	The same of	50			
*Manual Louver 2 Position (Nopes)		50			
Other					
Heat Trace OK (Check for Yes)		Z			
*Propane Tank Level OK (11 12 (Check for Yes))		12 1			
	Flare	3 - Monitoring		3.978S11(378.2	F3 = -/4 /
Time (hh:mm)		1545			
Technician (toltials)	1,	DB			
Control Panel			2017		Lon Duran
*Indicator Lights OK (Check for Yes)		8			
*Heating/Cooling OK (Check for Yes)		×			

- Process Overvie	-37.5			
	E ()			
	77			
	54 74			
	100%			
	798			
	76			
ock, Elower Menu, Select	Current Blower)	11		
	302 4023			1
	162%			
1				
1	17.65			1
11 Back X2, Flore Flow De	eto)			
	951			
	2,02			
	1185 117.			
	703,8140			
Main)				
	<u> </u>			
	1.54			
	+3,2			
	+2.8			
	+0.4			
	110			
	100	1		
_ 15 17.	50			
	7-			
	X			
Engles Bla				
Engine Plai	nt 1 - Wonntaring			
	73			
1.81	100 100			
<i>⊌€</i>				l l
	696 688			
	716			
	548.787.9			
	1003,801			
	97.1			
	-43.5			
	NO			
D	amarke			
- N	Cittatics			
	Modn) Engine Pla	Deck, Blower Menu, Select Current Blower) 302 4023	302 4023	Call Blower Mena, Select Current Blower) 302 4023

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	2/14/22				2/18/22
	Lowry Heads	r - Monitoring			
Time (bh mm)	14:55				14:25
echnician (initials)	DA				DB
Cantrol Panel - Digital Recorder					
Flow Rate (scrin)	226		1		227
Sas Temperature (r)	45.6				45.6
	Flare 2 - I	Monitoring			
fime (sh:mm)	15:40				14:35
Technician (Initials)	DB				DB
Control Panel	V 13				. 50
Indicator Lights OK (Check for Yes)	×			1	180
Heating/Cooling OK (Check for Yes)					N N
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)	N I				2
					<u>DE</u>
Control Panel - Touchscreen - Process Overview					-42,1
*Gas Handling Skid Inlet Pressure (Inwc)	-42,9				
*Flare DP (inwc)	5, 22				5, (1
*Flare Flame Temperature (r)	1232				1194
Control Panel - Touchscreen (Press Nest)					
Panel Temperature (r)	91				72
*Gas Handling Skid Inlet Temperature (F)	25				3 3
*Recirculation Valve Position (NClosed)	70%				70%
Control Panel - Touchscreen - Flore Flow Data	(Press Back 2x, Flore Flow Date)			
*Flow Rate (scrm)	507				504
*Total Flow (MMSCF)	1090.75				1093.58
*Flow Pressure (Inwc)	6.9				6.5
*Flow Temperature (F)	9.7				12
Control Panel - Touchscreen (Press Resettable Flow H		wee Detrail	1		
*Resettable Total Flow (MMSCF)	747. 0923		1		749.921
*Reset Date/Time (mm/dd/yy hh:mm:ss)	7770.1-3				
Cantrol Panel - Touchscreen - Blower Data (Pre					
*Blower 301 Runtime (Hours)	40624				40718
	0.19				
*Blower 301 Vibration (In/Sec)					0,27
*Blower 301 Speed (xxxxx)	87.6				37.6
*Blower 301 Inlet Bearing Temp (F)	51				16-5-44
*Blower 301 Outlet Bearing Temp (4)	99		1		105
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)	13.1				13.6
Gas Handling Skid					
"Demister Inlet Pressure (Inwc)	-43.3				-41.3
*Demister Outlet Pressure (mwc)	-44.7				-44.0
*Demister DP (Inwc)	+1.4				+2.7
"Flame Arrester Inlet Pressure (Inwc)	+ 7.35			1	+7.70
*Flame Arrester Outlet Pressure (Inwc)	14.50]	+4.50
*Flame Arrester DP (Inwc)	+2.85		1	1	+3.20
Flore	arranda rama arranda arranda esta esta esta esta esta esta esta est				
*Visible Emissions (Yes/No, II yes explain)	٥٥	***************************************			No
*Spiralator Position (Nopen)	G U			İ	56
*Manual Louver 1 Position (Kopen)	50				50
*Manual Louver 2 Position (Novem)	50			1	50
Other				1	
Heat Trace OK (Check for Yes)	86				1 3
*Propage Tank Level OK (T1 T2 (Check for Yes))	X ×				To The
FIGHER LANK LEVEL UK (TI T2 (Check for Yes))		Adamies in			1 1 51 51
		- Monitoring	1		14-45
Time (hh:mm)	15:50			1	1 1
Technician (tokish)	06			1	05
				and the second participants and the second	
Control Panel	The second secon				
*Indicator Lights OK (Check for Yes)	×				2
	X				<u> </u>

	Tuesday	Wednesday	Thursday	Friday
u - Process Overvie	W			
-41.4				-39.6
55		3		52
78				69
		10		100 6
				1275
8.3				76
Back, Blower Menu, Select	Current Blower)			
			1	302 1424
63%		1		61
0.01		4	1	6.61
27.1	1		1	29.
ress Back X2, Flore Flow D	eta)			1 4 11
937	1			1 603
1-2-13-100	संदर्भ २व			
7 2	-17-1, 67			798.61
(24)				78
2 12		-		18
C1.1 &		1		1. 45
494 7847				
177.6708				414.6078
	<u> </u>	<u> </u>		
الدا يا				
. 10:43 FOLC	ED 41 FLOW			
				-40,3
-41.5				-42.8
10,5				+ 2.5
				+2.8
+ 3. z				1 72.65
+0.5				+0.15
115				115
				10
NO				No
< <u>^</u>				
				50
50				
>				50
Da				12.2
N N				M
Z Z				X O
Engine Pla	nt 1 - Monitoring			N O
Engine Pla	nt 1 - Monitoring			t towns
Engine Pla	nt 1 - Monitoring			N O
Engine Pla	nt 1 - Monitoring			14:55 08
Engine Pla 16:05 DB	nt 1 - Monitoring			14:55 08
Engine Pla	nt 1 - Monitoring			14:55 08
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 08
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 08 695 673 687 691
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 DB 695 673 687 671 563 159.1
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 DB 695 673 687 691 563 59.1
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 DB 695 673 687 671 563 159.1
Engine Pla 16:05 0B 694 1676 709 1673	nt 1 - Monitoring			14:55 DB 695 673 687 691 563 59.1 1012.0 109
Engine Pla 16:05 DB 694 16:76 707 16:73	nt 1 - Monitoring			14:55 DB 695 673 687 691 563 59.1
Engine Pla 16:05 0B 694 1676 709 1673	nt 1 - Monitoring			14:55 DB 695 673 68.7 691 563 59.1 1012.0 109
	100 C 1139 83 Back, Blower Menu, Select 301 1467 10.01 127.1 10.01 127.1 10.01 2.7 10.12 10.12 10.12 10.13 10.143 Foke 10.15 10.15 10.5 119	100 / 113 9 83 83 80ck, Blower Menu, Select Current Blower) 301 1467 17 7 163 17 17 17 17 17 17 17 1	139 83 83 83 83 83 83 83	139 83 83 86ct Surrent Blower) 301 165 416 7 1 1 1 1 1 1 1 1 1

Day of Week	Monday	Tuesday	Wednesday	Thursday 2/24/22	Friday
Date (mm/skd/yy)			2/23/22	2/24/22	
ALCOHOL WATER OF THE PARTY OF T	Lowry Hea	der - Monitorin	9		
îme (sh mm)			1500	1500	
echnician (Initials)			00	D6	
Cantrol Panel - Digital Recorder					
low Rate (scrm)			204	224	
Gas Temperature (F)			45.0	44.9	
	Flare 2	- Manitoring			
Time (hh:mm)			1575	1505	
Cechnician (Initials)			DB	DE	
Control Panel		COTAGE.			TINDEN CARS
Indicator Lights OK (Check for Yes)			×	8	
leating/Cooling OK (Check for Yes)			X	N	
Contral Panel - Digital Recorder			N		
ocal Recorder On (check for Yes)				18	
Control Panel - Touchscreen - Process Overview			A		
'Gas Handling Skid Inlet Pressure (nwc)			25,3	42.7	O La Verigina de la Carte
*Flare DP (Inwc)			4.77	5.23	
Flare Flame Temperature (F)			4.77	1260	
Control Panel - Touchscreen (Press Nest)		Water Town			
Panel Temperature (r)			53	67	
*Gas Handling Skid Inlet Temperature (F)	, VE = 1/4-1		41	33	
*Recirculation Valve Position (scheet)			70%	701.	
Control Panel - Touchscreen - Flare Flow Data (Pres	s Back Zz, Flare Flow D	ato)	-		
*Flow Rate (scrm)		_	444	503	
*Total Flow (MMSCF)	2.01		1096.75	1077.46	
*Flow Pressure (Inwe)			1.1	6.5	
*Flow Temperature (r)			76	97	
Control Ponel - Touchscreen (Press Resettable Flow History	. Analog Dota Mesus A	lower Datal		1-7	
*Resettable Total Flow (MMSCF)			753 D917	753. 8021	
*Reset Date/Time (mm/dd/yy hhmm:ss)			72-1-110	. ,	
Control Panel - Touchscreen - Blower Data (Press Mg	sint	-			
*Blower 301 Runtime (Hours)			40824	40847	
*Blower 301 Vibration (In/Sec)			0.17	73.4	
*Blower 301 Speed (NMax)		0	741	e, 50 8,7°4	
*Blower 301 Inlet Bearing Temp (r)			27	70	
*Blower 301 Outlet Bearing Temp (r)			6C	78	
Control Panel - Blower Keypod		-	00		
*Blower 301 Current (Amps)			11.2	13.8	
Gas Handling Skid		1	111	13.0	
*Demister Inlet Pressure (nowc)			-255/	-431	
*Demister Outlet Pressure (Inwc)			-25.56	-45,8	
*Demister DP (nwc)		-	+ 2.64		
*Flame Arrester Inlet Pressure (wwc)		-	+7.11		7 72
*Flame Arrester Outlet Pressure (lawc)	201		+4,31	47.7 44.6	
*Flame Arrester DP (mwc)			+2.8	+3.1	
Flare	-		7 4.7	-3,1	
*Visible Emissions (Yes/No, If yes explain)		_	No	. 913	
*Spiralator Position (Nopen)		+	50	נע	
*Manual Louver 1 Position (Nopen)				50	
*Manual Louver 1 Position (sopen)			50		
Other		-	50	50	
			121	4	1.24
Heat Trace OK (theck for Yes)			<u> </u>	-	· L.
Propane Tank Level OK (11 12 (Check for Yes))	pt	Ada-ta-t	X X	X X	_ _ _ _
The same of the sa	Flare :	3 - Monitoring	1 1536	1510	
Time (hh:mm)		-	1530		
Technician (tokials)			06	D6	
milio Am A			The state of the s	1 50	
Control Panel					
*Indicator Lights OK (Check for Yes)			×	X	
			X X	×	

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Menu	- Pracess Overview				To coldan No. In.
Gas Handling Skid Inlet Vacuum (Inwc)			-21.8	=40,4	
Gas Handling Skid Inlet Temperature (F)			24	51	
Panel Temperature (F)			76	59	
Recirculation Valve Position (xclosed)			65%	100%	
Flare Flame Temperature (r)			121	1172	
Flame Arrestor Temperature (F)			27	2	
Control Panel - Touchscreen - Blower Data (Press Bo	ck, Blower Menu, Select Cu	urrent Blaweri			l
*Blower Runtime (Blower Runtime (Hours))			302 14327	30214327	1
*Blower Speed (Blower Speed (KMex))				175%	
Blower Vibration (Blower Vibration (In/Sec))		1	6	0,01	
Blower Current (Slower Current (Amps))		1	l Or	141.5	
Contral Panel - Touchscreen - Flare Flow Data (Pre	ts Back X2 Flore Flow Date				
Flow Rate (scrm)	nacz w2, 7 laię 2 low Data		-0	1540	
Total Flow (MMscr)			7/2/2/2		
Priow Pressure (Inwc)			26.33 202	26.25266	70278
Flow Temperature (r)			0	6.3	
Flow DP (Inwc)		-	22	9.3 5.7	
The state of the s			0	5.7	
Control Panel - Touchscreen (Press Resettable)					
Resettable Total Flow (MMSCF)			502.5460	502.7828	
Reset Date/Time (mm/dd/yy hh-mm:ss)				- 3	
Control Panel - Touchscreen - Alarm History (Press	Waln)	1,3839	and the second	2013/01/11	
'Alarm History (Check box If no alarm)			×	X	
Sas Handling Skid		10.000			
Demister Inlet Pressure (Inwc)			-23,5	-40.5	
Demister Outlet Pressure (Inwc)	1		-72.9	-43.1	
Demister DP (Inwc)			+0,6	+2.6	
Flame Arrester Inlet Pressure (Inwc)			-0.1	49,7	
Flame Arrester Outlet Pressure (Inwc)			-0.1	19,0	
Flame Arrester DP (lowg)			//	+0.7	
Fail-Close Valve Air Pressure (pu)			110		
Flore			11.0	115	
Visible Emissions (Yas/Na, If yes explain)			נע	-12	
Spiralator Position (Nopen)				70	
Manual Louver 1 Position (Nopes)			50		
Manual Louver 2 Position (Nopen)			50	50	
Other			50	50	
Pheat Trace OK (Check for Yes)			Teat	r Cu	
Propane Tank Level OK (Tz (Tz (Check for Yes))			X		
Proparte Tank Level UK (T2 T2 (Check for Yes))				X	
	Engine Plant	1 - Monitorin	g		
Tirrie (hh mm)			1540	1520	
Fechnician (Initials)			DB	OB	
Engine Control Panel					
Power Setpoint (kWh) (Engine #4 #3)			682 692	6781652	
Power Setpoint (kWh) (Engine #2 #1)			691 1685	695 712	
Control Room - Laptop					
Flow Total (MSCF)			4713	570415.9	571588.
Flow Rate (scrm)		· · · · · · · · · · · · · · · · · · ·	971.5	10605	2
Discharge Gas Temperature (F)			56.6	806	
ingine Bay/Control Room Window				80,0	
Inlet Gas Pressure (Inwc)			-24.5	-39.3	
Other			-01.7	C.1 L.	
Visible Emissions (yes/No, If yes exptain)			20	טע	
iote * Collect during device operation only			1770	7-0	
	n-	marks			
	l l l	Harks			

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	2/28/22	10			
	Lowry Head	er - Monitoring	7		100
lime (hh mm)	1505				
Fechnician (Initials)	D8				
Control Panel - Digital Recorder		W	700		
Flow Rate (SCFM)	714		1		7
Gas Temperature (5)	45.1				-
		Monitoring	-		-
fime (M:mm)	(515	monitoring	100		*
Technician (Inhals)	DB		1		
Control Panel	75				
*Indicator Lights OK (check for Yes)	5		T		
Control Contro	×		H		
Heating/Cooling OK (Check for Yes)					Lud ?
Control Panel - Digital Recorder	1 10				
Local Recorder On (Check for Yes)	1				
Control Panel - Touchscreen - Process Overvie					
*Gas Handling Skid Inlet Pressure (Inwc)	-42.3		5		
*Flare DP (InWC)	5.13				
*Flare Flame Temperature (r)	1236				
Control Panel - Touchscreen (Press Nest)			100	73.00	
Panel Temperature (f)	15				
*Gas Handling Skld Inlet Temperature (F)	21				
*Recirculation Valve Position (sclosed)	70%				
Cantrol Panel - Touchscreen - Flare Flow Data	(Press Back 2x, Flore Flow Date	»)			
*Flow Rate (scrm)	500		1		
*Total Flow (MMSCF)	1100.35		1		
*Flow Pressure (lawc)	6.5				
*Flow Temperature (r)	97				
Control Panel - Touchscreen (Press Resettable Flow)		under Florier I			-
*Resettable Total Flow (MMSCF)	756. 6902	mar breid/	T	1	0.000
*Reset Date/Time (mm/dd/yy hhmm:ss)	7 78. 4 700	_	-		
Control Panel - Touchscreen - Blower Data (Pr					
	40944				
*Blower 301 Runtime (Hours) *Blower 301 Vibration (In/Sec)	40744				-
THE PERSON NAMED IN COLUMN 1	0.23				
*Blower 301 Speed (xmax)					
*Blower 301 Inlet Bearing Temp (F)	56				
*Blower 301 Outlet Bearing Temp (F)	(13				
Control Panel - Blower Keypod					- 79
*Blower 301 Current (Amps)	13.5				
Gas Handling Skid					
*Demister inlet Pressure (mwc)	-42.0				
*Demister Outlet Pressure (Inwc)	-44.5				
*Demister DP (Inwc)	42.5				
*Flame Arrester Inlet Pressure (wwc)	+7.6	12 12 6 6 1			
*Flame Arrester Outlet Pressure (Inwc)	+4.7		Service Section	P. P. P. P. P.	
*Flame Arrester DP (tnwc)	£2.9	-			
Flore					
*Visible Emissions (Yes/No, II yes explain)	ادر				
*Spiralator Position (Nopen)	50			-	-
*Manual Louver 1 Position (Nopen)	50				-
*Manual Louver 2 Position (Kopen)	50				
Other	20				
Heat Trace OK (Check for Yes)	X		7		
	To their				
*Propane Tank Level OK (T1 T2 (Check for Yes))					
		- Manitoring	-		
Time (hh:mm)	1530				
Technician (trittals)	26				
Control Panel			1121 - 000		
*Indicator Lights OK (Check for Yes)	×				
*Heating/Cooling OK (Check for Yes)	8				
Control Panel - Digital Recorder					
*Remote Recorder On (Check for Yes)	X	Print.	proset.	T. Brenn,	

entent Princip Princip Princip	Monday	Tuesday	Wednesday	Thursday	Friday
ontrol Panel - Touchscreen - Analog Data Men					
Sas Handling Skid Inlet Vacuum (Inwc)	- 39.7				
Sas Handling Skid Inlet Temperature (F)	55				
Panel Temperature (r)	8 .				
Recirculation Valve Position (Monted)	100.6	-			
lare Flame Temperature (r)	1260				
lame Arrestor Temperature (f)	91				
ontrol Panel - Touchscreen - Blower Data (Press	Bock, Blower Menu, Select Cu	rrent Blower)			
Blower Runtime (Blower Runtime (Hours))	302 4424		1		
Nower Speed (slower Speed (%Max))	716	1	1		1
Hower Vibration (Blower Vibration (In/Sec))	0,02				
Slower Current (Slower Current (Amps))	136.9	. 1 0			
ontrol Panel - Touchscreen - Flare Flow Data (P	rest Back XI, Flore Flow Date				
low Rate (scrm)	1371				
Total Flow (MMSCF)	510,74				-
low Pressure (Inwc)	7.5				
low Temperature (F)	75				
law DP (Inwc)	4.65				
ontrol Panel - Touchscreen (Press Resettable)	111-7				
Resettable Total Flow (MMSCF)	500. 7395		1		
leset Date/Time (mm/dd/yy hh:mm:sz)	190. +375				
nntrol Panel - Touchscreen - Alarm History (Pres					
introi Paner - rouchscreen - Alarm History (Pres Marm History (Check box II no elerm)	a Main)	[7]			-
Narm History (Check box II no elerm)	X				
	20 -				
Demister Inlet Pressure (Inwc)	-39.7				
Demister Outlet Pressure (newc)	-41.5				
Demister DP (Inwc)	+(. 6				
lame Arrester Inlet Pressure (inwc)	+8.9				
lame Arrester Outlet Pressure (Inwc)	+8.1	LINE TO SERVE			
lame Arrester OP (Inwc)	+0.8			746	Same -
ail-Close Valve Air Pressure (psi)	115				
ore					
/isible Emissions (Yes/No, If yes explain)	טק				
piralator Position (xopen)	50	1 100 60			
Vanual Louver 1 Position (Kopen)	50				The second
Annual Louver 2 Position (Kopen)	50				
ther	-				
leat Trace OK (Check for Yes)	V.				
ropane Tank Level OK (T1 T2 (Check for Yes))	N				
		1 - Monitorino	1		
712 (hh mm)	1540		T I		
chnician (Intileis)	DE			9	
igine Control Panel	7		1		
Power Setpoint (kwh) (Engine #4 #3)	680 682			4	
Power Setpoint (kWh) (Engine #2 #1)	688 693				
ontrol Room - Laptop	619		<u> </u>	1	
low Total (Mscr)	(45 - 5 CA /)				
	577868.6				
low Rate (scrm)	1068, 1		!		
Discharge Gas Temperature (F)	77.6		į į		
igine Bay/Control Room Window	112				
nlet Gas Pressure (Inwo)	-43.8				
	00				
te * Collect during device operation anly					
ther /isible Emissions (ver/No, If yes esplain) ate * Collect during device operation anly	D0	marks			

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	3/7/22			2/10/2	3/1/22
	Lowry Heade	r - Monitoring			
Time (hh mm)	1515			1425	
Technician (Initials)	DS			DB	DB
Control Panel - Digital Recorder				10 10	
Flow Rate (scrm)	215			216	
Gas Temperature (F)	45.1			45.0	
	A company of the comp	Monitoring		73.0	
Time (Mamm)	1520	would be a second		1430	
Technician (totals)	06			DB	
Control Panel	1/10	A.C. Silver	100	US	
*Indicator Lights OK (Check for Yes)	5.7			52	
Heating/Cooling OK (Check for Yes)	X			X	
	×			LX9	
Control Panel - Digital Recorder	7 67 1			Feet .	
Local Recorder On (Check for Yes)	X			×	
Control Panel - Touchscreen - Process Overview					
*Gas Handling 5kid Inlet Pressure (nwc)	~42.3			-38.3	1000
*Flare DP (InWC)	5.21			5.15	- W. Te-m
*Flare Flame Temperature (r)	1224	CI LINE		1121	
Control Panel - Touchscreen (Press Nest)		STATE OF THE PARTY			
Panel Temperature (r)	69			68	
*Gas Handling Skid Inlet Temperature (r)	34			33	- Walletin
*Recirculation Valve Position (xclosed)	706	0.0		701	S. Installed
Control Panel - Touchscreen - Flare Flow Data	Press Back 2x, Flore Flow Data)		1.	
*Flow Rate (scrm)	501		1	500	
*Total Flow (MMSCF)	1105.40			1107.54	-
* Flow Pressure (Inwc)	1105.40			17	
*Flow Temperature (7)	00			6.3	
Control Panel - Touchscreen (Press Resettable Flow Hi	7.0	use Retel		43	
*Resettable Total Flow (MMSCF)	761.7408	wer ward)		763.8779	
*Reset Date/Time (mm/dd/yy hh.mm.ss)	TU1. +40E		-	163, 6747	
Control Panel - Touchscreen - Blower Data (Pres	-				
				1	
*Blower 301 Runtime (Hours)	41112			41183	
*Blower 301 Vibration (In/Sec)	6.27			0.27	
*Blower 301 Speed (MMan)	38.7			871	
*Blower 301 Inlet Bearing Temp (f)	3.3			0.27 87 l 24	
*Blower 301 Outlet Bearing Temp (r)	100			94	
Contral Panel - Blower Keypad					114.3
*Blower 301 Current (Amps)	13.6		Y 1	13.5	6 6
Gas Handling Skid		Same and the			
*Demister inlet Pressure (Inwc)	-42.4			-42.3	
*Demister Outlet Pressure (Inwc)	-45.1			-44.7	
*Demister DP (towc)	+2.7			+2.4	
*Flame Arrester Inlet Pressure (Inwc)	+7.5			+7.4	7-10-
*Flame Arrester Outlet Pressure (wwc)	+4.6			+4.5	
*Flame Arrester DP (lowc)	+2.9			+2.9	
Flare	1 -1 -1			617	
*Visible Emissions (Yan/No, If yes explain)	۵۵			טע	
*Spiralator Position (xopen)	50			The second secon	
*Manual Louver 1 Position (Kopen)				5.0	
*Manual Louver 2 Position (Kopen)	50			50	
Other	50			50	
The state of the s	10				
Heat Trace OK (Check for Yes)	18			×	
*Propane Tank Level OK (f1 12 (Check for Yes))	K K			X X	
		Monitoring		aretha.	
Time (hh:mm)	1530			1440	
Technician (toltials)	DB			DB	
Control Panel					
*Indicator Lights OK (Check for Yes)	X			×	
*Heating/Cooling OK (Check for Yes)	R			×	
Control Panel - Digital Recorder			137		
*Remote Recorder On (Check for Yes)	X	- people	T pros	X	

	Monday	Tuesday	Wednesday	Thursday	Friday
ontrol Panel - Touchscreen - Analog Data Menu -			PP-910-State involvement of		-
Gas Handling Skid Inlet Vacuum (Inwc)	-40.2			-39.9	
Sas Handling Skid Inlet Temperature (F)	5.2			55	
Panel Temperature (F)	62			55	
Recirculation Valve Position (scored)	108 /			100.7	
lare Flame Temperature (f)	1247			1261	- 100
lame Arrestor Temperature (r)	79			75	
ontrol Panel - Touchscreen - Blower Data (Press Boo	A, Blower Menu, Select Cu	rrent Blower)			
Blower Runtime (Blower Runtime (Hours))	102 4592			302 4663	1
Blower Speed (Blower Speed (%Mex))	70%		11 11 11 11 11 11	1 68 %	1
Blower Vibration (Blower Vibration (In/Sec))	601			10,01	1
Blower Current (Blower Current (Amps))	135.5	1		134.4	
ontrai Panel - Touchscreen - Flare Flow Data (Pres	t Back X2, Flare Flow Date,	1			
Flow Rate (scrm)	1322			1276	
Total Flow (MMSCF)	524.68			530,24	
Flow Pressure (Inwc)	6.4			5.6	
Flow Temperature (F)	81			77	
Flow DP (Inwc)	4.2.8		_	3.9	
ontrol Panel - Touchscreen (Press Resettable)		1		2.1	
	524.6897		T	530,2406	
Reset Date/Time (mm/dd/yy hh:mm:ss)	1.00.1			7 30, 6706	
Ontrol Panel - Touchscreen - Alarm History (Press A	tela1				
Alarm History (Check box If no elerm)	(Alan)				
as Handlina Skid	LYF			8	
Demister Inlet Pressure (Inwo)	-40.1			7725	
Demister Outlet Pressure (Inwc)				-40.0	
Demister Obuet Pressure (Inwc)	-41.8			-41.8	
	+1,7			+1. 8	
Flame Arrester Inlet Pressure (Inwc)	77.4			76.6	
lame Arrester Outlet Pressure (Inwc)	46.8			+5.3	
Flame Arrester OP (inwc)	+0.6		N	+1.3	
Fail-Close Valve Air Pressure (psl)	116			110	
are					
Visible Emissions (ves/No, If yes explain)	NO			טא	
Spiralator Position (Nopen)	50			50	
Manual Louver 1 Position (Nopen)	50			50	
Manual Louver 2 Position (Nopen)	50			50	
ther				- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	
Heat Trace OK (Check for Yes)	X			M	
Propane Tank Level OK (11 12 (Check for Yes))	X			X	
	Engine Plant	1 - Monitorin	G.	4 445	
me (hh mm)	1540			1450	
echnician (Initials)	DB			DB	
ngine Control Panel	V 4.3		-	70	
- Andrews - Andr	698 684	1		699 684	
	703 691				
ontrol Room - Laptop	105 091	<u> </u>		693 688	
	KON HOL		1	100 101 E	
Flow Rate (scrin)	587 484 941.9 95.7			592171.5	
THE PROPERTY OF THE PROPERTY O	971.7		_	1017.8	
Mechania Cas Townson	15.7		_1	95.1	
Discharge Gas Temperature (r)					
ngine Bay/Control Room Window	// -			-31.5	
ngine Bay/Control Room Window Inlet Gas Pressure (Inwc)	-41.0				
ngine Bay/Control Room Window Inlet Gas Pressure (IAWC) ther					
ngine Bay/Control Room Window Inlet Gas Pressure (Inwc)	-41.0			NO	
Title	15,7			-31.5	

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/ed/yy)	3/14/22				
	Lowry Head	er - Monitoring			
lime (Nh mm)	1440				
Technician (Inidels)	DB			_	
Control Panel - Digital Recorder					
Flow Rate (scrm)	217		V 1		
Gas Temperature (r)	45.0				
	Flare 2 -	Monitorina	A		
Time (M:mm)	1445				
Fechnician (Intrals)	01				
Control Panel	7.5				
*Indicator Lights OK (Check for Yes)	1 2				
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder			1		
Local Recorder On (check for Yes)					-
				Ш	LJ
Control Panel - Touchscreen - Process Overview					
Gas Handling Skid Inlet Pressure (nwc)	-414				AND SOME THE
*Flare DP (InWC)	5.18				
Flare Flame Temperature (r)	1129				
Control Panel - Touchscreen (Press Next)					
Panel Temperature (F)	73				
*Gas Handling Skid Inlet Temperature (F)	33	and the second			
*Recirculation Valve Position (xclosed)	70%				
Control Panel - Touchscreen - Flare Flow Data (Press Back 2x, Flare Flow Dat	a)			
*Flow Rate (scrm)	500				
*Total Flow (MMSCF)	1110.40		T .		
*Flow Pressure (Inwc)	6.7				
*Flow Temperature (r)	102				
Control Panel - Touchscreen (Press Resettable Flow HI		wer Datel	-		
*Resettable Total Flow (MMSCF)	766.7411	was areas	1		
*Reset Date/Time (mm/dd/yy bh.mm:1)	7.017		-		
Control Panel - Tauchscreen - Blower Data (Pres	Atolol		-		
*Blower 301 Runtime (Hours)	41278	ACC 1987			
*Blower 301 Vibration (in/Sec)					
*Blower 301 Speed (MALL)	85.0				
	87%				
*Blower 301 Inlet Bearing Temp (r)	5/				
*Blower 301 Outlet Bearing Temp (7)	113				
Control Panel - Blawer Keypad					
*Blower 301 Current (Amps)	13.6		200		
Gas Handling Skid					
*Demister inlet Pressure (Inwc)	-41.6				
*Demister Outlet Pressure (Inwc)	-43,9				
*Demister DP (tnwc)	+2.3				
*Flame Arrester Inlet Pressure (lawc)	+7.7	C. S. S.	10-10		
*Flame Arrester Outlet Pressure (Inwc)	+4.9				
*Flame Arrester DP (inwc)	-2.8				
Flare					
*Visible Emissions (Yes/No, If yes explain)	נע				
*Spiralator Position (Novem)	50				
*Manual Louver 1 Position (Kopen)	50	W-1-1-	1		
*Manual Louver 2 Position (Kopen)	50		1		
Other	Ju				
Heat Trace OK (Check for Yes)	No.				
	K				
*Propane Tank Level OK [T1 T2 (Check for Yes))				الله النا	
		- Monitoring			
Time (hh.mm)	1560				
Technician (Initials)	06				
Control Panel				The same of the same of	
*Indicator Lights OK (Check for Yes)	×				
"Heating/Cooling OK (Check for Yes)	×				
Control Panel - Digital Recorder				-	-
	X				

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Dato Me 'Gas Handling Skid Inlet Vacuum (Inwc)					
	-39.9				
Gas Handling Skid Inlet Temperature (F)	55	-			
Panel Temperature (F)	71				
Recirculation Valve Position (scored)	00 6				
Flare Flame Temperature (F)	1780				
Flame Arrestor Temperature (F)	85				
Control Panel - Touchscreen - Blower Data (Pri		rent Blower)			
Blower Runtime (Blower Runtime (Hours))	302 4758		i		-
Blower Speed (Blower Speed (MMax))	1667				and the
Blower Vibration (Blower Vibration [In/Sec]]	0,01				
Blower Current (Blower Current (Amps))	32.1	1			
Control Panel - Touchscreen - Flare Flow Data					
*Flow Rate (scrm)	1187				
Total Flow (MMSCF)	1 537.64	100			1.00
Flow Pressure (Inwc)	5.6				
Flow Temperature (F)	5.6				
Priow DP (Inwc)	3.41			-	
Contral Panel - Touchscreen (Press Resettable)					
Resettable Total Flow (MMSCF)	537.6439				
*Reset Date/Time (mm/dd/yy hh:mm:ss)	1-1.		1		
Control Panel - Touchscreen - Alarm History (bose At-dal				
Alarm History (Check box If no aterm)	ress Main)				parent .
Gas Handling Skid	1 125				
Demister inlet Pressure (INVC)	-70 -				
*Demister (niet Pressure (nwc)	-39.5				
The state of the s	-40.7				
*Demister DP (inwc)	+1.2		2		
Flame Arrester Inlet Pressure (Inwc)	-6.3				Service Tolland
*Flame Arrester Outlet Pressure (Inwc)	45.7			500.)	
*Flame Arrester DP (inwc)	+0.6				
*Fail-Close Valve Air Pressure (psl)	110				
Flare					
*Visible Emissions (Yes/No, II yes explain)	NO				
Spiralator Position (xopen)	50				
*Manual Louver 1 Position (Kopen)	50				
Manual Louver 2 Position (xopm)	50				
Other				4000000	
*Heat Trace OK (Check for Yes)	X				
Propane Tank Level OK (T2 T2 (Check for Yes))	N K	T-T-			
		1 - Monitorin			
Time (h) mm)	1510	2 - Womitalin	-		
Technician (mkulu)	Dis				
	1 15				
Engine Control Panel	/37 ///				
*Power Setpoint (NWh) (Engine #4 #2)	677 664				
*Power Setpoint (LWh) (Engine #2 #1)	680 699			1	14
Control Room - Leptop	- COME 50 -				
*Flow Total (MSCF)	598039.5				
*Flow Rate (scrm)	1059.0				
*Discharge Gas Temperature (r)	93.3				
Engine Bay/Control Room Window					State of the
*Inlet Gas Pressure (InWc)	-43.1				
Other					
*Visible Emissions (Yes/No, if yes explain)	100				
Note * Collect during device operation only				·····	
The latest distribution of the state of the	Rei	marke			
	Rei	marks			
,					
	PPP shift hand flashed with the shift the west among grap should also as so				

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)		3/22/22			3/25/22
	Lowry He	ader - Monitoring			
Time (hh mm)		1605			1215
Technician (Intuiti)		DB			DB
Control Panel - Digital Recorder					
Flow Rate (SCFM)		115			206
Gas Temperature (A)		44.9			45.0
	Flare	2 - Monitoring			
Time (Manus)		1610			1220
Technician (Initials)		DR.			DB
Control Panel		1 -			
*Indicator Lights OK (Check for Yes)					N A
Heating/Cooling OK (Check for Yes)		(8)			Sci
Control Panel - Digital Recorder			hand.		- Court
Local Recorder On (Check for Yes)		X			50
Control Panel - Touchscreen - Process Overview				-	-
Gas Handling Skid Inlet Pressure (Inwc)		-39.8			-39.9
*Flare DP (Inwc)		-39.8 5.06			6.3
*Flare Flame Temperature (r)		1007			1270
Control Panel - Touchscreen (Press Nest)		100/			1070
Panel Temperature (n)		63		7.00	32
*Gas Handling Skid Inlet Temperature (F)		10			73
*Recirculation Valve Position (Noteset)		38			70%
Control Panel - Touchscreen - Flare Flow Data (Pri	an Burth Su. Flora Plans				40 6
*Flow Rate (scrin)	23 BOCK ST, FIGHT FICHS				498
*Total Flow (MMSCF)		1115.52		-	and the same of th
*Flow Pressure (Inwc)		7117.70			1117. 77
*Flow Temperature (F)		6.3			6.4
					201
Control Panel - Touchscreen (Press Resettable Flaw Histo *Resettable Total Flow (MMSCF)	ry, Analog Dota Menu	, Blower Data)	****		14-4-15-15-1
		771,8565			773,9035
*Reset Date/Time (mm/dd/yy hh.mm.si)					
Control Panel - Touchscreen - Blower Data (Press & *Blower 301 Runtime (Hours)	(ale)	177749			
		41449			41517
*Blower 301 Vibration (In/Sec)		85.4			0.29
*Blower 301 Speed (KMsx)		85'4			86 6 54 92
*Blower 301 Inlet Bearing Temp (F)		34			54
*Blower 301 Outlet Bearing Temp (r)		90			92
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)		/3,3			13.3
Gas Handling Skid					
*Demister Inlet Pressure (mwc)		1-40.2			-39.8
*Demister Outlet Pressure (Inwc)		-42,1			-42.3
*Demister DP (triwc)		+0.9		Į .	+2,5
*Flame Arrester Inlet Pressure (inwc)		- 7.3		14	+7.5
*Flame Arrester Outlet Pressure (INWC)		74,4			+4.5
*Flame Arrester DP (InWC)		12.9			+3.0
Flare					
*Visible Emissions (Yes/No, II yes explain)		NO			NO
*Spiralator Position (Nopen)		56			50
*Manual Louver 1 Position (Kopen)		50			50
*Manual Louver 2 Position (xopen)		50		1	56
Other			**************************************		
Heat Trace OK (Check for Yes)		X			25
*Propane Tank Level OK (11) 12 (Check for Yes))					्रा । व
	Flore	3 - Manitoring			
Time (hh:mm)		=1645		1	17.35
Technician (Initials)		NG			1235 DB
Control Panel		3	1		L2
*Indicator Lights OK (Check for Yei)		Z			107
*Heating/Cooling OK (Check for Yes)		8			K.
Cantrol Panel - Digital Recorder	- Lad	DM			1
merchan mergerant such the first					

Monday	Tuesday	Wednesday	Thursday	Friday
- Process Overvie				
	-39,9			-37.9
	54			54
	51			73
	100%			100 4
	1240			1202
	72		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	84
lack, Blower Menu, Selec	f Current Blower)			
	302 4951		- 1	302 5020
	161.6			1662
1				10.01
				31.5
ess Back X2. Flore Flow I	lata)			1 100)
				1152
100000000000000000000000000000000000000				558.06
				4.8
	7.0			85
	300			3.26
	2.60			3.20
	EK3 1113 1			CC6 ALS
-	772.117			558.052
Moinj			-	
	N N			8
				-39.8
	-41.9	-3.5.00		-41.1
	+1.8			~4(,1 ~(,3
	+6.0			+5,4
	+513			+5.0
	+6.7			+0,4
	110		-	110
1	NU	70		NO
			L. Barrier	50
				50
				50
				,,,
	15			V.
				××
Feelen Di				
	1635			1.5 11.00
	returned to the same of the sa			1245
	78			town the
	لبيب مسيسي منادمات		·	76
	(92 1672			680 692
		-		680 692
	692 1672	1		685 696
	609741.5	}		680 692
	609741.5			685 696
	609741.5			680 692
	609741.5			685 696
	609741.5			685 696
	609741.5			685 696
	609741.5			685 1696
	ess Back X2, Flare Flow S	72 Sock, Blower Menu, Select Current Blower) 3	CC 1240 72 Sack, Blower Menu, Select Current Blower 3 c 2 4951 44 (12-40 72 13 24 44 51 14 44 51 14 44 51 14 44 51 15 55 5

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)		T. 44 to 1 (20)			4/29/22
	Lowry Hea	der – Monitoring	9		
Time (sh mm)					1350
Technician (Initials)					DB
Control Panel - Digital Recorder					
Flow Rate (scrm)					183
Gas Temperature (F)					49.4
	Flare 2	- Monitoring			ALCOHOLD IN THE
Time (sh:mm)					355
Technician (Initials)					D5
Control Panel					
*Indicator Lights OK (Check for Yes)					×
Heating/Cooling OK (Check for Yes)					1
Contral Panel - Digital Recorder			Accessors at the		
Local Recorder On (check for Yes)					
Control Panel - Touchscreen - Process Overview					
*Gas Handling Skid Inlet Pressure (inwc)					-36.8
*Flare DP (InWC)					
*Flare Flame Temperature (r)					5.32
Control Panel - Touchscreen (Press Nest)					
Panel Temperature (F)					77 45 70 L
*Gas Handling Skid Inlet Temperature (F)					45
*Recirculation Valve Position (sclosed)					247
Control Panel - Touchscreen - Flare Flow Data (Pro	rsz Bock Zz, Flore Flow De	ata)			700
*Flow Rate (scrw)					503
*Total Flow (MMSCF)					1147 04
*Flow Pressure (Inwc)					6.3
*Flow Temperature (r)					103
Control Ponel - Touchscreen (Press Resettable Flow Histo	ni Annian Data Menu A	lause Detail			103
*Resettable Total Flow (MMSCF)	y, many and mena, a	10001	7		799.180
*Reset Date/Time (mm/dd/yy hh.mm:ti)					771,100
Control Panel - Tauchscreen - Blower Data (Prott A	Inial	-			
*Blower 301 Runtime (Hours)					112 250
*Blower 301 Vibration (In/Sec)	70000		-		425
*Blower 301 Speed (MMax)		1222			0,27
*Blower 301 Inlet Bearing Temp (F)					42359 657. 58 99
*Blower 301 Outlet Bearing Temp (r)					78
Control Panel - Blower Keypod					77
*Blower 301 Current (Amps)			T		
Gas Handling Skid					13.1
*Demister Inlet Pressure (Inwc)					2/12
*Demister Outlet Pressure (Inwc)					- 38,2
*Demister DP (towc)					- 39.5
*Flame Arrester Inlet Pressure (lawc)		-			-11.3
*Flame Arrester Outlet Pressure (Inwc)			-		+7.4
*Flame Arrester Obdet Pressure (Inwc)					+4.5
Flare					+2.9
to the contract of the contrac					
*Visible Emissions (Yes/No, II yes explain) *Spiralator Position (Nopen)					No
					50
*Manual Louver 1 Position (Kopen)					50
*Manual Louver 2 Position (Kopen)					50
Other					Party.
Heat Trace OK (check for Yes)					[>
*Propane Tank Level OK [11 12 [Check for Yes]]					N N
	Flore 3	- Monitoring			
Time (hh:mm)					1405
Technician (totals)					DB
Control Panel	and a				
*Indicator Lights OK (Check for Yes)					2
"Heating/Cooling OK (Check for Yes)					×
Control Panel - Digital Recorder					20 - 20 - 20 - E
*Remote Recorder On (Check for Yes)					1

ontrol Panel - Touchscreen - Analog Data Me	Monday	Tuesday	Wednesday	Thursday	Friday
DILLIAL LANCE LOSCINGISCIECIS - MINIOR DOTA INC	nu - Process Overviev	· ·	*		
Gas Handling Skid Inlet Vacuum (Inwc)					-40 5
Gas Handling Skid Inlet Temperature (F)					-40.5
Panel Temperature (F)		-			68,
Recirculation Valve Position (sclosed)					100%
Flare Flame Temperature (F)					1404
Flame Arrestor Temperature (F)					81
ontrol Panel - Touchscreen - Blower Data (Pri	ts Back, Blower Menu, Select	Current Sinneri	1		8 !
Blower Runtime (Blower Runtime (Hours))				1	302 586
Blower Speed (Blower Speed (XM4=))					63
Blower Vibration (Blower Vibration (In/Sec))				1	
Blower Current (Slower Current (Amps))		1			0.0
Control Panel - Touchscreen - Flare Flow Data	(Brees Book Y2 Slove Claus Da	to!			127.
Flow Rate (scrw)	friess part of their time of	10)			756
Total Flow (MMSCF)	1				
'Flaw Pressure (Inwc)					613 48
Flow Temperature (F)			-		4.2 82 2.14
Flow DP (Inwc)					82
Control Panel - Touchscreen (Press Resettable)					2.14
Resettable Total Flow (MMscr)					6134785
Reset Date/Time (mm/dd/yy hh:mm:ss)					
Control Panel - Touchscreen - Alarm History (ress Main)	No.			
'Alarm History (Check box If no alarm)					X
Sas Handling Skid					V
Demister Inlet Pressure (Inwc)					-40.6
Demister Outlet Pressure (Inwc)					-41.4
'Demister DP (InWc)					+0,8
Flame Arrester Inlet Pressure (InWc)					44.2
Flame Arrester Outlet Pressure (Inwc)					+3.9
Flame Arrester OP (Inwc)		- 17-	1		+0.3
'Fail-Close Valve Air Pressure (pu)					107
Flare					107
Visible Emissions (Yes/Na, If yes explain)					טען
Spiralator Position (xopen)					50
Manual Louver 1 Position (Nopen)					50
Manual Louver 2 Position (Nopen)					50
Other					100
Heat Trace OK (Check for Yes)					X
Propane Tank Level OK (T1 T2 (Check for Yes))					K N
		nt 1 - Monitorin			
Property Tank Cevel On (11 12 (Check for Yes))					
	Engine Plai	it 1 - Monitorin	<u> </u>		1217175
lime (W. nm)	Engine Plai	it 1 - Monitorin			1416
lime (M nm) Fechnician (intuis)	Engine Plai	it 1 - Monitorin			1416 08
lime (M nm) Fechnician (inhul) Engine Control Ponel	Engine Pla	it 1 - Monitorin			UB
Firme (hh mm) Fechnician (inhala) Engline Control Panel "Power Setpoint (awh) (Engine 44 43)	Engine Plai	nt 1 - Monitorin			667 685
Fime (hk mm) Fechnician (intials) Engine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1)	Engine Plai	nt 1 - Wonitorin			
Fime (hh mm) Fechnician (intials) Engine Control Panel Power Setpoint (twh) (Engine #4 #3) Power Setpoint (twh) (Engine #2 #1) Control Room - Laptop	Engine Plai	nt 1 - Wionitorin		1	667 685
Fime (hh mm) Fechnician (inhist) Fengine Control Panel Power Setpoint (kwh) (Engine #4 #1) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF)	Engine Plai	nt 1 - Wionitorin		1	667 685 691 167
Fime (hh mm) Fechnician (intula) Fengine Control Panel Power Setpoint (kwh) (Engine #4 #1) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM)	Engine Plai	nt 1 - Wionitorin		1	667 685
Firme (hh mm) Fechnician (intels) Fengine Control Panel Power Setpoint (LWh) (Engine #4 #1) Power Setpoint (LWh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F)	Engine Plai	nt 1 - Wionitorin		1	667 685 691 167
Fime (hh mm) Fechnician (intula) Fengine Control Panel Power Setpoint (kwh) (Engine #4 #1) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM)	Engine Plai	nt 1 - Wionitorin			667 685 691 67 167 164 921.
Firme (hh mm) Fechnician (intels) Fengine Control Panel Power Setpoint (LWh) (Engine #4 #1) Power Setpoint (LWh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F)	Engine Plai	nt 1 - Wionitorin			667 1685 691 167 164 921. 1099.3 73.2
Firme (hh mm) Fechnician (initials) Fengine Control Panel Power Setpoint (kwh) (Engine #4 #1) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Engine Bay/Control Room Window Inlet Gas Pressure (INWC) Other	Engine Plai	nt 1 - Wionitorin			667 1685 691 167 164 921. 1099.3
Firme (Nr. mm) Fechnician (initials) Fengine Control Panel Power Setpoint (kWh) (Engine #4 #3) Power Setpoint (kWh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Engine Bay/Control Room Window Inlet Gas Pressure (INWC)	Engine Plai	1 L - WIONITOFIN			667 1685 691 167 164 921. 1099.3 73.2

ay of Week	Monday	Tuesday	Wednesday	Thursday	Friday
ate (mm/ad/yy)	13. 7. 15				4/22/22
	Lowry Hea	ader - Monitoring	7		
me (th mm)					1530 DB
echnician (Initials)		1			75
ontrol Panel - Digital Recorder	111				0->
ow Rate (scrm)					183
as Temperature (F)					48.3
	Flore 2	? - Monitoring			
ime (kh:mm)					1535
echnician (Initials)					PB
ontroi Panel					
Indicator Lights OK (Check for Yes)					2
eating/Cooling OK (check for Yes)					×
ontrol Panel - Digital Recorder					
ocal Recorder On (Check for Yes)					3
antrol Panel - Touchscreen - Process Overview					
Gas Handling Skid Inlet Pressure (Inwc)					-37.6
Flare DP (Inwc)		The state of the			5.25
Flare Flame Temperature (r)					1091
Control Panel - Touchscreen (Press Nest)					Zilliana elstenium
anel Temperature (r)					103
Gas Handling Skid Inlet Temperature (F)					
Recirculation Valve Position (scored)					70%
ontrol Panel - Touchscreen - Flare Flow Data (Pre	s Back 2x, Flore Flow	Date)			- 2010/42
Flow Rate (scrm)		1/4			499
Total Flow (MMSCF)					1137.85
Flow Pressure (Inwe)					6.7
Flow Temperature (r)		1			100
Control Panel - Touchscreen (Press Resettable Flow Histor	v Anaion Dota Menu	Alower Datal			100
Resettable Total Flow IMMSCFI		Total Control			794.1852
Reset Date/Time (mm/dd/yy hh.mm:s)				1	7
Control Panel - Tauchscreen - Blower Data (Press M.	olel				
Blower 301 Runtime (Hours)		1		1	42192
Blower 301 Vibration (In/Sec)			+		570
Blower 301 Speed (MANA)			-		00.7
Blower 301 Inlet Bearing Temp (r)		-			75
Blower 301 Outlet Bearing Temp (r)		-			0.78 88% 75 76
Control Panel - Blower Keypad				-	7.0
Blower 301 Current (Amps)					13.2
Sas Handlina Skid					12.2
Demister Inlet Pressure (nwc)					1-37.2
Demister Outlet Pressure (Inwc)					
Demister DP (mwc)				ļ	-40.0
'Flame Arrester Inlet Pressure (MWC)					+2.8
		ļ			+7.4
Flame Arrester Outlet Pressure (Inwc)				1	14.8
					+26
Flare				1	. 4
Visible Emissions (yes/No, if yes explain)					196
Spiralator Position (Kopen)	4-				55
Manual Louver 1 Position (xopen)					50
Manual Louver 2 Position (Kopen)				1	50
Other					
Teat Trace OK (Check for Yes)				ļ.,, <u>L.</u> ,	
*Propane Tank Level OK (11 12 (Check for Yes))					Z k
	Flare	3 - Monitoring			
Time (hh:mm)				!	1545
Fechnician (trivials)		-		1	DB
Control Ponel		-			
Indicator Lights OK (Check for Yes)					×
	[0]				<u> </u>
					10/19/2
*Heating/Cooling OK (Check for Yes) Control Panel - Digital Recorder *Remote Recorder On (Check for Yes)					

Control Panel - Touchscreen - Analog Data Ment Gas Handling Skid Inlet Vacuum (InWC) Gas Handling Skid Inlet Temperature (F) Panel Temperature (F) Recirculation Valve Position (*Cosed) Pflare Flame Temperature (F) Pflame Arrestor Temperature (F) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (*Mea)) Blower Vibration (Blower Vibration (In/Sec))			Wednesday	Thursday	Friday
Gas Handling Skid Inlet Vacuum (Inwc) Gas Handling Skid Inlet Temperature (F) Panel Temperature (F) Recirculation Valve Position (%Cosed) Flare Flame Temperature (F) Flame Arrestor Temperature (F) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (XMee))				VIII ON THE STATE OF THE STATE	-40.5
Panel Temperature (F) Recirculation Valve Position (%Cosed) Flare Flame Temperature (F) Flame Arrestor Temperature (F) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (%Mes))	Back, Blower Menu, Select C			VIII-DA AND GALLERY	61
Recirculation Valve Position (%Cosed) Flare Flame Temperature (r) Flame Arrestor Temperature (f) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (%Mas))	Back, Blower Menu, Select C				0
Plare Flame Temperature (r) Plame Arrestor Temperature (f) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (XMas))	Back, Blower Menu, Select O				
Flame Arrestor Temperature (f) Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (XMas))	Back, Blower Menu, Select O	Marine Marine San			477-10
Control Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (XMas))	Back, Blower Menu, Select C		1		9-209 100
ontrol Panel - Touchscreen - Blower Data (Press Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (XMee))	Back, Blower Menu, Select C				1205
Blower Runtime (Blower Runtime (Hours)) Blower Speed (Blower Speed (KMex))	merch minute lasting better fo	Name of Services	1		95
Blower Speed (Blower Speed (MMax))		WITHIT BIOWEY)			1
Blower Vibration (Blower Vibration (In/Seci)					302 15695
					686
Blower Current (Blower Current (Amps))					0.02
ontrol Panel - Touchscreen - Flare Flow Data In					1361
Flow Rate (scrm)	ress Back KZ, Flare Flow Date	0)			
Total Flow (MMSCF)					1127
Flow Pressure (Inwe)				272	603.74
					4.8
Flow Temperature (F)					97
Flow DP (Inwc)			20		3.18
ontrol Panel - Touchscreen (Press Resettable)					100
Resettable Total Flow (MMSCF)					603.7443
Reset Date/Time (mm/dd/yy hh:mm:ss)					
ontrol Panel - Touchscreen - Alarm History (Pres	s Main)				danse de la constante de la co
Alarm History (Check box If no alarm)					X
as Handling Skid			- Land		
Demister Inlet Pressure (Inwc)					410 44
Demister Outlet Pressure (Inwc)					-40,4
Demister DP (inWc)					-41.4
lame Arrester Inlet Pressure (Inwc)					+1.0
lame Arrester Outlet Pressure (inwc)					+5.6
Flame Arrester DP (Inwc)					+5.4
Fail-Close Valve Air Pressure (ps)					+0.2
are					07
/isible Emissions (Yes/No, If yes explain)					Pi
Spiralator Position (Mopen)			1		50
Manual Louver 1 Position (Kopen)			1		50
Manual Louver 2 Position (Kopen)			(50
ther				A-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	
Heat Trace OK (Check for Yes)					X
Propane Tank Level OK (T2 T2 Check for Yes})					X I X
	Engine Plant	t 1 - Monitoring			[27] ! C24
CTIE (hit enm)					1/40
echnician (inhiela)					1600
ngine Control Panel			<u> </u>		DB
Power Setpoint (kWh) (Engine #4 #2)		1			7721777
Power Setpoint (twh) (Engine #2 #1)		<u> </u>			674 680
ontrol Room - Laptop		1			681 1674
Flow Total (MSCF)					
low Rate (scrm)	<u> </u>				1626-26
					1626.2
Discharge Gas Temperature (F)					96.7
gine Bay/Control Room Window					
niet Gas Pressure (Inwc)					-44.0
her					
sible Emissions (ves/No, If yes explain)					
te * Collect during device operation anily			i		
	Pa	marks			
	77	144014474			
The second secon	productive desired when expression databases				

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	fair th	dan age to t			4/15/22
lime (th mm)	Lowry Hea	der - Monitoring	7		
Fechnician (taluar)					1715
Control Panel - Digital Recorder					DA
					1-12-1
Flow Rate (scrm)			1		186
Gas Temperature (F)		المراجع			47.4
	Flare 2	- Manitoring			
Time (hh:mm)					(720
Technician (Initials)					AB
Control Panel					
*Indicator Lights OK (Check for Yes)					2
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)					2
Cantral Panel - Touchscreen - Process Overview					
*Gas Handling Skid Inlet Pressure (Inwc)				2.11	-38.1
*Flare DP (InWC)					4127-5.1
*Flare Flame Temperature (r)					1187
Control Panel - Touchscreen (Press Nest)					
Panel Temperature (r)					81
*Gas Handling Skid Inlet Temperature (F)					35
*Recirculation Valve Position (scored)					70%
Control Panel - Touchscreen - Flare Flow Data (Pres	s Back 3x, Flore Flow Do	ito)			and the state of the state of
*Flow Rate (scrm)					476
*Total Flow (MMSCF)					1132.85
*Flow Pressure (INWC)					98
*Flow Temperature (r)					98
Control Panel - Touchscreen (Press Resettable Flow Hisson	y, Analog Data Menu, B	lower Data)			
*Resettable Total Flow (MMSCF)		T			789.1899
*Reset Date/Time (mm/dd/yy hh:mm:si)					
Control Panel - Touchscreen - Blower Data (Press Me	zie)				
*Blower 301 Runtime (Hours)			T		42.076
*Blower 301 Vibration (In/Sec)					0 25
*Blower 301 Speed (NAM)					42026 6,25 85.7 73
*Blower 301 Inlet Bearing Temp (r)					43
*Blower 301 Outlet Bearing Temp (r)			1		95
Control Panel - Blower Keypad	THE RESTRICTED TO SHARE				1
*Blower 301 Current (Amps)					12.9
Gas Handling Skid		<u> </u>			
*Demister Inlet Pressure (inwo)		1		1	- 37.4
*Demister Outlet Pressure (Inwc)					- 40.8
*Demister DP (mwc)		-	-	Manager and the second	+2.9
*Flame Arrester Inlet Pressure (Inwc)					77.6
*Flame Arrester Outlet Pressure (hwc)				1	
*Flame Arrester DP (mwc)					+4, 5
		L		<u> </u>	+3.1
Flare					1 10
*Visible Emissions (Yes/No. II yes explain)					No
*Spiralator Position (Kopen)					58
*Manual Louver 1 Position (Kopen)					50
*Manual Louver 2 Position (Kopen)		<u> </u>	_1		50
Other					רעוו
Heat Trace OK (check for Yes)		I partilla			K
*Propane Tank Level OK [71 72 [Check for Yes]]					N N
	Flare 3	- Monitoring			
Time (hh.mm)					1730
Technician (tokish)				í	06
Control Panel		w 21 27 01 -			
*Indicator Lights OK (Check for Yes)					>
*Heating/Cooling OK (Check for Yes)					Je
Control Panel - Digital Recorder					Ally T
*Remote Recorder On (Check for Yes)					139

	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Men	ıu - Pracess Overview				
Gas Handling Skid Inlet Vacuum (InWC)					-40.5
Gas Handling Skid Inlet Temperature (r)					77-56
Panel Temperature (F)					76
Recirculation Valve Position (xclosed)					60%
Flare Flame Temperature (F)					1126
Flame Arrestor Temperature (F)					86
ontrol Panel - Touchscreen - Blower Data (Pres	Back, Blower Menu, Select Cu	rrent Blower)			
Blower Runtime (alower Runtime (Hours))			i	1	30215529
Blower Speed (Blower Speed (KMax))			11.	1	68%
Blower Vibration (Blower Vibration (In/Sec))		1		1	10.61
Blower Current (Blower Current (Amps))					133.3
ontral Panel - Touchscreen - Flare Flow Data (Press Back X2, Flore Flow Date,	1			1 1271
Flow Rate (scrm)	T I				1231
Total Flow (MMscF)					
Flow Pressure (Inwc)					592.77 5.6 88
Flow Temperature (F)					12.6
Flow DP (Inwc)					3.76
Control Panel - Touchscreen (Press Resettable)	· · · · · · · · · · · · · · · · · · ·				1 5.76
Resettable Total Flow (MMSCF)			-		C479
Reset Date/Time (mm/dd/yy hh:mm:ss)			-		592.7672
Control Panel - Touchscreen - Alarm History Pre	en At-f-1				
Alarm History (Check boatt no alarm)	za mainj				.,
as Hondling Skid					又
Demister Inlet Pressure (Inwc)					
Demister Outlet Pressure (nwc)					-39.0
Demister Oddet Pressure (nwc)					-40.8
Flame Arrester Inlet Pressure (Inwc)					-1.8
					46.4
Flame Arrester Outlet Pressure (InWc)					+6.0
Flame Arrester DP (Inwc)					+0.4
Fail-Close Valve Air Pressure (ps)					115
lare					
Visible Emissions (res/No. If yes explain)					NO
Spiralator Position (Kopen)					50
Manual Louver 1 Position (Kopen)					50
Manual Louver 2 Position (sopen)					50
ther					
Heat Trace OK (Check for Yes)					
Propane Tank Level OK (T2 T2 (Check for Yes))					RIXI
	Engine Plant	1 - Monitoring			1 67 1 67
ime (hh mm)					1735
The part of the same of the sa					1735 DB
echnician (initials)					YD
echnician (Initials) ngine Control Panel					
ngine Control Panel					1/6 141
ngine Control Panel Power Setpoint (NWh) (Engine #4 #2)			1		668 1641
ngine Control Panel Power Setpoint (wh) (Engine 84 81) Power Setpoint (wh) (Engine 82 81)					676 1682
ngine Control Panel Power Setpoint (Awh) (Engine 84 81) Power Setpoint (Awh) (Engine 82 81) Ontrol Room - Laptop					
ngine Control Panel Power Setpoint (Wh) (Engine 84 81) Power Setpoint (Wh) (Engine 82 81) ontrol Room - Laptop Flow Total (MSCF)					-tesa.664
ngine Control Panel Power Setpoint (Wh) (Engine #4 #1) Power Setpoint (Wh) (Engine #2 #1) ontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM)					668 691 676 682 +690,6
ngine Control Panel Power Setpoint (Wh) (Engine #4 #1) Power Setpoint (Wh) (Engine #2 #1) Pontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F)			1		
rgine Control Pane! Power Setpoint (Wh) (Engine #4 #1) Power Setpoint (Wh) (Engine #2 #1) Pontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Ingine Bay/Control Room Window			1		1090.6 1090.6 98.5
rgine Control Panel Power Setpoint (Awh) (Engine #4 #1) Power Setpoint (Awh) (Engine #2 #1) Power Setpoint (Awh) Power Setpoint (Engine #2 #1) Power Setpoint (Engine #4 #1) Power Setpoint (Engine #4 #1) Power Setpoint (Awh) (Engine			1		-tesa.664
gine Control Panel Tower Setpoint (IWh) (Engine #4 #3) Tower Setpoint (IWh) (Engine #2 #1) Tower Setpoint (IWh) (Engine #2 #1) Tower Setpoint (IWh) (Engine #2 #1) Tower Setpoint (IWh)			1		1090.6 1090.6 98.5
rgine Control Panel Power Setpoint (Awh) (Engine #4 #1) Power Setpoint (Awh) (Engine #2 #1) Power Setpoint (Awh) (Engine #4 #1) Power Setpoint (Awh) (Awh) (Engine #4 #1) Power Setpoint (Awh) (Engine #4 #1) Power					1090.6 1090.6 98.5
rgine Control Panel Power Setpoint (AWA) (Engine #4 #1) Power Setpoint (AWA) (Engine #2 #1) Pontrol Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Rigine Bay/Control Room Window Inlet Gas Pressure (INWC)					1090.6 1090.6 98.5

Day of Week	Monday	Tuesday	Wednesday	Thursday	/ Friday
Date (mm/dd/yy)			Wednesday 4/6/22		4/8/22
	Lowry Hea	der - Monitorin	g		
Time (hh mm)			1550 DB		1600
Technician (Initials)			D5		PB
Control Panel - Digital Recorder			* Ot 1		CIL
Flow Rate (scrw)			191		194
Gas Temperature (F)			46.4		46.6
W1	Flare 2	- Monitoring	1555	10000	
Time (sh:mm) Technician (satuals)			The second secon		1605
Control Panel			DB		DA
*Indicator Lights OK (Check for Yes)			No.	-	
Heating/Cooling OK (Check for Yes)			N N		N N
Control Panel - Digital Recorder			8		
Local Recorder On (Check for Yes)			KZ		
Control Panel - Touchscreen - Process Overview			×		×
*Gas Handling Skid Inlet Pressure (Inwc)			24 2		77
			-30,5		-38.5 5.22
*Flare DP (Inwc)			-38.5 5.16 1179		5.22
*Flare Flame Temperature (r) Control Panel - Touchscreen (Press Nest)			1179		1249
			7.0		
Panel Temperature (r)			69		30
*Gas Handling Skid Inlet Temperature (r)			39		30
*Recirculation Valve Position (science)		1	70.7		706
Control Panel - Touchscreen - Flare Flow Data (Pres	s Bock 2x, Flore Flow D	nto)			
*Flow Rate (SCFM)			497	1000	504 1127, 77 6.5 99
*Total Flow (MMSCF)			1126.32		1127,77
*Flow Pressure (Inwc)			6.4		6.5
*Flow Temperature (F)			97		99
Control Panel - Touchscreen (Press Resettable Flow History	, Analog Data Menu, 8	lower Data)	-70		
*Resettable Total Flow (MMSCF)			782.6580		784. 169
*Reset Date/Time (mm/dd/yy hh.mm:ss)					
Control Panel - Touchscreen - Blower Data (Press Ma	in)				44-0-53
*Blower 301 Runtime (Hours)			41808		41857
*Blower 301 Vibration (In/Sec)			0.27		0.26
*Blower 301 Speed (MMss)			0.27 852		0.26 867 59
*Blower 301 Inlet Bearing Temp (F)	mean of		46		59
*Blower 301 Outlet Bearing Temp (r)			92		111
Control Panel - Blower Keypod					
*Blower 301 Current (Amps)			13.2		13.1
Gas Handling Skid					37270
*Demister Inlet Pressure (Inwc)			-39.5		-31.5
*Demister Outlet Pressure (Inwc)			-41.8		-40.5
*Demister DP (Invic)			72.3		+1.0
"Flame Arrester Inlet Pressure (inwc)			+7.5		+7.7
*Flame Arrester Outlet Pressure (INWC)			442		44,6
*Flame Arrester DP (Inwc)			+2.3		+3./
Flare					
*Visible Emissions (ves/No. If yes explain)			NC		NO
*Spiralator Position (stopen)			50		50
*Manual Louver 1 Position (sopen)			50		50
*Manual Louver 2 Position (Kopen)		= = =	50		50
Other					
Heat Trace OK (Check for Yes)			XI I		
*Propane Tank Level OK (T1 T2 (Check for Yes))			LA X		× 1 ×
T1	Flare 3	- Monitoring		7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Time (hk:mm)			600		1610
Technician (trittels)			25		DB
Control Panel					1000
*Indicator Lights OK (Check for Yes)			<u> </u>		X
*Heating/Cooling OK (Check for Yes)					20
Control Panel - Digital Recorder					
*Remote Recorder On (Check for Yes)			50		M

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data M					*******
*Gas Handling Skid Inlet Vacuum (Inwc)			-40.6		-39.7
*Gas Handling Skid Inlet Temperature (F)					57
Panel Temperature (r)			55		81
Recirculation Valve Position (xClosed)		7710	100 4		
Flare Flame Temperature (r)			1364		100%
*Flame Arrestor Temperature (r)			71		1234
Control Panel - Touchscreen - Blower Data (P	ers Rock Blower Mann Calast S	Cumpat Afamas)	76		67
*Blower Runtime (Blower Runtime (Hours))	177 DOLG, DIGWET MIETING, DEMELT	miteur minnetil	302 5311		747 677
*Blower Speed (Blower Speed (KMex))			62%		302 535
*Blower Vibration (Blower Vibration (In/Sec))				-	166
*Blower Current (Blower Current (Amps))			0,01		10.01
Control Panel - Touchscreen - Flare Flow Data	t formation of the same		26.8		129.
*Flow Rate Iscani	PIETE BOCK AZ, FIGTE FIOW DE	ra)	954		1 11 1
*Total Flow (MMSG)					1100
*Flow Pressure (Inwc)			577.09		479.94
*Flow Temperature (F)			3,9		
*Flow DP (Inwc)			79		70
			2.18		3.01
Control Panel - Touchscreen (Press Resettable)				Cr. Street	
*Resettable Total Flow (MMSCF)			577.0911		579.943
Reset Date/Time (mm/dd/yy hh-mm:ss)					-
Control Panel - Touchscreen - Alorm History (Press Main)				
*Alarm History (Check box If no alarm)					N N
Gas Handling Skid	making by the parties				
*Demister Inlet Pressure (Inwc)			- 39.8		-40.0
*Demister Outlet Pressure (Inwc)			-40.4		-40.6
*Demister DP (InWc)			+1.1		+0.6
*Flame Arrester Inlet Pressure (Inwc)		-	44.6		+5.1
*Flame Arrester Outlet Pressure (Inwc)			+4.1		14.7
*Flame Arrester DP (Inwc)			+0.5		
*Fail-Close Valve Air Pressure (psi)			110		+0,4
Flare			110		1
*Visible Emissions (Yas/No, If yes explain)	1	1700	NO		NO
*Spiralator Position (XOpen)			50		50
*Manual Louver 1 Position (Kopen)		described on the second			
*Manual Louver 2 Position (Kopen)			50		150
Other		-	50		50
*Heat Trace OK (Check for Yes)					>
*Propane Tank Level OK (71 72 (Check for Yes))					- Artual
. Properte rank cevet OK (13 12 (Check for fes))					N POR
	Engine Plan	t 1 - Monitorii	ng		
Time (hh mm)					1620
Technician (Inklels)			1610		08
Engine Control Panel			760 672		
*Power Setpoint (kWh) (Engine #4 #3)			7601672		1690 1664
*Power Setpoint (kwh) (Engine #2 #1)	<u> </u>		644 700		662 1697
Control Room - Laptop					
*Flow Total (MSCF)			632292.1		635450,
*Flow Rate (scrm)			1106:3		1625,3
*Discharge Gas Temperature (r)			79,7		82.0
Engine Bay/Control Room Window					0 0.0
*Inlet Gas Pressure (Inwc)			-41.8		-42.5
Other					
Visible Emissions (Yes/No, If yes explain)					
Note * Collect during device operation only	1				
		emarks			
	- R	EIIIGLK2			
			<u> </u>		

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/sid/yy)		5/3/22			15/6/22
The same of the sa	Lowry He	ader - Monitoring			
Time (th mm)		1635			1530
Technician (Initisis)		DB			PA
Control Panel - Digital Recorder					
Flow Rate (scrm)		191			194
Gas Temperature (F)		49:8			50.1
	Flare .	2 - Monitoring			
Time (hh:mm)		640			1535
Technician (Initials)		DB			DB
Cantrol Panel	_				
*Indicator Lights OK (Check for Yes)		区)c!
Heating/Cooling OK (Check for Yes)		2		100	- King
Control Panel - Digital Recorder					
Local Recorder On (Check for Yes)					
Control Panel - Touchscreen - Process Overview					- Laur
*Gas Handling Skid Inlet Pressure (Inwc)		-47.9			-42.8
*Flare DP (Inwc)		5,29			6 76
*Flare Flame Temperature (F)		-42.1 5.29 (188			5.35
Control Panel - Touchscreen (Press Next)		1.0.0			16.01
Panel Temperature (r)		78			105
*Gas Handling Skid Inlet Temperature (r)		7.0			29
*Recirculation Valve Position (scooled)		43			70%
Control Panel - Touchscreen - Flare Flaw Data (Pre	tt Back 2v Elson Elson	Data!			70 6
*Flow Rate (scrm)		499			F 6 7
*Total Flow (MMSCF)		1145 61	-		503
*Flow Pressure (lawc)		1145.81			6.7
*Flow Temperature (r)		109			110
Control Panel - Touchstreen (Press Resettable Flaw Histor					1110
*Resettable Total Flow (MMSCF)	y, Analog Data Mehil,	8002.1434			
*Reset Date/Time (mm/dd/yyhh.mm:11)		שעניי. שש		}	804,275
Control Panel - Touchscreen - Blower Data (Press M					
*Blower 301 Runtime (Hours)	ain)	40.467			
*Blower 301 Vibration (In/Sec)		42457			42528
*Blower 301 Speed (MAIL)		0,65			0.24
*Blower 301 Inlet Bearing Temp (r)		42457 0.25 90%			916
*Blower 301 Outlet Bearing Temp (r)					81
Control Panel - Blower Keypod		111			115
*Blower 301 Current (Amps)		-			
Gas Handling Skid		13.8			14.0
*Demister Inlet Pressure (Inwc)		1-43.0			-43.4
*Demister Outlet Pressure (InWc)		-45-7			-45.6
*Demister DP (Inwc)		t2.7			+ 2-2
*Flame Arrester Inlet Pressure (Inwc)		+7.6			+7.5
*Flame Arrester Outlet Pressure (Inwc)		+4.6			44.5
*Flame Arrester DP (mwc)		+3.0			+3.0
Flare					
*Visible Emissions (yes/No, II yes explain)		NO			لمادم
*Spiralator Position (Nopen)		50			50
*Manual Louver 1 Position (Kopen)		50			50
*Manual Louver 2 Position (Kopen)		50			50
Other					
Heat Trace OK (Check for Yes)		<u> </u>			- 2
*Propane Tank Level OK [71 72 (Check for Yes))		X			N I SI
	Flare	3 - Monitoring			
Time (hh:mm)		1645			1545
Technician (toltioh)		DB		1	06
Control Panel					ν0
*Indicator Lights OK (Check for Yes)		×			N
*Heating/Cooling OK (Check for Yes)		X		70	d
Control Panel - Digital Recorder		A street of the latter to the	_		X
*Remote Recorder On (Check for Yes)				-	×

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Control Panel - Touchscreen - Analog Data Men					- 1100
Gas Handling Skid Inlet Vacuum (Inwc)		_40.1			-40,0
Gas Handling Skid Inlet Temperature (F)	1				67
Panel Temperature (F)		60 74			50
Recirculation Valve Position (xdosed)		100 4			100%
Flare Flame Temperature (n		1329			1272
Flame Arrestor Temperature (r)		85			95
Control Panel - Touchscreen - Blower Data (Pres	Back Blower Menu Sele				
Blower Runtime (Blower Runtime (Hours))		301 3244			301 1331
Blower Speed (Blower Speed (XMax))		666	1		1 65
Blower Vibration (Blower Vibration (In/Sec.))		0.01			
*Blower Current (Blower Current (Amps))		132.1			0.6
Control Panel - Touchscreen - Flare Flow Data	Bress Seet WY Floor Floor	26.1			130.
Flow Rate (scrw)	PIEST BOCK AZ, FIOTE FIOW	1116			(051
'Total Flow (MMscn)		/ 10 77			624.12
*Flow Pressure (Inwc)		619.77			
*Flow Temperature (F)		5.0			4.4
Flow DP (Inwc)	1	3.10			96
Control Panel - Touchscreen (Press Resettable)		١ , ١ ، ٢			2.69
		119-7/10			1
Resettable Total Flow (MMSCF)		619.7668			624.115
*Reset Date/Time (mm/dd/yy hh:mm:sx)					
Control Panel - Touchscreen - Alarm History (Pro	rss Main)				
*Alarm History (Check box if no alarm)		B			
Gas Hendling Skid					
*Oemister Inlet Pressure (Inwc)		-34.7 -40.8 +1.1 +6.0			-39.4
*Demister Outlet Pressure (Inwc)		- 40.8			- 40.8
*Demister DP (Inwc)		+1.1			+14
Flame Arrester Inlet Pressure (Inwc)		46.0			+1.4
*Flame Arrester Outlet Pressure (Inwc)		+5.5			+4.4
*Flame Arrester DP (inwc)		+0.5			+0.5
*Fail-Close Valve Air Pressure (psl)		107			107
Flore	-				107
*Visible Emissions (Yes/No, If yes explain)	1	٥٧			NO
*Spiralator Position (Nopen)		50			50
*Manual Louver 1 Position (Kopen)		50			30
*Manual Louver 2 Position (xopen)		50			
Other	+			********	50
*Heat Trace OK (Check for Yes)		X			PC PC
Propane Tank Level OK (T1 T2 (check for Yeal))		X Z			ETE
Tropatte tank terefor (11) 12 (chect for feel)	Freina Bi	ant 1 - Monitoring			
	engine Pi	ant 1 - Monitoring		T	1555
Time (M mm)		1650			1555
Technician (intrini)	1	DB			DB
Engine Control Panel		122-122			
*Power Setpoint (kwh) (Engine #4 #3)		670 678		1	687 1692
*Power Setpoint (LWh) (Engine #2 #1)	11	693 681			685 685
Control Room - Laptop					
*Flow Total (Mscr)		671001,6			675735.
*Flow Rate (SCFM)		1107.0			1066.8
*Discharge Gas Temperature (r)		69.0			80,1
Engine Bay/Control Room Window					
*Inlet Gas Pressure (Inwc)		- 43,8			-4512
Other					
*Visible Emissions (Yes/No, If yes explain)		NO			NO
Note * Collect during device operation only					i
		Remarks			
BLR 2 31 ON 5/3/2	. 2				
30 1 00 3/3/6					

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	5/9/22				5/13/22
	Lowry Heade	r - Monitorin	7		
Time (bh mm)	1600				1610
Fechnician (Initials)	DB				D5
Control Panel - Digital Recorder					
Flow Rate (scrm)	184				190
Gas Temperature (r)	50.4				51.1
	The latest the second s	Monitoring			37.1
firme (hh:mm)	1605	nomicing	1		1620
Fechnician Antuals	DB				PB
Control Panel	DB				100
*Indicator Lights OK (Check for Yes)	K				
Heating/Cooling OK (Check for Yes)	- R				
Control Panel - Digital Recorder			LJ LJ		
Local Recorder On (Check for Yes)	×	pany			
		t _{en} l			<u>L</u>
Control Panel - Touchscreen - Process Overvie					
Gas Handling Skid Inlet Pressure (Inwc)	-42.9				-42.3
*Flare DP (InWc)	5,33				5.29
*Flare Flame Temperature (r)	932				1253
Control Panel - Touchscreen (Press Next)					
Panel Temperature (1)	90				00
*Gas Handling Skid Inlet Temperature (F)	39				36
Recirculation Valve Position (sclosed)	70%				706
Control Panel - Touchscreen - Flare Flow Data)			T
*Flow Rate (scrm)	501		1		500
*Total Flow (MMSCF)	501 [150, i]				1153,00
*Flow Pressure (Inwc)	6.8				6.8
Flow Temperature (F)	112				114
Control Panel - Touchscreen (Press Resettable Flaw)	tistory Angles Data Meny Alou	wee Dorrol			11 7
*Resettable Total Flow (MMSCF)	806.4481		T		809.340
Reset Date/Time (mm/dd/yy hh.mm:ss)	4-0.7.0				00113-10
Control Panel - Touchscreen - Blower Data (Pre	es telat				
*Blower 301 Runtime (Hours)	42601				112/07
	3,23 977				42697
*Blower 301 Speed (xmm)	212				0.04
*Blower 301 Inlet Bearing Temp (r)	91.6				90%.
	68				77
*Blower 301 Outlet Bearing Temp (r)	110			1	117
Control Panel - Blower Keypad				,	
*Blower 301 Current (Amps)	14.0				138
Gas Handling Skid					1"
*Demister Inlet Pressure (Inwc)	-43.3				-42.5
*Demister Outlet Pressure (Inwc)	-45.7				-44,9
*Demister DP (towc)	+2.4			ļ	42.4
*Flame Arrester Inlet Pressure (Inwc)	+7.5				+8.0
*Flame Arrester Outlet Pressure (Inwc)	+4.4	=			+4.8
*Flame Arrester DP (Inwc)	+3.1				73,2
Flare					
*Visible Emissions (ves/No, if yes explain)	NO				٥١٩
*Spiralator Position (Nopen)	50				
*Manual Louver 1 Position (xopen)	50			1	50
Manual Louver 2 Position (Kopen)	50			I	50
Other					10
Heat Trace OK (Check for Yes)					X
Propane Tank Level OK (T1 T2 (Check for Yes))	XX				P4 1 S2
		Adamies-in-		<u> L.J. L.J.</u>	
Firm the sent	1610	Monitoring			
Time (thims)					
Technician (Inklas)	P6			2	D8
Control Panel					
*Indicator Lights OK (Check for Yes)	×				K
*Heating/Cooling OK (check for Yes)	K				
Control Panel - Digital Recorder					
*Remote Recorder On (Check for Yes)	X		275.5		×

	Tuesday	Wednesday	Thursday	Friday
nu - Process Overview				
-40,2				- 39.8
62				64
79				80
				100 %
				1290
91				95
is Back, Blower Menu, Select Cu	rrent Blower)			
301 3387	1	1 1	1	301 1348
647		1	1	65
0.02	=			0.02
29.3	1			30.
(Press Bock X2, Flore Flow Data	J			30,
986				1048
628.73				634.75
3.7				
93				96
2.43			****	2.7 2
678.7777				674764
				634.75
ness Admini				
				~
12				2
29/				
-> 1.6				-39,5
.41,0		-		7 1.1
				45.0
and the first of the contract				+4,3
				+0.7
167				108
				100
				50
				50
50			there are	50
- K				
X X				
Engine Plant	1 - Monitoring	9		
Engine Plant	1 - Monitorin	7		1635
	1 - Monitorin			
1620 DB	1 - Monitarin	9		1635
1620 DB	1 - Monitaring	9		1635
1620 DB	1 - Monitarin			1635 PB
696 673 681 667	1 - Monitorin			1635 DB
696 673 681 667	1 - Monitarin		1	1635 PB 670 661 683 674
1620 DB	1 - Monitarin		1	1635 PB 670 661 683 674
696 673 681 667 680489.5	1 - Monitarin			1635 PB 670 661 683 674 6866752 10726
696 673 681 667 6804895 10895	1 - Monitarin		1	1635 PB 670 66 683 674
696 673 681 667 6804895 10895	1 - Monitarin			1635 DB 670 661 683 674 6866752 10726 74.8
696 673 681 667 680489.5	1 - Monitarin			1635 PB 670 661 683 674 6866752 10726
696 673 681 667 6804895 10895	1 - Monitaring			1635 DB 670 661 683 674 6866752 10726 74.8
	100' L 1319 91 13 Back, Blower Menu, Select Cu 301 3387 64' L 0.02 2-9,3 (Press Back X2, Flore Flow Data,	100' 13 19 9 18 18 18 18 18 18	100'	100' / 1319 91 18 Bock, Blower Menu, Select Current Blower) 301 3387

Day of Week	Monday	Tuesday	Wednesday	Thursday	Friday
Date (mm/dd/yy)	3/16/22			5/19/22	
	Lowry Heade	r - Monitoring	7		
Firme (bh mm)	1600			1530	
Fechnician (Initials)	DB			PB	
Control Panel - Digital Recorder					
Flow Rate (scrm)	192			196	
Gas Temperature (F)	51.6			52.1	
	Flare 2 - I	Vionitoring			
Time (hkimm)	1605			1540	
Technician (initials)	138			08	
Control Panel					
*Indicator Lights OK (Check for Yes)	N				
Heating/Cooling OK (Check for Yes)					
Control Panel - Digital Recorder	18				
Local Recorder On (Check for Yes)				T I'V	
			<u> </u>		
Control Panel - Touchscreen - Process Overvie				41.5	
*Gas Handling Skid Inlet Pressure (Inwc)	-42.8	<u> </u>	-	-41.2 5.26	
Flare DP (Inwc)	5,37			5,26	
*Flare Flame Temperature (r)	1251		<u> </u>	1755	
Control Panel - Touchscreen (Press Nest)					
Panel Temperature (r)	100			109	
*Gas Handling Skid Inlet Temperature (F)	35			32	
Recirculation Valve Position (sciosed)	70%			701	
Control Panel - Tauchscreen - Flare Flow Data	(Press Back 2x, Flore Flow Data)			
*Flow Rate (scrm)	500			498	
*Total Flow (MMSCF)	1155.16			1157.31	
*Flow Pressure (Inwc)	(.7			16	
*Flow Temperature (r)	1.7			110	
Control Panel - Touchscreen (Press Resemble Flow		uer Data			
*Resettable Total Flow MMSCFI	811.4935			813, 6450	
*Reset Date/Time (mm/dd/yy hh.mm:s)	0.11.11.0		-	1 01210120	
Control Panel - Touchscreen - Blower Data (P					
*Blower 301 Runtime (Hours)	42769		1	42840	-
*Blower 301 Vibration (In/Sec)	0,25			0.23	
*Blower 301 Speed (MALL)					
	90%			9,7	
*Blower 301 Inlet Bearing Temp (r)	81			83	
*Blower 301 Outlet Bearing Temp (r)	100			107	
Control Panel - Blower Keypad					
*Blower 301 Current (Amps)	14.0			13.7	
Gas Handling Skid					
*Demister Inlat Pressure (Inwc)	-42.6			141.2	
*Demister Outlet Pressure (Inwc)	-45.0			-44.2	
*Demister, DP (InWc)	+2.4			43.0	
*Flame Arrester Inlet Pressure (Inwc)	+7.8			+7.8	
*Flame Arrester Outlet Pressure (INVC)	+4.7			1 44.7	
*Flame Arrester DP (mwc)	+3,1			+3.1	
Flore					
*Visible Emissions (Yas/No, If yes explain)	100			NPO	
*Spiralator Position (Nopen)	50			50	
*Manual Louver 1 Position (Kopen)	50		1	50	
*Manual Louver 2 Position (Kopen)	50			1 50	
Other	70			20	
Heat Trace OK (Check for Yes)	R				
*Propane Tank Level OK (11 12 (Check for Yes))	No.				
r response rount DEVELOR (TI T2 (Cleck for Yes))		Administration		MIM	
		Monitoring		12117	
Time (hlumm)	1615			1545	
Technician (taktols)	DB			08	
Control Panel					
*Indicator Lights OK (Check for Yes)				Z I	
*Heating/Cooling OK (Check for Yes)				≥	
Control Panel - Digital Recorder					
*Remote Recorder On (Check for Yes)	361			The Management of the Control of the	

Tuesday Wednesday Thursday Friday -39,9 -63 -63 -63 -63 -63 -63 -63 -63 -63 -63
-39.9 63 84 160 / 1313 102 Select Current Blower) 55
Select Current Blower) 102
Select Correct Blower) (55) (55) (70) (73) (73) (73) (70)
Select Current Blower) 1
1 36 1 36 1 73 1 1 1 1 1 1 1 1 1
1 73 1 1 73 1 1 1 1 1 1 1 1 1
10.05 0.6 1.37.8 1000 Data) 3 16.43.94 8.2 16.53 4.66 4.86 10.7 10.9 10.7
1.37.8 1.37.8 1.37.8 1.37.8 1.38 1
153 6 1 1 3 8 1 6 4 3 9 4 8 2 1 6 2 8 2 1 6 2 8 2 8 2 8 2 8 2 8 2 8 2 8 2 8 2 8 2
1381 643.94 8.2 103 4.86 643.7635 643.7635 -41.1 +2.0 +2.6 *8.7 +0.9 107
8.2 163 4.86 643.7635 -39. -41. +2.0 +2.6 *8.7 +0.9 107
8.2 163 4.86 643.7635 -39. -41. +2.0 +2.6 *8.7 +0.9 107
163 4.86 643.9635 -39. -41. +2.0 +2.6 +8.7 +0.9 107
643.7635 -3941. +2.0 +2.6 -8.7 +0.9 107
643.7635 -3941. +2.0 +2.6 -8.7 +0.9 107
-39. -41. +2.0 +2.6 -8.7 +0.9 107
-39. -41. +2.0 +2.6 -8.7 +0.9 107
-39. -41. +2.0 +4.6 -8.7 +0.9 107
-39. -41. +2.0 +4.6 -8.7 +0.9 107
-39. -41. +2.0 +4.6 -8.7 +0.9 107
-41, +2.0 +2.6 +2.6 +2.6 +2.7 +0.9 107
-41, +2.0 +2.6 +2.6 +2.6 +2.7 +0.9 107
-41, +2.0 +2.6 +2.6 +2.6 +2.7 +0.9 107
#2.0 #9.6 #8.7 #0.9 107
#0.9 107 107
#0.9 107 107
+0.9 1D7 No 50
107 No 50
No 50
50 90
50 90
. 50
30
Plant 1 - Monitoring
1555 D8
D8
12 669 - 1
3 688 687
698869.3
85.7
-42.1
7761
No
NU
2

Rev[3/25/15]

Day of Week	Monday	Tuesday	Wednesday	Thursday 5/26	Friday
Date (mm/dd/yy)	5/23/22			5/26	
	5/23/22 Lowry Head	er - Monitoring			0-10-1
ime (bh mm)	1600			1435	
Technician (musis)	DR			PB	
Control Panel - Digital Recorder					
low Rate (scrm)	201			200	
Sas Temperature (r)	63.1		i	53,3	
		Monitoring	-	32.2	
(inte (hhana)	1605	omtoning		1440	
Fechnician (Intuits)	DB			DK	
Control Panel	DO		1		
*Indicator Ughts OK (Check for Yes)	20				
Martin State of the Control of the C	200			2	
Heating/Cooling OK (check for Yes)	129			126	
Control Panel - Digital Recorder				~	7
Local Recorder On (check for Yes)			L		L
Control Panel - Touchscreen - Process Overview				154	
*Gas Handling Skid Inlet Pressure (Inwc)	-40.5			-40.3	
*Flare DP (Inwc)	5,38			5.33	
*Flare Flame Temperature (r)	1225			(249	
Control Panel - Touchscreen (Press Nest)					
Panel Temperature (r)	82			102	N 9
*Gas Handling Skid Inlet Temperature (F)	46			37	
Recirculation Valve Position (scioses)	756			37 701	
Control Panel - Touchscreen - Flare Flow Data	(Press Back 2x, Flore Flow Dat	(a)		Carried Warrant	
*Flow Rate (scrm)	505			504	
*Total Flow (MMSCF)				1167.32	
*Flow Pressure (Inwc)	1160.71			1162.32	
*Flow Temperature (r)	107			112	
Control Panel - Touchscreen (Press Resettable Flow H		was flate!		116	-
*Resettable Total Flow (MMSG)	816, 5439	wer Galaj	T	8T8. 6609	
THE STATE OF THE S	016,7737			016,000	
*Reset Date/Time (mm/dd/yy hh:mm:ss)					-
Control Panel - Touchscreen - Blower Data (Pre				117	
*Blower 301 Runtime (Hours)	42937			43007	
*Blower 301 Vibration (In/Sec)	0,23			0.24	
*Blower 301 Speed (KMAA)	6, Z 3 88 '/ 59 102			887	
*Blower 301 Inlet Bearing Temp (f)	59				
*Blower 301 Outlet Bearing Temp (r)	102		1	119	
Control Panel - Blower Keypad					
*Blower 301 Current (Ampr)	13,9		12 - 34,017 (5,000)	13.8	
Gas Handling Skid				The second second	
*Demister inlet Pressure (Inwc)	-40.9			-40,5	
*Demister Outlet Pressure (Inwc)	-43.4			-429	
*Demister DP (nwc)	72.5		1	+2.4	
*Flame Arrester Inlet Pressure (wwc)	+7.3			+7.5	2
*Flame Arrester Outlet Pressure (wwc)	+4.4			+4.6	
*Flame Arrester DP (Inwc)	+2.9			+2.9	
Flore	7011			16-	
*Visible Emissions (ves/No, If yes explain)	NO			NO	
*Spiralator Position (Nopen)				50	
*Manual Louver 1 Position (xopen)	50		-	50	
*Manual Louver 2 Position (Kopen)	50		-		
	50			50	
Other Uses The OK in the Uses Th	101				
Heat Trace OK (Check for Yes)	X			×	
*Propane Tank Level OK [12 12 (Check for Yes))	Flore 3	- Monitoring		AC X	
Time (hh:mm)	1615		11 11 11 11 11 11 11 11 11 11 11 11 11	1446	
Technician (tokish)	DB		-	OB	
Control Panei	PD		1	0.0	
*Indicator Lights OK (Check for Yes)	X	F1		ICT	
*Heating/Cooling OK (Check for Yes)	Total			X	
Control Ponel - Digital Recorder	20			×	

Denver Arapahoe Disposal Site Aurora, Colorado S04012

1 L& Z Sum 1 Roy3/25/15)

Page 1 of 2

Control Panel - Touchscreen - Analog Data Mi Gas Handling Skid Inlet Vacuum (Inwc)	Monday	Tuesday	Wednesday	Thursday	Friday
Con Handling Fills tolers to severe and a			1		
	- 40,0		-40.7 64	-40.7	
Gas Handling Skid Inlet Temperature (F)	63		QK.	81	
Panel Temperature (+)	75		8/	81	
Recirculation Valve Position (school)	100.6		100	100%	
Flare Flame Temperature (r)	1287			1304	
Flame Arrestor Temperature (f)	86			1309	
Control Panel - Touchscreen - Blawer Data (Pr	ess Back, Blower Menu, Select Cur	rrent Blower)			
Blower fluntime (slower Kuntime (Hours))	301 3723			301 3794	1
Blower Speed (Blower Speed (MMax))	64%			651	
Blower Vibration (Blower Vibration (In/Sec))	0,01			0.02	-
Blower Current (Blower Current (Amps))	28.9	1	1	30.2	
Control Panel - Touchscreen - Flore Flow Data	(Press Back X2, Flore Flow Date)		-	30,0	
Flow Rate (scrm)	647			(030	
Total Flow (MMSCF)	651.05			655.31	
Flow Pressure (Inwc)	111				
Flow Temperature (f)	4.1 88		-	3.9	
Flow DP (Inwc)	2 7 7			100	
Control Panel - Touchscreen (Press Resettable)	2.72		-	7.56	
	101.00				
Resettable Total Flow (MMscr)	651.0513			655.3075	
Reset Date/Time (mm/dd/yy hh mm:ss)					
Control Panel - Touchscreen - Alarm History			N. S. C.		
Alarm History (Check box if no aterm)	×			≥	
Sas Handling Skid					
*Demister Inlet Pressure (Inwc)	-39.4			-39.7	
*Demister Outlet Pressure (Inwc)	-41.0			-41.0	
Demister DP (Inwc)	71.6			+/3	
Flame Arrester Inlet Pressure (Inwc)	+4.5			+4,9	=0.0
Flame Arrester Outlet Pressure (Inwc)	+4.1	1000		44.4	
Flame Arrester DP (Inwc)	+0.4			+0.4	
Fail-Close Valve Air Pressure (psi)	107				
Flore	10+			109	
Visible Emissions (Yes/No, II yes explain)	1 20		1		
Spiralator Position (Nopen)	50			No	
*Manual Louver 1 Position (Kopen)	50			56	-
Manual Louver 2 Position (Nopen)			-	50	
Other	50			50	
utner	×				
III Z OW			<u> </u>		
*Heat Trace OK (Check for Yes)					
*Heat Trace OK (Check for Yes) *Propane Tank Level OK (71 TZ (Check for Yes))	4 4			12 2	
Propane Tank Level OK (71 172 (Check for Yes))	Engine Plant	1 - Monitoring	7		
Propane Tank Level OK (73 72 (Check for Yes))	Engine Plant	1 - Monitoring	7	1455	
Propane Tank Level OK (73 72 (Check for Yes)) Firme (his mm) Technician (initials)	Engine Plant	1 - Monitoring	7	1455	
Propane Tank Level OK (73 72 (Check for Yes)) Firme (No mm) Fechnician (Initials) Engine Control Panel	Engine Plant	1 - Monitoring	7	1455	
Propane Tank Level OK (73 72 (Check for Yes)) Firme (bh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (Lwb) (Engine #4 #3)	Engine Plant	1 - Monitoring	9	1455	4
Propane Tank Level OK (73 72 (Check for Yes)) Firme (No mm) Fechnician (Initials) Engine Control Panel	Engine Plant	1 - Monitoring	3	1455 PB	1
Propane Tank Level OK (73 72 (Check for Yes)) Firme (bh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (Lwb) (Engine #4 #3)	Engine Plant	1 - Monitorin	3	1455	4
Propane Tank Level OK (71 TZ (Check for Yes)) Firme (hh mm) Fechnician (initials) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1)	Engine Plant 1620 08 698 685 697 715	1 - Monitorin	3	1455 AB 620 647 639 697	
Propane Tank Level OK (73 TZ (Check for Yas)) Firme (hk mm) Fechnician (Inklulu) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop	Engine Plant 1620 08 698 685 697 715	1 - Monitorin		690 647 699 697	1
Propane Tank Level OK (71 T2 (check for Yms)) Firme (hh mm) Fechnician (inklob) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Pflow Rate (scrm)	Engine Plant 1620 08 698 685 697 1715	1 - Monitorin		1459 160 647 699 697 70614 7.8 1662.9	1
Propane Tank Level OK (71 T2 (Check for Yes)) Firme (hh mm) Fechnician (Inklob) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F)	Engine Plant 1620 08 698 685 697 715	1 - Monitorin		690 647 699 697	1
Propane Tank Level OK (71 T2 (Check for Yas)) Firme (hh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Laptop Flow Total (MSCF) Flow Rate (SCFM) Discharge Gas Temperature (F) Engine Bay/Control Room Window	Engine Plant 1620 08 698 685 697 1715 7613294 11433 72.0	1 - Monitorin		1459 PB 620 647 659 697 70614 7.8 1662.9 81.8	
Propane Tank Level OK (71 T2 (Check for Yes)) Firme (hh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Loptop Pflow Total (MSCF) Pflow Rate (SCFM) Discharge Gas Temperature (F) Engine Bay/Control Room Window Inlet Gas Pressure (Inwc)	Engine Plant 1620 08 698 685 697 1715	1 - Monitorin		1459 160 647 699 697 70614 7.8 1662.9	1
Propane Tank Level OK (71 T2 (Check for Yes)) Firme (hh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Loptop Priow Total (MSCF) Priow Rate (SCFM) Oischarge Gas Temperature (F) Engine Bay/Control Room Window Inlet Gas Pressure (Inwc) Other	Engine Plant 1620	1 - Monitorin		1459 PB 690 647 699 697 70614 7.8 1662.9 81.8	A 4000-400-400
Propane Tank Level OK (71 T2 (Check for Yes)) Firme (hh mm) Fechnician (Inklols) Engine Control Panel Power Setpoint (kwh) (Engine #4 #3) Power Setpoint (kwh) (Engine #2 #1) Control Room - Loptop Pflow Total (MSCF) Pflow Rate (SCFM) Discharge Gas Temperature (F) Engine Bay/Control Room Window Inlet Gas Pressure (Inwc)	Engine Plant 1620 08 698 685 697 1715 7613294 11433 72.0	1 - Monitorin		1459 PB 620 647 659 697 70614 7.8 1662.9 81.8	

	-		DAILY L	OG	, ,	,
	Dhuh Buck]	Date 6/29	1/22
Temperature	85			1	Baro <u>2966</u>	
Reading Tim	e			,	Weather Ccour	4 4,00 200
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	- 28.9	177	27.6	27.2	2.2	43.0
FLARE 2	-32.1	506	35, 9 42.7	31.8	0.7	31.6
FLARE 3	-40.4	9/7		34.7	0.7	21.9
PLANT	-44.3 nlet Temp: 5	1110.Z	46.7	36.4	0, 6	16.3
Flame Temp Inlet Pres	Temp: Inlet 47 973 Panel 7 -32. [Flow P	res. 6.9	F Pilot Te		Recorde	or ON:
Totalizer Rea	ading: 8 3 9,	3869				
BLOWERS	: 301					
Runtime 43	(१८ Vibration <u>८</u>	Speed	<u>86</u> % Bearin	ig Temp IN 🥝	2_ Out_10 2	Amps: 12.8
	res. IN <u>- 31.7</u> C					
Flame Arres	ster: Pres. IN-8.	<u> </u>	DP +3.2 E	mis. Visible? Y	Y-(N) Spiral	. Pos. 50
Heat Trace C	K ? (Y)N	Propane Tank	Level OK? 1.0	ŷN 2. Ø]	N	
FLARE 3: T	emp: Inlet_69	Flow9	F Indicate	or Lights	Heating/Co	ooling
Flame Temp	1393 Panel 7	Temp 78	_F Pilot Te	mp <u>881</u>	Recorde	er ON:
	-46.4 Flow P		Recirc '	Valve Pos. 100	FA Temp_	97
Totalizer Rea	ading: <u>701.</u>	1854				
BLOWERS	301302					
Runtime 4485 Speed 65 % Vibration 0.02 Amps: 30.6						
Demister: Pres. IN <u>-40.1</u> OUT <u>-46.4</u> DP <u>+0.3</u> Louver 1 Pos. <u>50</u> 2 Pos. <u>50</u>						
Flame Arrester: Pres. IN +4.8 OUT +4.7 DP +0.1 Emis. Visible? Y Spiral. Pos. 56						
Heat Trace OK? ♥N Propane Tank Level OK? 1.♥N 2. �N						
PLANT:				5		
Power Setpo	ints:4 67	23	711	2 698	1 68	32
LFG Temp.	81.4 Inlet l	Pres 44	Flow F	Rate 1110,2	Totalizer	748280,0
Visible Emis	sions? Y®					
Remarks						

			I. FLARE 2.		LANI.	
Darconnal -	6/16/221	DAVL BUCK	DAILY L	OG	Date6 / /	6/20
	0 -					
Temperature_	17.				Baro <u>29.7</u>	
Reading Time	(600			_	Weather	L WIPOS, M. CER
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	-29.0	184	31.8	25.2	1.7	41.2
FLARE 2	- 36.7	506	41.1	30.0	0.6	28.3
FLARE 3	-48.4	1644	50.9	33.9	0-4	14.7
PLANT Gog In	46.3 let Temp: 5	1080.6	53.1	35.5	0.3	11.2
Flame Temp _ Inlet Pres	1148 Panel 7	res. <u>6.7</u>	F Indicate F Pilot Te Recirc	mp	Recorde	r ON:
BLOWERS:	301					
Runtime 43	Soc Vibration	5.23 Speed 9	36 % Bearin	g Temp IN 8	2 Out 110	Amps: <u>1</u> 3./
						2 Pos. 56
			DP <u>+ 3, 3</u> Er			
			- —— Level OK?1.Ć		=	
						oling
			F Pilot Te			
			Recirc \			
	ling: <u>688</u> .					
BLOWERS:	301302					
Runtime 429	8 Speed 6	5 % Vibratio	on 0.02	Amps: 30.	7	
						2 Pos. 50
						. Pos. <u>≤</u> ಶ
			Level OK ? 12			
PLANT:						,
Power Setpoin	nts : 476	03	683	2 695	1 70	3
LFG Temp	95.7 Inlet I	Pres46,	3 Flow R	ate (080, 6	Totalizer 7	31509-1
Visible Emissi						
Remarks						

	N		DAILY L	OG	, ,	/
	DAVE BUC	<u> </u>			Date $\frac{6}{14}$	
Temperature_					Baro <u>29.5</u>	3
Reading Time	16,30				Weather <u>L.C</u>	LOURS, M. WINA
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	-29.6	191	28.1	25.5	2.8	43.6
FLARE 2	-36.5	503 1017	38.8	369	0.6	28.8
FLARE 3 PLANT	-45.7	1070.7	47.3	34.9	0.4	17.4
	let Temp: <u>455</u>		71,0	<i>J ~· /</i>	075	11.0
	emp: Inlet <u>4</u> (1231 Panel 1					ooling
	36.5 Flow P			*	o'l FAT	
Totalizer Read	ding: 832. 2	-182				
BLOWERS:	301					
Runtime 43	459 Vibration (5.27 Speed	86 % Bearin	ig Temp IN 🙎	2 Out 119	Amps: 13.5
Demister: Pro	es. IN <u>-35.6</u> O	UT <u>- 39.4</u>	DP + 3.8	Louver	1 Pos. 50	2 Pos. 50
	t er: Pres. IN <u>† 7</u>					
Heat Trace Ol	K? 🚱N	Propane Tank	Level OK ? 1.0	ĎN 2. ὧ	N	
FLARE 3: Te	emp: Inlet <u>6</u> 9	Flow	F Indicate	or Lights	Heating/Co	oling
Flame Temp_	132Z Panel	Гетр <u>82</u>	_F Pilot Te	mp 399	Recorde	er ON:
	40.8 Flow P					
Totalizer Read	ding: 685.	7443				
BLOWERS:	301)302					
Runtime 42	Speed 6	52 % Vibrati	on 0.02	Amps: <u>30.0</u>		
Runtime 4260 Speed 652 % Vibration 0.02 Amps: 30.0 Demister: Pres. IN -40.4 OUT -396 DP +0.8 Louver 1 Pos. 50 2 Pos. 50						
Flame Arrester: Pres. IN <u>+4.9</u> OUT <u>+4.2</u> DP <u>+0.7</u> Emis. Visible? Y® Spiral. Pos. <u>50</u>						
Heat Trace OK ? 🕅N Propane Tank Level OK ? 1. 🕅N 2. 🗣N						
PLANT:						
Power Setpoin	nts:4_685	3	674	2 677	1 <i>[</i>	90
LFG Temp.	37.0 Inlet I	Pres 45	7 Flow R	Rate 1670.7	Totalizer 7	33592.4
Visible Emiss						
Remarks						

	N		DAILIL	UG	, 1.	1
Personnel	DAUK BUC	-K]	Date6/6/	122
Temperature_]	Baro	
Reading Time	1440			,	Weather M.	20004
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	-31.5	194	31.1	0.85	1.5	39.4
FLARE 2 FLARE 3	-38.6	1030	38.8	30.8	0.5	29.9
PLANT	-40.5	1050	51.1	36.3	0.3	10,3
	let Temp:5			- 0:2		
FLARE 2: Te	emp: Inlet3	2 Flow 1.08	F Indicate	or Lights X	Heating/Co	oling
						r ON:
						TRIV
	ding: 821.59					
BLOWERS:	301					
Runtime 432	나가 Vibration @	Speed &	子 % Bearin	ig Temp IN 7	9 Out 106	Amps: 13.4
Demister: Pre	es. IN <u>-37-0</u> O	UT <u>-39.6</u>	DP +2.6	Louver	1 Pos. <u>50</u>	2 Pos. 50
	er: Pres. IN <u>* 7</u>					. Pos
Heat Trace Of	K? (D-N,	Propane Tank	Level OK ? 1.(ĎN 2. Ø1	V	
	emp: Inlet <u>64</u>					
	1247 Panel 7					
	10.5 Flow P			Valve Pos. 16	6% FA 761	-r <u>98</u>
Totalizer Read	ding: 672.	5071				
BLOWERS:	301)302					
Runtime 4058 Speed 65 % Vibration 0.02 Amps: 30.3						
Demister: Pres. IN <u>-40.1</u> OUT <u>-40.9</u> DP <u>+0.8</u> Louver 1 Pos. <u>50</u> 2 Pos. <u>50</u>						
Flame Arrester: Pres. IN +4.7 OUT +4.3 DP +0.4 Emis. Visible? Y Spiral. Pos. 50						
Heat Trace OK? ØN Propane Tank Level OK? 1.ØN 2. ØN KO PLES LOF						
PLANT:						
Power Setpoir	nts:469	33	704	2 704	1_68	3
	92.0 Inlet I	res	Flow R	late / 650	Totalizer \(\overline{\pi}	22233.1
Visible Emiss	ions? Y🕥					
Remarks						

	- 4 . 4 . 0		DAILY L	OG		_
	DAVE BUCK	<u>. </u>]	Date <u>6/3/</u>	22
Temperature_	75]	Baro 29, (68
Reading Time	1250			,	Weather Acade	LOUDY, WEA
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	-30.6	196	28.2	26.6	1.8	43.4
FLARE 2	-38.7	497	37-6	30.9	0,5	31.1
FLARE 3	_40,7	1067	43.7	32.9	0.5	23.0
PLANT LOWEY Gas In	- 43, 9 let Temp: <i>5</i> 4,	loso O F	48.6	35.3	0.4	15.8
			F Indicate	or Liabte ➤	Heating/Co	alina X
	1766 Panel 7				_	er ON:
	30.6 Flow P	_	_	Valve Pos>		
	ling: _ \(\begin{array}{c} 24. \\ \end{array}		- Recife	varve ros	- PA 16	
BLOWERS:						
		0.25 Speed	37 % Bearin	g Temp IN 7	9 Out 105	Amps: 13.7
			DP <u>+2.3</u>			
			DP +3.0 Et			
			Level OK ? 1.			
			F Indicate			oling ×
			_F Pilot Te			
			Recirc \			
	ling: 668.1			-		
BLOWERS:	301-)-302					
Runtime 318	4 Speed 6	5_% Vibrati	on 0.02	Amps: 30.3		
Demister: Pre	es. IN <u>-32.5</u> C	UT _40.4	DP +0,9	Louver	1 Pos. 50	2 Pos. 50
Demister: Pres. IN -39.5 OUT -40.4 DP +0.9 Louver 1 Pos. 50 2 Pos. 50 Flame Arrester: Pres. IN +6.4 OUT +4.7 DP <0.7 Emis. Visible? Y Spiral. Pos. 50						
Heat Trace OK ? 🟵N Propane Tank Level OK ? 1. 🗗-N 2. 🜣N						
PLANT:						
Power Setpoir	nts:4682	3	642	2 684	1 71	6
LFG Temp	77.4 Inlet I	res. <u>-43</u> .	9 Flow R	late Loso	Totalizer 7	17492,8
Visible Emiss						
Remarks						

	A		DAILIL	UG	-1	/
Personnel _ D	AUK BULL				Date $5/31$	/22
Temperature_				,	Baro	
Reading Time	1545				Weather <u>Cw</u>	Up 4 MAIN
Location	Pressure	Flow	CH4	CO2	02	N2
	(in. w.c.)	(scfm)	(% - Vol)	(% -Vol)	(% - Vol)	(% - Vol)
LOWRY	<u>-3-0,4</u>	198	23,4	26,2	2.5	47.9
FLARE 2	~40,4	501	79.8	30.7	1.0	38.4
FLARE 3 PLANT	-40,8	905	47.8	35.3	0, 9	71.9
	et Temp: 5		7.8	38.4	0.7	13.7
FLARE 2: Te	mp: Inlet <u>49</u>	Flow Ga	F Indicate	or Lights <u>×</u>	Heating/Co	ooling \(\frac{\lambda}{\chi}\)
Timile Temp_	Taner.	temp	_1 11100 10	,mp	_ Kecolde	er ON:
			Recirc '			
Totalizer Read	ling: 8 22.	3000	PM IN	7001	DP	
DEO WERS.	201					
Runtime 431	Vibration	0, 2 7 Speed	% Bearin	ng Temp IN <u></u>	Z_Out_96	Amps: 13,3
Demister: Pre	s. IN <u>-39.2</u> O	UT -42.1	DP +2.9	Louver	1 Pos. <u>50</u>	2 Pos. <u>Γ6</u>
Flame Arrest	er: Pres. IN <u>+7</u>	.5 OUT +4.6	DP +2, 9 E1	mis. Visible? \	/{N Spiral	. Pos50
			Level OK? 1			
			F Indicate			
Flame Temp	1268 Panel 7	Temp <u>67</u>	_F Pilot Te	mp_ 350	Recorde	r ON: X
			Recirc '	Valve Pos i	ol FAT	rup 79
	ling: 663,	3732				
BLOWERS:	3012302					
			on 0.01			
Demister: Pres. IN <u>-40,6</u> OUT <u>-41,6</u> DP <u>+0,4</u> Louver 1 Pos. <u>50</u> 2 Pos. <u>50</u>						
Flame Arrester: Pres. IN +3.3 OUT +3.1 DP +0.7 Emis. Visible? Y Spiral. Pos. 50						
Heat Trace OF	(? (Ý)N	Propane Tank	Level OK? 1.(ŷN 2. Ø	N	
PLANT:						
Power Setpoin	ts:4677	ــــــــــــ3 <u></u>	690	2 680	169	6
LFG Temp.	76.4 Inlet I	Pres 40	, Z Flow R	late 1152.1	Totalizer	7951.9
Visible Emissi	ons? Y(N)				,	
Remarks						

APPENDIX D-3 ENGINES INLET METHANE AND HEAT CONTENT TEST FEBRUARY 16, 2022



Test Report

Waste Management of Colorado, Inc. 3500 South Gun Club Road Aurora, CO 80018

> Lowry / DADS Landfill Gas to Energy Facility Aurora, Colorado

Engines Inlet
Methane and Heat Content Test

Test Date: February 16, 2022

AST Project No. AAS-2022-0178

Prepared By
Alliance Source Testing, LLC
5530 Marshall Street
Arvada, CO 80002



CORPORATE OFFICE

255 Grant St. SE, Suite 600 Decatur, AL 35601 (256) 351-0121 SOURCE TESTING

stacktest.com

EMISSIONS MONITORING

alliance-em.com

ANALYTICAL SERVICES

allianceanalyticalservices.com



Regulatory Information

Regulatory Citation

40 CFR 60.18 – General Control Device Requirements

Source Information

Source Name
Fuel Gas Line

Target Parameters CH4, Heat Value

Contact Information

Test Location
Waste Management of
Colorado, Inc.
3500 S. Gun Club Road
Aurora, CO 80018

Patrick Mekled pmekled@wm.com (720) 876-2621 Test Company
Alliance Source Testing, LLC
5530 Marshall Street
Arvada, CO 80002

Project Manager Michael Pearson michael.pearson@stacktest.com (720) 457-9512

QA/QC Manager Heather Morgan heather.morgan@stacktest.com (256) 260-3972

Report Coordinator Alyssa Trujillo alyssa.trujillo@stacktest.com (801) 269-0550 Analytical Laboratory
Alliance Source Testing, LLC
5530 Marshall Street
Arvada, CO 80002
Michael Pearson
michael.pearson@stacktest.co
(720) 624-6986



Alliance Source Testing, LLC

Alliance Source Testing, LLC (AST) has completed the source testing as described in this report. Results apply only to the source(s) tested and operating condition(s) for the specific test date(s) and time(s) identified within this report. All results are intended to be considered in their entirety, and AST is not responsible for use of less than the complete test report without written consent. This report shall not be reproduced in full or in part without written approval from the customer.

To the best of my knowledge and abilities, all information, facts and test data are correct. Data presented in this report has been checked for completeness and is accurate, error-free and legible. Onsite testing was conducted in accordance with approved internal Standard Operating Procedures. Any deviations or problems are detailed in the relevant sections on the test report.


This report is only considered valid once an authorized representative of AST has signed in the space provided below; any other version is considered draft. This document was prepared in portable document format (.pdf) and contains pages as identified in the bottom footer of this document.

Michael Pearson Date



TABLE OF CONTENTS

1.0 Int	roduction	1-1
1.1	Project Team	1-1
2.0 Su	mmary of Results	2-1
3.0 Tes	sting Methodology	3-1
	LIST OF TABLES	
Table 1-1	Project Team	1-1
Table 2-1	Summary of Results	2-1
Table 3-1	Source Testing Methodology	3-1
	APPENDICES	
Appendix A	A Sample Calculations	
Appendix I	B Laboratory Data	





1.0 Introduction


Alliance Source Testing, LLC (AST) was retained by Waste Management of Colorado, Inc. (WMC) to conduct a series of performance tests at the DADS/Lowry Landfill located in Aurora, Colorado. The facility is subject to provisions of the 40 CFR 60.18 – General Control Device Requirements. Testing was conducted to determine the methane (CH₄) and heat content of the fuel line feeding the engines at the gas to energy facility.

1.1 Project Team

Personnel involved in this project are identified in the following table.

Table 1-1 Project Team

WMC Personnel	Patrick Mekled
AST Personnel	Michael Wildgruber





2.0 Summary of Results

AST conducted compliance testing at the WMC facility in Aurora, Colorado on February 16, 2022. At the fuel line to the generator engines, four gas samples were collected in Tedlar bags for off-site analyses of CH4 and heat content. The fuel gas samples were analyzed at the AST laboratory in Arvada, Colorado in accordance with ASTM D-1945. The heat content was calculated from values published in ASTM D3588.

Table 2-1 provides a summary of the emission testing results. Any difference between the summary results listed in the following table and the detailed results contained in appendices is due to rounding for presentation.

Table 2-1 Summary of Results

Run Number	Run 1	Run 2	Run 3	Run 4	Average	40 CED 840 10
Date	2/16/22	2/16/22	2/16/22	2/16/22		40 CFR §60.18 Performance Specifications
Heat Content						≥ 200 Btu/scf
Concentration, Btu/scf	573.01	562.67	563.19	572.29	567.79	§60.18(c)(3)(ii)
Methane Data						
Concentration, mol %	56.62	55.60	55.65	56.55	56.10	

Testing Methodology



3.0 Testing Methodology

The emission testing program was conducted in accordance with the test methods listed in Table 3-1.

Table 3-1
Source Testing Methodology

Parameter	U.S. EPA Reference Test Methods	Notes/Remarks
Methane Content	ASTM D1945	Constant Rate Sampling / Gas Chromatography Analysis
Heat Content	ASTM D3588	Published Values



Waste Management of Colorado Inc DADS / Lowry Landfill Lowry, Colorado Fuel Line Run 1 2/16/2022

F Factor Sample Calculations: Determination of Oxygen-Based F Factor (dry basis)

CH₄ - Fuel Gas Heat Content (Btu/scf)

= Gas Heat Content (Btu/scf) * Volume Percent (%)
100
= 1,010 * 56.62

CH₄ - Fuel Gas Heat Content (Btu/lb)

= Fuel Gas Heat Content (Btu/scf) * 379.4 Molecular Weight (gm/gm-mol)

= Results Below (All Included)

	Btu/scf	Btu/lb
Nitrogen	0.00	0.00
Oxygen	0.00	0.00
Carbon Monoxide	0.00	0.00
Hydrogen	0.98	13.8
Carbon Dioxide	0.00	0.00
Hydrogen Sulfide	0.02	0.30
Methane	571.9	8040.1
Acetylene	0.00	0.00
Ethylene	0.00	0.00
Ethane	0.00	0.00
Propadiene	0.00	0.00
Propylene	0.00	0.00
Propane	0.14	2.03
1,3-Butadiene	0.00	0.00
Butylenes	0.00	0.00
i-Butane	0.00	0.00
n-Butane	0.00	0.00
i-Pentane	0.00	0.00
n-Pentane	0.00	0.00
C6+	0.00	0.00
total	573.01	8056.28

Fuel Gas Heat Content (Btu/scf)

= 573.01

Fuel Gas Heat Content (Btu/lb)

8056.28

F-Factor (dscf/MMBtu)

= Fuel Gas Elemental Weight Percentages (FGEWP)

 Hydrogen [H]
 8.4840

 Carbon [C]
 41.3426

 Sulfur [S]
 0.004

 Nitrogen [N]
 6.3322

 Oxygen [O]
 43.8373

K values (K)

H 3.64 C 1.53 S 0.57 N 0.14

1000000 * H (FGEWP)* H (K) + C (FGEWP)* C (K) + S (FGEWP)* S (K) + N (FGEWP)* N (K) + O (FGEWP)* O (K)

Heat Content (Btu/lb)

= 1000000 * (8.4840 *3.64) + (41.3426 *1.53) + (0.004 *0.57) + (6.3322*0.14) + (43.8373 *-0.46) 8056.28

9,292

Waste Management of Colorado Inc DADS / Lowry Landfill Lowry, Colorado Fuel Line Run 1 2/1/2022

F Factor Sample Calculations: Determination of Oxygen-Based F Factor (dry basis)

Variables and Abbreviations

Btu/scf - British thermal units per standard cubic foot

Btu/lb - British thermal units per pound

dscf/MMBtu - dry standard cubic foot per million British thermal units

FGEWP - Fuel Gas Elemental Weight Percentages

gm/gm-mol - gram per gram-mole

K - K value

H - hydrogen

C - carbon

S - sulfur

N - nitrogen

O - oxygen





5530 Marshall Street Arvada, Colorado 80002 Phone: 303-420-5949 Fax: 303-420-5920

Certificate of Analysis Analysis By Gas Chromatography

Company Waste Management

Unit......DADS Landfill

Date Sampled...... 2/16/2022

Sample Name...... Bag #1

Sample Location...... Main Inlet at Gas to Energy Plant

Sample Pressure.......N/A (pump used)
Test Method...... ASTM D1945

Method of Analysis.... GC-TCD/FID
Instrument...... Agilent 7890 GC

Study Number..... AAS-2022-0178

Date Analyzed 2/17/22 8:57 AM

Container..... Tedlar Bag

C6+	Components	Normalized Mole%
Propane 0.0057 Propylene 0.0000 Isobutane 0.0000 Propadiene 0.0000 n-Butane 0.0000 1 - Butene 0.0000 Isobutylene 0.0000 trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Methylacetylene 0.0000	·	0.0000
Propylene 0.0000 Isobutane 0.0000 Propadiene 0.0000 n-Butane 0.0000 1 - Butene 0.0000 Isobutylene 0.0000 trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000		0.0057
Sobutane	·	0.0000
n-Butane 0.0000 1 - Butene 0.0000 Isobutylene 0.0000 trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Isobutane	0.0000
1 - Butene 0.0000 Isobutylene 0.0000 trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Propadiene	0.0000
1 - Butene 0.0000 Isobutylene 0.0000 trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	n-Butane	0.0000
trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Methylacetylene 0.0000 Neopentane 0.0000		0.0000
trans-2-Butene 0.0000 cis-2-Butene 0.0000 1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Isobutylene	0.0000
1,3-Butadiene 0.0000 Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	trans-2-Butene	0.0000
Isopentane 0.0000 n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	cis-2-Butene	0.0000
n-Pentane 0.0000 Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	1,3-Butadiene	0.0000
Helium 0.0000 Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Isopentane	0.0000
Hydrogen 0.3029 Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	n-Pentane	0.0000
Carbon Dioxide 36.2472 Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Helium	0.0000
Ethylene 0.0000 Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Hydrogen	0.3029
Ethane 0.0000 Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Carbon Dioxide	36.2472
Acetylene 0.0000 Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Ethylene	0.0000
Hydrogen Sulfide 0.0033 Oxygen 0.7214 Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Ethane	0.0000
Oxygen	Acetylene	0.0000
Nitrogen 6.0997 Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Hydrogen Sulfide	0.0033
Methane 56.6197 Carbon Monoxide 0.0000 Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Oxygen	0.7214
Carbon Monoxide	Nitrogen	6.0997
Cyclopropane 0.0000 Methylacetylene 0.0000 Neopentane 0.0000	Methane	56.6197
Methylacetylene	Carbon Monoxide	0.0000
Neopentane 0.0000	Cyclopropane	0.0000
aspect of the second se	Methylacetylene	0.0000
TOTAL 100.0000	Neopentane	0.0000
	TOTAL	100.0000

Molecular Weight (gm/gm-mol)	26.99
Heat Content (Btu/scf)	573.01
Heat Content (Btu/lb)	8,056
F Factor (dscf/MMBtu)	9,292



5530 Marshall Street Arvada, Colorado 80002 Phone: 303-420-5949 Fax: 303-420-5920

Certificate of Analysis
Analysis By Gas Chromatography

Company Waste Management

Unit......DADS Landfill

Date Sampled...... 2/16/2022

Sample Name...... Bag #2

Sample Location..... Main Inlet at Gas to Energy Plant

Sample Pressure.......N/A (pump used)
Test Method...... ASTM D1945

Method of Analysis.... GC-TCD/FID

Instrument..... Agilent 7890 GC

Study Number..... AAS-2022-0178

Date Analyzed 2/17/22 9:23 AM

Container..... Tedlar Bag

	Normalized
Components	Mole%
C6+	0.0000
Propane	0.0056
Propylene	0.0000
Isobutane	0.0000
Propadiene	0.0000
n-Butane	0.0000
1 - Butene	0.0000
Isobutylene	0.0000
trans-2-Butene	0.0000
cis-2-Butene	0.0000
1,3-Butadiene	0.0000
Isopentane	0.0000
n-Pentane	0.0000
Helium	0.0000
Hydrogen	0.2920
Carbon Dioxide	35.9845
Ethylene	0.0000
Ethane	0.0000
Acetylene	0.0000
Hydrogen Sulfide	0.0031
Oxygen	0.7927
Nitrogen	7.3217
Methane	55.6004
Carbon Monoxide	0.0000
Cyclopropane	0.0000
Methylacetylene	0.0000
Neopentane	0.0000
TOTAL	100.0000

Molecular Weight (gm/gm-mol)	27.07
Heat Content (Btu/scf)	562.67
Heat Content (Btu/lb)	7,886
F Factor (dscf/MMBtu)	9,318



5530 Marshall Street Arvada, Colorado 80002 Phone: 303-420-5949 Fax: 303-420-5920

Certificate of Analysis Analysis By Gas Chromatography

Company Waste Management

Unit......DADS Landfill

Date Sampled...... 2/16/2022

Sample Name..... Bag #3

Sample Location..... Main Inlet at Gas to Energy Plant

Sample Pressure.......N/A (pump used)
Test Method...... ASTM D1945

Method of Analysis.... GC-TCD/FID
Instrument...... Agilent 7890 GC

Study Number..... AAS-2022-0178

Date Analyzed 2/17/22 9:47 AM

Container..... Tedlar Bag

	Normalized Mole%
C6+	0.0000
Propane	0.0057
Propylene	0.0000
Isobutane	0.0000
Propadiene	0.0000
n-Butane	0.0000
1 - Butene	0.0000
Isobutylene	0.0000
trans-2-Butene	0.0000
cis-2-Butene	0.0000
1,3-Butadiene	0.0000
Isopentane	0.0000
n-Pentane	0.0000
Helium	0.0000
Hydrogen	0.2921
Carbon Dioxide	36.0506
Ethylene	0.0000
Ethane	0.0000
Acetylene	0.0000
Hydrogen Sulfide	0.0034
Oxygen	0.7700
Nitrogen	7.2270
Methane	55.6512
Carbon Monoxide	0.0000
Cyclopropane	0.0000
Methylacetylene	0.0000
Neopentane	0.0000
TOTAL	100.0000

Molecular Weight (gm/gm-mol)	27.07
Heat Content (Btu/scf)	563.19
Heat Content (Btu/lb)	7,892
F Factor (dscf/MMBtu)	9,318



5530 Marshall Street Arvada, Colorado 80002 Phone: 303-420-5949 Fax: 303-420-5920

Certificate of Analysis
Analysis By Gas Chromatography

Company Waste Management

Unit......DADS Landfill

Date Sampled...... 2/16/2022

Sample Name...... Bag #4

Sample Location..... Main Inlet at Gas to Energy Plant

Sample Pressure.......N/A (pump used)
Test Method...... ASTM D1945

Method of Analysis.... GC-TCD/FID
Instrument...... Agilent 7890 GC

Study Number..... AAS-2022-0178

Date Analyzed2/17/22 10:19 AM

Container..... Tedlar Bag

Components	Normalized Mole%
C6+	0.0000
Propane	0.0057
Propylene	0.0000
Isobutane	0.0000
Propadiene	0.0000
n-Butane	0.0000
1 - Butene	0.0000
Isobutylene	0.0000
trans-2-Butene	0.0000
cis-2-Butene	0.0000
1,3-Butadiene	0.0000
Isopentane	0.0000
n-Pentane	0.0000
Helium	0.0000
Hydrogen	0.3036
Carbon Dioxide	36.4244
Ethylene	0.0000
Ethane	0.0000
Acetylene	0.0000
Hydrogen Sulfide	0.0031
Oxygen	0.5332
Nitrogen	6.1816
Methane	56.5484
Carbon Monoxide	0.0000
Cyclopropane	0.0000
Methylacetylene	0.0000
Neopentane	0.0000
TOTAL	100.0000

Molecular Weight (gm/gm-mol)	27.01
Heat Content (Btu/scf)	572.29
Heat Content (Btu/lb)	8,037
F Factor (dscf/MMBtu)	9,310

APPENDIX D-4 LANDFILL GAS MONITORING PROBES (METHANE)

APPENDIX D-4

LFG GAS PROBE RESULTS (METHANE)

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Date	MP-1 Pressure (in. of H ₂ O) ^{a/}	MP-1 Methane (%) ^{b/}	MP-2 Pressure (in. of H ₂ O)	MP-2 Methane (%)	MP-3 Pressure (in. of H ₂ O)	MP-3 Methane (%)	MP-4 Pressure (in. of H ₂ O)	MP-4 Methane (%)	MP-5 Pressure (in. of H ₂ O)	MP-5 Methane (%)	MP-6B Pressure (in. of H ₂ O)	MP-6B Methane (%)	MP-7 Pressure (in. of H ₂ O)	MP-7 Methane (%)	MP-8 Pressure (in. of H ₂ O)	MP-8 Methane (%)	MP-8BH ^{c/} Pressure (in. of H ₂ O)	MP-8BH Methane (%)
3/4/2022	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	NA ^{d/}	NA
5/27/2022	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	NA	NA
	MP-9 Pressure (in. of H ₂ O)	MP-9 Methane (%)	MP-10 Pressure (in. of H ₂ O)	MP-10 Methane (%)	MP-11 Pressure (in. of H ₂ O)	MP-11 Methane (%)	MP-12 Pressure (in. of H ₂ O)	MP-12 Methane (%)	MP-13 Pressure (in. of H ₂ O)	MP-13 Methane (%)	MP-14 Pressure (in. of H ₂ O)	MP-14 Methane (%)	MP-15 Pressure (in. of H ₂ O)	MP-15 Methane (%)	MP-16 Pressure (in. of H ₂ O)	MP-16 Methane (%)	MP-17 Pressure (in. of H ₂ O)	MP-17 Methane (%)
3/4/2022	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
5/27/2022	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
3/4/2022	MP-18 Pressure (in. of H ₂ O) 0.00	MP-18 Methane (%) 0.00	MP-19 Pressure (in. of H ₂ O)	MP-19 Methane (%) 0.00	MP-20 Pressure (in. of H ₂ O)	MP-20 Methane (%) 0.00	MP-21 Pressure (in. of H ₂ O)	MP-21 Methane (%) 0.00									Barometric Pressure (Start) (in. of Hg) ^{e'} 29.83	Barometric Pressure (Finish) (in. of Hg) 29.74
5/27/2022	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00									30.05	30.02

 $_{a/}$ (in. of $\mathrm{H_{2}O}$) = Pressure measured in inches of water measurement taken in well casing before cap is removed.

b/ (%) = Percent of Methane measured

c/ MP-8BH is sampled if the water level was above the top of screen at MP-8. Six foot deep borehole probe (MP-8 BH) installed and sampled next to MP-8.

d/ NA = Not applicable

e/ (in. of Hg) = Barometric Pressure measured in inches of Mercury

APPENDIX E

COVER MONITORING FIELD INSPECTION AND MAINTENANCE REPORTS

APPENDIX E-1

SITE AND LANDFILL COVER INSPECTIONS

FIELD INSPECTION AND MAINTENANCE FORM

Inspector: Chris Carlson		Organization:	Parsons			
Date: <u>06/1/22</u>		Weather: <u>1.07</u>	7 inches of slow	and stea	dy rain 5	5/31/22 2 PM to 6/1/22 10 AM
Instructions: Complete checklist of visual eva tape and noted on the attached site plan. Estim sedimentation, settlement, animal burrows, etc.	ated mea	surements shall	be so noted. Atta	ach photo		
1. Visual Evaluation Items						
			CONDITION: (Check C	ne)	_
	Map		Not	Actio	n Requi	ired?
	<u>ID</u>	<u>Acceptable</u>	<u>Acceptable</u>	Yes	<u>No</u>	<u>REMARKS</u>
1) Covers						
a) Landfill Prism and Traffic Cap						
Vegetation		_ <u>X</u>			<u>X</u>	
Erosion		_ <u>X</u>			<u>X</u>	
Waste Breakthrough		X			X	

	Map		Not	Action	n Requi	red?
	<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
a) Landfill Prism and Traffic Cap (cor	nt'd)					
Settlement	_ <u>A</u> _	<u>X</u>			_ <u>X</u> _	Area appears nearly flat – no ponding.
Settlement	<u>B</u>	_ <u>X</u>			<u>X</u>	Area appears nearly flat – no ponding.
Settlement	_ <u>C</u> _	_ <u>X</u>			<u>X</u>	Area appears nearly flat – no ponding.
Settlement	D_	X			<u>X</u>	Area appears nearly flat – no ponding.
Settlement	_ <u>E</u> _	_ <u>X</u>			<u>X</u>	Area appears nearly flat – no ponding.
Settlement	<u>_</u> F_	<u>X</u> _			<u>X</u>	Area appears nearly flat – no ponding.
Settlement	<u>G</u>	X			<u>X</u>	Area appears nearly flat – no ponding.
Animal Burrows		_ <u>X</u>			<u>X</u>	
Other (litter, disposal)		<u>X</u> _			<u>X</u>	
Pooling or Ponding		_ <u>X</u>			<u>X</u>	Minor ponding on or near roads.

	Map		Not	Actio	n Requi	red?
	<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
b) SWRA Cover and NTES						
Vegetation		<u>X</u>			<u>X</u>	
Erosion		<u>X</u>			_ <u>X</u> _	
Waste Breakthrough		<u>X</u> _			<u>X</u>	
Settlement		<u>X</u>			<u>X</u>	
Animal Burrows		<u>X</u>			<u>X</u>	
Pooling or Ponding		_ <u>X</u>			_ <u>X</u> _	

	Map		Not	Actio	n Requi	red?
	<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
b) SWRA Cover and NTES (cont'd)						
Other (litter, disposal)		<u>X</u>			<u>X</u>	
c) FTPA Treatment Cell Area						
Vegetation		X			<u>X</u>	
Erosion		<u>X</u> _			<u>X</u>	
Waste Breakthrough		<u>X</u>			<u>X</u>	
Settlement		X			<u>X</u>	
Animal Burrows		<u>X</u>			_ <u>X</u> _	
Other (litter, disposal)		_ <u>X</u>			<u>X</u> _	
2) Integrity of Stormwater Conveyance Dite	ches					
a) Sediment Accumulation		_X			<u>X</u>	

	Map		Not	Actio	n Requi	red?
	<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
2) Integrity of Stormwater Conveyance Dite	ches (co	nt'd)				
b) Pooling or Ponding		_ <u>X</u> _			<u>X</u>	
c) Slope Integrity		_ <u>X</u>			<u>X</u>	
d) Erosion Protection		_ <u>X</u> _			<u>X</u>	
e) Obstruction of Culverts		<u>X</u>			<u>X</u>	
3) Condition of Traffic Cap/Perimeter Road	ds	<u>X</u>			<u>X</u> _	Minor ponding on or near roads.
4) Condition of Gates/Locks/Fences		<u>X</u>			<u>X</u>	


2. Specific Items (Write N.A. if not applicable) 1) Settlement Areas a. Map ID: A b. Area: -200 feet by -300 feet c. Depth: <u>NA</u> feet 2) Settlement Areas d. Map ID: _B e. Area: _~100 feet by _~150 feet f. Depth: _NA_ feet 3) Settlement Areas g. Map ID: <u>C</u> h. Area: ~150 feet by ~200 feet i. Depth: _NA_ feet 4) Settlement Areas j. Map ID: _D k. Area: <u>~150</u> feet by <u>~200</u> feet 1. Depth: <u>NA</u> feet 5) Settlement Areas m. Map ID: <u>E</u> n. Area: _~150 feet by _~200 feet o. Depth: <u>NA</u> feet 6) Settlement Areas p. Map ID: _F_ q. Area: <u>~200</u> feet by <u>~300</u> feet r. Depth: <u>NA</u> feet 7) Settlement Areas s. Map ID: <u>G</u>

	Area: Depth:	<u>~100</u> feet by <u>NA</u> feet	<u>~100</u> feet
8) P	onding or	Pooling	
	Map ID		
b		feet by	feet
c.		feet	
d			
e.		feet by	feet
f.	_	feet	
g			
h		feet by	feet
i.	Depth:	feet	
9) E	rosion		
	Map ID	: _NA_	
b	_		feet
c	Depth:	feet	
d	. Map ID		
e.		feet by	feet
f.		feet	
g			_
h		feet by	feet
i.	Depth:	feet	
10) V	Vaste Break	kthrough	
	Map ID		
b	_	feet by _	feet
c.		feet	
d	_		
e.		feet by	feet
f.	Depth:	feet	
g	. Map ID	: <u>NA</u> _	
h		feet by	feet
i.	Depth:	feet	

Areas A, B, C, D, E, F and G appears near flat but have no signs of ponding. Some of these areas received shallow fill and revegetated in 2020, currently adding more topsoil to some of these areas. Will continue to closely monitor this area for future signs of settling.

Vegetation in all areas is good, no major number of weeds observed.

Instructions: Complete checklist of visual evaluation items and then complete specific data items. Field measurements should be made with a cloth tape and noted on the attached site plan. Estimated measurements shall be so noted. Attach photographs or hand sketches of areas indicating erosion, sedimentation, settlement, animal burrows, etc. to further define conditions or problems.



June 2022 Cap and Drains Inspection Photo Documentation



Map ID A Looking South 6/1/22 (Near Flat Area of Concern – No Ponding. Topsoil staged to fill in a potentially low area)



Map ID A Looking Northwest 6/1/22 (Near Flat Area of Concern – Post shallow filling project. No Ponding)



Minor Ponding in Road South of Area A 6/1/22



Map ID G Looking South 6/1/22 (Near Flat Area of Concern – No Ponding)



Area B 6/1/22 (no ponding)



Area C 6/1/22 (post shallow filling and revegetation – no ponding)

June 2022 Cap and Drains Inspection Photo Documentation



Areas D, E and F 6/1/22 (no ponding)



Slope Drainage Ditch Near PM-11 6/1/22 (no erosion)

June 2022 Cap and Drains Inspection Photo Documentation



Eastern Surface Water Diversion Ditch Near PM-11 6/1/22 (no erosion)



Eastern Surface Water Diversion Ditch Near MW-51 Looking South 6/1/22

(No erosion, minor ponding on road)

June 2022 Cap and Drains Inspection Photo Documentation



Eastern Surface Water Diversion Ditch Near PM-15 Looking South 6/1/22 (no erosion)



Eastern Surface Water Diversion Ditch Near PM-15 Looking North 6/1/22 (no erosion)

June 2022 Cap and Drains Inspection Photo Documentation



Southwest Corner Surface Swale Water Near PM-5 Looking Southeast 6/1/22 (no erosion – or ponding)



Southern Traffic Cap Looking East 6/1/22 (minor ponding in road)

June 2022 Cap and Drains Inspection Photo Documentation



North Slope Drain Near PM-15 Area 6/1/22 (good condition)



North Slope Drain Looking West 6/1/22 (good condition)

June 2022 Cap and Drains Inspection Photo Documentation



Northwest Slope Drain Looking West 6/1/22 (good condition)



SWRA Cover Near South Pit Looking North 6/1/22 (good vegetation – no erosion)

June 2022 Cap and Drains Inspection Photo Documentation



SWRA Cover Near South Pit Looking South 6/1/22 (good vegetation – no erosion)



SWRA Cover Near North Pit Looking North 6/1/22 (good vegetation – no erosion)

June 2022 Cap and Drains Inspection Photo Documentation



SWRA Cover Near North Pit Looking North 6/1/22 (good vegetation – no erosion)

APPENDIX E-2 BUFFER ZONE INSPECTIONS

APPENDIX E-2.1 JANUARY 2022 BUFFER ZONE INSPECTION

Inspector: Chris Carlson	Organization: Parsons							
Date: <u>1/24/22</u>								
-	Estimated mea	asurements shall	l be so noted. A	ttach pho	otograph	measurements should be made with a cloth is or hand sketches of areas indicating fence problems.		
1. Visual Evaluation Items								
			CONDITION: (Check C	ne)	<u> </u>		
	Map		Not	Actio	n Requi	ired?		
	<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>		
1) E. ¼ Section 6								
a) Fencing / Security								
Locking Gates		<u>X</u>			<u>X</u>	- <u></u>		
Barbwire		<u>X</u>			<u>X</u>			
Braces		X			<u>X</u>			
Other (litter, disposal)		<u>X</u> _			<u>X</u>			

		Map		Not	Action	n Requi	red?
		<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	REMARKS
b) Ter	rain						
	Settlement		_ <u>X</u>			<u>X</u>	
	Animal Burrows		X			<u>X</u>	
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		_ <u>X</u>			<u>X</u>	
	Obstruction of Culverts		_X			<u>X</u>	
c) Veg	getation						
	Weeds		<u>X</u>			<u>X</u>	
	Ground Cover		<u>X</u>			<u>X</u>	

Sį	pecif	fic Items (Write N.A. if not applicable)
a)		ce / Secur Map ID: Area:	•
	•	Map ID: Area:	NA_ feet byfeet
))	Ter •	Map ID: Area:	feet byfeetfeet
			_ <u>NA</u> _ feet byfeet feet
:)		getation Map ID: Area:	_ <u>NA</u> feet byfeet
	•	Map ID: Area:	_ <u>NA</u> _ feet byfeet
		Map ID: Area:	_ <u>NA</u>

		<u>C</u>	CONDITION: (Check One)			
	Map		Not	Action	n Requi	red?
	<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	REMARKS
2) N. 1/2 Section 7						
a) Fencing / Security						
Locking Gates	s	_ <u>X</u>			_ <u>X</u> _	
Barbwire		<u>X</u>			<u>X</u>	
Braces		_X			_ <u>X</u> _	
Other (litter, d	lisposal)	_X			_ <u>X</u> _	

		Map		Not	Action	n Requi	red?
		<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
b) Ter	rain						
	Settlement		<u>X</u> _			<u>X</u>	
	Animal Burrows		<u>X</u>			<u>X</u>	Approximately 4 Active Burrows
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		X			<u>X</u>	
	Obstruction of Culverts		<u>X</u>			<u>X</u>	
c) Vegetation							
	Weeds		<u>X</u>			<u>X</u>	
	Ground Cover		<u>X</u>			<u>X</u>	

S	<u>pecif</u>	fic Items (Write	N.A. if not	applicable)
a)	Fen •	1.1up 12.	_NA	feet by	feet
	•	Map ID: Area:		feet by	feet
	•	Map ID: Area:		_ _feet by	feet
	•	Map ID: Area:		feet by	feet
b)	Ter •	Map ID: Area:		_feet by	feet
c)	Veg •	r		_ _feet by	feet

		CONDIT	_		
	Map	Not	Actio	n Requi	red?
	<u>ID</u> <u>Acc</u>	eptable Accer	otable Yes	<u>No</u>	<u>REMARKS</u>
3) E. ½ Section 1 a) Fencing / Security					
Locking Gates	_ <u>A</u>	_ <u>X</u> _	_ <u>X</u> _		Gate found unlocked. Relocked today
Barbwire	<u>></u>	<u> </u>		<u>X</u>	
Braces	<u>></u>	<u> </u>		<u>X</u>	
Other (litter, disposal)	<u>></u>	<u> </u>		<u>X</u>	

		Map		Not	Action	n Requi	red?
		<u>ID</u>	<u>Acceptable</u>	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
b) Ter	rain						
	Settlement		_ <u>X</u> _			<u>X</u>	
	Animal Burrows		<u>X</u>			<u>X</u>	Approximately 13 Active Burrows
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		X			<u>X</u>	
	Obstruction of Culverts		<u>X</u>			<u>X</u>	
c) Vegetation							
	Weeds		<u>X</u>			<u>X</u>	
	Ground Cover		<u>X</u>			<u>X</u>	

	<i>ecific I</i> Fence			N.A. if no	t ap	plicab	ole)				
	• An		NA G	Sate found	unl	ocked	. Reloc	cked d	uring i	inspect	ion.
		ap ID: ·ea:		_ _linier feet	-						
b)	ArDe	ap ID:		_feet by _feet		_feet					
	• An			_feet by		_feet					
c)		ap ID:		_ _feet by		_feet					
		ap ID: ea:		feet by		_feet					

	Map		Not	Actio	n Requi	ired?
	<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
4) E. ½ Section 36						
a) Fencing / Security						
Locking Gates		<u>X</u>			<u>X</u> _	
Barbwire		<u>X</u>			<u>X</u> _	
Braces		X			_X_	
Other (litter, disposal)		_X_			_X_	

		Map		Not	Action Requir		red?
		<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
b) Terr	rain						
	Settlement		_ <u>X</u>			<u>X</u>	
	Animal Burrows		_X_			<u>X</u>	Approximately 20 Active Burrows
	Erosion		_ <u>X</u> _			<u>X</u>	
	Sediment Accumulation		_ <u>X</u> _			<u>X</u>	
	Obstruction of Culverts		_X_			<u>X</u>	
c) Veg	etation						
	Weeds		_ <u>X</u> _			<u>X</u>	
	Ground Cover		_X_			<u>X</u>	

<u>Specific Items</u> (Write N.A. if not applicable)

- a) Fence / Security
 - Map ID: NA
 - Area: **NA** linier feet
 - Map ID: <u>NA</u>
 - Area: <u>NA</u> linier feet
 - Map ID: <u>NA</u>
 - Area: <u>NA</u> linier feet
 - Map ID: NA
 - Area: <u>NA</u> linier feet
 - Map ID: **NA**
 - Area: <u>NA</u> linier feet
- b) Terrain
 - Map ID: <u>NA</u>
 - Area: <u>NA</u> feet by <u>NA</u> feet
 - Depth: <u>NA</u> feet
 - Map ID: <u>NA</u>
 - Area: <u>NA</u> feet by <u>NA</u> feet
 - Depth: <u>NA</u> feet
- c) Vegetation
 - Map ID: <u>NA</u>
 - Area: ____feet by ____feet

Signature of Inspector:	
Attachments	
X Yes No	
If yes, list attachments:	
Jan 2022 Buffer Property Map.pdf	
Buffer Zone Pictures (1-24-22).pdf	

Actions taken: Gate found unlocked on Section 1. Prairie dogs to be addressed with mitigation scheduled for this Spring.

Date: __1/24/22_



E ½ Section 1 (MAP ID A) Gate Found Unlocked. Locked 1/24/22



E ½ Section 1 Approximately 13 Active Prairie Dog Burrows Present




N ½ Section 7 Approximately 10 Active Prairie Dog Burrows Present



E ½ Section 36 Active Prairie Dog Burrows



E ½ Section 36 Active Prairie Dog Burrows



Lowry Trust Buffer Property

Active Prairie Dog Burrows

Weeds

Buffer Zone Inspection

APPENDIX E-2.2

APRIL 2022 BUFFER ZONE INSPECTION

Inspector: Chris Carlson	Organization: Parsons							
Date: <u>4/14/22</u>								
-	stimated mea	asurements shall	be so noted. A	ttach pho	otograph	measurements should be made with a cloth is or hand sketches of areas indicating fence problems.		
1. Visual Evaluation Items								
	CONDITION: (Check One)							
	Map		Not	Actio	n Requi	ired?		
	<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>		
1) E. 1/4 Section 6								
a) Fencing / Security								
Locking Gates		<u>X</u>			<u>X</u>			
Barbwire		<u>X</u>			<u>X</u>			
Braces		X			<u>X</u>			
Other (litter, disposal)		<u>X</u>			<u>X</u>			

		Map		Not	Action	ı Requii	red?
		<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	REMARKS
b) Ter	rain						
	Settlement		_ <u>X</u>			<u>X</u>	
	Animal Burrows		_X_			<u>X</u>	
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		_ <u>X</u> _			<u>X</u>	
	Obstruction of Culverts		_X_			<u>X</u>	
c) Veg	getation						
	Weeds		_ <u>X</u>			<u>X</u>	
	Ground Cover		_X_			<u>X</u>	

Sį	<u>pecif</u>	fic Items (Write	N.A.	if not a	pplicable)
a)		nce / Secur Map ID: Area:	_NA	- _feet	by	feet
	•	Map ID: Area:			by	feet
)	Ter •	Map ID: Area:		_feet	by	_feet
	•	Map ID: Area: Depth:		_feet	by	feet
:)	•	getation Map ID: Area:			by	feet
	•	Map ID: Area:			by	feet
		Map ID: Area:			by	feet

	CONDITION: (Check One)						
	Map		Not	Action Requi		red?	
	<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>	
2) N. ½ Section 7							
a) Fencing / Security							
Locking Gates		<u>X</u>			<u>X</u>		
Barbwire		<u>X</u>			<u>X</u>		
Braces		_ <u>X</u>			<u>X</u> _		
Other (litter, disposal)		<u>X</u>			<u>X</u>		

		Map		Not	Action Requir		red?
		<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
b) Ter	rain						
	Settlement		<u>X</u> _			<u>X</u>	
	Animal Burrows		<u>X</u>			<u>X</u>	Approximately 4 Active Burrows
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		X			<u>X</u>	
	Obstruction of Culverts		<u>X</u>			<u>X</u>	
c) Veg	getation						
	Weeds		<u>X</u>			<u>X</u>	
	Ground Cover		<u>X</u>			<u>X</u>	

Sį	<u>pecif</u>	fic Items (Write	N.A. if n	ot ap	plicable)
a)	•	ce / Secur Map ID: Area:	_ <u>NA</u> _			_feet
	•	Map ID: Area:				_feet
	•	Map ID: Area:				_feet
	•	Map ID: Area:				_feet
o)	•	rain Map ID: Area: Depth:		_feet by _		_feet
c)	_	getation Map ID: Area:		- _feet by _		_feet

		CONDITION: (
	Map	Not	Action	n Requi	red?
	ID Accepta	<u>Acceptable</u>	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
3) E. ½ Section 1 a) Fencing / Security					
Locking Gates	<u>X</u>			<u>X</u> _	
Barbwire	_ <u>A</u>	_ <u>X</u> _	<u>X</u>		Approx. 30 LF of barbwire damaged
Braces	<u>X</u>			<u>X</u> _	
Other (litter, disposal)	X			<u>X</u>	

		Map		Not	Action Requir		red?
		<u>ID</u>	Acceptable	<u>Acceptable</u>	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>
b) Ter	rain						
	Settlement		_ <u>X</u> _			<u>X</u>	
	Animal Burrows		_ <u>X</u>			<u>X</u>	Approximately 13 Active Burrows
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		_X			<u>X</u>	
	Obstruction of Culverts		<u>X</u>			<u>X</u>	
c) Veg	getation						
	Weeds		<u>X</u>			<u>X</u>	
	Ground Cover		_ <u>X</u>			<u>X</u>	

Specific Items (Write N.A. if not applicable)
a) Fence / Security
 Map ID: A Area: 30 linier feet (Barbwire fencing along west side of S Gun Club Rd damaged. Repaired during inspection)
 Map ID: _NA_ Area:linier feet
b) Terrain
• Map ID: <u>NA</u>
Area:feet byfeetDepth:feet
• Map ID: <u>NA</u> • Area feet by feet
Area:feet byfeetDepth:feet
c) Vegetation
 Map ID: _NA_ Area:feet byfeet
• Map ID: <u>NA</u>
• Area:feet byfeet


	CONDITION: (Check One)						
	Map		Not	Actio	n Requi	red?	
	<u>ID</u>	Acceptable	Acceptable	<u>Yes</u>	<u>No</u>	<u>REMARKS</u>	
4) E. ½ Section 36							
a) Fencing / Security							
Locking Gates	<u>B</u>		<u>X</u>	_ <u>X</u> _		Gate found unlocked. Relocked today.	
Barbwire		_ <u>X</u>			<u>X</u>		
Braces		_X			<u>X</u>		
Other (litter, disposal)		_ <u>X</u>			<u>X</u> _		

		Map		Not	Action	n Requi	red?
		<u>ID</u>	Acceptable	Acceptable	Yes	<u>No</u>	<u>REMARKS</u>
b) Ter	rain						
	Settlement		_ <u>X</u> _			<u>X</u>	
	Animal Burrows		X			<u>X</u>	Approximately 20 Active Burrows
	Erosion		_ <u>X</u>			<u>X</u>	
	Sediment Accumulation		<u>X</u>			<u>X</u>	
	Obstruction of Culverts		<u>X</u>			<u>X</u>	
c) Veg	getation						
	Weeds		_ <u>X</u>			<u>X</u>	
	Ground Cover		_X_			<u>X</u>	

<u>Specific Items</u> (Write N.A. if not applicable)

- a) Fence / Security
 - Map ID: **B**
 - Area: <u>NA</u> Gate found unlocked. Relocked during inspection.
 - Map ID: <u>**NA**</u>
 - Area: <u>NA</u> linier feet
 - Map ID: <u>NA</u>
 - Area: **NA** linier feet
 - Map ID: NA
 - Area: **NA** linier feet
 - Map ID: **NA**
 - Area: <u>NA</u> linier feet
- b) Terrain
 - Map ID: _NA_
 - Area: <u>NA</u> feet by <u>NA</u> feet
 - Depth: <u>NA</u> feet
 - Map ID: <u>NA</u>
 - Area: <u>NA</u> feet by <u>NA</u> feet
 - Depth: <u>NA</u> feet
- c) Vegetation
 - Map ID: <u>NA</u>
 - Area: ____feet by ____feet

Signature of Inspector:
Attachments
If yes, list attachments:
April 2022 Buffer Property Map.pdf
Buffer Zone Pictures (4-14-22).pdf
Date:
Actions taken: Fence damaged on Section 1 on west side of S Gun Club Road found and repaired during Inspection. Prairie dogs to be addressed with mitigation scheduled for later this month.



 Active Prairie Dog Burrows Weeds

Buffer Zone Inspection



E ½ Section 1 (MAP ID A) Approximately 30 LF of Barbwire Fence Found Damaged



E ½ Section 1 (MAP ID A) Approximately 30 LF of Fencing Post 4/14/22 Repairs



N ½ Section 7 Approximately 10 Active Prairie Dog Burrows Present



N ½ Section 7 Approximately 10 Active Prairie Dog Burrows Present



E ¼ Section 6 Fencing Good and No Active Prairie Dog Burrows



E ¼ Section 6 Fencing Good and No Active Prairie Dog Burrows



E ½ Section 36 Active Prairie Dog Burrows



E ½ Section 36 Active Prairie Dog Burrows



E ½ Section 36 (MAP ID B) Gate Found Unlocked



E ½ Section 36 (MAP ID B) Gate Found Unlocked. Locked 4/14/22

APPENDIX F

ANALYTICAL DATA PACKAGES, DATA VALIDATION REPORTS, AND DATA QUALITY ASSESSMENT

APPENDIX F-1 SAMPLE LOCATION CROSS REFERENCE TABLE

GW ^{b/} - Compliance/Effectiveness	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
ow - Compilance/Effectiveness	B-314	4/13/2022	280-160946-1	EUROFINS	NR
GW - Compliance/Effectiveness	B-314	4/13/2022	A221519	PACE	NR
GW - Molybdenum Investigation	B-326-UD	2/8/2022	280-158480-1	EUROFINS	NR
GW - North End Monitoring	B-326-UD	2/8/2022	A220605	PACE	NR
GW - Molybdenum Investigation	B-326-UD	4/14/2022	280-161015-1	EUROFINS	X
GW - North End Monitoring	B-326-UD	4/14/2022	A221521	PACE	NR
GW - Molybdenum Investigation	B-326-WD	2/8/2022	280-158480-1	EUROFINS	NR
GW - North End Monitoring	B-326-WD	2/8/2022	A220605	PACE	NR
GW - Molybdenum Investigation	B-326-WD	4/14/2022	280-161009-1	EUROFINS	NR
GW - North End Monitoring	B-326-WD	4/14/2022	A221521	PACE	NR
GW - Compliance/Effectiveness	BM-11X-100N	5/18/2022	280-162481-1	EUROFINS	NR
GW - Compliance/Effectiveness	BM-11X-100N	5/18/2022	A222009	PACE	NR
GW - Compliance/Effectiveness	BM-11X-100N	5/18/2022	280-162481-1	EUROFINS	NR
GW - Compliance/Effectiveness	BM-11X-100S	5/18/2022	A222009	PACE	NR
GW - Compliance	BM-15E2	4/26/2022	280-161502-1	EUROFINS	NR
GW - Compliance	BM-15E2	4/26/2022	A221715	PACE	NR
GW - Compliance/Effectiveness	BM-15N6	4/25/2022	280-161502-1	EUROFINS	NR NR
GW - Compliance/Effectiveness					
Gw - Comphance/Effectiveness	BM-15N6 EARLY WARNING	4/25/2022	A221715	PACE	NR
WTP ^{c/} - Early Warning		4/4/2022	200 160552 1	ELIDOEDIC	NTD.
wir - Early warning	INFLUENT EARLY WARNING	4/4/2022	280-160553-1	EUROFINS	NR
WED E 1 W		4/5/2022	22 04020	EBS ^{d/}	37
WTP - Early Warning	INFLUENT	4/5/2022	22-04030		X
GW - Compliance	GW-106	4/18/2022	280-161157-1	EUROFINS	X
GW - Compliance	GW-106	4/18/2022	A221601	PACE	X
GW - Effectiveness	MNA-01	5/19/2022	280-162546-1	EUROFINS	NR
GW - Effectiveness	MNA-03	5/19/2022	280-162546-1	EUROFINS	NR
WTP - Compliance	MP-001	1/4/2022	22-01010	EBS	X
WTP - Compliance	MP-001	1/4/2022	280-157419-1	EUROFINS	X
WTP - Compliance	MP-001	2/2/2022	280-158347-1	EUROFINS	X
WTP - Compliance	MP-001	2/2/2022	280-158357-1	EUROFINS	X
WTP - Compliance	MP-001	3/2/2022	280-159255-1	EUROFINS	X
WTP - Compliance	MP-001	3/2/2022	280-159257-1	EUROFINS	X
WTP - Compliance	MP-001	4/5/2022	22-04030	EBS	X
WTP - Compliance	MP-001	4/5/2022	280-160539-1	EUROFINS	X
WTP - Compliance	MP-001	4/5/2022	280-160556-1	EUROFINS	X
WTP - Compliance	MP-001	5/3/2022	280-161798-1	EUROFINS	X
WTP - Compliance	MP-001	6/7/2022	280-163136-1	EUROFINS	X
WTP - Compliance	MP-001_010322_1200	1/3/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_010322_1600	1/3/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_010322_2000	1/3/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_010422_0000	1/4/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_010422_0400	1/4/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_010422_0800	1/4/2022	280-157420-1	EUROFINS	X
WTP - Compliance	MP-001_020122_1200	2/1/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020122_1200	2/1/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_020122_1600	2/1/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020122_1600	2/1/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_020122_2000	2/1/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020122_2000	2/1/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0000	2/2/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0000	2/2/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0400	2/2/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0400	2/2/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0800	2/2/2022	280-158345-1	EUROFINS	X
WTP - Compliance	MP-001_020222_0800	2/2/2022	280-158360-1	EUROFINS	X
WTP - Compliance	MP-001_030122_1200	3/1/2022	280-159263-1	EUROFINS	X
WTP - Compliance	MP-001 030122 1600	3/1/2022	280-159263-1	EUROFINS	X
W II - Comphance			i	1	i)

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Compliance	MP-001_030222_0000	3/2/2022	280-159263-1	EUROFINS	X
WTP - Compliance	MP-001_030222_0400	3/2/2022	280-159263-1	EUROFINS	X
WTP - Compliance	MP-001_030222_0800	3/2/2022	280-159263-1	EUROFINS	X
WTP - Compliance	MP-001_040422_1200	4/4/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001_040422_1200	4/4/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001_040422_1600	4/4/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001 040422 1600	4/4/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001_040422_2000	4/4/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001_040422_2000	4/4/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001_040422-1200	4/4/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001_040422-1600	4/4/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001 040422-2000	4/4/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001 040522 0000	4/5/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001 040522 0000	4/5/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001 040522 0400	4/5/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001 040522 0400	4/5/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001 040522 0800	4/5/2022	280-160527-1	EUROFINS	X
WTP - Compliance	MP-001 040522 0800	4/5/2022	280-160533-1	EUROFINS	NR
WTP - Compliance	MP-001 040522-0000	4/5/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001 040522-0400	4/5/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001 040522-0800	4/5/2022	280-160529-1	EUROFINS	X
WTP - Compliance	MP-001 050222 1200	5/2/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050222 1600	5/2/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050222 2000	5/2/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050322 0000	5/3/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050322 0400	5/3/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050322 0800	5/3/2022	280-161802-1	EUROFINS	X
WTP - Compliance	MP-001 050922 1200	5/9/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 050922 1600	5/9/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 050922 2000	5/9/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 051022 0000	5/10/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 051022 0400	5/10/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 051022 0800	5/10/2022	280-162140-1	EUROFINS	X
WTP - Compliance	MP-001 060622 1200	6/6/2022	280-163140-1	EUROFINS	X
WTP - Compliance	MP-001 060622 1600	6/6/2022	280-163140-1	EUROFINS	X
WTP - Compliance	MP-001 060622 2000	6/6/2022	280-163140-1	EUROFINS	X
WTP - Compliance	MP-001 060722 0000	6/7/2022	280-163140-1	EUROFINS	X
WTP - Compliance	MP-001 060722 0400	6/7/2022	280-163140-1	EUROFINS	X
WTP - Compliance	MP-001 060722 0800	6/7/2022	280-163140-1	EUROFINS	X
GW - North End Monitoring	MW05-WD	3/1/2022	A220918	PACE	NR
GW - North End Monitoring	MW102-WD	1/24/2022	A220403	PACE	NR
GW - North End Monitoring	MW102-WD	4/28/2022	A221718	PACE	NR
GW - North End Monitoring	MW103-WD	2/7/2022	A220605	PACE	NR
GW - North End Monitoring	MW103-WD	5/9/2022	A221901	PACE	NR
GW - Compliance	MW105-WD	4/20/2022	280-161274-1	EUROFINS	X
GW - Compliance	MW105-WD	4/20/2022	A221608	PACE	X
GW - Compliance	MW108-WD	4/21/2022	280-161328-1	EUROFINS	NR
GW - Compliance	MW108-WD	4/21/2022	A221612	PACE	NR
GW - North End Monitoring	MW113-EW-1	1/25/2022	280-158091-1	EUROFINS	NR
GW - North End Monitoring	MW113-EW-1	1/25/2022	A220404	PACE	X
GW - North End Monitoring	MW113-EW-1	4/19/2022	280-161199-1	EUROFINS	NR
GW - North End Monitoring	MW113-EW-1	4/19/2022	A221603	PACE	NR
GW - Molybdenum Investigation	MW113-UD	1/25/2022	280-158098-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-UD	1/25/2022	280-158098-1	EUROFINS	NR
GW - North End Monitoring	MW113-UD	1/25/2022	A220404	PACE	X
GW - Molybdenum Investigation	MW113-UD	2/8/2022	280-158481-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-UD	3/8/2022	280-159517-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-UD	4/5/2022	280-160555-1	EUROFINS	NR
	<u> </u>				- 122

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
GW - Molybdenum Investigation	MW113-UD	5/17/2022	280-162449-1	EUROFINS	NR
GW - North End Monitoring	MW113-UD	5/17/2022	A222004	PACE	NR
GW - Molybdenum Investigation	MW113-UD	6/15/2022	280-163656-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	1/11/2022	280-157594-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	1/25/2022	280-158098-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	2/8/2022	280-158481-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	2/22/2022	280-158989-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	3/8/2022	280-159517-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	3/22/2022	280-160028-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	4/5/2022	280-160555-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	4/19/2022	280-161200-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	5/3/2022	280-161809-1	EUROFINS	NR
GW - Investigation	MW113-WD	5/3/2022	A221815	PACE	NR
GW - Molybdenum Investigation	MW113-WD	5/17/2022	280-162449-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	6/7/2022	280-163135-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	6/15/2022	280-163449-1	EUROFINS	NR
GW - Molybdenum Investigation	MW113-WD	6/29/2022	280-163904-1	EUROFINS	NR
GW - North End Monitoring	MW114-WD	1/20/2022	A220309	PACE	NR
GW - North End Monitoring	MW114-WD	5/9/2022	A221901	PACE	NR
GW - North End Monitoring	MW117-WD	1/20/2022	A220309	PACE	NR
GW - North End Monitoring	MW117-WD	5/9/2022	A221901	PACE	NR
GW - North End Monitoring	MW118-WD	1/20/2022	A220309	PACE	NR
GW - North End Monitoring	MW118-WD	5/9/2022	A221901	PACE	NR
GW - North End Monitoring	MW121-WDR	1/26/2022	A220406	PACE	NR
GW - North End Monitoring	MW122-WDR	1/26/2022	A220406	PACE	NR
GW - North End Monitoring	MW123-WD	1/26/2022	A220406	PACE	NR
GW - North End Monitoring	MW124-WD	1/27/2022	A220408	PACE	NR
GW - North End Monitoring	MW125-WD	1/27/2022	A220408	PACE	NR
GW - North End Monitoring	MW129-WD	2/28/2022	A220911	PACE	NR
GW - North End Monitoring	MW132-WD	1/31/2022	A220501	PACE	NR
GW - North End Monitoring	MW132-WD	5/10/2022	A221907	PACE	NR
GW - North End Monitoring	MW135-WD	2/23/2022	A220901	PACE	X
GW - North End Monitoring	MW141-WD	2/15/2022	A220705	PACE	NR
GW - North End Monitoring	MW142-WD	2/23/2022	A220911	PACE	NR
GW - North End Monitoring	MW144-WD	2/15/2022	A220705	PACE	NR
GW - North End Monitoring	MW151-WD	1/31/2022	A220501	PACE	NR
GW - North End Monitoring	MW151-WD	5/16/2022	A222004	PACE	NR
GW - North End Monitoring	MW153-EW-1	1/27/2022	A220408	PACE	NR
GW - North End Monitoring	MW153-EW-1	4/27/2022	A221715	PACE	NR
GW - North End Monitoring	MW154-EW-1	1/27/2022	A220408	PACE	NR
GW - North End Monitoring	MW154-EW-1	4/28/2022	A221718	PACE	NR
GW - North End Monitoring	MW155-EW-1	1/31/2022	A220501	PACE	NR
GW - North End Monitoring	MW155-EW-1	5/2/2022	A221815	PACE	NR
GW - North End Monitoring	MW156-EW-1	2/9/2022	A220612	PACE	NR
GW - North End Monitoring	MW156-EW-1	5/2/2022	A221815	PACE	NR
GW - North End Monitoring	MW156-WD	2/10/2022	A220612	PACE	NR
GW - North End Monitoring	MW156-WD	5/16/2022	A222004	PACE	NR
GW - North End Monitoring	MW157-WD	2/10/2022	A220612	PACE	NR
GW - North End Monitoring	MW157-WD	5/16/2022	A222004	PACE	NR
GW - North End Monitoring	MW160-WD	1/31/2022	A220501	PACE	NR
GW - North End Monitoring	MW160-WD	4/26/2022	A221715	PACE	NR
GW - RAWP ^{e/} /MW77 Response					
Action/Molybdenum Investigation	MW170-EW-1	1/25/2022	280-158092-1	EUROFINS	X
GW - RAWP/MW77 Response Action	MW170-EW-1	1/25/2022	A220404	PACE	X
Action/Molybdenum Investigation	MW170-EW-1	5/10/2022	280-162131-1	EUROFINS	NR
GW - RAWP/MW77 Response Action	MW170-EW-1	5/10/2022	A221907	PACE	NR
GW - North End Monitoring	MW176-DEN	2/15/2022	A220705	PACE	NR
GW - Molybdenum Investigation	MW179-UDEN	3/1/2022	280-159261-1	EUROFINS	X

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
GW - North End Monitoring	MW179-UDEN	3/1/2022	A220918	PACE	NR
GW - Compliance	MW23-UPPER-C	4/20/2022	280-161275-1	EUROFINS	NR
GW - Compliance	MW23-UPPER-C	4/20/2022	A221608	PACE	X
GW - Compliance	MW36-WDR	5/10/2022	280-162129-1	EUROFINS	NR
GW - Compliance	MW36-WDR	5/10/2022	A221907	PACE	NR
GW - MW38 Source Control	MW38-1028N-256E	4/27/2022	280-161561-1	EUROFINS	NR
GW - MW38 Source Control	MW38-1028N-256E	4/27/2022	A221715	PACE	NR
GW - MW38 Source Control	MW38-170S-140W	4/27/2022	280-161561-1	EUROFINS	NR
GW - MW38 Source Control	MW38-170S-140W	4/27/2022	A221715	PACE	NR
GW - MW38 Source Control	MW38-825S-445E	4/27/2022	280-161561-1	EUROFINS	NR
GW - MW38 Source Control	MW38-825S-445E	4/27/2022	A221715	PACE	NR
GW - Compliance	MW38-830N-230E	4/13/2022	280-160946-1	EUROFINS	NR
GW - Compliance	MW38-830N-230E	4/13/2022	A221519	PACE	NR
GW - Compliance	MW43-WD	4/26/2022	280-161502-1	EUROFINS	NR
GW - Compliance	MW43-WD	4/26/2022	A221715	PACE	NR
GW - Compliance	MW54-WD	4/18/2022	280-161157-1	EUROFINS	X
GW - Compliance	MW54-WD	4/18/2022	A221601	PACE	X
GW - Compliance	MW60-WD	4/26/2022	280-161502-1	EUROFINS	NR
GW - Compliance	MW60-WD	4/26/2022	A221715	PACE	NR
GW - Compliance/Effectiveness	MW62-WDR	4/19/2022	280-161197-1	EUROFINS	NR
GW - Compliance/Effectiveness	MW62-WDR	4/19/2022	A221603	PACE	NR
GW - VES ^{f/} Performance		t			
GW - VES Performance GW - Compliance	MW70-WD	5/3/2022	280-161804-1	EUROFINS	NR
	MW71-WD	4/19/2022	280-161197-1	EUROFINS	NR
GW - Compliance GW - Compliance	MW71-WD MW74-WD	4/19/2022	A221603	PACE	NR
	·	4/13/2022	280-160946-1	EUROFINS	NR
GW - Compliance	MW74-WD	4/13/2022	A221519	PACE	NR
GW - North End Monitoring	MW77-EW-1	1/24/2022	A220403	PACE	NR
GW - North End Monitoring	MW77-EW-1	4/28/2022	A221718	PACE	NR
GW - North End Monitoring	MW77-EW-2	1/24/2022	A220403	PACE	NR
GW - North End Monitoring	MW77-EW-2	4/28/2022	A221718	PACE	NR
GW - Compliance GW - Compliance	MW77-WD	4/18/2022	280-161157-1	EUROFINS	X
•	MW77-WD	4/18/2022	A221601	PACE	X
GW - Compliance	MW78-WD	4/18/2022	280-161157-1	EUROFINS	X
GW - Compliance	MW78-WD	4/18/2022	A221601	PACE	X
GW - Compliance	MW90-WD	5/17/2022	280-162434-1	EUROFINS	NR
GW - Compliance	MW90-WD	5/17/2022	A222004	PACE	NR
GW - Compliance	MW91-WD	5/3/2022	280-161786-1	EUROFINS	NR
GW - Compliance	MW91-WD	5/3/2022	A221815	PACE	NR
GW - North End Monitoring	MW98-WD	1/24/2022	A220403	PACE	NR
GW - North End Monitoring GW - Effectiveness	MW98-WD	4/28/2022	A221718	PACE	NR
GW - Effectiveness	PM-13X	5/5/2022	280-161958-1	EUROFINS	NR
	PM-13X	5/5/2022	A221819	PACE	NR
GW - Compliance/Effectiveness	PM-14X	4/21/2022	280-161328-1	EUROFINS	NR
GW Effectiveness	PM-14X	4/21/2022	A221612	PACE	NR NR
GW - Effectiveness	PM-3X	5/5/2022	280-161958-1	EUROFINS	NR NR
GW - Effectiveness	PM-3X	5/5/2022	A221819	PACE	NR
GW - Effectiveness	PM-6X	5/5/2022	280-161958-1	EUROFINS	NR
GW - Effectiveness	PM-6X	5/5/2022	A221819	PACE	NR
Homeowner Well	Private Well 1	6/7/2022	A222333	PACE	NR NR
Homeowner Well	Private Well 2	6/7/2022	A222333	PACE	NR
GW - Molyhdenum Investigation	PTP-11	2/7/2022	280-158481-1	EUROFINS	NR
GW - Molybdenum Investigation	PTP-11	5/11/2022	280-162308-1	EUROFINS	NR
GW - Molybdenum Investigation	PTP-12	2/7/2022	280-158481-1	EUROFINS	NR
GW - North End Monitoring	PTP-12	2/14/2022	A220705	PACE	NR
GW - Molybdenum Investigation	PTP-12	5/11/2022	280-162308-1	EUROFINS	NR
GW - North End Monitoring	PTP-12	5/11/2022	A221907	PACE	NR
GW - Molybdenum Investigation	PTP-13	3/1/2022	280-159260-1	EUROFINS	NR
GW - North End Monitoring	PTP-13	3/1/2022	A220918	PACE	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
GW - Molybdenum Investigation	PTP-13	5/12/2022	280-162308-1	EUROFINS	NR
GW - North End Monitoring	PTP-13	5/12/2022	A221911	PACE	NR
WTP - Early Warning	TP-110	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Early Warning	TP-110	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Early Warning	TP-110	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Early Warning	TP-110	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-110	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Early Warning	TP-110	5/2/2022	280-161801-1	EUROFINS	NR NR
WTP - Early Warning	TP-110	6/6/2022	280-163137-1	EUROFINS	
WTP - Early Warning	TP-110	1/3/2022	280-157422-1	EUROFINS	NR
					NR
WTP - Early Warning	TP-120	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Early Warning	TP-120	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Early Warning	TP-120	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-120	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Early Warning	TP-120	5/2/2022	280-161801-1	EUROFINS	NR
WTP - Early Warning	TP-120	6/6/2022	280-163137-1	EUROFINS	NR
WTP - Early Warning	TP-140	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Early Warning	TP-140	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Early Warning	TP-140	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Early Warning	TP-140	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-140	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Early Warning	TP-140	5/2/2022	280-161801-1	EUROFINS	NR
WTP - Early Warning	TP-140	6/6/2022	280-163137-1	EUROFINS	NR
WTP - Early Warning	TP-150	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Early Warning	TP-150	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Early Warning	TP-150	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Early Warning	TP-150	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-150	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Early Warning	TP-150	5/2/2022	280-161801-1	EUROFINS	NR
WTP - Early Warning	TP-150	6/6/2022	280-163137-1	EUROFINS	NR
WTP - Early Warning	TP-160	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Early Warning	TP-160	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Early Warning	TP-160	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Early Warning	TP-160	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-160	4/4/2022	280-160525-1	EUROFINS	
WTP - Early Warning	TP-160	5/2/2022	280-161801-1	EUROFINS	NR
WTP - Early Warning	TP-160	6/6/2022	280-163137-1	EUROFINS	NR
WTP - Early warning WTP - Molybdenum Performance					NR
	TP-170	1/3/2022	280-157421-1	EUROFINS	NR
WTP - Early Warning	TP-170	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	1/11/2022	280-157595-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	1/18/2022	280-157832-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	1/25/2022	280-158099-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Early Warning	TP-170	2/1/2022	280-158293-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	2/1/2022	280-158296-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	2/8/2022	280-158485-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	2/15/2022	280-158767-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	2/22/2022	280-158975-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Early Warning	TP-170	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	3/1/2022	280-159201-1	EUROFINS	NR
	TP-170	3/8/2022	280-159507-1	EUROFINS	NR
W I P - Molyhdeniim Performance 1	11 1/0	31012022	200 137307-1	LOROI IIAD	1 11/
WTP - Molybdenum Performance WTP - Riotreatment System	TP-170	3/8/2022	280-150508-1	FURUEING	MD
WTP - Molybdenum Performance WTP - Biotreatment System WTP - Molybdenum Performance	TP-170 TP-170	3/8/2022 3/15/2022	280-159508-1 280-159745-1	EUROFINS EUROFINS	NR NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated?
WTP - Molybdenum Performance	TP-170	3/22/2022	280-160001-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	3/22/2022	280-160006-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	3/29/2022	280-160307-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Early Warning	TP-170	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-170	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	4/5/2022	280-160531-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-170	4/12/2022	280-160910-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-170	4/12/2022	280-160911-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-170	4/12/2022	280-161212-1	EUROFINS	
WTP - Biotreatment System	TP-170	4/19/2022	280-161212-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	4/19/2022	280-161516-1	EUROFINS	NR
					NR
WTP - Biotreatment System	TP-170	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Early Warning	TP-170	5/2/2022	280-161801-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	5/2/2022	280-161810-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	5/10/2022	280-162134-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	5/10/2022	280-162133-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	5/17/2022	280-162439-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	5/17/2022	280-162438-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	5/24/2022	280-162709-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	5/31/2022	280-162925-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	6/6/2022	280-163134-1	EUROFINS	NR
WTP - Early Warning	TP-170	6/6/2022	280-163137-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	6/14/2022	280-163423-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	6/21/2022	280-163655-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-170	6/28/2022	280-163849-1	EUROFINS	NR
WTP - Biotreatment System	TP-170	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-173A	1/3/2022	280-157421-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-173A	1/11/2022	280-157595-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-173A	6/21/2022	280-163655-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	1/3/2022	280-157421-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	1/11/2022	280-157595-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	1/18/2022	280-157832-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	1/25/2022	280-158099-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	2/1/2022	280-158296-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	2/8/2022	280-158485-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-174A	2/15/2022	280-158767-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-174A	2/22/2022	280-158975-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-174A	3/1/2022	280-159201-1	EUROFINS	
					NR
WTP - Molybdenum Performance	TP-174A	3/8/2022	280-159507-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	3/15/2022	280-159745-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	3/22/2022	280-160001-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	3/29/2022	280-160307-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	4/5/2022	280-160531-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	4/12/2022	280-160910-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	4/19/2022	280-161212-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	4/26/2022	280-161516-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	5/2/2022	280-161810-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	5/10/2022	280-162134-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	5/17/2022	280-162439-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	5/24/2022	280-162709-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	5/31/2022	280-162925-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	6/6/2022	280-163134-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	6/14/2022	280-163423-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-174A	6/21/2022	280-163655-1	EUROFINS	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Molybdenum Performance	TP-174A	6/28/2022	280-163849-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	1/18/2022	280-157832-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	1/25/2022	280-158099-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	2/1/2022	280-158296-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	2/8/2022	280-158485-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	2/15/2022	280-158767-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	2/22/2022	280-158975-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	3/1/2022	280-159201-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	3/8/2022	280-159507-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	3/15/2022	280-159745-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	3/22/2022	280-160001-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	3/29/2022	280-160307-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	4/5/2022	280-160531-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	4/12/2022	280-160910-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	4/19/2022	280-161212-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-175A	4/26/2022	280-161516-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A	5/2/2022	280-161810-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A	5/10/2022	280-162134-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A TP-175A	5/17/2022	280-162439-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A	5/24/2022	280-162709-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A TP-175A	5/31/2022	280-162925-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A	6/6/2022	280-163134-1	EUROFINS	
WTP - Molybdenum Performance	TP-175A TP-175A	6/14/2022	280-163423-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-175A TP-175A	6/28/2022	280-163849-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-1/3A TP-183	1/3/2022	280-157421-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	1/11/2022	280-157595-1	EUROFINS	NR NR
WTP - Molybdenum Performance	TP-183		280-157832-1		
WTP - Molybdenum Performance	TP-183	1/18/2022 1/25/2022	280-158099-1	EUROFINS EUROFINS	NR
WTP - Molybdenum Performance	TP-183	2/1/2022	280-158296-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	2/8/2022	280-158485-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	2/15/2022	280-158767-1	EUROFINS	NR
					NR
WTP - Molybdenum Performance WTP - Molybdenum Performance	TP-183 TP-183	2/22/2022 3/1/2022	280-158975-1 280-159201-1	EUROFINS EUROFINS	NR
	TP-183				NR
WTP - Molybdenum Performance		3/8/2022	280-159507-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	3/15/2022	280-159745-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	3/22/2022	280-160001-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	3/29/2022	280-160307-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	4/5/2022	280-160531-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	4/12/2022	280-160910-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	4/19/2022	280-161212-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	4/26/2022	280-161516-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	5/2/2022	280-161810-1	EUROFINS	NR
WTP - Molyhdenum Performance	TP-183	5/10/2022	280-162134-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	5/17/2022	280-162439-1	EUROFINS	NR
WTP - Molyhdenum Performance	TP-183	5/24/2022	280-162709-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	5/31/2022	280-162925-1	EUROFINS	NR
WTP - Molyhdenum Performance	TP-183	6/6/2022	280-163134-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	6/14/2022	280-163423-1	EUROFINS	NR
WTP - Molyhdenum Performance	TP-183	6/21/2022	280-163655-1	EUROFINS	NR
WTP - Molybdenum Performance	TP-183	6/28/2022	280-163849-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	1/25/2022	280-158100-1	EUROFINS	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-3300	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/1/2022	280-158297-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/8/2022	280-158482-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/8/2022	280-159485-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/8/2022	280-159508-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/15/2022	280-159727-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/15/2022	280-159744-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/22/2022	280-160004-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	3/22/2022	280-160004-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3300	3/22/2022	280-160298-1	EUROFINS	
WTP - Biotreatment System	TP-3300	3/29/2022	280-160298-1	EUROFINS	NR NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3300 TP-3300	4/5/2022	280-160306-1	EUROFINS	
WTP - Biotreatment System			280-160524-1		NR
	TP-3300	4/5/2022		EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/12/2022	280-160893-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/12/2022	280-160911-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/19/2022	280-161195-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/19/2022	280-161210-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/26/2022	280-161504-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/3/2022	280-161789-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/10/2022	280-162133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/17/2022	280-162438-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/24/2022	280-162705-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/31/2022	280-162922-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/7/2022	280-163133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/7/2022	280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3300	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Early Warning	TP-3310	1/3/2022	280-157422-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	2/1/2022	280-158289-1	EUROFINS	NR
		2/1/2022	280-158293-1	EUROFINS	NR
	1 12-3310				1 117
WTP - Early Warning	TP-3310 TP-3310				NIB
	TP-3310 TP-3310 TP-3310	2/1/2022 2/1/2022 2/8/2022	280-158297-1 280-158482-1	EUROFINS EUROFINS	NR NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-3310	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Early Warning	TP-3310	3/1/2022	280-159199-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/8/2022	280-159485-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/8/2022	280-159508-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/15/2022	280-159727-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/15/2022	280-159744-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/22/2022	280-160004-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/22/2022	280-160006-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/29/2022	280-160298-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Early Warning	TP-3310	4/4/2022	280-160525-1	EUROFINS	NR
WTP - Early Warning	TP-3310	4/4/2022	280-160534-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	4/5/2022	280-160526-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	4/12/2022	280-160893-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	4/12/2022	280-160911-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	4/12/2022	280-161195-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	4/19/2022	280-161210-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	4/26/2022	280-161504-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	4/26/2022	280-161518-1	EUROFINS	
WTP - Early Warning	TP-3310	5/2/2022	280-161801-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3310	5/3/2022	280-161789-1	EUROFINS	
WTP - Biotreatment System	TP-3310	5/3/2022	280-161806-1	EUROFINS	NR NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3310	5/10/2022	280-162132-1	EUROFINS	
WTP - Biotreatment System WTP - Biotreatment System	TP-3310	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3310	5/17/2022	280-162430-1	EUROFINS	NR
•	TP-3310		280-162438-1		NR
WTP - Biotreatment System	TP-3310	5/17/2022	280-162705-1	EUROFINS	NR
WTP - Biotreatment System		5/24/2022		EUROFINS	NR
WTP - Biotreatment System	TP-3310 TP-3310	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System		5/31/2022	280-162922-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310 TP-3310	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Early Warning		6/6/2022	280-163137-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/7/2022 6/7/2022	280-163133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310		280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3310	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/1/2022	280-158297-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/8/2022	280-158482-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/15/2022	280-158765-1	EUROFINS	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-3320	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/8/2022	280-159485-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/8/2022	280-159508-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/15/2022	280-159727-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/15/2022	280-159744-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/22/2022	280-160004-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/22/2022	280-160006-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/29/2022	280-160298-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	4/5/2022	280-160524-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3320	4/5/2022	280-160526-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	4/12/2022	280-160893-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3320	4/12/2022	280-160911-1	EUROFINS	NR NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3320	4/19/2022 4/19/2022	280-161195-1 280-161210-1	EUROFINS	NR
	TP-3320			EUROFINS	NR
WTP - Biotreatment System	TP-3320	4/26/2022	280-161504-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/3/2022	280-161789-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/10/2022	280-162133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/17/2022	280-162438-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/24/2022	280-162705-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/31/2022	280-162922-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/7/2022	280-163133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/7/2022	280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3320	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	2/8/2022	280-158482-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	3/8/2022	280-159485-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	3/15/2022	280-159727-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	3/22/2022	280-160004-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	3/29/2022	280-160298-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	4/12/2022	280-160893-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	4/19/2022	280-161195-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	4/26/2022	280-161504-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	5/3/2022	280-161789-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3331	5/10/2022	280-162132-1	EUROFINS	NR NR
WII - DIOIICAUIICIII SYSTEIII	11-3331	5/10/2022	200-102132-1	POYOURS	INIX

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-3331	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	5/24/2022	280-162705-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	5/31/2022	280-162922-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	6/7/2022	280-163133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-3331	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	2/8/2022	280-158482-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	3/8/2022	280-159485-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	3/15/2022	280-159727-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	3/13/2022	280-160004-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	3/29/2022	280-160298-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	4/12/2022	280-160893-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	4/12/2022	280-161195-1	EUROFINS	
WTP - Biotreatment System	TP-3332	4/26/2022	280-161504-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	5/3/2022	280-161789-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	5/10/2022	280-162132-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System	TP-3332	5/24/2022	280-162705-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	5/31/2022	280-162922-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	6/7/2022	280-163133-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	6/14/2022	280-163420-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3332	6/21/2022	280-163644-1	EUROFINS	
WTP - Biotreatment System	TP-3332	6/28/2022	280-163846-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	1/4/2022	280-157412-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	1/11/2022	280-157592-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	1/11/2022	280-157834-1	EUROFINS	
WTP - Biotreatment System	TP-3333	1/25/2022	280-158093-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	2/1/2022	280-158289-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	2/8/2022	280-158482-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3333	2/22/2022	280-158977-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	3/1/2022	280-159200-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	3/8/2022	280-159485-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	3/15/2022	280-159727-1		
WTP - Biotreatment System	TP-3333	3/13/2022	280-160004-1	EUROFINS EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	3/22/2022	280-160298-1	EUROFINS	
WTP - Biotreatment System	TP-3333	4/5/2022	280-160524-1	EUROFINS	NR ND
WTP - Biotreatment System	TP-3333	4/3/2022	280-160893-1	EUROFINS	NR
WTP - Biotreatment System	TP-3333	4/12/2022	280-161195-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	4/19/2022	280-161504-1	EUROFINS	
WTP - Biotreatment System	TP-3333	5/3/2022	280-161789-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	5/10/2022	280-162132-1	EUROFINS	
WTP - Biotreatment System	TP-3333	5/17/2022	280-162132-1	EUROFINS	NR ND
WTP - Biotreatment System	TP-3333	5/24/2022	280-162705-1	EUROFINS	NR ND
WTP - Biotreatment System	TP-3333		280-162703-1		NR ND
· ·	TP-3333	5/31/2022		EUROFINS	NR NB
WTP - Biotreatment System		6/7/2022	280-163133-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3333	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3333	6/21/2022	280-163644-1	EUROFINS	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-3333	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/1/2022	280-158297-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/8/2022	280-158482-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	3/8/2022	280-159485-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	3/8/2022	280-159508-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	3/15/2022	280-159727-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	3/15/2022	280-159744-1	EUROFINS	
WTP - Biotreatment System	TP-3340	3/13/2022	280-160004-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	3/22/2022	280-160004-1	EUROFINS	
WTP - Biotreatment System	TP-3340	3/29/2022	280-160298-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	3/29/2022	280-160306-1	EUROFINS	
WTP - Biotreatment System	TP-3340	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3340	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	4/12/2022	280-160893-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-3340	4/12/2022	280-160911-1	EUROFINS	
•	TP-3340				NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3340	4/19/2022 4/19/2022	280-161195-1 280-161210-1	EUROFINS EUROFINS	NR
•	TP-3340		280-161504-1		NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3340	4/26/2022 4/26/2022	280-161518-1	EUROFINS EUROFINS	NR
WTP - Biotreatment System	TP-3340	5/3/2022	280-161789-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3340	5/17/2022	280-162430-1	EUROFINS	NR NR
WTP - Biotreatment System WTP - Biotreatment System	TP-3340	5/24/2022	280-162438-1	EUROFINS	
•					NR NB
WTP - Biotreatment System	TP-3340	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340 TP-3340	5/31/2022	280-162922-1	EUROFINS EUROFINS	NR ND
WTP - Biotreatment System WTP - Biotreatment System		5/31/2022	280-162934-1		NR
'n	TP-3340	6/7/2022	280-163133-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/7/2022	280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-3340	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	2/1/2022	280-158297-1	EUROFINS	NR

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-710	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	3/8/2022	280-159508-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	3/15/2022	280-159744-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	3/22/2022	280-160006-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	4/5/2022	280-160526-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	4/12/2022	280-160911-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	4/19/2022	280-161210-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-710	5/10/2022	280-162133-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-710	5/17/2022	280-162438-1	EUROFINS	
WTP - Biotreatment System	TP-710	5/24/2022	280-162707-1	EUROFINS	NR NR
WTP - Biotreatment System	TP-710	5/31/2022	280-162934-1	EUROFINS	
<u> </u>	TP-710 TP-710				NR NR
WTP - Biotreatment System WTP - Biotreatment System	TP-/10 TP-710	6/7/2022	280-163174-1 280-163422-1	EUROFINS	NR NR
<u> </u>	TP-710 TP-710	6/14/2022 6/21/2022		EUROFINS EUROFINS	NR NR
WTP - Biotreatment System	TP-710 TP-710		280-163653-1		NR
WTP - Biotreatment System		6/28/2022	280-163850-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/4/2022	280-157412-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/11/2022	280-157592-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/18/2022	280-157834-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/25/2022	280-158093-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/1/2022	280-158289-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/1/2022	280-158297-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/15/2022	280-158765-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/22/2022	280-158977-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	3/1/2022	280-159200-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	3/29/2022	280-160298-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/5/2022	280-160524-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/5/2022	280-160526-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/12/2022	280-160893-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/12/2022	280-160911-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/19/2022	280-161195-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/19/2022	280-161210-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/26/2022	280-161504-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/3/2022	280-161789-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/10/2022	280-162132-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/10/2022	280-162133-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/17/2022	280-162430-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/17/2022	280-162438-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/24/2022	280-162705-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/31/2022	280-162922-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/7/2022	280-163133-1	EUROFINS	NR
II Dionoument System	11 /30	0.112022	200 103133-1	201011110	INIX

Data Type	Sample Location	Sample Date	Project Number	LAB	Validated? ^{a/}
WTP - Biotreatment System	TP-730	6/7/2022	280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/14/2022	280-163420-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/21/2022	280-163644-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/28/2022	280-163846-1	EUROFINS	NR
WTP - Biotreatment System	TP-730	6/28/2022	280-163850-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	1/4/2022	280-157415-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	1/11/2022	280-157593-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	1/18/2022	280-157833-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	1/25/2022	280-158100-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	2/1/2022	280-158297-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	2/8/2022	280-158483-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	2/15/2022	280-158768-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	2/22/2022	280-158979-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	3/1/2022	280-159203-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	3/8/2022	280-159508-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	3/15/2022	280-159744-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	3/22/2022	280-160006-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	3/29/2022	280-160306-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	4/5/2022	280-160526-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	4/12/2022	280-160911-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	4/19/2022	280-161210-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	4/26/2022	280-161518-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	5/3/2022	280-161806-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	5/10/2022	280-162133-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	5/17/2022	280-162438-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	5/24/2022	280-162707-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	5/31/2022	280-162934-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	6/7/2022	280-163174-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	6/14/2022	280-163422-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	6/21/2022	280-163653-1	EUROFINS	NR
WTP - Biotreatment System	TP-740	6/28/2022	280-163850-1	EUROFINS	NR
GW - Compliance	U-518R-WD	4/21/2022	280-161328-1	EUROFINS	NR
GW - Compliance	U-518R-WD	4/21/2022	A221612	PACE	NR
WTP - Sludge Analysis	WTP SLUDGE	3/14/2022	22-03072	EBS	NR
WTP - Sludge Analysis	WTP SLUDGE	3/14/2022	280-159746-1	EUROFINS	NR
WTP - Sludge Analysis (TENORM ^{g/})	WTP SLUDGE-1	3/14/2022	22-03071	EBS	NR
WTP - Sludge Analysis (TENORM)	WTP SLUDGE-2	3/14/2022	22-03071	EBS	NR
WTP - Sludge Analysis (TENORM)	WTP SLUDGE-3	3/14/2022	22-03071	EBS	NR

a/ Validated:

X = Level III validation

NR = Not required

b/ GW = groundwater

c/ WTP = Water Treatment Plant

d/ EBS - Eberline Services

e/ RAWP = Response Action Work Plan

f/ VES = Vapor Extraction System

g/ TENORM = Technologically Enhanced Naturally Occurring Radioactive Material

APPENDIX F-2 ANALYTICAL DATA PACKAGES AND DATA VALIDATION REPORTS

See folder APPENDIX F-2

APPENDIX F-3 DATA QUALITY ASSESSMENT

APPENDIX F-3

DATA QUALITY ASSESSMENT

JANUARY THROUGH JUNE 2022 OPERATIONS AND MAINTENANCE STATUS REPORT LOWRY LANDFILL SUPERFUND SITE

Based on the project or task requirements, a data evaluation process was performed on project analytical data. The data evaluation process provides an evaluation of the data quality in relation to specific project data quality criteria and with reference to the sampling and analysis requirements of the Quality Assurance Project Plan (QAPP).

The overall quality assurance objective for all measurement data is to maximize the probability that the data generated are of documented quality and are defensible for the intended data uses. To meet these objectives, data shall be: (1) representative of actual site physical and chemical conditions; (2) comparable to previous and subsequent data and other studies; (3) complete to the extent that necessary conclusions may be reached; and (4) of known quantitative statistical significance in terms of precision and accuracy, at levels appropriate for each stated data use for the project.

The data review process is performed in two phases. The initial phase, data verification, involves inspecting the laboratory data deliverables to determine if project requirements were met. The second phase, data validation, includes a review of data to assess data usability and application of data qualifiers to the analytical results based on adherence to method protocols and laboratory-specific quality assurance/quality control (QA/QC) limits.

F-3.1 DATA VERIFICATION

Data verification is the process of evaluating the completeness, correctness, and conformance/compliance of a specific data set against the method, procedural, or contractual requirements. Data verification is the review of sample data deliverables for completeness and compliance with project requirements. A checklist was completed for each data package to ensure that all documentation was provided. If deficiencies were revealed, resubmissions of the missing or incorrect data were requested and the data deliverable was updated. In addition, transcription checks of 100% of the compliance, effectiveness, vertical migration, Response Action, and North End groundwater results, Water Treatment Plant (WTP) Early Warning, molybdenum testing, and WTP effluent (MP-001) samples were performed to ensure the data reported in the database and the hardcopy data packages were the same. The following problems were noted during sample verification:

The following problems were identified:

280-161009 was missing the inorganic (general chemistry) raw sample data - the data package was resubmitted.

280-162131 was missing total and dissolved molybdenum in the EDD and the data package for MW170-EW-1. The analysis had been performed but not reported. The data package and EDD were resubmitted.

No other problems were encountered from data verification of the analytical data.

F-3.2 DATA VALIDATION

Data validation was performed on the following selected locations during the reporting period.

- 10% of the 30 compliance and effectiveness groundwater (GW) wells. Samples for validation were chosen at random:
- A representative set of the investigation wells (Molybdenum testing and North End Monitoring) were also validated.
- All MP-001 (WTP effluent) samples.

A Level III validation (summary quality control review) was performed consisting of manually examining data deliverables to determine data quality. Data validation included application of data qualifiers to the analytical results based on adherence to method protocols and project-specific QA/QC limits. Method protocols reviewed included:

- Analytical holding times,
- Method blanks (MB),
- Trip blanks (TB),
- Equipment blanks (EBs),
- Ambient blanks (AB),
- Matrix spikes/matrix spike duplicates (MS/MSDs),
- Laboratory control samples (LCSs),
- Shipping cooler temperatures,
- Laboratory duplicates,
- Internal Standards (ISs),
- Surrogates,
- Chemical recovery (radionuclides), or
- An out-of-control QC parameter that is mentioned in the case narrative.

Data qualifiers were applied to analytical results during the data validation process. All data were validated using method applicable guidelines and in accordance with the requirements of the National Functional Guidelines for Organic and Inorganic Data Review (EPA, 1994a & b, as amended) and by SW-846 guidelines specific to the method or as directed by EPA. All radionuclide results that were less than the critical value (Lc) were qualified as not detected (U).

Radionuc1ides were validated according to the guidelines and criteria specified in the Multi-Agency Radiological Laboratory Analytical Protocols (MARLAP) Manual (EPA, 2004, as amended).

The following definitions provide explanations of the USEPA qualifiers that may be assigned to analytical results during data validation.

- U = The analyte was analyzed for and is not present above the level of the associated value. The associated numerical value indicates the approximate concentration necessary to detect the analyte in the sample.
- UJ = The analyte analyzed for was not present above the level of the associated value. The associated numerical value may not accurately represent the concentration necessary to detect the analyte in the sample.
- UJ-= Same as UJ qualification but with an indication of negative bias in the associated numerical value.
- UJ+= Same as UJ qualification but with an indication of positive bias in the associated numerical value.
- NJ = The analysis indicates that the analyte is "tentatively identified" and the associated numerical value may not be consistent with the amount actually present in the sample.
- J = The analyte was analyzed for, and was positively identified, but the associated numerical value may not be consistent with the amount actually present in the environmental sample.
- J-= Same as J qualification but with an indication of negative bias in the sample concentration.
- J+= Same as J qualification but with an indication of positive bias in the sample concentration.

Data quality is summarized below only where problems were noted during the validation. Frequency requirements for field sample collection of QC samples (MS/MSDs, field duplicates, and blanks) were reviewed and meet project requirements. The frequency requirements for laboratory specific method QC were met overall.

F-3.2.1 Groundwater

Six samples associated with the 30 compliance and effectiveness wells plus 5 samples associated with investigation and North End groundwater monitoring were validated. Locations of wells sampled during the reporting period are shown on Figures 4.9 and 4.10. Data validation reports (DVRs), included in Appendix F-2, are cross-referenced by location and SDG number in Table F-1. Raw data packages and DVRs are presented in Appendix F-2.

The following methods were validated as required:

- SW8260B (VOCs),
- SW8260 SIM (low-level 1,4-Dioxane),
- SW6010B (Metals),
- E300.0A (Nitrate and Nitrite).

The following groundwater samples were validated as indicated for each method:

MASTER LOC	Sample Date	300_0A	6010B	8260_SIM	8260B
B-326-UD	4/14/2022		X		
GW-106	4/18/2022	X	X	X	X
MW105-WD	4/20/2022	X	X	X	X
MW113-UD	4/5/2022		X		
MW113-WD	4/5/2022		X		
MW135-WD	2/23/2022			X	
MW179-UDEN	3/1/2022		X		
MW23-UPPER-C	4/20/2022			X	
MW54-WD	4/18/2022	X	X	X	X
MW77-WD	4/18/2022	X	X	X	X
MW78-WD	4/18/2022	X	X	X	X

The results listed in the table below were qualified for exceeding the linear range (LR) of the calibration curve or for contaminated calibration blanks (CCBs). No other qualifiers were necessary for groundwater samples after validation.

Data Qualifications – Groundwater

MASTER LOC	Parameter Name	Sample Date	Result	Units	Final Q	LR	ССВ
MW105-WD	Cadmium	4/20/2022	0.53	ug/L	U		U
MW23-UPPER-C	Cadmium	4/20/2022	0.36	ug/L	U		U
MW62-WDR	Cadmium	4/19/2022	0.56	ug/L	U		U
MW71-WD	Cadmium	4/19/2022	0.38	ug/L	U		U
MW77-WD	Nitrogen, Nitrate	4/18/2022	13000	ug/L	J	J	

Continuing Calibration Blanks

The continuing calibration blank (CCB) is an aliquot that consists of the same matrix as that used for the calibration standards, but without the analytes, analyzed during an analysis sequence to verify the continued absence of instrumental interferences. Four cadmium samples were qualified for CCB contamination (U). Each qualified sample was from the same analytical run. This indicates contamination originating from lab processes.

Linear Range

One nitrate concentration exceeded the linear range of the calibration curve. The dilution reanalysis was performed after the holding time expired so could not be used. The results exceeding the linear range were reported and qualified as J, estimated.

F-3.2.2 WTP Effluent (MP-001)

The WTP effluent samples (MP-001) were validated for the following methods, if applicable:

- E200.8 and E200.7 Metals,
- E624 VOCs,
- E625 –SVOCs,
- SW8260SIM 1,4-Dioxane,
- E900.0 Gross alpha/beta,
- EPA 60017-79-08 Plutonium-238, -239, -240,
- ER110 LANL Americium-241,
- SM 7500-RA-B Radium-226 and Total Radium, and
- EPA-RA-05 Radium-228.

Data validation reports included in Appendix F are cross-referenced by location and SDG number in Appendix F-l. DVRs and raw data packages are presented in Appendix F-2.

The results listed in the table below were qualified because out-of-control chemical recovery, uncertainty, LCS recovery, MS recovery, trip blanks, continuing calibration verifications (CCVs), surrogates, and method blanks.

Data Qualifications – WTP Effluent

Sample ID	Sample Date	Parameter Name	Result	CE	Units	Final Q	Unc	MS Rec	Chem Rec	MB	LCS Rec	CCV %D	SUR
MP-001_010322_2000	1/3/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001_010322_1600	1/3/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001_010322_1200	1/3/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001_010322_1200	1/3/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001_010322_1600	1/3/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001_010322_2000	1/3/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001_010322_1200	1/3/22	o-Xylene	1		ug/L	R		R					
MP-001_010322_2000	1/3/22	o-Xylene	1		ug/L	R		R					
MP-001_010322_1600	1/3/22	o-Xylene	1		ug/L	R		R					
MP-001_010422_0400	1/4/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001_010422_0800	1/4/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001_010422_0000	1/4/22	1,2,3-Trichloropropane	3		ug/L	R		R					
MP-001	1/4/22	Alpha, Gross	15	5.9	pCi/l	UJ+		S+		B+	S+		
MP-001	1/4/22	Americium-241	0.013	0.029	pCi/l	J	Q						
MP-001	1/4/22	Benzidine	95		ug/L	R		R					
MP-001_010422_0000	1/4/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001_010422_0400	1/4/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001_010422_0800	1/4/22	Dichlorodifluoromethane	2		ug/L	R					R		
MP-001	1/4/22	Hexachlorocyclopentadiene	47		ug/L	R					R		
MP-001_010422_0800	1/4/22	o-Xylene	1		ug/L	R		R					
MP-001_010422_0400	1/4/22	o-Xylene	1		ug/L	R		R					
MP-001_010422_0000	1/4/22	o-Xylene	1		ug/L	R		R					
MP-001	1/4/22	Plutonium-238	0.083	0.072	pCi/l	UJ			J				
MP-001	1/4/22	Plutonium-239/240	0.049	0.059	pCi/l	J	Q		J				
MP-001	1/4/22	Radium-226	0.42	0.36	pCi/l	J	Q						

Sample ID	Sample Date	Parameter Name	Result	CE	Units	Final Q	Unc	MS Rec	Chem Rec	MB	LCS Rec	CCV %D	SUR
MP-001	1/4/22	Radium-228	1.2	0.71	pCi/l	J	Q						
MP-001	1/4/22	Total Radium	0.37	0.20	pCi/l	J	Q						
MP-001	1/4/22	Zinc	3.1		ug/L	U				U			
MP-001	2/2/22	Benzidine	93		ug/L	R		R					
MP-001	2/2/22	Hexachlorocyclopentadiene	47		ug/L	R		R			R		
MP-001	4/5/22	2-Chlorophenol	9.4		ug/L	UJ-							UJ-
MP-001	4/5/22	Acetophenone	9.4		ug/L	UJ-							UJ-
MP-001	4/5/22	Alpha, Gross	37.8	7.4	pCi/l	J+				B+			
MP-001	4/5/22	Americium-241	0.00011	0.051	pCi/l	UJ			J				
MP-001	4/5/22	Benzidine	94		ug/L	R		R					UJ-
MP-001	4/5/22	Hexachloroethane	9.4		ug/L	UJ-							UJ-
MP-001	4/5/22	N-Nitroso-Di-N- Propylamine	9.4		ug/L	UJ-							UJ-
MP-001_040422_1200	4/5/22	Nonylphenol	4.9		ug/L	R		R					
MP-001_040422_1600	4/5/22	Nonylphenol	4.9		ug/L	R		R					
MP-001_040422_2000	4/5/22	Nonylphenol	4.9		ug/L	R		R					
MP-001_040522_0000	4/5/22	Nonylphenol	4.9		ug/L	R		R					
MP-001_040522_0400	4/5/22	Nonylphenol	4.9		ug/L	R		R					
MP-001_040522_0800	4/5/22	Nonylphenol	4.9		ug/L	R		R					UJ-
MP-001	4/5/22	Plutonium-238	-0.019	0.033	pCi/l	UJ			J				
MP-001	4/5/22	Plutonium-239/240	0.0046	0.030	pCi/l	UJ			J				
MP-001	4/5/22	Radium-228	0.46	0.23	pCi/l	J	Q						
MP-001	4/5/22	Zinc	3.1		ug/L	UJ+						J+	

CE = Counting Error MB = Method Blank MS Rec = Matrix Spike Recovery SUR = Surrogate recovery Chem Rec = Chemical Recovery (RADs) Unc = Uncertainty CCV = Continuing Calibration Verification percent difference

LCS Rec = Laboratory Control Sample Recovery

Uncertainty

Samples for americium-241, plutonium-239/240 and radium-228 were qualified because of a high counting error in relation to the sample result (uncertainty). This indicates that the uncertainty of a measured value is too large compared to the result value. This usually occurs when the result value is just above the critical value. The final result is qualified as estimated (J).

Matrix Spike Recovery

Benzidine in three samples was rejected due to low matrix spike recoveries. Benzidine was extracted and analyzed in duplicate for each sample collected because of this problem. Benzidine experiences oxidative losses during extraction inhibiting recovery of matrix spikes. Because benzidine has never been detected at Lowry, Metro has allowed a variance for the method. The lab must analyze it twice and if the spikes fail twice, we do not have to resample. LCS recoveries will still need to be in control plus all other QC.

Gross alpha in one sample was out of control for matrix spike recoveries. Gross alpha may be biased high in the associated samples as indicated by matrix spike recoveries that were above the upper control limits.

1,2,3-Trichloropropane, nonylphenol, and o-xylene in one set of MP-001 samples were rejected due to low matrix recoveries. Hexachlorobutadiene was rejected in one MP-001 sample. The samples were recollected and reanalyzed with passing QC.

Qualifications resulting from matrix spike recoveries are most likely matrix-related because the associated LCSs were in control.

Chemical Recovery

Americium-241, plutonium-238 and plutonium-239/240 in one sample were qualified as estimated for chemical recovery. Chemical recovery measures the yield of a radioactive isotope of the analyte added to the sample to measure any losses of the analyte during the chemical separations or other processes employed in the analysis. Sample concentrations are corrected for chemical recovery but the lower the yield the greater the variance in the result. Therefore, the sample results were qualified as estimated (J).

Method Blanks

The method blank measures possible contamination by the laboratory. One zinc sample was qualified for method blank contamination (U). Two gross alpha samples were qualified as B+ (estimated with a high bias, final Q=J+). This indicates contamination originating from lab processes.

Laboratory Control Samples

LCSs are designed to check the accuracy of the analytical procedure by measuring a known concentration of an analyte of interest. One set of six samples for dichlorodifluoromethane and two samples for hexachlorocyclopentadiene were rejected for low LCS recoveries. The samples

were recollected and reanalyzed with passing QC. One gross alpha sample was qualified S+ for high bias.

Continuing Calibration Verification

Initial calibration curves must be verified daily prior to sample analysis using a CCV to monitor the accuracy of the analysis and every 10 samples for metals analysis. One sample for zinc was qualified as biased high for a failing CCV.

Surrogates

Surrogate spike analyses are used to determine the efficiency of target analyte recovery during sample preparation and analysis. One sample for nonylphenol, 2-chlorophenol, acetophenone, hexachloroethane, N-nitroso-di-N-propylamine and benzidine were out of control with a low bias. Qualifications resulting from surrogate recoveries are most likely matrix-related.

F-3.3 DATA ASSESSMENT

Data quality assessment (DQA) criteria were used to evaluate the quality of the field sampling efforts, field screening results, and laboratory results for compliance with project data quality objectives (DQOs). The DQA criteria are expressed in terms of analytical precision, accuracy, representativeness, completeness, and comparability (PARCC). Procedures used to assess data accuracy and precision are in accordance with the respective analytical methods and QAPP requirements.

F-3.3.1 Precision

Precision is the measure of variability between individual sample measurements under prescribed conditions. The relative percent difference (RPD) for field duplicate, MS/MSD, and laboratory duplicate analyses demonstrates the precision of the analytical methods and, in the case of field duplicates, sampling methods. An RPD within the method-specific control limit indicates satisfactory precision in a measurement system. Methods (matrix specific) were considered out of control when greater than 50 percent of all precision data exceeded criteria. Out-of-control methods are evaluated for trends in bias. If a specific bias is evident, it is discussed below.

Precision results (i.e., MS/MSD, laboratory replicates, and field duplicates) for all methods and matrices were in control overall. The tables below present field duplicate precision for groundwater and WTP effluent where at least one of the duplicate results was detected. Field duplicates have an RPD control limit for sample concentrations exceeding the RL by 5 times of 35% and a range limit equal to the two times the RL is applied to sample values less than 5 times the RL. The field duplicate results were in control.

Field Duplicate Results

Sample ID	Analyte	Sample Date	RL	Sample Conc (ug/L)	Dupe Conc (ug/L)	Range	RPD
MW170-EW-1	1,1,1-Trichloroethane	1/25/2022	1	1.8	1.8	0	

Sample ID	Analyte	Sample Date	RL	Sample Conc (ug/L)	Dupe Conc (ug/L)	Range	RPD
MW170-EW-1	1,1-Dichloroethane	1/25/2022	1	3.7	3.8	0.1	
MW170-EW-1	1,1-Dichloroethene	1/25/2022	1	3	3	0	
MW170-EW-1	cis-1,2-Dichloroethene	1/25/2022	1	9	8.7		3%
MW170-EW-1	Tetrachloroethene	1/25/2022	1	1.2	1.1	0.1	
MW170-EW-1	Trichloroethene	1/25/2022	1	0.49	0.49	0	
MW170-EW-1	Nitrate as N	1/25/2022	2.5	11	11	0	
MW170-EW-1	Molybdenum, Total	1/25/2022	20	1.4	1	0.4	
MW170-EW-1	Molybdenum, Dissolved	1/25/2022	20	1.3	2	0.7	
MW105-WD	Cadmium	4/20/2022	5	0.53	1	0.47	
MW105-WD	Nitrate as N	4/20/2022	0.5	0.22	0.2	0.02	
MW113-WD	Molybdenum, Total	1/15/2022	200	32000	31000		3%
MW113-WD	Molybdenum, Dissolved	1/15/2022	200	31000	31000		0%
MP-001_010422_0800	1,1,1-Trichloroethane	1/4/2022	1	8.7	8.4		4%
MP-001 010422 0800	1,1-Dichloroethane	1/4/2022	1	22	21		5%
MP-001_040522-0800	1,1-Dichloroethane	4/5/2022	1	6.8	6.7		1%
MP-001_010422_0800	1,2-Dichloroethene, Total	1/4/2022	1	4.9	4.9	0	
MP-001 010422 0800	1,4-Dioxane	1/4/2022	1.4	14	13		7%
MP-001_040522-0800	1,4-Dioxane	4/5/2022	20	28	23	5	
MP-001_040522_0800	1,4-Dioxane	4/5/2022	1.4	12	11		9%
MP-001_010422_0800	cis-1,2-Dichloroethene	1/4/2022	1	4.9	4.9	0	
MP-001	Copper	4/5/2022	2.5	21	21		0%
MP-001	Diethyl phthalate	4/5/2022	3.8	0.42	0.63	0.21	
MP-001	Molybdenum	1/4/2022	5	13	13	0	
MP-001	Molybdenum	4/5/2022	5	14	14	0	
MP-001	Nickel	4/5/2022	2.5	3.5	3.1	0.4	
MP-001	Selenium	1/4/2022	2.5	19	18		5%
MP-001	Selenium	4/5/2022	2.5	17	17		0%
MP-001	Zinc	1/4/2022	10	3.1	3.3	0.2	
MP-001	Zinc	4/5/2022	10	3.1	3	0.1	

No qualifiers are applied based on field duplicate results unless resampling is indicated. Field duplicates are used as a measure of field sampling reproducibility and may be used to judge the representativeness of the samples collected.

F-3.3.2 Accuracy

F-3.3.2.1 Accuracy of Laboratory QC Samples

Accuracy is the degree of agreement of a measurement with an accepted reference or true value. The results of surrogate, MS/MSD, and LCS analyses, when expressed in terms of percent recovery, demonstrate the accuracy of the method. Surrogate and MS/MSD spike recoveries indicate accuracy relevant to a unique sample matrix. LCS spike recoveries indicate accuracy relevant to an analytical batch lot and are strictly a measure of laboratory analytical accuracy

conditions independent of samples and matrices. As with precision determinations, methods (matrix specific) were considered systematically out of control when greater than 50 percent of all accuracy data exceeded criteria. Out-of-control methods are evaluated for trends in bias. If a specific bias is evident, it is discussed below. If insufficient data are available (i.e., fewer than 20 occurrences) to represent a viable sample population, then statistical certainty in an out-of-control condition cannot be assumed. Control charts were developed to demonstrate if a change in the lab analysis process is occurring over time. The most current analyses were compared against the control limits and mean of the previous twenty analyses. By comparing current data to the control limits and mean of the previous set, you can determine whether the process variation is consistent (in control) or is unpredictable (out of control, affected by special causes of variation).

Control charts were developed for groundwater for the LCS/LCSD and MS/MSD spike recoveries for cadmium (representing SW6010B, Figures F-3.1, F-3.2, F-3.3, and F-3.4), trichloroethene (TCE) (representing SW8260B, Figures F-3.5, F-3.6, F-3.7, and F-3.8), and 1,4-dioxane by method SW8260 SIM (Figures F-3.9, F-3.10, and F-3.11). One LCS for cadmium was less than the lower control limit during the reporting period at 91% in a window of 93 to 107%. The accuracy of their LCSs over time has caused the control chart limits to be narrow. TCE exceeded the control limit for the LCS, MS and MSD in one analysis run indicating the laboratory analytical system was biased high. The associated sample (MW170-EW-1) had a trace detect of 0.49 J consistent with previous results.

Control charts or plots were developed for WTP effluent for the LCS/LCSD and MS/MSD spike recoveries for TCE (representing SW8260B, Figures F-3.12, F-3.13, F-3.14 and F-3.15), selenium (representing SW6010B, Figures, F-3.16, F-3.17, 3.18, and F-3.19), and pyridine by method SW8270 (Figures F-3.20, F-3.21, F-3.22 and F-3.23). LCS, LCSD, MS and MSD results were in control for the reporting period.

MP-001 was resampled for out-of-control matrix spike recoveries for benzidine, 1,2,3-trichloropropane, hexachlorocyclopentadiene, nonylphenol, and o-xylene. Benzidine experiences oxidative losses during the extraction inhibiting recovery of matrix spikes. A variance has been approved by Metro where the samples are extracted twice and analyzed twice for each sample. If the recoveries of the LCSs and MSs still do not pass, the results may be submitted to Metro. The other compounds were resampled with acceptable results.

LCSs associated with MP-001 were out of control for dichlorodifluoromethane and hexachlorocyclopentadiene. The associated samples were recollected and analyzed with acceptable results.

Surrogates were out of control with a low bias for nonylphenol, benzidine, hexachloroethane, N-nitroso-di-N-propylamine, acetophenone, and 2-chlorophenol in one sample.

Accuracy results (i.e., MS/MSD, LCS, surrogate spikes, and post digestion spikes) for all methods and matrices are predominantly in control except where noted. The accuracy results which were out-of-control are not significant for any one compound, method, or matrix (except benzidine) and do not represent a negative impact to data quality. Therefore, overall accuracy was acceptable.

F-3.4.3 Representativeness

Compliance sample data are believed to be representative of the site conditions prevailing at the time of sample collection because samples were properly collected, stored, and preserved. Although blank contamination did occur, sample data quality was not predominantly affected. Holding times were met for all compliance samples.

F-3.4.4 Comparability


All samples were reported in industry-standard units. Water reporting units were micrograms per liter (μ g/L) or picoCuries per liter (pCi/L). Landfill gas units were in ug/m³. Analytical protocols for the methods were adhered to and analytical results are considered comparable.


F-3.4.5 Completeness


Completeness is defined as the percentage of laboratory measurements judged to be valid on a method-by-method basis. Valid data are defined as all data and/or qualified data which meet the DQOs for this project. Data completeness is expressed as percent complete (PC), which is (1-(the number of rejected samples per compound ÷ total number of samples per compound) X 100. Completeness for the reporting period was 100%, understanding that all results qualified with U, UJ* or J* are usable to meet project objectives. Benzidine results were 0% complete but are not included in the calculation. The method required by the Metro permit is inadequate to analyze for this compound and does not provide a usable result. The goal for meeting analytical holding times was 100% and was met for all reported compliance samples. The rejected MP-001 samples that were rejected were replaced with resampled results.


F-3.4.6 Conclusion


The groundwater and WTP data for the reporting period are of acceptable quality and are considered usable to support project objectives. Samples are representative of the Site and comparable with previous and future investigations (when used in accordance with the validation qualifiers).



























































APPENDIX G

ELECTRONIC DATABASE

see the external database